LINE: Performance and Reliability Analysis Engine

User manual

Version: 2.0.0-BETA

Last revision: May 4, 2019

Contents

1	Intr	oductio	n	5
	1.1	What i	s Line?	5
	1.2	Obtain	ing the latest release	6
	1.3			6
	1.4	Contac	xt	7
	1.5		ght and license	7
	1.6			8
2	Gett	ting star	rted	9
	2.1	Installa	ation and support	9
		2.1.1	Minimal requirements	9
		2.1.2	Documentation	10
		2.1.3	Getting help	10
	2.2	Getting		10
		2.2.1	Example 1: A M/M/1 queue	11
		2.2.2	Example 2: A multiclass M/G/1 queue	13
		2.2.3	Example 3: Machine interference problem	15
		2.2.4	Example 4: Round-robin load-balancing	17
		2.2.5	Example 5: Modelling a re-entrant line	19
		2.2.6	Example 6: A queueing network with caching	21
		2.2.7		23
		2.2.8	Example 8: Optimizing a performance metric	25
3	Netv	work mo	odels 2	27
	3.1	Netwo	rk object definition	28
		3.1.1	Creating a network and its nodes	28
		3.1.2	Job classes	32
		3.1.3	Routing strategies	33
		3.1.4	Class switching	35

CONTENTS 3

		3.1.5	Finite buffers	38
		3.1.6	Service and inter-arrival time processes	38
		3.1.7	Debugging and visualization	41
	3.2	Model i	import and export	43
		3.2.1	Creating a LINE model using JMT	44
		3.2.2	Supported JMT features	44
4	Ana	lysis met	thods	46
-	4.1	•	state analysis	46
		•	Station average performance	46
			Station response time distribution	47
		4.1.3	System average performance	47
	4.2	Specify	ring states	48
			Station states	48
			Network states	51
		4.2.3	Initialization of transient classes	52
	4.3	Transie	nt analysis	52
		4.3.1	Computing transient averages	52
		4.3.2	First passage times into stations	53
	4.4	Sensitiv	rity analysis and numerical optimization	53
		4.4.1	Internal representation of the model structure	53
		4.4.2	Fast parameter update	55
		4.4.3	Refreshing a network topology with non-probabilistic routing	55
		4.4.4	Saving a network object before a change	56
5	Netv	vork solv	vers	57
	5.1	Overvie	ew	57
	5.2	Solution	n methods	58
		5.2.1	AUTO	59
		5.2.2	CTMC	59
		5.2.3	FLUID	60
		5.2.4	GEN	60
		5.2.5	JMT	60
		5.2.6	MAM	61
		5.2.7	MVA	61
		5.2.8	NC	61
		5.2.9	SSA	61
	5.3		ted language features and options	62
			Solver features	62
		532	Class functions	62

4	CONTENTS
---	----------

		5.3.3 Node types	. 63
		5.3.4 Scheduling strategies	. 64
		5.3.5 Statistical distributions	. 64
		5.3.6 Solver options	. 64
	5.4	Solver maintenance	. 65
6	Lay	ered network models	72
	6.1	LayeredNetwork object definition	. 72
		6.1.1 Creating a layered network topology	. 72
		6.1.2 Describing service times of entries	. 73
		6.1.3 Debugging and visualization	
	6.2	Decomposition into layers	. 74
		6.2.1 Running a decomposition	. 75
		6.2.2 Initialization and update	
	6.3	Solvers	. 76
		6.3.1 LQNS	. 76
		6.3.2 LN	. 77
	6.4	Model import and export	. 77
7	Ran	dom environments	79
	7.1	Environment object definition	. 79
		7.1.1 Specifying the environment transitions	
		7.1.2 Specifying the system models	
	7.2	Solvers	
		7.2.1 ENV	
A	Exa	mples	84

Chapter 1

Introduction

1.1 What is LINE?

LINE is an engine for system performance and reliability evaluation based on queueing theory and stochastic modeling. The goal of the tool is to simplify the computation of performance and reliability metrics in systems such as software applications, business processes, or computer networks. LINE decomposes a high-level system model into one or more stochastic models, typically extended queueing networks, that are subsequently analyzed for performance and reliability metrics using either numerical algorithms or simulation.

A key feature of LINE is that the engine decouples the model description from the solvers used for its solution. That is, the engine implements model-to-model transformations that automatically translate the model specification into the input format (or data structure) accepted by the target solver. External solvers supported by LINE include Java Modelling Tools (JMT; http://jmt.sf.net) and LQNS (http://www.sce.carleton.ca/rads/lqns/). Native model solvers are instead based on formalisms and techniques such as:

- Continuous-time Markov chains (CTMC)
- Fluid ordinary differential equations (FLUID)
- Matrix analytic methods (MAM)
- Normalizing constant analysis (NC)
- Mean-value analysis (MVA)
- Stochastic simulation (SSA)

Each solver encodes a general solution paradigm and can implement both exact and approximate analysis methods. For example, the MVA solver implements both exact mean value analysis (MVA) and approximate mean value analysis (AMVA). The offered methods typically differ for accuracy, computational cost, and

the subset of model features they support. A special solver (AUTO) is supplied that provides an automated recommendation on which solver to use for a given model.

The above techniques can be applied to models specified in the following formats:

- LINE modeling language (MATLAB script format). This is a MATLAB-based object-oriented language designed to resemble the abstractions available in JMT's queueing network simulator (JSIM). Among the main benefits of this language is that LINE models can be exported to, and visualized with, JSIMgraph and JSIMwiz.
- Layered queueing network models (LQNS XML format). LINE is able to solve a sub-class of layered queueing network models, either specified in LINE or using the XML metamodel of the LQNS solver.
- *JMT simulation models (JSIMg, JSIMw formats)*. LINE is able to import and solve queueing network models specified using JMT's simulation tools, namely JSIMgraph and JSIMwiz.
- *Performance Model Interchange Format (PMIF XML format)*. LINE is able to import and solve closed queueing network models specified using PMIF v1.0.

1.2 Obtaining the latest release

This document contains the user manual for LINE version 2.0.0-BETA, which can be obtained from:

http://line-solver.sourceforge.net/

LINE 2.0.0-BETA has been tested on MATLAB R2018a and later releases and requires the *Statistics and Machine Learning Toolbox*. Some advanced features also require the *Parallel Computing Toolbox*. If you are interested to obtain LINE as a JAR, or as an executable distribution for any of the operating systems supported by the MATLAB Compiler Runtime (MCR), please contact the maintainer.

1.3 References

To cite LINE, we recommend to reference:

- G. Casale. "Automated Multi-paradigm Analysis of Extended and Layered Queueing Models with LINE", in *Proc. of ACM/SPEC 2019*, ACM Press, Apr 2019. *This paper introduces* LINE *version* 2.0.0.
- J. F. Pérez and G. Casale. "LINE: Evaluating Software Applications in Unreliable Environments", in *IEEE Transactions on Reliability*, Volume 66, Issue 3, pages 837-853, Feb 2017. *This paper introduces* LINE version 1.0.0.

The following papers discuss applications of LINE:

1.4. CONTACT 7

• C. Li and G. Casale. "Performance-Aware Refactoring of Cloud-based Big Data Applications", in Proceedings of 10th IEEE/ACM International Conference on Utility and Cloud Computing, 2017. This paper uses LINE to model stream processing systems.

- D. J. Dubois, G. Casale. "OptiSpot: minimizing application deployment cost using spot cloud resources", in *Cluster Computing*, Volume 19, Issue 2, pages 893-909, 2016. This paper uses LINE to determine bidding costs in spot VMs.
- R. Osman, J. F. Pérez, and G. Casale. "Quantifying the Impact of Replication on the Quality-of-Service in Cloud Databases'. Proceedings of the IEEE International Conference on Software Quality, Reliability and Security (QRS), 286-297, 2016. This paper uses LINE to model the Amazon RDS database.
- C. Müller, P. Rygielski, S. Spinner, and S. Kounev. Enabling Fluid Analysis for Queueing Petri Nets via Model Transformation, Electr. Notes Theor. Comput. Sci, 327, 71–91, 2016. *This paper uses* LINE to analyze Descartes models used in software engineering.
- J. F. Pérez and G. Casale. "Assessing SLA compliance from Palladio component models," in Proceedings of the 2nd Workshop on Management of resources and services in Cloud and Sky computing (MICAS), IEEE Press, 2013. This paper uses LINE to analyze Palladio component models used in model-driven software engineering.

1.4 Contact

Project coordinator and maintainer contact:

Giuliano Casale
Department of Computing
Imperial College London
180 Queen's Gate
SW7 2AZ, London, United Kingdom.

Web: http://wp.doc.ic.ac.uk/gcasale/

1.5 Copyright and license

Copyright Imperial College London (2012-Present). LINE is freeware and open-source, released under the 3-clause BSD license. Additional licensing information is available in the file: https://sourceforge.net/p/line-solver/code/ci/master/tree/LICENSE. License files of third-party libraries are placed under the lib/directory.

1.6 Acknowledgement

LINE has been partially funded by the European Commission grants FP7-318484 (MODAClouds), H2020-644869 (DICE), H2020-825040 (RADON), and by the EPSRC grant EP/M009211/1 (OptiMAM).

Chapter 2

Getting started

2.1 Installation and support

This is the fastest way to get started with LINE:

- 1. Obtain the latest release:
 - Stable release (zip file): https://sourceforge.net/projects/line-solver/files/latest/download
 - Development release (git): https://sourceforge.net/p/line-solver/code/ci/master/tree/

Ensure that the files are decompressed in the chosen installation folder.

2. Before running LINE you always need to add all subfolders to the MATLAB path. In order to do so, start MATLAB and change the active directory to the installation folder, then run

```
addpath(genpath(pwd))
```

3. LINE is now ready to use. For example, you can run the demonstrators using

```
allExamples
```

2.1.1 Minimal requirements

Certain features of LINE depend on external tools and libraries. Below are the minimal requirements:

- MATLAB: version 2018a or later, with the Statistics and Machine Learning Toolbox.
- Java Modelling Tools (http://jmt.sf.net): version 1.0.4 or later. The latest version is automatically downloaded at the first call of the JMT solver.

- LQNS (http://www.sce.carleton.ca/rads/lqns/): version 6.0 or later. System paths need to be configured such that the lqns and lqnsim solvers need are available on the command line (i.e., can be invoked from MATLAB via the dos or unix commands without need to specify the paths of the executables).
- BuTools (http://webspn.hit.bme.hu/~telek/tools/butools/): version 2.0 or later. This release is already included under the *lib/* subfolder.
- KPC-Toolbox (https://github.com/kpctoolboxteam/kpc-toolbox): version 0.3.2 or later. This release is already included under the *lib*/ subfolder.

2.1.2 Documentation

This manual introduces the main concepts required to use LINE. It includes in particular many tables that outline the currently supported features in the models and within each solver. An online version of this manual is available at:

https://github.com/line-solver/LINE/wiki

In addition to this manual, a detailed description of the LINE APIs is available at:

http://line-solver.sourceforge.net/api/index.html

2.1.3 Getting help

For discussions, bug reports, new feature requests, please open a thread on one of the following Sourceforge boards:

- General discussion: https://sourceforge.net/p/line-solver/discussion/help/
- Bugs and issues: https://sourceforge.net/p/line-solver/tickets/
- Feature requests: https://sourceforge.net/p/line-solver/feature-requests/

2.2 Getting started examples

Systems can be described in LINE using one of the available classes of stochastic models:

• Network models are extended queueing networks. Typical instances are open, closed and mixed queueing networks, including advanced features such as class-switching, finite capacity, priorities, non-exponential distributions, and others. Technical background on these models can be found in books such as [3, 17] or in tutorials [1, 16].

• LayeredNetwork models are layered queueing networks, i.e., models consisting of layers, each corresponding to a Network object, which interact through synchronous and asynchronous calls. Technical background on layered queueing networks can be found in [25].

The goal of the remainder of this chapter is to provide simple examples that explain the basics on how these models can be analyzed in LINE. More advanced forms of evaluation, such as probabilistic or transient analyses, are discussed in later chapters. Additional examples are supplied under the examples / folder.

2.2.1 Example 1: A M/M/1 queue

The M/M/I queue is a classic model of a queueing system where jobs arrive into an infinite-capacity buffer, wait to be processed in first-come first-served (FCFS) order, and then leave after service completion. Arrival and service times are assumed to be independent and exponentially distributed random variables.

In this example, we wish to compute average performance measures for the M/M/1 queue. We assume that arrivals come in at rate $\lambda=1$ job/s, while service has rate $\mu=2$ job/s. It is known from theory that the exact value of the server utilization in this case is $\rho=\lambda/\mu=0.5$, i.e., 50%, while the mean response time for a visit is $R=1/(\mu-\lambda)=1$ s. We wish to verify these values using JMT-based simulation, instantiated through LINE.

The general structure of a LINE script consists of four blocks:

- 1. Definition of nodes
- 2. Definition of job classes and associated statistical distributions
- 3. Instantiation of model topology
- 4. Solution

For example, the following script solves the M/M/1 model

```
model = Network('M/M/1');
% Block 1: nodes
source = Source(model, 'mySource');
queue = Queue(model, 'myQueue', SchedStrategy.FCFS);
sink = Sink(model, 'mySink');
% Block 2: classes
oclass = OpenClass(model, 'myClass');
source.setArrival(oclass, Exp(1));
queue.setService(oclass, Exp(2));
% Block 3: topology
model.link(Network.serialRouting(source, queue, sink));
% Block 4: solution
AvgTable = SolverJMT(model,'seed',23000).getAvgTable
```

In the example, source and sink are arrival and departure points of jobs; queue is a queueing station with FCFS scheduling; oclass defines an open class of jobs that arrive, get served, and leave the system; Exp(x) defines an exponential distribution with rate x; finally, the getAvgTable command solves for average performance measures with JMT's simulator, using for reproducibility a specific seed for the random number generator.

The result is a table with mean performance measures including: the number of jobs in the station either queueing or receiving service (QLen); the utilization of the servers (Util); the mean response time per visit to the station (RespT); the mean throughput of departing jobs (Tput)

AvgTable = 2x6 table Station	Class	QLen	Util	RespT	Tput
'mySource' 'myQueue'	'myClass'	0.9555	0 0.48736	0 0.95429	0.99894 0.99987

One can verify that this matches JMT results by first typing

```
model.jsimgView
```

which will open the model inside JSIMgraph, as shown in Figure 2.1. From this screen, the simulation can be started using the green "play" button in the JSIMgraph toolbar.




Figure 2.1: M/M/1 example in JSIMgraph

LINE also offers shortcuts to accelerate the definition of basic models. For example, an M/M/1 with arrival rate 1 and service rate 2 can be readily instantiated as

```
model=Network.tandemFcfs(1,2)
```

2.2.2 Example 2: A multiclass M/G/1 queue

We now consider a more challenging variant of the first example. We assume that there are two classes of incoming jobs with non-exponential service times. For the first class, service times are Erlang distributed with unit rate and variance 1/3; they are instead read from a trace for the second class. Both classes have exponentially distributed inter-arrival times with mean 2s. To run this example, we assume that the reader has changed the MATLAB working directory to the examples / folder.

We first specify the node block

```
clear;
model = Network('M/G/1');
source = Source(model, 'Source');
queue = Queue(model, 'Queue', SchedStrategy.FCFS);
sink = Sink(model, 'Sink');
```

The next step consists in defining the classes. We fit automatically from mean and squared coefficient of variation (i.e., variance/mean²) an Erlang distribution and use the Replayer distribution to request that the specified trace is cyclically read to obtain the service times of class 2

```
jobclass1 = OpenClass(model, 'Class1');
jobclass2 = OpenClass(model, 'Class2');

source.setArrival(jobclass1, Exp(0.5));
source.setArrival(jobclass2, Exp(0.5));

queue.setService(jobclass1, Erlang.fitMeanAndSCV(1, 1/3));
queue.setService(jobclass2, Replayer('example_trace.txt'));
```

Note that the example_trace.txt file consists of a single column of doubles, each representing a service time sample, e.g.,

```
1.2377474e-02
4.4486055e-02
1.0027642e-02
2.0983173e-02
```

We now specify a linear route through source, queue, and sink for both classes

```
P = model.initRoutingMatrix();
P{jobclass1} = Network.serialRouting(source, queue, sink);
P{jobclass2} = Network.serialRouting(source, queue, sink);
model.link(P);
```

and solve the model with JMT

```
>>AvgTable = SolverJMT(model).getAvgTable
```

AvgTable = 4x6 table Station	Class	QLen	Util	RespT	Tput
'Source'	'Class1'	0	0	0	0.5022
'Source'	'Class2'	0	0	0	0.49999
'Queue'	'Class1'	0.92002	0.51294	1.7724	0.5071
'Queue'	'Class2'	0.44506	0.051639	0.85211	0.49996

We wish now to validate this value against an analytical solver. Since jobclass2 has trace-based service times, we first need to revise its service time distribution to make it analytically tractable, e.g., we may ask LINE to fit a Coxian distribution based on the trace

```
queue.setService(jobclass2, Replayer('example_trace.txt').fitCox());
```

We can now use a Continuous Time Markov Chain (CTMC) to solve the system, but since the state space is infinite in open models, we need to truncate it to be able to use this solver. For example, we may restrict to states with at most 2 jobs in each class, checking with the verbose option the size of the resulting state space

```
>> SolverCTMC (model, 'cutoff', 2, 'verbose', true) .getAvgTable
State space size: 46 states.
CTMC analysis completed in 0.096734 sec
ans =
  4x6 table
    Station
                 Class
                                           Util
                              OLen
                                                      RespT
                                                                  Tput
    'Source'
                 'Class1'
                                   0
                                                0
                                                                 0.44948
                 'Class2'
    'Source'
                                   0
                                                0
                                                            0
                                                                 0.48424
                 'Class1'
    'Queue'
                             0.56734
                                          0.44948
                                                      1.2863
                                                                 0.44107
    'Queue'
                 'Class2'
                             0.24455
                                         0.048942
                                                     0.51396
                                                                 0.47583
```

However, we see from comparison with the JMT results that the errors are rather large. Since the truncated state space consists of just 46 states, we can further increase the cutoff to 4, trading a slower solution time for higher precision

```
>> SolverCTMC (model, 'cutoff', 4, 'verbose', true) .getAvgTable
State space size: 626 states.
CTMC analysis completed in 1.051784 sec
ans =
  4x6 table
   Station
                Class
                             QLen
                                         Util
                                                    RespT
                                                               Tput
                'Class1'
                                0
                                             0
                                                         0
                                                              0.49215
    'Source'
                                                         0
    'Source'
                'Class2'
                                 0
                                             0
                                                              0.49626
    'Queue'
                'Class1'
                            0.7958
                                        0.49215
                                                              0.49162
                                                    1.6187
    'Queue'
                'Class2'
                            0.37558
                                       0.050157
                                                   0.75763
                                                              0.49573
```

To gain more accuracy, we could either keep increasing the cutoff value or, if we wish to compute an exact solution, we may call the matrix-analytic method (MAM) solver instead. MAM uses the repetitive structure of the CTMC to exactly analyze open systems with an infinite state space

Table = x6 table					
Station	Class	QLen	Util	RespT	Tput
'Source'	'Class1'	0	0	0	0.5
'Source'	'Class2'	0	0	0	0.5
'Queue'	'Class1'	0.87646	0.5	1.7529	0.5
'Queue'	'Class2'	0.427	0.050536	0.85399	0.5

The current MAM implementation is primarily constructed on top of the BuTools solver [14].

2.2.3 Example 3: Machine interference problem

Closed models involve jobs that perpetually cycle within a network of queues. The machine interference problem is a classic example, in which a group of repairmen is tasked with fixing machines as they break and the goal is to choose the optimal size of the group. We here illustrate how to evaluate the performance of a given group size. We consider a scenario with S=2 repairmen, with machines that break at a rate of 4.0 failed machines/week, after which a machine operates as normal for an exponential distributed time with rate 0.5 failed machines/week. There are a total of N=3 machines.

Suppose that we wish to obtain an exact numerical solution using Continuous Time Markov Chains (CTMCs). The above model can be analyzed as follows:

```
S=2; N=3;
model = Network('MIP');
% Block 1: nodes
delay = Delay(model, 'WorkingState');
queue = Queue(model, 'RepairQueue', SchedStrategy.FCFS);
queue.setNumberOfServers(S);
% Block 2: classes
cclass = ClosedClass(model, 'Machines', N, delay);
delay.setService(cclass, Exp(0.5));
queue.setService(cclass, Exp(4.0));
% Block 3: topology
model.link(Network.serialRouting(delay,queue));
% Block 4: solution
solver = SolverCTMC(model);
solver.getAvgTable()
```

Here, delay appears in the constructor of the closed class to specify that a machine fixing job will be considered completed once it returns to the delay (i.e., the machine is in working state). We say that the delay is thus the *reference station* of class cclass. The above code prints the following result

```
ans =
  2x6 table
       Station
                         Class
                                      QLen
                                                  Util
                                                              RespT
                                                                         Tput
    'WorkingState'
                       'Machines'
                                       2.6648
                                                  2.6648
                                                                        1.3324
    'RepairQueue'
                       'Machines'
                                      0.33516
                                                 0.16655
                                                             0.25154
                                                                        1.3324
```

As before, we can inspect and analyze the model in JSIMgraph using the command

```
model.jsimgView
```

Figure 2.2 illustrates the result, demonstrating the automated definition of the closed class.




Figure 2.2: Machine interference model in JSIMgraph

We can now also inspect the CTMC more in the details as follows

```
StateSpace = solver.getStateSpace()
InfGen = full(solver.getGenerator())
```

which produces in output the state space of the model and the infinitesimal generator of the CTMC

```
StateSpace =
    0
          1
                2
    1
          0
                2
    2
          0
                1
    3
InfGen =
  -8.0000
            8.0000
                          0
                                      0
           -8.5000
   0.5000
                       8.0000
                                      0
                     -5.0000
           1.0000
        0
                               4.0000
                     1.5000
                               -1.5000
```

For example, the first state (0 1 2) consists of two components: the initial 0 denotes the number of jobs in service in the delay, while the remaining part is the state of the FCFS queue. In the latter, the 1 means

that a job of class 1 (the only class in this model) is in the waiting buffer, while the 2 means that there are two jobs in service at the queue.

The second state $(1\ 0\ 2)$ is similar, but one job has completed at the queue and then moved to the delay, concurrently triggering an admission in service for the job that was in the queue buffer. As a result of this, the buffer is now empty. The corresponding transition rate in the infinitesimal generator matrix is InfGen (1,2)=8.0, which sums the completion rates at the queue for each server, and where indexes 1 and 2 are the rows in StateSpace associated to the two states.

2.2.4 Example 4: Round-robin load-balancing

In this example we consider a system of two parallel processor-sharing queues and we wish to study the effect of load-balancing on the average performance of an open class of jobs. We begin as usual with the node block, where we now include a special node, called the Router, to control the routing of jobs from the source into the queues:

```
model = Network('RRLB');
source = Source(model, 'Source');
lb = Router(model, 'LB');
queue1 = Queue(model, 'Queue1', SchedStrategy.PS);
queue2 = Queue(model, 'Queue2', SchedStrategy.PS);
sink = Sink(model, 'Sink');
```

Let us then define the class block by setting exponentially-distributed inter-arrival times and service times, e.g.,

```
oclass = OpenClass(model, 'Class1');
source.setArrival(oclass, Exp(1));
queuel.setService(oclass, Exp(2));
queue2.setService(oclass, Exp(2));
```

We now wish to express the fact that the router applies a round-robin strategy to dispatch jobs to the queues. Since this is now a non-probabilistic routing strategy, we need to adopt a slightly different style to declare the routing topology as we cannot specific anymore routing probabilities. First, we indicate the connections between the nodes, using the addLinks function:

At this point, all nodes are automatically configured to route jobs with equal probabilities on the outgoing links (RoutingStrategy.RAND policy). If we solve the model at this point, we see that the response time at the queues is around 0.66s.

```
>> SolverJMT(model).getAvgTable
ans =
  3x6 table
    Station
                  Class
                                          Util
                               QLen
                                                      RespT
                                                                  Tput
    'Source'
                 'Class1'
                                                0
                                                           0
                                                                  1.0178
    'Queue1'
                 'Class1'
                              0.32089
                                          0.24179
                                                     0.65821
                                                                 0.50222
    'Queue2'
                 'Class1'
                              0.32605
                                          0.25078
                                                     0.66978
                                                                 0.50161
```

After resetting the internal data structures, which is required before modifying a model already solved at least once, we can require LINE to solve again the model using this time a round-robin policy at the router.

```
model.reset()
lb.setRouting(oclass, RoutingStrategy.RR);
```

A representation of the model at this point is shown in Figure 2.3.




Figure 2.3: Load-balancing model

Lastly, we run again JMT and find that round-robin produces a visible decrease in response times, which are now around 0.56s.

>> SolverJMT(model).getAvgTable					
3x6 table Station	Class	QLen	Util	RespT	Tput
'Source'	'Class1'	0	0	0	0.97298
'Queue1' 'Queue2'	'Class1' 'Class1'	0.27649 0.29316	0.24399 0.24761	0.55775 0.56565	0.48615 0.4932

2.2.5 Example 5: Modelling a re-entrant line

Let us now consider a simple example inspired to the classic problem of modeling *re-entrant lines*. This arises in manufacturing systems where parts (i.e., jobs) re-enter multiple times a machine (i.e., a queueing station), asking at every visit a different class of service. This implies, for example, that the service time at every visit could feature a different mean or a different distribution compared to the previous visits, thus modeling a different stage of processing.

To illustrate this, consider for example a degenerate model composed by a single FCFS queue and K classes. In this model, a job that completes processing in class k is routed back at the tail of the queue in class k+1, unless k=K in which case the job re-enters in class 1.

We take the following assumptions: K=3 and class k has an Erlang-2 service time distribution at the queue with mean equal to k; the system starts with $N_1=1$ jobs in class 1 and zero jobs inside all other classes.

```
model = Network('RL');
queue = Queue(model, 'Queue', SchedStrategy.FCFS);

K = 3; N = [1,0,0];
for k=1:K
    jobclass{k} = ClosedClass(model, ['Class',int2str(k)], N(k), queue);
    queue.setService(jobclass{k}, Erlang.fitMeanAndOrder(k,2));
end

P = model.initRoutingMatrix();
P{jobclass{1},jobclass{2}}(queue,queue) = 1.0;
P{jobclass{2},jobclass{3}}(queue,queue) = 1.0;
P{jobclass{3},jobclass{1}}(queue,queue) = 1.0;
model.link(P);
```

The corresponding JMT model is shown in Figure 2.4, where it can be seen that the class-switching rule is automatically enforced by introduction of a ClassSwitch node in addition to the queue.



Figure 2.4: Re-entrant lines as an example of class-switching

We can now simulate the performance indexes for the different classes

```
>> SolverCTMC (model) .getAvgTable
ans =
 3x6 table
                                Util
   Station Class QLen
                                         RespT
                                                   Tput
   'Queue'
            'Class1'
                      0.16667
                                 0.16667
                                                  0.16667
   'Oueue'
            'Class2'
                      0.33333
                               0.33333
                                            2
                                                  0.16667
   'Oueue'
            'Class3'
                         0.5
                                    0.5
                                            3
                                                  0.16667
```

Suppose now that the job is considered completed, for the sake of computation of the system performance metrics, only when it departs the queue in class K (here Class3). By default, LINE will return system-wide performance metrics using the getAvgSysTable method, i.e.,

```
>> SolverCTMC(model).getAvgSysTable
ans =
1x4 table
Chain Classes SysRespT SysTput

'Chain1' {1x3 cell} 2 0.5
```

This method identifies the model *chains*, i.e., groups of classes that can exchange jobs with each other, but not with classes in other chains. Since the job can switch into any of the three classes, in this model there is a single chain comprising the three classes.

We see that the throughput of the chain is 0.5, which means that LINE is counting every departure from the queue from any class as a completion for the whole chain. This is incorrect for our model since we want to count completions only when jobs depart in Class3. To require this behavior, we can tell to the solver that passages for classes 1 and 2 through the reference station should not be counted as completions

```
jobclass{1}.completes = false;
jobclass{2}.completes = false;
```

This modification then gives the correct chain throughput, matching the one of Class3 alone

```
>> SolverCTMC(model).getAvgSysTable
ans =
1x4 table
Chain Classes SysRespT SysTput

'Chain1' {1x3 cell} 6 0.16667
```

2.2.6 Example 6: A queueing network with caching

In this more advanced example, we show how to include in a queueing network a cache adopting a least-recently used (LRU) replacement policy. Under LRU, upon a cache miss the least-recently accessed item will be discarded to make room for the newly requested item.

We consider a cache with a capacity of 50 items, out of a set of 1000 cacheable items. Items are accessed by jobs visiting the cache according to a Zipf-like law with exponent $\alpha=1.4$ and defined over the finite set of items. A client cyclically issues requests for the items, waiting for a reply before issuing the next request. We assume that a cache hit takes on average 0.2ms to process, while a cache hit takes 1ms. We ask for the average request throughput of the system, differentiated across hits and misses.

Node block As usual, we begin by defining the nodes. Here a delay node will be used to describe the time spent by the requests in the system, while the cache node will determine hits and misses:

```
model = Network('QNC');
% Block 1: nodes
clientDelay = Delay(model, 'Client');
cacheNode = Cache(model, 'Cache', 1000, 50, ReplacementStrategy.LRU);
cacheDelay = Delay(model, 'CacheDelay');
```

Class block We define a set of classes to represent the incoming requests (clientClass), cache hits (hitClass) and cache misses (missClass). These classes need to be closed to ensure that there is a single outstanding request from the client at all times:

```
% Block 2: classes
clientClass = ClosedClass(model, 'ClientClass', 1, clientDelay, 0);
hitClass = ClosedClass(model, 'HitClass', 0, clientDelay, 0);
missClass = ClosedClass(model, 'MissClass', 0, clientDelay, 0);
```

We then assign the processing times, using the Immediate distribution to ensure that the client issues immediately the request to the cache:

```
clientDelay.setService(clientClass, Immediate());
cacheDelay.setService(hitClass, Exp.fitMean(0.2));
cacheDelay.setService(missClass, Exp.fitMean(1));
```

The next step involves specifying that the request uses a Zipf-like distribution to select the item to read from the cache

```
cacheNode.setRead(clientClass, Zipf(1.4,1000));
```

Finally, we ask that the job should become of class hitClass after a cache hit, and should become of class missClass after a cache miss:

```
cacheNode.setHitClass(clientClass, hitClass);
cacheNode.setMissClass(clientClass, missClass);
```

Topology block Next, in the topology block we setup the routing so that the request, which starts in clientClass at the clientDelay, then moves from there to the cache, remaining in clientClass

```
% Block 3: topology
P = model.initRoutingMatrix();
P{clientClass, clientClass}(clientDelay, cacheNode) = 1.0;
```

Internally to the cache, the job will switch its class into either hitClass or missClass. Upon departure in one of these classes, we ask it to join in the same class cacheDelay for further processing

```
P{hitClass, hitClass}(cacheNode, cacheDelay) = 1.0;
P{missClass, missClass}(cacheNode, cacheDelay) = 1.0;
```

Lastly, the job returns to clientDelay for completion and start of a new request, which is done by switching its class back to clientClass

```
P{hitClass, clientClass}(cacheDelay, clientDelay) = 1.0;
P{missClass, clientClass}(cacheDelay, clientDelay) = 1.0;
```

The above routing strategy is finally applied to the model

```
model.link(P);
```

Solution block To solve the model, since JMT does not support cache modeling, we use the native MATLAB-based simulation engine provided within LINE, the SSA solver:

```
% Block 4: solution
AvgTable = SolverSSA(model, 'samples', 2e4, 'seed', 1, 'verbose', true) .getAvgTable
```

The above script produces the following result

```
SSA samples: 20000
SSA analysis completed in 11.902675 sec
AvgTable =
3x6 table
                   Class
                               QLen
                                         Util
    Station
                                                  RespT
                                                            Tput
  'Client'
                'ClientClass'
                                           0
                                                     0
                                                            2.9917
                                0
  'CacheDelay' 'HitClass'
'CacheDelay' 'MissClass'
                              0.49108 0.49108
                                                    0.2
                                                            2.4554
                'MissClass' 0.50892
  'CacheDelay'
                                         0.50892
                                                     1
                                                            0.50892
```

The departing flows from the CacheDelay are the miss and hit rates. Thus, the hit rate is 2.4554 req/ms, while the miss rate is 0.50892 req/ms, which both include the service times.

Let us now suppose that we wish to verify the result with a longer simulation, for example with 10 times more samples. To this aim, we can use the automatic parallelization of SSA based on MATLAB's spmd construct:

```
SolverSSA(model, 'samples', 2e4, 'seed', 1, 'method', 'para').getAvgTable
```

This gives us a rather similar result, when run on a dual-core machine

```
Starting parallel pool (parpool) using the 'local' profile ...
connected to 2 workers.
AvgTable =
3x6 table
                     Class
    Station
                                   QLen
                                            Util
                                                     RespT
                                                              Tput
                 'ClientClass'
   'Client'
                                 0
                                            0
                                                      0
                                                              2.8636
              'HitClass' 0.4709
'MissClass' 0.5291
   'CacheDelay'
                                           0.4709
                                                      0.2
                                                              2.3545
   'CacheDelay'
                                           0.5291
                                                              0.5291
                                                        1
```

The execution time is longer than usual at the first invocation of the parallel solver due to the time needed by MATLAB to bootstrap the parallel pool, in this example around 22 seconds. Successive invocations of parallel SSA normally take much less, with this example around 7 seconds each.

2.2.7 Example 7: Response time distribution and percentiles

In this example we illustrate the computation of response time percentiles in a queueing network model. We begin by instantiating a simple closed model consisting of a delay followed by a processor-sharing queueing station.

```
model = Network('model');
% Block 1: nodes
node{1} = Delay(model, 'Delay');
node{2} = Queue(model, 'Queuel', SchedStrategy.PS);
```

There is a single class consisting of 5 jobs that circulate between the two stations, taking exponential service times at both.

```
% Block 2: classes
jobclass{1} = ClosedClass(model, 'Class1', 5, node{1}, 0);
node{1}.setService(jobclass{1}, Exp(1.0));
node{2}.setService(jobclass{1}, Exp(0.5));

% Block 3: topology
model.link(Network.serialRouting(node{1},node{2}));
```

We now wish to compare the response time distribution at the PS queue computed analytically with a fluid approximation against the simulated values returned by JMT. To do so, we call the getCdfRespT method

```
% Block 4: solution
RDfluid = SolverFluid(model).getCdfRespT();
RDsim = SolverJMT(model, 'seed', 23000, 'samples', 1e4).getCdfRespT();
```

The returned data structures, RDfluid and RDsim, are cell arrays consisting of a 2-column matrix. The element in position $\{i,r\}$ of the cell array describes the response times at station i for class r. The two columns within such matrices are defined similar to the output of MATLAB's ecdf function, i.e., the first column represents the cumulative distribution function (CDF) value $F(t) = Pr(T \le t)$, where T is the random variable denoting the response time, while t is the percentile appearing in the corresponding entry of the second column.

For example, to plot the complementary CDF 1 - F(t) we can use the following code

```
% Plot results
semilogx(RDsim{2,1}(:,2),1-RDsim{2,1}(:,1),'r'); hold all;
semilogx(RDfluid{2,1}(:,2),1-RDfluid{2,1}(:,1),'--');
legend('jmt-transient','fluid-steady','Location','Best');
ylabel('Pr(T > t)'); xlabel('time t');
```

which produces the graph shown in Figure 2.5 The graph shows that, although the simulation refers to a




Figure 2.5: Comparison of simulated response time distribution and its fluid approximation

transient, while the fluid approximation refers to steady-state, there is a tight matching between the two response time distributions.

We can also readily compute the percentiles from the RDfluid and RDsim data structures, e.g., for the 95th and 99th percentiles of the simulated distribution

```
>> prc95=max(RDsim{2,1}(RDsim{2,1}(:,1)<0.95,2))
```

```
prc95 =
    27.0222
>> prc99=max(RDsim{2,1}(RDsim{2,1}(:,1)<0.99,2))
prc99 =
    41.8743</pre>
```

That is, 95% of the response times at the PS queue (node 2, class 1) are less than or equal to 27.0222 time units, while 99% are less than or equal to 41.8743 time units.

2.2.8 Example 8: Optimizing a performance metric

In this example, we show how to optimize with the help of LINE a performance metric. We wish to find the optimal routing probabilities that minimize average response times for two parallel processor sharing queues. We assume that jobs are fed by a delay station, arranged with the two queues in a closed network topology.

We first create a MATLAB function (e.g., ex8.m) with header

```
function p_star = ex8()
```

Within the function definition, we instantiate the two queues and the delay station

```
model = Network('LoadBalCQN');
% Block 1: nodes
delay = Delay(model, 'Think');
queue1 = Queue(model, 'Queue1', SchedStrategy.PS);
queue2 = Queue(model, 'Queue2', SchedStrategy.PS);
```

We assume that 16 jobs circulate among the nodes, and that the service rates are $\sigma=1$ job/s at the delay, and $\mu_1=0.75$ and $\mu_2=0.50$ at the two queues:

```
% Block 2: classes
cclass = ClosedClass(model, 'Job1', 16, delay);
delay.setService(cclass, Exp(1));
queue1.setService(cclass, Exp(0.75));
queue2.setService(cclass, Exp(0.50));
```

We initially setup a topology with arbitrary values for the routing probabilities between delay and queues, ensuring that jobs completing at the queues return to the delay:

```
% Block 3: topology
P = model.initRoutingMatrix();
P{cclass}(queue1, delay) = 1.0;
P{cclass}(queue2, delay) = 1.0;
model.link(P);
```

We now write a nested function that returns the system response time for the jobs as a function of the routing probability p to choose queue 1 instead of queue 2:

```
% Block 4: solution
  function R = objFun(p)
    P{cclass} (delay, queue1) = p;
    P{cclass} (delay, queue2) = 1-p;
    model.link(P);
    R = SolverMVA(model, 'method', 'exact', 'verbose', false).getAvgSysRespT;
  end
p_opt = fminbnd(@(p) objFun(p), 0,1)
```

In the above listing, objFun first updates the routing topology, prior to obtaining the corresponding system response time. To search for the optimal routing probability p, we have also used MATLAB's fminbnd which restricts the search range in the interval [0,1].

We are now ready to run ex8 from the MATLAB command line. The execution returns the optimal value p-opt= 0.6105.

Chapter 3

Network models

Throughout this chapter, we discuss the specification of Network models, which are extended queueing networks. LINE currently support open, closed and mixed networks with non-exponential service and arrivals, and state-dependent routing. All solvers support the computation of basic performance metrics, while some more advanced features are available only in specific solvers. Each Network model requires in input a description of the nodes, the network topology, and the characteristics of the jobs that circulate within the network. In output, LINE returns performance and reliability metrics. The default metrics supported by all solvers are as follows:

- Mean queue-length (QLen). This is the mean number of jobs residing at a node when this is observed at a random instant of time.
- Mean utilization (Util). For nodes that serve jobs, this is the mean fraction of time the node is busy processing jobs. In both single-server and multi-server nodes, this is a number normalized between 0 and 1, corresponding to 0% and 100%. In infinite-server nodes, the utilization is set by convention equal to the mean queue-length, therefore taking the interpretation of mean number of jobs in execution at the station.
- Mean response time (RespT). This is the mean time a job spends to traverse a node within a network. If the node is visited multiple times, the response time is the time spent for a single visit to the node.
- Mean throughput (Tput). This is the mean departure rate of jobs completed at a resource per time unit. Typically, this matches the mean arrival rate, unless the node switches the class of the jobs in which case the arrival rate of a class may not match its departure rate.

The above metrics refer to performance characteristics of individual nodes. Response times and throughputs can also be system-wide, meaning that they can describe end-to-end performance during the visit to the network. In this case, these metrics are called *system* metrics.

3.1 Network object definition

3.1.1 Creating a network and its nodes

A queueing network can be described in LINE using the Network class constructor with a unique string identifying the model name:

```
model = Network('myModel');
```

The returned object of the Network class offers functions to instantiate and manage resource *nodes* (stations, delays, caches, ...) visited by jobs of several types (*classes*).

A node is a resource in the network that can be visited by a job. A list of nodes available in Network models is given in Table 3.1.1.

Table 3.1: Nodes available in Network models

Node	Description
Cache	A node to switch job classes based on hits/misses in its cache
ClassSwitch	A node to switch job classes based on a static probability matrix
Delay	A station where jobs spend time without queueing
Fork	A node that forks jobs into tasks
Join	A node that joins sibling tasks into the original job
Logger	A node that logs passage of jobs
Queue	A node where jobs queue and receive service
Router	A node that routes jobs to other nodes
Sink	Exit point for jobs in open classes
Source	Entry point for jobs in open classes

We now provide more details on each of the nodes available in Network models.

Queue node. A Queue specifies a queueing station from its name and scheduling strategy, e.g.

```
queue = Queue(model, 'Queuel', SchedStrategy.FCFS);
```

specifies a first-come first-served queue. It is alternatively possible to instantiate a queue using the QueueingStation constructor, which is merely an alias for Queue.

Queueing stations have by default a single server, however the setNumberOfServers method can be used to instantiate multi-server stations.

Valid scheduling strategies are specified within the SchedStrategy static class and include:

- First-come first-served (SchedStrategy.FCFS)
- Infinite-server (SchedStrategy.INF)

- Processor-sharing (SchedStrategy.PS)
- Discriminatory processor-sharing (SchedStrategy.DPS)
- Generalized processor-sharing (SchedStrategy.GPS)
- Shortest expected processing time (SchedStrategy.SEPT)
- Shortest job first (SchedStrategy.SJF)
- Head-of-line priority (SchedStrategy.HOL)

If a strategy requires class weights, these can be specified directly as an argument to the setService function or using the setStrategyParam function, see later the description of DPS scheduling for an example.

Delay node. Infinite-server stations may be instantiated either as objects of Queue class with the SchedStrategy. INF strategy or using the following specialized constructor

```
delay = Delay(model, 'ThinkTime');
```

As for queues, for readability it is possible to instantiate delay nodes using the DelayStation constructor, which is entirely equivalent to the one of the Delay class.

Source and Sink nodes. As seen in the M/M/1 getting started example, these nodes are mandatory elements for the specification of open classes. Their constructor only requires a specification of the unique name associated to the nodes:

```
source = Source(model, 'Source');
sink = Sink(model, 'Sink');
```

Fork and Join nodes. The fork and join nodes are currently available only for the JMT solver. The Fork splits an incoming job into a set of sibling tasks, sending out one task for each outgoing link. These tasks inherit the class of the original job and are served as normal jobs until they are reassembled at a Join station.

Their specification of Fork and Join only requires the name of the node

```
source = Fork(model, 'Fork');
sink = Join(model, 'Join');
```

The number of tasks sent by a Fork on each output link can be set using the setTasksPerLink method. Note that the routing probabilities out of the Fork node need to be set to 1.0 towards every other node connected to the Fork. For example, a Fork sending jobs in class 1 to nodes A, B and C, cannot send jobs

in class 2 only to A and B: it must send them to all three connected nodes A, B and C. A new fork visited only by class-2 jobs need to be created to output only to A and B.

ClassSwitch node. This is a stateless node to change the class of a transiting job based on a static probabilistic policy. For example, it is possible to specify that all jobs belonging to class 1 should become of class 2, or that a class 2 job should become of class 1 with probability 0.3. This example is instantiated as follows

```
cs = ClassSwitch(model, 'ClassSwitchPoint',[0.0, 1.0; 0.3, 0.7]);
```

Cache node. This is a stateful node to store one or more items in a cache of finite size, for which it is possible to specify a replacement policy. The cache constructor requires the total cache capacity and the number of items that can be referenced by the jobs in transit, e.g.,

```
cacheNode = Cache(model, 'Cachel', nitems, capacity, ReplacementStrategy.LRU);
```

If the capacity is an integer (e.g., [15]), then it represents the total number of items that can be cached and the value cannot be greater than the number of items. Conversely, if it is a vector (e.g., [10, 5]) then the node is a list-based cache, where the vector entries specify the capacity of each list. We point to [12] for more details on list-based caches and their replacement policies.

Available replacement policies are specified within the ReplacementStrategy static class and include:

- First-in first-out (Replacement Strategy . FIFO)
- Random replacement (Replacement Strategy . RAND)
- Least-recently used (ReplacementStrategy.LRU)
- Strict first-in first-out (ReplacementStrategy.SFIFO)

Upon cache hit or cache miss, a job in transit is switched to a user-specified class. More details are given later in Section 3.1.4.

Router node. This node is able to route jobs according to a specified RoutingStrategy, which can either be probabilistic or not (e.g., round-robin). Upon entering a Router, a job neither waits nor receive service; it is instead directly forwarded to the next node according to the specified routing strategy. A Router can be instantiated as follows:

```
router = Router(model, 'RouterNode');
```

An example of use of this node is given in Section 2.2.4. Routing strategies need to be specified for each class using the setRouting method and valid choices are as follows:

- Random routing (RoutingStrategy.RAND)
- Round robin (RoutingStrategy.RR)
- Probabilistic routing (RoutingStrategy.PROB)
- Join-the-shortest-queue (RoutingStrategy.JSQ)

For example, assume that oclass is a class of jobs. In order to route it with equal probabilities to any of the outgoing links we set

```
router.setRouting(oclass, RoutingStrategy.RAND);
```

It should be note that setRouting is also available for all other nodes such as queueing stations, delays, etc. Therefore, the added value of the Router node is the ability to represent certain system elements that centralize the routing logic without a time-consuming service process, such as load balancers.

Logger node. A logger node is a node that closely resembles the logger node available in the JSIMgraph simulator within JMT. At present, models that include this element can only be solved using the JMT solver.

A Logger node records information about passing jobs in a csv file, such as timestamp of passage and information about the jobs. The node can be instantiated as follows

```
logger=Logger(self, 'LoggerNode', 'logfile.csv');
```

The following methods can be used to specify the information that needs to be stored in the csv file

- setStartTime: record a timestamp for the wallclock time when the simulation started.
- setJobID: record a unique identificator for the passing job.
- setJobClass: record the class of the passing job.
- setTimestamp: record a timestamp for the simulated time when the job passed in the logger.
- setTimeSameClass: record the time elapsed since last passage of a job of the same class.
- setTimeAnyClass: record the time elapsed since last passage of a job of any class.

Each method can be called either with a single true or false argument, to enable or disable the recording of the corresponding information, e.g.

```
logger.setJobClass(true);
```

The routing behavior of jobs can be set up as for regular nodes such as queues or delay stations.

3.1.2 Job classes

Jobs travel within the network placing service demands at the stations. The demand placed by a job at a station depends on the class of the job. Jobs in *open classes* arrive from the external world and, upon completing the visit, leave the network. Jobs in *closed classes* start within the network and are forbidden to ever leave it, perpetually cycling among the nodes.

Open classes

The constructor for an open class only requires the class name and the creation of special nodes called Source and Sink

```
source = Source(model, 'Source');
sink = Sink(model, 'Sink');
```

Sources are special stations holding an infinite pool of jobs and representing the external world. Sinks are nodes that route a departing job back into this infinite pool, i.e., into the source. Note that a network can include at most a single Source and a single Sink.

Once source and sink are instantiated in the model, it is possible to instantiate open classes using

```
class1 = OpenClass(model, 'Class1');
```

LINE does not require to associate source and sink with the open classes in their constructors, as this is done automatically. However, the LINE language requires to explicitly create these nodes since the routing topology needs to indicate the arrival and departure points of jobs in open classes. However, if the network does not includes open classes, the user will not need to instantiate a Source and a Sink.

Closed classes

To create a closed class, we need instead to indicate the number of jobs that start in that class (e.g., 5 jobs) and the *reference station* for that class (e.g., queue), i.e.:

```
class2 = ClosedClass(model, 'Class2', 5, queue);
```

The reference station indicates a point in the network used to calculate certain performance indexes, called *system performance indexes*. The end-to-end response time for a job in an open class to traverse the system is an example of system performance index (system response time). The reference station of an open class is always automatically set by LINE to be the Source. Conversely the reference station needs to be indicated explicitly in the constructor for closed classes, since the point at which a class job completes execution depends on the semantics of the model.

Mixed models

LINE also accepts models where a user has instantiated both open and closed classes. The only requirement is that, if two classes communicate by means of a class-switching mechanism, then the two classes must either be all closed or all open. In other words, classes in the same chain must either be both closed or both open. Furthermore, for closed classes in the same chain it is required that the reference station is the same.

Class priorities

If a class has a priority, with 0 representing the highest priority, this can be specified as an additional argument to both OpenClass and ClosedClass, e.g.,

```
class2 = ClosedClass(model, 'Class2', 5, queue, 0);
```

In Network models, priorities are intended as hard priorities and the only supported priority scheduling strategy (SchedStrategy.HOL) is non-preemptive. Weight-based policies such as DPS and GPS may be used, as an alternative, to prevent starvation of jobs in low priority classes.

3.1.3 Routing strategies

Probabilistic routing

Jobs travel between nodes according to the network topology and a routing strategy. Typically a queueing network will use a probabilistic routing strategy (RoutingStrategy.PROB), which requires to specify routing probabilities among the nodes. The simplest way to specify a large routing topology is to define the routing probability matrix for each class, followed by a call to the link function. This function will automatically add certain nodes to the network to ensure the correct switching of class for jobs moving between stations (ClassSwitch elements).

In the running case, we may instantiate a routing topology as follows:

```
P = model.initRoutingMatrix;
P{class1} (source, queue) = 1.0;
P{class1} (queue, [queue, delay]) = [0.3,0.7]; % self-loop with probability 0.3
P{class1} (delay, sink) = 1.0;
P{class2} (delay, queue) = 1.0; % closed class starts at delay
P{class2} (queue, delay) = 1.0;
model.link(P);
```

When used as arguments to a cell array or matrix, class and node objects will be replaced by a corresponding numerical index. Normally, the indexing of classes and nodes matches the order in which they are instantiated in the model and one can therefore specify the routing matrices using this property. In this case we would have

```
P = model.initRoutingMatrix;
```

The <code>getClassIndex</code> and <code>getNodeIndex</code> functions return the numerical index associated to a node name, e.g., <code>model.getNodeIndex('Delay')</code>. Class and node names in a network need to be unique. The list of used names can be obtained with the <code>getClassNames</code>, <code>getStationNames</code>, and <code>getNodeNames</code> functions of the <code>Network</code> class.

It is also important to note that the routing matrix in the last example is specified between *nodes*, instead than between just stations or stateful nodes, which means that elements such as the Sink need to be explicitly considered in the routing matrix. The only exception is that ClassSwitch elements do not need to be explicitly instantiated and explicited in the routing matrix, provided that one uses the link function to instantiate the topology. Note that the routing matrix assigned to a model can be printed on screen in human-readable format using the printRoutingMatrix function.

Other routing strategies

The above routing specification style is only for models with probabilistic routing strategies between every pair of nodes. A different style should be used for scheduling policies that do not require to explicit routing probabilities, as in the case of state-dependent routing. Currently supported strategies include:

- Round robin (RoutingStrategy.RR). This is a non-probabilistic strategy that sends jobs to outgoing links in a cyclic order.
- Random routing (RoutingStrategy.RAND). This is equivalent to a standard probabilistic strategy that for each class assigns identical values to the routing probabilities of all outgoing links.
- Join-the-Shortest-Queue (RoutingStrategy.JSQ). This is a non-probabilistic strategy that sends jobs to the destination with the smallest total number of jobs in it. If multiple stations have the same total number of jobs, then the destination is chosen at random with equal probability across these stations.

For such policies, the function addLink should be first used to specify pairs of connected nodes

```
model.addLink(queue, queue); %self-loop
model.addLink(queue, delay);
```

Then an appropriate routing strategy should be selected at every node, e.g.,

```
queue.setRouting(class1,RoutingStrategy.RR);
```

assigns round robin among all outgoing links from the queue node.

A model could also include both classes with probabilistic routing strategies and classes that use round robin or other non-probabilistic startegies. To instantiate routing probabilities in such situations one should then use, e.g.,

```
queue.setRouting(class1,RoutingStrategy.PROB);
queue.setProbRouting(class1, queue, 0.7)
queue.setProbRouting(class1, delay, 0.3)
```

where setProbRouting assigns the routing probabilities to the two links.

3.1.4 Class switching

In LINE, jobs can switch class while they travel between nodes (including self-loops on the same node). For example, this feature can be used to model queueing properties such as re-entrant lines in which a job visiting a station a second time may require a different average service demand than at its first visit.

A chain defines the set of reachable classes for a job that starts in the given class r and over time changes class. Since class switching in LINE does not allow a closed class to become open, and vice-versa, chains can themselves be classified into *open chains* and *closed chains*, depending on the classes that compose them.

Jobs in open classes can only switch to another open class. Similarly, jobs in closed classes can only switch to a closed class. Thus, class switching from open to closed classes (or vice-versa) is forbidden. The strategy to describe the class switching mechanism is integrated in the specification of the routing between stations as described next.

Probabilistic class switching

In models with class switching and probabilistic routing at all nodes, a routing matrix is required for each possible pair of source and target classes. For example, suppose that in the previous example the job in the closed class class2 switches into a new closed class (class3) while visiting the queue node. We can specify this routing strategy as follows:

```
class3 = ClosedClass(model, 'Class3', 0, queue, 0);

P = model.initRoutingMatrix;
P{class1,class1}(source, queue) = 1.0;
P{class1,class1}(queue, [queue,delay]) = [0.3,0.7];
P{class1,class1}(delay, sink) = 1.0;
P{class2,class3}(delay, queue) = 1.0; % closed class starts at delay
P{class3,class2}(queue, delay) = 1.0;
model.link(P);
```

where $P\{r, s\}$ is the routing matrix for jobs switching from class r to s. That is, $P\{r, s\}$ (i, j) is the probability that a job in class r departs node i routing into node j as a job of class s.

Importantly, LINE assumes that a job switches class an instant *after* leaving a station, thus the performance metrics of a class at the node refer to the class that jobs had upon arrival to that node.

Depending on the specified probabilities, a job will be able to switch class only among a subset of the available classes. Each subset is called a *chain*. Chains are computed in LINE as the weakly connected components of the routing probability matrix of the network, when this is seen as an undirected graph. The function model.getChains produces the list of chains for the model, inclusive of a list of their composing classes.

An advanced feature of LINE available for example within the Cache node, is that the class-switching decision can dynamically depend on the state of the node (e.g., cache hit/cache miss). However, in order to statically determine chains, LINE requires that every class-switching node declares the pair of classes that can potentially communicate with each other via a switch. This is called the *class-switching mask* and it is automatically computed. The boolean matrix returned by the model.getClassSwitchingMask function provides this mask, which has entry in row r and column s set to true only if jobs in class r can switch into class s at some node in the network.

Class switching with non-probabilistic routing strategies

In the presence of non-probabilistic routing strategies, one needs to specify more details of the class switching mechanism. This can be done through addition to the network topology of ClassSwitch elements. The constructor of this node requires to specify a probability matrix C such that C(r,s) is the probability that a job of class r arriving into the ClassSwitch switches to class s during the visit. For example, in a 2-class model the following node will switch all visiting jobs into class s

```
C = [0, 1; 0, 1];
node = ClassSwitch(model, 'CSNode', C);
```

Note that for a network with M stations, up to M^2 ClassSwitch elements may be required to implement class-switching across all possible links, including self-loops. Moreover, refreshing network parameters under non-probabilistic routing strategies may .

Contrary to the link function, one cannot specify in the argument to setProbRouting a class switching probability. The setProbRouting function should instead be used to route the job through an appropriate ClassSwitch element.

Routing probabilities for Source and Sink nodes

In the presence of open classes, and in mixed models with both open and closed classes, one needs only to specify the routing probabilities *out* of the source. The probabilities out of the sink can all be set to zero for all classes and destinations (including self-loops). The solver will take care of adjusting these inputs to create a valid routing table.

Cache-based class-switching

Upon cache hit or cache miss, a job in transit is switched to a user-specified class, as specified by the setHitClass and setMissClass, so that it can be routed to a different destination based on wether it found the item in the cache or not. The setRead function allows the user to specify a discrete distribution (e.g., Zipf, DiscreteSampler) for the frequency at which an item is requested. For example,

```
refModel = Zipf(0.5, nitems);
cacheNode.setRead(initClass, refModel);
cacheNode.setHitClass(initClass, hitClass);
cacheNode.setMissClass(initClass, missClass);
```

Here initClass, hitClass, and missClass can be either open or closed instantiated as usual with the OpenClass or ClosedClass constructors.

Reference station

Before we have shown that the specification of classes requires to choose a reference station. In LINE, reference stations are properties of chains, thus if two closed classes belong to the same chain they must have the same reference station. This avoids ambiguities in the definition of the completion point for jobs within a chain.

For example, the system throughput for a chain is defined as sum of the arrival rates at the reference station for all classes in that chain. That is, the solver counts a return to the reference station as a completion of the visit to the system. In the case of open chains, the reference station is always the Source and the system throughput corresponds to the rate at which jobs arrive to the sink Sink, which may be seen as the arrival rate seen by the infinite pool of jobs in the external world. If there is no class switching, each chain contain a single class, thus per-chain and per-class performance indexes will be identical.

Tandem and cyclic topologies

Tandem networks are open queueing networks with a serial topology. LINE provides functions that ease the definition of tandem networks of stations with exponential service times. For example, we can rapidly instantiate a tandem network consisting of stations with PS and INF scheduling as follows

```
lambda = [10,20]; % lambda(r) - arrival rate of class r
D = [11,12; 21,22]; % D(i,r) - class-r demand at station i (PS)
Z = [91,92; 93,94]; % Z(i,r) - class-r demand at station i (INF)
modelPsInf = Network.tandemPsInf(lambda,D,Z)
```

The above snippet instantiates an open network with two queueing stations (PS), two delay stations (INF), and exponential distributions with the given inter-arrival rates and mean service times. The Network.tandemPs, Network.tandemFcfs, and Network.tandemFcfsInf functions provide static constructors for networks with other combinations of scheduling policies, namely only PS, only FCFS, or FCFS and INF.

A tandem network with closed classes is instead called a cyclic network. Similar to tandem networks, LINE offers a set of static constructors: Network.cyclicPs, Network.cyclicPsInf, Network.cyclicFcfs, and Network.cyclicFcfsInf. These functions only require to replace the arrival rate vector A by a vector N specifying the job populations for each of the closed classes, e.g.,

```
N = [10,20]; % N(r) - closed population in class r
D = [11,12; 21,22]; % D(i,r) - class-r demand at station i (PS)
modelPsInf = Network.cyclicPs(N,D)
```

3.1.5 Finite buffers

The functions setCapacity and setChainCapacity of the Station class are used to place constraints on the number of jobs, total or for each chain, that can reside within a station. Note that LINE does not allow one to specify buffer constraints at the level of individual classes, unless chains contain a single class, in which case setChainCapacity is sufficient for the purpose.

For example,

```
example_closedModel_3
delay.setChainCapacity([1,1])
model.refreshCapacity()
```

creates an example model with two chains and three classes (specified in example_closedModel_3.m) and requires the second station to accept a maximum of one job in each chain. Note that if we were to ask for a higher capacity, such as setChainCapacity([1,7]), which exceeds the total job population in chain 2, LINE would have automatically reduced the value 7 to the chain 2 job population (2). This automatic correction ensures that functions that analyze the state space of the model do not generate unreachable states.

The refreshCapacity function updates the buffer parameterizations, performing appropriate sanity checks. Since example_closedModel_3 has already invoked a solver prior to our changes, the requested modifications are materially applied by LINE to the network only after calling an appropriate refreshStruct function, see the sensitivity analysis section. If the buffer capacity changes were made before the first solver invocation on the model, then there would not be need for a refreshCapacity call, since the internal representation of the Network object used by the solvers is still to be created.

3.1.6 Service and inter-arrival time processes

A number of statistical distributions are available to specify job service times at the stations and inter-arrival times from the Source station. The class PhaseType offers distributions that are analytically tractable, which are defined upon certain absorbing Markov chains consisting of one or more states (*phases*) that are called phase-type distributions. They include as special case the following distributions supported in LINE, along with their respective constructors:

• Exponential distribution: $Exp(\lambda)$, where λ is the rate of the exponential

- n-phase Erlang distribution: Erlang (α, n) , where α is the rate of each of the n exponential phases
- 2-phase hyper-exponential distribution: HyperExp $(p, \lambda_1, \lambda_2)$, that returns an exponential with rate λ_1 with probability p, and an exponential with rate λ_2 otherwise.
- *n*-phase hyper-exponential distribution: HyperExp (p, λ) , that builds a *n*-phase hyper-exponential from the rate vector $\lambda = [\lambda_1, \dots, \lambda_n]$ and the phase selection probabilities $p = [p_1, \dots, p_n]$.
- 2-phase Coxian distribution: Coxian(μ_1, μ_2, ϕ_1), which assigns rates μ_1 and μ_2 to the two rates, and completion probability from phase 1 equal to ϕ_1 (the probability from phase 2 is $\phi_2 = 1.0$).
- n-phase Coxian distribution: $Coxian(\mu, \phi)$, which builds an arbitrary Coxian distribution from a vector $\mu = [\mu_1, \dots, \mu_n]$ of n rates and a completion probability vector $\phi = [\phi_1, \dots, \phi_n]$ with $\phi_n = 1.0$.
- n-phase acyclic phase-type distribution: $APH(\alpha, T)$, which defines an acyclic phase-type distribution with initial probability vector $\alpha = [\alpha_1, \dots, \alpha_n]$ and transient generator T.

For example, given mean $\mu = 0.2$ and squared coefficient of variation SCV=10, where SCV=variance/ μ^2 , we can assign to a node a 2-phase Coxian service time distribution with these moments as

```
queue.setService(class2, Cox2.fitMeanAndSCV(0.2,10));
```

where Cox2 is a static class to help fitting 2-phase Coxian distributions. Inter-arrival time distributions can be instantiated in a similar way, using setArrival instead of setService on the Source node. For example, if the Source is node 3 we may assign the inter-arrival times of class 2 to be exponential with mean 0.1 as follows

```
source.setArrival(class2, Exp.fitMeanAndSCV(0.1));
```

where we have used a single parameter in fitMeanAndSCV since the exponential distribution does not allow to choose the SCV.

Non-Markovian distributions are also available, but typically they restrict the available network analysis techniques to simulation. They include the following distributions:

- Deterministic distribution: $Det(\mu)$ assigns probability 1.0 to the value μ .
- Uniform distribution: Uniform(a, b) assigns uniform probability 1/(b-a) to the interval [a, b].
- Gamma distribution: Gamma (α, k) assigns a gamma density with shape α and scale k.
- Pareto distribution: Pareto(α, k) assigns a Pareto density with shape α and scale k.

Lastly, we discuss two special distributions. The Disabled distribution can be used to explicitly forbid a class to receive service at a station. This may be useful in models with sparse routing matrices, both to

ensure an efficient model solution and to debug the model specification. Performance metrics for disabled classes will be set to NaN.

Conversely, the Immediate class can be used to specify instantaneous service (zero service time). Typically, LINE solvers will replace zero service times with small positive values ($\varepsilon = 10^{-7}$).

Fitting a distribution

The fitMeanAndSCV function is available for all distributions that inherit from the PhaseType class. This function provides exact or approximate matching of the requested moments, depending on the theoretical constraints imposed by the distribution. For example, an Erlang distribution with SCV=0.75 does not exist, because in a n-phase Erlang it must be SCV=1/n. In a case like this, Erlang.fitMeanAndSCV (1, 0.75) will return the closest approximation, e.g., a 2-phase Erlang (SCV=0.5) with unit mean. The Erlang distribution also offer a function fitMeanAndOrder(μ , n), which instantiates a n-phase Erlang with given mean μ .

In distributions that are uniquely determined by more than two moments, fitMeanAndSCV chooses a particular assignment of the residual degrees of freedom other than mean and SCV. For example, HyperExp depends on three parameters, therefore it is insufficient to specify mean and SCV to identify the distribution. Thus, HyperExp.fitMeanAndSCV automatically chooses to return a probability of selecting phase 1 equal to 0.99, as this spends the degree of freedom corresponding to the (unspecified) third moment of the distribution. Compared to other choices, this particular assignment corresponds to an higher probability mass in the tail of the distribution.

Inspecting and sampling a distribution

To verify that the fitted distribution has the expected mean and SCV it is possible to use the getMean and getSCV functions, e.g.,

```
>> dist = Exp(1);
>> dist.getMean
ans =
          1
>> dist.getSCV
ans =
          1
```

Moreover, the sample function can be used to generate values from the obtained distribution, e.g. we can generate 3 samples as

```
>> dist.sample(3)
ans =
0.2049
0.0989
2.0637
```

The evalCDF and evalCDFInterval functions return the cumulative distribution function at the specified point or within a range, e.g.,

```
>> dist.evalCDFInterval(2,5)
ans =
     0.1286
>> dist.evalCDF(5)-dist.evalCDF(2)
ans =
     0.1286
```

For more advanced uses, the distributions of the PhaseType class also offer the possibility to obtain the standard (D_0, D_1) representation used in the theory of Markovian arrival processes by means of the getRenewalProcess function. The result will be a cell array where element k+1 corresponds to matrix D_k .

Temporal dependent processes

It is sometimes useful to specify the statistical properties of a *time series* of service or inter-arrival times, as in the case of systems with short- and long-range dependent workloads. When the model is stochastic, we refer to these as situations where one specifies a *process*, as opposed to only specifying the *distribution* of the service or inter-arrival times. In LINE processes inherit from the PointProcess class, and include the 2-state Markov-modulated Poisson process (MMPP2) and empirical traces read from files (Replayer).

In particular, LINE assumes that empirical traces are supplied as text files (ASCII), formatted as a column of numbers. Once specified, the Replayer object can be used as any other distribution. This means that it is possible to run a simulation of the model with the specified trace. However, analytical solvers will require tractable distributions from the PhaseType class.

Scheduling parameters

Upon setting service distributions at a station, one may also specify scheduling parameters such as weights as additional arguments to the setService function. For example, if the node implements discriminatory processor sharing (SchedStrategy.DPS), the command

```
queue.setService(class2, Cox2.fitMeanAndSCV(0.2,10), 5.0);
```

assigns a weight 5.0 to jobs in class 2. The default weight of a class is 1.0.

3.1.7 Debugging and visualization

JSIMgraph is the graphical simulation environment of the JMT suite. LINE can export models to this environment for visualization purposes using the command

```
model.jsimgView
```




Figure 3.1: jsimgView function

An example is shown in Figure 3.1 below. Using a related function, <code>jsimwView</code>, it is also possible to export the model to the JSIMwiz environment, which offers a wizard-based interface.

Another way to debug a LINE model is to transforming it into a MATLAB graph object, e.g.

```
G = model.getGraph();
plot(G, 'EdgeLabel', G.Edges.Weight, 'Layout', 'Layered')
```

plots a graph of the network topology in term of stations only. In a similar manner, the following variant of the same command shows the model in terms of nodes, which corresponds to the internal representation within LINE.

```
[~,H] = model.getGraph();
plot(H,'EdgeLabel',H.Edges.Weight,'Layout','Layered')
```

The next figures shows the difference between the two commands for an open queueing network with two classes and class-switching. Weights on the edges correspond to routing probabilities. In the station topology on the left, note that since the Sink node is not a station, departures to the Sink are drawn as returns to the Source. The node topology on the right, illustrates all nodes, including certain ClassSwitch nodes that are automatically added by LINE to apply the class-switching routing strategy. Double arcs between nodes indicate that both classes are routed to the destination.

Furthermore, the graph properties concisely summarize the key features of the network




Figure 3.2: getGraph function: station topology (left) and node topology (right) for a 2-class tandem queueing network with class-switching.

<pre>>> G.Nodes ans = 2x5 table Name</pre>	Туре	2	Sched	Jobs Cl	.osedClass1
Ivanic	1712	_	benea	0005 C1	0504014551
'Delay'	'Delay'	'inf'	5		
'Queue1'	'Queue'	'ps'	0	2	
>> G.Edges					
ans =					
3x4 table					
EndN	odes	Weight	Rate	Class	
'Delay'	'Delay'	0.7	1	'ClosedCla	nss1'
'Delay'	'Queue1'	0.3	1	'ClosedCla	ass1'
'Queue1'	'Delay'	1	0.5	'ClosedCla	ass1'

Here, Edge.Weight is the routing probability between the nodes, whereas Edge.Rate is the service rate of the source node.

3.2 Model import and export

LINE offers a number of scripts to import external models into Network object instances that can be analyzed through its solvers. The available scripts are as follows:

- JMT2LINE imports a JMT simulation model (.jsimg or .jsimw file) instance.
- PMIF2LINE imports a XML file containing a PMIF 1.0 model.

Both scripts require in input the filename and desired model name, and return a single output, e.g.,

```
qn = PMIF2LINE([pwd,'\\examples\\data\\PMIF\\pmif_example_closed.xml'],'Mod1')
```

where qn is an instance of the Network class.

Network object can be saved in binary .mat files using MATLAB's standard save command. However, it is also possible to export a textual script that will dynamically recreate the same Network object. For example,

```
example_closedModel_1; LINE2SCRIPT(model, 'script.m')
```

creates a new file script.m with code

```
model = Network('model');
queue = Delay(model, 'Delay');
delay = Queue(model, 'Queuel', SchedStrategy.PS);
delay.setNumServers(1);
class1 = ClosedClass(model, 'ClosedClass1', 5, queue, 0);
queue.setService(class1, Cox2.fitMeanAndSCV(1.000000,1.000000));
delay.setService(class1, Cox2.fitMeanAndSCV(2.000000,1.000000));
P = cell(1);
P{1,1} = [0.7 0.3;1 0];
model.link(P);
```

that is equivalent to the model specified in example_closedModel_1.m.

3.2.1 Creating a LINE model using JMT

Using the features presented in the previous section, one can create a model in JMT and automatically derive a corresponding LINE script from it. For instance, the following command performs the import and translation into a script, e.g.,

```
LINE2SCRIPT(JMT2LINE('myModel.jsimg'),'myModel.m')
```

transforms and save the given JSIMgraph model into a corresponding LINE model.

LINE also gives two static functions to inspect jsimg and jsimw files before conversion, i.e., SolverJMT.jsimgOpe and SolverJMT.jsimwOpen require as an input parameter only the JMT file name, e.g., 'myModel.jsimg'.

3.2.2 Supported JMT features

Table 3.2 lists the JSIMgraph/JSIMwiz model features supported by the JMT2LINE transformation. We indicate as "Fully" supported a feature that is supported in the import and such that the resulting model can be solved in Line using at least SolverJMT. A feature with "Partial" support implies that some core aspects of this feature available in JSIM are not available in Line.

A few notes are needed to clarify the entries with partial support:

JMT Feature	Support	Notes					
Distributions	Full	Deterministic, Exponential, Erlang, Gamma, Hyperexponential,					
		Coxian, Pareto, Uniform, Zero Service Time, Replayer					
Classes	Full	Open class, Closed class, Class priorities					
Metrics	Full	Number of customers, Residence Time, System Throughput, System					
		Response Time, Throughput, Throughput per sink, Utilization					
Nodes	Full	ClassSwitch, Delay, Queue, Router, Source					
Routing	Full	Random, Probabilities, Round Robin, Join the Shortest Queue					
Scheduling	Full	FCFS, HOL, LCFS, RAND, SJF, SEPT, LJF, LEPT, PS, DPS, GPS					
Distributions	Partial	Phase-Type					
Nodes	Partial	Fork, Join, Logger, Sink					
Distributions	No	Burst (General), Burst (MAP), Burst (MMPP2), Normal					
Nodes	No	Finite Capacity Region, Place, Scaler, Semaphore, Transition					
Routing	No	Shortest Response Time, Least Utilization, Fastest Service, Load De-					
		pendent					
Scheduling	No	Load Dependent					

Table 3.2: Supported JSIM features for automated model import and analysis

- LINE does not support general phase-type distributions, rather the most general supported class are acyclic phase-type (APH) distributions with an arbitrary number of phases. When a APH in LINE has 2 phases, then it is mapped to a JMT Phase-Type distribution; conversely, a *n*-phase APH in LINE will be mapped to a JMT Phase-Type distribution with *n* phases.
- Fork and Join are supported with their default policies. Advanced policies, such as partial joins or setting a distribution for the forked tasks on each output link, are not supported yet.
- the Logger is created automatically by LINE in certain methods (e.g., getCdfRespT), however it is not debugged yet for explicit inclusion by the user.
- a single Sink can be instantiated in a LINE model, whereas there is no such constraint in JMT.

Chapter 4

Analysis methods

4.1 Steady-state analysis

4.1.1 Station average performance

LINE decouples network specification from its solution, allowing to evaluate the same model with multiple solvers. Model analysis is carried out in LINE according to the following general steps:

Step 1: Definition of the model. This proceeds as explained in the previous chapters.

Step 2: Instantiation of the solver(s). A solver is an instance of the Solver class. LINE offers multiple solvers, which can be configured through a set of common and individual solver options. For example,

```
solver = SolverJMT(model);
```

returns a handle to a simulation-based solver based on JMT, configured with default options.

Step 3: Solution. Finally, this step solves the network and retrieves the concrete values for the performance indexes of interest. This may be done as follows, e.g.,

```
% QN(i,r): mean queue-length of class r at station i
QN = solver.getAvgQLen()
% UN(i,r): utilization of class r at station i
UN = solver.getAvgUtil()
% RN(i,r): mean response time of class r at station i (summed on visits)
RN = solver.getAvgRespT()
% TN(i,r): mean throughput of class r at station i
TN = solver.getAvgTput()
```

Alternatively, all the above metrics may be obtained in a single method call as

```
[QN,UN,RN,TN] = solver.getAvg()
```

In the methods above, LINE assigns station and class indexes (e.g., i, r) in order of creation in order of creation of the corresponding station and class objects. However, large models may be easier to debug by checking results using class and station names, as opposed to indexes. This can be done either by requesting LINE to build a table with the result

```
AvgTable = solver.getAvgTable()
```

which however tends to be a rather slow data structure to use in case of repeated invocations of the solver, or by indexing the matrices returned by getAvg using the model objects. That is, if the first instantiated node is queue with name 'MyQueue' and the second instantiated class is cclass with name 'MyClass', then the following commands are equivalent

```
QN(1,2)
QN(queue,cclass)
QN(model.getStationIndex('MyQueue'),model.getClassIndex('MyClass'))
```

Similar methods are defined to obtain aggregate performance metrics at chain level at each station, namely getAvgQLenChain for queue-lengths, getAvgUtilChain for utilizations, getAvgRespTChain for response times, getAvgTputChain for throughputs, and the getAvgChain method to obtain all the previous metrics.

4.1.2 Station response time distribution

SolverFluid supports the computation of response time distributions for individual classes through the getCdfRespT function. The function returns the response time distribution for every station and class. For example, the following code plots the cumulative distribution function at steady-state for class 1 jobs when they visit station 2:

```
solver = SolverFluid(model);
FC = solver.getCdfRespT();
plot(FC{2,1}(:,2),FC{2,1}(:,1)); xlabel('t'); ylabel('Pr(RespT<t)');</pre>
```

4.1.3 System average performance

LINE also allows users to analyze models for end-to-end performance indexes such a system throughput or system response time. However, in models with class switching the notion of system-wide metrics can be ambiguous. For example, consider a job that enters the network in one class and departs the network in another class. In this situation one may attribute system response time to either the arriving class or the departing one, or attempt to partition it proportionally to the time spent by the job within each class. In general, the right semantics depends on the aim of the study.

LINE tackles this issue by supporting only the computation of system performance indexes by chain, instead than by class. In this way, since a job switching from a class to another remains by definition in

the same chain, there is no ambiguity in attributing the system metrics to the chain. The solver functions getAvgSys and getAvgSysTable return system response time and system throughput per chain as observed: (i) upon arrival to the sink, for open classes; (ii) upon arrival to the reference station, for closed classes.

In some cases, it is possible that a chain visits multiple times the reference station before the job completes. This also affects the definition of the system averages, since in some applications one may want to avoid counting each visit as a completion of the visit to the system. In such cases, LINE allows to specify which classes of the chain can complete at the reference station. For example, in the code below we require that a job visits reference station 1 twice, in classes 1 and 2, but completes at the reference station only when arriving in class 2. Therefore, the system response time will be counted between successive passages in class 2.

```
class1 = ClosedClass(model, 'ClosedClass1', 1, queue, 0);
class2 = ClosedClass(model, 'ClosedClass2', 0, queue, 0);

class1.completes = false;

P = cell(2); % 2-classes model
P{1,1} = [0,1; 0,0]; % routing within class 1 (no switching)
P{1,2} = [0,0; 1,0]; % routing from class 1 into class 2
P{2,1} = [0,0; 1,0]; % routing within class 2 (no switching)
P{2,2} = [0,1; 0,0]; % routing from class 2 into class 2

model.link(P);
```

Note that LINE does not allow a chain to complete at heterogeneous stations, therefore the completes property of a class always refers to the reference station for the chain.

4.2 Specifying states

In some analyses it is important to specify the state of the network, for example to assign the initial position of the jobs in a transient analysis. We thus discuss the native support in LINE for state modeling.

4.2.1 Station states

We begin by explaining how to specify a state s_0 . State modelling is supported only for stations with scheduling policies that depend on the number of jobs running or waiting at the node. For example, it is not supported for shortest job first (SchedStrategy.SJF) scheduling, in which state depends on the service time samples for the jobs.

Suppose that the network has R classes and that service distributions are phase-type, i.e., that they inherit from PhaseType. Let K_r be the number of phases for the service distribution in class r at a given station. Then, we define three types of state variables:

- c_j : class of the job waiting in position $j \le b$ of the buffer, out of the b currently occupied positions. If b = 0, then the state vector is indicated with a single empty element $c_1 = 0$.
- n_r : total number of jobs of class r in the station
- b_r : total number of jobs of class r in the station's buffer
- s_{rk} : total number of jobs of class r running in phase k in the server

Here, by phase we mean the number of states of a distribution of class PhaseType. If the distribution is not Markovian, then there is a single phase. With these definitions, the table below illustrates how to specify in LINE a valid state for a station depending on its scheduling strategy. All state variables are non-negative integers. The SchedStrategy. EXT policy is used for the Source node, which may be seen as a special station with an infinite pool of jobs sitting in the buffer and a dedicated server for each class r=1,...,R.

14016 4.1.	State descriptors for Markovian scheduling	oncies
Sched. strategy	Station state vector	State condition
EXT	$[\text{Inf}, s_{11},, s_{1K_1},, s_{R1},, s_{RK_R}]$	$\sum_{k} s_{rk} = 1, \forall r$
FCFS, HOL, LCFS	$[c_b,, c_1, s_{11},, s_{1K_1},, s_{R1},, s_{RK_R}]$	$\sum_{r} \sum_{k} s_{rk} = 1$
SEPT, RAND	$[b_1,, b_R, s_{11},, s_{1K_1},, s_{R1},, s_{RK_R}]$	$\sum_{r} \sum_{k} s_{rk} = 1$
PS, DPS, GPS, INF	$[s_{11},,s_{1K_1},,s_{R1},,s_{RK_R}]$	None

Table 4.1: State descriptors for Markovian scheduling policies

States can be manually specified or enumerated automatically. LINE library functions for handling and generating states are as follows:

- State.fromMarginal: enumerates all states that have the same marginal state $[n_1, n_2, ..., n_R]$.
- State.fromMarginalAndRunning: restricts the output of State.fromMarginal to states with given number of running jobs, irrespectively of the service phase in which they currently run.
- State.fromMarginalAndStarted: restricts the output of State.fromMarginal to states with given number of running jobs, all assumed to be in service phase k=1.
- State.fromMarginalBounds: similar to State.fromMarginal, but produces valid states between given minimum and maximum of resident jobs.
- State.toMarginal: extracts statistics from a state, such as the total number of jobs in a given class that are running at the station in a certain phase.

Note that if a function call returns an empty state ([]), this should be interpreted as an indication that no valid state exists that meets the required criteria. Often, this is because the state supplied in input is invalid.

Example

We consider the example network in example_closedModel_4.m. We look at the state of station 3, which is a multi-server FCFS station. There are 4 classes all having exponential service times except class 2 that has Erlang-2 service times. We are interested to states with 2 running jobs in class 1 and 1 in class 2, and with 2 jobs, respectively of classes 3 and 4, waiting in the buffer. We can automatically generate this state space, which we store in the space variable, as:

Here, each row of space corresponds to a valid state. The argument [2,1,1,1] gives the number of jobs in the node for the 4 classes, while [2,1,0,0] gives the number of running jobs in each class. This station has four valid states, differing on whether the class-2 job runs in the first or in the second phase of the Erlang-2 and on the relative position of the jobs of class 3 and 4 in the waiting buffer.

To obtain states where the jobs have just started running, we can instead use

If we instead remove the specification of the running jobs, we can use State.fromMarginal to generate all possible combinations of states depending on the class and phase of the running jobs. In the example, this returns a space of 20 possible states.

```
>> space = State.fromMarginal(model, 3, [2, 1, 1, 1], [2, 1, 0, 0])
space =
   4
        3
   4
            2
                 0
                     1
                          0
                               0
        2
            2
                0
                     0
   4
                          1
                               0
   4
            1
                     0
        1
                1
                          1
   4
       1
           1
                0
                     1
                          1
                               0
   3
            2
       4
                1
                     0
                          0
                               0
   3
        4
           2
                0
                     1
                          0
   3
       2
           2
                0
                     0
                         0
                               1
   3
           1
                     0
       1
                1
                         0
                              1
   3
        1
           1
                0
                    1
                         0
           2
   2
       4
                0
                    0
                         1
                               0
   2
        3
            2
                0
                     0
                          0
                               1
   2
        1
            1
                 0
                     0
                          1
        4
                     0
```

	1	4	1	0	1	1	0
	1	3	1	1	0	0	1
	1	3	1	0	1	0	1
1	1	2	1	0	0	1	1
	1	1	0	1	0	1	1
	1	1	0	0	1	1	1

Assigning a state to a station

Given a single or multiple states, it is possible to assign the initial state to a station using the setState function on that station's object. To cope with multiple states, LINE offers the possibility to specify a prior probability on the initial states, so that if multiple states have a non-zero prior, then the solver will need to analyze the network from all those states and weight the results according to the prior probabilities. The default prior value assigned probability 1.0 to the *first* specified state. The functions setStatePrior and getStatePrior of the Station class can be used to check and change the prior probabilities for the supplied initial states.

4.2.2 Network states

A collection of states that are valid for each station is not necessarily valid for the network as a whole. For example, if the sum of jobs of a closed class exceeds the population of the class, then the network state would be invalid. To identify these situations, LINE requires to specify the initial state of a network using functions supplied by the Network class. These functions are initFromMarginal, initFromMarginalAndRunning, and initFromMarginalAndStarted. They require a matrix with elements n(i,r) specifying the total number of resident class-r jobs at node i and the latter two require a matrix s(i,r) with the number of running (or started) class-r jobs at node i. The user can also manually verify if the supplied network state is going to be valid using State.IsValid.

It is also possible to request LINE to automatically identify a valid initial state, which is done using the initDefault function available in the Network class. This is going to select a state where:

- no jobs in open classes are present in the network;
- jobs in closed classes all start at their reference stations;
- the server of reference stations are occupied in order of class id, i.e., jobs in the firstly created class are assigned to the server in phase 1, then spare servers are allocated to the second class in phase 1, and so forth;
- if the scheduling strategy requires it, jobs are ordered in the buffer by class, with the firstly created class at the head and the lastly created class at the tail of the buffer.

Lastly, the initFromAvgQLen is a wrapper for initFromMarginal to initialize the system as close as possible to the average steady-state distribution of the network. Since averages are typically not

integer-valued, this function rounds the average values to the nearest integer and adjusts the result to ensure feasibility of the initialization.

4.2.3 Initialization of transient classes

Because of class-switching, it is possible that a class r with a non-empty population at time t=0 becomes empty at some position time t'>t without ever being visited again by any job. LINE allows one to place jobs in transient classes and therefore it will not trigger an error in the presence of this situation. If a user wishes to prohibit the use of a class at a station, it is sufficient to specify that the corresponding service process uses the Disabled distribution.

Certain solvers may incur problems in identifying that a class is transient and in setting to zero its steady-state measures. For example, the JMT solver uses an heuristic whereby a class is considered transient if it has fewer events than jobs initially placed in the corresponding chain the class belongs to. For such classes, JMT will set the values of steady-state performance indexes to zero.

4.3 Transient analysis

So far, we have seen how to compute steady-state average performance indexes, which are given by

$$E[n] = \lim_{t \to +\infty} E[n(t)]$$

where n(t) is an arbitrary performance index, e.g., the queue-length of a given class at time t.

We now consider instead the computation of the quantity $E[n(t)|s_0]$, which is the transient average of the performance index, conditional on a given initial system state s_0 . Compared to n(t), this quantity averages the system state at time t across all possible evolutions of the system from state s_0 during the t time units, weighted by their probability. In other words, we observe all possible stochastic evolutions of the system from state s_0 for t time units, recording the final values of n(t) in each trajectory, and finally average the recorded values at time t to obtain $E[n(t)|s_0]$.

4.3.1 Computing transient averages

At present, LINE supports only transient computation of queue-lengths, throughputs and utilizations using the CTMC and FLUID solvers. Transient response times are not currently supported, as they do not always obey Little's law.

The computation of transient metrics proceeds similarly to the steady-state case. We first obtain the handles for transient averages:

```
[Qt,Ut,Tt] = model.getTranHandlers();
```

After solving the model, we will be able to retrieve *both* steady-state and transient averages as follows

```
[QNt,UNt,TNt] = solver{s}.getTranAvg(Qt,Ut,Tt)
plot(QNt{1,1}(:,2), QNt{1,1}(:,1))
```

The transient average queue-length at node i for class r is stored within QNt $\{i, r\}$.

Note that the above code does not show how to specify a maximum time t for the output time series. This can be done using the timespan field of the options, as described later in the solvers chapter.

4.3.2 First passage times into stations

When the model is in a transient, the average state seen upon arrival to a station changes over time. That is, in a transient, successive visits by a job may experience different response time distributions. The function getTranCdfRespT, implemented by SolverJMT offers the possibility to obtain this distribution given the initial state specified for the model. As time passes, this distribution will converge to the steady-state one computed by solvers equipped with the function getCdfRespT.

However, in some cases one prefers to replace the notion of response time distribution in transient by the one of *first passage time*, i.e., the distribution of the time to complete the *first visit* to the station under consideration. The function <code>getTranCdfFirstPassT</code> provides this distribution, assuming as initial state the one specified for the model, e.g., using <code>setState</code> or <code>initDefault</code>. This function is available only in <code>SolverFluid</code> and has a similar syntax as <code>getCdfRespT</code>.

4.4 Sensitivity analysis and numerical optimization

Frequently, performance and reliability analysis requires to change one or more model parameters to see the sensitivity of the results or to optimize some goal function. In order to do this efficiently, we discuss the internal representation of the Network objects used within the LINE solvers. By applying changes directly to this internal representation it is possible to considerably speed-up the sequential evaluation of several models.

4.4.1 Internal representation of the model structure

For efficiency reasons, once a user requests to solve a Network, LINE calls internally generates a static representation of the network structure using the refreshStruct function. This function returns a representation object that is then passed on to the chosen solver to parameterize the analysis.

The representation used within LINE is the NetworkStruct class, which describes an extended multiclass queueing network with class-switching and acyclic phase-type (APH) service times. APH generalizes known distributions such as Coxian, Erlang, Hyper-Exponential, and Exponential. The representation can be obtained as follows

```
qn = model.getStruct()
```

The table below presents the properties of the NetworkStruct class.

Table 4.2: NetworkStruct properties

Field	Type	Description
cap(i)	integer	Total capacity at station i
${\tt chains}(c,r)$	logical	true if class r is in chain c , or false otherwise
${ t classcap}(i,r)$	integer	Maximum buffer capacity available to class r at station i
${\tt classname}\{r\}$	string	Name of class r
${ t classprio}(r)$	integer	Priority of class r (0 = highest priority)
$\operatorname{csmask}(r,s)$	logical	true if class r can switch into class s at some node
isstation(i)	logical	true if node i is a station
isstateful(i)	logical	true if node i is a stateful node
$\mathrm{mu}\{i,r\}(k)$	double	Service or arrival rate in phase k for class r at station i , with $\max\{i,r\}=$ NaN if Disabled and $\max\{i,r\}=10^7$ if Immediate.
nchains	integer	Number of chains in the network
nclasses	integer	Number of classes in the network
nclosedjobs	integer	Total number of jobs in closed classes
njobs(r)	integer	Number of jobs in class r (Inf for open classes)
nnodes	integer	Number of nodes in the network
$ ext{nservers}(i)$	integer	Number of servers at station i
nstations	integer	Number of stations in the network
nstateful	integer	Number of stateful nodes in the network
$nodenames\{i\}$	string	Name of node i
$nodetypes\{i\}$	string	Type of node i (e.g., NodeType.Sink)
nvars	integer	Number of local state variables at stateful nodes
$\mathtt{phases}(i,r)$	integer	Number of phases for service process of class r at station i
$\mathtt{phasessz}(i,r)$	integer	Number of state vector elements used to describe phase
$ exttt{phaseshift}(i,r)$	integer	Position shift to read phase element in state
$\mathtt{ph}\{i,r\}$	cell	Matrix representation i of the class r service process at station i
$\mathtt{phi}\{i,r\}(k)$	double	Completion probability in phase k for class r at station i
rates(i,r)	double	Service rate of class r at station i (or arrival rate if i is a Source)
$\operatorname{refstat}(r)$	integer	Index of reference station for class r
$rt(idx_{ir},idx_{js})$	double	Probability of routing from stateful node i to j , switching class from r to s where, e.g., $idx_{ir} = (i-1)*$ nclasses $+ r$.
$rtnodes(idx_{ir},idx_{js})$	double	Same as rt , but i and j are nodes, not necessarily stateful ones.
rtfun(st1,st2)	matrix	State-dependent routing table given initial (st1) and final (st2) state cell arrays. Table entries defined as in rt.
$\operatorname{schedparam}(i,r)$	double	Parameter for class r strategy at station i
$\mathrm{sched}\{i\}$	cell	Scheduling strategy at station i (e.g., <code>SchedStrategy.PS</code>)
$ exttt{schedid}(i)$	integer	Scheduling strategy id at station i (e.g., SchedStrategy . ID_PS)
$\operatorname{sync}\{s\}$	struct	Data structure specifying a synchronization s among nodes
$\mathrm{scv}(i,r)$	double	Squared coefficient of variation of class r service times at station i (or interarrival times if station i is a Source)
$\operatorname{space}\{t\}$	integer	The t -th state in the state space (or a portion thereof). This field may be initially empty and updated by the solver during execution.
$state\{i\}$	integer	Current state of stateful node i . This field may be initially empty and updated by the solver during execution.
${\tt visits}\{c\}(i,r)$	double	Number of visits that a job in chain c pays to node i in class r
extstyle ext	double	Parameters for local variable instantiation at stateful node i

4.4.2 Fast parameter update

Successive invocations of getStruct() will return a cached copy of the NetworkStruct representation, unless the user has called model.refreshStruct() or model.reset() in-between the invocations. The refreshStruct function regenerates the internal representation, while reset destroys it, together with all other representations and cached results stored in the Network object. In the case of reset, the internal data structure will be regenerated at the next refreshStruct() or getStruct() call.

The performance cost of updating the representation can be significant, as some of the structure array field require a dedicated algorithm to compute. For example, finding the chains in the model requires an analysis of the weakly connected components of the network routing matrix. For this reason, the Network class provides several functions to selectively refresh only part of the NetworkStruct representation, once the modification has been applied to the objects (e.g., stations, classes, ...) used to define the network. These functions are as follows:

- refreshArrival: this function should be called after updating the inter-arrival distribution at a Source.
- refreshCapacity: this function should be called after changing buffer capacities, as it updates the capacity and classcapacity fields.
- refreshChains: this function should be used after changing the routing topology, as it refreshes the rt, chains, nchains, nchainjobs, and visits fields.
- refreshPriorities: this function updates class priorities in the classprio field.
- refreshScheduling: updates the sched, schedid, and schedparam fields.
- refreshService: updates the mu, phi, phases, rates and scv fields.

For example, suppose we wish to update the service time distribution for class-1 at node 1 to be exponential with unit rate. This can be done efficiently as follows:

```
queue.setService(class1, Exp(1.0));
model.refreshService;
```

4.4.3 Refreshing a network topology with non-probabilistic routing

The resetNetwork function should be used before changing a network topology with non-probabilistic routing. It will destroy by default all class switching nodes. This can be avoided if the function is called as, e.g., model.resetNetwork (false). The default behavior is though shown in the next example

```
>> model = Network('model');
node{1} = ClassSwitch(model,'CSNode',[0,1;0,1]);
node{2} = Queue(model, 'Queuel', SchedStrategy.FCFS);
>> model.getNodes
ans =
    2x1 cell array
    {1x1 ClassSwitch}
    {1x1 Queue}
>> model.resetNetwork
ans =
    1x1 cell array
    {1x1 Queue}
```

As shown, resetNetwork updates the station indexes and the revised list of nodes that compose the topology is obtained as a return parameter. To avoid stations to change index, one may simply create ClassSwitch nodes as last before solving the model. This node list can be employed as usual to reinstantiate new stations or ClassSwitch nodes. The addLink, setRouting, and possibly the setProbRouting functions will also need to be re-applied as described in the previous sections.

4.4.4 Saving a network object before a change

The Network object, and its inner objects that describe the network elements, are always passed by reference. The copy function should be used to clone LINE objects, for example before modifying a parameter for a sensitivity analysis. This function recursively clones all objects in the model, therefore creating an independent copy of the network. For example, consider the following code

```
modelByRef = model; modelByRef.setName('myModel1');
modelByCopy = model.copy; modelByCopy.setName('myModel2');
```

Using the getName function it is then possible to verify that model has now name 'myModell', since the first assignment was by reference. Conversely, modelByCopy.setName did not affect the original model since this is a clone of the original network.

Chapter 5

Network solvers

5.1 Overview

Solvers analyze objects of class Network to return average, transient, distributions, or state probability metrics. A solver can implement one or more *methods*, which although sharing a similar overall solution strategy, they can differ significantly from each other in the way this is actually implemented and on wether the final solution is exact or approximate.

The method field in the options structure array passed to a solver can be used to select the desired method, e.g., options.method='default' requires the solver to use default options, while options.method='exact' requires to solve the model exactly, if an exact solution method is available.

In what follows, we describe the general characteristics and supported model features for each solver available in LINE and their methods.

Available solvers

The following Network solvers are available within LINE 2.0.0-ALPHA:

- AUTO: This solver uses an algorithm to select the best solution method for the model under consideration, among those offered by the other solvers. Analytical solvers are always preferred to simulation-based solvers. This solver is implemented by the SolverAuto class.
- CTMC: This is a solver that returns the exact values of the performance metrics by explicit generation of the continuous-time Markov chain (CTMC) underpinning the model. As the CTMC typically incurs state-space explosion, this solver can successfully analyze only small models. The CTMC solver is the only method offered within LINE that can return an exact solution on all Markovian models, all other solvers are either approximate or are simulators. This solver is implemented by the SolverCTMC class.

- FLUID: This solver analyzes the model by means of an approximate fluid model, leveraging a representation of the queueing network as a system of ordinary differential equations (ODEs). The fluid model is approximate, but if the servers are all PS or INF, it can be shown to become exact in the limit where the number of users and the number of servers in each node grow to infinity [19]. This solver is implemented by the SolverFluid class.
- GEN This is a solver based on the theory of general open queueing systems such as M/G/1, G/M/1, and G/GI/1 queues. Because it supports general arrival and departure processes, it can be used also with non-Markovian distributions. This solver is implemented by the SolverGen class.
- JMT: This is a solver that uses a model-to-model transformation to export the LINE representation into a JMT simulation (JSIM) or analytical (JMVA) models [2]. The JSIM simulation solver can analyze also non-Markovian models, in particular those involving deterministic or Pareto distributions, or empirical traces. This solver is implemented by the SolverJMT class.
- MAM: This is a matrix-analytic method solver, which relies on quasi-birth death (QBD) processes to analyze open queueing systems. This solver is implemented by the SolverMAM class.
- MVA: This is a solver based on approximate and exact mean-value analysis. This solver is typically the fastest and offers very good accuracy in a number of situations, in particular models where stations have a single-server. This solver is implemented by the SolverMVA class.
- NC: This solver uses a combination of methods based on the normalizing constant of state probability to solve a model. The underpinning algorithm are particularly useful to compute marginal and joint state probabilities in queueing network models. This solver is implemented by the SolverNC class.
- SSA: This is a discrete-event simulator based on the CTMC representation of the model. Contrary to the JMT simulator, which has online estimators for all the performance metrics, SSA estimates only the probability distribution of the system states, indirectly deriving the metrics after the simulation is completed. Moreover, the SSA execution can more efficiently parallelized on multi-core machines. Moreover, it is possible to retrieve the evolution over time of each node state, including quantities that are not loggable in JMT, e.g., the active phase of a service or arrival distribution. This solver is implemented by the SolverSSA class.

5.2 Solution methods

We now describe the solution methods available within the Network solvers. Table 5.1 provides a global summary. Some of the listed methods (e.g., mg1) are not associated to a specific solver, as they do not fall in one of the reference formalisms. A solver that runs these methods can be instantiated as follows, e.g.:

```
>> solver = Solver.load('mg1', model);
>> solver.getAvgTable();
```

Note that the Solver.load notation can also be used to instantiate a custom solver pre-configured with the specified method. For example

```
>> solver = Solver.load('ctmc', model);
```

runs the CTMC solver with default options. Solver-specific methods can be specified by appending their name to the method option, e.g. this command creates the CTMC solver with qpu method enabled:

```
>> solver = Solver.load('ctmc.gpu', model);
```

5.2.1 AUTO

The SolverAuto class provides interfaces to the core solution functions (e.g., getAvg, ...) that dynamically bind to one of the other solvers implemented in LINE (CTMC, NC, ...). It is often not possible to identify the best solver without some performance results on the model, for example to determine if it operates in light, moderate, or heavy-load regime.

Therefore, heuristics are used to identify a solver based on structural properties of the model, such as based on the scheduling strategies used at the stations as well as the number of jobs, chains, and classes. Such heuristics, though, are independent of the core function called, thus it is possible that the optimal solver does not support the specific function called (e.g., getTranAvg). In such cases SolverAuto determines what other solvers would be feasible and prioritizes them in execution time order, with the fastest one on average having the higher priority. Eventually, the solver will be always able to identify a solution strategy, through at least simulation-based solvers such as JMT or SSA.

5.2.2 CTMC

The SolverCTMC class solves the model by first generating the infinitesimal generator of the Network and then calling an appropriate solver. Steady-state analysis is carried out by solving the global balance equations defined by the infinitesimal generator. If the keep option is set to true, the solver will save the infinitesimal generator in a temporary file and its location will be shown to the user.

Transient analysis is carried out by numerically solving Kolmogorov's forward equations using MAT-LAB's ODE solvers. The range of integration is controlled by the timespan option. The ODE solver choice is the same as for SolverFluid.

The CTMC solver heuristically limits the solution to models with no more than 6000 states. The force option needs to be set to true to bypass this control. In models with infinite states, such as networks with open classes, the cutoff option should be used to reduce the CTMC to a finite process. If specified as a scalar value, cutoff is the maximum number of jobs that a class can place at an arbitrary station. More generally, a matrix assignment of cutoff indicates to LINE that cutoff(i,r) is the maximum number of jobs of class r that can be placed at station i.

5.2.3 FLUID

This solver is based on the system of fluid ordinary differential equations for INF-PS queueing networks presented in [20].

The fluid ODEs are normally solved with the 'NonNegative' ODE solver option enabled. Four types of ODE solvers are used: fast or accurate, the former only if options.iter_tol> 10^{-3} , and stiff or non-stiff, depending on the value of options.stiff. The default choice of solver is stored in the following static functions:

- Solver.accurateStiffOdeSolver, set to MATLAB's ode15s.
- Solver.accurateOdeSolver, set to ode45.
- Solver.fastStiffOdeSolver, set to ode23s.
- Solver.fastOdeSolver, set to ode23.

ODE variables corresponding to an infinite number of jobs, as in the job pool of a source station, or to jobs in a disabled class are not included in the solution vector. These rules apply also to the <code>options.init_sol</code> vector.

The solution of models with FCFS stations maps these stations into corresponding PS stations where the service rates across classes are set identical to each other with a service distribution given by a mixture of the service processes of the service classes. The mixture weights are determined iteratively by solving a sequence of PS models until convergence. Upon initializing FCFS queues, jobs in the buffer are all initialized in the first phase of the service.

5.2.4 GEN

This is a solver for general open queueing systems such as M/G/1, G/M/1, G/GI/1, and several other types of queues. The solver default analysis method is the G/GI/1 approximation formula by Krämer and Langenbach-Belz [15].

5.2.5 JMT

The class is a wrapper for the JMT and consists of a model-to-model transformation from the <code>Network</code> data structure into the JMT's input XML formats (either <code>.jsimg</code> or <code>.jmva</code>) and a corresponding parser for JMT's results. Upon first invocation, the <code>JMT</code> JAR archive will be searched in the MATLAB path and if unavailable automatically downloaded.

This solver offers two main methods. The default method is the JSIM solver ('jsim' method), which runs JMT's discrete-event simulator. The alternative method is the JMVA analytical solver ('jmva' method), which is applicable only to queueing network models that admit a product-form solution. This can be verified calling model.hasProductFormSolution prior to running the JMVA solver.

In the transformation to JSIM, artificial nodes will be automatically added to the routing table to represent class-switching nodes used in the simulator to specify the switching rules. One such class-switching node is defined for every ordered pair of stations (i, j) such that jobs change class in transit from i to j.

5.2.6 MAM

This is a basic solver for some Markovian open queueing systems that can be analyzed using matrix analytic methods. The core solver is based on the BU tools library for matrix-analytic methods [14]. The solution of open queueing networks is based on traffic decomposition methods that compute the arrival process at each queue resulting from the superposition of multiple source streams.

5.2.7 MVA

The solver is primarily based on the Bard-Schweitzer approximate mean value analysis (AMVA) algorithm (options.method='default'), but also offers and implementation of the exact MVA algorithm (options.method='exact'). Non-exponential service times in FCFS nodes are treated using a M/G/1-type approximation. Multi-server FCFS is dealt with using a slight modification of the Rolia-Sevcik method [23]. DPS queues are analyzed with a time-scale separation method, so that for an incoming job of class r and weight w_r , classes with weight $w_s \geq 5w_r$ are replaced by high-priority classes that are analyzed using the standard MVA priority approximation. Conversely the remaining classes are treated by weighting the queue-length seen upon arrival in class $s \neq r$ by the correction factor w_s/w_r .

5.2.8 NC

The SolverNC class implements a family of solution algorithms based on the normalizing constant of state probability of product-form queueing networks. Contrary to the other solvers, this method typically maps the problem to certain multidimensional integrals, allowing the use of numerical methods such as MonteCarlo sampling and asymptotic expansions in their approximation.

5.2.9 SSA

The SolverSSA class is a basic stochastic simulator for continuous-time Markov chains. It reuses some of the methods that underpin SolverCTMC to generate the network state space and subsequently simulates the state dynamics by probabilistically choosing one among the possible events that can incur in the system, according to the state spaces of each of node in the network. For efficiency reasons, states are tracked at the level of individual stations, and hashed. The state space is not generated upfront, but rather stored during the simulation, starting from the initial state. If the initialization of a station generates multiple possible initial states, SSA initializes the model using the first state found. The list of initial states for each station can be obtained using the getInitState functions of the Network class.

The SSA solver offers four methods: 'serial' (default), 'serial.hash', 'para', and 'para.hash'. The serial methods run on a single core, while the parallel methods run on multicore via MATLAB's spmd

command. The 'hash' sub-option requires the solver to maintain in memory a hashed list of the node states, as opposed to the joint state vector for the system. As a result, the memory occupancy is lower, but the simulation tends to become slower on models with nodes that have large state spaces, due to the extra cost for hashing.

5.3 Supported language features and options

5.3.1 Solver features

Once a model is specified, it is possible to use the getUsedLangFeatures function to obtain a list of the features of a model. For example, the following conditional statement checks if the model contains a FCFS node

```
if (model.getUsedLangFeatures.list.SchedStrategy_FCFS)
...
```

Every LINE solver implements the support to check if it supports all language features used in a certain model

```
>> SolverJMT.supports(model)
ans =
  logical
  1
```

It is possible to programmatically check which solvers are available for a given model as follows

In the example, SolverMAM is not feasible for the considered model and therefore not returned. Note that SolverAuto is never included in the list returned by this methods since this is a wrapper for other solvers.

5.3.2 Class functions

The table below lists the steady-state and transient analysis functions implemented by the Network solvers. Since the features of the AUTO solver are the union of the features of the other solvers, in what follows it will be omitted from the description.

The functions listed above with the Table suffix (e.g., getAvgTable) provide results in tabular format corresponding to the corresponding core function (e.g., getAvg). The features of the core functions are as follows:

- getAvg: returns the mean queue-length, utilization, mean response time (for one visit), and throughput for each station and class.
- getAvgChain: returns the mean queue-length, utilization, mean response time (for one visit), and throughput for every station and chain.
- getAvgSys: returns the system response time and system throughput, as seen as the reference node, by chain.
- getCdfRespT: returns the distribution of response times (for one visit) for the stations at steadystate.
- getAvgNode: behaves similarly to getAvg, but returns performance metrics for each node and class. For example, throughputs at the sinks can be obtained with this method.
- getProb: returns state probabilities at equilibrium at a given station.
- getProbAggr: returns marginal state probabilities for jobs of different classes at a given station.
- getProbSys: returns joint probabilities for a given system state.
- getProbSysAggr: returns joint probabilities for jobs of different classes at all stations.
- getTranAvg: returns transient mean queue length, utilization and throughput for every station and chain from a given initial state.
- getTranCdfPassT: returns the distribution of first passage times in transient regime.
- getTranCdfRespT: returns the distribution of response times in transient regime.
- sample: returns the transient marginal state for a station from a given initial state.
- sampleAggr: returns the transient marginal state for jobs of different classes at a given station from a given initial state.
- sampleSys: returns the transient marginal system state for a station from a given initial state.
- sampleSysAggr: returns the transient marginal system state for jobs of different classes at a given station from a given initial state.

5.3.3 Node types

The table below shows the node types supported by the different solvers. It should be noted that the FLUID solver is capable of handling Sink and Source nodes, but due to low accuracy when run on open models this feature is disabled in the current release.

5.3.4 Scheduling strategies

The table below shows the supported scheduling strategies within LINE queueing stations. Each strategy belongs to a policy class: preemptive resume (SchedStrategyType.PR), non-preemptive (SchedStrategyType.NP), non-preemptive priority (SchedStrategyType.NPPrio).

5.3.5 Statistical distributions

The table below summarizes the current level of support for arrival and service distributions within each solver. Replayer represents an empirical trace read from a file, which will be either replayed as-is by the JMT solver, or fitted automatically to a Cox by the other solvers. Note that JMT requires that the last row of the trace must be a number, *not* an empty row.

5.3.6 Solver options

Solver options are encoded in LINE in a structure array that is internally passed to the solution algorithms. This can be specified as an argument to the constructor of the solver. For example, the following two constructor invocations are identical

```
s = SolverJMT(model)
opt = SolverJMT.defaultOptions; s = SolverJMT(model, opt)
```

Modifiers to the default options can either be specified directly in the options data structure, or alternatively be specified as argument pairs to the constructor, i.e., the following two invocations are equivalent

```
s = SolverJMT(model, 'method', 'jmva')
opt = SolverJMT.defaultOptions; opt.method='jmva'; s = SolverJMT(model, opt)
```

Available solver options are as follows:

- cache (logical) if set to true the solver after the first invocation will return the same result upon subsequent calls, without solving again the model. This option is true by default. Caching can be bypassed using the refresh methods (see Section 4.4).
- config (struct) this is data structure to pass solver-specific configuration options to customize the execution of particular methods.
- cutoff (integer ≥ 1) requires to ignore states where stations have more than the specified number of jobs. This is a mandatory option to analyze open classes using the CTMC solver.
- force (logical) requires the solver to proceed with analyzing the model. This bypasses checks and therefore can result in the solver either failing or requiring an excessive amount of resources from the system.

- iter_max (integer ≥ 1) controls the maximum number of iterations that a solver can use, where applicable. If iter_max= n, this option forces the FLUID solver to compute the ODEs over the timespan $t \in [0, 10n/\mu^{\min}]$, where μ^{\min} is the slowest service rate in the model. For the MVA solver this option instead regulates the number of successive substitutions allowed in the fixed-point iteration.
- iter_tol (double) controls the numerical tolerance used to convergence of iterative methods. In the FLUID solver this option regulates both the absolute and relative tolerance of the ODE solver.
- init_sol (solver dependent) re-initializes iterative solvers with the given configuration of the solution variables. In the case of MVA, this is a matrix where element (i,j) is the mean queue-length at station i in class j. In the case of FLUID, this is a model-dependent vector with the values of all the variables used within the ODE system that underpins the fluid approximation.
- keep (logical) determines if the model-to-model transformations store on file their intermediate outputs. In particular, if verbose ≥ 1 then the location of the .jsimg models sent to JMT will be printed on screen.
- method (string) configures the internal algorithm used to solve the model.
- samples (integer \geq 1) controls the number of samples collected *for each* performance index by simulation-based solvers. JMT requires a minimum number of samples of $5 \cdot 10^3$ samples.
- seed (integer ≥ 1) controls the seed used by the pseudo-random number generators. For example, simulation-based solvers will give identical results across invocations only if called with the same seed.
- stiff (logical) requires the solver to use a stiff ODE solver.
- timestamp (real interval) requires the transient solver to produce a solution in the specified temporal range. If the value is set to [Inf, Inf] the solver will only return a steady-state solution. In the case of the FLUID solver and in simulation, [Inf, Inf] has the same computational cost of [0, Inf] therefore the latter is used as default.
- tol default numerical tolerance for all uses other than the ones where iter_tol is used.
- verbose controls the verbosity level of the solver. Supported levels are 0 for silent, 1 for standard verbosity, 2 for debugging.

5.4 Solver maintenance

The following best practices can be helpful in maintaining the LINE installation:

- To install a new release of JMT, it is necessary to delete the JMT.jar file under thr 'SolverJMT' folder. This forces LINE to download the latest version of the JMT executable.
- Periodically running the jmtCleanTempDir script can help removing temporary by-products of the JMT solver. This is strongly encouraged under repeated enabling of the 'keep' option, as this stores on disk the temporary models sent to JMT.

Table 5.1: Solution methods for Network solvers. Solver Method Description Refs.								
		Description						
CTMC	default	Solution based on global balance	[3, §2.1.2]					
CTMC	gpu	Solution based on global balance run on GPU if available	_					
FLUID	default	ODE-based mean field approximation	[20]					
GEN	gig1.allen	Allen-Cunneen formula for the GI/G/1 queue	[3, §6.3.4]					
GEN	gig1.heyman	Heyman formula for the GI/G/1 queue	_					
GEN	gig1.kingman	Kingman formula for the GI/G/1 queue	[3, §6.3.6]					
GEN	gig1.klb	Kramer-Langenbach-Belz formula for the GI/G/1 queue	[3, §6.3.4]					
GEN	gigl.kobayashi	Kobayashi diffusion approximation for the GI/G/1 queue	[3, §10.1.1]					
GEN	gig1.marchal	Marchal formula for the GI/G/1 queue	[3, §10.1.3]					
GEN	mg1	Pollaczek–Khinchine formula for the M/G/1 queue	[3, §3.3.1]					
GEN	mm1	Exact formula for the M/M/1 queue	[3, §6.2.1]					
JMT	default	Alias for the jsim method	_					
JMT	jmva	Alias for the jmva.mva method	_					
JMT	jmva.mva	Exact MVA in JMVA	[21]					
JMT	jmva.recal	Exact RECAL algorithm in JMVA	[9]					
JMT	jmva.comom	Exact CoMoM algorithm in JMVA	[4]					
JMT	jmva.amva	Approximate MVA, alias for jmva.bs.	_					
JMT	jmva.aql	AQL algorithm in JMVA	[26]					
JMT	jmva.bs	Bard-Schweitzer algorithm in JMVA	[3, §9.1.1]					
JMT	jmva.chow	Chow algorithm in JMVA	[8]					
JMT	jmva.dmlin	De Souza-Muntz Linearizer in JMVA	[10]					
JMT	jmva.lin	Linearizer algorithm in JMVA	[7]					
JMT	jmva.ls	Logistic sampling in JMVA	[5]					
JMT	jsim	Exact discrete-event simulation in JSIM	[2]					
MAM	default	Matrix-analytic solution of structured CTMCs	[14]					
MVA	default	Alias for the amva method	_					
MVA	amva	Bard-Schweitzer approximate MVA	[3, §9.1.1]					
MVA	exact	Alias for the mva method	_					
MVA	mva	Exact mean-value analysis (MVA)	[21]					
NC	default	Auto-select best method based on model features	_					
NC	exact	Alias for the ca method.	_					
NC	ca	Exact convolution algorithm	_					
NC	imci	Improved Monte carlo integration sampler	[24]					
NC	le	Logistic asymptotic expansion	[5]					
NC	ls	Logistic sampling	[5]					
NC	 pana	Panacea asymptotic expansion	[18], [22]					
NC	mmint	McKenna-Mitra numerical integration for 2-station models	[18]					
SSA	default	Alias for the serial method	_					
SSA	serial	CTMC stochastic simulation on a single core	[13]					
SSA	serial.hash	serial with state hashing (slower, but lower memory usage)	_					
SSA	para	Parallel simulations (independent replicas of serial sim.)	_					
SSA	para.hash	para with state hashing (slower, but lower memory usage)	_					

Table 5.2: Solver support for average performance metrics

	z. Server supp		, erage pe	Netwoi		er		
Function	Regime	CTMC	FLUID	JMT	MAM	MVA	NC	SSA
getAvg	Steady-state	✓	~	✓	✓	✓	✓	✓
getAvgTable	Steady-state	~	/	~	✓	~	~	✓
getAvgChain	Steady-state	~	/	~	✓	~	~	✓
getAvgChainTable	Steady-state	✓	/	~	✓	~	/	✓
getAvgNode	Steady-state	✓	/	~	✓	~	/	✓
getAvgNodeTable	Steady-state	~	/	~	✓	~	~	✓
getAvgSys	Steady-state	✓	✓	✓	✓	✓	~	✓
getAvgSysTable	Steady-state	✓	/	✓	✓	~	~	✓
getAvgArvR	Steady-state	✓	✓	✓	✓	✓	✓	✓
getAvgArvRChain	Steady-state	✓	✓	✓	✓	✓	✓	✓
getAvgQLen	Steady-state	✓	✓	✓	✓	✓	~	✓
getAvgQLenTable	Steady-state	✓	/	✓	✓	~	~	✓
getAvgQLenChain	Steady-state	✓	/	~	✓	~	~	✓
getAvgRespT	Steady-state	✓	~	✓	✓	~	~	✓
getAvgRespTTable	Steady-state	✓	/	~	✓	~	~	✓
getAvgRespTChain	Steady-state	✓	/	✓	✓	~	~	✓
getAvgSysRespT	Steady-state	✓	/	✓	✓	~	~	✓
getAvgTput	Steady-state	✓	✓	✓	✓	✓	~	✓
getAvgTputTable	Steady-state	✓	✓	✓	✓	✓	~	✓
getAvgTputChain	Steady-state	✓	~	✓	✓	✓	/	✓
getAvgSysTput	Steady-state	✓	~	✓	✓	~	✓	✓
getAvgUtil	Steady-state	✓	/	/	✓	/	/	✓
getAvgUtilTable	Steady-state	✓	/	/	✓	/	/	✓
getAvgUtilChain	Steady-state	✓	/	/	~	/	/	✓
getTranAvg	Transient	✓	✓	✓				

Table 5.3: Solver support for advanced metrics

				Netwoi	k Solve	er		
Function	Regime	CTMC	FLUID	JMT	MAM	MVA	NC	SSA
getCdfRespT	Steady-state		~	~	~			
getProb	Steady-state	✓						
getProbAggr	Steady-state	~	/	✓		~	~	
getProbSys	Steady-state	~						✓
getProbSysAggr	Steady-state	/		~			~	
getTranCdfPassT	Transient		~					
getTranCdfRespT	Transient			✓				
getTranProb	Transient	~						
getTranProbAggr	Transient	✓						
getTranProbSys	Transient	✓						
getTranProbSysAggr	Transient	~						
sample	Transient							✓
sampleAggr	Transient			/				✓
sampleSys	Transient							✓
sampleSysAggr	Transient			✓				✓

Table 5.4: Solver support for scheduling strategies

		Network Solver							
Strategy	CTMC	FLUID	JMT	MAM	MVA	NC	SSA		
Cache							/		
ClassSwitch	~	✓	~	~	~	~	✓		
Delay	/	✓	~	✓	~	~	✓		
Fork			~						
Join			~						
Queue	~	✓	~	~	~	~	✓		
Sink	/	Disabled	/	/	/	/	/		
Source	/	Disabled	✓	✓	/	/	✓		

Table 5.5: Solver support for scheduling strategies

			- 11	Netwoi	k Solve	er		
Strategy	Class	CTMC	FLUID	JMT	MAM	MVA	NC	SSA
FCFS	NP	~	✓	✓	~	~	✓	✓
INF	NP	~	✓	✓		✓	✓	/
RAND	NP	~		~		✓	/	✓
SEPT	NP	~		✓				✓
SJF	NP			✓				
HOL	NPPrio	✓		✓				/
PS	PR	~	✓	~		~	/	✓
DPS	PR	~	✓	✓		~		✓
GPS	PR	✓		✓				✓

Table 5.6: Solver support for statistical distributions

		Network Solver							
Distribution	CTMC	FLUID	JMT	MAM	MVA	NC	SSA		
APH	✓	✓	✓	✓	✓	✓	✓		
Coxian	✓	✓	✓	✓	✓	✓	✓		
Exp	✓	✓	✓	~	✓	✓	✓		
Erlang	✓	✓	✓	✓	✓	✓	✓		
HyperExp	✓	✓	✓	✓	✓	✓	✓		
Disabled	✓	✓	✓	✓	✓	✓	✓		
Det			✓						
Gamma			✓						
Pareto			✓						
Replayer			✓						
Uniform			✓						

71

Table 5.7: Default values of the LINE solver options and their default assignments

		Solver default											
Option	MVA	CTMC	FLUID	JMT	MAM	NC	SSA						
cache	true	true	true	true	true	true	true						
config													
cutoff		(no default)											
force	false	false	false	false	false	false	false						
keep				false									
init_sol	[]		[]										
iter_max	10^{3}		10										
iter_tol	10^{-6}		10^{-4}		10^{-4}								
method	'default'	'default'	'default'	'default'	'default'	'default'	'default'						
samples				10^{4}			10^{4}						
seed	rand	rand	rand	rand	rand	rand	rand						
stiff			true										
timespan		[Inf,Inf]	[0,Inf]	[0,Inf]		[Inf,Inf]	[0,Inf]						
tol		10^{-4}	10^{-4}										
verbose	1	1	1	1	1	1	1						

Chapter 6

Layered network models

In this chapter, we present the definition of the LayeredNetwork class, which encodes the support in LINE for layered queueing networks. These models are extended queueing networks where servers, in order to process jobs, can issue synchronous and asynchronous calls among each other. The topology of call dependencies makes it possible to partition the model into a set of layers, each consisting of a subset of the resources, which are then iterative solved in isolation after certain parameter updates until converging to a solution for the entire network.

6.1 LayeredNetwork object definition

6.1.1 Creating a layered network topology

A layered queueing network consists of four types of elements: processors, tasks, entries and activities. An entry is a class of service specified through a finite sequence of activities, and hosted by a task running on a (physical) processor. A task is typically a software queue that models access to the capacity of the underpinning processor. Activities model either service demands required at the underpinning processor, or calls to entries exposed by some remote tasks.

To create our first layered network, we instantiate a new model as

```
model = LayeredNetwork('myLayeredModel');
```

We now proceed to instantiate the static topology of processors, tasks and entries:

```
P1 = Processor(model, 'P1', 1, SchedStrategy.PS);

P2 = Processor(model, 'P2', 1, SchedStrategy.PS);

T1 = Task(model, 'T1', 5, SchedStrategy.REF).on(P1);

T2 = Task(model, 'T2', Inf, SchedStrategy.INF).on(P2);

E1 = Entry(model, 'E1').on(T1);

E2 = Entry(model, 'E2').on(T2);
```

Here, the on method specifies the associations between the elements, e.g., task T1 runs on processor P1, and accepts calls to entry E1. Furthermore, the multiplicity of T1 is 5, meaning that up to 5 calls can be simultaneously served by this element (i.e., 5 is the number of servers in the underpinning queueing system for T1).

Both processors and tasks can be associated to the standard LINE scheduling strategies. For instasnce, T2 will process incoming requests in parallel according as an infinite server node, . An exception is that SchedStrategy.REF should be used to denote the reference task (e.g. a node representing the clients of the models), which has a similar meaning to the reference node in the Network object.

6.1.2 Describing service times of entries

The service demands placed by an entry on the underpinning processor is described in terms of execution of one or more activities. Although in tools such as LQNS activities can be associated to either entries or tasks, LINE supports only the more general of the two options, i.e., the definition of activities of the level of tasks. In this case:

- Every task defines a collection of activities.
- Every entry needs to specify an initial activity where the execution of the entry starts (the activity is said to be "bound to the entry") and a final activity, which upon completion terminates the execution of the entry.

For example, we can associate an activity to each entry as follows:

```
A1 = Activity(model, 'A1', Exp(1.0)).on(T1).boundTo(E1).synchCall(E2,3.5);
A2 = Activity(model, 'A2', Exp(2.0)).on(T2).boundTo(E2).repliesTo(E2);
```

Here, A1 is a task activity for T1, acts as initial activity for E1, consumes an exponential distributed time on the processor underpinning T1, and requires on average 3.5 synchronous calls to E2 to complete. Each call to entry E2 is served by the activity A2, with a service time on the processor underneath T2 given by an exponential distribution with rate $\lambda = 2.0$.

At present, LINE 2.0.0-ALPHA supports only synchronous calls. Support for asynchronous calls is available in older versions, e.g. LINE 1.0.0. Extension of LINE 2.0.0-ALPHA to asynchronous calls

Activity graphs

Often, it is useful to structure the sequence of activities carried out by an entry in a graph. Currently, LINE supports this feature only for activities places in series. For example, we may replace the specification of the activities underpinning a call to E2 as

```
A20 = Activity(model, 'A20', Exp(1.0)).on(T2).boundTo(E2);
A21 = Activity(model, 'A21', Erlang.fitMeanAndOrder(1.0,2)).on(T2);
A22 = Activity(model, 'A22', Exp(1.0)).on(T2).repliesTo(E2);
T2.addPrecedence(ActivityPrecedence.Serial(A20, A21, A22));
```




Figure 6.1: LayeredNetwork.plot method

such that a call to E2 serially executes A20, A21, and A22 prior to replying. Here, A21 is chosen to be an Erlang distribution with given mean (1.0) and number of phases (2).

6.1.3 Debugging and visualization

The structure of a LayeredNetwork object can be graphically visualized as follows

```
plot(model)
```

An example of the result is shown in the next figure. The figure shows two processors (P1 and P2), two tasks (T1 and T2), and three entries (E1, E2, and E3) with their associated activities. Both dependencies and calls are both shown as directed arcs, with the edge weight on call arcs corresponding to the average number of calls to the target entry. For example, A1 calls E3 on average 2.0 times. As in the case of the Network class, the getGraph method can be called to inspect the structure of the LayeredNetwork object.

Lastly, the <code>jsimgView</code> and <code>jsimwView</code> methods can be used to visualize in JMT each layer. This can be done by first calling the <code>getLayers</code> method to obtain a cell array consisting of the <code>Network</code> objects, each one corresponding to a layer, and then invoking the <code>jsimgView</code> and <code>jsimwView</code> methods on the desired layer. This is discussed in more details in the next section.

6.2 Decomposition into layers

Layers are a form of decomposition where the influence of resources not explicitly represented in that layer is taken into account through an artificial delay station, placed in a closed loop to the resources [23]. This

artificial delay is used to model the inter-arrival time between calls from resources that belong to other layers.

6.2.1 Running a decomposition

The current version of LINE adopts SRVN-type layering [11], whereby a layer corresponds to one and only one resource, either a processor or a task. The only exception are reference tasks, which can only appear as clients to their processors. The <code>getLayers</code> method returns a cell array consisting of the <code>Network</code> objects corresponding to each layer

```
layers = model.getLayers()
```

Within each layer, classes are used to model the time a job spends in a given activity or call, with synchronous calls being modeled by classed with label including an arrow, e.g., 'AS1=>E3' is a closed class used represent synchronous calls from activity AS1 to entry E3. Artificial delays and reference nodes are modelled as a delay station named 'Clients', whereas the task or processor assigned to the layer is modelled as the other node in the layer.

6.2.2 Initialization and update

In general, the parameters of a layer will depend on the steady-state solution of an other layer, causing a cyclic dependence that can be broken only after the model is analyzed by a solver. In order to assign parameters within each layer prior to its solution, the LayeredNetwork class uses the initDefault method, which sets the value of the artificial delay to simple operational analysis bounds [17].

The layer parameterization depends on a subset of performance indexes stored in a param structure array within the LayeredNetwork class. After initialization, it is possible to update the layer parameterization for example as follows

```
layers = model.getLayers();
for l=1:model.getNumberOfLayers()
    AvgTableByLayer{1} = SolverMVA(layers{1}).getAvgTable;
end
model.updateParam(AvgTableByLayer);
model.refreshLayers;
```

Here, the refreshParam method updates the param structure array from a cell array of steady-state solutions for the Network objects in each layer. Subsequently, the refreshLayers method enacts the new parameterization across the Network objects in each layer.

6.3 Solvers

LINE offers two solvers for the solution of a LayeredNetwork model consisting in its own native solver (LN) and a wrapper (LQNS) to the LQNS solver [11]. The latter requires a distribution of LQNS to be available on the operating system command line.

The solution methods available for LayeredNetwork models are similar to those for Network objects. For example, the getAvgTable can be used to obtain a full set of mean performance indexes for the model, e.g.,

x6 tabl	e				
Node	NodeType	QLen	Util	RespT	Tput
'P1'	'Processor'	NaN	0.071429	NaN	NaN
'T1'	'Task'	0.28571	0.071429	NaN	0.071429
'E1'	'Entry'	0.28571	0.071429	4	0.071429
'A1'	'Activity'	0.28571	0.071429	4	0.071429
'P2'	'Processor'	NaN	0.21429	NaN	NaN
'T2'	'Task'	0.21429	0.21429	NaN	0.21429
'E2'	'Entry'	0.21429	0.21429	1	0.21429
'A2'	'Activity'	0.21429	0.21429	1	0.21429

Note that in the above table, some performance indexes are marked as NaN because they are not defined in a layered queueing network. Further, compared to the getAvgTable method in Network objects, LayeredNetwork do not have an explicit differentiation between stations and classes, since in a layer a task may either act as a server station or a client class.

The main challenge in solving layered queueing networks through analytical methods is that the parameterization of the artificial delays depends on the steady-state performance of the other layers, thus causing a cyclic dependence between input parameters and solutions across the layers. Depending on the solver in use, such issue can be addressed in a different way, but in general a decomposition into layers will remain parametric on a set of response times, throughputs and utilizations.

This issue can be resolved through solvers that, starting from an initial guess, cyclically analyze the layers and update their artificial delays on the basis of the results of these analyses. Both LN and LQNS implement this solution method. Normally, after a number of iterations the model converges to a steady-state solution, where the parameterization of the artificial delays does not change after additional iterations.

6.3.1 LQNS

The LQNS wrapper operates by first transforming the specification into a valid LQNS XML file. Subsequently, LQNS calls the solver and parses the results from disks in order to present them to the user in the appropriate LINE tables or vectors. The options.method can be used to configure the LQNS execution as follows:

- options.method='std' or 'lqns': LQNS analytical solver with default settings.
- options.method='exact': the solver will execute the standard LQNS analytical solver with the exact MVA method.
- options.method='srvn': LQNS analytical solver with SRVN layering.
- options.method='srvnexact': the solver will execute the standard LQNS analytical solver with SRVN layering and the exact MVA method.
- options.method='lqsim': LQSIM simulator, with simulation length specified via the samples field (i.e., with parameter -A options.samples, 0.95).

Upon invocation, the lqns or lqsim commands will be searched for in the system path. If they are unavailable, the termination of SolverLQNS will interrupt.

6.3.2 LN

The native LN solver iteratively applies the layer updates until convergence of the steady-state measures. Since updates are parametric on the solution of each layer, LN can apply any of the Network solvers described in the solvers chapter to the analysis of individual layers, as illustrated in the following example for the MVA solver

```
options = SolverLN.defaultOptions;
mvaopt = SolverMVA.defaultOptions;
SolverLN(model, @(layer) SolverMVA(layer, mvaopt), options).getAvgTable
```

Options parameters may also be omitted. The LN method converges when the maximum relative change of mean response times across layers from the last iteration is less than options.iter_tol.

6.4 Model import and export

A LayeredNetwork can be easily read from, or written to, a XML file based on the LQNS meta-model format¹. The read operation can be done using a static method of the LayeredNetwork class, i.e.,

```
model = LayeredNetwork.parseXML(filename)
```

Conversely, the write operation is invoked directly on the model object

```
model.writeXML(filename)
```

¹https://raw.githubusercontent.com/layeredqueuing/V5/master/xml/lqn.xsd

In both examples, filename is a string including both file name and its path.

Finally, we point out that it is possible to export a LQN in the legacy SRVN file format 2 by means of the writeSRVN (filename) function.

²http://www.sce.carleton.ca/rads/lqns/lqn-documentation/format.pdf

Chapter 7

Random environments

Systems modeled with LINE can be described as operating in an environment with a state that affects the way the system dynamics. To distinguish the states of the environment from the ones of the system within it, we shall refer to the former as the environment *stages*. In particular, LINE 2.0.0-ALPHA supports the definition of a class of random environments subject to three assumptions:

- The stage of the environment evolves independently of the state of the system.
- The dynamics of the environment stage can be described by a continuous-time Markov chain.
- The topology of the system is independent of the environment stage.

The above definitions are in particular appropriate to describe systems specified by input parameters (e.g., service rates, scheduling weights, etc) that change with the environment stage. For example, an environment with two stages, say normal load and peak load, may differ for the number of servers that are available in a queueing station, i.e., the system controller may add more servers during peak load. Upon a stage change in the environment, the model parameters will instantaneously change, and the system state reached during the previous stage will be used to initialize the system in the new stage.

Although in a number of cases the system performance may be similar to a weighted combination of the average performance in each stage, this is not true in general, especially if the system dynamic (i.e., the rate at which jobs arrive and get served) and the environment dynamic (i.e., the rate at which the environment changes active stage) have a similar magnitude [6].

7.1 Environment object definition

7.1.1 Specifying the environment transitions

To specify an environment, it is sufficient to define a cell array with entries describing the distribution of time before the environment jumps to a given target state. For example

```
env{1,1} = Exp(0);
env{1,2} = Exp(1);
env{2,1} = Exp(1);
env{2,2} = Exp(0);
```

describes an environment consisting of two stage, where the time before a transition to the other stage is exponential with unit rate. If we were to set instead

```
env{2,2} = Erlang.fitMeanAndOrder(1,2);
```

this would cause a race condition between two distributions in stage two: the exponential transition back to stage 1, and the Erlang-2 distributed transition with unit rate that remains in stage 2. The latter means that periodically the system will be re-initialized in stage 2, meaning that jobs in execution at a server are required all to restart execution.

In LINE, an environment is internally described by a Markov renewal process (MRP) with transition times belonging to the PhaseType class. A MRP is similar to a Markov chain, but state transitions are not restricted to be exponential. Although the time spent in each state of the MRP is not exponential, the MRP can be easily transformed into an equivalent continuous-time Markov chain (CTMC) to enable analysis, a task that LINE performs automatically. In the example above, the underpinning CTMC will therefore consider the distribution of the minimum between the exponential and the Erlang-2 distribution, in order to decide the next stage transition.

State space explosion may occur in the definition of an environment if the user specifies a large number of non-exponential transition. For example, a race condition among n Erlang-2 distribution translates at the level of the CTMC into a state space with 2^n states. In such situations, it is recommended to replace some of the distributions with exponential ones.

7.1.2 Specifying the system models

LINE places loose assumptions in the way the system should be described in each stage. It is just expected that the user supplies a model object, either a Network or a LayeredNetwork, in each stage, and that a transient analysis method is available in the chosen solver, a requirement fulfilled for example by SolverFluid.

However, we note that the model definition can be somewhat simplified if the user describes the system model in a separate MATLAB function, accepting the stage-specific parameters in input to the function. This enables reuse of the system topology across stages, while creating independent model objects. An example of this specification style is given in <code>example_randomEnvironment_1.m</code> under LINE's example folder.

7.2. SOLVERS 81

7.2 Solvers

The steady-state analysis of a system in a random environment is carried out in LINE using the blending method [6], which is an iterative algorithm leveraging the transient solution of the model. In essence, the model looks at the *average* state of the system at the instant of each stage transition, and upon restarting the system in the new stage re-initializes it from this average value. This algorithm is implemented in LINE by the SolverEnv class, which is described next.

7.2.1 ENV

The SolverEnv class applies the blending algorithm by iteratively carrying out a transient analysis of each system model in each environment stage, and probabilistically weighting the solution to extract the steady-state behavior of the system.

As in the transient analysis of Network objects, LINE does not supply a method to obtain mean response times, since Little's law does not hold in the transient regime. To obtain the mean queue-length, utilization and throughput of the system one can call as usual the getAvg method on the SolverEnv object, e.g.,

```
models = {model1, model2, model3, model4};
envSolver = SolverEnv(models, env, @SolverFluid,options);
[QN,UN,TN] = envSolver.getAvg()
```

Note that as model complexity grows, the number of iterations required by the blending algorithm to converge may grow large. In such cases, the options.iter_max option may be used to bound the maximum analysis time.

Bibliography

- [1] Simonetta Balsamo. Product form queueing networks. In Günter Haring, Christoph Lindemann, and Martin Reiser, editors, *Performance Evaluation: Origins and Directions*, volume 1769 of *Lecture Notes in Computer Science*, pages 377–401. Springer, 2000.
- [2] M. Bertoli, G. Casale, and G. Serazzi. The JMT simulator for performance evaluation of non-product-form queueing networks. In *Proc. of the 40th Annual Simulation Symposium (ANSS)*, pages 3–10, 2007.
- [3] G. Bolch, S. Greiner, H. de Meer, and K. S. Trivedi. *Queueing Networks and Markov Chains*. Wiley, 2006.
- [4] G. Casale. CoMoM: Efficient class-oriented evaluation of multiclass performance models. *IEEE Trans. on Software Engineering*, 35(2):162–177, 2009.
- [5] G. Casale. Accelerating performance inference over closed systems by asymptotic methods. In *Proc.* of ACM SIGMETRICS. ACM Press, 2017.
- [6] Giuliano Casale, Mirco Tribastone, and Peter G. Harrison. Blending randomness in closed queueing network models. *Perform. Eval.*, 82:15–38, 2014.
- [7] K. M. Chandy and D. Neuse. Linearizer: A heuristic algorithm for queuing network models of computing systems. *Comm. of the ACM*, 25(2):126–134, 1982.
- [8] We-Min Chow. Approximations for large scale closed queueing networks. *Perform. Eval*, 3(1):1–12, 1983.
- [9] A. E. Conway and N. D. Georganas. RECAL A new efficient algorithm for the exact analysis of multiple-chain closed queueing networks. *JACM*, 33(4):768–791, 1986.
- [10] Edmundo de Souza e Silva and Richard R. Muntz. A note on the computational cost of the linearizer algorithm for queueing networks. *IEEE Trans. Computers*, 39(6):840–842, 1990.
- [11] G. Franks, P. Maly, C. M. Woodside, D. C. Petriu, A. Hubbard, and M. Mroz. Layered Queueing Network Solver and Simulator User Manual, 2012.

BIBLIOGRAPHY 83

[12] Nicolas Gast and Benny Van Houdt. Transient and steady-state regime of a family of list-based cache replacement algorithms. *Queueing Syst*, 83(3-4):293–328, 2016.

- [13] Daniel T. Gillespie. Exact stochastic simulation of coupled chemical reactions. *J. Phys. Chem.*, 81(25):2340–2361, 1977.
- [14] G. Horváth and M. Telek. Butools 2: A rich toolbox for markovian performance evaluation. In *Proc. of VALUETOOLS*, pages 137–142, ICST, Brussels, Belgium, Belgium, 2017. ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering).
- [15] W. Krämer and M. Langenbach-Belz. Approximate formulae for general single server systems with singleand batch arrivals. *Angewandte informatik*, 9, 1978.
- [16] S. S. Lavenberg. A perspective on queueing models of computer performance. *Perform. Eval.*, 10(1):53–76, 1989.
- [17] E. D. Lazowska, J. Zahorjan, G. S. Graham, and K. C. Sevcik. *Quantitative System Performance*. Prentice-Hall, 1984.
- [18] J. McKenna and D. Mitra. Asymptotic expansions and integral representations of moments of queue lengths in closed markovian networks. *JACM*, 31(2):346–360, April 1984.
- [19] J. F. Pérez and G. Casale. Assessing SLA compliance from Palladio component models. In *Proceedings of the 2nd MICAS*, 2013.
- [20] J. F. Pérez and G. Casale. Line: Evaluating software applications in unreliable environments. *IEEE Transactions on Reliability*, 66(3):837–853, Sept 2017.
- [21] M. Reiser and S. Lavenberg. Mean-value analysis of closed multichain queuing networks. *Journal of the ACM*, 27:313–322, 1980.
- [22] T. G. Robertazzi. Computer Networks and Systems. Springer, 2000.
- [23] J. A. Rolia and K. C. Sevcik. The method of layers. *IEEE Transactions on Software Engineering*, 21(8):689–700, August 1995.
- [24] Weikun Wang, Giuliano Casale, and Charles A. Sutton. A bayesian approach to parameter inference in queueing networks. *ACM Trans. Model. Comput. Simul.*, 27(1):2:1–2:26, 2016.
- [25] Murray Woodside. *Tutorial Introduction to Layered Modeling of Software Performance*. Carleton University, February 2013.
- [26] J. Zahorjan, D. L. Eager, and H. M. Sweillam. Accuracy, speed, and convergence of approximate mean value analysis. *Perform. Eval.*, 8(4):255–270, 1988.

Appendix A

Examples

The table below lists the scripts available under the examples folder.

Table A.1: Examples

Example	Problem			
example_cdfRespT_1	Station response time distribution in a single-class single-job closed network			
example_cdfRespT_2	Station response time distribution in a multi-chain closed network			
example_cdfRespT_3	Station response time distribution in a multi-chain open network			
example_cdfRespT_4	Simulation-based station response time distribution analysis			
example_cdfRespT_5	Station response time distribution under increasing job populations			
example_closedModel_1	Solving a single-class exponential closed queueing network			
example_closedModel_2	Solving a closed queueing network with a multi-class FCFS station			
example_closedModel_3	Solving exactly a multi-chain product-form closed queueing network			
example_closedModel_4	Local state space generation for a station in a closed network			
example_closedModel_5	1-line exact MVA solution of a cyclic network of PS and INF stations			
example_closedModel_6	Closed network with round robin scheduling			
example_initState_1	Specifying an initial state and prior in a single class model.			
example_initState_2	Specifying an initial state and prior in a multiclass model.			
example_layeredModel_1	Analyze a layered network specified in a LQNS XML file			
example_layeredModel_2	Specifying and solving a basic layered network			
example_misc_1	Use of performance indexes handles			
example_misc_2	Update and refresh of service times			
example_misc_3	Parameterization of a discriminatory processor sharing (DPS) station			
example_misc_4	Automatic detection of solvers that cannot analyze the model			
example_forkJoin_1	A single class open fork-join network			
example_forkJoin_2	A multiclass open fork-join network			
example_forkJoin_3	A closed model with nested forks and joins			
example_forkJoin_4	An open model with a fork but without a join			
example_mixedModel_1	Solving a queueing network model with both closed and open classes			
example_openModel_1	Solving a queueing network model with open classes, scalar cutoff options			
example_openModel_2	1-line solution of a tandem network of PS and INF stations			
example_openModel_3	Solving a queueing network model with open classes, matrix cutoff options			
example_openModel_4	Trace-driven simulation of an M/M/1 queue			
example_randomEnvironment_1	Solving a model in a 2-stage random environment			
example_randomEnvironment_2	Solving a model in a 4-stage random environment			
example_stateProbabilities_1	Computing marginal state probabilities for a node			
example_stateProbabilities_2	Computing marginal state probabilities for a node under class-switching			
example_stateProbabilities_3	Computing joint state probabilities for the system			