

ELECTRIC FOOD-WASTE DISPOSER

Technical FAQ & Product Brochure — Partnership Reference Edition (Shihao Intelligent)

Executive Overview: This technical brochure aligns the engineering excellence and smart-sensing capabilities of Shihao Intelligent manufacturing platforms with the design-centric, high-efficiency premium standards of international market partners (the top brands in KR/JP). Utilizing high-temperature dehydration combined with intelligent automated crushing, this system converts raw domestic organic waste into sterile, low-volume, soil pre-fertilizers.

1. Core Product Functions & Smart Features

The Electric Food-Waste Disposer delivers an advanced premium appliance standard designed to slide effortlessly into modern residential kitchen spaces due to its optimized cubic layout. It addresses three primary domestic pain points: Efficient and quite operation, odor decomposition, and efficient low power-consumption.

Intelligent Dehydration & Grinding

The system achieves up to a **96%** volume reduction of common food-waste by high-temperature and forced airflow dehydration, meanwhile grinding through the self-developed fixed die-cast aluminum module and internal rotating blades. Operating at a quiet noise threshold of **≤45 dB (Max)(and even lower 35db with the latest model)**, it allows residential users to comfortably trigger the cycles overnight.

Odor Decomposition

High-temperature steam containing grease and odorous components is captured by a turbine exhaust fan inside the machine and transported to the activated carbon module for odor removal and purification.

Intelligent Sensing Technology

Equipped with dynamic integrated load and moisture feedback sensors, the machine continuously calculates the core volume of food scrap content. It dynamically regulates real-time power outputs and automated cycle run-times (e.g., ranging from 3 hours to 12 hours for a maximum of 5.5L), optimizing total electricity consumption profiles.

1. Technical Specifications

The manufacturing parameters of the 3L balanced capacity platform configurations:

Technical Parameter	Electric Kitchen Composter (3L)
Effective Capacity	2.0 Liters to 5.5 Liters
Rated Voltage & Frequency	100V–110V AC / 220V–240V AC (50/60Hz)
Rated Power Input	500W (@100V) / 550W (@110V–230V)
Drive Motor Architecture	Premium 24V DC Brushless Motor (Detachable clean structure of fan air duct)
Acoustic Emission Level	≤45 dB ≤35 dB (latest 5.5L)
Structural Dimensions	400 × 220 × 304 mm (Optimized Side-Slide)
Filter Core Operational Life	400 Active Process Hours (Removable Filter)
Core Internal Assemblies	Removable Dishwasher-Safe Bucket; Washable Air Ducts

2. Product Installation, Operation & Processing

Q: What specific home organic waste profiles can the system process efficiently?

A: The machine safely handles standard table scraps, vegetable residues, organic plant food matter, soft fruit residuals, eggshells, bread, meat trimmings, soft poultry/chicken bone structures, fish cartilage, and grain inputs.

Q: Can you dispose of any kind of waste?

A: 90% of food waste, like fruits, vegetables, eggshells, breads, leftover meat scraps, and even pet foods, chicken bones can be dehydrated and ground.

Q: What items are strictly put into prevent blade damage or mechanical jamming?

A: Hard non-organic structures such as beef/pork leg bones, thick oyster shells, clam shells, metallic objects, plastic wrappers, glass particles, high-viscosity synthetic rubbers, or concentrated volatile cooking oils cannot be introduced into the internal bucket chamber.

Q: What's the reduction rate of the food waste?

A: It reduces food waste to 96%! (according to the internal testing and the customers' feedback).

Q: How long does each round of work take to process food waste?

A: The processing time varies from 3-12 hours (abt 4 hours for 3.8L), depending on the type, quantity, condition, and moisture content of the food waste. It is equipped with dynamic integrated load and moisture feedback sensors; the machine continuously calculates the core volume of food scrap content. It dynamically regulates real-time power outputs and automated cycle run-times, optimizing total electricity consumption profiles.

Q: What's the power consumption of the food-waste disposer?

A: The maximum power of the whole machine is 550W, and the average power during the whole working period is about 150W.

Q: I'd like to use it as fertilizer for my home garden. How should I go about doing that?

A: When reusing dried waste as fertilizer, it needs to be mixed with soil and allowed to mature for several months.

Q: How should high-sugar fruit contents be added?

A: High-Sugar Fruits: High-fructose scraps can caramelize under heat. Mix them with standard leafy vegetable scraps to maintain proper consistency.

Q: Can the processed dry residual compound be applied straight to the garden soil matrix structures?

A: No, the immediate output is highly concentrated dehydrated organic matter. To use it as an effective fertilizer, mix it thoroughly with standard yard soil at a 1:3 ratio and let it mature for several weeks. This allows natural microbes to break it down safely without burning plant roots.

Q: How often should activated carbon be replaced?

A: Removable Filter at a modular design, easy to replace. Activated carbon service life is 400 hours; it can be replaced by the indicator reminder.

Q: How long is the product warranty period?

A: 1 year for the disposer unit, 2 years for the Core Components of the Motor & Circuit Board, and consumable parts of the Activated Carbon are excluded.

Q: What capacity sizes of garbage disposers do you offer as an option?

A: Now, we have over 20+ SKUs available for customers' option, and the capacity size is from 2L to 5.5L.

Q: OEM/ODM/Private Label supported?

A: Yes, your brand will be printed or labeled on the products and the packaging box. Our R&D team is capable of supporting ODM/OEM, and the new design and development/co-development of the new model is welcomed as a new project development.

Please feel free to write for further information, jocelyn.zhou@foodcycler-manufacturer.top