

Package ‘cloudml’

June 12, 2018

Title Interface to the Google Cloud Machine Learning Platform

Version 0.5.1

Description Interface to the Google Cloud Machine Learning Platform
<<https://cloud.google.com/ml-engine>>, which provides cloud tools for training machine learning models.

Depends R (>= 3.3.0), tfruns (>= 1.3)

Imports jsonlite, packrat, processx, rprojroot, rstudioapi, tools,
utils, withr, yaml

Suggests tensorflow (>= 1.4.2), keras (>= 2.1.2), knitr, testthat

License Apache License 2.0

SystemRequirements Python (>= 2.7.0)

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

VignetteBuilder knitr

NeedsCompilation no

Author Javier Luraschi [aut, cre],
JJ Allaire [aut],
Kevin Ushey [aut],
RStudio [cph]

Maintainer Javier Luraschi <javier@rstudio.com>

Repository CRAN

Date/Publication 2018-06-12 14:05:22 UTC

R topics documented:

cloudml_deploy	2
cloudml_predict	3
cloudml_train	3
gcloud_init	4

gcloud_install	5
gcloud_terminal	5
gs_copy	6
gs_local_dir	6
gs_rsync	7
job_cancel	8
job_collect	8
job_list	9
job_status	10
job_stream_logs	10
job_trials	11

Index	12
--------------	-----------

cloudml_deploy	<i>Deploy SavedModel to CloudML</i>
----------------	-------------------------------------

Description

Deploys a SavedModel to CloudML model for online predictions.

Usage

```
cloudml_deploy(export_dir_base, name, version = paste0(name, "_1"),
               region = NULL, config = NULL)
```

Arguments

export_dir_base	A string containing a directory containing an exported SavedModels. Consider using tensorflow::export_savedmodel() to export this SavedModel.
name	The name for this model (required)
version	The version for this model. Versions start with a letter and contain only letters, numbers and underscores. Defaults to name_1
region	The region to be used to deploy this model.
config	A list, YAML or JSON configuration file as described https://cloud.google.com/ml-engine/reference/rest/v1/projects.jobs .

See Also

[cloudml_predict\(\)](#)

Other CloudML functions: [cloudml_predict](#), [cloudml_train](#)

cloudml_predict	<i>Perform Prediction over a CloudML Model.</i>
-----------------	---

Description

Perform online prediction over a CloudML model, usually, created using [cloudml_deploy\(\)](#)

Usage

```
cloudml_predict(instances, name, version = paste0(name, "_1"),  
               verbose = FALSE)
```

Arguments

instances	A list of instances to be predicted. While predicting a single instance, list wrapping this single instance is still expected.
name	The name for this model (required)
version	The version for this model. Versions start with a letter and contain only letters, numbers and underscores. Defaults to name_1
verbose	Should additional information be reported?

See Also

[cloudml_deploy\(\)](#)

Other CloudML functions: [cloudml_deploy](#), [cloudml_train](#)

cloudml_train	<i>Train a model using Cloud ML</i>
---------------	-------------------------------------

Description

Upload a TensorFlow application to Google Cloud, and use that application to train a model.

Usage

```
cloudml_train(file = "train.R", master_type = NULL, flags = NULL,  
             region = NULL, config = NULL, collect = "ask", dry_run = FALSE)
```

Arguments

file	File to be used as endpoint for training.
master_type	Training master node machine type. "standard" provides a basic machine configuration suitable for training simple models with small to moderate datasets. See the documentation at https://cloud.google.com/ml-engine/docs/tensorflow/machine-types#machine_type_table for details on available machine types.
flags	Named list with flag values (see flags()) or path to YAML file containing flag values.
region	The region to be used for training.
config	A list, YAML or JSON configuration file as described https://cloud.google.com/ml-engine/reference/rest/v1/projects.jobs .
collect	Logical. If TRUE, collect job when training is completed (blocks waiting for the job to complete). The default ("ask") will interactively prompt the user whether to collect the results or not.
dry_run	Triggers a local dry run over the deployment phase to validate packages and packing work as expected.

See Also

[job_status\(\)](#), [job_collect\(\)](#), [job_cancel\(\)](#)

Other CloudML functions: [cloudml_deploy](#), [cloudml_predict](#)

Examples

```
## Not run:
library(cloudml)

gcloud_install()
job <- cloudml_train("train.R")

## End(Not run)
```

gcloud_init

Initialize the Google Cloud SDK

Description

Initialize the Google Cloud SDK

Usage

```
gcloud_init()
```

See Also

Other Google Cloud SDK functions: [gcloud_install](#), [gcloud_terminal](#)

gcloud_install	<i>Install the Google Cloud SDK</i>
----------------	-------------------------------------

Description

Installs the Google Cloud SDK which enables CloudML operations.

Usage

```
gcloud_install(update = TRUE)
```

Arguments

update	Attempt to update an existing installation.
--------	---

See Also

Other Google Cloud SDK functions: [gcloud_init](#), [gcloud_terminal](#)

Examples

```
## Not run:  
library(cloudml)  
gcloud_install()  
  
## End(Not run)
```

gcloud_terminal	<i>Create an RStudio terminal with access to the Google Cloud SDK</i>
-----------------	---

Description

Create an RStudio terminal with access to the Google Cloud SDK

Usage

```
gcloud_terminal(command = NULL, clear = FALSE)
```

Arguments

command	Command to send to terminal
clear	Clear terminal buffer

Value

Terminal id (invisibly)

See Also

Other Google Cloud SDK functions: [gcloud_init](#), [gcloud_install](#)

 gs_copy

Copy files to / from Google Storage

Description

Use the `gsutil cp` command to copy data between your local file system and the cloud, copy data within the cloud, and copy data between cloud storage providers.

Usage

```
gs_copy(source, destination, recursive = FALSE, echo = TRUE)
```

Arguments

source	The file to be copied. This can be either a path on the local filesystem, or a Google Storage URI (e.g. <code>gs://[BUCKET_NAME]/[FILENAME.CSV]</code>).
destination	The location where the source file should be copied to. This can be either a path on the local filesystem, or a Google Storage URI (e.g. <code>gs://[BUCKET_NAME]/[FILENAME.CSV]</code>).
recursive	Boolean; perform a recursive copy? This must be specified if you intend on copying directories.
echo	Echo command output to console.

 gs_local_dir

Get a local path to the contents of Google Storage bucket

Description

Provides a local filesystem interface to Google Storage buckets. Many package functions accept only local filesystem paths as input (rather than `gs://` URLs). For these cases the `gcloud_path()` function will synchronize `gs://` buckets to the local filesystem and provide a local path interface to their contents.

Usage

```
gs_local_dir(url, local_dir = "gs", echo = FALSE)
```

Arguments

url	Google Storage bucket URL (e.g. <code>gs://<your-bucket></code>).
local_dir	Local directory to synchronize Google Storage bucket(s) to.
echo	Echo command output to console.

Details

If you pass a local path as the url it will be returned unmodified. This allows you to for example use a training flag for the location of data which points to a local directory during development and a Google Cloud bucket during cloud training.

Value

Local path to contents of bucket.

Examples

```
library(cloudml)
gs_local_dir(getwd())
```

gs_rsync	<i>Synchronize content of two buckets/directories</i>
----------	---

Description

The `gs_rsync` function makes the contents under destination the same as the contents under source, by copying any missing files/objects (or those whose data has changed), and (if the delete option is specified) deleting any extra files/objects. source must specify a directory, bucket, or bucket subdirectory.

Usage

```
gs_rsync(source, destination, delete = FALSE, recursive = FALSE,
         parallel = TRUE, dry_run = FALSE, options = NULL, echo = TRUE)
```

Arguments

source	The file to be copied. This can be either a path on the local filesystem, or a Google Storage URI (e.g. <code>gs://[BUCKET_NAME]/[FILENAME.CSV]</code>).
destination	The location where the source file should be copied to. This can be either a path on the local filesystem, or a Google Storage URI (e.g. <code>gs://[BUCKET_NAME]/[FILENAME.CSV]</code>).
delete	Delete extra files under destination not found under source By default extra files are not deleted.
recursive	Causes directories, buckets, and bucket subdirectories to be synchronized recursively. If you neglect to use this option <code>gs_rsync()</code> will make only the top-level directory in the source and destination URLs match, skipping any sub-directories.
parallel	Causes synchronization to run in parallel. This can significantly improve performance if you are performing operations on a large number of files over a reasonably fast network connection.

dry_run	Causes rsync to run in "dry run" mode, i.e., just outputting what would be copied or deleted without actually doing any copying/deleting.
options	Character vector of additional command line options to the gsutil rsync command (as specified at https://cloud.google.com/storage/docs/gsutil/commands/rsync).
echo	Echo command output to console.

job_cancel	<i>Cancel a job</i>
------------	---------------------

Description

Cancel a job.

Usage

```
job_cancel(job = "latest")
```

Arguments

job	Job name or job object. Pass "latest" to indicate the most recently submitted job.
-----	--

See Also

Other job management functions: [job_collect](#), [job_list](#), [job_status](#), [job_stream_logs](#), [job_trials](#)

job_collect	<i>Collect job output</i>
-------------	---------------------------

Description

Collect the job outputs (e.g. fitted model) from a job. If the job has not yet finished running, `job_collect()` will block and wait until the job has finished.

Usage

```
job_collect(job = "latest", trials = "best", destination = "runs",
  timeout = NULL, view = interactive())
```


Arguments

job	Job name or job object. Pass "latest" to indicate the most recently submitted job.
trials	Under hyperparameter tuning, specifies which trials to download. Use "best" to download best trial, "all" to download all, or a vector of trials c(1,2) or 1.
destination	The destination directory in which model outputs should be downloaded. Defaults to runs.
timeout	Give up collecting job after the specified minutes.
view	View the job results after collecting it. You can also pass "save" to save a copy of the run report at tfruns.d/view.html

See Also

Other job management functions: [job_cancel](#), [job_list](#), [job_status](#), [job_stream_logs](#), [job_trials](#)

job_list	<i>List all jobs</i>
----------	----------------------

Description

List existing Google Cloud ML jobs.

Usage

```
job_list(filter = NULL, limit = NULL, page_size = NULL, sort_by = NULL,
         uri = FALSE)
```

Arguments

filter	Filter the set of jobs to be returned.
limit	The maximum number of resources to list. By default, all jobs will be listed.
page_size	Some services group resource list output into pages. This flag specifies the maximum number of resources per page. The default is determined by the service if it supports paging, otherwise it is unlimited (no paging).
sort_by	A comma-separated list of resource field key names to sort by. The default order is ascending. Prefix a field with ~ for descending order on that field.
uri	Print a list of resource URIs instead of the default output.

See Also

Other job management functions: [job_cancel](#), [job_collect](#), [job_status](#), [job_stream_logs](#), [job_trials](#)

job_status	<i>Current status of a job</i>
------------	--------------------------------

Description

Get the status of a job, as an R list.

Usage

```
job_status(job = "latest")
```

Arguments

job	Job name or job object. Pass "latest" to indicate the most recently submitted job.
-----	--

See Also

Other job management functions: [job_cancel](#), [job_collect](#), [job_list](#), [job_stream_logs](#), [job_trials](#)

job_stream_logs	<i>Show job log stream</i>
-----------------	----------------------------

Description

Show logs from a running Cloud ML Engine job.

Usage

```
job_stream_logs(job = "latest",  
  polling_interval = getOption("cloudml.stream_logs.polling", 5),  
  task_name = NULL, allow_multiline_logs = FALSE)
```

Arguments

job	Job name or job object. Pass "latest" to indicate the most recently submitted job.
polling_interval	Number of seconds to wait between efforts to fetch the latest log messages.
task_name	If set, display only the logs for this particular task.
allow_multiline_logs	Output multiline log messages as single records.

See Also

Other job management functions: [job_cancel](#), [job_collect](#), [job_list](#), [job_status](#), [job_trials](#)

job_trials	<i>Current trials of a job</i>
------------	--------------------------------

Description

Get the hyperparameter trials for job, as an R data frame

Usage

```
job_trials(x)
```

Arguments

x	Job name or job object.
---	-------------------------

See Also

Other job management functions: [job_cancel](#), [job_collect](#), [job_list](#), [job_status](#), [job_stream_logs](#)

Index

cloudml_deploy, [2](#), [3](#), [4](#)
cloudml_deploy(), [3](#)
cloudml_predict, [2](#), [3](#), [4](#)
cloudml_predict(), [2](#)
cloudml_train, [2](#), [3](#), [3](#)

flags(), [4](#)

gcloud_init, [4](#), [5](#), [6](#)
gcloud_install, [4](#), [5](#), [6](#)
gcloud_terminal, [4](#), [5](#), [5](#)
gs_copy, [6](#)
gs_local_dir, [6](#)
gs_rsync, [7](#)

job_cancel, [8](#), [9–11](#)
job_cancel(), [4](#)
job_collect, [8](#), [8](#), [9–11](#)
job_collect(), [4](#)
job_list, [8](#), [9](#), [9](#), [10](#), [11](#)
job_status, [8–10](#), [10](#), [11](#)
job_status(), [4](#)
job_stream_logs, [8–10](#), [10](#), [11](#)
job_trials, [8–10](#), [11](#)

tensorflow::export_savedmodel(), [2](#)