LFM4Ads: Large Foundation Model for Ads Recommendation

Jie Jiang*
Shangyu Zhang*
Shijie Quan*
zeus@tencent.com
vitosyzhang@tencent.com
justinquan@tencent.com
Tencent
Shenzhen, China

Zhongren Wang*
Tianqu Zhuang*
wcr23@mails.tsinghua.edu.cn
zhuang-qu@qq.com
Tsinghua University
Shenzhen, China

Junwei Pan†
Bo Fu
Yilong Sun
jonaspan@tencent.com
leonardfu@tencent.com
elonsun@tencent.com
Tencent
Shenzhen, China

Jieying Lin
Jushuo Chen
Xiaotian Li
jieyinglin@tencent.com
jushuochen@tencent.com
dylanxtli@tencent.com
Tencent
Shenzhen, China

Wenjie Li
liwj20@mails.tsinghua.edu.cn
Tsinghua University
Shenzhen, China

Zhixiang Feng
Xian Hu
lionelfeng@tencent.com
sirlyhu@tencent.com
Tencent
Shenzhen, China

Huiting Deng
Hua Lu
timmydeng@tencent.com
hualu@tencent.com
Tencent
Shenzhen, China

Jinpeng Wang
wangjp26@gmail.com
Tsinghua University
Shenzhen, China

Boqi Dai
Xiaoyu Chen
Bin Hu
ericbqdai@tencent.com
sakyachen@tencent.com
glennbinhu@tencent.com
Tencent
Shenzhen, China

Lili Huang
Yanwen Wu
Yeshou Cai
lilillhuang@tencent.com
steveywwu@tencent.com
showcai@tencent.com
Tencent
Shenzhen, China

Qi Zhou
Huang Tang
Chunfeng Yang
dzhouqi@gmail.com
michaeltang@tencent.com
yannisyang@tencent.com
Tencent
Shenzhen, China

Chengguo Yin
Tingyu Jiang
Lifeng Wang
turingyin@tencent.com
travisjiang@tencent.com
327939898@qq.com
Tencent
Shenzhen, China

Shudong Huang†
ericdhuang@tencent.com
Tencent
Shenzhen, China

Dapeng Liu
Yuekui Yang
rocliu@tencent.com
yuekuiyang@tencent.com
Tencent
Shenzhen, China

Shu-Tao Xia
xiast@sz.tsinghua.edu.cn
Tsinghua University
Shenzhen, China

Lei Xiao
Haijie Gu
shawnxiao@tencent.com
jerrickgu@tencent.com
Tencent
Shenzhen, China


Abstract

Recent work leverages large-scale pretrained foundation models (FMs) to transfer generalizable representations to downstream advertising tasks. Most existing paradigms transfer user representations (URs) and item representations (IRs), while underutilizing the user-item cross representations (CRs) generated by deeper interaction layers. Although a recent approach transfers target-aware embeddings (TAEs), it requires real-time upstream FM inference alongside downstream model inference, introducing additional engineering complexity and overhead.

To address these limitations, we propose Large Foundation Model for Ads Recommendation (LFM4Ads), an efficient *pretrain-then-transfer* framework for cross-domain ad recommendation. LFM4Ads jointly exploits URs, IRs, and CRs from the upstream FM, covering both isolated user/item semantics and fine-grained user-item interactions. It extracts sample-level CRs from pretrained interaction layers and aggregates them into user-level CRs with temporal decay, thereby decoupling upstream FM inference from downstream online serving. To enable efficient utilization of CRs, we further propose *multi-granular downstream usages*, including feature-level gating for CR fusion, module-level fine-tuning to yield downstream CRs, and model-level retrieval by matching CRs with IRs.

Since Q4 2024, LFM4Ads has been deployed on Tencent's advertising platform. It has supported 10+ launches across major scenarios, yielding a platform-wide gross merchandise value (GMV) lift of 2.45% and annual revenue gains in the hundreds of millions of dollars. Offline experiments on KuaiRand-1K also validate the effectiveness of LFM4Ads, and our code is available at https://github.com/ZhuangQu/LFM4Ads.

*Equal contribution.
†Corresponding authors.



This work is licensed under a Creative Commons Attribution 4.0 International License.

CIKM '26, Rome, Italy.

© 2026 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-2539-5/2026/11
https://doi.org/10.1145/3799682.3840163

CCS Concepts

• **Information systems** → **Recommender systems**; **Online advertising**; • **Computing methodologies** → *Transfer learning*.

Keywords

Recommendation System, Pretraining, Transfer Learning

ACM Reference Format:

Jie Jiang, Shangyu Zhang, Shijie Quan, Zhongren Wang, Tianqu Zhuang, Junwei Pan, Bo Fu, Yilong Sun, Jieying Lin, Jushuo Chen, Xiaotian Li, Wenjie Li, Zhixiang Feng, Xian Hu, Huiting Deng, Hua Lu, Jinpeng Wang, Boqi Dai, Xiaoyu Chen, Bin Hu, Lili Huang, Yanwen Wu, Yeshou Cai, Qi Zhou, Huang Tang, Chunfeng Yang, Chengguo Yin, Tingyu Jiang, Lifeng Wang, Shudong Huang, Dapeng Liu, Yuekui Yang, Shu-Tao Xia, Lei Xiao, and Haijie Gu. 2026. LFM4Ads: Large Foundation Model for Ads Recommendation. In *Proceedings of the 35th ACM International Conference on Information and Knowledge Management (CIKM '26), November 7–11, 2026, Rome, Italy*. ACM, New York, NY, USA, 9 pages. https://doi.org/10.1145/3799682.3840163

1 Introduction

Online advertising has grown into a massive digital economy, driving hundreds of billions of dollars in annual revenue [13]. Its ranking and bidding systems depend on click-through rate (CTR) and conversion rate (CVR) prediction, motivating extensive research on multi-field feature interactions [5, 29, 35] and sequential behavior modeling [6, 49, 50]. As platforms span many scenarios and tasks, multi-task and multi-domain learning can share statistical strength [17, 24, 28, 38], but may suffer from negative transfer and the seesaw effect [1, 27, 40, 51]. Strict latency, throughput, and cost constraints also make a single large joint model difficult to deploy. This motivates the *pretrain-then-transfer* paradigm, in which foundation models (FMs) learn reusable knowledge from cross-scenario data and adapt it to specialized downstream models [4, 15, 18, 23, 32, 43, 48, 52].

However, existing FM transfer pipelines remain incomplete in both *what* is transferred and *how* it is utilized. First, most methods transfer user representations (URs) and item representations (IRs), typically obtained from upstream user or item towers [30, 32, 48]. Although URs and IRs can capture user-side and item-side characteristics, they underutilize finer-grained user-item correlations generated by deeper interaction layers. A recent work transfers Target-Aware Embeddings (TAEs) of user-item pairs [15], but it requires the FM to compute TAEs in real time, resulting in an additional upstream inference alongside downstream inference. Efficient transfer of user-item cross representations (CRs) therefore remains unresolved.

Second, the transferability of CRs is underexplored. Modern recommenders contain multiple explicit and implicit interaction layers [14, 39, 42], but it is unclear which layers preserve the most generalizable CRs. Moreover, CRs are sample-specific and lack reusable coarse-grained forms for downstream tasks. Additionally, existing transfer mechanisms are largely confined to feature-level injection through simple projections, which may fail to bridge upstream-downstream semantic gaps and may dilute FM signals among thousands of downstream features. Module-level reuse and model-level deployment of FM representations for standalone retrieval are rarely explored.




Figure 1: Overview. (a) LFM4Ads is pretrained on content and ad samples across scenarios and tasks, whose representations are transferred to downstream models. (b) Cross representations are fused by gating for feature-level usage. (c) Modules that yield cross representations are fine-tuned for module-level usage. (d) Cross and item representations are matched for model-level usage.

To bridge these gaps, we propose Large Foundation Model for Ads Recommendation (LFM4Ads), a novel *pretrain-then-transfer* framework for cross-domain ad recommendation, as shown in Figure 1. Our contributions include the following:

- We extract all available representations from FM and leverage their complementary strengths: URs record user interests, IRs alleviate the item cold-start problem, and CRs provide finer-grained interaction signals that outperform isolated URs.
- We investigate CRs from diverse interaction layers and aggregate sample-level CRs into user-level CRs using time-dependent decay, making CRs reusable for downstream tasks.
- We transfer upstream knowledge at the feature, module, and model levels. Specifically, we fuse CRs via a nonlinear gate, reuse upstream structures and weights, and perform retrieval directly with CRs and IRs. From feature-level to module-level and then to model-level, our transfer granularity increases and fewer parameters require training, demonstrating that *the stronger the foundation, the thinner the downstreams.*

On the public dataset KuaiRand-1K, CR transfer with nonlinear gating improves the average AUC by 2.5‰ over SUM [48]. Further analyses show that intermediate CRs favor feature-level transfer, while deeper CRs favor retrieval; gains are particularly pronounced in sample-scarce scenarios.

LFM4Ads has supported 10+ production launches and yields a platform-wide gross merchandise value (GMV) lift of 2.45%, translating to annual revenue increases in the hundreds of millions of dollars. In Weixin Moments, it improves AUC by 1‰ with a 1.35% GMV lift. Ablation studies further highlight the importance of CR aggregation and nonlinear gating. Module-level reuse accelerates convergence; standalone retrieval lifts GMV by 1.17% in Weixin Channels.

2 Related Work

Industrial advertising and recommendation models learn user-item relevance using complementary techniques, including multi-field feature interaction modeling [5, 9, 42], multi-task learning [28], sequential behavior modeling [6, 49, 50], and multi-domain modeling [19, 20]. Together, they underpin modern click-through-rate and conversion-rate prediction pipelines. Although these models capture high-order interactions and evolving user interests, strict latency, capacity, and feature-budget constraints limit their scale in online serving [8, 11, 34].

To address these constraints, upstream-downstream systems pretrain large models on broad data and transfer knowledge through representation injection or model adaptation. Representative systems learn sequence-based user embeddings [32, 48], transfer multimodal item signals [2, 36], or reuse learned user-item similarities [30]. Model-adaptation methods instead fine-tune pretrained activity-sequence models [4] or distill an external foundation model into smaller domain-specific models [23]. Despite these advances, sample-specific interaction knowledge from deeper layers remains difficult to store, transfer, and reuse across heterogeneous downstream architectures.

A parallel line of research explores large language model (LLM)-based approaches to e-commerce instruction tuning [22, 33, 37] and generative, cross-domain, or generalizable recommendation [43, 45, 52]. These approaches exploit linguistic knowledge and generative capabilities; in contrast, LFM4Ads targets large-scale sparse advertising signals and transfers user, item, and cross representations under tight production budgets while decoupling upstream FM inference from downstream online serving.

3 Methodology

We first design our upstream foundation model in Section 3.1, then enhance cross representations in Section 3.2, and finally discuss downstream usages in Section 3.3.

3.1 Pretrain and Extract Representations

Our Large Foundation Model for Ads Recommendation (LFM4Ads) is illustrated in Figure 1a. We adopt a *two-tower* design, where a user tower extracts a user representation (UR) from user features, and an item tower extracts an item representation (IR) from item features. Then we employ interaction layers (e.g., DCNv2 [42]) to capture the user-item cross correlations.

Formally, let $\mathbf{UR}(u)$ be the representation of user u, and $\mathbf{IR}(i)$ be the representation of item i. Whenever a sample (u, i) arrives at LFM4Ads, we extract $\mathbf{UR}(u)$ and $\mathbf{IR}(i)$ from the two towers. Besides, the interaction layers capture the correlations between $\mathbf{UR}(u)$ and $\mathbf{IR}(i)$ at finer-grained levels, including explicit and implicit feature interactions. To leverage these interactions, we extract the output of an interaction layer as a user-item cross representation (CR), denoted as $\mathbf{CR}(u, i)$. *Together, URs, IRs, and CRs constitute the three representation types transferred in LFM4Ads.*

LFM4Ads is pretrained on all samples from multiple scenarios (e.g., Weixin Moments, Search Ads), multiple tasks (e.g., pCTR, pCVR), and two domains (content and advertising). Considering the distributional differences between content and ad samples, we adopt a *dual-branch* design after the two towers, where one branch is for content tasks, and the other branch is for ad tasks. Notably, we transfer CRs only from the ad branch because our downstream tasks are ad recommendation. For content tasks, transferring the CRs from the content branch is also feasible.

3.2 Enhance Transferability of CRs

There are two main challenges when transferring CRs: (1) CR is a sample-level representation of a user-item pair, which is too fine-grained for downstream tasks. (2) It is impractical to calculate and store the CRs for all user-item pairs. Although a recent approach [15] computes Target-Aware Embeddings (TAEs) in real time, it requires an additional upstream inference pass alongside downstream inference.

To address these challenges, we propose to aggregate multiple CRs into one user-level CR. Formally, let $\mathbf{CR}(u)$ be the aggregated CR of user u. We initialize $\mathbf{CR}(u) \leftarrow \mathbf{0}$. Whenever a new $\mathbf{CR}(u, i)$ is generated, we update $\mathbf{CR}(u)$ by

$$\mathbf{CR}(u) \leftarrow \beta(t) \cdot \mathbf{CR}(u) + \big(1 - \beta(t)\big) \cdot \mathbf{CR}(u, i), \tag{1}$$

where t is the time interval since the previous update of $\mathbf{CR}(u)$, and $\beta : [0, +\infty) \to [0, 1]$ is a decreasing function.

We refer to (1) as a *time-aware exponential moving average*, which adapts to user activity. For inactive users, t is large and we have $\beta(t) \approx 0$ to prioritize current interactions and address distribution drift. For active users, t is small and we have $\beta(t) \approx 1$ to retain more historical interactions.

To further enhance the transferability of CRs, we explore which layer yields the best CRs. We find that the optimal CRs are extracted from the middle layer for feature-level usage, and from the deepest layer for model-level usage. More details are in Sections 4.2 and 4.4.

3.3 Three Downstream Usages

In this section, we discuss how to use CRs for downstream tasks. We propose feature-level, module-level, and model-level usages, ranging from fine-grained to coarse-grained.

3.3.1 Feature-Level Usage: Nonlinear Gating. The most straightforward fusion is to treat an upstream representation as an additional feature and concatenate it with downstream embeddings, like SUM [48]. Formally, let $\boldsymbol{E}$ be the concatenation of downstream embeddings. The concat-based fusion yields

$$\boldsymbol{E}' = \big[\boldsymbol{E}, \quad \boldsymbol{M} \cdot \mathbf{CR}(u)\big], \tag{2}$$

where $\boldsymbol{M}$ is a learnable projection matrix that reduces the dimensionality of $\mathbf{CR}(u)$.

However, (2) may be ineffective because it directly mixes two semantically misaligned representation spaces. We tried several approaches, including employing an alignment loss between the upstream and downstream features [21], but none of them led to a performance gain over production baselines during online A/B tests. Inspired by self-gating [3, 12, 46], we adopt a gating-based fusion, which yields

$$\boldsymbol{E}' = \boldsymbol{E} \odot \boldsymbol{\sigma}\big(\boldsymbol{M} \cdot \mathbf{CR}(u)\big), \tag{3}$$

where $\boldsymbol{\sigma}$ is a nonlinear function, and $\odot$ is Hadamard product. For gating, $\boldsymbol{M}$ projects $\mathbf{CR}(u)$ to the same dimensionality as $\boldsymbol{E}$. Here $\boldsymbol{\sigma}(\boldsymbol{M}\cdot)$ serves as a gate as illustrated in Figure 1b. A recent work [46] revealed the mechanism behind (3) — $\boldsymbol{\sigma}(\boldsymbol{M}\cdot)$ *serves as a nonlinear*

encoder to construct new representations, thereby mitigating dimensional collapse and representation redundancy.

3.3.2 Module-Level Usage: Fine-Tuning Cross Representations. As discussed in Section 3.2, when a sample (u, i) arrives at the downstream, there are challenges in transferring upstream $\mathbf{CR}(u, i)$. To overcome this, we have proposed transferring the aggregated $\mathbf{CR}(u)$ in Section 3.2. In this section, we propose another solution — transferring the upstream modules that yield $\mathbf{CR}(u, i)$.

As illustrated in Figure 1c, we initialize the downstream model with the same modules as LFM4Ads, including the two towers and the interaction layers in the ad branch. Thus, the downstream model yields the same $\mathbf{CR}(u, i)$ as LFM4Ads. After training on downstream samples, $\mathbf{CR}(u, i)$ is fine-tuned into $\mathbf{CR}'(u, i)$, which is better aligned with downstream requirements.

Inspired by prior work showing that pretrained representations can transfer learned user-item similarity structures across models [30, 31, 36], we transfer these upstream modules together with the user-item correlations (i.e., distance or similarity) learned by LFM4Ads. This makes downstream learning start from a representation space where user-item interactions have already been broadly shaped by multi-scenario pretraining.

3.3.3 Model-Level Usage: Standalone Retrieval. The URs and IRs learned by LFM4Ads naturally encode the relevance between users and items, so they can be directly used for retrieval [32]. Formally, given a user u, we retrieve the best-matching item i from the candidate pool, with the highest

$$\text{score}(u, i) = \left\langle \mathbf{Adapter}\big(\mathbf{UR}(u)\big), \quad \mathbf{IR}(i) \right\rangle, \tag{4}$$

where $\langle \cdot, \cdot \rangle$ denotes the dot product, and **Adapter** is a tiny learnable layer (e.g., a projection matrix). We optimize **Adapter** using binary cross-entropy (BCE) or the InfoNCE loss [41].

Since our $\mathbf{CR}(u)$ can be regarded as a user representation like $\mathbf{UR}(u)$, we explore replacing $\mathbf{UR}(u)$ with $\mathbf{CR}(u)$ in (4), and find that $\mathbf{CR}(u)$ generally performs better. More details are in Section 4.4.

As shown in Figure 1d, our retrieval model (4) does not require two parameter-heavy towers in the downstream model. Benefiting from our effective and refined $\mathbf{CR}(u)$, a tiny adapter is sufficient to serve as a whole retrieval model. This highlights the potential of LFM4Ads — *it provides not only an additional representation, but also a standalone model.*

3.3.4 Trade-off among Three Usages. Feature-level usage is compatible with existing online ranking models, since it only injects an additional representation as a new feature. It can provide incremental performance gains for well-trained mature systems.

Module-level usage is suitable for new ranking scenarios. It not only accelerates training convergence but also leverages full-scenario knowledge to tackle long-tail and sparse scenarios. But it lacks flexibility, since it requires upstream and downstream models to share similar architectures.

Model-level usage is convenient for fast deployment. With a small parameter footprint and low latency, it is suitable for large-scale retrieval. In our offline experiments, as reported in Section 4.5 and Table 1, model-level usage achieves lower AUC than the other two usages, possibly due to its more limited inputs and smaller model capacity.

From feature-level to module-level and then to model-level, *the transfer granularity ranges from fine to coarse, and thus the downstream training cost shifts from heavy to light.*

4 Offline Experiments

There is no widely adopted benchmark for evaluating recommendation foundation models. We therefore use KuaiRand-1K [7], which contains interactions spanning 15 scenarios, to emulate a *pretrain–then-transfer* pipeline. Specifically, we pretrain an upstream foundation model on the union of data from all scenarios, and then transfer it to 15 scenario-specific downstream models, each trained only on samples from its own scenario.

4.1 Settings

4.1.1 Dataset. KuaiRand-1K contains 1,000 users, 4,369,953 items, and 11,713,045 samples. These samples cover 15 scenarios and span 31 days. We use the first 25 days as the training set, the following 3 days as the validation set, and the last 3 days as the test set. Each downstream dataset contains only samples from a single scenario. We discard continuous features, and each sample has 27 user-side and 9 item-side categorical features. We take click or not as the label, constructing a pCTR task.

4.1.2 Upstream Model. Our foundation model comprises a user tower, an item tower, and a DCNv2 [42]. The DCNv2 has 3 cross layers and a 3-layer DNN. All layers are sequentially denoted as

$$Towers,\ Cross_1,\ Cross_2,\ Cross_3,\ DNN_1,\ DNN_2,\ DNN_3.$$

$Towers$ map each feature to an embedding of length 10, and then concatenate them. The size of $Cross_1, \cdots, DNN_2$ is 360×360, while the size of DNN_3 is 360×15. The foundation model consumes samples from all 15 scenarios, emulating online cross-scenario pretraining. The output is 15 logits for 15 scenarios, but only the logit for the sample's scenario is used.


4.1.3 Training. Our foundation and downstream models share the same training settings. The loss is BCE and the optimizer is AdamW [26]. The settings of AdamW follow PyTorch defaults, where the learning rate is 0.001, betas are (0.9, 0.999), and weight decay is 0.01. The samples are sorted by timestamp and the batch size is 10,000. We stop training when the validation AUC declines.

4.1.4 Upstream Representations. After training the foundation, we freeze it and extract $\mathbf{UR}(u)$, $\mathbf{IR}(i)$, and $\mathbf{CR}(u)$ for every user u and item i. $\mathbf{UR}(u)$ and $\mathbf{IR}(i)$ are extracted from $Towers$. For extracting $\mathbf{CR}(u)$, we replay the training and validation samples. For each sample (u, i), we extract $\mathbf{CR}(u, i)$ from $Towers, Cross_1, \cdots$, or DNN_2. We aggregate sample-level $\mathbf{CR}(u, i)$ into user-level $\mathbf{CR}(u)$ using (1) with $\beta = 0.99$.

4.1.5 Evaluation. We evaluate the test AUC of each downstream model, which is trained only on samples from a specific scenario. Each AUC is averaged over 100 runs, i.e., 100 pairs of foundation and downstream models.

4.2 Feature-Level Usage

We deploy downstream models with the same architecture as the upstream foundation model and fuse $\mathbf{CR}(u)$ into the downstream



(a) Feature-level usage. SUM fuses UR via concat [48]. ■ indicates the gain from CR, and ■ indicates the gain from gating.

(b) Module-level usage. Vanilla trains from scratch. ■ indicates the gain from upstream initialization, while ■ indicates the drop.

(c) Model-level usage. TwoTower has its two towers. ■ indicates the gain from CR & IR, while ■ indicates the drop.

Figure 2: Offline results on two typical scenarios of KuaiRand-1K.

embeddings. For concat-based fusion (2), the dimensionality of $\mathbf{CR}(u)$ is reduced to 10 to match that of a downstream embedding. For gating-based fusion (3), we let $\boldsymbol{\sigma} = \mathbf{sigmoid}$. As a baseline, SUM fuses $\mathbf{UR}(u)$ via concat [48].

The results for Scenarios 1 and 4 are presented in Figure 2a. Scenario 1 is a large-scale scenario with 65.9% samples, and Scenario 4 is a medium-scale scenario with 7.6% samples. We have the following observations:

First, fusing CRs via concat generally outperforms SUM, as indicated by ■ in Figure 2a. With CRs extracted from $Cross_3$, concat improves AUC over SUM by 1.5‰ in Scenario 1 and 4.1‰ in Scenario 4. Note that a 1‰ AUC gain can be practically meaningful in recommendation [16, 25]. These gains support the benefit of capturing finer-grained user-item cross correlations.

Second, fusing CRs via gating (3) generally outperforms concat (2), as indicated by ■ in Figure 2a. At $Cross_3$, gating yields additional AUC gains of 0.9‰ and 0.8‰ over concat in Scenarios 1 and 4, respectively. Gating also preserves the dimensionality of downstream embeddings, avoiding the DCNv2 expansion required by concat.

Third, as CRs are extracted from progressively deeper layers, downstream AUC first increases and then decreases. Thus the highest AUC is achieved with CRs extracted from $Cross_3$ in Scenario 1 and DNN_1 in Scenario 4. Both $Cross_3$ and DNN_1 are intermediate layers. This finding aligns with [47], suggesting a trade-off between less processed shallow representations and more task-specific deep representations.

4.3 Module-Level Usage

We deploy downstream models with the same architecture as the upstream foundation model. The initial layers are initialized with upstream weights, while the remaining layers are initialized from scratch. As a baseline, Vanilla initializes all layers from scratch.

Figure 2b shows the effect of transferring different numbers of layers. We have the following observations:

First, both AUC curves increase monotonically over the transfer depths, suggesting that more transferred layers yield better performance. This is also consistent with [47], suggesting that transferring more layers can be beneficial when upstream and downstream tasks are similar.

Second, the performance gains vary with scenario size. In Scenario 1, transferring only a subset of layers leads to negative transfer, as indicated by ■ in Figure 2b. Initializing all layers with upstream weights yields an AUC gain of 0.2‰ over Vanilla. This may be because the abundant downstream samples allow scenario-specific embeddings to be learned from scratch, whereas upstream embeddings must accommodate all scenarios. In Scenario 4, however, transferring upstream layers consistently improves AUC over Vanilla, as indicated by ■. With all layers initialized with upstream weights, the AUC gain is 8.4‰ over Vanilla. The larger gain in Scenario 4 suggests that upstream initialization can be more beneficial when downstream samples are limited.

4.4 Model-Level Usage

We instantiate the **Adapter** in (4) as a matrix $\boldsymbol{W}$, i.e.,

$$\text{score}(u, i) = \mathbf{UR}^T(u) \cdot \boldsymbol{W} \cdot \mathbf{IR}(i). \tag{5}$$

We also evaluate a variant that replaces URs with CRs:

$$\text{score}(u, i) = \mathbf{CR}^T(u) \cdot \boldsymbol{W} \cdot \mathbf{IR}(i). \tag{6}$$

As a baseline, we train a model with its own two towers, formalized as

$$\text{score}(u, i) = \mathbf{UserTower}^T(u) \cdot \boldsymbol{W} \cdot \mathbf{ItemTower}(i), \tag{7}$$

where **UserTower** and **ItemTower** have the same architecture as *Towers* and are trained from scratch on downstream samples.

We denote Models (5), (6), and (7) as UR & IR, CR & IR, and TwoTower, respectively. Figure 2c compares the three models. We have the following observations:

First, in Scenario 1, TwoTower outperforms UR & IR, suggesting that abundant downstream samples allow the two towers to learn effective representations from scratch. In Scenario 4, however, UR & IR slightly outperforms TwoTower, suggesting that upstream representations can be beneficial when downstream samples are more limited.

Second, both AUC curves increase monotonically with the CR extraction depth. This may be because the lightweight retrieval model benefits from more refined upstream representations. With CRs extracted from DNN_2, CR & IR improves AUC over TwoTower by 9.8‰ and 42.5‰ in Scenarios 1 and 4, respectively. Compared with

Table 1: Offline results on all available scenarios of KuaiRand-1K. Highest is bolded and lowest is italicized. Average is weighted by the number of samples. CR is extracted from $Cross_3$ for feature-level usage, and DNN_2 for model-level usage. All layers are fine-tuned to yield CR′ for module-level usage.

Scenario		1	0	4	2	6	3	8	5	Average
# of samples		7,717,601	2,407,352	895,385	402,293	183,403	37,418	17,430	16,424	-
% of samples		65.9%	20.6%	7.6%	3.4%	1.6%	0.3%	0.1%	0.1%	-
Feature	**SUM**	*0.7310*	0.7123	*0.7101*	*0.7975*	*0.7183*	*0.7017*	*0.7622*	*0.6562*	*0.7275*
	concat CR	0.7325	0.7123	0.7142	0.7993	**0.7277**	0.7114	**0.7668**	0.6622	0.7291
	gating CR	**0.7334**	**0.7132**	**0.7150**	**0.8000**	0.7249	**0.7302**	0.7657	**0.6699**	**0.7300**
Module	**Vanilla**	0.7309	0.7120	0.7086	0.7971	0.7173	0.7038	0.7627	0.6606	0.7273
	CR′	**0.7311**	**0.7136**	**0.7170**	**0.7990**	**0.7361**	**0.7387**	**0.7861**	**0.6834**	**0.7288**
Model	**TwoTower**	0.6972	0.6450	*0.6464*	*0.7570*	*0.5776*	*0.5838*	**0.6550**	*0.5562*	0.6821
	UR & IR	*0.6340*	*0.6376*	0.6478	**0.7662**	0.5915	0.5911	0.6449	0.5565	*0.6395*
	CR & IR	**0.7070**	**0.6821**	**0.6889**	0.7645	**0.6553**	**0.6122**	*0.5646*	**0.6012**	**0.7010**

UR & IR, the corresponding AUC gains are 73.0‰ and 41.1‰. In addition to these performance gains, CR & IR requires only a trainable adapter, avoiding the need to train and store two downstream towers.

4.5 Overall Comparisons

We conduct comprehensive comparisons on eight scenarios with enough samples. Based on the preceding experiments, we extract CRs from $Cross_3$ for feature-level usage, initialize all layers with upstream weights for module-level usage, and extract CRs from DNN_2 for model-level usage.

The results are listed in Table 1. Based on the reported weighted-average AUCs, feature-level gating, module-level fine-tuning, and model-level retrieval yield gains of 2.5‰, 1.5‰, and 18.9‰ over SUM, Vanilla, and TwoTower, respectively. The gains vary across scenarios and transfer strategies. For Scenarios 6, 3, 8, and 5 which are sample-scarce, the AUC gains across the three transfer granularities span 23.4–77.7‰ over corresponding baselines. These results suggest that cross-scenario pretraining can be particularly beneficial when downstream supervision is limited.

5 Online Deployment

We instantiate LFM4Ads as an industrial system, and deploy it on Tencent's advertising platform at scale.

5.1 Samples and Features

We collect samples from all available advertising scenarios, including Weixin Moments, Weixin Channels, Weixin Official Accounts, Tencent News, Tencent Sports, Demand-Side Platform, and other pCTR and pCVR scenarios. Besides advertisements, we also collect samples from the content domain, which is on a much larger scale and hence contains more collaborative information about users' interests. The total number of samples fed into LFM4Ads is tens of billions per day, with 80% from the content domain and 20% from the ad domain. The number of samples is 20 to hundreds of times larger than that of individual downstream tasks.




Figure 3: Online response process.

Each upstream sample contains approximately 1,800 features, most of which are on the user side. In contrast, most downstream ranking samples have 200–1,000 features, while retrieval and matching samples have 100–500 features. 87% of the user features are multi-valued, including around 50 sequences, with lengths ranging from dozens to thousands. On average, flattening all multi-valued features yields more than 60,000 feature values per sample.

5.2 Scale of Models

LFM4Ads has a 4-TB parameter footprint, which is 48% larger than the largest downstream model (Weixin Moments pCTR), 233% larger than the Weixin Channels pCTR model, and 427% larger than the average size of downstream models. It processes 6.3B sparse features, which is 270% larger than the largest downstream task's. The FLOPS is 1.45B and the QPS is 500K. To save storage, we employ quantization to compress an upstream representation from 4KB down to 1KB.

5.3 Response Process

The response process of our online system is shown in Figure 3. Formally, whenever a user u and an ad i arrive, we retrieve $\mathbf{UR}(u)$, $\mathbf{IR}(i)$, and $\mathbf{CR}(u)$ from storage, and transfer them into the downstream model. Meanwhile, LFM4Ads performs inference on (u, i) and extracts new $\mathbf{UR}(u)$, $\mathbf{IR}(i)$ and $\mathbf{CR}(u, i)$. Then in the storage, $\mathbf{UR}(u)$ and $\mathbf{IR}(i)$ are updated directly, and $\mathbf{CR}(u)$ is updated by

Table 2: Online A/B results.

Usage	Scenario	Task	GMV
Feature	Weixin Moments	pCTR	+0.42%
	Weixin Moments	pCVR	+2.53%
	Weixin Channels	matching	+0.70%
	Search Ads	matching	+1.75%
	Demand-Side Platform	pCTR	+0.76%
	Internet Service	pLTV	+0.93%
Module	Weixin Moments	pCVR	+0.92%
	Weixin Channels	pCVR	+0.92%
	Weixin Official Accounts	pCVR	+0.94%
	Content Platform	pCVR	+1.59%
	Audience Network	pCVR	+0.95%
Model	Weixin Channels	retrieval	+1.17%

(1). Whenever the label arrives (i.e., the user reacts to the ad), we update the weights of LFM4Ads and the downstream model. In addition, LFM4Ads is updated irregularly using content samples.

5.4 Launches and Productization

LFM4Ads has been productized in 10+ major online launches, lifting overall GMV by 2.45% across the platform. At the scenario level, Weixin Moments and Channels achieve GMV lifts of 2.16% and 1.18%, respectively. At the task level, pCTR, pCVR, and pLTV models bring improvements of 0.18%, 1.33%, and 0.44%, respectively.

Table 2 summarizes the online A/B test results of the three usages. Feature-level usage generally improves diverse scenarios and tasks, with the largest GMV gain of +2.53% on the Weixin Moments pCVR model, indicating substantial business impact. For module-level usage, LFM4Ads modules have been productized in multiple pCVR models, contributing to an overall GMV lift of 1.88%. In addition to the GMV gain, it also speeds up downstream convergence and reduces training costs. For model-level usage, a standalone retrieval model achieves a +1.17% GMV lift in Weixin Channels, while also improving CTR by 1.83%, CTCVR by 3.34%, reducing quick-slip rate by 0.36%, and increasing average dwell time by 1.66%.

5.5 Online Ablation

We conduct online ablation studies on Weixin Moments, a production scenario in Tencent's advertising system. As reported in Table 3, we derive the following findings:

First, faced with abundant content samples and scarce ad samples, the single-branch SUM degrades downstream performance. Nevertheless, the dual-branch SUM lifts GMV by 0.79%, indicating the necessity of decoupling users' commercial and non-commercial interests for ad tasks.

Second, LFM4Ads lifts GMV by 1.35%, which outperforms dual-branch SUM, demonstrating the superiority of our CR transfer. Furthermore, without aggregation or nonlinear fusion, AUC declines and GMV becomes non-positive, which confirms that our aggregation (1) and gating (3) are essential.

Table 3: Online ablations on transfer methods.

Transferred	Branch	Fusion	AUC	GMV
None	-	-	0.8515	-
$\mathbf{UR}(u)$	single	concat	0.8501	negative
$\mathbf{UR}(u)$	dual	concat	0.8520	+0.79%
$\mathbf{CR}(u), \beta = 0$	dual	gating	0.8513	negative
$\mathbf{CR}(u), \boldsymbol{\sigma} = \mathbf{id}$	dual	gating	0.8521	negative
$\mathbf{CR}(u)$	dual	gating	**0.8525**	**+1.35%**

Table 4: Online ablations on upstream domains.

	Static Only	+ Content Sequence	+ Ad Sequence	+ Both Sequences
AUC	-	+0.031	+0.042	+0.052

5.6 Cross-Domain Analysis

We examine how upstream behavior sequences from the content and ad domains contribute to downstream ad recommendation. The upstream baseline relies solely on non-sequential features. The upstream representations are transferred to the Weixin Channels pCTR model for ad recommendation.

As shown in Table 4, incorporating behavior sequences from both domains yields the largest AUC gain of 52‰. This exceeds the gain from ad-domain sequences alone by 10‰. Content-domain sequences alone yield a 31‰ AUC gain. These results suggest that content-domain behavior provides complementary information for ad prediction when combined with ad-domain behavior.

6 Conclusion

LFM4Ads is a pretrain-then-transfer framework for cross-domain ad recommendation, transferring upstream user, item, and cross representations at multiple granularities. Feature-level gating, module-level fine-tuning, and model-level retrieval accommodate different downstream architectures and deployment requirements. Offline experiments on KuaiRand-1K and production deployment on Tencent's advertising platform validate its effectiveness. Extending transferable recommendation representations to downstream multi-channel bidding with explicit budget and ROI constraints remains an important direction [10, 44].

Acknowledgments

This work is supported in part by the National Natural Science Foundation of China under Grant 624B2088.

GenAI Usage Disclosure

Generative AI assisted only with manuscript language, grammar, phrasing, and minor formatting. It did not generate research ideas, design methods, process or analyze data, conduct experiments, write or execute code, or produce results. All technical content, experimental results, claims, and conclusions were independently developed, reviewed, and verified by the authors.

References

[1] Ting Bai, Yudong Xiao, Bin Wu, Guojun Yang, Hongyong Yu, and Jian-Yun Nie. 2022. A Contrastive Sharing Model for Multi-Task Recommendation. In *Proceedings of the ACM Web Conference 2022*. Association for Computing Machinery, New York, NY, USA, 3239–3247. doi:10.1145/3485447.3512043

[2] Paul Baltescu, Haoyu Chen, Nikil Pancha, Andrew Zhai, Jure Leskovec, and Charles Rosenberg. 2022. ItemSage: Learning Product Embeddings for Shopping Recommendations at Pinterest. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. Association for Computing Machinery, New York, NY, USA, 2703–2711. doi:10.1145/3534678.3539170

[3] Jianxin Chang, Chenbin Zhang, Yiqun Hui, Dewei Leng, Yanan Niu, Yang Song, and Kun Gai. 2023. PEPNet: Parameter and Embedding Personalized Network for Infusing with Personalized Prior Information. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. Association for Computing Machinery, New York, NY, USA, 3795–3804. doi:10.1145/3580305.3599884

[4] Xiangyi Chen, Kousik Rajesh, Matthew Lawhon, Zelun Wang, Hanyu Li, Haomiao Li, Saurabh Vishwas Joshi, Pong Eksombatchai, Jaewon Yang, Yi-Ping Hsu, Jiajing Xu, and Charles Rosenberg. 2025. PinFM: Foundation Model for User Activity Sequences at a Billion-scale Visual Discovery Platform. In *Proceedings of the Nineteenth ACM Conference on Recommender Systems*. Association for Computing Machinery, New York, NY, USA, 381–390. doi:10.1145/3705328.3748050

[5] Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, Rohan Anil, Zakaria Haque, Lichan Hong, Vihan Jain, Xiaobing Liu, and Hemal Shah. 2016. Wide & Deep Learning for Recommender Systems. In *Proceedings of the 1st Workshop on Deep Learning for Recommender Systems*. Association for Computing Machinery, New York, NY, USA, 7–10. doi:10.1145/2988450.2988454

[6] Ningya Feng, Junwei Pan, Jialong Wu, Baixu Chen, Ximei Wang, Qian Li, Xian Hu, Jie Jiang, and Mingsheng Long. 2025. Long-Sequence Recommendation Models Need Decoupled Embeddings. In *The Thirteenth International Conference on Learning Representations*. https://openreview.net/forum?id=jkpGIxSsUD

[7] Chongming Gao, Shijun Li, Yuan Zhang, Jiawei Chen, Biao Li, Wenqiang Lei, Peng Jiang, and Xiangnan He. 2022. KuaiRand: An Unbiased Sequential Recommendation Dataset with Randomly Exposed Videos. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*. Association for Computing Machinery, New York, NY, USA, 3953–3957. doi:10.1145/3511808.3557624

[8] Mihajlo Grbovic and Haibin Cheng. 2018. Real-time Personalization using Embeddings for Search Ranking at Airbnb. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. Association for Computing Machinery, New York, NY, USA, 311–320. doi:10.1145/3219819.3219885

[9] Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. 2017. DeepFM: A Factorization-Machine based Neural Network for CTR Prediction. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*. International Joint Conferences on Artificial Intelligence Organization, California, USA, 1725–1731. doi:10.24963/ijcai.2017/239

[10] Hengquan Guo, Haobo Zhang, Junwei Pan, Shudong Huang, Nianhua Xie, Lei Xiao, Haijie Gu, Jie Jiang, and Xin Liu. 2026. Towards Safe and Optimal Online Bidding: A Modular Look-Ahead Lyapunov Framework. In *The Fourteenth International Conference on Learning Representations*. https://openreview.net/forum?id=AtbRCnvcrZ

[11] Xingzhuo Guo, Junwei Pan, Ximei Wang, Baixu Chen, Jie Jiang, and Mingsheng Long. 2024. On the Embedding Collapse when Scaling up Recommendation Models. In *Proceedings of the 41st International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 235)*. PMLR, 16891–16909. https://proceedings.mlr.press/v235/guo24e.html

[12] Jie Hu, Li Shen, and Gang Sun. 2018. Squeeze-and-Excitation Networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. IEEE Computer Society, Los Alamitos, CA, USA, 7132–7141. doi:10.1109/CVPR.2018.00745

[13] Interactive Advertising Bureau. 2025. *IAB/PwC Internet Advertising Revenue Report: Full Year 2024*. Industry Report. PwC Advisory Services LLC. Accessed: 2026-08-23. https://www.iab.com/insights/internet-advertising-revenue-report-full-year-2024/

[14] Yu Kang, Junwei Pan, Jipeng Jin, Shudong Huang, Xiaofeng Gao, and Lei Xiao. 2026. Towards Unifying Feature Interaction Models for Click-Through Rate Prediction. In *Machine Learning and Knowledge Discovery in Databases. Research Track (Lecture Notes in Computer Science, Vol. 16017)*. Springer Nature Switzerland, Cham, Switzerland, 451–467. doi:10.1007/978-3-032-06096-9_26

[15] Dai Li, Kevin Course, Wei Li, Hongwei Li, Jie Hua, Yiqi Chen, Zhao Zhu, Rui Jian, Xuan Cao, Bi Xue, Yu Shi, Jing Qian, Kai Ren, Matt Ma, Qunshu Zhang, and Rui Li. 2025. *Realizing Scaling Laws in Recommender Systems: A Foundation-Expert Paradigm for Hyperscale Model Deployment*. arXiv:2508.02929 [cs.IR] https://arxiv.org/abs/2508.02929

[16] Honghao Li, Lei Sang, Yi Zhang, and Yiwen Zhang. 2024. SimCEN: Simple Contrast-enhanced Network for CTR Prediction. In *Proceedings of the 32nd ACM International Conference on Multimedia*. Association for Computing Machinery, New York, NY, USA, 2311–2320. doi:10.1145/3664647.3681203

[17] Wenjie Li, Zhongren Wang, Jinpeng Wang, Shu-Tao Xia, Jile Zhu, Mingjian Chen, Jiangke Fan, Jia Cheng, and Jun Lei. 2024. ReFer: Retrieval-Enhanced Vertical Federated Recommendation for Full Set User Benefit. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*. Association for Computing Machinery, New York, NY, USA, 1763–1773. doi:10.1145/3626772.3657763

[18] Wenjie Li, Zhongren Wang, and Shu-Tao Xia. 2026. Self-supervised Vertical Federated Advertising via Fine-Grained Multi-Scale Perturbation–Detection. In *The 22nd International Conference on Advanced Data Mining and Applications (ADMA 2026)*.

[19] Wenjie Li and Shu-Tao Xia. 2026. Prefer: Prototype-Guided Retrieval Utilization for Vertical Federated Recommendation. In *The 27th International Web Information Systems Engineering Conference (WISE 2026)*.

[20] Wenjie Li, Shu-Tao Xia, Jiangke Fan, Teng Zhang, and Xingxing Wang. 2026. Vertical Semi-Federated Learning for Efficient Online Advertising. In *Proceedings of the ACM Web Conference 2026*. Association for Computing Machinery, New York, NY, USA, 8685–8688. doi:10.1145/3774904.3792940

[21] Xiangyang Li, Bo Chen, Lu Hou, and Ruiming Tang. 2025. CTRL: Connect Collaborative and Language Model for CTR Prediction. *ACM Transactions on Recommender Systems* 4, 2 (2025), 23 pages. doi:10.1145/3713080

[22] Yangning Li, Shirong Ma, Xiaobin Wang, Shen Huang, Chengyue Jiang, Hai-Tao Zheng, Pengjun Xie, Fei Huang, and Yong Jiang. 2024. EcomGPT: Instruction-Tuning Large Language Models with Chain-of-Task Tasks for E-commerce. *Proceedings of the AAAI Conference on Artificial Intelligence* 38, 17 (2024), 18582–18590. doi:10.1609/aaai.v38i17.29820

[23] Mingfu Liang, Xi Liu, Rong Jin, Boyang Liu, Qiuling Suo, Qinghai Zhou, Song Zhou, Laming Chen, Hua Zheng, Zhiyuan Li, Shali Jiang, Jiyan Yang, Xiaozhen Xia, Fan Yang, Yasmine Badr, Ellie Wen, Shuyu Xu, Hansey Chen, Zhengyu Zhang, Jade Nie, Chunzhi Yang, Zhichen Zeng, Weilin Zhang, Xingliang Huang, Qianru Li, Shiquan Wang, Evelyn Lyu, Wenjing Lu, Rui Zhang, Wenjun Wang, Jason Rudy, Mengyue Hang, Kai Wang, Bo Long, Wenlin Chen, Santanu Kolay, and Huayu Li. 2025. External Large Foundation Model: How to Efficiently Serve Trillions of Parameters for Online Ads Recommendation. In *Companion Proceedings of the ACM on Web Conference 2025*. Association for Computing Machinery, New York, NY, USA, 344–353. doi:10.1145/3701716.3715223

[24] Zhutian Lin, Junwei Pan, Haibin Yu, Xi Xiao, Ximei Wang, Zhixiang Feng, Shifeng Wen, Shudong Huang, Dapeng Liu, and Lei Xiao. 2025. Crocodile: Cross Experts Covariance for Disentangled Learning in Multi-Domain Recommendation. In *Proceedings of the 34th ACM International Conference on Information & Knowledge Management*. Association for Computing Machinery, New York, NY, USA, 1839–1849. doi:10.1145/3746252.3761332

[25] Dugang Liu, Chaohua Yang, Xing Tang, Yejing Wang, Fuyuan Lyu, Weihong Luo, Xiuqiang He, Zhong Ming, and Xiangyu Zhao. 2024. MultiFS: Automated Multi-Scenario Feature Selection in Deep Recommender Systems. In *Proceedings of the 17th ACM International Conference on Web Search and Data Mining*. Association for Computing Machinery, New York, NY, USA, 434–442. doi:10.1145/3616855.3635859

[26] Ilya Loshchilov and Frank Hutter. 2019. Decoupled Weight Decay Regularization. In *International Conference on Learning Representations*. https://openreview.net/forum?id=Bkg6RiCqY7

[27] Jiaqi Ma, Zhe Zhao, Xinyang Yi, Jilin Chen, Lichan Hong, and Ed H. Chi. 2018. Modeling Task Relationships in Multi-task Learning with Multi-gate Mixture-of-Experts. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. Association for Computing Machinery, New York, NY, USA, 1930–1939. doi:10.1145/3219819.3220007

[28] Junwei Pan, Yizhi Mao, Alfonso Lobos Ruiz, Yu Sun, and Aaron Flores. 2019. Predicting Different Types of Conversions with Multi-Task Learning in Online Advertising. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. Association for Computing Machinery, New York, NY, USA, 2689–2697. doi:10.1145/3292500.3330783

[29] Junwei Pan, Jian Xu, Alfonso Lobos Ruiz, Wenliang Zhao, Shengjun Pan, Yu Sun, and Quan Lu. 2018. Field-weighted Factorization Machines for Click-Through Rate Prediction in Display Advertising. In *Proceedings of the 2018 World Wide Web Conference*. International World Wide Web Conferences Steering Committee, Republic and Canton of Geneva, Switzerland, 1349–1357. doi:10.1145/3178876.3186040

[30] Junwei Pan, Wei Xue, Ximei Wang, Haibin Yu, Xun Liu, Shijie Quan, Xueming Qiu, Dapeng Liu, Lei Xiao, and Jie Jiang. 2024. Ads Recommendation in a Collapsed and Entangled World. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. Association for Computing Machinery, New York, NY, USA, 5566–5577. doi:10.1145/3637528.3671607

[31] Junwei Pan, Zhilin Zhang, Han Zhu, Jian Xu, Jie Jiang, and Bo Zheng. 2025. Computational Advertising: Recent Advances. In *Companion Proceedings of the ACM on Web Conference 2025*. Association for Computing Machinery, New York, NY, USA, 37–40. doi:10.1145/3701716.3715872

[32] Nikil Pancha, Andrew Zhai, Jure Leskovec, and Charles Rosenberg. 2022. PinnerFormer: Sequence Modeling for User Representation at Pinterest. In *Proceedings*

of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining. Association for Computing Machinery, New York, NY, USA, 3702–3712. doi:10.1145/3534678.3539156

[33] Bo Peng, Xinyi Ling, Ziru Chen, Huan Sun, and Xia Ning. 2024. eCeLLM: Generalizing Large Language Models for E-commerce from Large-scale, High-quality Instruction Data. In *Proceedings of the 41st International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 235)*. PMLR, 40215–40257. https://proceedings.mlr.press/v235/peng24c.html

[34] Qi Pi, Weijie Bian, Guorui Zhou, Xiaoqiang Zhu, and Kun Gai. 2019. Practice on Long Sequential User Behavior Modeling for Click-Through Rate Prediction. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. Association for Computing Machinery, New York, NY, USA, 2671–2679. doi:10.1145/3292500.3330666

[35] Steffen Rendle. 2010. Factorization Machines. In *Proceedings of the 10th IEEE International Conference on Data Mining*. IEEE Computer Society, Los Alamitos, CA, USA, 995–1000. doi:10.1109/ICDM.2010.127

[36] Xiang-Rong Sheng, Feifan Yang, Litong Gong, Biao Wang, Zhangming Chan, Yujing Zhang, Yueyao Cheng, Yong-Nan Zhu, Tiezheng Ge, Han Zhu, Yuning Jiang, Jian Xu, and Bo Zheng. 2024. Enhancing Taobao Display Advertising with Multimodal Representations: Challenges, Approaches and Insights. In *Proceedings of the 33rd ACM International Conference on Information and Knowledge Management*. Association for Computing Machinery, New York, NY, USA, 4858–4865. doi:10.1145/3627673.3680068

[37] Kaize Shi, Xueyao Sun, Dingxian Wang, Yinlin Fu, Guandong Xu, and Qing Li. 2025. LLaMA-E: Empowering E-commerce Authoring with Object-Interleaved Instruction Following. In *Proceedings of the 31st International Conference on Computational Linguistics*. Association for Computational Linguistics, Abu Dhabi, UAE, 870–885. https://aclanthology.org/2025.coling-main.58/

[38] Liangcai Su, Junwei Pan, Ximei Wang, Xi Xiao, Shijie Quan, Xihua Chen, and Jie Jiang. 2024. STEM: Unleashing the Power of Embeddings for Multi-Task Recommendation. *Proceedings of the AAAI Conference on Artificial Intelligence* 38, 8 (2024), 9002–9010. doi:10.1609/aaai.v38i8.28749

[39] Yang Sun, Junwei Pan, Alex Zhang, and Aaron Flores. 2021. FM^2: Field-matrixed Factorization Machines for Recommender Systems. In *Proceedings of the Web Conference 2021*. Association for Computing Machinery, New York, NY, USA, 2828–2837. doi:10.1145/3442381.3449930

[40] Hongyan Tang, Junning Liu, Ming Zhao, and Xudong Gong. 2020. Progressive Layered Extraction (PLE): A Novel Multi-Task Learning (MTL) Model for Personalized Recommendations. In *Proceedings of the 14th ACM Conference on Recommender Systems*. Association for Computing Machinery, New York, NY, USA, 269–278. doi:10.1145/3383313.3412236

[41] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. 2018. *Representation Learning with Contrastive Predictive Coding*. arXiv:1807.03748 [cs.LG] https://arxiv.org/abs/1807.03748

[42] Ruoxi Wang, Rakesh Shivanna, Derek Z. Cheng, Sagar Jain, Dong Lin, Lichan Hong, and Ed H. Chi. 2021. DCN V2: Improved Deep & Cross Network and Practical Lessons for Web-scale Learning to Rank Systems. In *Proceedings of the Web Conference 2021*. Association for Computing Machinery, New York, NY, USA, 1785–1797. doi:10.1145/3442381.3450078

[43] Zhoumeng Wang. 2024. Empowering Few-Shot Recommender Systems With Large Language Models-Enhanced Representations. *IEEE Access* 12 (2024), 29144–29153. doi:10.1109/ACCESS.2024.3368027

[44] Hongchang Wu, Weitong Ou, Hengquan Guo, Zixin Shao, Hongyan Xue, Junwei Pan, Shudong Huang, Zhangbin Zhu, Xin Liu, Nianhua Xie, Lei Xiao, and Haijie Gu. 2026. GRB: A Generative Reinforcement Bidding Framework for Multi-Channel Online Advertising. In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*. Association for Computing Machinery, New York, NY, USA, 8225–8235. doi:10.1145/3770855.3818427

[45] Haoran Xin, Ying Sun, Chao Wang, and Hui Xiong. 2025. LLMCDSR: Enhancing Cross-Domain Sequential Recommendation with Large Language Models. *ACM Transactions on Information Systems* 43, 5, Article 120 (2025), 33 pages. doi:10.1145/3715099

[46] Mingjia Yin, Junwei Pan, Hao Wang, Ximei Wang, Shangyu Zhang, Jie Jiang, Defu Lian, and Enhong Chen. 2025. From Feature Interaction to Feature Generation: A Generative Paradigm of CTR Prediction Models. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 72393–72413. https://proceedings.mlr.press/v267/yin25c.html

[47] Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. 2014. How transferable are features in deep neural networks?. In *Advances in Neural Information Processing Systems*, Vol. 27. Curran Associates, Inc., 3320–3328. https://proceedings.neurips.cc/paper_files/paper/2014/hash/532a2f85b6977104bc93f8580abbb330-Abstract.html

[48] Wei Zhang, Dai Li, Chen Liang, Fang Zhou, Zhongke Zhang, Xuewei Wang, Ru Li, Yi Zhou, Yaning Huang, Dong Liang, Kai Wang, Zhangyuan Wang, Zhengxing Chen, Fenggang Wu, Minghai Chen, Huayu Li, Yunnan Wu, Zhan Shu, Mindi Yuan, and Sri Reddy. 2024. Scaling User Modeling: Large-scale Online User Representations for Ads Personalization in Meta. In *Companion Proceedings of the ACM Web Conference 2024*. Association for Computing Machinery, New York, NY, USA, 47–55. doi:10.1145/3589335.3648301

[49] Guorui Zhou, Na Mou, Ying Fan, Qi Pi, Weijie Bian, Chang Zhou, Xiaoqiang Zhu, and Kun Gai. 2019. Deep Interest Evolution Network for Click-Through Rate Prediction. *Proceedings of the AAAI Conference on Artificial Intelligence* 33, 1 (2019), 5941–5948. doi:10.1609/aaai.v33i01.33015941

[50] Haolin Zhou, Junwei Pan, Xinyi Zhou, Xihua Chen, Jie Jiang, Xiaofeng Gao, and Guihai Chen. 2024. Temporal Interest Network for User Response Prediction. In *Companion Proceedings of the ACM Web Conference 2024*. Association for Computing Machinery, New York, NY, USA, 413–422. doi:10.1145/3589335.3648340

[51] Jie Zhou, Xianshuai Cao, Wenhao Li, Lin Bo, Kun Zhang, Chuan Luo, and Qian Yu. 2023. HiNet: Novel Multi-Scenario & Multi-Task Learning with Hierarchical Information Extraction. In *Proceedings of the 39th IEEE International Conference on Data Engineering*. IEEE Computer Society, Los Alamitos, CA, USA, 2969–2975. doi:10.1109/ICDE55515.2023.00227

[52] Zheli Zhou, Chenxu Zhu, Jianghao Lin, Bo Chen, Ruiming Tang, Yong Yu, and Weinan Zhang. 2026. Generative Representational Learning of Foundation Models for Recommendation. In *Database Systems for Advanced Applications (Lecture Notes in Computer Science, Vol. 16535)*. Springer Nature Singapore, Singapore, 552–568. doi:10.1007/978-981-92-0363-5_34