

Machine Learning

Fine-tuning

Mostafa S. Ibrahim

Teaching, Training and Coaching for more than a decade!

Artificial Intelligence & Computer Vision Researcher

PhD from Simon Fraser University - Canada

Bachelor / MSc from Cairo University - Egypt

Ex-(Software Engineer / ICPC World Finalist)



© 2023 All rights reserved.

Please do not reproduce or redistribute this work without permission from the author

Exploring pretrained models

- There are many models that are trained on popular tasks
- Some of them, like image classifiers are already in your framework
- Let's explore PyTorch Alexnet

AlexNet


- You can load the pretrained model from pytorch
- The code is arranged nicely as
 - Features attribute: it has all the CNN layers and ends with last heatmap
 - Classifier attribute: the last fully connected layers
 - Note: different networks might be arranged differently

```
import torch
import torchvision.models as models
import torch.nn as nn

alexnet_model = models.alexnet(pretrained=True)
print(alexnet_model)
print(alexnet_model.features)
print(alexnet_model.classifier)
```

Fine-tuning

- Assume a pre-trained exists for a CNN train with 1 million images of wide diversity of scenes to classify 1000 classes
- Except the last 2 layers, all these CNN layers has a lot of generic features
- What If I want to classify 5 classes for images about a person action? A specific animal species?
- We can simply drop the last 2 layers only and add 2 layers ending with classes
- Now, fine-tune this network with way less images!



Fine-tuning

- Fine-tuning a Convolutional Neural Network (CNN) involves taking a pre-trained network and adapting its parameters to a new, but **similar** problem
 - Choose a Pre-trained Model (e.g. imagenet, resnet50, etc)
 - Prepare Your Dataset (which can be a small dataset)
 - Modify the Network Architecture: Replace the final fully connected layer(s) with new layers suited to your specific problem.
 - Initialize the weights of new layers
 - Where to freeze?
 - You may want to freeze the early layers and never update as they are already good low-level to medium level features. Only fine-tune the high-level features
 - Hyperparameter Tuning: Explore relevant hyperparameters. You may start from a **lower** LR and train for a **few** epochs (already weights went in a long journey)

Fine-tuning AlexNet - Simple

- Assume we wanted to fine-tune alexnet for CIFAR10 dataset
 - This dataset is small dimension images with 10 different classes

airplane



automobile



bird



cat



deer



dog



frog



horse



ship



truck



Fine-tuning AlexNet - Simple

- Assume we just want to replace one of the fully connected layers
- Let's explore what we have
- It seems from `model.classifier.children()`, the classifier actually has 3 FC
- Let's say we want to make last layers as
 - $9216 \Rightarrow 1096$
 - $4096 \Rightarrow 1024$
 - $1024 \Rightarrow 10$
- Then we need to remove last 2 FCs
 - We remove 3 layers
 - L/R/L

```
In[2]: list(model.classifier.children())
Out[2]:
[Dropout(p=0.5, inplace=False),
 Linear(in_features=9216, out_features=4096, bias=True),
 ReLU(inplace=True),
 Dropout(p=0.5, inplace=False),
 Linear(in_features=4096, out_features=4096, bias=True),
 ReLU(inplace=True),
 Linear(in_features=4096, out_features=1000, bias=True)]
```

Fine-tuning AlexNet - Simple

```
# Remove the last fully-connected layer
features = list(model.classifier.children())[:-3] features:

# Add your custom fully connected layers
features.extend([
    nn.Linear(4096, 1024),
    nn.ReLU(inplace=True),
    nn.Linear(1024, 10) # CIFAR-10 has 10 nodes
])

# Replace the model's classifier with your custom classifier
model.classifier = nn.Sequential(*features)
```


Fine-tuning AlexNet - Simple

- Now, your model is ready for normal train/test cycle
- Refer to the code for full normal details
- Tip: we refer to such critical pretrained models as **backbones**


```
In[2]: list(model.classifier.children())  
Out[2]:  
[Dropout(p=0.5, inplace=False),  
 Linear(in_features=9216, out_features=4096, bias=True),  
 ReLU(inplace=True),  
 Dropout(p=0.5, inplace=False),  
 Linear(in_features=4096, out_features=1024, bias=True),  
 ReLU(inplace=True),  
 Linear(in_features=1024, out_features=10, bias=True)]
```

Fine-tuning AlexNet - Complex

- What if we want
 - Use only a part of the pretrained CNN
 - Also freeze these layers
 - Extend the CNN with our new CNN layers
 - Then build a relevant FC layers

Fine-tuning AlexNet - Complex

- What if we want to keep only the first 3 Conv2D filters?
 - Then we need to keep the first 8 layers



```
In[3]: list(model.features.children())
Out[3]:
[Conv2d(3, 64, kernel_size=(11, 11), stride=(4, 4), padding=(2, 2)),
 ReLU(inplace=True),
 MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False),
 Conv2d(64, 192, kernel_size=(5, 5), stride=(1, 1), padding=(2, 2)),
 ReLU(inplace=True),
 MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False),
 Conv2d(192, 384, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)),
 ReLU(inplace=True),
 Conv2d(384, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)),
 ReLU(inplace=True),
 Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)),
 ReLU(inplace=True),
 MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False)]
```

Fine-tuning AlexNet - Complex

```
11  # Get the first 3 Conv2D compoenets
12  features = list(model.features.children())[:8]
13
14  # Freeze their layers (never update weights)
15  for layer in features:
16      for param in layer.parameters():
17          param.requires_grad = False
18
19  # Extend the model with custom layers
20  features.extend([
21      nn.Conv2d(192, 256, kernel_size=3, stride=1, padding=1),
22      nn.ReLU(inplace=True),
23      nn.MaxPool2d(kernel_size=3, stride=2),
24      nn.AdaptiveAvgPool2d((6, 6))
25  ])
26
27  # Replace the feature layers
28  model.features = nn.Sequential(*features)
```

Fine-tuning AlexNet - Complex

- Last layer ended with 256 filters and 6x6 grid
- Let's update our FC layers
- Now, train normally

```
30 # Add custom classifier layers (fully connected layers)
31 model.classifier = nn.Sequential(
32     nn.Dropout(),
33     nn.Linear(256 * 6 * 6, 4096),
34     nn.ReLU(inplace=True),
35     nn.Dropout(),
36     nn.Linear(4096, 2048),
37     nn.ReLU(inplace=True),
38     nn.Linear(2048, 10)
39 )
40
```

Fine-tuning **ResNet** - Complex

- Sometimes, you want your backbone part to be the early stage of another model
 - This is just matter of coding
- Prepare the pretrained model and pass it to your new model
- Let's say we want to remove the last 4 main blocks of resnet

```
original_model = resnet50(pretrained=True)

# Remove the last 4 main blocks (layer3, layer4, avgpool, fc)
layers = list(original_model.children())[:-4]
# By debugging, our last layer's shape: 512 * 28 * 28

# Create truncated model
truncated_model = nn.Sequential(*layers)
```

Extend the truncated model with custom layers

```
class ExtendedModel(nn.Module):  
    def __init__(self, backbone):  
        super(ExtendedModel, self).__init__()  
        self.backbone = backbone  
        self.fc_layers = nn.Sequential(  
            nn.Linear(512 * 28 * 28, 265),  
            nn.ReLU(),  
            nn.Linear(265, 128),  
            nn.ReLU(),  
            nn.Linear(128, 10)  
        )  
  
    def forward(self, x):  
        x = self.backbone(x)  
        x = x.view(x.size(0), -1)  
        x = self.fc_layers(x)  
        return x  
  
model = ExtendedModel(truncated_model)
```


Features Extraction

- Another possible scenario (pre trained / fine tuned networks) is features extraction
- This typically happens from the layer **before the last layer**
- For example, the last layer of resnet 50 has 1000 features for categories
 - The one before it has 2048 features
 - Then we can pass an image to the model and extract 2048 equal representation

```
model = models.resnet50(pretrained=True)
model = nn.Sequential(*(list(model.children())[:-1]))
```

```
dnn_repr = model(preprocessed_image)
dnn_repr = dnn_repr.view(1, -1)
```


“Acquire knowledge and impart it to the people.”

“Seek knowledge from the Cradle to the Grave.”

