SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

SEARCH: Search

Package org.springframework.data.jpa.repository

# Interface JpaRepository<T,ID>

### All Superinterfaces:

CrudRepository CrudRe

#### All Known Subinterfaces:

EnversRevisionRepository<T,ID,N>, JpaRepositoryImplementation<T,ID>

### All Known Implementing Classes:

QuerydslJpaRepository, SimpleJpaRepository

@NoRepositoryBean<sup>™</sup>

public interface JpaRepository<T,ID>

extends ListCrudRepository d<T,ID>, ListPagingAndSortingRepository d<T,ID>, QueryByExampleExecutor d<T>

JPA specific extension of Repository™.

#### Author:

Oliver Gierke, Christoph Strobl, Mark Paluch, Sander Krabbenborg, Jesse Wouters, Greg Turnquist, Jens Schauder

## Method Summary

All Methods In	stance Methods	Abstract Methods	Default Methods	Deprecated Methods	
Modifier and Type	Method		Description	n	
void	deleteAllByI	dInBatch(Iterable <sup>©</sup> <1	Do ids) Deletes the	e entities identified by the given ids using a single query.	
void	deleteAllInBatch()		Deletes all	Deletes all entities in a batch call.	
void	deleteAllInB	Batch(Iterable <sup>©</sup> <t> er</t>	tities) Deletes the	e given entities in a batch which means it will create a single query.	
default void	deleteInBato	:h( <b>Iterable</b> <sup>©</sup> < <b>T</b> > entit		e <b>d.</b> eAllInBatch(Iterable) instead.	
<s extends="" t=""> List<sup>©</sup><s></s></s>	findAll(Exam	ı <b>ple</b> <sup>☑</sup> <s> example)</s>			
<s extends="" t=""> List<sup>©</sup><s></s></s>	findAll(Exam	n <b>ple</b> ⊡ <s> example, <b>Sor</b></s>	t <sup>™</sup> sort)		
void	flush()		Flushes all	pending changes to the database.	
Т	getById(ID id)		Deprecate use getRef	e <b>d.</b> ferenceBvId(ID) instead.	