# cSlope

## Verification Manual

Limit equilibrium slope stability analysis — comparison with published results

This document presents factors of safety computed by cSlope for 164 verification problems from the geotechnical literature and from the verification manuals of other slope stability programs, next to the values the sources publish and the range of other programs' results, and for the 6 benchmark models bundled with the program.

| | |
|---|---|
| Program version | cSlope 0.1.0 (commit 576efd4) |
| Report generated | 2026-10-16 |
| Problems | 164 |
| Values published by the sources | 170 |
| cSlope analyses | 306 |

*Generated automatically by packages/desktop/scripts/verification-report.ts from the engine's verification test cases.*

# 1 Introduction

Each problem below is defined once in the engine's verification data (packages/engine/src/verification/problems.ts). The same definitions are run by the automated test suite on every change, so the values in this report are the values the program computes.

## Analysis settings

| Setting | Value |
|---|---|
| Slip surfaces | Circular, or the non-circular surface the source gives. Fixed surfaces where the source gives one, otherwise a critical-circle search (with non-circular optimisation where stated). |
| Number of slices | 50 unless the problem states otherwise |
| Search | 4000 entry/exit combinations plus 2000 refined around the best surfaces |
| Convergence tolerance | 0.001 on the factor of safety; 0.001 with non-circular optimisation |
| Methods | Bishop simplified, Janbu simplified (uncorrected unless stated), Morgenstern-Price with half-sine interslice function; Spencer = Morgenstern-Price with a constant interslice function |
| Pore pressure | Piezometric line; head = vertical distance below the line (default, the usual convention). Checks marked "phreatic correction" use vertical distance × $\cos^2\theta$. |
| Unit weight of water | 9.81 kN/m³ |

## Units

Problems published in imperial units without water are entered in their own units (ft, psf, pcf); the factor of safety is dimensionless. Problems with water are converted to SI because the program uses $\gamma w$ = 9.81 kN/m³ (62.4 pcf = 9.80 kN/m³, < 0.1 % difference).

## Source of the input data

The input data were transcribed from the publications and from the verification manuals of other slope stability programs, most of them commercial, and cross-checked against an independent open-source transcription of the same problems. For each problem the report lists the values the source publishes, with the method where the source names one; some are hand calculations, charts, trial wedges or finite elements rather than the method of slices. For each analysis cSlope runs, it gives the range of results that other programs publish in their verification manuals, without naming the programs, and cSlope's result. The report presents the results; it does not mark them as passed or failed. Problem ids are cSlope's own: a number is one slope, a letter a variant of it.

# 2 Summary of results

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V001 | Arai & Tagyo (1985) example 1 | 1.451; 1.265; 1.357 | Bishop simplified | 1.409–1.417 | 1.404 |
| | | | Morgenstern-Price (half-sine) | 1.414 | 1.401 |
| | | | Spencer, non-circular | 1.386 | 1.385 |
| | | | Janbu simplified, non-circular | – | 1.253 |
| | | | Janbu corrected, non-circular | – | 1.346 |
| V002 | Arai & Tagyo (1985) example 2, three layers | 0.417; 0.405; 0.43; 0.43; 0.39–0.44; 0.39 | Bishop simplified | 0.420 | 0.419 |
| | | | Spencer, non-circular | 0.414 | 0.412 |
| | | | Janbu simplified, non-circular | – | 0.393 |
| | | | Janbu corrected, non-circular | – | 0.413 |
| V003 | Arai & Tagyo (1985) example 3, water table | 1.138; 0.995; 1.071 | Bishop simplified | 1.112–1.118 | 1.113 |
| | | | Spencer | 1.118 | 1.113 |
| | | | Janbu corrected | 1.131 | 1.124 |
| | | | Janbu simplified, non-circular | – | 0.967 |
| | | | Janbu corrected, non-circular | – | 1.048 |
| V004a | 4:1 slope, Mohr-Coulomb fit | 2.66 | Spencer | 2.794 | 2.802 |
| | | | Janbu simplified | 2.662 | 2.677 |
| V004b | Baker (2003) ex. 2 slope, Mohr-Coulomb iteration parameters | 2.64; 2.66 | Janbu simplified | 2.610 | 2.609 |
| | | | Spencer | 2.696 | 2.666 |
| V005 | Baker (1993) dam, end of construction, infinite-slope face | 2.50 | Bishop simplified | – | 2.523 |
| | | | Spencer | – | 2.523 |
| V006 | Baker (2001) planar surface | 1.35 | Spencer | 1.351 | 1.352 |
| | | | Janbu simplified | 1.351 | 1.352 |
| V007a | Baker (2003) ex. 1, Mohr-Coulomb, Janbu simplified on the reference circle | 1.50 | Janbu simplified | 1.469 | 1.468 |
| V007b | Baker (2003) ex. 1 slope, Mohr-Coulomb iteration parameters | 0.97; 1.50 | Janbu simplified | 0.957 | 0.955 |
| | | | Spencer | 0.981 | 0.978 |
| V007c | Baker (2003) ex. 3, Janbu simplified | 1.35 | Janbu simplified | 1.291 | 1.290 |
| V008a | Baker (2003) example 1, Mohr-Coulomb fit | 1.50 | Spencer | 1.536 | 1.519 |
| V008b | Baker (2003) London clay slope, Mohr-Coulomb fit | 1.35 | Spencer | 1.366 | 1.365 |
| V009a | Baker & Leshchinsky clay-core dam, reservoir and crest crack | – | Spencer | 1.925 | 1.926 |
| V009b | Baker & Leshchinsky dam, Baker's non-circular surface | 1.91 | Spencer | – | 1.882 |
| V009c | Baker & Leshchinsky clay-core dam, critical surface search | 1.91 | Spencer, non-circular | 1.868 | 1.868 |
| V010 | Borges & Cardoso embankment 2 (geosynthetic) | 1.15 | Morgenstern-Price (half-sine) | 1.171 | 1.162 |
| | | | Bishop simplified | 1.170 | 1.164 |
| V011a | Borges & Cardoso embankment 3, H = 7 m, circle A | 1.25 | Bishop simplified | 1.230 | 1.219 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V011b | Borges & Cardoso embankment 3, H = 7 m, circle B | 1.19 | Bishop simplified | 1.220 | 1.216 |
| V012 | Borges & Cardoso embankment 3, H = 8.75 m, circle C | 0.99 | Bishop simplified | 0.980 | 0.982 |
| V013a | Cai & Ugai (2000) slope, no pile (see V013b, V013c, V013d and V013e for the pile rows) | 1.13 | Bishop simplified | 1.140 | 1.143 |
| V013b | Cai & Ugai slope, pile row D1/D = 2 | 1.54 | Bishop simplified | 1.540 | 1.541 |
| V013c | Cai & Ugai slope, pile row D1/D = 3 | 1.37 | Bishop simplified | 1.430 | 1.450 |
| V013d | Cai & Ugai slope, pile row D1/D = 4 | 1.31 | Bishop simplified | 1.330 | 1.342 |
| V013e | Cai & Ugai slope, pile row D1/D = 6 | 1.25 | Bishop simplified | 1.250 | 1.260 |
| V014 | Nailed wall, 14 rows, deep wedge | – | Janbu corrected | 1.448–1.460 | 1.448 |
| | | | Spencer | 1.576 | 1.575 |
| V015 | Soldier-pile tieback wall | – | Janbu corrected | 1.479 | 1.476 |
| | | | Janbu simplified | 1.446 | 1.442 |
| V016a | Stepped gabion wall, equivalent cohesion | – | Bishop simplified | 1.787–1.790 | 1.791 |
| | | | Spencer | 1.791 | 1.797 |
| V016b | Stepped gabion wall, mesh as geosynthetic supports | – | Bishop simplified | 1.830–1.835 | 1.830 |
| | | | Spencer | 1.839 | 1.835 |
| V016c | Gabion wall with weak joint layers | – | Bishop simplified | 1.790–1.799 | 1.791 |
| | | | Spencer | 1.803 | 1.797 |
| V017a | Vancouver gabion wall, equivalent cohesion | – | Bishop simplified | 1.373–1.382 | 1.382 |
| | | | Spencer | 1.386 | 1.398 |
| V017b | Vancouver gabion wall, mesh as geosynthetic supports | – | Bishop simplified | 1.378–1.382 | 1.382 |
| V018 | Chen & Shao (1988) frictionless 60° slope, Prandtl mechanism | 1.05 | Spencer | 1.051 | 1.052 |
| | | | Morgenstern-Price (specified f(x)) | 1.009–1.017 | 1.008 |
| V019 | Cheng et al. 11 m homogeneous slope | 1.383 | Spencer | 1.380–1.398 | 1.398 |
| | | | Bishop simplified | 1.401 | 1.401 |
| V020 | Cheng et al. benched slope, global minimum | 1.327 | Spencer | 1.336–1.338 | 1.338 |
| | | | Bishop simplified | 1.342 | 1.343 |
| V021a | Chowdhury & Xu (1995) example 1, Congress Street cut, circle tangent to the base of clay 2 | 1.128 | Morgenstern-Price (half-sine) | 1.132 | 1.128 |
| | | | Bishop simplified | – | 1.128 |
| | | | Bishop simplified (60 slices) | 1.128 | 1.128 |
| V021b | Chowdhury & Xu (1995) example 1, Congress Street cut, circle tangent to the base of clay 3 | 1.109 | Morgenstern-Price (half-sine) | 1.116 | 1.110 |
| | | | Bishop simplified | – | 1.110 |
| | | | Bishop simplified (60 slices) | 1.109 | 1.110 |
| V021c | Chowdhury & Xu (1995) example 2, Congress Street cut, circle tangent to the base of clay 2 | 1.1096 | Morgenstern-Price (half-sine) | 1.110 | 1.108 |
| | | | Bishop simplified | 1.108 | 1.108 |
| V021d | Chowdhury & Xu (1995) example 2, Congress Street cut, circle tangent to the base of clay 3 | 1.0639 | Morgenstern-Price (half-sine) | 1.063 | 1.058 |
| | | | Bishop simplified | 1.058 | 1.058 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V021e | Chowdhury & Xu (1995) example 3, Congress Street cut, circle tangent to the base of clay 2 | 2.2343 | Morgenstern-Price (half-sine) | 2.248 | 2.245 |
| | | | Bishop simplified | 2.245 | 2.245 |
| V021f | Chowdhury & Xu (1995) example 3, Congress Street cut, circle tangent to the base of clay 3 | 2.1396 | Morgenstern-Price (half-sine) | 2.138 | 2.128 |
| | | | Bishop simplified | 2.128 | 2.128 |
| V021g | Chowdhury & Xu (1995) example 4, Congress Street cut, circle tangent to the base of clay 2 | 1.4239 | Morgenstern-Price (half-sine) | 1.422 | 1.428 |
| | | | Bishop simplified | – | 1.428 |
| V022a | Chowdhury & Xu (1995) example 5, embankment on soft clay, circle tangent to y = 15 | 1.1625 | Morgenstern-Price (half-sine) | 1.158 | 1.157 |
| | | | Bishop simplified | – | 1.159 |
| | | | Bishop simplified (60 slices) | 1.160 | 1.159 |
| V022b | Chowdhury & Xu (1995) example 5, embankment on soft clay, circle tangent to y = 5 | 1.1479 | Morgenstern-Price (half-sine) | 1.178 | 1.174 |
| | | | Bishop simplified | 1.185 | 1.177 |
| V023 | LASH terminal trench, Duncan's Taylor series example | 1.17 | Spencer | 1.145 | 1.138 |
| V024 | Dam on a layered foundation with artesian uplift, piezometric line (D&W fig. 6.39) | 1.57 | Bishop simplified | 1.563–1.572 | 1.572 |
| | | | Spencer | 1.557 | 1.562 |
| V025 | Duncan & Wright fig. 6.38, piezometric line | 1.141 | Bishop simplified | 1.142 | 1.132 |
| | | | Spencer | 1.142 | 1.132 |
| V026 | Duncan & Wright fig. 7.12, embankment on clay | 1.22 | Bishop simplified | 1.228 | 1.220 |
| | | | Spencer, non-circular | 1.190 | 1.173 |
| V027 | Duncan & Wright fig. 14.3, undrained clay | 1.124 | Bishop simplified | 1.126 | 1.122 |
| | | | Spencer | – | 1.132 |
| V028 | Duncan & Wright fig. 14.3, undrained clay on a 46.5 ft foundation | 1.124 | Bishop simplified | 1.126 | 1.122 |
| | | | Spencer | – | 1.122 |
| V029 | Duncan & Wright fig. 14.3, undrained clay on a 60 ft foundation | 1.124 | Bishop simplified | 1.125 | 1.117 |
| | | | Spencer | – | 1.117 |
| V030 | Duncan & Wright fig. 14.4 | 1.40 | Bishop simplified | 1.412 | 1.408 |
| | | | Spencer | – | 1.399 |
| V031a | Duncan & Wright fig. 14.5, R = 87 ft | 2.56 | Bishop simplified | 2.549 | 2.534 |
| | | | Spencer | 2.545 | 2.531 |
| V031b | Duncan & Wright fig. 14.5, R = 102 ft | 1.35 | Bishop simplified | 1.398 | 1.389 |
| | | | Spencer | 1.359 | 1.352 |
| V032a | Duncan & Wright fig. 14.7, deep circle | 1.21 | Bishop simplified | 1.230 | 1.224 |
| | | | Spencer | 1.209 | 1.205 |
| V032b | Duncan & Wright fig. 14.7, infinite-slope mechanism | 1.15 | Bishop simplified | 1.155 | 1.156 |
| | | | Spencer | 1.155 | 1.156 |
| V033 | Duncan & Wright fig. 14.20a, water table | 1.535 | Bishop simplified | 1.533 | 1.521 |
| | | | Spencer | – | 1.533 |
| | | | Spencer, non-circular | 1.534 | 1.524 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V034a | Duncan & Wright fig. 14.20b, Su = 200 + 15·depth | 1.30 | Bishop simplified | 1.313 | 1.306 |
| | | | Spencer | – | 1.276 |
| | | | Spencer, non-circular | 1.262 | 1.269 |
| V034b | Duncan & Wright fig. 14.20b, Su = 300 psf | 1.312 | Bishop simplified | 1.335 | 1.329 |
| | | | Spencer | – | 1.328 |
| | | | Spencer, non-circular | 1.182 | 1.173 |
| V035a | Duncan & Wright tieback, active | 1.51 | Morgenstern-Price (half-sine) | 1.575 | 1.568 |
| V035b | Duncan & Wright tieback, passive | 1.32 | Bishop simplified | 1.324 | 1.319 |
| V036a | Embankment on an undrained foundation, cz = 0 (D&W fig. 15.9) | 0.75 | Bishop simplified | 0.761 | 0.757 |
| | | | Spencer | 0.756 | 0.752 |
| | | | Spencer, non-circular | 0.740 | 0.737 |
| V036b | Embankment on an undrained foundation, cz = 5 psf/ft | 0.90 | Bishop simplified | 0.909 | 0.906 |
| | | | Spencer | 0.898 | 0.898 |
| | | | Spencer, non-circular | 0.903 | 0.884 |
| V036c | Embankment on an undrained foundation, cz = 10 psf/ft | 1.03 | Bishop simplified | 1.045 | 1.042 |
| | | | Spencer | 1.032 | 1.028 |
| | | | Spencer, non-circular | 1.018 | 1.017 |
| V036d | Embankment on an undrained foundation, cz = 15 psf/ft | 1.13 | Bishop simplified | 1.154 | 1.152 |
| | | | Spencer | 1.134 | 1.132 |
| | | | Spencer, non-circular | 1.116 | 1.121 |
| V037 | Geogrid-reinforced fill on rock (D&W fig. 7.28) | 1.61 | Bishop simplified | 1.629 | 1.613 |
| | | | Spencer | 1.620 | 1.607 |
| V038 | Homogeneous dam with a piezometric line (D&W fig. 7.19) | 1.16 | Bishop simplified | 1.070–1.090 | 1.069 |
| | | | Spencer | 1.100 | 1.077 |
| V039 | James Bay dyke (Duncan & Wright fig. 7.16) | 1.45; 1.17 | Bishop simplified | – | 1.424 |
| | | | Spencer | – | 1.421 |
| | | | Spencer, non-circular | 1.167 | 1.155 |
| V040 | James Bay dyke, reference model (deterministic) | – | Bishop simplified | 1.461 | 1.433 |
| V041a | Submerged slope, pool 30 ft above the crest (D&W fig. 6.27) | 1.60 | Bishop simplified | 1.603 | 1.597 |
| | | | Spencer | 1.599 | 1.594 |
| | | | Spencer, non-circular | 1.592 | 1.591 |
| V041b | Submerged slope, pool 60 ft above the crest (D&W fig. 6.27) | 1.60 | Bishop simplified | 1.603 | 1.597 |
| | | | Spencer | 1.599 | 1.594 |
| | | | Spencer, non-circular | 1.590 | 1.589 |
| V042 | Thick-core dam with a piezometric line (D&W fig. 7.24) | 1.67 | Bishop simplified | 1.584–1.591 | 1.591 |
| | | | Spencer | 1.648 | 1.658 |
| | | | Morgenstern-Price (half-sine) | 1.670 | 1.670 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V043 | Syncrude tailings dyke (El-Ramly et al.), composite circle | 1.31 | Bishop simplified | 1.320 | 1.320 |
| V044 | Fredlund & Krahn (1977), dry | 2.08; 2.076 | Bishop simplified | – | 2.076 |
| | | | Morgenstern-Price (half-sine) | – | 2.072 |
| V045 | Fredlund & Krahn (1977), with water table | 1.834; 1.832 | Bishop simplified | – | 1.829 |
| | | | Morgenstern-Price (half-sine) | – | 1.827 |
| V046 | Fredlund & Krahn slope on a weak seam, composite surface | 1.37 | Bishop simplified | 1.382 | 1.380 |
| | | | Spencer | 1.382 | 1.379 |
| | | | Morgenstern-Price (half-sine) | – | 1.370 |
| V047a | ACADS 1(a), homogeneous slope, dry | 1.00 | Bishop simplified | 0.987–0.992 | 0.985 |
| | | | Spencer | 0.986 | 0.984 |
| | | | Janbu corrected | 0.990 | 0.986 |
| | | | Morgenstern-Price (half-sine) | 0.991 | 0.984 |
| V047b | ACADS tension crack, reference crack depth 3.6 m (results correspond to a dry crack) | 1.65–1.70 | Bishop simplified | 1.664 | 1.659 |
| | | | Morgenstern-Price (half-sine) | 1.660 | 1.656 |
| V048 | ACADS 1(b), water-filled tension crack | 1.65 | Bishop simplified | 1.596 | 1.587 |
| | | | Spencer | 1.592 | 1.582 |
| | | | Janbu corrected | 1.489 | 1.475 |
| V049 | ACADS 1(c), three-layer slope | 1.39 | Bishop simplified | 1.403–1.405 | 1.403 |
| | | | Spencer | 1.375 | 1.372 |
| | | | Janbu corrected | 1.357 | 1.355 |
| | | | Morgenstern-Price (half-sine) | 1.382 | 1.372 |
| V050a | ACADS 3(b), weak layer, specified non-circular surface | 1.34 | Janbu corrected | 1.294 | 1.294 |
| | | | Spencer | 1.277 | 1.276 |
| | | | Morgenstern-Price (half-sine) | 1.261 | 1.260 |
| V050b | ACADS 3(a), weak layer, non-circular search | 1.24–1.27 | Spencer, non-circular | 1.246 | 1.228 |
| V051 | ACADS 4, weak layer, water table and surcharges | 0.78 | Spencer, non-circular | 0.707 | 0.698 |
| V052a | Talbingo Dam, end of construction | 1.95 | Bishop simplified | 1.948–1.951 | 1.964 |
| | | | Spencer | 1.948 | 1.964 |
| | | | Janbu corrected | 1.949 | 1.974 |
| V052b | Talbingo Dam, specified circle | 2.29 | Bishop simplified | 2.208 | 2.206 |
| | | | Spencer | 2.292 | 2.290 |
| | | | Janbu corrected | 2.073 | 2.073 |
| | | | Morgenstern-Price (half-sine) | 2.299 | 2.299 |
| V053 | Greco (1996) ex. 5 / Chen & Shao weak-layer slope, reference geometry | 1.01–1.03; 1.08 | Spencer, non-circular | 1.010 | 1.009 |
| V054 | Greco (1996) example 5 / Chen & Shao (1988) | 1.08 | Bishop simplified | 1.087 | 1.086 |
| | | | Spencer | 1.093 | 1.091 |
| V055 | Griffiths & Lane example 2, slope with a foundation layer | 1.40 | Spencer | 1.366 | 1.366 |
| V056 | Griffiths & Lane example 3, thin weak layer, cu2/cu1 = 0.2 | 0.485 | Janbu corrected | – | 0.499 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V057a | Griffiths & Lane example 4, cu2/cu1 = 1 (deep base circle) | 1.46 | Spencer | 1.468 | 1.471 |
| V057b | Griffiths & Lane example 4, cu2/cu1 = 2 (toe circle) | 2.04 | Spencer | 2.022 | 2.023 |
| V058 | Griffiths & Lane example 6, earth dam with full reservoir | 1.90 | Spencer | 1.915 | 1.915 |
| V059a | Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.4 | – | Spencer, non-circular | 1.215 | 1.216 |
| V059b | Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.5 | – | Spencer, non-circular | 1.290 | 1.292 |
| V059c | Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.6 | – | Spencer, non-circular | 1.315 | 1.314 |
| V060a | Cannon Dam end of construction (Hassan & Wolff), critical circle | – | Bishop simplified | 2.529–2.551 | 2.530 |
| V060b | Cannon Dam end of construction (Hassan & Wolff), reliability on the minimum-β circle | – | Bishop simplified | 2.973 | 2.974 |
| V061 | Clarence Cannon Dam (Wolff & Harr), specified surface | 2.36 | Morgenstern-Price (half-sine) | 2.384 | 2.384 |
| | | | Spencer | 2.423 | 2.423 |
| V062a | Clarence Cannon Dam, surface 7A | 2.753 | Bishop simplified | 2.551–2.560 | 2.549 |
| V062b | Clarence Cannon Dam, surface 7B | 2.352 | Bishop simplified | 2.806–2.820 | 2.815 |
| V062c | Clarence Cannon Dam, surface 7C | 2.523 | Bishop simplified | 2.771–2.777 | 2.779 |
| V062d | Clarence Cannon Dam, surface 7D | 2.457 | Bishop simplified | 2.583–2.589 | 2.577 |
| V062e | Clarence Cannon Dam, surface 7E | 2.602 | Bishop simplified | 2.692–2.703 | 2.690 |
| V062f | Clarence Cannon Dam, surface 8B | 2.995 | Bishop simplified | 2.672–2.673 | 2.673 |
| V062g | Clarence Cannon Dam, surface 8F | 3.916 | Bishop simplified | 3.586–3.598 | 3.592 |
| V062h | Clarence Cannon Dam, surface 8G | 10.576 | Bishop simplified | 6.069–6.074 | 6.063 |
| V062i | Clarence Cannon Dam, surface 8H | 6.293 | Bishop simplified | 11.583 | 11.567 |
| V063 | Huang & Jia earth dam, dry | 2.43 | Spencer | 2.455 | 2.451 |
| V064 | Leshchinsky & Han MSE wall, five tiers | 1.00 | Bishop simplified | 1.020 | 1.017 |
| V065 | Leshchinsky & Han MSE wall, weak foundation | 1.00; 0.86 | Spencer | 0.964 | 0.961 |
| | | | Bishop simplified | – | 0.979 |
| V066a | Leshchinsky & Han three-tier MSE wall, baseline | 1.00; 0.99 | Bishop simplified | 1.040 | 1.031 |
| V066b | Leshchinsky & Han MSE wall, L = 4.2 m | 1.00; 0.98 | Spencer | 1.011 | 1.011 |
| | | | Bishop simplified | – | 1.013 |
| V066c | Leshchinsky & Han MSE wall, two reinforcement types | 1.00; 1.01 | Bishop simplified | 1.004 | 1.012 |
| V066d | Leshchinsky & Han MSE wall, water hw = 3 m | 1.00; 1.01 | Bishop simplified | 1.010 | 1.010 |
| V066e | Leshchinsky & Han MSE wall, surcharge | 1.00; 1.02 | Bishop simplified | 0.958 | 0.961 |
| V067 | Low (1989), layered undrained clay | 1.44 | Bishop simplified | 1.439 | 1.436 |
| V068 | Low (1989), stiff crust over soft clays, published circle | 1.36; 1.14; 1.17 | Bishop simplified | 1.192 | 1.197 |
| V069a | Morgenstern (1963) complete drawdown, 3:1 | 1.20 | Bishop simplified | – | 1.200 |
| | | | Spencer | – | 1.205 |
| V069b | Morgenstern complete drawdown, the reference circle | 1.20 | Bishop simplified | 1.212 | 1.209 |
| V070 | Partial drawdown, $\bar{B} = 1$ (Morgenstern chart) | 1.41 | Bishop simplified | 1.417 | 1.415 |
| | | | Spencer | 1.422 | 1.421 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V071a | Pockoski & Duncan (2000) slope 1 | – | Bishop simplified | 1.293 | 1.290 |
| | | | Spencer | 1.300 | 1.296 |
| V071b | Pockoski & Duncan slope 1, circular search | – | Bishop simplified | 1.293 | 1.288 |
| | | | Spencer | 1.300 | 1.294 |
| | | | Janbu simplified | 1.151 | 1.147 |
| V072a | Pockoski & Duncan test slope 2, dry tension crack | – | Bishop simplified | 1.285 | 1.282 |
| | | | Spencer | 1.290 | 1.287 |
| V072b | Pockoski & Duncan slope 2, circular search | – | Bishop simplified | 1.285 | 1.282 |
| | | | Spencer | 1.290 | 1.287 |
| | | | Janbu simplified | 1.141 | 1.135 |
| V073 | Pockoski & Duncan test slope 3, clay seam and dry crack | – | Bishop simplified | 1.417 | 1.410 |
| | | | Spencer | 1.422 | 1.415 |
| V074 | Soil-nailed wall with tension crack and surcharges | – | Spencer | 1.009 | 1.010 |
| | | | Janbu corrected | 1.073 | 1.075 |
| V075 | Tieback wall in sand, drawdown water table | – | Janbu corrected | 0.579 | 0.578 |
| | | | Spencer | 0.596 | 0.599 |
| V076 | Tied-back wall in layered soil | – | Bishop simplified | 1.147 | 1.142 |
| | | | Spencer | 1.145 | 1.140 |
| V077 | Prandtl bearing capacity on level ground | 1.00 | Spencer | 0.940 | 0.943 |
| V078 | Prandtl bearing capacity, fully specified Prandtl surface (reference values) | 1.00 | Morgenstern-Price (half-sine) | 0.960 | 0.957 |
| V079 | Priest (1993) rigid block on a plane, water-filled crack | 1.049 | Janbu simplified | 1.049 | 1.048 |
| | | | Spencer | 1.049 | 1.048 |
| V080 | Priest (1993) rigid block, reference geometry (60° face) | 1.049 | Morgenstern-Price (half-sine) | 1.049 | 1.049 |
| | | | Spencer | – | 1.049 |
| V081a | Sharma (1996) reinforcement example, unreinforced | – | Bishop simplified | 0.764 | 0.764 |
| V081b | Sharma (1996) slope with a reinforced zone (φ = 54.93°) | – | Bishop simplified | 1.504 | 1.501 |
| V082a | Sharma (1996) slope, 11 ft dry tension crack instead of the zero-strength cap | – | Bishop simplified | 1.532 | 1.504 |
| | | | Spencer | 1.532 | 1.503 |
| | | | Morgenstern-Price (half-sine) | 1.532 | 1.503 |
| V082b | Sharma (1996) slope, 11 ft tension crack with 6 ft of water | – | Bishop simplified | 1.511 | 1.483 |
| | | | Spencer | 1.510 | 1.482 |
| V082c | Sharma (1996) slope over undulating bedrock, zero-strength cap | – | Bishop simplified | 1.369–1.396 | 1.369 |
| | | | Spencer | 1.375–1.402 | 1.375 |
| V083 | Soil-nailed wall in clay (Amherst test wall) | 0.887 | Janbu corrected | 0.890 | 0.899 |
| V084a | Soil-nailed wall in sand (Clouterre test wall) | 0.989 | Janbu corrected | 0.989 | 0.988 |
| V084b | Soil-nailed wall in sand (Clouterre test wall), 45° plane | 1.176 | Janbu corrected | 1.123 | 1.124 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V084c | Soil-nailed wall in sand (Clouterre test wall), 50° plane | 1.07 | Janbu corrected | 1.043 | 1.043 |
| V084d | Soil-nailed wall in sand (Clouterre test wall), 60° plane | 0.929 | Janbu corrected | 0.945 | 0.944 |
| V084e | Soil-nailed wall in sand (Clouterre test wall), 65° plane | 0.893 | Janbu corrected | 0.922 | 0.920 |
| V084f | Soil-nailed wall in sand (Clouterre test wall), 70° plane | 0.887 | Janbu corrected | 0.923 | 0.920 |
| V085 | Bradwell excavated slope, stiff-fissured London clay | 1.76; 1.63; 1.74 | Bishop simplified | 1.762 | 1.759 |
| | | | Spencer | 1.758 | 1.759 |
| | | | Janbu corrected | 1.736 | 1.735 |
| | | | Janbu simplified | – | 1.627 |
| V086a | Tandjiria embankment, clay fill, geosynthetic T = 169 kN/m | 1.35 | Spencer | 1.332–1.350 | 1.333 |
| V086b | Tandjiria embankment, clay fill, water-filled crack | 0.981 | Spencer (2 m tension crack) | 0.975 | 0.968 |
| | | | Spencer (tension crack of automatic depth) | 0.975 | 0.966 |
| V086c | Tandjiria embankment, sand fill, dry crack | 1.219 | Spencer | 1.209 | 1.206 |
| V087 | USACE dam, chart-check properties (EM 1110-2-1902 fig. 4-3) | 2.30 | Spencer | 2.258 | 2.258 |
| | | | Bishop simplified | 2.254 | 2.255 |
| | | | Janbu corrected | 2.290 | 2.258 |
| V088 | USACE dam, end of construction (EM 1110-2-1902 fig. 4-1) | 2.44 | Spencer | 2.445 | 2.442 |
| | | | Bishop simplified | 2.447 | 2.442 |
| | | | Janbu corrected | 2.430 | 2.444 |
| V089 | USACE dam, upstream low pool (EM 1110-2-1902 fig. 4-2) | 2.71 | Bishop simplified | 2.716 | 2.698 |
| | | | Spencer | 2.736 | 2.721 |
| | | | Janbu corrected | 2.650 | 2.648 |
| V090 | USACE EM 1110-2-1902, example F-5 | 1.33 | Bishop simplified | 1.332 | 1.320 |
| | | | Spencer | 1.328 | 1.317 |
| | | | Janbu corrected | 1.345 | 1.341 |
| V091 | USACE example E-10, ponded water | 1.33 | Bishop simplified | 1.241 | 1.235 |
| | | | Spencer | 1.241 | 1.235 |
| | | | Morgenstern-Price (half-sine) | 1.244 | 1.235 |
| | | | Janbu corrected | 1.385 | 1.380 |
| V092 | USACE example F-6, steady-seepage dam | 2.01 | Bishop simplified | 2.011 | 1.998 |
| | | | Spencer | 2.026 | 2.012 |
| | | | Janbu corrected | 1.830 | 1.832 |
| V093 | Yamagami & Ueta (1988) | 1.348; 1.282; 1.185; 1.339; 1.33 | Bishop simplified | 1.344 | 1.343 |
| | | | Spencer, non-circular | 1.325 | 1.324 |
| | | | Janbu simplified, non-circular | – | 1.178 |
| V094 | Yamagami & Ueta (1988) four-layer slope, non-circular | 1.40–1.42 | Spencer, non-circular | 1.398 | 1.401 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| | | | Morgenstern-Price (half-sine), non-circular | 1.389 | 1.395 |
| V095a | Yamagami micro-pile slope, no pile | 1.10 | Bishop simplified | 1.102 | 1.101 |
| V095b | Homogeneous slope, no micro piles | 1.10 | Bishop simplified | 1.102 | 1.101 |
| V095c | Homogeneous slope with a micro-pile row | 1.20 | Bishop simplified | 1.193 | 1.196 |
| V096a | Zhu & Lee heterogeneous slope, dry, deep circle | 1.836; 1.823; 1.429; 1.229 | Bishop simplified | 1.804 | 1.793 |
| | | | Spencer | 1.804 | 1.794 |
| | | | Morgenstern-Price (half-sine) | – | 1.780 |
| V096b | Zhu & Lee heterogeneous slope with a water table, deep circle | 1.211; 1.197 | Bishop simplified | 1.176 | 1.173 |
| | | | Spencer | 1.189 | 1.187 |
| | | | Morgenstern-Price (half-sine) | – | 1.172 |
| V096c | Zhu & Lee slope, surface 3 (the reference circle), dry, 1 m crack | 1.836; 1.823; 1.429; 1.229 | Spencer | 1.804 | 1.799 |
| | | | Bishop simplified | 1.804 | 1.799 |
| | | | Morgenstern-Price (half-sine) | – | 1.785 |
| V097a | Eurocode 7 cutting with surcharge | – | Bishop simplified | 1.173 | 1.172 |
| V097b | Eurocode 7 cutting, partial factors applied by cSlope | – | Bishop simplified | 1.173 | 1.172 |
| | | | Spencer | 1.174 | 1.174 |
| V098 | Example slope without seismic load | – | Spencer | 1.360–1.372 | 1.372 |
| V021a | Congress Street cut, probabilistic (tangent to clay 2) | – | Pf, share FOS < 1 (Monte Carlo) | 0.246 | 0.239 |
| V021a | Congress Street cut, probabilistic (tangent to clay 2) | – | β lognormal (Monte Carlo) | 0.650 | 0.671 |
| V021a | Chowdhury & Xu (1995) example 1, probability of failure | – | Pf, share FOS < 1 (Monte Carlo) | 0.253 | 0.245 |
| V021b | Congress Street cut, probabilistic (tangent to clay 3) | – | Pf, share FOS < 1 (Monte Carlo) | 0.279 | 0.282 |
| V021b | Congress Street cut, probabilistic (tangent to clay 3) | – | β lognormal (Monte Carlo) | 0.537 | 0.553 |
| V022a | Embankment on soft clay, probabilistic (tangent to the interface) | – | Pf, share FOS < 1 (Monte Carlo) | 0.206–0.212 | 0.206 |
| V022a | Embankment on soft clay, probabilistic (tangent to the interface) | – | β lognormal (Monte Carlo) | 0.799–0.800 | 0.812 |
| V022a | Embankment on soft clay, probabilistic (tangent to the interface) | – | β lognormal (Taylor series) | 0.787 | 0.788 |
| V022a | Chowdhury & Xu (1995) example 5, probability of failure | – | Pf, share FOS < 1 (Monte Carlo) | 0.210 | 0.208 |
| V022b | Embankment on soft clay, probabilistic (tangent to the clay base) | – | Pf, share FOS < 1 (Monte Carlo) | 0.199–0.209 | 0.212 |
| V022b | Embankment on soft clay, probabilistic (tangent to the clay base) | – | β lognormal (Monte Carlo) | 0.789–0.820 | 0.789 |
| V022b | Embankment on soft clay, probabilistic (tangent to the clay base) | – | β lognormal (Taylor series) | 0.798 | 0.802 |
| V022b | Chowdhury & Xu (1995) example 5, probability of failure | – | Pf, share FOS < 1 (Monte Carlo) | 0.214 | 0.216 |
| V060b | Cannon Dam end of construction (Hassan & Wolff), reliability on the minimum-β circle | – | β lognormal (Taylor series) | 3.353 | 3.354 |

| Problem | Description | Published | cSlope analysis | Other programs | cSlope |
|---|---|---|---|---|---|
| V023 | LASH terminal trench, Duncan's Taylor series example | 0.900 | β lognormal (Taylor series) | – | 0.892 |
| V023 | LASH terminal trench, Duncan's Taylor series example | 0.180 | Pf lognormal (Taylor series) | – | 0.186 |
| V062a | Clarence Cannon Dam, surface 7A | – | β lognormal (Monte Carlo) | 10.953 | 11.034 |
| V062b | Clarence Cannon Dam, surface 7B | – | β lognormal (Monte Carlo) | 4.351 | 4.402 |
| V062c | Clarence Cannon Dam, surface 7C | – | β lognormal (Monte Carlo) | 4.263 | 4.325 |
| V062d | Clarence Cannon Dam, surface 7D | – | β lognormal (Monte Carlo) | 11.092 | 11.076 |
| V062e | Clarence Cannon Dam, surface 7E | – | β lognormal (Monte Carlo) | 10.281 | 10.329 |
| V062f | Clarence Cannon Dam, surface 8B | – | β lognormal (Monte Carlo) | 4.858 | 4.933 |
| V062g | Clarence Cannon Dam, surface 8F | – | β lognormal (Monte Carlo) | 5.485 | 5.528 |
| V062h | Clarence Cannon Dam, surface 8G | – | β lognormal (Monte Carlo) | 5.563 | 5.490 |
| V062i | Clarence Cannon Dam, surface 8H | – | β lognormal (Monte Carlo) | 6.394 | 6.431 |

# 3 Verification problems

## 3.1 V001 — Arai & Tagyo (1985) example 1

*Arai & Tagyo (1985), example 1.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous 1.5:1 slope, 20 m high; critical circle search.





*Figure 1. V001: critical circle (Bishop simplified, FOS = 1.404).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.82 | c' = 41.65 | 15.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.451 | Bishop simplified | Arai & Tagyo (1985) | 1.404 |
| 1.265 | Janbu simplified, non-circular | Arai & Tagyo (1985) | 1.253 |
| 1.357 | Janbu corrected, non-circular | Arai & Tagyo (1985) | 1.346 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.409–1.417 | 1.404 |
| Morgenstern-Price (half-sine) | 1.414 | 1.401 |
| Spencer, non-circular | 1.386 | 1.385 |
| Janbu simplified, non-circular | – | 1.253 |
| Janbu corrected, non-circular | – | 1.346 |

*Arai & Tagyo's Bishop value 1.451 is 2–3 % above the other programs (1.409–1.417) and cSlope on the same slope; their non-circular Janbu values are within 1 % of cSlope's.*

## 3.2 V002 — Arai & Tagyo (1985) example 2, three layers

*Arai & Tagyo (1985), example 2.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Slope with a weak middle layer between a stronger upper layer and a very strong base; critical circle search.





*Figure 2. V002: critical circle (Bishop simplified, FOS = 0.419).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper | Mohr-Coulomb | 18.82 | c' = 29.40 | 12.00° |
| Middle | Mohr-Coulomb | 18.82 | c' = 9.80 | 5.00° |
| Lower | Mohr-Coulomb | 18.82 | c' = 294.0 | 40.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.417 | Bishop simplified | Arai & Tagyo (1985) | 0.419 |
| 0.405 | Janbu simplified, non-circular | Arai & Tagyo (1985) | 0.393 |
| 0.43 | Janbu corrected, non-circular | Arai & Tagyo (1985) | 0.413 |
| 0.43 | Bishop simplified | Kim et al. (2002) | 0.419 |
| 0.39–0.44 | Spencer, non-circular | Kim et al. (2002) | 0.412 |
| 0.39 | Spencer, non-circular | Greco (1996) | 0.412 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.420 | 0.419 |
| Spencer, non-circular | 0.414 | 0.412 |
| Janbu simplified, non-circular | – | 0.393 |
| Janbu corrected, non-circular | – | 0.413 |

## 3.3 V003 — Arai & Tagyo (1985) example 3, water table

*Arai & Tagyo (1985), Soils and Foundations 25(1).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous slope with a water table; critical-circle search.





*Figure 3. V003: critical circle (Bishop simplified, FOS = 1.113).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| A&T ex3 soil | Mohr-Coulomb | 18.82 | c' = 41.65 | 15.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.138 | Bishop simplified | Arai & Tagyo (1985) | 1.113 |
| 0.995 | Janbu simplified, non-circular | Arai & Tagyo (1985) | 0.967 |
| 1.071 | Janbu corrected, non-circular | Arai & Tagyo (1985) | 1.048 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.112–1.118 | 1.113 |
| Spencer | 1.118 | 1.113 |
| Janbu corrected | 1.131 | 1.124 |
| Janbu simplified, non-circular | – | 0.967 |
| Janbu corrected, non-circular | – | 1.048 |

*Arai & Tagyo's Bishop value 1.138 is about 2 % above the other programs (1.112–1.118 with Bishop).*

## 3.4 V004a — 4:1 slope, Mohr-Coulomb fit

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

12 m high 4:1 slope with the same soil as V008a; critical circle search.





*Figure 4. V004a: critical circle (Spencer, FOS = 2.802).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 11.64 | 24.70° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.66 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 2.794 | 2.802 |
| Janbu simplified | 2.662 | 2.677 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit and for the non-linear envelope without naming the slice method.*

## 3.5 V004b — Baker (2003) ex. 2 slope, Mohr-Coulomb iteration parameters

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V004a 4:1 slope with Baker's iterated Mohr-Coulomb parameters (c′ = 2.439 kPa, φ′ = 30.392°); critical-circle search.





*Figure 5. V004b: critical circle (Janbu simplified, FOS = 2.609).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 2.44 | 30.39° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.64 | non-linear strength envelope | Baker (2003) | – |
| 2.66 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu simplified | 2.610 | 2.609 |
| Spencer | 2.696 | 2.666 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit and for the non-linear envelope without naming the slice method.*

## 3.6 V005 — Baker (1993) dam, end of construction, infinite-slope face

*Baker (1993).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Compacted-clay embankment (c′ = 6.5 kPa, φ′ = 40°) on a deep natural-clay foundation (c′ = 0, φ′ = 32°) whose 4H:1V downstream face governs; dry; circular search. Theoretical (infinite slope) FOS tan 32°/tan 14.04° = 2.50.





*Figure 6. V005: critical circle (Bishop simplified, FOS = 2.523).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Compacted clay | Mohr-Coulomb | 18.00 | c' = 6.50 | 40.00° |
| Natural clay | Mohr-Coulomb | 18.00 | c' = 0.00 | 32.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.50 | infinite slope | Theory | 2.523 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | – | 2.523 |
| Spencer | – | 2.523 |

## 3.7 V006 — Baker (2001) planar surface

*Baker (2001).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Homogeneous 10 m slope on the critical plane from the toe to the crest at 49.6°.





*Figure 7. V006: analysed surface (Spencer, FOS = 1.352).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 30.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.35 | Culmann (planar wedge) | Baker (2001) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.351 | 1.352 |
| Janbu simplified | 1.351 | 1.352 |

## 3.8 V007a — Baker (2003) ex. 1, Mohr-Coulomb, Janbu simplified on the reference circle

*Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V008a slope (Mohr-Coulomb fit c′ = 11.64 kPa, φ′ = 24.7°) with Janbu simplified (uncorrected) on the reference critical circle (Fig. 44.3).





*Figure 8. V007a: analysed circle (Janbu simplified, FOS = 1.468).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 11.64 | 24.70° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.50 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu simplified | 1.469 | 1.468 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit and for the non-linear envelope without naming the slice method.*

## 3.9 V007b — Baker (2003) ex. 1 slope, Mohr-Coulomb iteration parameters

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V008a slope with Baker's Mohr-Coulomb parameters from his iterative linearisation (c′ = 0.39 kPa, φ′ = 38.6°); critical-circle search.





*Figure 9. V007b: critical circle (Janbu simplified, FOS = 0.955).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 0.39 | 38.60° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.97 | non-linear strength envelope | Baker (2003) | – |
| 1.50 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu simplified | 0.957 | 0.955 |
| Spencer | 0.981 | 0.978 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit and for the non-linear envelope without naming the slice method; 1.50 is his Mohr-Coulomb value for the same slope.*

## 3.10 V007c — Baker (2003) ex. 3, Janbu simplified

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V008b London clay slope (c′ = 6 kPa, φ′ = 32°) with Janbu simplified (uncorrected); critical-circle search.





*Figure 10. V007c: critical circle (Janbu simplified, FOS = 1.290).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 6.00 | 32.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.35 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu simplified | 1.291 | 1.290 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit without naming the slice method.*

## 3.11 V008a — Baker (2003) example 1, Mohr-Coulomb fit

*Baker (2003), example 1.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

6 m high slope at about 43° in soil with a linear Mohr-Coulomb fit to a curved envelope; critical circle search.





*Figure 11. V008a: critical circle (Spencer, FOS = 1.519).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.00 | c' = 11.64 | 24.70° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.50 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.536 | 1.519 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit without naming the slice method.*

## 3.12 V008b — Baker (2003) London clay slope, Mohr-Coulomb fit

*Baker (2003) example 3.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

43° slope, 6 m high, with the Mohr-Coulomb envelope fitted to London clay data (c' = 6 kPa, φ' = 32°); critical circle search.





*Figure 12. V008b: critical circle (Spencer, FOS = 1.365).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| London clay | Mohr-Coulomb | 18.00 | c' = 6.00 | 32.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.35 | Mohr-Coulomb strength | Baker (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.366 | 1.365 |

*Baker (2003) gives the factor of safety for the Mohr-Coulomb fit without naming the slice method.*

## 3.13 V009a — Baker & Leshchinsky clay-core dam, reservoir and crest crack

*Baker & Leshchinsky (2001).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Granular dam with a diamond clay core on a hard base, half-full reservoir standing on the face (free water), phreatic surface through the core and a 5 m dry tension crack at the crest; a commercial program's critical circle.





*Figure 13. V009a: analysed circle (Spencer, FOS = 1.926).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Granular fill | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Clay core | Mohr-Coulomb | 20.00 | c' = 20.00 | 20.00° |
| Granular fill below core | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Hard base | Mohr-Coulomb | 24.00 | c' = 200.0 | 45.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.925 | 1.926 |

*The published 1.91 belongs to Baker & Leshchinsky's own non-circular surface (V009b), not to this circle.*

## 3.14 V009b — Baker & Leshchinsky dam, Baker's non-circular surface

*Baker & Leshchinsky (2001).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

As V009a, on the non-circular surface published by Baker & Leshchinsky.





*Figure 14. V009b: analysed surface (Spencer, FOS = 1.882).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Granular fill | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Clay core | Mohr-Coulomb | 20.00 | c' = 20.00 | 20.00° |
| Granular fill below core | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Hard base | Mohr-Coulomb | 24.00 | c' = 200.0 | 45.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.91 | Spencer | Baker & Leshchinsky | 1.882 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | – | 1.882 |

## 3.15 V009c — Baker & Leshchinsky clay-core dam, critical surface search

*Baker & Leshchinsky (2001).*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

The V009a clay-core dam (reservoir on the face, 5 m dry crest crack) with a circular search and non-circular optimisation.





*Figure 15. V009c: critical surface (Spencer, non-circular, FOS = 1.868).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Granular fill | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Clay core | Mohr-Coulomb | 20.00 | c' = 20.00 | 20.00° |
| Granular fill below core | Mohr-Coulomb | 21.50 | c' = 0.00 | 40.00° |
| Hard base | Mohr-Coulomb | 24.00 | c' = 200.0 | 45.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.91 | Spencer, non-circular | Baker & Leshchinsky (2001) | 1.868 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.868 | 1.868 |

*Baker & Leshchinsky's 1.91 is for their own surface (V009b); searches find lower surfaces.*

## 3.16 V010 — Borges & Cardoso embankment 2 (geosynthetic)

*Borges & Cardoso (2002), Geotextiles and Geomembranes 20(6).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

5 m embankment (φ′ = 35°) on four soft clays with Su increasing with depth (Table 55: clay 3 from 16 to 18.4 kPa, clay 4 from 18.4 to 55.1 kPa), a 200 kN/m geosynthetic at y = 1 m (axial, active, not anchored, interface friction 33.7° on both faces); a commercial program's critical circle.





*Figure 16. V010: analysed circle (Morgenstern-Price (half-sine), FOS = 1.162).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 20.00 | c' = 0.00 | 35.00° |
| Clay 1 | Undrained (φ = 0) | 17.00 | Su = 33.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 17.00 | Su = 16.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 17.00 | Su = 16.00 at y = -4.50, +0.95 kPa/m below | 0° |
| Clay 4 | Undrained (φ = 0) | 17.00 | Su = 18.38 at y = -7.00, +2.63 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.15 | Morgenstern-Price (half-sine) | Borges & Cardoso | 1.162 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.171 | 1.162 |
| Bishop simplified | 1.170 | 1.164 |

## 3.17 V011a — Borges & Cardoso embankment 3, H = 7 m, circle A

*Borges & Cardoso (2002), Geotextiles and Geomembranes 20(6).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Granular fill (two stages) on five soft clay layers with a T = 200 kN/m geosynthetic at y = 0.9 m (axial, passive as in a commercial program, pullout over 1.3 m from each end); Bishop on circle A of the paper.





*Figure 17. V011a: analysed circle (Bishop simplified, FOS = 1.219).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper embankment | Mohr-Coulomb | 21.90 | c' = 0.00 | 35.00° |
| Lower embankment | Mohr-Coulomb | 17.20 | c' = 0.00 | 33.00° |
| Clay 1 | Undrained (φ = 0) | 18.00 | Su = 43.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 16.60 | Su = 31.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 13.50 | Su = 30.00 | 0° |
| Clay 4 | Undrained (φ = 0) | 17.00 | Su = 32.00 | 0° |
| Clay 5 | Undrained (φ = 0) | 17.50 | Su = 32.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.25 | not stated | Borges & Cardoso (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.230 | 1.219 |

*Borges & Cardoso print two decimals and do not name the method; the other programs differ from them by up to 2.5 %.*

## 3.18 V011b — Borges & Cardoso embankment 3, H = 7 m, circle B

*Borges & Cardoso (2002), Geotextiles and Geomembranes 20(6).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V011a on circle B.





*Figure 18. V011b: analysed circle (Bishop simplified, FOS = 1.216).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper embankment | Mohr-Coulomb | 21.90 | c' = 0.00 | 35.00° |
| Lower embankment | Mohr-Coulomb | 17.20 | c' = 0.00 | 33.00° |
| Clay 1 | Undrained (φ = 0) | 18.00 | Su = 43.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 16.60 | Su = 31.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 13.50 | Su = 30.00 | 0° |
| Clay 4 | Undrained (φ = 0) | 17.00 | Su = 32.00 | 0° |
| Clay 5 | Undrained (φ = 0) | 17.50 | Su = 32.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.19 | not stated | Borges & Cardoso (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.220 | 1.216 |

*Borges & Cardoso print two decimals and do not name the method; the other programs differ from them by up to 2.5 %.*

## 3.19 V012 — Borges & Cardoso embankment 3, H = 8.75 m, circle C

*Borges & Cardoso (2002), Geotextiles and Geomembranes 20(6).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The second fill stage (8.75 m crest) on circle C.





*Figure 19. V012: analysed circle (Bishop simplified, FOS = 0.982).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper embankment | Mohr-Coulomb | 21.90 | c' = 0.00 | 35.00° |
| Lower embankment | Mohr-Coulomb | 17.20 | c' = 0.00 | 33.00° |
| Clay 1 | Undrained (φ = 0) | 18.00 | Su = 43.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 16.60 | Su = 31.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 13.50 | Su = 30.00 | 0° |
| Clay 4 | Undrained (φ = 0) | 17.00 | Su = 32.00 | 0° |
| Clay 5 | Undrained (φ = 0) | 17.50 | Su = 32.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.99 | not stated | Borges & Cardoso (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.980 | 0.982 |

*Borges & Cardoso print two decimals and do not name the method.*

## 3.20 V013a — Cai & Ugai (2000) slope, no pile (see V013b, V013c, V013d and V013e for the pile r

*Cai & Ugai (2000).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous 1:1.5 slope, 10 m high, without piles; critical circle search.





*Figure 20. V013a: critical circle (Bishop simplified, FOS = 1.143).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.13 | Bishop simplified | Cai & Ugai | 1.143 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.140 | 1.143 |

## 3.21 V013b — Cai & Ugai slope, pile row D1/D = 2

*Cai & Ugai (2000), Géotechnique 50(2).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

A row of 0.8 m piles at mid-slope, centre-to-centre 1.6 m, with the Ito & Matsui force (passive); Bishop search.





*Figure 21. V013b: critical circle (Bishop simplified, FOS = 1.541).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.54 | not stated | Cai & Ugai (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.540 | 1.541 |

*Cai & Ugai's values are for surfaces through the pile row; the programs search their own critical surfaces, which can differ.*

## 3.22 V013c — Cai & Ugai slope, pile row D1/D = 3

*Cai & Ugai (2000), Géotechnique 50(2).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V013b at 2.4 m spacing.





*Figure 22. V013c: critical circle (Bishop simplified, FOS = 1.450).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.37 | not stated | Cai & Ugai (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.430 | 1.450 |

*Cai & Ugai's values are for surfaces through the pile row; the programs search their own critical surfaces, which can differ.*

## 3.23 V013d — Cai & Ugai slope, pile row D1/D = 4

*Cai & Ugai (2000), Géotechnique 50(2).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V013b at 3.2 m spacing.





*Figure 23. V013d: critical circle (Bishop simplified, FOS = 1.342).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.31 | not stated | Cai & Ugai (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.330 | 1.342 |

*Cai & Ugai's values are for surfaces through the pile row; the programs search their own critical surfaces, which can differ.*

## 3.24 V013e — Cai & Ugai slope, pile row D1/D = 6

*Cai & Ugai (2000), Géotechnique 50(2).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V013b at 4.8 m spacing.





*Figure 24. V013e: critical circle (Bishop simplified, FOS = 1.260).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.25 | not stated | Cai & Ugai (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.250 | 1.260 |

*Cai & Ugai's values are for surfaces through the pile row; the programs search their own critical surfaces, which can differ.*

## 3.25 V014 — Nailed wall, 14 rows, deep wedge

*Caltrans soil nail reference manual.*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Nail-reinforced wall with 14 horizontal rows (per-row length, capacity and bond; fully anchored at the wall, tangent, active) on the printed bilinear wedge. Converted to SI.





*Figure 25. V014: analysed surface (Janbu corrected, FOS = 1.448).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 19.64 | c' = 0.00 | 32.00° |
| Layer 2 | Mohr-Coulomb | 20.11 | c' = 23.94 | 35.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 1.448–1.460 | 1.448 |
| Spencer | 1.576 | 1.575 |

*The reference results come from design programs quoted in the soil nail manual; no independent value is published.*

## 3.26 V015 — Soldier-pile tieback wall

*Caltrans soil nail reference manual.*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Two-layer slope cut by a soldier-pile wall with two grouted tieback rows (8 ft spacing); the soldier pile is a shear force of 5900 lb/ft where the surface passes, as a commercial program models it; the manual's bilinear wedge from the wall toe. Converted to SI.





*Figure 26. V015: analysed surface (Janbu corrected, FOS = 1.476).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 18.85 | c' = 28.73 | 24.00° |
| Layer 2 | Mohr-Coulomb | 20.42 | c' = 14.36 | 34.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 1.479 | 1.476 |
| Janbu simplified | 1.446 | 1.442 |

*The reference results come from design programs quoted in the soil nail manual; no independent value is published.*

## 3.27 V016a — Stepped gabion wall, equivalent cohesion

*Cao et al. (2016); Grodecki (2017).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

4 m gabion wall of 1 m cubes with the steps facing outwards on a sloping two-layer profile, dry; mesh as an equivalent cohesion (59.7 kPa); the reference circle.





*Figure 27. V016a: analysed circle (Bishop simplified, FOS = 1.791).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 21.00 | c' = 5.00 | 30.00° |
| Soil #2 | Mohr-Coulomb | 20.00 | c' = 0.00 | 25.00° |
| Gabion wall | Mohr-Coulomb | 23.00 | c' = 59.70 | 42.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.787–1.790 | 1.791 |
| Spencer | 1.791 | 1.797 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.28 V016b — Stepped gabion wall, mesh as geosynthetic supports

*Cao et al. (2016); Grodecki (2017).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V016a with the mesh as geosynthetic supports (T = 100 kN/m) at the course interfaces.





*Figure 28. V016b: analysed circle (Bishop simplified, FOS = 1.830).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 21.00 | c' = 5.00 | 30.00° |
| Soil #2 | Mohr-Coulomb | 20.00 | c' = 0.00 | 25.00° |
| Gabion wall | Mohr-Coulomb | 23.00 | c' = 0.00 | 42.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.830–1.835 | 1.830 |
| Spencer | 1.839 | 1.835 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.29 V016c — Gabion wall with weak joint layers

*Cao et al. (2016); Grodecki (2017).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V016 wall with 6 cm weak bands at the course interfaces (φ = 37.8°, c = 20.4 kPa from the joint tensile strength); the reference circle through the joints.





*Figure 29. V016c: analysed circle (Bishop simplified, FOS = 1.791).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 21.00 | c' = 5.00 | 30.00° |
| Soil #2 | Mohr-Coulomb | 20.00 | c' = 0.00 | 25.00° |
| Gabion wall | Mohr-Coulomb | 23.00 | c' = 59.70 | 42.00° |
| Weak joint | Mohr-Coulomb | 23.00 | c' = 20.40 | 37.80° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.790–1.799 | 1.791 |
| Spencer | 1.803 | 1.797 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.30 V017a — Vancouver gabion wall, equivalent cohesion

*Cao et al. (2016); Grodecki (2017).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

6 m battered gabion wall retaining a 30° backfill with a 12 kPa crest surcharge and a water table in the retained slope; the gabion mesh as an equivalent cohesion (100 kPa); the reference circle.





*Figure 30. V017a: analysed circle (Bishop simplified, FOS = 1.382).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 21.00 | c' = 0.00 | 32.00° |
| Soil #2 | Mohr-Coulomb | 20.00 | c' = 0.00 | 30.00° |
| Gabion wall | Mohr-Coulomb | 20.00 | c' = 100.0 | 45.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.373–1.382 | 1.382 |
| Spencer | 1.386 | 1.398 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.31 V017b — Vancouver gabion wall, mesh as geosynthetic supports

*Cao et al. (2016); Grodecki (2017).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V017a with the steel mesh as geosynthetic supports at every course interface instead of the equivalent cohesion.





*Figure 31. V017b: analysed circle (Bishop simplified, FOS = 1.382).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 21.00 | c' = 0.00 | 32.00° |
| Soil #2 | Mohr-Coulomb | 20.00 | c' = 0.00 | 30.00° |
| Gabion wall | Mohr-Coulomb | 20.00 | c' = 0.00 | 45.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.378–1.382 | 1.382 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.32 V018 — Chen & Shao (1988) frictionless 60° slope, Prandtl mechanism

*Chen & Shao (1988).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Weightless, frictionless 10 m slope at 60° under the critical strip load (149.31 kPa) on the Prandtl surface (wedge, fan and passive wedge); theoretical FOS 1.0.





*Figure 32. V018: analysed surface (Spencer, FOS = 1.052).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 0.00 | c' = 49.00 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.05 | Spencer | Chen & Shao (1988) | 1.052 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.051 | 1.052 |
| Morgenstern-Price (specified f(x)) | 1.009–1.017 | 1.008 |

## 3.33 V019 — Cheng et al. 11 m homogeneous slope

*Cheng, Lansivaara & Wei (2007), Computers and Geotechnics 34.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

11 m homogeneous slope (c = 10 kPa, φ = 30°, γ = 20 kN/m³); circular search.





*Figure 33. V019: critical circle (Spencer, FOS = 1.398).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| soil | Mohr-Coulomb | 20.00 | c' = 10.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.383 | Spencer | Cheng et al. | 1.398 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.380–1.398 | 1.398 |
| Bishop simplified | 1.401 | 1.401 |

## 3.34 V020 — Cheng et al. benched slope, global minimum

*Cheng, Lansivaara & Wei (2007), Computers and Geotechnics 34.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous benched slope; the global minimum on the mid-lower face by circular search.





*Figure 34. V020: critical circle (Spencer, FOS = 1.338).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| soil | Mohr-Coulomb | 20.00 | c' = 5.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.327 | Spencer | Cheng et al. | 1.338 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.336–1.338 | 1.338 |
| Bishop simplified | 1.342 | 1.343 |

## 3.35 V021a — Chowdhury & Xu (1995) example 1, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 1, the Congress Street cut as a commercial program models it (Su = 55, 43, 56 kPa under a strengthless sand cap, digitised piezometric line), on the critical circle tangent to the base of clay 2.





*Figure 35. V021a: analysed circle (Morgenstern-Price (half-sine), FOS = 1.128).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 55.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 43.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 56.00 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.128 | Bishop simplified | Chowdhury & Xu | 1.128 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.132 | 1.128 |
| Bishop simplified | – | 1.128 |
| Bishop simplified (60 slices) | 1.128 | 1.128 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.246 | 0.239 |
| β lognormal (Monte Carlo) | – | 0.650 | 0.671 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.253 | 0.245 |

## 3.36 V021b — Chowdhury & Xu (1995) example 1, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V021a on the critical circle tangent to the base of clay 3.





*Figure 36. V021b: analysed circle (Morgenstern-Price (half-sine), FOS = 1.110).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 55.00 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 43.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 56.00 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.109 | Bishop simplified | Chowdhury & Xu | 1.110 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.116 | 1.110 |
| Bishop simplified | – | 1.110 |
| Bishop simplified (60 slices) | 1.109 | 1.110 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.279 | 0.282 |
| β lognormal (Monte Carlo) | – | 0.537 | 0.553 |

## 3.37 V021c — Chowdhury & Xu (1995) example 2, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 2 (Su = 68.1, 39.3, 50.8 kPa), circle tangent to the base of clay 2.





*Figure 37. V021c: analysed circle (Morgenstern-Price (half-sine), FOS = 1.108).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 68.10 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 39.30 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 50.80 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.1096 | Bishop simplified | Chowdhury & Xu | 1.108 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.110 | 1.108 |
| Bishop simplified | 1.108 | 1.108 |

## 3.38 V021d — Chowdhury & Xu (1995) example 2, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 2, circle tangent to the base of clay 3.





*Figure 38. V021d: analysed circle (Morgenstern-Price (half-sine), FOS = 1.058).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 68.10 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 39.30 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 50.80 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.0639 | Bishop simplified | Chowdhury & Xu | 1.058 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.063 | 1.058 |
| Bishop simplified | 1.058 | 1.058 |

## 3.39 V021e — Chowdhury & Xu (1995) example 3, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 3 (Su = 136, 80, 102 kPa), circle tangent to the base of clay 2.





*Figure 39. V021e: analysed circle (Morgenstern-Price (half-sine), FOS = 2.245).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 136.0 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 80.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 102.0 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.2343 | Bishop simplified | Chowdhury & Xu | 2.245 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 2.248 | 2.245 |
| Bishop simplified | 2.245 | 2.245 |

## 3.40 V021f — Chowdhury & Xu (1995) example 3, Congress Street cut, circle tangent to the base

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 3, circle tangent to the base of clay 3.





*Figure 40. V021f: analysed circle (Morgenstern-Price (half-sine), FOS = 2.128).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Undrained (φ = 0) | 21.00 | Su = 136.0 | 0° |
| Clay 2 | Undrained (φ = 0) | 22.00 | Su = 80.00 | 0° |
| Clay 3 | Undrained (φ = 0) | 22.00 | Su = 102.0 | 0° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.1396 | Bishop simplified | Chowdhury & Xu | 2.128 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 2.138 | 2.128 |
| Bishop simplified | 2.128 | 2.128 |

## 3.41 V021g — Chowdhury & Xu (1995) example 4, Congress Street cut, circle tangent to the bas

*Chowdhury & Xu (1995); Ireland (1954).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 4 (c-φ clays with the digitised piezometric line), circle tangent to the base of clay 2.





*Figure 41. V021g: analysed circle (Morgenstern-Price (half-sine), FOS = 1.428).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Undrained (φ = 0) | 22.00 | Su = 0.00 | 0° |
| Clay 1 | Mohr-Coulomb | 17.00 | c' = 55.00 | 5.00° |
| Clay 2 | Mohr-Coulomb | 22.00 | c' = 43.00 | 7.00° |
| Clay 3 | Mohr-Coulomb | 22.00 | c' = 56.00 | 8.00° |
| Bed | Mohr-Coulomb | 22.00 | c' = 200.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.4239 | Bishop simplified | Chowdhury & Xu | 1.428 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.422 | 1.428 |
| Bishop simplified | – | 1.428 |

## 3.42 V022a — Chowdhury & Xu (1995) example 5, embankment on soft clay, circle tangent to y =

*Chowdhury & Xu (1995).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Chowdhury & Xu example 5: embankment fill (c′ = 10 kPa, φ′ = 12°) on soft clay (Su = 40 kPa), the geometry of V022a; circle tangent to the fill–clay interface.





*Figure 42. V022a: analysed circle (Morgenstern-Price (half-sine), FOS = 1.157).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 20.00 | c' = 10.00 | 12.00° |
| Layer 2 | Undrained (φ = 0) | 18.00 | Su = 40.00 | 0° |
| Hard layer | Undrained (φ = 0) | 20.00 | Su = 1000.0 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.1625 | Bishop simplified | Chowdhury & Xu | 1.159 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.158 | 1.157 |
| Bishop simplified | – | 1.159 |
| Bishop simplified (60 slices) | 1.160 | 1.159 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.206–0.212 | 0.206 |
| β lognormal (Monte Carlo) | – | 0.799–0.800 | 0.812 |
| β lognormal (Taylor series) | – | 0.787 | 0.788 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.210 | 0.208 |

## 3.43 V022b — Chowdhury & Xu (1995) example 5, embankment on soft clay, circle tangent to y =

*Chowdhury & Xu (1995).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V022a with the circle tangent to the base of the soft clay.





*Figure 43. V022b: analysed circle (Morgenstern-Price (half-sine), FOS = 1.174).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 20.00 | c' = 10.00 | 12.00° |
| Layer 2 | Undrained (φ = 0) | 18.00 | Su = 40.00 | 0° |
| Hard layer | Undrained (φ = 0) | 20.00 | Su = 1000.0 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.1479 | Bishop simplified | Chowdhury & Xu (1995) | 1.177 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.178 | 1.174 |
| Bishop simplified | 1.185 | 1.177 |

*Chowdhury & Xu's 1.1479 is about 2.5 % below the other programs on this family of circles.*

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.199–0.209 | 0.212 |
| β lognormal (Monte Carlo) | – | 0.789–0.820 | 0.789 |
| β lognormal (Taylor series) | – | 0.798 | 0.802 |

Probabilistic analysis on the same surface: 3 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| Pf, share FOS < 1 (Monte Carlo) | – | 0.214 | 0.216 |

## 3.44 V023 — LASH terminal trench, Duncan's Taylor series example

*Duncan (2000), J. Geotech. Geoenviron. Eng. 126(4).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Underwater trench in San Francisco Bay Mud: Su = 100 psf at el. −20 ft increasing 9.8 psf/ft, γ = 100 pcf, water at el. 0. Duncan's surface as a circle, Spencer; σγ = 3.3 pcf and σ of the Su gradient 1.2 psf/ft (a commercial program's Table 29.2). Converted to SI.





*Figure 44. V023: analysed circle (Spencer, FOS = 1.138).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| San Francisco Bay Mud | Undrained (φ = 0) | 15.71 | Su = 4.79 at y = -6.10, +1.54 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.17 | not stated | Duncan (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.145 | 1.138 |

*Duncan (2000) prints two decimals; the other programs give 1.145 on the same input.*

Probabilistic analysis on the same surface: 2 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Taylor series) | 0.900 Duncan (2000) | – | 0.892 |
| Pf lognormal (Taylor series) | 0.180 Duncan (2000) | – | 0.186 |

## 3.45 V024 — Dam on a layered foundation with artesian uplift, piezometric line (D&W fig. 6.39)

*Duncan & Wright, Soil Strength and Slope Stability, figs. 6.39–6.40.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Symmetric dam with a narrow clay core on 30 ft of clay over permeable sand; a commercial program's piezometric line from the underseepage; the circle tangent to el. 197 ft. Converted to SI.





*Figure 45. V024: analysed circle (Bishop simplified, FOS = 1.572).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Outer shell | Mohr-Coulomb | 19.64 | c' = 0.00 | 34.00° |
| Clay core | Mohr-Coulomb | 19.16 | c' = 4.79 | 26.00° |
| Foundation clay | Mohr-Coulomb | 19.32 | c' = 0.00 | 24.00° |
| Foundation sand | Mohr-Coulomb | 19.95 | c' = 0.00 | 32.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.57 | Bishop simplified | Duncan & Wright | 1.572 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.563–1.572 | 1.572 |
| Spencer | 1.557 | 1.562 |

## 3.46 V025 — Duncan & Wright fig. 6.38, piezometric line

*Duncan & Wright, Soil Strength and Slope Stability, fig. 6.38.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous 2:1 slope with a nearly flat piezometric line; critical circle search. Converted to SI; the water line was traced from a figure.





*Figure 46. V025: critical circle (Bishop simplified, FOS = 1.132).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 19.64 | c' = 9.58 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.141 | not stated | Duncan & Wright | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.142 | 1.132 |
| Spencer | 1.142 | 1.132 |

## 3.47 V026 — Duncan & Wright fig. 7.12, embankment on clay

*Duncan & Wright, Soil Strength and Slope Stability, fig. 7.12.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Sand embankment on a thick undrained clay foundation; critical circle search.





*Figure 47. V026: critical circle (Bishop simplified, FOS = 1.220).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Sand | Mohr-Coulomb | 140.0 | c' = 0.00 | 40.00° |
| Clay | Mohr-Coulomb | 140.0 | c' = 2500.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.22 | Bishop simplified | Duncan & Wright | 1.220 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.228 | 1.220 |
| Spencer, non-circular | 1.190 | 1.173 |

## 3.48 V027 — Duncan & Wright fig. 14.3, undrained clay

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.3.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Homogeneous undrained clay slope (φ = 0); critical circle search.





*Figure 48. V027: critical circle (Bishop simplified, FOS = 1.122).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 100.0 | c' = 1000.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.124 | Spencer | Duncan & Wright | 1.132 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.126 | 1.122 |
| Spencer | – | 1.132 |

## 3.49 V028 — Duncan & Wright fig. 14.3, undrained clay on a 46.5 ft foundation

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

The V027 φ = 0 clay slope with a 46.5 ft thick foundation; critical-circle search (the minimum of the toe and base-tangent circles of Tables 78.4–78.5).





*Figure 49. V028: critical circle (Bishop simplified, FOS = 1.122).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 100.0 | c' = 1000.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.124 | Spencer | Duncan & Wright | 1.122 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.126 | 1.122 |
| Spencer | – | 1.122 |

## 3.50 V029 — Duncan & Wright fig. 14.3, undrained clay on a 60 ft foundation

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

As V028 with a 60 ft thick foundation (Tables 78.6–78.7).





*Figure 50. V029: critical circle (Bishop simplified, FOS = 1.117).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 100.0 | c' = 1000.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.124 | Spencer | Duncan & Wright | 1.117 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.125 | 1.117 |
| Spencer | – | 1.117 |

## 3.51 V030 — Duncan & Wright fig. 14.4

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.4.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Cohesionless fill on undrained clay; critical circle search.





*Figure 51. V030: critical circle (Bishop simplified, FOS = 1.408).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 120.0 | c' = 0.00 | 30.00° |
| Clay | Mohr-Coulomb | 120.0 | c' = 450.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.40 | Spencer | Duncan & Wright | 1.399 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.412 | 1.408 |
| Spencer | – | 1.399 |

## 3.52 V031a — Duncan & Wright fig. 14.5, R = 87 ft

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.5.*

**Fixed circle · Units: imperial (ft, psf, pcf)**

Embankment over alternating cohesive and frictional layers; circle of radius 87 ft.





*Figure 52. V031a: analysed circle (Bishop simplified, FOS = 2.534).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 120.0 | c' = 1.00 | 35.00° |
| L60 | Mohr-Coulomb | 110.0 | c' = 950.0 | 0.00° |
| L45 | Mohr-Coulomb | 122.0 | c' = 1.00 | 32.00° |
| L35 | Mohr-Coulomb | 98.00 | c' = 500.0 | 0.00° |
| L25 | Mohr-Coulomb | 131.0 | c' = 1.00 | 37.00° |
| L20 | Mohr-Coulomb | 103.0 | c' = 600.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.56 | Spencer | Duncan & Wright | 2.531 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.549 | 2.534 |
| Spencer | 2.545 | 2.531 |

## 3.53 V031b — Duncan & Wright fig. 14.5, R = 102 ft

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.5.*

**Fixed circle · Units: imperial (ft, psf, pcf)**

As V031a with a deeper circle of radius 102 ft, reaching the weak clay layers.





*Figure 53. V031b: analysed circle (Bishop simplified, FOS = 1.389).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 120.0 | c' = 1.00 | 35.00° |
| L60 | Mohr-Coulomb | 110.0 | c' = 950.0 | 0.00° |
| L45 | Mohr-Coulomb | 122.0 | c' = 1.00 | 32.00° |
| L35 | Mohr-Coulomb | 98.00 | c' = 500.0 | 0.00° |
| L25 | Mohr-Coulomb | 131.0 | c' = 1.00 | 37.00° |
| L20 | Mohr-Coulomb | 103.0 | c' = 600.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.35 | Spencer | Duncan & Wright | 1.352 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.398 | 1.389 |
| Spencer | 1.359 | 1.352 |

## 3.54 V032a — Duncan & Wright fig. 14.7, deep circle

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.7.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Cohesionless embankment on an undrained clay foundation. Entry is limited to the crest and exit to the toe flat to find the published deep circle.





*Figure 54. V032a: critical circle (Bishop simplified, FOS = 1.224).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 124.0 | c' = 0.00 | 30.00° |
| Foundation | Mohr-Coulomb | 98.00 | c' = 500.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.21 | Spencer | Duncan & Wright | 1.205 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.230 | 1.224 |
| Spencer | 1.209 | 1.205 |

## 3.55 V032b — Duncan & Wright fig. 14.7, infinite-slope mechanism

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.7. Verification manual of a commercial slope stability program.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

The V032a embankment without search limits: the critical surface is the shallow infinite-slope sliver in the cohesionless fill (tan 30° / tan 26.6° = 1.155).





*Figure 55. V032b: critical circle (Bishop simplified, FOS = 1.156).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 124.0 | c' = 0.00 | 30.00° |
| Foundation | Mohr-Coulomb | 98.00 | c' = 500.0 | 0.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.15 | Spencer | Duncan & Wright | 1.156 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.155 | 1.156 |
| Spencer | 1.155 | 1.156 |

## 3.56 V033 — Duncan & Wright fig. 14.20a, water table

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.20a.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Cohesive-frictional fill over sand with a piezometric line; critical circle search. Converted to SI.





*Figure 56. V033: critical circle (Bishop simplified, FOS = 1.521).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 19.64 | c' = 28.73 | 25.00° |
| Sand | Mohr-Coulomb | 20.74 | c' = 0.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.535 | Spencer | Duncan & Wright | 1.533 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.533 | 1.521 |
| Spencer | – | 1.533 |
| Spencer, non-circular | 1.534 | 1.524 |

## 3.57 V034a — Duncan & Wright fig. 14.20b, Su = 200 + 15·depth

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.20b.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Granular fill over clay with undrained strength increasing linearly with depth; critical circle search.





*Figure 57. V034a: critical circle (Bishop simplified, FOS = 1.306).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 123.0 | c' = 0.00 | 36.00° |
| Clay | Undrained (φ = 0) | 97.00 | Su = 200.0 at y = 30.00, +15.00 psf/ft below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.30 | Spencer | Duncan & Wright | 1.276 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.313 | 1.306 |
| Spencer | – | 1.276 |
| Spencer, non-circular | 1.262 | 1.269 |

## 3.58 V034b — Duncan & Wright fig. 14.20b, Su = 300 psf

*Duncan & Wright, Soil Strength and Slope Stability, fig. 14.20b.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

As V034a with a constant undrained strength of 300 psf.





*Figure 58. V034b: critical circle (Bishop simplified, FOS = 1.329).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 123.0 | c' = 0.00 | 36.00° |
| Clay | Undrained (φ = 0) | 97.00 | Su = 300.0 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.312 | Spencer | Duncan & Wright | 1.328 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.335 | 1.329 |
| Spencer | – | 1.328 |
| Spencer, non-circular | 1.182 | 1.173 |

## 3.59 V035a — Duncan & Wright tieback, active

*Duncan & Wright, Soil Strength and Slope Stability, fig. 6.34.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Homogeneous slope with a 9000 lb/ft tieback applied horizontally at mid-height as an active force, on the reference printed GLE circle. Converted to SI.





*Figure 59. V035a: analysed circle (Morgenstern-Price (half-sine), FOS = 1.568).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| saturated clay | Undrained (φ = 0) | 15.39 | Su = 16.76 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.51 | not stated | Duncan & Wright | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.575 | 1.568 |

*Duncan & Wright's 1.51 is about 4 % below the other programs on this surface.*

## 3.60 V035b — Duncan & Wright tieback, passive

*Duncan & Wright, Soil Strength and Slope Stability, fig. 6.34.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V035a with the tieback applied as a passive force (divided by F), on the reference printed Bishop circle.





*Figure 60. V035b: analysed circle (Bishop simplified, FOS = 1.319).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| saturated clay | Undrained (φ = 0) | 15.39 | Su = 16.76 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.32 | Bishop simplified | Duncan & Wright | 1.319 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.324 | 1.319 |

## 3.61 V036a — Embankment on an undrained foundation, cz = 0 (D&W fig. 15.9)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 15.9.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Embankment (c′ = 0, φ′ = 35°, γ = 125 pcf) on a 20 ft undrained foundation, cu = 300 psf, constant; circular search. Converted to SI.





*Figure 61. V036a: critical circle (Bishop simplified, FOS = 0.757).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation | Undrained (φ = 0) | 15.71 | Su = 14.36 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.75 | Spencer | Duncan & Wright | 0.752 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.761 | 0.757 |
| Spencer | 0.756 | 0.752 |
| Spencer, non-circular | 0.740 | 0.737 |

## 3.62 V036b — Embankment on an undrained foundation, cz = 5 psf/ft

*Duncan & Wright, Soil Strength and Slope Stability, fig. 15.9.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V036a with cu increasing 5 psf/ft with depth.





*Figure 62. V036b: critical circle (Bishop simplified, FOS = 0.906).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation | Undrained (φ = 0) | 15.71 | Su = 14.36 at y = 6.10, +0.79 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.90 | Spencer | Duncan & Wright | 0.898 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.909 | 0.906 |
| Spencer | 0.898 | 0.898 |
| Spencer, non-circular | 0.903 | 0.884 |

## 3.63 V036c — Embankment on an undrained foundation, cz = 10 psf/ft

*Duncan & Wright, Soil Strength and Slope Stability, fig. 15.9.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V036a with cu increasing 10 psf/ft with depth.





*Figure 63. V036c: critical circle (Bishop simplified, FOS = 1.042).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation | Undrained (φ = 0) | 15.71 | Su = 14.36 at y = 6.10, +1.57 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.03 | Spencer | Duncan & Wright | 1.028 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.045 | 1.042 |
| Spencer | 1.032 | 1.028 |
| Spencer, non-circular | 1.018 | 1.017 |

## 3.64 V036d — Embankment on an undrained foundation, cz = 15 psf/ft

*Duncan & Wright, Soil Strength and Slope Stability, fig. 15.9.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V036a with cu increasing 15 psf/ft with depth.





*Figure 64. V036d: critical circle (Bishop simplified, FOS = 1.152).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation | Undrained (φ = 0) | 15.71 | Su = 14.36 at y = 6.10, +2.36 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.13 | Spencer | Duncan & Wright | 1.132 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.154 | 1.152 |
| Spencer | 1.134 | 1.132 |
| Spencer, non-circular | 1.116 | 1.121 |

## 3.65 V037 — Geogrid-reinforced fill on rock (D&W fig. 7.28)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 7.28.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

24 ft fill slope (φ′ = 37°) on a strong rock foundation with five 800 lb/ft geogrids, 20 ft long, every 4 ft; circular search for surfaces through the toe. Converted to SI.





*Figure 65. V037: critical circle (Bishop simplified, FOS = 1.613).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| fill | Mohr-Coulomb | 20.42 | c' = 0.00 | 37.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.61 | not stated | Duncan & Wright | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.629 | 1.613 |
| Spencer | 1.620 | 1.607 |

## 3.66 V038 — Homogeneous dam with a piezometric line (D&W fig. 7.19)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 7.19.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous embankment (c′ = 100 psf, φ′ = 30°, γ = 100 pcf) with the pool at el. 40 ft and a commercial program's piezometric line; critical-circle search. Converted to SI.





*Figure 66. V038: critical circle (Bishop simplified, FOS = 1.069).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 15.71 | c' = 4.79 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.16 | not stated | Duncan & Wright | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.070–1.090 | 1.069 |
| Spencer | 1.100 | 1.077 |

*Duncan & Wright's 1.16 is 5–8 % above the other programs (1.07–1.10) on the same input.*

## 3.67 V039 — James Bay dyke (Duncan & Wright fig. 7.16)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 7.16.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Granular fill embankment with a wide berm (c′ = 0, φ′ = 30°) on a 4 m clay crust (Su = 41), 8 m marine clay (34.5) and 7 m lacustrine clay (31.2); circular search. The critical circle is deep and tangent to the base of the lacustrine clay.





*Figure 67. V039: critical circle (Bishop simplified, FOS = 1.424).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 20.00 | c' = 0.00 | 30.00° |
| Clay crust | Undrained (φ = 0) | 20.00 | Su = 41.00 | 0° |
| Marine clay | Undrained (φ = 0) | 18.80 | Su = 34.50 | 0° |
| Lacustrine clay | Undrained (φ = 0) | 20.30 | Su = 31.20 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.45 | Bishop simplified | Duncan & Wright | 1.424 |
| 1.17 | Spencer, non-circular | Duncan & Wright | 1.155 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | – | 1.424 |
| Spencer | – | 1.421 |
| Spencer, non-circular | 1.167 | 1.155 |

## 3.68 V040 — James Bay dyke, reference model (deterministic)

*El-Ramly et al. (2002); Duncan & Wright fig. 7.16.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The James Bay dyke as a commercial program models it (crest 36 m, berm at 30 m, clay crust Su = 43 kPa, till below y = 5); critical-circle search, deterministic.





*Figure 68. V040: critical circle (Bishop simplified, FOS = 1.433).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 20.00 | c' = 0.00 | 30.00° |
| Clay crust | Undrained (φ = 0) | 18.80 | Su = 43.00 | 0° |
| Marine clay | Undrained (φ = 0) | 18.80 | Su = 34.50 | 0° |
| Lacustrine clay | Undrained (φ = 0) | 20.30 | Su = 31.20 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.461 | 1.433 |

## 3.69 V041a — Submerged slope, pool 30 ft above the crest (D&W fig. 6.27)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 6.27.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Fully submerged homogeneous slope (c = 100 psf, φ = 20°, γ = 128 pcf) with the pool 30 ft above the crest: the extra water weight and pore pressure cancel. Converted to SI.





*Figure 69. V041a: critical circle (Bishop simplified, FOS = 1.597).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 20.11 | c' = 4.79 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.60 | Spencer | Duncan & Wright | 1.594 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.603 | 1.597 |
| Spencer | 1.599 | 1.594 |
| Spencer, non-circular | 1.592 | 1.591 |

## 3.70 V041b — Submerged slope, pool 60 ft above the crest (D&W fig. 6.27)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 6.27.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V041a with the pool 60 ft above the crest: the same factor of safety.





*Figure 70. V041b: critical circle (Bishop simplified, FOS = 1.597).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 20.11 | c' = 4.79 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.60 | Spencer | Duncan & Wright | 1.594 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.603 | 1.597 |
| Spencer | 1.599 | 1.594 |
| Spencer, non-circular | 1.590 | 1.589 |

## 3.71 V042 — Thick-core dam with a piezometric line (D&W fig. 7.24)

*Duncan & Wright, Soil Strength and Slope Stability, fig. 7.24.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Symmetric dam with a thick clay core (φ′ = 20°) in a shell (φ′ = 38°), pond at el. 315 ft, a commercial program's piezometric line; the deep circle. Converted to SI.





*Figure 71. V042: analysed circle (Bishop simplified, FOS = 1.591).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Shell | Mohr-Coulomb | 21.99 | c' = 0.00 | 38.00° |
| Core | Mohr-Coulomb | 18.85 | c' = 0.00 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.67 | not stated | Duncan & Wright | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.584–1.591 | 1.591 |
| Spencer | 1.648 | 1.658 |
| Morgenstern-Price (half-sine) | 1.670 | 1.670 |

## 3.72 V043 — Syncrude tailings dyke (El-Ramly et al.), composite circle

*El-Ramly, Morgenstern & Cruden (2003), Can. Geotech. J. 40.*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Cohesionless tailings sand, glacio-fluvial sands and tills (φ = 34°) on a presheared clay-shale (φ = 7.5°) with a water table; the reference circle (327.5, 394, R = 124) reaches below the model base, so the surface follows the base there (composite).





*Figure 72. V043: analysed surface (Bishop simplified, FOS = 1.320).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Tailing sand (TS) | Mohr-Coulomb | 20.00 | c' = 0.00 | 34.00° |
| Glacio-fluvial sand (Pf4) | Mohr-Coulomb | 17.00 | c' = 0.00 | 34.00° |
| Sandy till (Pgs) | Mohr-Coulomb | 17.00 | c' = 0.00 | 34.00° |
| Clayey till (Pgc) | Mohr-Coulomb | 17.00 | c' = 0.00 | 7.50° |
| Disturbed clay-shale (Kca) | Mohr-Coulomb | 17.00 | c' = 0.00 | 7.50° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.31 | Bishop simplified | El-Ramly et al. | 1.320 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.320 | 1.320 |

## 3.73 V044 — Fredlund & Krahn (1977), dry

*Fredlund, D.G. & Krahn, J. (1977). Comparison of slope stability methods of analysis. Can. Geotech. J. 14(3).*

**Fixed circle · Units: imperial (ft, psf, pcf)**

Homogeneous 2:1 slope, 40 ft high, on a firm base; the classic comparison problem of Fredlund & Krahn analysed with the published circle and no pore pressure.





*Figure 73. V044: analysed circle (Bishop simplified, FOS = 2.076).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 120.0 | c' = 600.0 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.08 | Bishop simplified | Fredlund & Krahn | 2.076 |
| 2.076 | Morgenstern-Price (half-sine) | Fredlund & Krahn | 2.072 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | – | 2.076 |
| Morgenstern-Price (half-sine) | – | 2.072 |

## 3.74 V045 — Fredlund & Krahn (1977), with water table

*Fredlund, D.G. & Krahn, J. (1977). Can. Geotech. J. 14(3).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The Fredlund & Krahn slope with a piezometric line, analysed on the published circle. Converted to SI.





*Figure 74. V045: analysed circle (Bishop simplified, FOS = 1.829).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.85 | c' = 28.73 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.834 | Bishop simplified | Fredlund & Krahn | 1.829 |
| 1.832 | Morgenstern-Price (half-sine) | Fredlund & Krahn | 1.827 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | – | 1.829 |
| Morgenstern-Price (half-sine) | – | 1.827 |

## 3.75 V046 — Fredlund & Krahn slope on a weak seam, composite surface

*Fredlund, D.G. & Krahn, J. (1977). Can. Geotech. J. 14(3).*

**Specified non-circular surface · Units: imperial (ft, psf, pcf)**

The a related problem slope with a 1 ft weak seam (c′ = 0, φ′ = 10°) on the impenetrable base at el. 15; the published circle (120, 90, R = 80) reaches below the base, so the surface follows the arc down to the base, runs along the seam and climbs back on the arc. Dry.





*Figure 75. V046: analysed surface (Bishop simplified, FOS = 1.380).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Upper soil | Mohr-Coulomb | 120.0 | c' = 600.0 | 20.00° |
| Weak seam | Mohr-Coulomb | 120.0 | c' = 0.00 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.37 | Morgenstern-Price (half-sine) | Fredlund & Krahn | 1.370 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.382 | 1.380 |
| Spencer | 1.382 | 1.379 |
| Morgenstern-Price (half-sine) | – | 1.370 |

## 3.76 V047a — ACADS 1(a), homogeneous slope, dry

*Giam & Donald (1989).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

ACADS 1(a): homogeneous 2:1 slope, 10 m high (c′ = 3 kPa, φ′ = 19.6°, γ = 20 kN/m³), dry; critical-circle search.





*Figure 76. V047a: critical circle (Bishop simplified, FOS = 0.985).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 3.00 | 19.60° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Spencer | ACADS | 0.984 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.987–0.992 | 0.985 |
| Spencer | 0.986 | 0.984 |
| Janbu corrected | 0.990 | 0.986 |
| Morgenstern-Price (half-sine) | 0.991 | 0.984 |

## 3.77 V047b — ACADS tension crack, reference crack depth 3.6 m (results correspond to a dry c

*Giam & Donald (1989), ACADS problem 1(b).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

ACADS 1(b) as a commercial program models it: c′ = 32 kPa, φ′ = 10°, a 3.6 m tension crack (dry); critical-circle search.





*Figure 77. V047b: critical circle (Bishop simplified, FOS = 1.659).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 32.00 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.65–1.70 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.664 | 1.659 |
| Morgenstern-Price (half-sine) | 1.660 | 1.656 |

## 3.78 V048 — ACADS 1(b), water-filled tension crack

*Giam & Donald (1989), ACADS problem 1(b).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The ACADS 1(a) slope (10 m high, 2:1) with c' = 32 kPa, φ' = 10° and a water-filled tension crack 4 m deep, the crack zone of a commercial program's Fig. 2.1 (35 → 31 m; the formula 2c/(γ√Ka) gives 3.814 m); critical circle search.





*Figure 78. V048: critical circle (Bishop simplified, FOS = 1.587).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 20.00 | c' = 32.00 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.65 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.596 | 1.587 |
| Spencer | 1.592 | 1.582 |
| Janbu corrected | 1.489 | 1.475 |

*The ACADS reference 1.65 corresponds to a dry tension crack; with the crack filled with water the programs give about 1.59–1.60.*

## 3.79 V049 — ACADS 1(c), three-layer slope

*Giam & Donald (1989), ACADS slope stability programs review.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Non-homogeneous three-layer slope (ACADS 1c); critical-circle search.





*Figure 79. V049: critical circle (Bishop simplified, FOS = 1.403).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 19.50 | c' = 0.00 | 38.00° |
| Soil #2 | Mohr-Coulomb | 19.50 | c' = 5.30 | 23.00° |
| Soil #3 | Mohr-Coulomb | 19.50 | c' = 7.20 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.39 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.403–1.405 | 1.403 |
| Spencer | 1.375 | 1.372 |
| Janbu corrected | 1.357 | 1.355 |
| Morgenstern-Price (half-sine) | 1.382 | 1.372 |

## 3.80 V050a — ACADS 3(b), weak layer, specified non-circular surface

*Giam & Donald (1989), ACADS problem 3(b).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Slope with a 0.5 m weak layer (c' = 0, φ' = 10°) and a water table at its base, analysed on the published four-point non-circular surface that runs along the weak layer.





*Figure 80. V050a: analysed surface (Janbu corrected, FOS = 1.294).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.84 | c' = 28.50 | 20.00° |
| Weak layer | Mohr-Coulomb | 18.84 | c' = 0.00 | 10.00° |
| Soil 1 below | Mohr-Coulomb | 18.84 | c' = 28.50 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.34 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 1.294 | 1.294 |
| Spencer | 1.277 | 1.276 |
| Morgenstern-Price (half-sine) | 1.261 | 1.260 |

*The ACADS referee value comes from the 1989 survey; programs today give 1.26–1.29 on the specified surface.*

## 3.81 V050b — ACADS 3(a), weak layer, non-circular search

*Giam & Donald (1989), ACADS problem 3(a).*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

As V050a, with a circular search followed by non-circular optimisation; the critical surface slides along the weak layer with a back scarp to the crest.





*Figure 81. V050b: critical surface (Spencer, non-circular, FOS = 1.228).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.84 | c' = 28.50 | 20.00° |
| Weak layer | Mohr-Coulomb | 18.84 | c' = 0.00 | 10.00° |
| Soil 1 below | Mohr-Coulomb | 18.84 | c' = 28.50 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.24–1.27 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.246 | 1.228 |

*ACADS accepted 1.24–1.27; cSlope's search finds a surface along the weak layer at 1.228 (Spencer), unchanged at 50, 100 and 200 slices.*

## 3.82 V051 — ACADS 4, weak layer, water table and surcharges

*Giam & Donald (1989), ACADS slope stability programs review.*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

Weak-layer slope with a piezometric line and two surcharge strips (20 kPa on the bench, 20–40 kPa ramp on the crest); non-circular search. The published spread is wide: a search-difficulty benchmark.





*Figure 82. V051: critical surface (Spencer, non-circular, FOS = 0.698).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.84 | c' = 28.50 | 20.00° |
| Weak Layer | Mohr-Coulomb | 18.84 | c' = 0.00 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.78 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 0.707 | 0.698 |

*The ACADS referee value 0.78 comes from the 1989 survey, where the participating programs averaged 0.81; optimised non-circular searches today give about 0.68–0.71.*

## 3.83 V052a — Talbingo Dam, end of construction

*Giam & Donald (1989), ACADS slope stability programs review.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

ACADS 2(a): Talbingo Dam, four zones, critical-circle search. The minimum is a shallow slide parallel to the steeper upstream face.





*Figure 83. V052a: critical circle (Bishop simplified, FOS = 1.964).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Rockfill | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Transitions | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Filter | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Core | Mohr-Coulomb | 18.10 | c' = 85.00 | 23.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.95 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.948–1.951 | 1.964 |
| Spencer | 1.948 | 1.964 |
| Janbu corrected | 1.949 | 1.974 |

## 3.84 V052b — Talbingo Dam, specified circle

*Giam & Donald (1989), ACADS slope stability programs review.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

ACADS 2(b): Talbingo Dam on the circle (100.3, 291.0, R = 278.8).





*Figure 84. V052b: analysed circle (Bishop simplified, FOS = 2.206).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Rockfill | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Transitions | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Filter | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Core | Mohr-Coulomb | 18.10 | c' = 85.00 | 23.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.29 | not stated | Giam & Donald (1989), ACADS | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.208 | 2.206 |
| Spencer | 2.292 | 2.290 |
| Janbu corrected | 2.073 | 2.073 |
| Morgenstern-Price (half-sine) | 2.299 | 2.299 |

## 3.85 V053 — Greco (1996) ex. 5 / Chen & Shao weak-layer slope, reference geometry

*Greco (1996) example 5; Chen & Shao (1988).*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

Greco's weak-seam slope (V054) with a commercial program's geometry and water table; circular search with non-circular optimisation, vertical pore-pressure head.





*Figure 85. V053: critical surface (Spencer, non-circular, FOS = 1.009).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 20.00 | c' = 9.80 | 35.00° |
| Layer 2 | Mohr-Coulomb | 19.00 | c' = 58.80 | 25.00° |
| Layer 3 | Mohr-Coulomb | 21.50 | c' = 19.80 | 30.00° |
| Layer 4 | Mohr-Coulomb | 21.50 | c' = 9.80 | 16.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.01–1.03 | Spencer, non-circular | Chen & Shao (1988) | 1.009 |
| 1.08 | not stated | Greco (1996) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.010 | 1.009 |

*Chen & Shao give 1.01–1.03 for a surface sliding along the weak layer; Greco's 1.08 is for the surface of his own search.*

## 3.86 V054 — Greco (1996) example 5 / Chen & Shao (1988)

*Greco (1996), example 5; Chen & Shao (1988).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Four layers including a weak seam, with a water table; critical circle search, vertical pore-pressure head.





*Figure 86. V054: critical circle (Bishop simplified, FOS = 1.086).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 20.00 | c' = 9.80 | 35.00° |
| Layer 2 | Mohr-Coulomb | 19.00 | c' = 58.80 | 25.00° |
| Layer 3 | Mohr-Coulomb | 21.50 | c' = 19.80 | 30.00° |
| Seam | Mohr-Coulomb | 21.50 | c' = 9.80 | 16.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.08 | Spencer, nearly circular surface | Greco (1996) | 1.091 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.087 | 1.086 |
| Spencer | 1.093 | 1.091 |

## 3.87 V055 — Griffiths & Lane example 2, slope with a foundation layer

*Griffiths & Lane (1999), Géotechnique 49(3).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The 2:1 slope (c/γH = 0.05, φ = 20°) on a foundation of the same soil; unconstrained circular search finds the toe circle. Converted to SI.





*Figure 87. V055: critical circle (Spencer, FOS = 1.366).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| soil | Mohr-Coulomb | 19.64 | c' = 14.96 | 20.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.40 | finite elements | Griffiths & Lane | 1.366 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.366 | 1.366 |

## 3.88 V056 — Griffiths & Lane example 3, thin weak layer, cu2/cu1 = 0.2

*Griffiths & Lane (1999), Géotechnique 49(3).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Undrained clay slope with a thin weak layer at a fifth of the strength, on the three-line wedge through the layer (the paper's Janbu mechanism). Converted to SI.





*Figure 88. V056: analysed surface (Janbu corrected, FOS = 0.499).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Surrounding clay | Undrained (φ = 0) | 19.64 | Su = 74.81 | 0° |
| Thin weak layer | Undrained (φ = 0) | 19.64 | Su = 14.96 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.485 | Janbu wedge | Griffiths & Lane | 0.499 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | – | 0.499 |

## 3.89 V057a — Griffiths & Lane example 4, cu2/cu1 = 1 (deep base circle)

*Griffiths & Lane (1999), Géotechnique 49(3).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Undrained clay slope over a foundation of the same strength; the deep base circle. Converted to SI.





*Figure 89. V057a: critical circle (Spencer, FOS = 1.471).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Slope clay | Undrained (φ = 0) | 19.64 | Su = 74.81 | 0° |
| Foundation clay | Undrained (φ = 0) | 19.64 | Su = 74.81 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.46 | limit-equilibrium chart | Griffiths & Lane | 1.471 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.468 | 1.471 |

## 3.90 V057b — Griffiths & Lane example 4, cu2/cu1 = 2 (toe circle)

*Griffiths & Lane (1999), Géotechnique 49(3).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The same slope over a foundation twice as strong; the shallow toe circle. Converted to SI.





*Figure 90. V057b: critical circle (Spencer, FOS = 2.023).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Slope clay | Undrained (φ = 0) | 19.64 | Su = 74.81 | 0° |
| Foundation clay | Undrained (φ = 0) | 19.64 | Su = 149.6 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.04 | limit-equilibrium chart | Griffiths & Lane | 2.023 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 2.022 | 2.023 |

## 3.91 V058 — Griffiths & Lane example 6, earth dam with full reservoir

*Griffiths & Lane (1999), Géotechnique 49(3).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Two-sided earth dam with the reservoir full and a piezometric line; circular search. Converted to SI.





*Figure 91. V058: critical circle (Spencer, FOS = 1.915).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 18.20 | c' = 13.80 | 37.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.90 | finite elements | Griffiths & Lane | 1.915 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.915 | 1.915 |

## 3.92 V059a — Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.4

*Guo & Griffiths (2020), Can. Geotech. J. 57.*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

18 m embankment at 1V:2H (Su = 60 kPa) on an 18 m undrained foundation (Su = 84 kPa), γ = 20, firm base; optimised non-circular search. The deep mechanism governs.





*Figure 92. V059a: critical surface (Spencer, non-circular, FOS = 1.216).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Undrained (φ = 0) | 20.00 | Su = 60.00 | 0° |
| Foundation | Undrained (φ = 0) | 20.00 | Su = 84.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.215 | 1.216 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.93 V059b — Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.5

*Guo & Griffiths (2020), Can. Geotech. J. 57.*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

18 m embankment at 1V:2H (Su = 60 kPa) on an 18 m undrained foundation (Su = 90 kPa), γ = 20, firm base; optimised non-circular search. The deep mechanism governs.





*Figure 93. V059b: critical surface (Spencer, non-circular, FOS = 1.292).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Undrained (φ = 0) | 20.00 | Su = 60.00 | 0° |
| Foundation | Undrained (φ = 0) | 20.00 | Su = 90.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.290 | 1.292 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.94 V059c — Guo & Griffiths two-layer undrained slope, cu2/cu1 = 1.6

*Guo & Griffiths (2020), Can. Geotech. J. 57.*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

18 m embankment at 1V:2H (Su = 60 kPa) on an 18 m undrained foundation (Su = 96 kPa), γ = 20, firm base; optimised non-circular search. The shallow mechanism governs.





*Figure 94. V059c: critical surface (Spencer, non-circular, FOS = 1.314).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Undrained (φ = 0) | 20.00 | Su = 60.00 | 0° |
| Foundation | Undrained (φ = 0) | 20.00 | Su = 96.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.315 | 1.314 |

*The paper gives its results in figures only; the comparison is with the other programs.*

## 3.95 V060a — Cannon Dam end of construction (Hassan & Wolff), critical circle

*Hassan & Wolff (1999), J. Geotech. Geoenviron. Eng. 125(4).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Two clay fills with a sand-filter strip under the crest and a spoil-covered downstream toe; Bishop search for the minimum factor of safety at the mean strengths. The reliability index on the minimum-β surface is V060b.





*Figure 95. V060a: critical circle (Bishop simplified, FOS = 2.530).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II clay fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Phase I clay fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 23.00 | c' = 1000.0 | 45.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.529–2.551 | 2.530 |

*Hassan & Wolff give 2.753 on a fixed circle (V062a), not a search result.*

## 3.96 V060b — Cannon Dam end of construction (Hassan & Wolff), reliability on the minimum-β c

*Hassan & Wolff (1999), J. Geotech. Geoenviron. Eng. 125(4).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V060a dam on the circle of minimum reliability index: Phase I fill φ = 8.5° ± 8.5°, c = 117.8 ± 58.9 kPa; Phase II fill c = 143.6 ± 79 kPa, φ = 15° ± 9°, treated as independent normal variables (another program's Taylor series has no correlation term); Bishop.





*Figure 96. V060b: analysed circle (Bishop simplified, FOS = 2.974).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II clay fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Phase I clay fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 23.00 | c' = 1000.0 | 45.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.973 | 2.974 |

*The source gives reliability indices on fixed circles; no factor of safety is published for the minimum-β circle.*

Probabilistic analysis on the same surface: 4 normal variables (independent); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Taylor series) | – | 3.353 | 3.354 |

## 3.97 V061 — Clarence Cannon Dam (Wolff & Harr), specified surface

*Wolff & Harr (1987).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Phase I and II fills with a chimney drain and a cutoff trench to rock, flat water table at el. 557 ft; the printed non-circular surface. Converted to SI.





*Figure 97. V061: analysed surface (Morgenstern-Price (half-sine), FOS = 2.384).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 23.56 | c' = 138.9 | 14.80° |
| Sand drain | Mohr-Coulomb | 18.85 | c' = 0.00 | 30.00° |
| Phase I fill | Mohr-Coulomb | 23.56 | c' = 106.8 | 6.34° |
| Foundation sand | Mohr-Coulomb | 18.85 | c' = 0.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.36 | Morgenstern-Price (half-sine) | Wolff & Harr | 2.384 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 2.384 | 2.384 |
| Spencer | 2.423 | 2.423 |

## 3.98 V062a — Clarence Cannon Dam, surface 7A

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 7A (centre 320.175, 313.336; tangent elevation 145.347), Bishop.





*Figure 98. V062a: analysed circle (Bishop simplified, FOS = 2.549).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.753 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.551–2.560 | 2.549 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 10.953 | 11.034 |

## 3.99 V062b — Clarence Cannon Dam, surface 7B

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 7B (centre 295.235, 277.589; tangent elevation 156.298), Bishop.





*Figure 99. V062b: analysed circle (Bishop simplified, FOS = 2.815).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.352 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.806–2.820 | 2.815 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 4.351 | 4.402 |

## 3.100 V062c — Clarence Cannon Dam, surface 7C

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 7C (centre 303.683, 310.206; tangent elevation 155.928), Bishop.





*Figure 100. V062c: analysed circle (Bishop simplified, FOS = 2.779).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.523 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.771–2.777 | 2.779 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 4.263 | 4.325 |

## 3.101 V062d — Clarence Cannon Dam, surface 7D

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 7D (centre 322.152, 310.206; tangent elevation 145.36), Bishop.





*Figure 101. V062d: analysed circle (Bishop simplified, FOS = 2.577).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.457 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.583–2.589 | 2.577 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 11.092 | 11.076 |

## 3.102 V062e — Clarence Cannon Dam, surface 7E

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 7E (centre 327.693, 324.018; tangent elevation 147.163), Bishop.





*Figure 102. V062e: analysed circle (Bishop simplified, FOS = 2.690).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.602 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.692–2.703 | 2.690 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 10.281 | 10.329 |

## 3.103 V062f — Clarence Cannon Dam, surface 8B

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 8B (centre 304.239, 307.858; tangent elevation 155.311), Bishop.





*Figure 103. V062f: analysed circle (Bishop simplified, FOS = 2.673).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.995 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.672–2.673 | 2.673 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 4.858 | 4.933 |

## 3.104 V062g — Clarence Cannon Dam, surface 8F

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 8F (centre 313.114, 304.784; tangent elevation 160.368), Bishop.





*Figure 104. V062g: analysed circle (Bishop simplified, FOS = 3.592).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 3.916 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 3.586–3.598 | 3.592 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 5.485 | 5.528 |

## 3.105 V062h — Clarence Cannon Dam, surface 8G

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 8G (centre 314.856, 305.604; tangent elevation 165.756), Bishop.





*Figure 105. V062h: analysed circle (Bishop simplified, FOS = 6.063).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 10.576 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 6.069–6.074 | 6.063 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 5.563 | 5.490 |

## 3.106 V062i — Clarence Cannon Dam, surface 8H

*Hassan & Wolff (1999).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Six-zone embankment dam on sand over limestone, analysed on the published circle 8H (centre 316.198, 305.604; tangent elevation 170.537), Bishop.





*Figure 106. V062i: analysed circle (Bishop simplified, FOS = 11.567).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Phase II fill | Mohr-Coulomb | 22.00 | c' = 143.6 | 15.00° |
| Phase I fill | Mohr-Coulomb | 22.00 | c' = 117.8 | 8.50° |
| Sand filter | Mohr-Coulomb | 22.00 | c' = 0.00 | 35.00° |
| Spoil fill | Mohr-Coulomb | 25.00 | c' = 5.00 | 35.00° |
| Foundation sand | Mohr-Coulomb | 20.00 | c' = 5.00 | 18.00° |
| Limestone | Mohr-Coulomb | 20.00 | c' = 100.0 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 6.293 | not stated | Hassan & Wolff (1999) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 11.583 | 11.567 |

*Hassan & Wolff's own factors of safety differ from all programs by 3–75 %, while the programs agree with each other within 0.5 %.*

Probabilistic analysis on the same surface: 4 normal variables (ρ = -0.55, ρ = 0.1 between pairs); Taylor series (mean ± σ) and Monte Carlo with 10000 samples (seed 1). Differences in β and Pf are absolute.

| Quantity | Published | Other programs | cSlope |
|---|---|---|---|
| β lognormal (Monte Carlo) | – | 6.394 | 6.431 |

## 3.107 V063 — Huang & Jia earth dam, dry

*Huang & Jia (2008).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous earth dam (c′ = 13.8 kPa, φ′ = 37°, γ = 18.2 kN/m³) before the reservoir is filled; circular search.





*Figure 107. V063: critical circle (Spencer, FOS = 2.451).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 18.20 | c' = 13.80 | 37.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.43 | finite-element strength reduction | Huang & Jia | 2.451 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 2.455 | 2.451 |

## 3.108 V064 — Leshchinsky & Han MSE wall, five tiers

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Five 1.8 m tiers (Ta = 10.1 kN/m).





*Figure 108. V064: analysed circle (Bishop simplified, FOS = 1.017).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 1.017 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.020 | 1.017 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.109 V065 — Leshchinsky & Han MSE wall, weak foundation

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V066a on a c = 0, φ = 18° foundation.





*Figure 109. V065: analysed circle (Spencer, FOS = 0.961).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 0.00 | 18.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 0.979 |
| 0.86 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 0.964 | 0.961 |
| Bishop simplified | – | 0.979 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.110 V066a — Leshchinsky & Han three-tier MSE wall, baseline

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Three 3 m tiers offset 1.2 m, block facing, geotextiles every 0.6 m (L = 6.3 m, Ta = 10 kN/m, applied horizontally, passive), a commercial program's critical circle.





*Figure 110. V066a: analysed circle (Bishop simplified, FOS = 1.031).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 1.031 |
| 0.99 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.040 | 1.031 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.111 V066b — Leshchinsky & Han MSE wall, L = 4.2 m

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V066a with 4.2 m geotextiles (Ta = 11.4 kN/m).





*Figure 111. V066b: analysed circle (Spencer, FOS = 1.011).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 1.013 |
| 0.98 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.011 | 1.011 |
| Bishop simplified | – | 1.013 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.112 V066c — Leshchinsky & Han MSE wall, two reinforcement types

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V066a with two reinforcement strengths (7.5 and 11.0 kN/m).





*Figure 112. V066c: analysed circle (Bishop simplified, FOS = 1.012).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 1.012 |
| 1.01 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.004 | 1.012 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.113 V066d — Leshchinsky & Han MSE wall, water hw = 3 m

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V066a with the water table 3 m above the toe: pore pressure in the foundation only (drained fill); Ta = 9.25 kN/m. The pond in front of the wall is left out of this comparison: another program's water loads apply no pressure to the vertical facing, whereas cSlope does.





*Figure 113. V066d: analysed circle (Bishop simplified, FOS = 1.010).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 1.010 |
| 1.01 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.010 | 1.010 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.114 V066e — Leshchinsky & Han MSE wall, surcharge

*Leshchinsky & Han (2004), J. Geotech. Geoenviron. Eng. 130(12).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V066a with a 20 kPa surcharge.





*Figure 114. V066e: analysed circle (Bishop simplified, FOS = 0.961).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Reinforced and retained fill | Mohr-Coulomb | 18.00 | c' = 0.00 | 34.00° |
| Foundation soil | Mohr-Coulomb | 18.00 | c' = 10.00 | 34.00° |
| Blocks | Mohr-Coulomb | 18.00 | c' = 2.50 | 34.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | Bishop simplified, circular | Leshchinsky & Han (2004) | 0.961 |
| 1.02 | finite differences | Leshchinsky & Han (2004) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.958 | 0.961 |

*Leshchinsky & Han give 1.00 with Bishop's method for every variant of the wall (the reinforcement was designed for that value), and a finite-difference value.*

## 3.115 V067 — Low (1989), layered undrained clay

*Low (1989).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Embankment on three undrained clay layers of different strength; critical circle search.





*Figure 115. V067: critical circle (Bishop simplified, FOS = 1.436).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| A | Undrained (φ = 0) | 18.00 | Su = 30.00 | 0° |
| B | Undrained (φ = 0) | 18.00 | Su = 20.00 | 0° |
| C | Undrained (φ = 0) | 18.00 | Su = 150.0 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.44 | Ordinary | Low (1989) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.439 | 1.436 |

## 3.116 V068 — Low (1989), stiff crust over soft clays, published circle

*Low (1989).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Stiff upper slope on two undrained clays, the lowest with Su increasing linearly with depth (S = f(datum)), on the circle that carries a commercial program's published values.





*Figure 116. V068: analysed circle (Bishop simplified, FOS = 1.197).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper | Mohr-Coulomb | 20.00 | c' = 95.00 | 15.00° |
| Middle | Mohr-Coulomb | 20.00 | c' = 15.00 | 0.00° |
| Lower | S = f(datum) | 20.00 | Su = 15.00 at y = 4.00, 3.75 kPa/m below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.36 | Ordinary | Low (1989) | – |
| 1.14 | Bishop simplified | Low (1989) | 1.197 |
| 1.17 | not stated | Kim (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.192 | 1.197 |

*Low's Bishop value 1.14 is about 4 % below the other programs (1.19); Kim (2002) gives 1.17.*

## 3.117 V069a — Morgenstern (1963) complete drawdown, 3:1

*Morgenstern, N. (1963). Stability charts for earth slopes during rapid drawdown. Géotechnique 13(2).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

3:1 slope after complete drawdown: piezometric line on the slope face, base at the toe (D = 1). Pore pressure from the vertical head. Converted to SI.





*Figure 117. V069a: critical circle (Bishop simplified, FOS = 1.200).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 19.60 | c' = 14.94 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.20 | stability chart | Morgenstern | 1.200 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | – | 1.200 |
| Spencer | – | 1.205 |

## 3.118 V069b — Morgenstern complete drawdown, the reference circle

*Morgenstern, N. (1963). Stability charts for earth slopes during rapid drawdown. Géotechnique 13(2). Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V069a slope after complete drawdown on the reference critical circle (Fig. 100.2); pore pressure from the vertical head. Converted to SI.





*Figure 118. V069b: analysed circle (Bishop simplified, FOS = 1.209).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 19.60 | c' = 14.94 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.20 | stability chart | Morgenstern (1963) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.212 | 1.209 |

*Morgenstern's 1.2 is read from a stability chart.*

## 3.119 V070 — Partial drawdown, $\bar{B} = 1$ (Morgenstern chart)

*Morgenstern (1963).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous embankment after a partial drawdown from 100 to 50 ft with $\bar{B} = 1$: the piezometric line follows the face above the pool and stays at the pool below it, which loads the submerged face. Converted to SI.





*Figure 119. V070: critical circle (Bishop simplified, FOS = 1.415).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Morgenstern soil | Mohr-Coulomb | 19.60 | c' = 14.94 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.41 | stability chart | Morgenstern | 1.415 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.417 | 1.415 |
| Spencer | 1.422 | 1.421 |

## 3.120 V071a — Pockoski & Duncan (2000) slope 1

*Pockoski & Duncan (2000), slope 1.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

2:1 slope with a water table, on the circle published by a commercial program; pore pressure from the vertical head below the piezometric line. Converted to SI.





*Figure 120. V071a: analysed circle (Bishop simplified, FOS = 1.290).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Mohr-Coulomb | 18.85 | c' = 14.36 | 30.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.293 | 1.290 |
| Spencer | 1.300 | 1.296 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.121 V071b — Pockoski & Duncan slope 1, circular search

*Pockoski & Duncan (2000), slope 1. Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V071a slope (Pockoski & Duncan slope 1) with a circular search instead of the given circle; pore pressure from the vertical head. Converted to SI.





*Figure 121. V071b: critical circle (Bishop simplified, FOS = 1.288).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Mohr-Coulomb | 18.85 | c' = 14.36 | 30.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.293 | 1.288 |
| Spencer | 1.300 | 1.294 |
| Janbu simplified | 1.151 | 1.147 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.122 V072a — Pockoski & Duncan test slope 2, dry tension crack

*Pockoski & Duncan (2000).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V071a slope with a dry 5.5 ft tension crack, on the reference critical circle. Converted to SI.





*Figure 122. V072a: analysed circle (Bishop simplified, FOS = 1.282).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Mohr-Coulomb | 18.85 | c' = 14.36 | 30.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.285 | 1.282 |
| Spencer | 1.290 | 1.287 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.123 V072b — Pockoski & Duncan slope 2, circular search

*Pockoski & Duncan (2000). Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V072a slope (dry 5.5 ft tension crack) with a circular search. Converted to SI.





*Figure 123. V072b: critical circle (Bishop simplified, FOS = 1.282).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Mohr-Coulomb | 18.85 | c' = 14.36 | 30.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.285 | 1.282 |
| Spencer | 1.290 | 1.287 |
| Janbu simplified | 1.141 | 1.135 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.124 V073 — Pockoski & Duncan test slope 3, clay seam and dry crack

*Pockoski & Duncan (2000).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Sandy clay over a 5 ft highly plastic clay seam on the model base, water table and a dry 6 ft tension crack; circular search. Converted to SI.





*Figure 124. V073: critical circle (Bishop simplified, FOS = 1.410).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Mohr-Coulomb | 20.42 | c' = 14.36 | 35.00° |
| Plastic clay seam | Mohr-Coulomb | 20.42 | c' = 0.00 | 25.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.417 | 1.410 |
| Spencer | 1.422 | 1.415 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.125 V074 — Soil-nailed wall with tension crack and surcharges

*Pockoski & Duncan (2000), Comparison of computer programs for analysis of reinforced slopes. Virginia Tech.*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

25 ft nailed wall in undrained clay (800 psf) with crest surcharges, a dry 7 ft crack and five passive nail rows at 15°; the reference circle truncated by the crack. Converted to SI.





*Figure 125. V074: analysed surface (Spencer, FOS = 1.010).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sandy clay | Undrained (φ = 0) | 18.85 | Su = 38.30 | 0° |
| Firm soil | Mohr-Coulomb | 20.42 | c' = 239.4 | 35.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.009 | 1.010 |
| Janbu corrected | 1.073 | 1.075 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.126 V075 — Tieback wall in sand, drawdown water table

*Pockoski & Duncan (2000), Comparison of computer programs for analysis of reinforced slopes. Virginia Tech.*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Single-row tieback wall in sand (φ′ = 30°) with a water table drawn down to the wall face (a vertical step there) and the phreatic correction; the printed surface from the wall toe. Converted to SI.





*Figure 126. V075: analysed surface (Janbu corrected, FOS = 0.578).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Mohr-Coulomb | 18.85 | c' = 0.00 | 30.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.579 | 0.578 |
| Spencer | 0.596 | 0.599 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.127 V076 — Tied-back wall in layered soil

*Pockoski & Duncan (2000), Comparison of computer programs for analysis of reinforced slopes. Virginia Tech.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

44 ft tied-back excavation in eight layers, water table at grade in front of the wall and at el. 102.5 behind it (a vertical step at the wall), three tieback rows at 20° (88 ft, 40 ft bond). a commercial program's critical circle. Converted to SI.





*Figure 127. V076: analysed circle (Bishop simplified, FOS = 1.142).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Granular Fill | Mohr-Coulomb | 18.91 | c' = 0.00 | 30.00° |
| Cohesive Fill | Mohr-Coulomb | 18.02 | c' = 0.00 | 30.00° |
| Organic Silt | Undrained (φ = 0) | 17.31 | Su = 43.09 | 0° |
| OC Crust | Undrained (φ = 0) | 18.50 | Su = 119.0 | 0° |
| Upper Marine Clay | Undrained (φ = 0) | 18.50 | Su = 79.96 | 0° |
| Middle Marine Clay | Undrained (φ = 0) | 18.50 | Su = 45.97 | 0° |
| Lower Marine Clay | Undrained (φ = 0) | 18.50 | Su = 51.95 | 0° |
| Glaciomarine Deposits | Undrained (φ = 0) | 23.11 | Su = 71.82 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.147 | 1.142 |
| Spencer | 1.145 | 1.140 |

*Pockoski & Duncan compare computer programs and publish no independent value.*

## 3.128 V077 — Prandtl bearing capacity on level ground

*Prandtl (1920)*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Weightless (γ = 0.01 kN/m³) c = 20 kPa soil (φ = 0) loaded by a strip load of 102.83 kPa = c·(2 + π) over 10 m, the exact bearing capacity. Analysed on the Prandtl mechanism of Fig. 26.2: active wedge under the load, a 90° fan arc of radius 7.071 m about the load's edge (5, 10), lowest point 2.929, and the passive wedge.





*Figure 128. V077: analysed surface (Spencer, FOS = 0.943).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| soil | Undrained (φ = 0) | 0.01 | Su = 20.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | plasticity theory | Prandtl (1920) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 0.940 | 0.943 |

*The theoretical factor of safety is 1.0; limit equilibrium with slices gives about 6 % less on this mechanism.*

## 3.129 V078 — Prandtl bearing capacity, fully specified Prandtl surface (reference values)

*Prandtl (1921).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Prandtl bearing capacity as a commercial program specifies it: weightless c = 20 kPa soil, 102.83 kPa over 10 m, the fully specified Prandtl surface (active wedge, 90° fan about the load edge, passive wedge).





*Figure 129. V078: analysed surface (Morgenstern-Price (half-sine), FOS = 0.957).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Undrained (φ = 0) | 0.00 | Su = 20.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.00 | plasticity theory | Prandtl (1921) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 0.960 | 0.957 |

*The theoretical factor of safety is 1.0; limit equilibrium with slices gives about 4 % less on this mechanism.*

## 3.130 V079 — Priest (1993) rigid block on a plane, water-filled crack

*Priest (1993).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Block on a 30° plane from the toe, a 15 m tension crack holding 3.75 m of water and a water table along the plane up to the crack.





*Figure 130. V079: analysed surface (Janbu simplified, FOS = 1.048).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Block | Mohr-Coulomb | 25.00 | c' = 20.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.049 | not stated | Priest (1993) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu simplified | 1.049 | 1.048 |
| Spencer | 1.049 | 1.048 |

## 3.131 V080 — Priest (1993) rigid block, reference geometry (60° face)

*Priest (1993).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

Priest's rigid block on a 30° plane with a commercial program's 60° face (crest at x = 17.321): 15 m tension crack with 3.75 m of water and a water table along the plane.





*Figure 131. V080: analysed surface (Morgenstern-Price (half-sine), FOS = 1.049).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Block | Mohr-Coulomb | 25.00 | c' = 20.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.049 | Spencer | Priest | 1.049 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Morgenstern-Price (half-sine) | 1.049 | 1.049 |
| Spencer | – | 1.049 |

## 3.132 V081a — Sharma (1996) reinforcement example, unreinforced

*Sharma (1996).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

45° cohesionless sand slope with a 40 kPa surcharge behind the crest, on the published toe circle.





*Figure 132. V081a: analysed circle (Bishop simplified, FOS = 0.764).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Sand | Mohr-Coulomb | 20.00 | c' = 0.00 | 36.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 0.764 | 0.764 |

*The source compares programs and publishes no independent value.*

## 3.133 V081b — Sharma (1996) slope with a reinforced zone (φ = 54.93°)

*Sharma (1996). Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V081a sand slope (φ′ = 36°, 40 kPa surcharge) with a 7.6 m reinforced zone of φ = 54.93° (tan φ = 1.96 tan 36°) behind the face, on the reference critical toe circle (8.707, 18.307, R = 13.813).





*Figure 133. V081b: analysed circle (Bishop simplified, FOS = 1.501).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 20.00 | c' = 0.00 | 36.00° |
| Reinforced zone | Mohr-Coulomb | 20.00 | c' = 0.00 | 54.93° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.504 | 1.501 |

*The source compares programs and publishes no independent value.*

## 3.134 V082a — Sharma (1996) slope, 11 ft dry tension crack instead of the zero-strength cap

*Sharma (1996); Malkawi et al. (2001). Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V082c slope with the zero-strength cap replaced by an 11 ft dry tension crack (Table 27.4, analysis 3), on the V082c circle; phreatic correction. Converted to SI.





*Figure 134. V082a: analysed circle (Bishop simplified, FOS = 1.504).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.28 | c' = 23.94 | 14.00° |
| Soil 2 (zero strength) | Undrained (φ = 0) | 18.28 | Su = 0.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.532 | 1.504 |
| Spencer | 1.532 | 1.503 |
| Morgenstern-Price (half-sine) | 1.532 | 1.503 |

*The source compares programs and publishes no independent value.*

## 3.135 V082b — Sharma (1996) slope, 11 ft tension crack with 6 ft of water

*Sharma (1996); Malkawi et al. (2001). Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V082a with 6 ft of water in the 11 ft crack (Table 27.4, analysis 4).





*Figure 135. V082b: analysed circle (Bishop simplified, FOS = 1.483).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.28 | c' = 23.94 | 14.00° |
| Soil 2 (zero strength) | Undrained (φ = 0) | 18.28 | Su = 0.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.511 | 1.483 |
| Spencer | 1.510 | 1.482 |

*The source compares programs and publishes no independent value.*

## 3.136 V082c — Sharma (1996) slope over undulating bedrock, zero-strength cap

*Sharma (1996); Malkawi et al. (2001).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Two-material slope over undulating bedrock with a zero-strength cap layer and a water table (phreatic correction); soil 1 has moist/saturated unit weights 116.4/124.2 pcf. Specified circle (59.52, 219.21, R = 157.68). Converted to SI.





*Figure 136. V082c: analysed circle (Bishop simplified, FOS = 1.369).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Mohr-Coulomb | 18.28 | c' = 23.94 | 14.00° |
| Soil 2 (zero strength) | Undrained (φ = 0) | 18.28 | Su = 0.00 | 0° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.369–1.396 | 1.369 |
| Spencer | 1.375–1.402 | 1.375 |

*The source compares programs and publishes no independent value.*

## 3.137 V083 — Soil-nailed wall in clay (Amherst test wall)

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

6 m vertical cut in undrained clay (Su = 25 kPa) with two nail rows at 20° (tensile 118 kN, plate 86 kN, bond 15 kN/m, spacing 1.5 m; axial, passive) and the facing weight as a line load; critical plane at 44.5°.





*Figure 137. V083: analysed surface (Janbu corrected, FOS = 0.899).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Amherst Clay | Undrained (φ = 0) | 18.90 | Su = 25.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.887 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.890 | 0.899 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.138 V084a — Soil-nailed wall in sand (Clouterre test wall)

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

7 m cut in sand (c′ = 3 kPa, φ′ = 38°) with seven passive nail rows at 10° (tensile 15 kN, plate 59 kN, bond 7.5 kN/m, i.e. the tensile capacity develops over 2 m; spacing 1.15 m) and the facing weight; 55° plane through the toe. V084b … V084f are the other planes of Table 48.3.





*Figure 138. V084a: analysed surface (Janbu corrected, FOS = 0.988).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.989 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.989 | 0.988 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.139 V084b — Soil-nailed wall in sand (Clouterre test wall), 45° plane

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

The V084a wall on the 45° plane through the toe.





*Figure 139. V084b: analysed surface (Janbu corrected, FOS = 1.124).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.176 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 1.123 | 1.124 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 5 %.*

## 3.140 V084c — Soil-nailed wall in sand (Clouterre test wall), 50° plane

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

The V084a wall on the 50° plane through the toe.





*Figure 140. V084c: analysed surface (Janbu corrected, FOS = 1.043).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.07 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 1.043 | 1.043 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.141 V084d — Soil-nailed wall in sand (Clouterre test wall), 60° plane

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

The V084a wall on the 60° plane through the toe.





*Figure 141. V084d: analysed surface (Janbu corrected, FOS = 0.944).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.929 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.945 | 0.944 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.142 V084e — Soil-nailed wall in sand (Clouterre test wall), 65° plane

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

The V084a wall on the 65° plane through the toe.





*Figure 142. V084e: analysed surface (Janbu corrected, FOS = 0.920).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.893 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.922 | 0.920 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.143 V084f — Soil-nailed wall in sand (Clouterre test wall), 70° plane

*Sheahan & Ho (2003).*

**Specified non-circular surface · Units: SI (m, kPa, kN/m³)**

The V084a wall on the 70° plane through the toe.





*Figure 143. V084f: analysed surface (Janbu corrected, FOS = 0.920).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fontainebleau Sand | Mohr-Coulomb | 20.00 | c' = 3.00 | 38.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.887 | force-equilibrium trial wedge | Sheahan & Ho (2003) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Janbu corrected | 0.923 | 0.920 |

*Sheahan & Ho use a force-equilibrium trial wedge; Janbu's method on the same planes differs by up to 4 %.*

## 3.144 V085 — Bradwell excavated slope, stiff-fissured London clay

*Skempton & LaRochelle (1965); Duncan & Wright, Soil Strength and Slope Stability.*

**Critical circle search · Units: imperial (ft, psf, pcf)**

Excavation in London clay (six sublayers with Su increasing with depth, S = f(datum)) under Marsh clay and a clay fill cracked to its full depth (11.4 ft); search for the deep failure, entering on the crest and leaving at the excavation toe.





*Figure 144. V085: critical circle (Bishop simplified, FOS = 1.759).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Clay fill | Mohr-Coulomb | 110.0 | c' = 1.00 | 35.00° |
| Marsh clay | Mohr-Coulomb | 105.0 | c' = 300.0 | 0.00° |
| Brown London clay 1 | S = f(datum) | 120.0 | Su = 750.0 at y = -3.00, 90.00 psf/ft below | 0° |
| Brown London clay 2 | S = f(datum) | 120.0 | Su = 1335.0 at y = -9.50, 82.00 psf/ft below | 0° |
| Brown London clay 3 | S = f(datum) | 120.0 | Su = 1704.0 at y = -14.00, 53.00 psf/ft below | 0° |
| Brown London clay 4 | S = f(datum) | 120.0 | Su = 2234.0 at y = -24.00, 47.00 psf/ft below | 0° |
| Blue London clay 1 | S = f(datum) | 120.0 | Su = 2375.0 at y = -27.00, 47.00 psf/ft below | 0° |
| Blue London clay 2 | S = f(datum) | 120.0 | Su = 2469.0 at y = -29.00, 39.00 psf/ft below | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.76 | Bishop simplified | Duncan & Wright | 1.759 |
| 1.63 | Janbu simplified | Duncan & Wright | 1.627 |
| 1.74 | Janbu corrected | Duncan & Wright | 1.735 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.762 | 1.759 |
| Spencer | 1.758 | 1.759 |
| Janbu corrected | 1.736 | 1.735 |
| Janbu simplified | – | 1.627 |

## 3.145 V086a — Tandjiria embankment, clay fill, geosynthetic T = 169 kN/m

*Tandjiria (2002).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V086b clay-fill embankment with a 169 kN/m geosynthetic at its base (axial, active, fully anchored) and the water-filled 2 m crack, on the critical circle.





*Figure 145. V086a: analysed circle (Spencer, FOS = 1.333).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fill | Undrained (φ = 0) | 19.40 | Su = 20.00 | 0° |
| Soft Clay | Undrained (φ = 0) | 19.40 | Su = 20.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.35 | Spencer, at T = 170 kN/m | Tandjiria (2002) | 1.333 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.332–1.350 | 1.333 |

## 3.146 V086b — Tandjiria embankment, clay fill, water-filled crack

*Tandjiria (2002).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Half-embankment (9 m crest, 10 m wide crest, 1V:1.67H face) of clay fill (Su = 20 kPa) on soft clay (Su = 20 kPa), γ = 19.4; 2 m water-filled tension crack, unreinforced; circular search. Also run with the automatic (Rankine) crack depth.





*Figure 146. V086b: critical circle (Spencer (2 m tension crack), FOS = 0.968).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fill | Undrained (φ = 0) | 19.40 | Su = 20.00 | 0° |
| Soft clay | Undrained (φ = 0) | 19.40 | Su = 20.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 0.981 | Spencer | Tandjiria (2002) | 0.968 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer (2 m tension crack) | 0.975 | 0.968 |
| Spencer (tension crack of automatic depth) | 0.975 | 0.966 |

## 3.147 V086c — Tandjiria embankment, sand fill, dry crack

*Tandjiria (2002).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

The V086 embankment as a sand fill (φ′ = 37°, γ = 17) on soft clay (Su = 20 kPa, γ = 20) with a dry 2 m tension crack, unreinforced; circular search.





*Figure 147. V086c: critical circle (Spencer, FOS = 1.206).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Fill | Mohr-Coulomb | 17.00 | c' = 0.00 | 37.00° |
| Soft clay | Undrained (φ = 0) | 20.00 | Su = 20.00 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.219 | Spencer | Tandjiria (2002) | 1.206 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.209 | 1.206 |

## 3.148 V087 — USACE dam, chart-check properties (EM 1110-2-1902 fig. 4-3)

*USACE EM 1110-2-1902 (2003), fig. 4-3.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V088 dam family with single unit weights (embankment c = 200 psf, φ = 25°, γ = 115; sand 0/35/130; clay 0/27/115), slightly flatter faces and ponded water at el. 20 on both faces. the reference circle (−135, 169, R = 169.1), tangent to the sand top. Converted to SI.





*Figure 148. V087: analysed circle (Spencer, FOS = 2.258).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 18.07 | c' = 9.58 | 25.00° |
| Sand | Mohr-Coulomb | 20.42 | c' = 0.00 | 35.00° |
| Foundation clay | Mohr-Coulomb | 18.07 | c' = 0.00 | 27.00° |
| Rock | Mohr-Coulomb | 25.13 | c' = 0.00 | 45.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.30 | not stated | USACE EM 1110-2-1902 | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 2.258 | 2.258 |
| Bishop simplified | 2.254 | 2.255 |
| Janbu corrected | 2.290 | 2.258 |

## 3.149 V088 — USACE dam, end of construction (EM 1110-2-1902 fig. 4-1)

*USACE EM 1110-2-1902 (2003), fig. 4-1.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Symmetric 50 ft embankment (crest ±12 ft, toes ±206.18 ft) with c = 1000 psf, φ = 5°, a core trench through a 10 ft sand blanket over foundation clay (Su = 3000 psf) and rock; groundwater at the sand top, 7 ft dry crest crack; moist/saturated unit weights. Specified circle (102, 163, R = 163). Converted to SI.





*Figure 149. V088: analysed circle (Spencer, FOS = 2.442).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 18.07 | c' = 47.88 | 5.00° |
| Sand | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation clay | Undrained (φ = 0) | 17.28 | Su = 143.6 | 0° |
| Rock | Mohr-Coulomb | 25.13 | c' = 0.00 | 45.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.44 | Spencer | USACE EM 1110-2-1902 | 2.442 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 2.445 | 2.442 |
| Bishop simplified | 2.447 | 2.442 |
| Janbu corrected | 2.430 | 2.444 |

## 3.150 V089 — USACE dam, upstream low pool (EM 1110-2-1902 fig. 4-2)

*USACE EM 1110-2-1902 (2003), fig. 4-2.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V088 dam family, 45 ft high (crest ±15 ft, toes ±200 ft), with drained strengths (embankment c = 100 psf, φ = 25°; sand 0/35; clay 0/28; rock 0/45; moist/saturated unit weights) and the pool at el. 20 standing on the upstream face. USACE's circle (−102, 163, R = 173), tangent to the clay top. Converted to SI.





*Figure 150. V089: analysed circle (Bishop simplified, FOS = 2.698).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 18.07 | c' = 4.79 | 25.00° |
| Sand | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |
| Foundation clay | Mohr-Coulomb | 17.28 | c' = 0.00 | 28.00° |
| Rock | Mohr-Coulomb | 25.13 | c' = 0.00 | 45.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.71 | Bishop simplified | USACE EM 1110-2-1902 | 2.698 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.716 | 2.698 |
| Spencer | 2.736 | 2.721 |
| Janbu corrected | 2.650 | 2.648 |

## 3.151 V090 — USACE EM 1110-2-1902, example F-5

*US Army Corps of Engineers (2003). Slope Stability, EM 1110-2-1902, Appendix F.*

**Fixed circle · Units: imperial (ft, psf, pcf)**

Embankment (c = 1780 psf, φ = 5°) on a foundation (c = 1600 psf, φ = 2°), analysed with the circle given in the Corps of Engineers example.





*Figure 151. V090: analysed circle (Bishop simplified, FOS = 1.320).*

| Material | Model | γ (pcf) | Strength (psf) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 135.0 | c' = 1780.0 | 5.00° |
| Foundation | Mohr-Coulomb | 127.0 | c' = 1600.0 | 2.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.33 | not stated | USACE EM 1110-2-1902 | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.332 | 1.320 |
| Spencer | 1.328 | 1.317 |
| Janbu corrected | 1.345 | 1.341 |

## 3.152 V091 — USACE example E-10, ponded water

*USACE EM 1110-2-1902, example E-10.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Undrained three-layer slope with 8 ft of water ponded against its toe (pool el. 0), on a commercial program's circle (48.262, 28, R = 47.683 ft; Fig. 68.2). Converted to SI.





*Figure 152. V091: analysed circle (Bishop simplified, FOS = 1.235).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil 1 | Undrained (φ = 0) | 18.85 | Su = 28.73 | 0° |
| Soil 2 | Undrained (φ = 0) | 15.71 | Su = 19.15 | 0° |
| Soil 3 | Undrained (φ = 0) | 16.49 | Su = 23.94 | 0° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.33 | not stated | USACE EM 1110-2-1902 | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.241 | 1.235 |
| Spencer | 1.241 | 1.235 |
| Morgenstern-Price (half-sine) | 1.244 | 1.235 |
| Janbu corrected | 1.385 | 1.380 |

*The USACE value 1.33 is read from a chart; on the circle the example describes, the programs give about 1.24.*

## 3.153 V092 — USACE example F-6, steady-seepage dam

*USACE EM 1110-2-1902, example F-6.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

112 ft embankment on a granular foundation under steady seepage: piezometric line from the pool through the chimney drain to the tailwater, which stands on the downstream toe (free water). USACE's circle. Converted to SI.





*Figure 153. V092: analysed circle (Bishop simplified, FOS = 1.998).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Embankment | Mohr-Coulomb | 20.42 | c' = 0.00 | 34.00° |
| Foundation | Mohr-Coulomb | 19.64 | c' = 0.00 | 35.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 2.01 | not stated | USACE EM 1110-2-1902 | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 2.011 | 1.998 |
| Spencer | 2.026 | 2.012 |
| Janbu corrected | 1.830 | 1.832 |

## 3.154 V093 — Yamagami & Ueta (1988)

*Yamagami & Ueta (1988).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Homogeneous 2:1 slope, 5 m high; critical circle search.





*Figure 154. V093: critical circle (Bishop simplified, FOS = 1.343).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 17.64 | c' = 9.80 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.348 | Bishop simplified | Yamagami & Ueta (1988) | 1.343 |
| 1.282 | Ordinary | Yamagami & Ueta (1988) | – |
| 1.185 | Janbu simplified, non-circular | Yamagami & Ueta (1988) | 1.178 |
| 1.339 | Spencer, non-circular | Yamagami & Ueta (1988) | 1.324 |
| 1.33 | Spencer, non-circular | Greco (1996) | 1.324 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.344 | 1.343 |
| Spencer, non-circular | 1.325 | 1.324 |
| Janbu simplified, non-circular | – | 1.178 |

## 3.155 V094 — Yamagami & Ueta (1988) four-layer slope, non-circular

*Greco (1996) example 4; Yamagami & Ueta (1988).*

**Circle search with non-circular optimisation · Units: SI (m, kPa, kN/m³)**

Four-layer slope without water whose critical surface is non-circular; circular search followed by non-circular optimisation.





*Figure 155. V094: critical surface (Spencer, non-circular, FOS = 1.401).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper layer | Mohr-Coulomb | 20.38 | c' = 49.00 | 29.00° |
| Layer 2 | Mohr-Coulomb | 17.64 | c' = 0.00 | 30.00° |
| Layer 3 | Mohr-Coulomb | 20.38 | c' = 7.84 | 20.00° |
| Bottom layer | Mohr-Coulomb | 17.64 | c' = 0.00 | 30.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.40–1.42 | Spencer, non-circular | Greco (1996) | 1.401 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer, non-circular | 1.398 | 1.401 |
| Morgenstern-Price (half-sine), non-circular | 1.389 | 1.395 |

## 3.156 V095a — Yamagami micro-pile slope, no pile

*Yamagami micro-pile slope example.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Homogeneous 2:1 slope, 4 m high, without piles, on the published circle.





*Figure 156. V095a: analysed circle (Bishop simplified, FOS = 1.101).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 15.68 | c' = 4.90 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.10 | not stated | Yamagami et al. (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.102 | 1.101 |

## 3.157 V095b — Homogeneous slope, no micro piles

*Yamagami et al. (2000).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Homogeneous slope on the printed critical circle, unreinforced.





*Figure 157. V095b: analysed circle (Bishop simplified, FOS = 1.101).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 15.68 | c' = 4.90 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.10 | not stated | Yamagami et al. (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.102 | 1.101 |

## 3.158 V095c — Homogeneous slope with a micro-pile row

*Yamagami et al. (2000).*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V095b with a micro-pile row (1 m spacing) whose shear strength of 10.7 kN acts as a passive force tangent to the slip surface, on the reference with-pile circle (2.674, 7.376, R = 8.102).





*Figure 158. V095c: analysed circle (Bishop simplified, FOS = 1.196).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Material 1 | Mohr-Coulomb | 15.68 | c' = 4.90 | 10.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.20 | not stated | Yamagami et al. (2000) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.193 | 1.196 |

## 3.159 V096a — Zhu & Lee heterogeneous slope, dry, deep circle

*Zhu & Lee (2002).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

Four horizontal layers under a two-bench slope with a dry tension crack 1.015 m deep at the crest (Fig. 52.1; the depth of a commercial program's surface end below the crest), dry; the circular search lands in the deep family (surface 3).





*Figure 159. V096a: critical circle (Bishop simplified, FOS = 1.793).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 (top) | Mohr-Coulomb | 18.80 | c' = 20.00 | 18.00° |
| Layer 2 | Mohr-Coulomb | 18.50 | c' = 40.00 | 22.00° |
| Layer 3 | Mohr-Coulomb | 18.40 | c' = 25.00 | 26.00° |
| Layer 4 (bottom) | Mohr-Coulomb | 18.00 | c' = 10.00 | 12.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.836 | Spencer | Zhu & Lee (2002) | 1.794 |
| 1.823 | Morgenstern-Price | Zhu & Lee (2002) | 1.780 |
| 1.429 | Bishop simplified | Zhu & Lee (2002) | 1.793 |
| 1.229 | Ordinary | Zhu & Lee (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.804 | 1.793 |
| Spencer | 1.804 | 1.794 |
| Morgenstern-Price (half-sine) | – | 1.780 |

*Zhu & Lee's Bishop value 1.429 is about 20 % below their own Spencer and Morgenstern-Price values; the programs give about 1.80 with both methods.*

## 3.160 V096b — Zhu & Lee heterogeneous slope with a water table, deep circle

*Zhu & Lee (2002).*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

As V096a (dry 1.015 m crack) with the water table of Table 52.2.





*Figure 160. V096b: critical circle (Bishop simplified, FOS = 1.173).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 (top) | Mohr-Coulomb | 18.80 | c' = 20.00 | 18.00° |
| Layer 2 | Mohr-Coulomb | 18.50 | c' = 40.00 | 22.00° |
| Layer 3 | Mohr-Coulomb | 18.40 | c' = 25.00 | 26.00° |
| Layer 4 (bottom) | Mohr-Coulomb | 18.00 | c' = 10.00 | 12.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.211 | Spencer | Zhu & Lee (2002) | 1.187 |
| 1.197 | Morgenstern-Price | Zhu & Lee (2002) | 1.172 |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.176 | 1.173 |
| Spencer | 1.189 | 1.187 |
| Morgenstern-Price (half-sine) | – | 1.172 |

## 3.161 V096c — Zhu & Lee slope, surface 3 (the reference circle), dry, 1 m crack

*Zhu & Lee (2002). Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

The V096a slope with the dry 1.015 m crack on the reference surface 3 circle (10.911, 23.208, R = 32.106; Fig. 52.4).





*Figure 161. V096c: analysed circle (Spencer, FOS = 1.799).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Layer 1 | Mohr-Coulomb | 18.80 | c' = 20.00 | 18.00° |
| Layer 2 | Mohr-Coulomb | 18.50 | c' = 40.00 | 22.00° |
| Layer 3 | Mohr-Coulomb | 18.40 | c' = 25.00 | 26.00° |
| Layer 4 | Mohr-Coulomb | 18.00 | c' = 10.00 | 12.00° |

| Published value | Method | Source | cSlope |
|---|---|---|---|
| 1.836 | Spencer | Zhu & Lee (2002) | 1.799 |
| 1.823 | Morgenstern-Price | Zhu & Lee (2002) | 1.785 |
| 1.429 | Bishop simplified | Zhu & Lee (2002) | 1.799 |
| 1.229 | Ordinary | Zhu & Lee (2002) | – |

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.804 | 1.799 |
| Bishop simplified | 1.804 | 1.799 |
| Morgenstern-Price (half-sine) | – | 1.785 |

*Zhu & Lee's Bishop value 1.429 is about 20 % below their own Spencer and Morgenstern-Price values; the programs give about 1.80 with both methods.*

## 3.162 V097a — Eurocode 7 cutting with surcharge

*Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

Cutting in clay with an inclined piezometric line and a 35 kPa surcharge on the crest, analysed on the published circle.





*Figure 162. V097a: analysed circle (Bishop simplified, FOS = 1.172).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 20.00 | c' = 8.00 | 23.04° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.173 | 1.172 |

*The problem comes from a program manual only; no independent value is published.*

## 3.163 V097b — Eurocode 7 cutting, partial factors applied by cSlope

*Verification manual of a commercial slope stability program.*

**Fixed circle · Units: SI (m, kPa, kN/m³)**

As V097a, but with the characteristic strength c' = 10 kPa, φ' = 28° and Design Approach 3 material factors (set M2: γc' = γφ' = 1.25) applied by the analysis; the surcharge is permanent (factor 1.0). The FOS is the over-design factor on design values.





*Figure 163. V097b: analysed circle (Bishop simplified, FOS = 1.172).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Clay | Mohr-Coulomb | 20.00 | c' = 10.00 | 28.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Bishop simplified | 1.173 | 1.172 |
| Spencer | 1.174 | 1.174 |

*The problem comes from a program manual only; no independent value is published.*

## 3.164 V098 — Example slope without seismic load

*Verification manual of a commercial slope stability program.*

**Critical circle search · Units: SI (m, kPa, kN/m³)**

10 m, 2:1 slope in three layers over a horizontal base, dry, no seismic load; Spencer search.





*Figure 164. V098: critical circle (Spencer, FOS = 1.372).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| soil1 | Mohr-Coulomb | 19.50 | c' = 0.00 | 38.00° |
| soil2 | Mohr-Coulomb | 19.50 | c' = 5.30 | 23.00° |
| soil3 | Mohr-Coulomb | 19.50 | c' = 7.20 | 20.00° |

*The source publishes no factor of safety for this problem.*

| cSlope analysis | Other programs | cSlope |
|---|---|---|
| Spencer | 1.360–1.372 | 1.372 |

*The problem comes from a program manual only; no independent value is published.*

# 4 Benchmark models bundled with cSlope

These models are shipped with the program (Help → Benchmarks). They are run through the same request builder as the user interface, with the analysis options saved in each model. They repeat problems of section 3, where the published values are given.

## 4.1 T-ACADS Simple

**Bundled model "T-ACADS Simple" · Units: SI (m, kPa, kN/m³) · Critical circle search · 30 slices, 1000 + 500 search iterations**





*Figure 165. T-ACADS Simple: critical circle (Morgenstern-Price, FOS = 0.984).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| M1 | Mohr-Coulomb | 20.00 | c' = 3.00 | 19.60° |

| Method | cSlope |
|---|---|
| Morgenstern-Price | 0.984 |
| Bishop simplified | 0.984 |
| Janbu simplified | 0.935 |

## 4.2 T-ACADS Non-Homogeneous

**Bundled model "T-ACADS Non-Homogeneous" · Units: SI (m, kPa, kN/m³) · Critical circle search · 30 slices, 1000 + 500 search iterations**





*Figure 166. T-ACADS Non-Homogeneous: critical circle (Morgenstern-Price, FOS = 1.372).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil #1 | Mohr-Coulomb | 19.50 | c' = 0.00 | 38.00° |
| Soil #2 | Mohr-Coulomb | 19.50 | c' = 5.30 | 23.00° |
| Soil #3 | Mohr-Coulomb | 19.50 | c' = 7.20 | 20.00° |

| Method | cSlope |
|---|---|
| Morgenstern-Price | 1.372 |

## 4.3 Arai & Tagyo (1985)

**Bundled model "Arai & Tagyo (1985)" · Units: SI (m, kPa, kN/m³) · Critical circle search · 30 slices, 1000 + 500 search iterations**





*Figure 167. Arai & Tagyo (1985): critical circle (Bishop simplified, FOS = 1.113).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Soil | Mohr-Coulomb | 18.82 | c' = 41.65 | 15.00° |

| Method | cSlope |
|---|---|
| Bishop simplified | 1.113 |

## 4.4 Arai & Tagyo (1985), weak layer

**Bundled model "Arai & Tagyo (1985), weak layer" · Units: SI (m, kPa, kN/m³) · Critical circle search · 30 slices, 1000 + 500 search iterations**





*Figure 168. Arai & Tagyo (1985), weak layer: critical circle (Morgenstern-Price, FOS = 0.412).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Upper | Mohr-Coulomb | 18.82 | c' = 29.40 | 12.00° |
| Weak layer | Mohr-Coulomb | 18.82 | c' = 9.80 | 5.00° |
| Lower | Mohr-Coulomb | 18.82 | c' = 294.0 | 40.00° |

| Method | cSlope |
|---|---|
| Morgenstern-Price | 0.412 |

## 4.5 Talbingo Dam

**Bundled model "Talbingo Dam" · Units: SI (m, kPa, kN/m³) · Critical circle search · 30 slices, 1000 + 500 search iterations**





*Figure 169. Talbingo Dam: critical circle (Morgenstern-Price, FOS = 1.951).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Rockfill | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Transition | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Filter | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Core | Mohr-Coulomb | 18.10 | c' = 85.00 | 23.00° |

| Method | cSlope |
|---|---|
| Morgenstern-Price | 1.951 |

## 4.6 Talbingo Dam (Single Circle)

**Bundled model "Talbingo Dam (Single Circle)" · Units: SI (m, kPa, kN/m³) · Fixed circle · 30 slices, 1000 + 500 search iterations**





*Figure 170. Talbingo Dam (Single Circle): critical circle (Morgenstern-Price, FOS = 2.301).*

| Material | Model | γ (kN/m³) | Strength (kPa) | φ |
|---|---|---|---|---|
| Rockfill | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Transition | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Filter | Mohr-Coulomb | 20.40 | c' = 0.00 | 45.00° |
| Core | Mohr-Coulomb | 18.10 | c' = 85.00 | 23.00° |

| Method | cSlope |
|---|---|
| Morgenstern-Price | 2.301 |