Big Data Engineer Bootcamp

Part 1

Agenda

- More on Big Data
- Introduction to Kafka
- Introduction to Zookeeper
- Introduction to Cassandra
- Q&A

Agenda

- **More on Big Data**
- Introduction to Kafka
- Introduction to Zookeeper
- Introduction to Cassandra
- Q&A

More on Big Data

- **History of Big Data**
- Frameworks and Tools

History of Big Data

- 1991 - internet was born (yay)
- 1996 - digital storage is so cheap, cheaper than paper
- 1998 - Google was founded (yay)
- 1999 - the word Big Data first used in a paper
- 2001 - idea of 3V of data described by Doug Laney

Web 1.0

- Front End
  - HTML
  - CSS
  - JavaScript
- Dynamic Content
  - PHP
  - JSP
  - ASP.NET
  - Ruby
  - Perl
- Database
  - RDBMS
- Site Owner Generates Content

History of Big Data

- 2004 - Facebook was founded (yay)
- 2005 - Web 2.0
- 2007 - iPhone and AWS was released (yay)
- 2008 - 14.7 EB of data being generated
- 2014 - Mobile system surpass desktops

Web 2.0

- Front End
  - AngularJS, etc
- Dynamic Content
  - PHP
  - JSP
  - ASP.NET
  - Ruby
  - JavaScript
- Data Processing
  - Hadoop, etc
- Database
  - NoSQL
- Users Generate Content

o Album

nd?

Friends

Post

Mount Sunapee Resort.

Navin Bhatia's birthday is today

TODAY'S GAMES

BOS

LAD

7:10pm

TRENDING

iPhone 7 Plus: YouTube Group Releases Video Claiming to Detail Upcoming Device

Norah Jones: Singer Releases Music Video for New Single 'Carry On' Off Upcoming Album

Frank Ocean: Singer's 'Boys Don't Cry' Album Reportedly to Be Released Friday on Apple Music

See More

SPONSORED

Create Ad

Gartner Cycle of Hype 2014

- Every year Gartner publish a list buzzwords and their trends
- Divided into 5 categories
- Divided into 5 time ranges

- Big Data is doing OK



Gartner Cycle of Hype 2015

- Big Data is gone!?

History of Big Data

- 2014 - end of a buzzword
- 2015 - the wide deployment stage

More on Big Data

- History of Big Data
- **Frameworks and Tools**

Explosion of Frameworks and Tools

Frameworks and Tools

- Google leads the way
  - Google File System
  - MapReduce
  - Bigtable
  - Chubby
  - Pregel
  - Dremel
  - Tenzing
  - Spanner
  - F1
  - Borg
  - Omega

Frameworks and Tools

- Community follows
  - Apache Hadoop HDFS
  - Apache Hadoop MapReduce
  - Apache HBase
  - Apache Zookeeper
  - Apache Pig
  - Apache Hive
  - Apache Drill
  - Apache Impala
  - Apache Giraph
  - Apache Mesos
  - Apache Spark

Key Projects

- Apache Zookeeper
- Apache Hadoop
- Apache Kafka
- Apache Mesos

Apache Zookeeper

- Make building distributed system easier
- Enabled a wide range of open-source projects
- Ground of truth for distributed system

Apache Hadoop

- Make distributed computation easier
- Expose simple API
  - Map
  - Reduce

Apache Kafka

- Make data transportation easier
- Make SOA model more reliable
- De facto data transportation framework

Apache Mesos

- Make distributed task scheduling easier
- Dramatically increase resource utilization

Frameworks and Tools

- Computation
  - Hadoop, Spark, Samza, Flink, Hive, Pig, Drill, etc
- Transportation
  - Kafka, Flume, Sqoop, Scribe, RabbitMQ, ZeroMQ, IronMQ, etc
- Storage
  - HBase, Cassandra, CouchDB, MongoDB, etc
- Coordination
  - Zookeeper, Consul, Etcd, Eureka, etc
- Scheduling
  - Mesos, Yarn, Oozie, etc

Explosion of Frameworks and Tools

- Don’t Panic
- Building Big Data Platform become LEGO building



Introduction to Zookeeper

Because distributed system is a ZOO

Agenda

- **Use Cases**
- What is Zookeeper
- Architecture
- Zookeeper Usage

An Example Computing Problem

Given a truck of fruits, calculate the quantity for each kind of fruit

Standalone Program

- Runs on a single machine
- Predictable
- Isolated
- Performance is limited by the machine

Image credit: Docker Inc

Distributed System/Program

- Runs on multiple machines
- Distribute the workload
- Hard to coordinate



Image credit: Docker Inc

Master Slave Model

- Master knows a list of tasks
- Master in charge of distributing tasks
- Slaves in charge of executing tasks
- Slaves need to report status back to Master



Image credit: Docker Inc

Master Slave Model Common Issues

- How to come up with a Master?
- What happens when master crash?
- What happens when worker crash?
- What if master and worker cannot communicate?

Master Slave Model Common Tasks

- Master Election
  - The process of deciding who is the master
- Crash Detection
  - The master need to detect when workers crash
- Group Membership
  - The master must learn who is available for tasks
- Metadata Management
  - All the nodes must be able to reliably store/retrieve status

Agenda

- Use Cases
- **What is Zookeeper**
- Architecture
- Zookeeper Usage

What is Zookeeper

- An open source distributed system that provides
  - Strong consistency, ordering, and durability guarantees
  - The ability to implement typical synchronization primitives
  - A simpler way of dealing with concurrency

- Inspired by Google Chubby
- Developed in Yahoo using Java

Agenda

- Use Cases
- What is Zookeeper
- **Architecture**
- Zookeeper Usage

Architecture

- **Coordinate Strategy**
- Concepts
- Internal

Ways to Coordinate

- Message passing
  - Processes exchange messages directly through a network
- Shared storage
  - Read or write to shared storage

Coordinating with Messages

- Communicate to each other by passing messages



Image credit: Docker Inc

Coordinating with Message Passing

- Network Delays
  - Messages might get delayed arbitrarily
- Speed of Processing
  - Some machines might process things faster
- Clock Difference
  - The time on the machines are different

- Cannot tell the difference between real crash or network issue

A Split-brain Example

- In a system, we have one master, one backup master, and many workers
- Part of the workers are having trouble to reach master
- Connect with backup master instead

Coordinate with Shared Storage

- More straightforward
- Still rely on network to transfer data

- Zookeeper use this model to implement coordination

Architecture

- Coordinate Strategy
- **Concepts**
- Internal

Data Tree

- Organized in hierarchical structure
- Similar to file system



API

API Name	Usage
`create /path data`	Create a znode /path with data
`delete /path`	Delete znode /path
`exists /path`	Check if /path exists
`setData /path data`	Set znode /path to data
`getData /path`	Get the data in /path znode
`getChildren /path`	Return a list of children under /path

znode

- Basic unit for Data Tree
- Persistent znode
  - Data is persisted unless **`delete`** is called
- Ephemeral znode
  - Node is deleted if the client created it loses connection to zookeeper
- Sequential znode
  - Zookeeper will assign sequence number and append it to the path

Watcher

- Help client to know changes to znodes
- Avoid race conditions in polling
- Notifications are one-time operation

Watcher



Image credit: O'Reilly

Architecture

- Coordinate Strategy
- Concepts
- **Internal**

Client - Server Interaction

- Connection
  - TCP connection
  - Client only connects to server with newer/equal state
  - Configurable session timeout
- Read
  - Read can be read from any of the servers
- Write
  - Write requests will be forwarded to the leader of zookeeper cluster

zxid

- A 64-bit integer id
- Generated when there is a new update of znode

Leader Election within Zookeeper

- Zookeeper cluster AKA Ensemble
- Server has following mode
  - Leader
  - Follower
  - Observer
- Server has following state
  - LOOKING
  - LEADING
  - FOLLOWING

Leader Election within Zookeeper



Image credit: O'Reilly

State Replication within Zookeeper

- Follow a consensus protocol called Zab
- Leader
  - Receives Write requests
  - Convert requests into transaction
  - Leader send PROPOSAL message to all follower
  - Once receiving acknowledges from a quorum, leader sends COMMIT message

State Replication within Zookeeper

- Follower
  - Received PROPOSAL message from leader
  - Check if the leader is the correct leader
  - Check if the transaction is in correct order
  - Send acknowledgement back to leader
  - Received COMMIT message from leader
  - Apply change to the Data Tree

Agenda

- Use Cases
- What is Zookeeper
- Architecture
- **Zookeeper Usage**

Zookeeper Usage

- Master Election
- Crash Detection
- Group Membership
- Metadata Management

Master Election

- Have all the process go and create sequential ephemeral znode
- Znode with smallest sequence number is the leader
- Setup watcher for changes

Crash Detection

- Have slaves create ephemeral znodes
- Setup watcher on the znodes

Group Membership

- The members need to create ephemeral znodes under group node

Metadata Management

- Store metadata in persistent znode
- Use persistent znode as source of truth

Similar Systems

- Consul (https://www.consul.io/)
  - Use Raft for Consensus
- Etcd (https://coreos.com/etcd/)
  - Use Raft for Consensus
- Eureka (https://github.com/Netflix/eureka)

Introduction to Kafka

A High-throughput Distributed Messaging System

Agenda

- **Use Cases**
- What is Kafka
- Architecture
- Kafka Usage

Microservice Architecture

A monolithic application puts all its functionality into a single process...

... and scales by replicating the monolith on multiple servers



A microservices architecture puts each element of functionality into a separate service...



... and scales by distributing these services across servers, replicating as needed.



Image credit: Martin Fowler

Microservice Architecture

- Organize around business capabilities
- Decentralized data management
- Better deployment infrastructure

Image credit: Martin Fowler



microservices - application databases

How Does Microservices Communicate

- Sync
  - RESTful API
  - RPC frameworks
- Async
  - Drop a message and back to work

Message Queue



Message Queue Benefits

- Service Decoupling
- Increase Scalability
- Data Redundancy
- Deal with Peak Traffic
- Buffer Cushion for Failed Components

Message Queue Issues

- Spaghetti of queues
- Skip Messages
- Brokers need to record client positions





Agenda

- Use Cases
- **What is Kafka**
- Architecture
- Kafka Usage

What is Kafka

- An open source distributed messaging system
  - Fast - hundreds MB/s from thousands of clients
  - Scalable - easily scale up and down without downtime
  - Durable - Messages are persisted on disk to prevent data loss

- Developed in LinkedIn using Scala

Agenda

- Use Cases
- What is Kafka
- **Architecture**
- Kafka Usage

Architecture

- **Design Strategy**
- Concepts
- Internal

Pull vs Push

- Push model
  - High throughput
  - Complex server logic
- Pull model
  - Simple server logic
  - Reply feature

Architecture

- Design Strategy
- **Concepts**
- Internal

Topic and Partition

- Messages are organized logically into topics
- Physically divided into Partitions



Offset

- A incremental sequence number
- The position of a message in a partition

API

API Name	Usage
`publish topic data`	Publish data onto a topic
`consume topic offset`	Consume from a topic

Producer

- Producer in charge of sending messages to Kafka broker

Consumer

- Consumer pull messages from Kafka broker
- Can use offset to target a specific message on a partition
  - By default point to the latest offset
  - Can set the offset to an older value to read old data
- Consumer maintain message state
- No ACK

Consumer Group

- A group of consumers
- Mapped to partitions
  - Messages in certain partition can only be consumed by corresponding consumer

Consumer Group

- A group of consumers
- Mapped to partitions
  - Messages in certain partition can only be consumed by corresponding consumer



Architecture

- Design Strategy
- Concepts
- **Internal**

Log File Format

- One partition is a physical folder
- One message:
  - offset
  - Message length
  - Magic value, 1 byte
  - CRC value, 4 bytes
  - Payload, N bytes

Log File Format

- Active Segment List maintains mapping to segment files
- Log entries in segment files



IO Optimization

- Append-only writing
- Reads do not block writes
- Super fast writing speed because one partition is one log file



IO Optimization - zerocopy

- OS reads data from disk into pagecache in kernel space
- Application reads data from kernel space into user space
- Application writes data back to kernel space into socket buffer
- OS copies data from socket buffer to NIC buffer

- zerocopy copies data into pagecache only once and reuse

Data Replication inside Kafka

- Producer write through Partition Leader
- Partition Leader write the message into local disk
- Partition Follower pull from Partition Leader
- Once Leader received ACK from all the

ISR (in-sync Replica)

- A nice balance between sync and async copy
- Configurable lag behind
  - If one replica is too slow, will be removed from ISR
- Follower can batch read from Leader

Agenda

- Use Cases
- What is Kafka
- Architecture
- **Kafka Usage**

Kafka Usage

- Log Aggregation
- Real-time Data Analysis

Log Aggregation

- Forward all the logs into specific Kafka topic
- Setup Consumer/Consumer Group on the topic and forward to indexing service
- Query on the data through Kibana, etc

Read-time Analysis

- Forward interested data into Kafka topic
- Integrate with Spark/Samza for steaming processing

Similar Systems

- RabbitMQ (https://www.rabbitmq.com/)
  - Erlang, based on AMQP
- ZeroMQ (http://zeromq.org/)
  - Middleware less
- Redis (http://redis.io/)
  - C/C++, can be used as lightweight queue
- ActiveMQ (http://activemq.apache.org/)
  - Java, based on AMQP
- SQS (https://aws.amazon.com/sqs/)
  - An AWS service, the visibility timeout feature is awesome

Introduction to Cassandra

Manage massive amounts of data, fast, without losing sleep

Agenda

- **Use Cases**
- What is Cassandra
- Architecture
- Cassandra Usage

An Example Storage Problem

- We are creating a system for people to store:
  - First name
  - Last name
  - Phone number

- Initially we can just go with one simple table

An Example Storage Problem

- Your application is getting popular, you noticed that people are getting slow read
- Read/Write separation



An Example Storage Problem

- Your app is so popular you are hitting the storage limit of database
- Shard/Partition data based on some rules



Agenda

- Use Cases
- **What is Cassandra**
- Architecture
- Cassandra Usage

What is Cassandra

- An open source distributed storage system that provides
  - High availability
  - No single point of failure

- Inspired by Amazon DynamoDB
- Developed in Facebook using Java

Agenda

- Use Cases
- What is Cassandra
- **Architecture**
- Cassandra Usage

Architecture

- **Design Strategy**
- Concepts
- Internal

Revisit Master Slave Model

- Single point of failure
- Even backup master might fail
- Capacity depends on master



Gossip Protocol

- Runs every second
- Choose a random node to gossip with
- Use accrual failure detection to determine if a node is down
    - For example, increase the convict threshold on cloud services

Tunable Consistency

- Consistency means whether read always return the most recently written value
- In other systems, the consistency level is defined by the protocol

CAP Theorem


Available
Consistent
Partition-Tolerant


A
Relational:
MySQL, SQL Server,
Postgres
Amazon Dynamo derivatives:
Cassandra, Voldemort,
CouchDB, Riak
C
P
Neo4J, Google Bigtable, and
Bigtable derivatives: MongoDB HBase,
Hypertable, Redis

Architecture

- Design Strategy
- **Concepts**
- Internal

Ring

- In a Cassandra cluster, data is assigned to nodes as if they form a ring of tokens



Partitioner

- A hashing algorithm to determine how data is distributed across the cluster
- By default murmur3 hashing algorithm is being used

Architecture

- Design Strategy
- Concepts
- **Internal**

Internal Data Structure

- Commit log
- memtable
- SSTable



Commit log

- Crash-recovery mechanism
- All write operation is immediately written to commit log
- Will not count if no commit log is written

memtable

- Value will be added to memtable after commit log
- In-memory store to speed up operations

SSTables

- Content of memtable gets written to SSTable after memtable is full
- Immutable cannot be changed
- Changes are appended
- Sequential write to disk

Compaction

- Merge of SSTables
- New merged data is sorted as well
- Reduce number of seeks

Read Operations inside Cassandra

- Client can contact any node to read



Write Operations inside Cassandra

- Client can contact any node to Write



Data Replication Inside Cassandra

- A node can serve as replica for other ranges
- If nodes goes down replica will serve the request



Agenda

- Use Cases
- What is Cassandra
- Architecture
- **Cassandra Usage**

Cassandra Usage

- General Data Storage
- Time-series Data Storage
- TTL Data Storage

General Data Storage

- You can use Cassandra cluster as your primary data persistence layer
- Easy to operate

Time-series Data Storage

- Data is sorted and written sequentially to disk
- Perfect for retrieving data and filter range
- Fast access due to small disk seeks

TTL Data Storage

- Some data can be discarded after some time
- With Cassandra TTL on data, this feature is easy to implement

Similar Systems

- HBase (https://hbase.apache.org/)
  - Java, inspired by Google BigTable
- MongoDB (https://www.mongodb.com/)
  - C++, C, JavaScript, document based database
- CouchDB (http://couchdb.apache.org/)
  - Erlang, document based database

Q&A