



# Big Data Engineer Bootcamp

Code 2



# Agenda

## Dev Environment

Work with Kafka

Work with Cassandra


# Github Link

- <https://github.com/UncleBarney/big-data-bootcamp>



# Project Structure

- Apache Kafka
- Apache Zookeeper
- Apache Cassandra



# Start Docker Environment (MacOS, \*nix)

- Have a docker-machine vm called bigdata

- Start a Zookeeper Container

- `docker run -d -p 2181:2181 -p 2888:2888 -p 3888:3888 --name zookeeper confluent/zookeeper`

- Start a Kafka Container

- `docker run -d -p 9092:9092 -e KAFKA_ADVERTISED_HOST_NAME=`docker-machine ip bigdata` -e KAFKA_ADVERTISED_PORT=9092 --name kafka --link zookeeper:zookeeper confluent/kafka`

- If backtick is not working for you, use your virtual machine ip directly

- Start a Cassandra Container

- `docker run -d -p 7199:7199 -p 9042:9042 -p 9160:9160 -p 7001:7001 --name cassandra cassandra:3.7`



# Start Docker Environment (Windows)

- Have a docker-machine vm called bigdata

- Start a Zookeeper Container

- `docker run -d -p 2181:2181 -p 2888:2888 -p 3888:3888 --name zookeeper confluent/zookeeper`

- Start a Kafka Container

- `docker run -d -p 9092:9092 -e KAFKA_ADVERTISED_HOST_NAME=`docker-machine ip bigdata` -e KAFKA_ADVERTISED_PORT=9092 --name kafka --link zookeeper:zookeeper confluent/kafka`

- If backtick is not working for you, use your virtual machine ip directly

- Start a Cassandra Container

- `docker run -d -p 7199:7199 -p 9042:9042 -p 9160:9160 -p 7001:7001 --name cassandra cassandra:3.7`



# Why Use Docker For This

- Fast iteration
  - Develop once, deploy everywhere
  - Continuous integration, Continuous delivery
- Isolated environment
  - Experiment with unsafe stuff





# Agenda

Dev Environment

**Work with Kafka**

Work with Cassandra



# Functionality

- Write data to Kafka
  - Should be able to write to any kafka cluster
  - Should be able to write to any kafka topic
- Fetch data from stock exchange
  - Should be able to specify which stock

# Work with Kafka Using Python

- `pip install schedule`
- `pip install kafka-python`
- `pip install googlefinance`
- `pip freeze > requirements.txt`
- 可以使用virtualenv来进行开发环境隔离
  - `pip install virtualenv`
  - `virtualenv env`
  - `source env/bin/active` (MacOS \*nix)
  - 直接去env/Scripts/目录下运行active脚本 (Windows)



# Code LifeCycle

- Help you release resources properly
  - ThreadPool
  - Database Connections
  - Network Connections
- Otherwise you might create leak on server side





# Agenda

Dev Environment

Work with Kafka

**Work with Cassandra**

# Functionality

- Read data from Kafka
  - Should be able to read from any kafka cluster
  - Should be able to read from any kafka topic
- Write data to Cassandra
  - Should be able to write to any Cassandra cluster
  - Should be able to write to any Cassandra table, etc

# Work with Cassandra Using Python

- `pip install virtualenv`
- `virtualenv env`
- `pip install cassandra-driver`
- `pip freeze > requirements.txt`




# Work with Cassandra Using Python

- How to model data?
  - Our data is time series
  - Leveraging this will give us better performance
- ```
CREATE KEYSPACE "stock" WITH replication = {'class': 'SimpleStrategy', 'replication_factor': 1}
AND durable_writes = 'true';
```
- ```
USE stock;
```
- ```
CREATE TABLE stock (stock_symbol text, trade_time timestamp, trade_price float, PRIMARY KEY
(stock_symbol,trade_time));
```




# Logging

- Log is your god when things go south
- Sometimes, logging is not enough in distributed system






# Tracing




# Cassandra Data Modeling



Stored by last name

Multiple partitions,  
non-sequential rows




Stored by age

Single partition,  
sequential rows



# Cassandra Data Modeling

- `SortedMap<String, SortedMap<ColumnKey, ColumnValue>>`



# Further Reading

- Google Dapper Paper: <http://research.google.com/pubs/pub36356.html>
- Zipkin: <http://zipkin.io>
- Cassandra Data Modeling
  - <http://www.planetcassandra.org/blog/the-most-important-thing-to-know-in-cassandra-data-modeling-the-primary-key/>
- HBase Internal
  - <https://www.mapr.com/blog/in-depth-look-hbase-architecture>

# Before Next Class

- `docker pull mesosphere/mesos-master:0.28.0-2.0.16.ubuntu1404`
- `docker pull mesosphere/mesos-slave:0.28.0-2.0.16.ubuntu1404`
- `docker pull mesosphere/marathon:v1.1.1`
- `docker pull redis:alpine`