Hewlett Packard Enterprise

Antilear Petroleum Operations

Hewlett Packard Enterprise

Installation and configuration Guide for Frame

HPE SYNERGY 12000

Hewlett Packard Enterprise

Amilcar Petroleum Operations

Table of contents

1. Objective

This document provides instructions for installing and configuring the HPE SYNERGY frame

2. HLD Architecture



3. Port connections

	Virtual Connect		port	Switch
HPE Synergy SFAX	VC3	Q1 (LAN)	3	Core LAN
		Q2 (LAN)	4	Core LAN
		Q3	1	Switch SAN 1
		Q4	2	Switch SAN1
		Q5		
		Q6		
	VC6	Q1 (LAN)	5	Core LAN
		Q2 (LAN)	6	Core LAN
		Q3	1	Switch SAN 2
		Q4	2	Switch SAN 2
		Q5		
		Q6		
	MGMT	FLM 1	1	Core LAN
		FLM 2	2	Core LAN

4. HPE SYNERGY Frame Initialization

- Access the HPE Synergy Console using the VNC Viewer.	
- Connect to the Synergy Console and launch “Hardware Setup procedure” through Frame Health & Inventory-- Connect	

- Connect to HPE OneView and select Hardware Setup.	
- Configure the necessary Synergy network settings. - Specify the IP address as well as the two service addresses, subnet mask and gateway.	

- Add the two DNS servers (primary and secondary).	
- Wait for the network settings application to finish	

- Wait until the hardware discovery to complete	
-Agree with OneView licensing terms .	

- Log in to the HPE OneView management interface using default credentials.	
-change the default password	

-Access to Onview Dashboard	
- Choose Update appliance at Appliance > Settings level. The version is 6.5	

- Select the update image after downloading it	
-choose Upload the image file and wait for a prompt to install it and click Upload	

- Wait for the image to finish downloading	
-Accept the terms in the license agrement and click Update	

-Click yes update	
- Monitor the progress of the update	

-when the update process from 6.5 to 7.0 ,is accomplished. Update again the Oneview Appliance To version 7.2 then to version 8.2	
The version of HPE OneView is 8.2	

5. HPE OneView Management Console

HPE OneView uses a resource model that reduces complexity and simplifies managing your data center. This pattern provides logical resources, including models, groups, and sets, which when applied to physical resources provides a common structure across your data center.

Summary diagram of resource models

The following figure summarizes some of the most frequently used resources and shows the relationships between them.



a. Set IP address and subnet ranges

Connect to the HPE Oneview management console, Select Settings then Addresses & Identifiers	

Choose Add IPV4 subnet and address range





b. Firmware Bundle Synergy service Pack

A firmware bundle, also known as an SPP, is a comprehensive collection of firmware and system software components, all tested together as a single solution stack that includes drivers, agents, utilities, and firmware packages.

You can apply SPPs as baselines to frames, interconnects, and server profiles, establishing a desired version for firmware and drivers across devices. Each SPP deliverable contains the Smart Update Manager (SUM) and firmware smart components. Hot fixes are software and firmware component updates that have an additional release outside the normal SPP release cycle and that address specific issues. Each hot fix is listed on the "Hot Fix and Advisories" page associated with a specific SPP. These pages are available from the SPP download page at the site that is displayed on the slide

In the main menu choose Appliance then Firmware Bundle	
Cliquer Add firmware Bundle	

Choose SPP	
Click OK in order to start Click Start upload.	

Adding the SPP bundle is successfully completed	

c. Configuring Networks and Network Set

i. Configuring Ethernet networks

In the main menu, select Networks then click on + Create network The Create network dialog opens	

Create Ethernet Network For Name: VLAN2009-VM-PROD2 Type **Ethernet**. For VLAN, select **Tagged** For VLAN ID (ID de VLAN), enter **ID** For Purpose General	
Vue of all networks created	

ii. Configuration SAN Fibre Channel Networks

From the main menu, select Networks then click + Create network in the main pane.
The Create network dialog opens.
2. For Name SAN-A enter FC For Type, select Fiber Channel.
For Fabric type, select Direct attach. For this datacenter, use the default values for the other attributes of configuration. Click Create +



For Name SAN-B enter FC For Type, select Fiber Channel. For Fabric type, select Direct attach. For this datacenter, use the default values for the other attributes of configuration. Click Create	

Same procedure to create other networks

- **Site Sfax**

Network Name	VLAN	Ethernet/FC	Purpose
HD-VLAN2008-VM-PROD01	2008	Ethernet	General
HD-VLAN2009-VM-PROD02	2009	Ethernet	General
HD-VLAN2010-VM-NON-PROD	2010	Ethernet	General
HD-VLAN171-VM-MGMT	171	Ethernet	General
HD-VLAN-2011-BACKUP	2011	Ethernet	General
HD-VLAN-2019-VM-MGMT	2019	Ethernet	General
SAN-A		FC	
SAN-B		FC	
Vmotion	Untagged	Ethernet	VM Migration

iii. Configuration des ensembles de réseaux

You use network sets to create multiple networks per connection. During this task, you will use the device's smart search capabilities to quickly narrow the list of networks that you add to the network set.

From Main Menu
Select Network Sets),
then click
network set.



Create Network set for
Management and for
Prod
and select Networks





d. Create Logical Interconnects Groups : LIG

A logical interconnect group is a set of logical interconnects that represent the available networks based on internal networks, uplink sets, and interconnect settings for a set of physical interconnects in a single enclosure or set of enclosures. You can have multiple logical interconnect groups per enclosure group.

In the main Menu, sélect Logical InterConnect Groups and click + Create logical InterConnect group



Select HP VC 100Gb F32 Module For Synergy.
Choose Enclosure Count :1
Interconnect bay Set 3 & 6



Click Add uplink set to create ethernet uplink set.
Add Networks



Configuration of uplinks ports

Choose
- ICM 3 : Q1 :1 Q2 :1

ICM 6 :Q1 :1 Q2 :1



Configure internal network for VMotion



Configure Uplink set for **Fibre Channel network** and define the uplink ports
ICM3 :Q3 :1
ICM3 :Q4 :1
For SAN –B define uplink port
ICM6 :Q3 :1
ICM6 :Q4 :1





Site Tunis				
Uplink Set	**Type**	**Networks**	**Uplink Port**	
LAN	Ethernet	Corporate	ICM3	Q1:1
		DMZ		Q2:1
		Management DNS	ICM6	Q1:1
		Management SRV		Q2:1
RX-SAN -A	FC	SAN A	ICM3	Q3:1
			ICM3	Q4:1
RX-SAN -B	FC	SAN B	ICM6	Q3:1
			ICM6	Q4:1
Backup	Ethernet	Backup	ICM 3	Q5:1
			ICM 6	Q5:1

e. Create Enclosure Group

A part of the procedure to manage a frame includes specifying the enclosure group to which it will belong. Each enclosure group is associated with one or more logical interconnect groups that act as a recipe for creating and configuring the logical interconnects. That configuration is then applied to each enclosure added as a member of the enclosure group.

From the main menu, select Enclosure Groups, click Create enclosure group . The Create enclosure group dialog box appears.



Set Name, Select The management pool.
Click Create



Select LIG in Inetrconnect Bay Configuration side



f. Add Logical Enclosure

A logical enclosure (LE) contains the configuration intended for a set of physical enclosures. It also automatically creates a logical interconnect (LI) for each logical interconnect group

defined in an enclosure group.A logical enclosure is created by specifying the enclosures and the enclosure group template. Firmware baseline is an optional setting

In the main menu select servers, logical Enclosures then create logical Enclousure	

Set informations of the LE and EG	
Wait until the end of the logical enclosure addition phase	
Update the Inteconnect Firmware version using SPP	

Choose orchestrated activation and click update	
Wait untill the update firmware process finish	

g. Server Profile template

Server profile templates help to monitor, flag, and update server profiles in HPE OneView. A server profile template serves as a structural reference when creating a server profile and defines the centralized source for the configuration of firmware, connections, local storage, SAN storage, boot, BIOS, profile affinity, and hides unused FlexNICs. Typically, you capture best-practice configurations in a server profile template, and then create and deploy server profiles.

In the main menu select Server Profile Template



Choose create Server Profile Template.
Set the needed informations
NAME : ESXI-Template
Server Hardware Type : Sy 480Gen 10



Click Add Connection and define Connections types for this profile.
Create Connection: SAN-A
And associate it to port Mezzanine 3 :1-b



Vue sur les différents Connection crées




5 SAN-B SAN-B Fabric attach Mezzanine 3:2-b Not bootable
Type Fibre Channel
WWPN Auto
WWNN Auto
MAC address Auto
Requested bandwidth 6 Gb/s
6 VMOTION-P1 Vmotion Untagged Mezzanine 3:1-e Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 2.5 Gb/s
Link aggregation group None
7 MGMT-P1 HD-MGMT (network set) Mezzanine 3:1-f Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 2.5 Gb/s
Link aggregation group None
Isolated trunk No
AK
8 PROD-P2 HD-PROD (network set) Mezzanine 3:2-a Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 9 Gb/s
Link aggregation group None
Isolated trunk No
9 NON-PROD-P2 HD-VLAN2010-VM-NON-PROD VLAN2010 Mezzanine 3:2-c Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
10 Backup-P2 HD-VLAN-2011-BACKUP VLAN2011 Mezzanine 3:2-d Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 2.5 Gb/s
Link aggregation group None
11 VMOTION-P2 Vmotion Untagged Mezzanine 3:2-e Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 2.5 Gb/s
Link aggregation group None
12 MGMT-P2 HD-MGMT (network set) Mezzanine 3:2-f Not bootable
Type Ethernet
MAC address Auto
Requested virtual functions None
Requested bandwidth 2.5 Gb/s
Link aggregation group None
Isolated trunk No
AK

For boot mode choose :UEFI optimized	
Different server profile template created	

❖ Site Sfax

Profil connexion mapping for server profile Template “Template-ESXI”

ref. name	Connection name	Network / network set name	Port	Requested bandwidth (Gb/s)
server connection #1	Mgmt-P1	HD-MGMT	Mezz3-Port1-f	2,5GB
server connection #2	Mgmt-P2	HD-MGMT	Mezz3-Port2-f	2,5GB
server connection #3	Prod-P1	HD-Prod	Mezz3-Port1-a	9Gb
server connection #4	Prod-P2	HD-Prod	Mezz3-Port2-a	9GB

server connection #5	Non-Prod-P1	HD-VLAN2010-VM-NON-PROD	Mezz3-Port1-c	2,5GB
server connection #6	Non-Prod-P2	HD-VLAN2010-VM-NON-PROD	Mezz3-Port2-c	2,5GB
server connection #7	backup-1	HD-VLAN-2011-BACKUP	Mezz3-Port1-d	2,5GB
server connection #8	backup-2	HD-VLAN-2011-BACKUP	Mezz3-Port2-d	2,5GB
server connection #9	Vmotion-P1	Vmotion	Mezz3-Port1-e	2,5GB
server connection #10	Vmotion-P2	Vmotion	Mezz3-Port2-e	2,5GB
server connection #11	SAN-A	SAN-A	Mezz3-Port1-b	8GB
server connection #12	SAN-B	SAN-B	Mezz3-Port2-b	8GB

- **Profil connexion mapping for server profile Template "Template-Oracle"**

ref. name	**Connection name**	**Network / network set name**	**Port**	**Requested bandwidth (Gb/s)**
server connection #1	PROD-ORACLE-P1	HD-VLAN2009-VM-PROD02	Mezz3-Port1-a	20 GB
server connection #2	PROD-ORACLE-P2	HD-VLAN2009-VM-PROD02	Mezz3-Port2-a	20 GB

h. Server Profile

From the main menu, select Server Profile Templates and select a template from the list of available templates.Click Actions → Create server profile in the menu on the upper right



Provide a unique name and optional description for this new server profile. Select a server hardware to assign (enclosure and enclosure bay), or select unassigned if that profile will not be applied immediately. Click the Create button.	
List of server profile created “Site-Sfax”	

- Site SFAX

Server profile Name
HD-PROF-ESXI-01
HD-PROF-ESXI-02
HD-PROF-ESXI-03
HD-PROF-ORACLE