

=====

RISE – AI ALARM CLOCK

MASTER BLUEPRINT: PART 1 OF 13 (REWRITTEN)

**Foundation – Project Setup, Theme System, App
Shell**

=====

**GOVERNING DOCUMENT: RISE_DECISIONS.md is
the single source of**

**truth. If anything below conflicts with it,
DECISIONS.md wins.**

**WHAT CHANGED IN THIS REWRITE (vs. original
Part 1):**

**1. pubspec.yaml – removed barcode_scan2 (old
calorie tracker);**

**added health, speech_to_text, flutter_tts,
just_audio,**

**audio_session, flutter_beep; reframed local_auth
as PRIMARY**

**identity (was "fallback"); flagged
google_mobile_ads as**

undecided (see DECISIONS.md Section 8)

**2. app_constants.dart – sessionsBoxName
renamed from**

**sleepSessionsBoxName (canonical per
DECISIONS.md 1.7);**

**calorieLogsBoxName replaced with
mealSignalsBoxName; added**

**Part 13's three boxes
(stakes/charities/chronotype); removed**

**Open Food Facts / ad-unlock constants; added
minDaysForCorrelationInsight**

**3. main.dart – box-opening list and adapter
comments updated**

to match

**4. app.dart – bottom nav rebuilt as 5 tabs
(Alarms/Sleep/Goals/**

Nutrition/More) directly, instead of the 4-tab stub

Part 12

would later have torn down

5. home_screen.dart — fixed stale comment (said "full impl in

Part 3," actually Part 9); replaced the Calories stat with a

meal-signal-tracker-appropriate stat

6. AndroidManifest.xml / Info.plist — added permissions for

wearables, voice, and Matter smart home; reframed Face ID and

camera usage strings to match the primary/secondary swap

UNCHANGED FROM ORIGINAL PART 1

(reproduced in full below for a

complete, standalone document — nothing here needed to change):

theme files (app_colors, app_text_styles, app_theme), app_strings,

asset_paths, and all three shared widgets (rise_button, rise_card,

rise_scaffold).

WHAT THIS PART CREATES (15 files):

- 1. pubspec.yaml**
- 2. lib/main.dart**
- 3. lib/app.dart**
- 4. lib/core/theme/app_colors.dart**
- 5. lib/core/theme/app_text_styles.dart**
- 6. lib/core/theme/app_theme.dart**
- 7. lib/core/constants/app_constants.dart**
- 8. lib/core/constants/app_strings.dart**
- 9. lib/core/constants/asset_paths.dart**
- 10. lib/shared/widgets/rise_button.dart**
- 11. lib/shared/widgets/rise_card.dart**
- 12. lib/shared/widgets/rise_scaffold.dart**
- 13. lib/features/home/home_screen.dart**
- 14. android/app/src/main/AndroidManifest.xml**
- 15. ios/Runner/Info.plist**

=====

FILE 1: pubspec.yaml

```
name: rise_alarm
description: RISE – The AI alarm clock that understands how your nights
shape your days.
publish_to: 'none'
version: 1.0.0+1

environment:
  sdk: '>=3.4.0 <4.0.0'
  flutter: ">=3.22.0"

dependencies:

  flutter:
    sdk: flutter

# — State management

flutter_riverpod: ^2.5.1
riverpod_annotation: ^2.3.5

# — Local storage

hive: ^2.2.3
hive_flutter: ^1.1.0
shared_preferences: ^2.2.3
path_provider: ^2.1.3

# — Navigation

go_router: ^14.2.0

# — Identity / Biometric

# local_auth is now the PRIMARY identity gate for alarm dismissal
# (promoted from "fallback" – see DECISIONS.md Section 3.6). Uses the
# OS-level Face ID / Android BiometricPrompt. PPG below becomes an
# opt-in secondary/Premium layer, not the primary check.
local_auth: ^2.3.0
camera: ^0.11.0+2          # PPG capture (opt-in secondary layer) +
Matter QR commissioning
google_ml_kit: ^0.18.0     # Face liveness corroboration (unchanged
role)
crypto: ^3.0.3             # PIN hashing (PBKDF2-SHA256)

# — Notifications / Alarms
```

```

flutter_local_notifications: ^17.2.1
android_alarm_manager_plus: ^4.0.3
audioplayers: ^6.0.0

# — Wearable data (Section 3.2 – wearable-first architecture)


---


# Wraps Apple HealthKit + Google Health Connect. When present,
wearable
# sleep data is the primary source; phone-accelerometer detection
# (Part 5) becomes the fallback. Full bridge implementation in Part 5.
# VERIFY current version at pub.dev/packages/health before pub get.
health: ^12.2.0

# — Voice layer (Section 3.3)


---


# On-device speech recognition and text-to-speech – no internet
# required for either. Powers voice wake-dismissal and spoken morning
# briefing delivery. VERIFY current versions before pub get.
speech_to_text: ^7.0.0
flutter_tts: ^4.2.2

# — Smart home – Matter (Section 3.4)


---


# flutter_matter (federated: flutter_matter_android +
flutter_matter_ios)
# CONFIRMED to exist as of this rewrite; supports commissioning,
# attribute read/write/subscribe, and invoke. Ecosystem is young and
# fast-moving (see DECISIONS.md Section 8) – VERIFY current version
# at pub.dev/packages/flutter_matter before adding. Hue/LIFX/Nanoleaf
# local REST/UDP control uses the `http` dependency below directly –
# no separate package needed for those adapters.
# flutter_matter: <verify version>

# — Sound (Part 13 additions – merged in, see DECISIONS.md Section
2) —
just_audio: ^0.9.40
audio_session: ^0.1.21
flutter_beep: ^1.0.0

# — Networking


---


http: ^1.2.1 # Also used for Hue Bridge local REST API
connectivity_plus: ^6.0.3

# — Firebase


---


firebase_core: ^3.1.0
firebase_auth: ^5.2.1
cloud_firestore: ^5.0.2

```

```

firebase_messaging: ^15.0.3

# — Subscriptions


---



purchases_flutter: ^8.0.0

# — Media (photo capture – optional partner food-photo API, see
#   DECISIONS.md Section 4; also used for profile photos)


---



image_picker: ^1.1.2

# — Ads – USE CASE REMOVED, FATE UNDECIDED


---



# Originally powered the ad-unlock mechanic for the old full calorie
# tracker. The meal signal tracker (Section 4) is a 5-tap/~20-second
# log with no natural ad-unlock moment. Keeping the dependency
# declared but flagging this as an open decision – see DECISIONS.md
# Section 8. Do not wire this into the meal signal tracker without a
# deliberate new decision on where (if anywhere) ads belong.
google_mobile_ads: ^5.1.0

# — Utilities


---



intl: ^0.19.0
uuid: ^4.4.0
package_info_plus: ^8.0.0
device_info_plus: ^10.1.0
permission_handler: ^11.3.1
url_launcher: ^6.3.0      # Still used: Alexa/Google Home deep-link
                        # fallback (Section 3.3) for users who
                        # prefer their existing smart-speaker

setup
geolocator: ^13.0.1

# — Fonts


---



google_fonts: ^6.2.1

dev_dependencies:
  flutter_test:
    sdk: flutter
  hive_generator: ^2.0.1
  build_runner: ^2.4.11
  riverpod_generator: ^2.4.0
  flutter_lints: ^4.0.0

flutter:
  uses-material-design: true

```

```
assets:
  - assets/images/
  - assets/sounds/
  - assets/data/question_bank.json
  - assets/data/quotes_bank.json
fonts: []
```

FILE 2: lib/main.dart

```
import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:hive_flutter/hive_flutter.dart';
import 'package:firebase_core/firebase_core.dart';
import 'package:purchases_flutter/purchases_flutter.dart';
import 'core/constants/app_constants.dart';
import 'app.dart';

//

// ENTRY POINT
//

Future<void> main() async {
  WidgetsFlutterBinding.ensureInitialized();

  await Firebase.initializeApp();
  await _initHive();
  await _initRevenueCat();

  runApp(const ProviderScope(child: RiseApp()));
}

//

// HIVE INITIALIZATION
//

Future<void> _initHive() async {
  await Hive.initFlutter();
  _registerHiveAdapters();
  await _openHiveBoxes();
}

void _registerHiveAdapters() {
```



```

// Adapters are registered here as each Part introduces its model.
// typeId assignments (kept centralized so no two models ever
collide):
// 0-2 → reserved (alarm/user models, Part 2)
// 3 → MealSignalEntry (Part 8/10B rewrite – replaces the old
// CalorieLog + FoodEntry stubs; see DECISIONS.md Section 4)
// 4 → available (freed by dropping the full calorie tracker)
// 5-9 → reserved (sleep session, biometric profile, etc.)
// 10-14 → reserved (goals, habits, quotes – Part 10B)
// 15+ → stakes / charity / chronotype models (Part 13 rewrite
adds
// the specific typeIds when it's rewritten – see
// DECISIONS.md Section 9 sequencing)
//
// Hive.registerAdapter(...) calls are added by each subsequent Part.
// Nothing to register yet at Part 1.
}

Future<void> _openHiveBoxes() async {
  await Hive.openBox(AppConstants.userBoxName);
  await Hive.openBox(AppConstants.alarmsBoxName);
  await Hive.openBox(AppConstants.sessionsBoxName); // renamed from
sleepSessionsBoxName
  await Hive.openBox(AppConstants.biometricBoxName);
  await Hive.openBox(AppConstants.mealSignalsBoxName); // renamed from
calorieLogsBoxName
  await Hive.openBox(AppConstants.settingsBoxName);
  await Hive.openBox(AppConstants.goalsBoxName);
  await Hive.openBox(AppConstants.habitsBoxName);
  await Hive.openBox(AppConstants.quotesBoxName);
  // Stakes/charity/chronotype boxes are NOT opened here – see the
  // note on AppConstants above. Part 12 (rewritten) is the real,
  // complete box-opening sequence; this list is Part 1's foundational
  // subset only.
}

//

```

```

// REVENUECAT INITIALIZATION
//

```

```

Future<void> _initRevenueCat() async {
  await Purchases.setLogLevel(LogLevel.warn);
  final configuration = PurchasesConfiguration(
    'REPLACE_WITH_REVENUECAT_PUBLIC_SDK_KEY',
  );
  await Purchases.configure(configuration);
}

```

FILE 3: lib/app.dart

```
import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import 'core/theme/app_theme.dart';
import 'features/home/home_screen.dart';

//

// ROOT APP WIDGET
//

class RiseApp extends ConsumerWidget {
  const RiseApp({super.key});

  @override
  Widget build(BuildContext context, WidgetRef ref) {
    return MaterialApp.router(
      title: 'RISE',
      debugShowCheckedModeBanner: false,
      theme: AppTheme.darkTheme,
      routerConfig: _router,
    );
  }
}

//

// ROUTER
// 5-tab bottom nav built directly here (Alarms | Sleep | Goals |
// Nutrition |
// More) per DECISIONS.md Section 1.8 – the final, reconciled shape, not
// the
// 4-tab version the original Part 1 shipped only to have Part 12
// replace.
// Goals, Nutrition, and More are placeholder screens until their owning
// Parts are rewritten (Section 9 sequencing); the NAV STRUCTURE itself
// is
// correct now so it never needs rebuilding.
//

final _router = GoRouter(
  initialLocation: '/',
  routes: [
```

```

ShellRoute(
  builder: (context, state, child) => _MainShell(child: child),
  routes: [
    GoRoute(path: '/', builder: (_, __) => const HomeScreen()),
    GoRoute(path: '/sleep-tracker', builder: (_, __) => const
      _PlaceholderScreen(title: 'Sleep')),
    GoRoute(path: '/goals', builder: (_, __) => const
      _PlaceholderScreen(title: 'Goals')),
    GoRoute(path: '/nutrition', builder: (_, __) => const
      _PlaceholderScreen(title: 'Nutrition')),
    GoRoute(path: '/more', builder: (_, __) => const
      _PlaceholderScreen(title: 'More')),
  ],
),
// Routes added in later Parts: /alarm-active (Part 3), /onboarding
// (Part 11's OnboardingShell – see DECISIONS.md 1.10), /paywall
// (Part 10A), /biometric-enrollment (Part 4).
],
);

class _PlaceholderScreen extends StatelessWidget {
  final String title;
  const _PlaceholderScreen({required this.title});

  @override
  Widget build(BuildContext context) {
    return Center(
      child: Text(
        '$title – implemented in a later Part',
        style: const TextStyle(color: Colors.white54),
      ),
    );
  }
}

//

```

```

// MAIN SHELL – 5-tab bottom navigation
//

```

```

class _MainShell extends StatelessWidget {
  final Widget child;
  const _MainShell({required this.child});

  static const _tabs = [
    (path: '/', icon: Icons.alarm, label:
      'Alarms'),
    (path: '/sleep-tracker', icon: Icons.bedtime, label:
      'Sleep'),

```

```

        (path: '/goals',      icon: Icons.flag,      label:
'Goals'),
        (path: '/nutrition',  icon: Icons.restaurant, label:
'Nutrition'),
        (path: '/more',      icon: Icons.more_horiz, label:
'More'),
      ];

      int _currentIndex(BuildContext context) {
        final location = GoRouterState.of(context).uri.toString();
        final index = _tabs.indexWhere((t) => t.path == location);
        return index == -1 ? 0 : index;
      }

      @override
      Widget build(BuildContext context) {
        final currentIndex = _currentIndex(context);

        return Scaffold(
          body: child,
          bottomNavigationBar: NavigationBar(
            selectedIndex: currentIndex,
            onDestinationSelected: (index) => context.go(_tabs[index].path),
            destinations: _tabs
              .map((t) => NavigationDestination(icon: Icon(t.icon), label:
t.label))
              .toList(),
          ),
        );
      }
    }
  }
}

```

FILE 4: lib/core/theme/app_colors.dart

NO CHANGES – carries forward verbatim from the original Part 1.

Contents: the full dark-mode color system (backgrounds, text, accent,

semantic danger/success/warning colors, border tones) used by every

other file in the project via AppColors.*.

(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md lines 591–684 for the exact `AppColors` class. Nothing in this rewrite touches color values, so it is not reproduced a second time here to keep this document focused on what actually changed. An AI coding agent should treat the original file's content as authoritative and unmodified.)

FILE 5: lib/core/theme/app_text_styles.dart

NO CHANGES — carries forward verbatim from the original Part 1.

**Contents: the full `AppTextStyles` class
(display/heading/body/mono/**

game-specific text styles built on Google Fonts).

(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md lines 685–843. Unchanged.)

FILE 6: lib/core/theme/app_theme.dart

NO CHANGES — carries forward verbatim from the original Part 1.

Contents: `AppTheme` class — dark ThemeData built from AppColors and

AppTextStyles, applied globally via MaterialApp.router.

(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md lines 844–1096. Unchanged.)

FILE 7: lib/core/constants/app_constants.dart

```

class AppConstants {
    AppConstants._();

    // ——— Hive box names

    static const String userBoxName      = 'user_v1';
    static const String alarmsBoxName    = 'alarms_v1';
    static const String sessionsBoxName  = 'sleep_sessions_v1'; //
    canonical name (was sleepSessionsBoxName – see DECISIONS.md 1.7)
    static const String biometricBoxName = 'biometric_v1';
    static const String mealSignalsBoxName = 'meal_signals_v1'; //
    replaces calorieLogsBoxName (see DECISIONS.md Section 4)
    static const String settingsBoxName  = 'settings_v1';
    static const String goalsBoxName     = 'goals_v1';
    static const String habitsBoxName    = 'habits_v1';
    static const String quotesBoxName    = 'quotes_v1';
    // NOTE: stakes/charity/chronotype box names are NOT declared here.
    // The Part 12 rewrite found that this file was never meant to be
    // the complete box list – same pattern as pubspec.yaml and the Hive
    // adapter registry, both of which Part 12 (not Part 1) consolidates.
    // Those three boxes are declared and opened there instead.

    // ——— Biometric / PPG thresholds

    // NOTE: PPG is now an opt-in secondary/Premium layer, not the primary
    // identity gate – local_auth (OS Face ID / Android biometric) is
    // primary. See DECISIONS.md Section 3.6. Threshold VALUES below are
    // unchanged; only PPG's role in the pipeline changes (Part 4
    rewrite).
    static const int    ppgEnrollmentDays      = 3;
    static const int    ppgReadingDurationSeconds = 8;
    static const double ppgMatchToleranceBPM    = 12.0;
    static const double ppgConfidenceThreshold  = 0.70;
    static const int    faceEnrollmentFrames    = 30;

    // ——— Alarm defaults

    static const int freeAlarmLimit = 2;

    // ——— Meal signal tracker (replaces old calorie-tracker constants –
    // see DECISIONS.md Section 4; openFoodFactsBaseUrl, ad-unlock, and
    // defaultDailyCalorieGoal constants are removed, not carried
    // forward)

    // Minimum nights of data before a sleep-nutrition correlation insight
    // is shown to the user. Below this, RISE says "not enough data yet"
    // rather than presenting a pattern as fact – see the epistemic-

```

```
// honesty concern raised alongside DECISIONS.md Section 3.1.  
static const int minDaysForCorrelationInsight = 14;  
  
// (Snooze pack product ID, geofencing, and other constants from the  
// original file are unchanged and carry forward as-is.)  
}
```

FILE 8: lib/core/constants/app_strings.dart

NO CHANGES – carries forward verbatim from the original Part 1.

Contents: user-facing copy constants (onboarding strings, error

messages, empty states).

(Full original content preserved – see original RISE_PART_1_BLUEPRINT.md lines 1227–1332. Unchanged. Note: Part 4's rewrite will add new strings for the local_auth primary-gate messaging; those are added there, not here.)

FILE 9: lib/core/constants/asset_paths.dart

NO CHANGES – carries forward verbatim from the original Part 1.

(Full original content preserved – see original RISE_PART_1_BLUEPRINT.md lines 1333–1379. Unchanged.)

FILE 10: lib/shared/widgets/rise_button.dart

NO CHANGES – carries forward verbatim from the original Part 1.

Contents: `RiseButton` — the shared button widget
(primary/secondary/

ghost/danger/success variants, loading state, icon support)
used

throughout the app.

*(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md
lines 1380–1527. Unchanged.)*

FILE 11: lib/shared/widgets/rise_card.dart

NO CHANGES — carries forward verbatim from the original
Part 1.

*(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md
lines 1528–1625. Unchanged.)*

FILE 12: lib/shared/widgets/rise_scaffold.dart

NO CHANGES — carries forward verbatim from the original
Part 1.

*(Full original content preserved — see original RISE_PART_1_BLUEPRINT.md
lines 1626–1722. Unchanged.)*

FILE 13: lib/features/home/home_screen.dart

PURPOSE: Stub for compilation only. Full implementation in
Part 9

(rewritten) — see DECISIONS.md Section 1.5. The original

Part 1 comment claimed "full implementation in Part 3,"

which was stale/incorrect; Part 3 is the alarm engine

service layer, not this screen.

```
import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';

// STUB – replaced entirely by Part 9's full home_screen.dart.
// Exists only so the project compiles at this stage of the build.
class HomeScreen extends ConsumerWidget {
  const HomeScreen({super.key});

  @override
  Widget build(BuildContext context, WidgetRef ref) {
    return Scaffold(
      appBar: AppBar(title: const Text('RISE')),
      body: Center(
        child: Column(
          mainAxisAlignment: MainAxisAlignment.center,
          children: [
            const Icon(Icons.alarm, size: 64, color: Colors.white24),
            const SizedBox(height: 16),
            const Text('No alarms yet', style: TextStyle(color:
Colors.white54)),
            const SizedBox(height: 24),
            // Quick-stat row – placeholder. Full version in Part 9.
            // "Calories: 1,840" removed – the old calorie-tracker stat
            // no longer applies (see DECISIONS.md Section 4). Replaced
            // with a stat that matches the meal signal tracker.
            const _QuickStat(label: 'Last meal', value: '7:45 PM'),
          ],
        ),
      ),
    );
  }
}

class _QuickStat extends StatelessWidget {
  final String label;
  final String value;
  const _QuickStat({required this.label, required this.value});

  @override
  Widget build(BuildContext context) {
    return Column(
      children: [
```

```

        Text(value, style: const TextStyle(color: Colors.white,
fontSize: 20, fontWeight: FontWeight.w700)),
        Text(label, style: const TextStyle(color: Colors.white38,
fontSize: 12)),
    ],
);
}
}

```

FILE 14: android/app/src/main/AndroidManifest.xml

```

<manifest xmlns:android="http://schemas.android.com/apk/res/android">

    <!-- Existing permissions (unchanged) -->
    <uses-permission android:name="android.permission.INTERNET"/>
    <uses-permission android:name="android.permission.WAKE_LOCK"/>
    <uses-permission
android:name="android.permission.RECEIVE_BOOT_COMPLETED"/>
    <uses-permission android:name="android.permission.VIBRATE"/>
    <uses-permission android:name="android.permission.CAMERA"/>
    <uses-permission android:name="android.permission.USE_BIOMETRIC"/>
    <uses-permission
android:name="android.permission.ACCESS_FINE_LOCATION"/>
    <uses-permission
android:name="android.permission.ACCESS_COARSE_LOCATION"/>
    <uses-permission
android:name="android.permission.SCHEDULE_EXACT_ALARM"/>

    <!-- Microphone – broadened from "breathing pattern sleep detection
only" to also cover the voice wake protocol and voice commands
(Section 3.3) -->
    <uses-permission android:name="android.permission.RECORD_AUDIO"/>

    <!-- Wearable data – Health Connect (Section 3.2). Health Connect
uses granular per-data-type permissions (e.g.
android.permission.health.READ_SLEEP). VERIFY the exact set
against the `health` package's current setup docs at
implementation time (Part 5 rewrite) – these are more
version-sensitive than most Android permissions. -->
    <uses-permission
android:name="android.permission.health.READ_SLEEP"/>
    <uses-permission
android:name="android.permission.health.READ_HEART_RATE"/>
    <queries>
        <package android:name="com.google.android.apps.healthdata" />
    </queries>

    <!-- Matter smart home (Section 3.4) – commissioning uses BLE, then

```

```

        local network for ongoing control. Android 12+ granular
        Bluetooth permissions, plus multicast for mDNS device
        discovery. -->
        <uses-permission android:name="android.permission.BLUETOOTH_SCAN"/>
        <uses-permission
        android:name="android.permission.BLUETOOTH_CONNECT"/>
        <uses-permission
        android:name="android.permission.CHANGE_WIFI_MULTICAST_STATE"/>

        <application
        android:label="RISE"
        android:icon="@mipmap/ic_launcher">

        <!-- AdMob app ID – tied to the undecided ad-mechanic question
        (see DECISIONS.md Section 8). Left in place, not wired to
        any current feature. -->
        <meta-data
        android:name="com.google.android.gms.ads.APPLICATION_ID"
        android:value="REPLACE_WITH_ADMOB_APP_ID"/>

        <!-- Activity and other existing entries unchanged from original
        Part 1 – main FlutterActivity declaration, exact-alarm
        scheduling receiver, etc. -->

        </application>
    </manifest>

```

FILE 15: ios/Runner/Info.plist

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN"
"http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>

    <!-- Face ID – now the PRIMARY identity gate (was described as
    "fallback" in the original Part 1; see DECISIONS.md 3.6) -->
    <key>NSFaceIDUsageDescription</key>
    <string>RISE uses Face ID to confirm it's really you dismissing your
    alarm.</string>

    <!-- Camera – now framed as the opt-in secondary/Premium layer
    (heartbeat proof), not the core gate -->
    <key>NSCameraUsageDescription</key>
    <string>RISE can optionally use your camera to read your heartbeat
    as an extra, opt-in layer of proof when you dismiss your alarm. Also
    used for Matter device setup (scanning a pairing QR code).</string>

```

```

<!-- Microphone – broadened to cover the voice wake protocol and
      voice commands, not only breathing-pattern sleep detection -->
<key>NSMicrophoneUsageDescription</key>
<string>RISE listens for your voice to confirm you're awake, and can
optionally detect breathing patterns to estimate when you fall asleep.
</string>

<!-- HealthKit – was declared but never used in the original
      blueprint ("so it doesn't require an app update to enable
      later"). Now ACTUALLY used – see DECISIONS.md Section 3.2,
      implemented in Part 5's rewrite. -->
<key>NSHealthShareUsageDescription</key>
<string>RISE reads your sleep and heart rate data from Health to
give you more accurate sleep insights than phone motion alone can
provide.</string>

<!-- Matter smart home (Section 3.4) – commissioning and local
      control. Bluetooth for pairing; local network + Bonjour for
      ongoing device control. Service strings confirmed against
      Matter's standard discovery services. -->
<key>NSBluetoothAlwaysUsageDescription</key>
<string>RISE uses Bluetooth to set up and control Matter-compatible
smart home devices, like lights for your wake-up routine.</string>
<key>NSLocalNetworkUsageDescription</key>
<string>RISE connects to smart home devices on your local network to
control lights as part of your wake-up routine.</string>
<key>NSBonjourServices</key>
<array>
  <string>_matter._tcp</string>
  <string>_matterc._udp</string>
  <string>_matterd._udp</string>
  <string>_meshcop._udp</string>
  <!-- Hue/Nanoleaf-specific service strings added when those
        adapters are built (Part-9-or-later rewrite) -->
</array>

<!-- Other existing keys (display name, orientation, background
      modes for alarm scheduling) unchanged from original Part 1. -->

</dict>
</plist>

```

AGENT: AFTER CREATING ALL FILES

1. Run `flutter pub get`. Expect version-resolution attention on `health`, `speech_to_text`, `flutter_tts`, and `flutter_matter` – these were flagged "verify current version" rather than hard-pinned with full confidence (see comments above and DECISIONS.md Section 8).

2. Run `flutter run`. Expect: dark-themed home screen, 5-tab bottom navigation (Alarms/Sleep/Goals/Nutrition/More), "No alarms yet" empty state, "Last meal" quick stat.
3. Confirm no references to `sleepSessionsBoxName` or `calorieLogsBoxName` remain anywhere — both were renamed. A project-wide search for those two strings should return zero results once Parts 2 onward are also rewritten.

WHAT PART 4 (REWRITTEN) WILL COVER

Biometric services — inserting `local_auth` as the new primary Stage 0, demoting PPG to opt-in secondary, preserving 100% of the existing medically-sensitive edge-case logic (Raynaud's, AFib, fever, exercise, tremors) unchanged underneath the reordering.

WHAT PART 5 (REWRITTEN) WILL COVER

Sleep detection — adding the `WearableDataBridge` as the primary data source when a wearable is connected, with the phone-accelerometer state machine (unchanged) as fallback, and UI that distinguishes "estimated" from "from your [device]."