

```
%Assessment 2                                :Geared-shaft Torsional Vibration System
%Name                                           :Ziphozethu Maggazolo
%Student Number                               :16622685
%Module                                         :SME3701
```

%%Given Parameters

```
d = 0.050; %Diameter in meters
L = 1.00; %Length in meters
G = 79.3e9; %Shear modulus in Pascals
J0 = 0.10; %Mass moment of Inertia in kg.m^2
T = 1000; %Transmitted Torque in N.m
N_driven = 1000; %Driving speed in rpm
Teeth = 16; %Number of driving gear teeth
```

%System Parameter Calculation for Simulink

%Calculate Polar Moment of Inertia (J_p):

```
J_p = (pi / 32) * d^4; % Polar moment of inertia = (pi / 32) * 0.05^4 =
6.136x10^-7 m^4
```

%Calculate Torsional Stiffness (k_t):

```
k_t = (G * J_p) / L; % Torsional stiffness = (79.3e9 * 6.136x10^-7) / 1 =
48657.8 N.m/rad
```

%Calculate System's Natural Frequency (f_n):

```
omega_n = sqrt(k_t / J0); % omega_n = sqrt(48657.8 / 0.10) = 697.55 rad/s
% Calculate the system's natural frequency in Hz
f_n = omega_n / (2 * pi); % Convert from rad/s to Hz = 697.55 / (2 * pi) =
111.02 Hz
```

%Nominal Driven Angular Velocity:

```
omega_driven = (2 * pi * N_driven) / 60; % omega_driven = (2 * pi * 1000) /
60 = 104.72 rad/s
```

%Calculate Static Deflection (theta) Under Steady Condition:

```
theta = T / k_t; % Static Deflection = 1000 / 48657.8 = 0.02055 rad
```

%Calculate Frequency of Driven Gear:

```
N_driven_Hz = N_driven / 60; % Frequency of driven gear = 1000 / 60 = 16.67
Hz
t_p = 1 / N_driven_Hz; % Pulse period per broken tooth = 1 / 16.67 = 0.06 s
```

%Calculate Tooth Mesh/Impact Frequency (f_"tooth"):

```
f_tooth = N_driven_Hz * Teeth; % Tooth mesh frequency = 16.67 * 16 = 266.67
Hz
T_impact = 1 / f_tooth; % Time between tooth impact = 1 / 266.67 = 0.00375 s
```

%1.2 Simulink scope video attached

```
%1.3 a) Max angular displacement in rad = 27.23 rad
%1.3 b) Max angular velocity in rad = 0.0596 rad

%1.4 Natural frequency = 111.02 Hz (dominant torsional vibration)
%1.4 Tooth Mesh frequency = 266.67 Hz
%1.4 Driven gear frequency = 16.67 Hz
% Based on these different frequencies resonance does not occur, large
% spikes are not caused by resonance continuous build-up. Instead each time
% tooth hits every 0.06 sec it triggers a strong natural free vibration
% then gradually fades away before the next impact.
```

https://github.com/Ziphozethu-Magqazolo/16622685/blob/main/16622685_SME3701_SIMULINK_VIDEO.mp4

<https://drive.mathworks.com/files/b16622685.mlx>

<https://drive.mathworks.com/files/b16622685.slx>