more manuals need colouring pages

Thank you for your purchase! If you have any questions, you can email me at:

or dm me on discord:



discord.gg/vpxSHmUSXH

1-2. Product Diagram
3-6. Setup Guide
7. Light Guide
8. Button Guide
9. Firmware Updates
10-12. Troubleshooting \* Disassembly
13-14. Dock Information
15. Pin Defines & Maintenance

Attributions

'9T

inì

17. Colouring Page 18-19 Schematic

#### Maintenance

Keep your trackers happy

"ZRO" calibration should be done frequently, ideally before each session (but once every couple weeks is Just Fine)

To calibrate, hold your tracker against a flat & stable surface, then double-press the side button. Make sure it doesn't move.

The light will hold solid while calibrating,

then blink a few times when finished.

Straps can be damaged by high temperatures. Make sure to wash only with warm (not hot!) or colder water. Do not machine dry: dryers are too hot. Air drying is preferable.


### Pin defines

what are you doing.

8.0	SCF
9.0	Ads
7 I.O	soiq <b>g-0</b> 1ni
SI.0	20iq-b91
62.0	clk-gpios
IE.0	0 M S

## Product Diagram


This side goes against your body.



#### Dock

do you have one yet?

Trackers can plug in in either direction. Charging brick should be rated for 0.1A/100mA per tracker ie. 10 trackers = 1A brick



# Setup Guide Pre-flight checks

Calibration should be performed upon receiving your trackers, since it's likely been a while since their last calibration.

 Press tracker against a flat, stable surface.

2. Double-press the side button. Make sure it doesn't move!

3. The light will hold red for a few seconds, then flash.


4. Calibration complete, now repeat for all other trackers.

Calibration should be done every week or so. See the Maintenance page for more info.

## Troubleshooting

Hopefully you never need to know this

SIM Ejector. a small metal pin, such as a paperclip or thing to try is a hard reboot. You will need If there is an issue with the tracker, the first



it the other way to reconnect the battery. Switch toward the Electronics Tray. Then slide Use the tool to slide the Battery Disconnect

tell you what the issue is. "Select Device" and find your tracker, it may Plug in your tracker, then in the top left press to install the Serial Terminal app, and open it. "nRF Connect for Desktop" by Mordic. Use it If this doesn't work, download the program

Discord: fui\_\_ Email: fui@macroplastics.ca If nothing here has helped, contact me.

## Setup Guide

Using your trackers

#### **J**nəmnpi]A

Vive trackers. see the Trackers appear in SteamVR as Slime VR Server and Steam VR. You should Put your headset on and launch both the

full reset. You will hear a jingle from the forward. Triple-tap your left thigh tracker to in line with your shoulders and pointed Stand up and look forward. Keep your feet

Server Home screen. Do this at the start of press the "Full Reset" button in the SlimeVR SlimeVR Server settings, or you can manually the "Trackers over threshold" value in the If it won't activate, you may need to increase Slime VR Server.

alignment perfect is a bit of a skill. in games! Keep in mind that etting the You should now be able to use your trackers every VR session.

#### Yaw Kesetting

environment. the tracker type you ordered and your takes until the drift is noticeable) will vary on drift over time. Your drift times (the time it Because these are IMU-based trackers, they

button in the SlimeVR Server. Double tap the chest tracker, or press the To reset the drift, you have to Yaw Reset.

### Firmware Updates

Do you think it feels good?

Downloading

#mps4firmware updates from my Discord server. I post them occassionally in #mps4firmware

Make sure to read the messgae before you download, some firmware might have spooky

custom settings you dont want.

You can also build the firmware yourself if you know what you're doing. See Pin Defines (pg 9) for how to set up your build and Attributions (pg 10) for the firmware github.

Uploading Plug the tracker into your computer and press the Side Button 4 times. The light should start fading slowly in and out and it should appear as a USB flash drive.

Please note it is not a flash drive. Don't store files on it.
Please note it is not a flash drive. Don't store files on it.
Prag and drop the .uf2 file into the tracker.

Your tracker should now have the latest firmware.

# Button Guide HOW DO I TURN THIS THING OFF?!?!

plod bae 33	9.1.9 G.1.95
√ bresses	Update mode Did it by accident? Reboot using battery disconnect switch (or just update it)
3 press & hold while plugged in	Pair Receiver must also be in pairing mode.
z bresses	Calibrate  Be sure to hold it against a stable surface during calibration. It cannot move!
J buess	Reboot/Power-on