aquaCare
The Water Treatment Company

Product Bulletin
Cleaner

Aqua clean 215

Principal Uses

Aqua clean 215 is a dry acid product specially formulated for removing water hardness deposits from industrial equipment. It is particularly effective in dissolving calcium carbonate scale formed in water lines, boilers, evaporators, air conditioning systems and process equipment.

Aqua clean 215 has a built-in dye indicator. Combined with the dry form this makes the product convenient and easy to use. It also contains an effective inhibitor that minimizes corrosion during the cleaning application.

Product Benefits

Aqua clean 215 provides the following benefits:

- Do-it-yourself acid scale remover
- Specially formulated blend of dry acids designed to remove water hardness deposits from industrial equipment
- Inhibited to protect metals commonly encountered during cleaning
- Easy-to-use with built-in dye indicator (produces a colour change, from blue-green to purple as acid strength is depleted)
- More convenient to handle compared to strong liquid acids

General Description

Aqua clean 215 is a pulverized product containing a blend of dry acids. It is inhibited to help protect the metals commonly encountered in industrial equipment. The dye indicator produces a colour change (blue-green to purple) in **Aqua clean 215** solutions as the acid strength is depleted. For typical chemical and physical properties, refer to **Aqua clean 215** Material Safety Data Sheet.

aquaCare
The Water Treatment Company

Dosage

Dosage will vary between 2-5% solutions by weight depending on the water holding capacity of the equipment.

Note: 2 kg of **Aqua clean 215** will dissolve up to 1kg of hardness salts.

Feeding: Dissolve in water. Pour or pump into equipment to be cleaned, and then circulate. The product may be added directly to a water system where good solution and mixing are ensured.

When the scale is heavy or very adherent, higher solution strengths or several cleanings may be necessary for complete scale removal. Contact your Aqua Care representative for specific recommendations.

Product Benefits

Solution Temperature – Although cool solutions of **Aqua clean 215** will dissolve scale, the dissolving action is accelerated as solution temperatures increase. When systems are fabricated from steel, brass, bronze or copper, the solution temperature may be increased to 71°C. In aluminium or galvanized equipment, the temperature should be kept below 48°C.

Cleaning Time – Generally 4-12 hours; varies with temperature, solution strength and type of scale.

Colour change – As **Aqua clean 215** (in solution) reacts with mineral deposits, the pH of the solution increases. When the solution loses its strength, the colour changes from blue-green to blue to purple. If the deposit has not been completely removed, additional **Aqua clean 215** may be added to bring back the blue colour, or the cleaning process may be repeated.

After Wash – After cleaning, flush equipment thoroughly with water to remove all loosened deposits. To ensure complete removal of acid, neutralization with **NaOH /Soda ash** is recommended.

Precautions – Provide suitable venting when cleaning closed systems. Keep open flames away from the vent during and immediately following cleaning. Do not apply **Aqua clean 215** to any water system while it is operating under pressure.

aquaCare
The Water Treatment Company

Application

Silica, organics and calcium sulphate normally do not respond to acid treatment. When a deposit contains a substantial percentage of these substances, a two-stage cleaning (alkaline followed by acid) is recommended. Consult your **Aqua clean 215** representatives for specific cleaning instructions and techniques.

Handling & Storage

Aqua clean 215 and its solutions are more convenient to handle than strong liquid acids. When using any acid-type materials, however, reasonable precautions should be taken.

Personal protective equipment is required for this product. Read the label information and the Material Safety Data Sheet (Section 10) before using this product. Handle product with care.

Aqua clean 215 should be stored in a dry environment, away from cold temperatures and excessive heat.

Shipping

Aqua clean 215 is shipped in plastic-lined disposable fibre drums of approximately 20/100 Kg net weight.