AQUAFLOC LT-7991

Potable water grade liquid cationic coagulant

Chemical nature

Aqueous polymer solution of epichlorohydrin amine condensates.

Application areas

Used as a primary coagulant for the clarification of potable water and a wide range of industrial effluents.

American Standard **ANSI/NSF** 60 compliant for coagulation and flocculation up to a maximum 20 mg/L.

This product is **FDA** approved. Contact a sales representative for more information.

Benefits

- Reduction or elimination of inorganic primary coagulants
- Reduction in sludge volume produced in the system
- Reduction in overall treatment cost
- Can be used in combination with inorganic coagulants
- Decrease in pH sensitivity of coagulation/flocculation process
- Stable to degradation by chlorine

Typical properties

Product type	solution polymer
Physical form	clear viscous colorless-yellow liquid
Solids content	50 %
Molecular weight	high
Specific gravity	1.14 g/cm^3
Bulk density	9.51 lb/gal
pH	5-7
Supplied viscosity	4,500 – 7,500 cPs

Storage

Under normal, dry storage conditions within the temperature range 5 – 25 °C (41 – 77 °F), this product will be stable for at least 24 months. Storage outside the above specified temperature range for long periods may adversely affect the product over a long period and should thus be avoided, if possible.

It is recommended that stock solutions at 0.25 – 0.5 % are prepared regularly, and for maximum effect such solutions should be used within 5 days.
Beyond this period some loss in efficiency of the product may occur.

Packaging

Product is available in bulk and in non-returnable packaging. Please contact your local sales office for advice.

Shipping and handling

As with all cationic polyelectrolyte polymers this product exhibits toxicity towards fish. It is important that precautions are taken where the product may come into direct contact with fresh water courses, streams and rivers.

Corrosion towards most standard materials of construction is very low. Stainless steel, fiberglass, polyethylene, polypropylene and epoxy coated surfaces are recommended. In some cases, aluminum surfaces can be adversely affected.

Spilled product is slippery underfoot, very slippery when wet. Product should be protected from frost. Information on the shipping and handling of this product can be found in the relevant Material Safety Data Sheet (MSDS). Disposal of product must comply with all national, state and local laws.

Health and safety

Detailed information on this product can be found in the relevant Material Safety Data Sheet (MSDS).

Technical service

AQUACARE sales representatives and field service technicians are available to give advice and assistance in the running of laboratory tests and machine trials to select the correct product and determine the best application conditions.

Note:

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose.

Any descriptions, drawings, photographs, data, proportions, weights etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.