MULTICARE B 326

Boiler Corrosion Inhibitor

Product Benefits

- Effectively scavenges oxygen to reduce corrosion in feed water, boiler and condensate equipment.
- Promotes magnetite formation on metal surfaces to help improve system reliability.
- Reduces pitting type corrosion in boiler systems by directly scavenging dissolved oxygen present in the feed water. Reducing corrosion will extend the useful life of the equipment and minimize unscheduled outages and down time.
- Provides effective neutralization of acidic gases, such as CO_2 in the initial condensate and the extended areas of a complex condensate system.
- Minimizes the potential for boiler tube failures causes by transported metallic corrosion products by reducing the pick-up of iron and copper in the condensate system.

Principal Uses

- **Multicare B 326** is a fast acting chemical scavenger of oxygen and also neutralizer of CO_2 gas to reduce total corrosion in steam generating and other industrial water systems.
- It may be used at boiler operating pressures from 50 to 2400 psi.

Dosage

- Total dosage will be the sum of requirements for reaction of dissolved oxygen removal 1-5 ppm of **Multicare B 326** is required per ppm of dissolved oxygen.
- Aqua Care representative will be pleased to recommend the proper dosage needed to ensure maximum program performance.

aquaCare
The Water Treatment Company

Feeding

- **Multicare B 326** should be fed as far back in the system as possible to provide maximum reaction time and to protect as much of the system as possible. For boiler feed water systems, typical feed point is the storage section of the deaerating heater or the suction side of the feed water pump.

- Make a maximum 5% solution using water of less than 40°C temperature.

- Mix only until dissolving is complete. A floating “doughnut” type cover is recommended to minimize product loss.

- Polyethylene, stainless steel and fiberglass are preferred materials for solution tanks and pumps.

- A stainless steel quill must be used to inject the solution.

Handling

- May cause irritation to skin and eyes. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid breathing dust. Do not take internally

- In case of contact:
  Skin - wash with soap and water.

- **Eyes** - immediately irrigate with copious amounts of water for at least 15 minutes and seek medical advice.

- **Clothing** - remove and wash before reuse.

Storage

- Drums should be stored in a dry area. Replace lid after use.
- Suggested in-plant storage limit is Two (02) year.

Remarks

If you need assistance or information, please contact your nearest Aqua Care representative.