



# IDX G9 Computer Science S

## Study Guide Issue #1

By Leona Cai, Edited by Doris

**NOTE: This is an official document by Indexademics. Unless otherwise stated, this document may not be accredited to individuals or groups other than the club IDX, nor should this document be distributed, sold, or modified for personal use in any way.**

### **Contents:**

1. Computer Category and Programming Language
2. Programming Intro
3. Variables and Data Types
4. Expressions
5. List
6. For-Loop
7. For-Range
8. If Statement
9. Boolean Operators

### **1.1 Computer Category and Programming Language**

#### The History of Computers

- 3000 B.C.: The **abacus**, used for addition, subtraction, division and multiplication, it can also extract square roots and cubic roots
- 1973: Xerox introduced Ethernet (wired internet), allowing computers to connect
- Various computer companies were established, including *Microsoft* (Bill Gates and Paul Allen, 1975) with the first home kit-built computer, and *Apple* (Steve Jobs and Steve Wozniak, 1976) with the first computer with a single circuit board
- 1999: Wi-Fi was invented, replacing wired Ethernet connections

## Categories of Computers

- **Special-Purpose Computers:** Designed for a particular function, executing the same stored set of instructions (EX. Microwave, washing machine etc.)
- **General-Purpose Computers:** Used for solving many different types of problems, available in a variety of sizes and capabilities.
  - **Microcomputers:** AKA personal computer (PC), can be placed on a desktop or carried from room to room
    - Size varies, from the smallest laptop computers/notebook computers to the largest type of microcomputer known as a workstation
  - **Mainframe Computers:** Powerhouse with massive memory and extremely rapid processing power, used for large businesses, scientific/military applications where computer needs to handle massive amounts of data or complicated processes
  - **Supercomputers:** Used for tasks requiring extremely rapid and complex calculations with hundreds of thousands of variable factors
    - Used for scientific research, weather prediction, aircraft design, nuclear weapons etc.

## Languages

- **Programming Languages:** Agreed upon format of symbols that allow a programmer to instruct a computer to perform certain predefined tasks
- **Machine Languages:** Natural language of a computer, and is the only language that a computer can directly use. Its instruction is a binary string of 0s and 1s.
- **Assembly Language:** Consists of English-like abbreviations, making them easier to understand. It uses language translators called **assemblers** to convert them to machine code.
- **High-level Languages:** Machine-independent, does not require programmers to know anything about the internal structure of the computer

## 1.2 Programming Intro

### Hardware and Software

- **Hardware:** Only understands the binary system
- **Software:** set of steps for instructions for computer hardware operations

## Programming Problems

- Define the problem -> Plan the solution -> Write the code -> Testing/Debugging the program
- **Interactive mode:** Start with >>>, runs one line at a time
- **Script mode:** Uses “.py” file, runs all lines you wrote at once
- **Indentation:** Indicates a block of code

## Math Operators

Operator	Operation	Example	Output
+	Addition	2+2	4
-	Subtraction	5-3	2
*	Multiplication	2*3	6
/	Division	10/2	5
**	Exponents	3**2	9

- Python follows the **PEMDAS** rule, so uses parentheses when needed

## print() function

- A value that is passed to a function call is an **argument**
- EX. print(“Hello World”), output: Hello World
- If it is a value, don’t use quotation marks. Use quotation marks for letters

## 1.3 Variables and Data Types

Operator “+” is used to **concatenate** two strings as the operation

- **input() function**
  - It will return a string type, and the user can input
    - EX. input(“What is your name”); output: What is your name; Then the user can input a name
- **Variables**
  - Containers for storing data values can store numerical or textual values
  - Rules for naming variables:
    - Can contain only letters, numbers, and underscores
    - Cannot start with a number
    - Spaces and **special characters** (-, !, @, #, %, ^, &, \*) are not allowed

- Variables are **case sensitive**, meaning age, AGE, and Age are different
- Avoid using **reserved keywords**: EX. “True”, “False”, “or”, “not”, “and”, “if”
- **Camel Case**: makes compound names easier, EX. myList, listOfNumbers
  - Can contain only letters, numbers, and underscores
- When assigning values, use “=” operator
  - Multiple assignment: multiple variables in a single statement, EX. x=y=z=50, or a,b,c=5,10,15

## Data Types

- **Integer**: int(), converts a number/string into an integer
- **Float**: float(), approximations to real numbers, they are decimals
- **String**: str(), converts a number to a string

## 1.4 Expressions

Consists of values and operators so they always evaluate down to a single value

Importing Modules: from the standard library, contains related group of functions that can be embedded in your programs

- Math Modules
  - math.pi: on its own, it returns the first 15 digits of pi
  - math.ceil(x): returns an integer  $\geq x$  (EX math.ceil(2.4); output: 3)
  - math.floor(x): returns an integer  $\leq x$  (EX math.floor(2.4); output: 2)
  - math.sqrt(x): returns the square root of x (EX math.sqrt(9); output: 3)

## 1.5 List

A collection of items in a particular order, indicated by square brackets []

- Access an element in a list by its index: listName[index]. (EX. myList[3]; output: the fourth element in the list)
- len() function: returns the number of elements in a list
  - Index of a list starts at 0. (1<sup>st</sup> element's index is 0, 2<sup>nd</sup> element's index is 1, etc.)
  - len(myList), (assuming myList has 5 elements); output: 5
- lst.index(value) function: finds the index of an element

Action	Methods/Functions
Modifying an element	<b>listName[index of element you want to change]=(new value/string)</b> EX. myList[1]=4; myList now equals [1,4,3,4]
Adding an element	<b>append():</b> adds the new element to the end of a list EX. myList.append(5); myList now equals [1,4,3,4,5]
	<b>insert( , ):</b> insert (index,value) EX. myList.insert(2,6); myList now equals [1,4,6,4,5]
Removing an element	<b>del listName[index]:</b> removes the element of that index EX. del myList[1]; myList now equals [1,6,4,5]
	<b>remove():</b> removes the specific value, deletes the first occurrence of the value you specify EX. myList.remove(1); myList now equals [6,4,5]

## 1.6 For-Loop

- **split()** function: splits a string to a list
  - `str.split(x)` will remove every x from str and return a list of the leftover
- **for loop:** repeatedly perform the same task with each element in a list
  - `for variable in range` OR `for variable in myList`; enter the task you want to perform
  - iterate a block of statements several times
- **sum()** function: sum of the entire list

## 1.7 For-Range

- **range()** function/syntax: generates a sequence of numbers in that range
  - `for i in range(5); print(i)`; output: 0, 1, 2, 3, 4 (starts from 0, ends at the integer < 5)
  - `for I in range (2,6,2):` (start, stop, step)
    - output: 2, 4
    - if there isn't an end (2,6,-3), then it will return nothing
- **random numbers:** use module **random**. (import **random**)
  - **randint(a,b):** returns in integer in the range [a,b]
  - EX. `random.randint(1,5)`; output: 4

## 1.8 If Statement

- Boolean values: True or False
- Relational Operators

Operator	Description	Example	Output
<	Less than	2<3	True
>	Greater than	3>4	False
<=	Less than or equal to	3<=9	True
>=	Greater than or equal to	8>=7	True
==	equal	2==3	False
!=	Not equal to	2!=2	False

- **If Statement:** if condition: -> statements
  - The condition has to be a Boolean expression that evaluates to True or False
  - **If else:** if condition: statement 1; else: statement2
  - **If elif else:** if condition: statement 1; elif: statement 2; else: statement 3

## 1.9 Boolean Operators

- Boolean operators: evaluate the expressions down to a Boolean value
  - () > not > and > or: meaning the computer evaluates Boolean operators in this order
  - **and** operator truth table:
    - True and True: True
    - True and False: False / False and True: False
    - False and False: False
  - **or** operator truth table:
    - True or True: True
    - True or False: True / False or True: True
    - False and False: False
  - **not** operator truth table:
    - not True: False, not False: true
- Remainder(%): gives the remained of division (EX: 22%5=2)
- Integer division: floor value of a quotient produced by a division (EX: 1234//100=12)
- Precedence: \*\*(Exponents) > (\*, /, %, //) > (+ -) > (<=, <, >, >=, !=, ==) > (not, and, or)