

# IDX G9 Computer Science S

## Study Guide S1 Monthly 2

By Leona, Edited by Doris



**NOTE: This is an official document by Indexademics. Unless otherwise stated, this document may not be accredited to individuals or groups other than the club IDX, nor should this document be distributed, sold, or modified for personal use in any way.**

### Contents:

1. Computer Colors
2. Digital Graphics
3. Alpha Channel
4. Computer Monitors
5. Image Compression


### **Computer Colors:**

- A computer's primary colors are **red, green and blue**
  - all colors we generate form the three spectral hues of red, green and blue
  - CMYK: proper reference for printed color
- HSV/HSL/HSI
  - H: Hue -> the pure dominant color (original colorness)
  - S: Saturation -> intensity/purity of a color
  - V: Value -> lightness or darkness
  - L: Lightness -> color's brightness (amount of black/white)
  - I: Intensity -> brightness or dullness of a color



- Binary notation of colors: using 24 numbers to represent a color

- EG: 111111 111111 111111 is white
- The first 6 “1”s represent the red part of the color, the next group of “1”s represent the green part and the last group of “1”s represent the blue part



- Hexadecimal: using 6 letters/numbers to represent a color

- EG: #FF FF FF represents white
- The first group of “F”s represent the red part, the second group represents green, and the third group represents blue

- Ways to store characters:

- **Morse code:** the use of dots and dashes. This can be ineffective as letters can be mixed up

- ASCII: developed from telegraph codes, encodes 128 specified characters into **7-bit integers**

- For letters, it is a capital letter, start with “10” and lowercase letters start with “11”

Dec	Hx	Oct	Char	Dec	Hx	Oct	Html	Chr	Dec	Hx	Oct	Html	Chr	Dec	Hx	Oct	Html	Chr
0	0	000	NUL (null)	32	20	040	Space	32	64	100	64	40	100	96	60	140	96	60
1	1	001	SOH (start of heading)	33	21	041	!	33	65	101	65	41	101	97	61	141	97	61
2	2	002	STX (start of text)	34	22	042	"	34	66	102	66	42	102	98	62	142	98	62
3	3	003	ETX (end of text)	35	23	043	#	35	67	103	67	43	103	99	63	143	99	63
4	4	004	EOF (end of transmission)	36	24	044	\$	36	68	104	68	44	104	100	64	144	100	64
5	5	005	ENQ (enquiry)	37	25	045	%	37	69	105	69	45	105	101	65	145	101	65
6	6	006	ACK (acknowledge)	38	26	046	&	38	70	106	70	46	106	102	66	146	102	66
7	7	007	BEL (bell)	39	27	047	'	39	71	107	71	47	107	103	67	147	103	67
8	8	010	BS (backspace)	40	28	050	(	40	72	110	72	48	110	104	68	150	104	68
9	9	011	TAB (horizontal tab)	41	29	051	)	41	73	111	73	49	111	105	69	151	105	69
10	A	012	LF (NL line feed, new line)	42	2A	052	*	42	74	112	74	4A	112	106	6A	152	106	6A
11	B	013	VT (vertical tab)	43	2B	053	+	43	75	113	75	4B	113	107	6B	153	107	6B
12	C	014	FF (NP form feed, new page)	44	2C	054	,	44	76	114	76	4C	114	108	6C	154	108	6C
13	D	015	CR (carriage return)	45	2D	055	-	45	77	115	77	4D	115	109	6D	155	109	6D
14	E	016	SO (shift out)	46	2E	056	.	46	78	116	78	4E	116	110	6E	156	110	6E
15	F	017	SI (shift in)	47	2F	057	/	47	79	117	79	4F	117	111	6F	157	111	6F
16	10	020	DLE (data link escape)	48	30	060	0	48	80	120	80	50	120	112	70	160	112	70
17	11	021	DC1 (device control 1)	49	31	061	1	49	81	121	81	51	121	113	71	161	113	71
18	12	022	DC2 (device control 2)	50	32	062	2	50	82	122	82	52	122	114	72	162	114	72
19	13	023	DC3 (device control 3)	51	33	063	3	51	83	123	83	53	123	115	73	163	115	73
20	14	024	DC4 (device control 4)	52	34	064	4	52	84	124	84	54	124	116	74	164	116	74
21	15	025	NAK (negative acknowledge)	53	35	065	5	53	85	125	85	55	125	117	75	165	117	75
22	16	026	SYN (synchronous idle)	54	36	066	6	54	86	126	86	56	126	118	76	166	118	76
23	17	027	ETB (end of trans. block)	55	37	067	7	55	87	127	87	57	127	119	77	167	119	77
24	18	030	CAN (cancel)	56	38	070	8	56	88	130	88	58	130	120	78	170	120	78
25	19	031	EM (end of medium)	57	39	071	9	57	89	131	89	59	131	121	79	171	121	79
26	1A	032	SUB (substitute)	58	3A	072	:	58	90	132	90	5A	132	122	7A	172	122	7A
27	1B	033	ESC (escape)	59	3B	073	;	59	91	133	91	5B	133	123	7B	173	123	7B
28	1C	034	FS (file separator)	60	3C	074	<	60	92	134	92	5C	134	124	7C	174	124	7C
29	1D	035	GS (group separator)	61	3D	075	=	61	93	135	93	5D	135	125	7D	175	125	7D
30	1E	036	RS (record separator)	62	3E	076	>	62	94	136	94	5E	136	126	7E	176	126	7E
31	1F	037	US (unit separator)	63	3F	077	?	63	95	137	95	5F	137	127	7F	177	127	7F

Source: [www.LookupTables.com](http://www.LookupTables.com)

- Graphic formats: format in

- GIF, shows 256 kinds of colors at most in one picture
- JPEG: millions of kinds of colors ( $2^8 \times 2^8 \times 2^8 = 16777216$ ), saves memory space in computer
- PNG: combines advantages of GIF and JPEG, good quality, can be transparent, not very popular as many web pages cannot show pictures in this format
- BMP/RLE: one of the most popular formats used to save images on windows operating system

- PSD: used in photoshop, save all detailed elements made in photoshop such as layers, color modes, path and channel etc, occupy large memory in computer but can be compressed
- HEIF: supports multiple bit depths, depending on the encoder and use case, memory is about 50% smaller than the JPEG format, shows billions of colors ( $2^{30}$ ), records images with richer information, compatibility is limited
- bit depth: color depth per channel, not the total file size or container overhead

## Digital Graphics:

- An image created/edited on a computer is either a bitmapped or vector graphic
  - **Bitmapped:** AKA raster graphics, consists of pixels, if you enlarge a bitmap you enlarge a pixel
    - pixels become more obvious and image loses crispness and clarity
  - **Vector:** uses mathematical formulas to define lines, curves and other attributes of digital images
    - you use vector graphics editing program
    - Vector files are generally much smaller than bitmapped
- The number of **pixel per inch** (ppi) determines the resolution of bitmap graphics
  - photo display on a computer screen usually looks realistic at 72 ppi
  - vector graphics do not rely on resolution for clarity, but its' display on a computer screen does
- **color depth:** in graphic files and applications, color depth refers to the number of distinct colors an image can contain/how many bits per pixel
  - EG 24-bit image has color depth of 16.7 million colors, called **full color image**
- **Field of View/Field of vision (FOV):** extent of observable world that is seen at any given moment
  - Humans have  $\approx 210$  degree of forward facing horizontal arc of their visual field'
  - vertical range of the visual field in humans is around 150 degrees
  - some birds have complete/nearly complete 360 degree FOV
- **Aspect ratio:** relationship between its width and height

- expressed as (x,y)
- common aspect ratios: 5:4, 4:3, 16:10, 16:9
- Brief history
  - **2003**: most computer monitors had 4:3 aspect ratio, some had 5:4
  - **2003-2006**: 16:10 became common in laptops and standalone monitors
  - **2008**: industry moved from 4:3 and 16:10 to 19:9 as the standard ratio
  - **2010**: All monitors and laptops moved to 16:9 aspect ratio
  - **2011**: 16:9 reso of 1920\*1080 became popular among steam users
  - **2012**: resolution became 1366\*768

### Alpha Channel:

- **alpha compositing**: process of combining an image with a background to create the appearance of partial or full transparency
  - keep an associate matte for each element
  - In a 2D image element, which stores a color for each pixel, additional data is stored in the alpha channel with a value between 0 and 1
    - 0 means pixel does not have any coverage info and is transparent
    - 1 means the pixel is opaque because the geometry overlapped the pixel
  - one more number is required to store **alpha**
    - from (148,255,255) to (148,255,255,0)
      - first 3 numbers imply the color
      - last three imply the alpha
- if three primary colors share the same number, this color contains only brightness, it can only be black, white or gray
  - (0,0,0) is black
  - (255,255,255) is white
  - (100,100,100) is gray
- **premultiplied alpha**: if the alpha channel is used in an image, its common to alsp multiply the color by the alpha value
  - saves space

- **linear interpolation:** given two red points, the blue line is the linear interpolate between the points, and then value  $y$  at  $x$  may be found using this method

### Computer monitors:

- **computer monitors:** the size of a display is usually given by monitor manufacturers based on the diagonal
  - measure in unit inch
  - display devices: cathode ray tube (CRT), liquid crystal display (LCD), organic light-emitting diode (OLED)
    - **CRT:** old fashioned, vacuum tube containing an electron gun and phosphorescent screen used to view images
    - **LCD:** most common, has diffraction grating, crystal and backlight
    - **OLED:** monitor of the future, simple structure, self emissive

### Image Compression:

- **uncompressed image - raw file:** captured by a digital camera or scanner's sensors, this captures a high level of image detail, with large file sizes and lossless quality
  - direct image data means you start with a high-quality image that can be edited, converted and compressed in a non-destructive manner
- **lossy vs lossless**
  - lossless: preferred for archival purposes, for medical imaging, technical drawings, clip art, comics
  - lossy: suitable for natural images e.g. photographs in applications
- **lossless compression**
  - Run-length encoding (RLE) is a simple form of data compression where runs of data are stored as a single data value and count, rather than as the original run
    - example of RLE: W representing white and B representing black:  
WWWWWBWW
    - instead this can be compressed into 5W1B2W
  - Differential pulse-code modulation (DPCM) encodes the changes between consecutive samples of a signal rather than the signal's value directly

- reduces the bit rate
  - input can be an analog signal or digital signal
  - methods of encoding:
    - quantize the samples, output is the difference between the current and previous sample
    - quantize the difference between the current sample and output of a local decoder
  - color spaced is reduced to the most common colots, these selected colors are defined in a color palette stored within the mage harder
    - each pixel references the index of its corresponding color in the palette
    - this approach can be combined with dithering to minimize posterization artifacts
- **entropy encoding:**
- **Huffman coding:** separating the input into component symbols and replacing each with a code, uses variable length codes to represent different characters
    - shorter codes -> assigned to more frequently occuring characters and longer to less frequent ones, results in compressed data representation
    - optimal for minimizing the total number of bits used
  - **Arithmetic coding:** encoding the entire message into a single number, a fraction  $n$  where  $(0 \leq n \leq 1)$
- **chroma subsampling:** human eye perceives spatial changes of brightness more sharply than color, so this method averages/drops some of the chominance info in the image
- **transform coding:** most commonly used method, Fourier related transform such as the **discrete cosine transform (DCT)** is widely used
- wavelet transform is also used extensively, followed by quantization and entropy coding