



# IDX G9 Computer Science S

## Study Guide S1 Midterms

By Leona Cai, Edited by Doris Chu

**NOTE: This is an official document by Indexademics. Unless otherwise stated, this document may not be accredited to individuals or groups other than the club IDX, nor should this document be distributed, sold, or modified for personal use in any way.**

### **Contents:**

1. Computer Category and Programming Language
2. Programming Intro
3. Variables and Data Types
4. Expressions
5. List
6. For-Loop
7. For-Range
8. If Statement
9. Boolean Operators

## **1.1 Computer Category and Programming Language**

### The History of Computers

- 3000 B.C.: The **abacus**, used for addition, subtraction, division and multiplication, it can also extract square roots and cubic roots
- 1973: Xerox introduced Ethernet (wired internet), allowing computers to connect
- Various computer companies were established, including *Microsoft* (Bill Gates and Paul Allen, 1975) with the first home kit-built computer, and *Apple* (Steve Jobs and Steve Wozniak, 1976) with the first computer with a single circuit board
- 1999: Wi-Fi was invented, replacing wired Ethernet connections

### Categories of Computers

- **Special-Purpose Computers:** Designed for a particular function, executing the same stored set of instructions (EX. Microwave, washing machine etc.)
- **General-Purpose Computers:** Used for solving many different types of problems, available in a variety of sizes and capabilities.
  - **Microcomputers:** AKA personal computer (PC), can be placed on a desktop or carried from room to room
    - Size varies, from the smallest laptop computers/notebook computers to the largest type of microcomputer known as a workstation
  - **Mainframe Computers:** Powerhouse with massive memory and extremely rapid processing power, used for large businesses, scientific/military applications where computer needs to handle massive amounts of data or complicated processes
  - **Supercomputers:** Used for tasks requiring extremely rapid and complex calculations with hundreds of thousands of variable factors
    - Used for scientific research, weather prediction, aircraft design, nuclear weapons etc.

## Languages

- **Programming Languages:** Agreed upon format of symbols that allow a programmer to instruct a computer to perform certain predefined tasks
- **Machine Languages:** Natural language of a computer, and is the only language that a computer can directly use. Its instruction is a binary string of 0s and 1s.
- **Assembly Language:** Consists of English-like abbreviations, making them easier to understand. It uses language translators called **assemblers** to convert them to machine code.
- **High-level Languages:** Machine-independent, does not require programmers to know anything about the internal structure of the computer

## 1.2 Programming Intro

### Hardware and Software

- **Hardware:** Only understands the binary system
- **Software:** set of steps for instructions for computer hardware operations

### Programming Problems

- Define the problem -> Plan the solution -> Write the code -> Testing/Debugging the program
- **Interactive mode:** Start with >>>, runs one line at a time
- **Script mode:** Uses “.py” file, runs all lines you wrote at once
- **Indentation:** Indicates a block of code

## Math Operators

Operator	Operation	Example	Output
+	Addition	2+2	4
-	Subtraction	5-3	2
*	Multiplication	2*3	6
/	Division	10/2	5
**	Exponents	3**2	9

- Python follows the **PEMDAS** rule, so uses parentheses when needed

## print() function

- A value that is passed to a function call is an **argument**
- EX. print(“Hello World”), output: Hello World
- If it is a value, don’t use quotation marks. Use quotation marks for letters

## 1.3 Variables and Data Types

Operator “+” is used to **concatenate** two strings as the operation

- **input() function**
  - It will return a string type, and the user can input
    - EX. input(“What is your name”); output: What is your name; Then the user can input a name
- **Variables**
  - Containers for storing data values can store numerical or textual values
  - Rules for naming variables:
    - Can contain only letters, numbers, and underscores
    - Cannot start with a number
    - Spaces and **special characters** (-, !, @, #, %, ^, &, \*) are not allowed
    - Variables are **case sensitive**, meaning age, AGE, and Age are different

- Avoid using **reserved keywords**: EX. “True”, “False”, “or”, “not”, “and”, “if”
- **Camel Case**: makes compound names easier, EX. myList, listOfNumbers
  - Can contain only letters, numbers, and underscores
- When assigning values, use “=” operator
  - Multiple assignment: multiple variables in a single statement, EX. x=y=z=50, or a,b,c=5,10,15

## Data Types

- **Integer**: int(), converts a number/string into an integer
- **Float**: float(), approximations to real numbers, they are decimals
- **String**: str(), converts a number to a string

## 1.4 Expressions

Consists of values and operators so they always evaluate down to a single value

Importing Modules: from the standard library, contains related group of functions that can be embedded in your programs

- Math Modules
  - math.pi: on its own, it returns the first 15 digits of pi
  - math.ceil(x): returns an integer  $\geq x$  (EX math.ceil(2.4); output: 3)
  - math.floor(x): returns an integer  $\leq x$  (EX math.floor(2.4); output: 2)
  - math.sqrt(x): returns the square root of x (EX math.sqrt(9); output: 3)

## 1.5 List

A collection of items in a particular order, indicated by square brackets []

- Access an element in a list by its index: listName[index]. (EX. myList[3]; output: the fourth element in the list)
- len() function: returns the number of elements in a list
  - Index of a list starts at 0. (1<sup>st</sup> element's index is 0, 2<sup>nd</sup> element's index is 1, etc.)
  - len(myList), (assuming myList has 5 elements); output: 5
- lst.index(value) function: finds the index of an element

Action	Methods/Functions
--------	-------------------

Modifying an element	<b>listName[index of element you want to change]=(new value/string)</b> EX. myList[1]=4; myList now equals [1,4,3,4]
Adding an element	<b>append():</b> adds the new element to the end of a list EX. myList.append(5); myList now equals [1,4,3,4,5]
	<b>insert( , ):</b> insert (index,value) EX. myList.insert(2,6); myList now equals [1,4,6,4,5]
Removing an element	<b>del listName[index]:</b> removes the element of that index EX. del myList[1]; myList now equals [1,6,4,5]
	<b>remove():</b> removes the specific value, deletes the first occurrence of the value you specify EX. myList.remove(1); myList now equals [6,4,5]

## 1.6 For-Loop

- **split()** function: splits a string to a list
  - `str.split(x)` will remove every x from str and return a list of the leftover
- **for loop:** repeatedly perform the same task with each element in a list
  - `for variable in range` OR `for variable in myList`; enter the task you want to perform
  - iterate a block of statements several times
- **sum()** function: sum of the entire list

## 1.7 For-Range

- **range()** function/syntax: generates a sequence of numbers in that range
  - `for i in range(5); print(i)`; output: 0, 1, 2, 3, 4 (starts from 0, ends at the integer < 5)
  - `for I in range (2,6,2): (start, stop, step)`
    - output: 2, 4
    - if there isn't an end (2,6,-3), then it will return nothing
- **random numbers:** use module **random**. (import **random**)
  - **randint(a,b):** returns in integer in the range [a,b]
  - EX. `random.randint(1,5)`; output: 4

## 1.8 If Statement

- Boolean values: True or False
- Relational Operators

Operator	Description	Example	Output
<	Less than	2<3	True
>	Greater than	3>4	False
<=	Less than or equal to	3<=9	True
>=	Greater than or equal to	8>=7	True
==	equal	2==3	False
!=	Not equal to	2!=2	False

- **If Statement:** if condition: -> statements
  - The condition has to be a Boolean expression that evaluates to True or False
  - **If else:** if condition: statement 1; else: statement2
  - **If elif else:** if condition: statement 1; elif: statement 2; else: statement 3

## 1.9 Boolean Operators

- Boolean operators: evaluate the expressions down to a Boolean value
  - () > not > and > or: meaning the computer evaluates Boolean operators in this order
  - **and** operator truth table:
    - True and True: True
    - True and False: False / False and True: False
    - False and False: False
  - **or** operator truth table:
    - True or True: True
    - True or False: True / False or True: True
    - False and False: False
  - **not** operator truth table:
    - not True: False, not False: true
- Remainder(%): gives the remained of division (EX: 22%5=2)
- Integer division: floor value of a quotient produced by a division (EX: 1234//100=12)
- Precedence: \*\*(Exponents) > (\*, /, %, //) > (+ -) > (<=, <, >, >=, !=, ==) > (not, and, or)

## 1.10 Number System

### Decimal Number System

- denary (decimal) system: positional system that uses 10 digits (0,1,2,3,4,5,6,7,8,9) to represent numbers
  - **base-10**: the place value in a decimal number is always a power of 10
  - EG  $6352_{10}$ : if the base is omitted, it is assumed that the number is in the base-10 system

### Binary Number System

- It is the most widely used number system in computer science
- consists of only two digits: 0 and 1
  - each 0 or 1 is called a bit (lowercase b)
  - a group of eight bits is called a Byte and is usually abbreviated as an (uppercase B); used to express storage space
  - base-2: the place value in a binary number is always a power of 2
- $101110_2$ : the base number cannot be omitted the number system

decimal 1000	binary 1024
kilobyte	kibibyte
megabyte	mebibyte
gigabyte	gibibyte
terabyte	tebibyte
petabyte	pebibyte
exabyte	exbibyte
zettabyte	zebibyte
yottabyte	yobibyte

### Data Representation & Conversion

Take the number you want to convert, divide it by the binary number  $b$ , and the remainders (from bottom to top) form the number in  $b$  binary

### Hexadecimal Notation

1 2 3 4 5 6 7 8 9 A B C D E F

A=10; B=11; C=12; D=13; E=14; F=15

Dec	Bin	Hex	Dec	Bin	Hex
0	0000	0	8	1000	8
1	0001	1	9	1001	9
2	0010	2	10	1010	10
3	0011	3	11	1011	11
4	0100	4	12	1100	12
5	0101	5	13	1101	13
6	0110	6	14	1110	14
7	0111	7	15	1111	15

### 1.11 While-Loop

In situations where you don't know how many loop iterations to execute.

Given a condition, as long as that condition is true, it will execute the statement designed (in the indented code block); when the condition becomes false, the computer ends the loop and moves on to the next statement.

`+=` is called **augmented assignment operator**, EG `s=s+1` can be written as `s+=1`; this works for `+`, `-`, `*`, `/`, `//`, `%`

### 1.12 & 1.14 String Manipulation

In situations where you don't know how many loop iterations to execute.

Given a condition, as long as that condition is true, it will execute the statement designed (in the indented code block); when the condition becomes fa

#### **strip() function**

- `str.strip()`: returns a new string without any blanks (including space, tab and new lines)
- `str.strip(s)`: returns a new string with first and last "s" removed



- `lstrip()`: returns a new string without blank characters from the left end
- `rstrip()`: returns a new string without blank characters from the right end

### **join() function**

- `delimiter.join(list)`: This will take all of the strings in the list “list,” and join them with the delimiter
  - EG: delimiter is “,”, list=[“banana”, “apple”, “cherry”]; The output of the function “,”.join(list) will be: banana,apple,cherry
  - EG delimiter is “a”, list=[“banana”, “apple”, “cherry”]; The output of the function “a”.join(list) will be: bananaaappleacherry
- `delimiter.join(str)`: puts the delimiter between every character
  - EG if str is “hello”, the function: “,”.join(str) will give you “h,e,l,l,o”

### **split () function**

- `str.split(delimiter)`: splits the string based on the delimiter
  - EG if delimiter=e, str=”hello”, `str.split(“e”)` will give you: [“h”, ”llo”]
  - `str.split()`: this means the delimiter is blank characters (space, tab and new lines)

### **string methods**

- `str.isalnum()`: returns True if the characters in the string are letters of numbers (alphanumeric)
- `str.isdigit()`: returns True if all the characters are digits
- `str.isalpha()`: returns True if all the characters are alphabets/letters

## **1.15 Nested Loop**

A nested loop just means to put a loop within another loop, here there will be an inner loop and an outer loop. The outer loop is run first.

New line character: use ‘\n’

Used for 2D arrays, matrices, grids, printing patterns etc.

### **syntax**

```
for outer_variable in outer_sequence:
```

```
    for inner_variable in inner_sequence:
```