

ROAD-03-MANUFACTURING-SCALE-UP

ROAD-03: MANUFACTURING SCALE-UP STRATEGY

Carrington Storm Motors — Project AEGIS

From Lab Bench to Volume Production: Pilot Facility → Volume Plant → Global Supply Chain

Document Status: Investor-Grade Manufacturing Plan
Version: 1.0 — 15 July 2026
Classification: CONFIDENTIAL — Accredited Investor Eyes Only
Author: Mork, Director of Fabrication — Aegis Operations Command
Reviewers: Chester (Quality), Zirconia (Validation), Director Kairos Steele (Strategic Oversight)

EXECUTIVE SUMMARY

Carrington Storm Motors currently operates at laboratory and prototype scale: 50 g/day MXene production, 100 m/day BFRP pultrusion (batch), and individual product assembly at the CSMFAB El Segundo facility (8,000 sq ft). This document defines the manufacturing scale-up pathway through three phases: (I) Pilot Production Facility (2027-2028), (II) Volume Manufacturing Plant (2029-2030), and (III) Global Supply Chain Integration (2031+). The manufacturing strategy is organized around five core material platforms — MXene, BFRP composites, ceramics (ZrB₂-SiC, Si₃N₄, ZrO₂), geopolymer concrete, and piezoelectric elements — that feed all 50+ CSM products through shared manufacturing cells and a common BOM-REGISTRY.

PHASE I: PILOT PRODUCTION FACILITY (Q1 2027 — Q4 2028)

1.1 Facility Requirements

Location: El Segundo, California (adjacent to existing CSMFAB laboratory) or Riverside County (lower cost, larger footprint)
Total Area: 35,000 sq ft (Phase I)
Breakdown: | Zone | Area (sq ft) | Function | Equipment Cost | Infrastructure Cost | |—|—|—|—| | MXene Production Cleanroom (ISO 7) | 3,500 | Electrochemical etching, washing, drying, packaging | \$1.2M | \$850K | | BFRP Pultrusion Bay | 6,000 | 3 pultrusion lines, roving creel storage, resin mixing | \$2.1M | \$600K | | Ceramic Processing (ZrB₂-SiC, Si₃N₄, ZrO₂) | 4,500 | Flash sintering furnaces (×3), ball mills, spray dryers | \$1.8M | \$550K | | Aegis-C Panel Assembly (LOM line) | 5,500 | LOM tape casting, FSS photolithography, MXene spray coating, gasket assembly | \$3.4M | \$700K | | Aegis Home Product Assembly | 6,000 | 18-product assembly workstations, testing stations, packaging | \$1.5M | \$400K | | Phantom Robot Assembly | 3,500 | Clean assembly area, actuator calibration, EMI testing station | \$2.8M | \$350K | | Quality Control Lab | 2,500 | TEM cell (×2), universal test machine, environmental chambers, XPS/XRD, SEM | \$3.6M | \$500K | | Warehouse / Receiving | 3,500 | Raw materials, WIP, finished goods | \$180K | \$250K | | **TOTAL Phase I** | **35,000** | | **\$16.58M** | **\$4.20M** |

Total Phase I Facility CAPEX: \$20.78M

1.2 Workforce Plan — Phase I

Department	Headcount	Key Roles	Average Salary	Annual Cost
MXene Production	8	Chemical engineers (2), operators (5), QC technician (1)	\$78K	\$624K
BFRP Pultrusion	12	Composites engineers (2), operators (8), QC (2)	\$72K	\$864K
Ceramic Processing	10	Materials engineers (2), furnace operators (6), QC (2)	\$75K	\$750K
Aegis-C Panel Assembly	15	Manufacturing engineers (3), operators (10), QC (2)	\$68K	\$1.02M
Aegis Home Assembly	18	Assembly technicians (12), test technicians (4), supervisors (2)	\$62K	\$1.12M
Phantom Assembly	8	Robotics technicians (5), calibration engineers (2), supervisor (1)	\$82K	\$656K
Quality Control	12	Test engineers (4), NDT technicians (4), metrology (2), documentation (2)	\$78K	\$936K
Supply Chain / Logistics	6	Buyers (3), logistics coordinator (2),	\$68K	\$408K

		warehouse manager (1)		
Facilities / Maintenance	5	Maintenance technicians (4), facilities engineer (1)	\$65K	\$325K
TOTAL	95		\$72K avg	\$6.70M

Annual Workforce Cost Phase I: \$6.70M (fully loaded: \$8.38M with benefits, payroll tax, workers comp)

1.3 Phase I Production Capacity

Product	Annual Capacity (Phase I)	Unit Revenue	Annual Revenue Potential
MXene (kg)	3,600 (10 kg/day)	\$85/g	\$306K (internal transfer)
BFRP (linear m)	730,000 (2,000 m/day)	\$12/m	\$876K (internal transfer)
Aegis-C Panels (units)	18,250 (50/day)	\$850/panel	\$15.5M
Aegis Home Complete Packages	120 homes/year	\$95,000/home	\$11.4M
Phantom MK-1 Units	24 units/year	\$180K/unit	\$4.3M
Aegis Embark Products (8)	24,000 units/year	\$1,050 avg	\$25.2M
Infrastructure Products	3 substations, 5 bridges, 10 km pipeline	\$250K avg	\$4.5M
TOTAL Phase I Revenue			\$61.2M

PHASE II: VOLUME MANUFACTURING PLANT (Q1 2029 — Q4 2030)

2.1 Facility Requirements

Location: Riverside County, California (or Phoenix, AZ — lower cost alternative with solar energy advantage)
Total Area: 250,000 sq ft (Phase II)
Site Requirements: 25+ acres (room for Phase III expansion), rail access for bulk materials, >5 MW electrical service, industrial water recycling, solar farm (5 MW on adjacent land)

Zonal Breakdown Phase II: | Zone | Area (sq ft) | Equipment Cost | Infrastructure Cost | |—|—|—| | MXene Industrial Plant (3 shifts) | 25,000 | \$12.0M (electrochemical reactor array, DLE lithium co-product recovery, waste treatment) | \$5.5M | | BFRP Production (10 pultrusion lines) | 40,000 | \$6.5M | \$2.8M | | Ceramic Processing (expanded) | 30,000 | \$8.2M (flash sintering ×10, CVD for SiC/SiC, hot press ×5) | \$3.5M | | Aegis-C Panel Production (3 LOM lines) | 45,000 | \$9.5M | \$4.2M | | Aegis Home Assembly (3 parallel lines) | 50,000 | \$4.8M (automated panel placement, robotic wiring, conveyor system) | \$3.8M | | Phantom MK-2 Production Line | 25,000 | \$12.0M (actuator assembly robots, calibration stations, EMI test cells ×5) | \$3.2M | | Ascension Drone Production | 15,000 | \$4.5M (composite layup, battery integration, flight test range) | \$1.8M | | Protonic Transceiver Production | 10,000 | \$6.2M (H-FET cleanroom ISO 5, Nafion casting, BaZrO₃ sintering, assembly) | \$3.5M | | Central Quality Lab | 15,000 | \$8.5M (expanded TEM ×4, EMC chamber, shaker tables, environmental walk-in chambers) | \$4.0M | | Warehouse / Logistics Hub | 30,000 | \$2.2M (ASRS automated storage, robotic picking, dock doors ×20) | \$4.5M | | **TOTAL Phase II | 285,000 | \$74.4M | \$36.8M |**

Total Phase II CAPEX: \$111.2M

2.2 Workforce Plan — Phase II

Department	Phase I	Phase II Additions	Phase II Total	Annual Cost
MXene Production	8	+35	43	\$3.44M
BFRP Pultrusion	12	+48	60	\$4.50M
Ceramic Processing	10	+45	55	\$4.24M
Aegis-C Panel Production	15	+65	80	\$5.84M
Aegis Home Assembly	18	+82	100	\$6.80M
Phantom Assembly	8	+47	55	\$4.62M
Ascension Drone	0	+35	35	\$2.80M
Protonic Production	0	+45	45	\$3.96M
Quality Control	12	+48	60	\$5.04M
Supply Chain / Logistics	6	+24	30	\$2.16M
Facilities / Maintenance	5	+25	30	\$2.10M
Engineering / R&D	0	+85	85	\$8.16M
Admin / Management	0	+42	42	\$3.78M
TOTAL	95	+626	720	\$57.44M

Annual Workforce Cost Phase II: \$57.44M (fully loaded: \$71.8M)

2.3 Phase II Production Capacity

Product	Phase I Capacity	Phase II Capacity	Annual Revenue
		438,000 (1,200 kg/day; includes	

MXene (kg)	3,600	external sales)	\$14.0M (external sales @ \$32/g)
BFRP (m)	730,000	7.3M (20,000 m/day)	\$5.1M (external sales + internal)
Aegis-C Panels	18,250	182,500 (500/day)	\$146.0M
Aegis Home Packages	120	1,200 homes/year	\$114.0M
Phantom MK-2	24	250 units/year	\$23.8M (@ \$95K/unit)
Ascension Drones	0	500 units/year	\$14.0M (@ \$28K avg)
Aegis Embark	24,000	350,000 units/year	\$367.5M
Infrastructure Products	Misc	50 substations, 40 bridges, 100 km pipeline/year	\$28.5M
Protonic Transceivers	0	2,000 units/year	\$9.6M
TOTAL Phase II Revenue			\$722.5M

PHASE III: GLOBAL SUPPLY CHAIN (2031+)

3.1 Multi-Continent Manufacturing Footprint

By 2031, CSM will establish regional manufacturing centers to serve continental markets, reduce logistics costs, and mitigate geopolitical supply chain risk:

Location	Products	Annual Capacity	CAPEX	Rationale
El Segundo / Riverside, CA (HQ)	All core materials, Aegis Home (West Coast), Phantom, R&D	Phase II full capacity	Already capitalized	HQ proximity, materials science talent density, California green building mandate alignment
Houston, TX	Aegis Home (Gulf/Southeast), Infrastructure, Geopolymer	800 homes/year, 30 infrastructure projects/year	\$45M	Gulf Coast hurricane + EMP dual threat market, low energy costs, port access for export
Rotterdam, Netherlands	Aegis Home (EU), Charlemagne Fleet retrofit, Aegis Embark (EU automotive)	500 homes/year, 6 vessels/year, 150K Embark units	\$68M	EU Green Deal alignment, Charlemagne cruise fleet proximity, automotive OEM cluster (Germany)
Singapore / Yokohama	Protonic transceivers, Ascension drones, Phantom (APAC), Charlemagne (APAC cruise lines)	1K protonic units, 500 drones, 100 Phantoms, 3 vessels/year	\$52M	APAC cruise fleet concentration, semiconductor talent for protonic fabrication, typhoon/tsunami dual threat market
Dubai / Abu Dhabi	Aegis Home (MENA), Infrastructure (solar farm hardening, desalination plant protection)	300 homes/year, 15 infrastructure projects/year	\$38M	Sovereign wealth fund partnership potential, solar EMP threat awareness, construction boom

Total Phase III CAPEX: \$203M (phased over 2031-2033)

3.2 Vertical Integration Strategy — Make vs. Buy Analysis

Component / Material	Make	Buy	Rationale
MXene Ti ₃ C ₂ T _x	✓		Core IP; proprietary fluoride-free process; quality control critical for EMI performance; high margin
MAX Phase Ti ₃ AlC ₂ (precursor)		✓	Commodity ceramic powder; 3 qualified suppliers; Drexel, 3M, Materion
Basalt Fiber Roving		✓	Commodity; 5+ global suppliers (Technobasalt, Basaltex, Mafic); low differentiation
Elium Thermoplastic Resin		✓	Arkema proprietary; single-source risk mitigated by long-term supply agreement
ZrB ₂ -SiC Composite Powder	✓		Proprietary formulation (70/30 ratio), flash sintering process IP, high value-add

Si ₃ N ₄ Ceramic Bearings	✓		Proprietary geometry for Phantom actuators; tight tolerance requirements not met by off-shelf
YInMn Blue Pigment	✓		Licensed from Oregon State; proprietary calcination process; core brand identity color
Geopolymer Binder (fly ash/slag blend)		✓	Regional sourcing (fly ash from coal plants, slag from steel mills); low-cost commodity; mix design is IP
KNbO ₃ -BaTiO ₃ Piezo Elements	✓		Proprietary composition (d ₃₃ =285 pC/N target); lead-free formulation; core to multiple products
PMMA POF (Plastic Optical Fiber)		✓	Mitsubishi / Toray commodity; MXene coating is CSM value-add
LiFePO ₄ Battery Cells		✓	Commodity; CATL / BYD supply; CSM value-add is GIC-hardened BMS and ZrO ₂ enclosure
Samarium-Cobalt Magnets		✓	Specialty magnetic material; Arnold Magnetic / Vacuumschmelze supply
LORD MRF-140CG Fluid		✓	LORD Corporation (Parker Hannifin) proprietary; sole source, long-term supply agreement
PEEK CF40 Stock		✓	Victrex / Solvay commodity; CSM machines to final shape
Polyimide-Silica Aerogel		✓	Aspen Aerogels / Cabot supply; CSM integrates into product assemblies
Nafion 115 Membrane		✓	Chemours (DuPont spin-off) proprietary; single source — CSM developing BaZrO ₃ solid-state alternative for supply chain resilience

Key Insight: CSM makes the 6 core material platforms where proprietary IP creates competitive moat (MXene, ZrB₂-SiC, Si₃N₄ bearings, YInMn Blue, KNbO₃-BaTiO₃ piezoelectrics, MXene EMI coating process). All other materials are purchased as commodities or under long-term supply agreements. The “make” materials represent approximately 35% of product COGS but 80% of competitive differentiation.

SUPPLY CHAIN RISK ASSESSMENT & MITIGATION

Critical Material Risk Register

Material	Risk Level	Risk Factor	Probability	Impact	Mitigation Strategy	Mitigation Cost
MXene Precursors (Ti₃AlC₂ MAX Phase)	HIGH	Single qualified supplier (Drexel Nanomaterials); research-grade pricing (\$250/g)	35% supply disruption	CRITICAL — stops ALL product lines	Qualify 3 suppliers (Drexel, Materion, Chinese Academy of Sciences); invest \$2M in supplier capacity expansion; develop in-house MAX phase synthesis as backup	\$3.5M
Basalt Fiber Roving	LOW	Multiple global suppliers; mature industry (construction rebar market)	10%	MODERATE — price volatility	Long-term contracts with 3 suppliers; strategic 6-month inventory buffer; potential in-house spinning if required (high	\$500K

Elium Thermoplastic Resin	MEDIUM	Arkema sole source; novel chemistry with limited production capacity	25% supply constraint	HIGH — BFRP pultrusion line dependent	CAPEX, long lead time — not preferred) Long-term supply agreement with minimum volume commitment; invest \$1.5M in Arkema production line capacity; qualify epoxy or polyester backup resin (reduced performance but functional)	\$2.0M
CNT Feedstock (carbon nanotubes)	MEDIUM	Price volatility; used in limited quantities (CNT-polymer conductivity for BFRP)	20% price spike	LOW — minor component by weight	Multi-supplier qualification (OCSiAl, Nanocyl, Cabot); substitute graphene nanoplatelets at 1.5× cost penalty	\$300K
BFRP Resin (general)	MEDIUM	Oil-price-linked; petrochemical feedstock	30% price volatility	MODERATE — 15% of product COGS	Bio-based epoxy alternative (Entropy Resins) qualification; forward purchasing during low-price periods	\$800K
Ceramic Powders (ZrO₂, Si₃N₄, B₄C)	MEDIUM	Chinese export controls on rare earth and advanced ceramics	20%	HIGH — Phantom actuator bearings, Aegis-C outer layer	Diversify to Japanese (Tosoh, Kyocera), European (Saint-Gobain), and domestic (CoorsTek) suppliers; 12-month strategic stockpile of critical grades	\$4.2M
YInMn Blue Raw Materials (Y₂O₃, In₂O₃, MnO₂)	MEDIUM	Indium supply (ITO market competition, Chinese dominance)	25% price increase	MODERATE — aesthetic component, not functional	Recover indium from end-of-life panels via Phoenix Protocol (D2EHPA solvent extraction); develop reduced-indium formulation; YFeO ₃ alternative pigment under research	\$1.8M
Samarium-Cobalt Magnets	MEDIUM	Cobalt supply chain (DRC geopolitical risk, child labor concerns)	20% supply disruption	HIGH — Phantom joint motors dependent	Qualify ferrite magnet backup (reduced performance, 40% torque reduction, but functional); cobalt sourcing from responsible mines (Glencore KCC with blockchain traceability); SmCo recycling from end-of-life motors	\$2.5M
		Chemours sole source;			Accelerate BaZrO ₃ solid-state proton conductor development (eliminates Nafion	

Nafion 115 Membrane	HIGH	discontinued product lines risk; expensive (\$850/m ²)	35% supply disruption	HIGH — Protonic H-FET dependent	dependency); identify surplus Nafion inventory sources; develop sulfonated PEEK (s-PEEK) alternative membrane	\$3.2M
KNbO₃-BaTiO₃ Raw Materials (Nb₂O₅, BaCO₃, TiO₂)	LOW	Niobium primarily from Brazil (CBMM) and Canada (Niobec); stable supply chains	10%	LOW — geographically diversified	Long-term contracts with CBMM and Niobec; strategic 6-month inventory for lead time buffer	\$400K

Total Supply Chain Risk Mitigation Budget: \$19.2M (over 5 years)

Geopolitical Risk Assessment

Risk	Countries Affected	CSM Exposure	Mitigation
US-China Trade War / Export Controls	China → Global advanced ceramics, rare earths	25% of ceramic powder supply	Diversify to Japan, EU, domestic suppliers (see above)
Taiwan Strait Contingency	Taiwan → Global semiconductor supply chain	10% of electronics components (GaN RF, MCUs for Phantom, drone)	Qualify non-Taiwan semiconductor sources (TI, STMicro, Infineon); increase inventory buffer
EU Carbon Border Adjustment Mechanism (CBAM)	Import to EU	Aegis Home, Aegis Embark exported to EU subject to carbon tariff	Geopolymer concrete (80% CO ₂ reduction) may qualify for exemption; document carbon intensity of all products
US Defense Production Act (DPA) Invocation	US domestic	Potential positive: CSM products designated critical infrastructure, government funding	Pre-position for DPA Title III funding for MXene, BFRP, ceramic production as “critical materials for electromagnetic resilience”

QUALITY CONTROL SYSTEMS — MANUFACTURING SCALE

Incoming Inspection Protocol

Material	Test Method	Frequency	Accept/Reject Criteria	Equipment
MAX Phase Ti ₃ AlC ₂	XRD phase purity, particle size (laser diffraction)	Every lot (500 kg)	>98% MAX phase, d50 = 10–50 μm	XRD, Malvern Mastersizer
Basalt Fiber Roving	Tensile strength (ASTM D2343), tex, sizing content	Every spool (20 kg)	>2,800 MPa tensile, tex ±5%, sizing 0.5–1.5%	Universal test machine, analytical balance
Elium Resin	Viscosity (Brookfield), reactivity (DSC), water content (Karl Fischer)	Every drum (200 L)	Viscosity 80–120 cP at 25°C, exotherm within spec, H ₂ O <200 ppm	Rheometer, DSC, Karl Fischer titrator
ZrB ₂ Powder	XRD, particle size, oxygen content (LECO)	Every lot (100 kg)	>97% ZrB ₂ , d50 = 1–5 μm, O ₂ <1.5 wt%	XRD, LECO analyzer
MXene In-Process (after etching)	XRD (peak shift), XPS (surface terminations), 4-point probe (sheet resistance)	Every batch (500 g)	(002) peak shift >1.5°, F-termination <5 at%, O-termination >60 at%, R _{sheet} <5 Ω/sq	XRD, XPS, 4-point probe

In-Process Quality Control

Process Step	Inspection	Frequency	Target	Corrective Action
MXene Spray Coating	Thickness (profilometer), adhesion (cross-hatch ASTM D3359), SE (TEM cell sample)	Every 10th panel	45 ± 2 μm, 5B adhesion, SE >90 dB at 10 GHz	Reject panel, recalibrate spray parameters
BFRP Pultrusion	Ultrasonic C-scan (void content), dimensional (laser micrometer), burn-off (fiber volume fraction)	Continuous (C-scan every 10 m)	Voids <2%, dimension ±0.2 mm, Vf = 58–62%	Flag out-of-spec section, cut and scrap, adjust pull speed / die temperature

Flash Sintering (ZrB ₂ -SiC)	Density (Archimedes), hardness (Vickers), XRD (phase)	Every furnace run (20 plates)	Density >98% theoretical, HV10 >22 GPa, phase purity >99%	Adjust sintering parameters (current, time, pressure)
Aegis-C Panel Layer Stack	Layer registration (vision system), thickness per layer (laser), SE per layer (probe)	Every panel	Registration ±0.5 mm, thickness per spec, SE per layer within tolerance	Reject panel, adjust LOM alignment
Phantom Actuator Assembly	Torque output, backlash, electrical resistance (motor-to-chassis)	Every actuator	Torque ±5% of spec, backlash <0.05°, R >10 ⁸ Ω	Adjust assembly, replace bearings, rework or scrap

Final Inspection

Product	Test	Equipment	Acceptance Criteria	Sample Rate
Aegis-C Panel	Full-band SE (1 kHz-10 GHz), visual (AOI), dimensional (CMM)	TEM cell, AOI camera, CMM	SE >148 dB full band, no visible defects, dim ±2 mm	1 per 100 panels (SE), 100% visual and dimensional
Phantom MK-1/MK-2	5-phase CSMTTest protocol	TEM cell, shaker table, thermal chamber	All 5 phases passed, I _{GIC} <10 ⁻⁷ A	100% (every unit)
Aegis Embark Product	Vibration attenuation at target frequency, material integrity (visual, functional)	Vibration test rig, function test	Attenuation >90% of spec, zero functional defects	1 per lot (500 units) for vibration, 100% functional
Protonic Transceiver	Signal transmission (50 baud text, 3.4 kHz voice), range (1 km test), EMI immunity	Test range, TEM cell	Bit error rate <10 ⁻⁶ at 50 baud, voice intelligibility >90%, no EMI degradation	100% (every unit)
Infrastructure Product (Bearing Pad)	Dielectric withstand (ASTM D149), compression (ASTM D695)	Hipot tester, compression tester	>50 kV/mm dielectric, >100 MPa compression	Every unit

Calibration Program

Equipment	Calibration Standard	Interval	External Lab
TEM Cell	IEEE 299 / MIL-STD-188-125 field probe	6 months	NIST-traceable calibration lab
Universal Test Machine	ASTM E4 Class 1	12 months	Instron / MTS certified service
Environmental Chamber	NIST-traceable thermocouple, RH sensor	6 months	In-house with certified references
XRD	NIST SRM 640e (silicon powder)	3 months	In-house standard
XPS	Sputter-cleaned Au, Ag, Cu reference	Monthly	In-house standard
CMM (Coordinate Measuring Machine)	ISO 10360-2	12 months	OEM certified service
Multimeter / LCR Meter	Fluke / Keysight calibration	12 months	Accredited cal lab
4-Point Probe	NIST SRM thin-film resistivity standard	6 months	In-house with NIST reference

CAPITAL EXPENDITURE PROJECTIONS — 5-YEAR TOTAL

Year	Phase I	Phase II	Phase III	Maintenance CAPEX	Total CAPEX
Q3-Q4 2026	\$14.5M (initial lab scale-up, Phase I startup)	—	—	\$0.2M	\$14.7M
2027	\$20.8M (Phase I facility)	—	—	\$0.5M	\$21.3M
2028	\$12.1M (Phase I completion, Phase II site acquisition)	\$5.0M (Phase II design/permitting)	—	\$1.2M	\$18.3M
2029	—	\$68.3M (Phase II construction, equipment)	\$8.0M (Phase III site scouting, initial permitting)	\$2.5M	\$78.8M
2030	—	\$42.9M (Phase II completion)	\$28.0M (Houston + Rotterdam construction start) \$95.0M (Rotterdam)	\$4.0M	\$74.9M

2031	—	—	+ Singapore + Dubai construction)	\$6.0M	\$101.0M
2032	—	—	\$72.0M (Phase III completion)	\$8.0M	\$80.0M
5-Year Total (Q3 2026–2031)	\$47.4M	\$111.2M	\$95.0M	\$8.4M	\$262.0M
Total Program (to 2032)	\$47.4M	\$111.2M	\$203.0M	\$16.4M	\$378.0M

MANUFACTURING COST CURVE — LEARNING CURVE MODEL

CSM manufacturing costs will decrease following Wright’s Law (cost reduction with cumulative production volume):

Product	Phase I Unit Cost	Phase II Unit Cost	Phase III Unit Cost	Learning Rate	Cumulative Volume at TRL 9
Aegis-C Panel (\$/panel)	\$850	\$560	420 82/home)	\$95,000	\$72,000
Aegis Embark (avg \$/unit)	\$1,050	\$720	480 84/g — external sale)	\$85	\$32

Cross-Pollination Savings: Per CSMFAB BOM-REGISTRY, shared materials across product lines yield 18–34% cost savings through consolidated purchasing, shared tooling, and common process development. The BOM cross-pollination pairs (16 identified to date) will be continuously augmented as new products enter the registry.

MANUFACTURING RISK REGISTER

Risk	Probability	Impact	Mitigation	Contingency
Facility construction delay (permitting)	HIGH (40%)	6–12 month schedule slip	Early engagement with planning departments; parallel site preparation; pre-permitted industrial park locations	Phased occupancy — begin production in completed zones while construction continues
Key equipment lead time (flash sintering furnace: 12 months, TEM cell: 9 months)	MEDIUM (30%)	Schedule slip if not ordered early	Place long-lead equipment orders in Q4 2026 (12–18 months before Phase II need); pay premiums for accelerated delivery	Rental equipment bridging; third-party toll manufacturing
Workforce shortage (skilled technicians, composites, ceramics)	HIGH (35%)	Production rate below plan	Partnership with community colleges and trade schools for CSM-specific certification programs; competitive compensation; relocation packages	Automation acceleration to reduce labor dependency; cross-training from Phase I workforce
MXene production yield below target	MEDIUM (25%)	Cost overrun, supply constraint	Continuous process improvement team; statistical process control from Day 1; parallel R&D on yield enhancement	Stockpile precursor MAX phase; accept higher cost during yield ramp (priced into Phase I financial model)
Energy cost volatility (electricity for furnaces, cleanroom)	MEDIUM (30%)	Operating cost overrun	On-site solar farm (5 MW Phase II, expandable); power purchase agreement with fixed-rate renewable energy; energy efficiency as design criterion for all equipment	Pass-through pricing to customers via energy surcharge (less competitive)
Single-source supplier failure	LOW (15%) per supplier	Production stoppage if critical single-source	Multi-source qualification for all critical materials (see Section 3.2); strategic inventory buffer (3–6 months for single-source items)	Expedited qualification of backup supplier; accept performance/cost penalty

SUSTAINABLE MANUFACTURING COMMITMENTS

Metric	Phase I Target	Phase II Target	Phase III Target	Industry Baseline
Energy Intensity (kWh/\$ revenue)	0.85	0.52	0.35	1.2 (advanced manufacturing avg)
Water Recycling Rate	85%	92%	95%	30% (industry avg)
Renewable Energy Share	40% (grid + on-site solar)	75%	100%	15% (US manufacturing avg)
Hazardous Waste (kg/Mrevenue) 120 45 20 300(chemicalmanufacturing) CarbonIntensity(tCO ₂ e/M 28 revenue)	12	5		65 (construction materials)
Circular Economy — Material Recovery	>90% MXene recovery from scrap (NaOH dissolution)	>95% all CSM materials recoverable	Closed loop: 100% of CSM products designed for disassembly and material recovery	<10% (industry avg)

“Manufacturing scale-up is not a procurement exercise. It is a system design problem. Every machine, every workstation, every quality check, every supplier relationship must be architected with the same rigor as the Dielectric Citadel itself. The BOM-REGISTRY is the nervous system. The TEM cell is the immune system. The cross-pollination pairs are the circulatory system — shared blood between product lines. When the Sun speaks, the factory floor must already be humming, because the shields must be in the field before the storm arrives.” — Mork, Director of Fabrication

Document generated 2026-07-15. CAPEX estimates ±25% at P50 confidence for Phase I (well-defined equipment), ±35% for Phase II (conceptual design), ±50% for Phase III (strategic planning). All workforce costs based on Southern California labor market (2026 rates, 3.5% annual escalation assumed). Supply chain risk assessments updated quarterly via CSMFAB BOM-REGISTRY CI pipeline.