SC2006 LAB 4

Software Testing Report

Black-box equivalence-class and boundary-value testing, plus white-box basis-path testing

Work product	Test Cases and Testing Results
Prepared by	Group 1 - Software Testing
System	Group Scheduling Application
Target code	feature/production-pilot tree at 26cb622
Execution date	7 November 2026 (Asia/Singapore)
Result	29/29 assessment tests passed

Submission scope

This report satisfies Lab 4 Manual sections 3.2.1-3.2.4. It tests one important control boundary using equivalence classes and boundary values, tests two complex methods using basis paths, minimises redundant inputs, and records input, expected output, actual output, and pass/fail results.

1 Executive Summary

Black-box testing treats the recommendation control boundary as a sealed unit: tests provide complete recommendation requests and inspect only public results or validation errors. White-box testing reads the method structure, draws its control-flow graph, calculates cyclomatic complexity, and executes a basis set of independent paths.

All 29 assessment-focused automated tests passed. The complete backend regression suite passed 293 tests; all 21 frontend tests, lint, and the production build also passed. No production behaviour was changed for this work product.

Selected test subjects

Technique	Selected unit	Reason for selection
Black-box	RecommendationEngine.generate()	Core UC-09/UC-10 control boundary; validates the request and coordinates timeslots, venues, routing, feasibility, scoring, and ranking.
White-box 1	pre_routing_exclusion()	Implements FR-D1, FR-D4, and FR-D5 with ordered feasibility decisions before external routing.
White-box 2	_ParticipantAvailability.status_for()	Implements four distinct attendance states and the BUSY-overrides-AVAILABLE rule.

Environment and evidence

Item	Value
Language/runtime	Python 3.13.5
Test framework	pytest 8.3.5
Assessment run	29 passed, 0 failed, 0 errors
Full backend regression	293 passed; one dependency deprecation warning
Frontend verification	21 tests passed; lint passed; production build passed
External routing	Deterministic test double at provider port; all application logic remains real

2 Black-box Test Design

The control boundary is tested without using its internal branch structure. Inputs were partitioned by externally observable behaviour. Boundary values use the nearest invalid value and each valid endpoint where numeric limits exist.

2.1 Equivalence classes

Input characteristic	Equivalence classes	Representative cases
Session duration	Invalid low: <15; valid: 15-480; invalid high: >480	BB-DUR-01..04
Attendance outcome	Threshold met; requested threshold missed but best>=2; no two-person group	BB-THR-01..03
Venue compatibility	At least one supporting venue; no supporting venue	BB-THR-01, BB-VEN-01
Participant locations	At least one active valid origin; no valid origin	BB-THR-01, BB-LOC-01
Routing provider	Available duration; explicitly unavailable; exception/error	BB-JRN-01, BB-RTE-01..02
Individual journey	At or below 60-minute cap; above cap	BB-JRN-01..02
Attendance weight	Invalid low: <0; valid: 0-100; invalid high: >100	BB-WGT-01..04

2.2 Boundary-value analysis

Boundary	Values selected	Expected behaviour	Cases
Duration minimum 15	14, 15	14 rejected; 15 accepted	BB-DUR-01..02
Duration maximum 480	480, 481	480 accepted; 481 rejected	BB-DUR-03..04
Weight minimum 0	-1, 0	-1 rejected; 0 accepted	BB-WGT-03, BB-WGT-01
Weight maximum 100	100, 101	100 accepted; 101 rejected	BB-WGT-02, BB-WGT-04
Journey cap 60	60, 61	60 retained; 61 excluded	BB-JRN-01..02

2.3 Minimisation rationale

The test set uses one representative for each non-boundary partition and the adjacent values around every numeric boundary. Cases deliberately cover several compatible conditions at once. For example, BB-THR-01 also supplies a valid venue, valid locations, successful routing, and a valid mid-range weight. Additional combinations that would repeat the same observable class were omitted.

3 Black-box Test Cases and Results

Case	Req.	Test input / precondition	Expected output	Actual output	Result
BB-DUR-01	FR-A1.1	duration=14 min	Reject below 15	ValueError: duration must be 15 to 480 minutes (FR-A1.1)	PASS
BB-DUR-02	FR-A1.1	duration=15 min	Accept minimum	RunStatus.OK; ranked options returned	PASS
BB-DUR-03	FR-A1.1	duration=480 min	Accept maximum	RunStatus.OK; ranked options returned	PASS
BB-DUR-04	FR-A1.1	duration=481 min	Reject above 480	ValueError: duration must be 15 to 480 minutes (FR-A1.1)	PASS
BB-THR-01	FR-D1 / UC-09	2 overlap; threshold=2	OK with two attendees	RunStatus.OK; all ranked options have attendee_count=2	PASS
BB-THR-02	UC-09 recovery	best=2; requested=3	Label best-available fallback	BEST_AVAILABLE_BELOW_THRESHOLD; two-attendee options; warning names 3	PASS
BB-THR-03	FR-D1 / UC-09	no overlap of 2; threshold=2	No eligible timeslot; no routing	NO_TIMESLOT_MEETS_THRESHOLD; 0 combinations; 0 routing calls	PASS
BB-VEN-01	FR-C3	activity=badminton; venue=football	No supporting venue	NO_SUPPORTING_VENUES; no ranked options	PASS
BB-LOC-01	FR-C4 / NFR-3	all locations invalid/unavailable	No centroid; no routing	NO_VALID_LOCATIONS; no ranked options; 0 routing calls	PASS
BB-RTE-01	NFR-3 / NFR-8	provider UNAVAILABLE; minutes=None	Keep data unavailable; never invent 0	All combinations DATA_UNAVAILABLE; all minutes=None; no ranking	PASS
BB-RTE-02	NFR-3	provider raises RuntimeError	Contain error and continue safely	All travel statuses ERROR; all combinations DATA_UNAVAILABLE	PASS
BB-JRN-01	FR-D3	journey=60 min; cap=60	Keep boundary value	RunStatus.OK; ranked options; limit flags False	PASS
BB-JRN-02	FR-D3	journey=61 min; cap=60	Exclude above cap	No ranked options; every reason JOURNEY_LIMIT	PASS
BB-WGT-01	FR-D9	attendance weight=0%	Accept minimum	RunStatus.OK; reported weight=0; ranked options returned	PASS
BB-WGT-02	FR-D9	attendance weight=100%	Accept maximum	RunStatus.OK; reported weight=100; ranked options returned	PASS
BB-WGT-03	FR-D9	attendance weight=-1%	Reject below 0	ValueError: attendance weight must be between 0 and 100	PASS
BB-WGT-04	FR-D9	attendance weight=101%	Reject above 100	ValueError: attendance weight must be between 0 and 100	PASS

Evidence: every row above corresponds to one passing pytest function with the same case ID. The JUnit result contained 17 black-box cases, 0 failures, and 0 errors.

4 White-box Method 1: Pre-routing Exclusion

This method applies feasibility rules in priority order before any routing request: the session threshold (FR-D1), sports-facility minimum group size (FR-D4), and sports-facility booking lead time (FR-D5). The compound minimum-group expression is split into two short-circuit decisions in the control-flow graph.

4.1 Source excerpt

```
20  def pre_routing_exclusion(
21      combo: Combination,
22      minimum_attendee_threshold: int,
23      now: datetime,
24  ) -> ExclusionReason | None:
25      """FR-D1, FR-D4 and FR-D5, in that order. Returns the first reason that applies."""
26      count = combo.attendee_count
27      venue = combo.venue
28
29      # FR-D1: attendance below the Session's Minimum-Attendee Threshold.
30      if count < minimum_attendee_threshold:
31          return ExclusionReason.BELOW_THRESHOLD
32
33      if venue.category is VenueCategory.SPORTS_FACILITY:
34          # FR-D4: attendance below the Venue's minimum group size.
35          if venue.min_group_size is not None and count < venue.min_group_size:
36              return ExclusionReason.GROUP_SIZE
37          # FR-D5: Timeslot falls inside the Venue's required advance-booking window,
38          # i.e. it starts sooner than the Venue's minimum booking lead time.
39          if venue.advance_booking_lead_minutes:
40              earliest_bookable = now + timedelta(minutes=venue.advance_booking_lead_minutes)
41              if combo.timeslot.start < earliest_bookable:
42                  return ExclusionReason.BOOKING_LEAD_TIME
43
44      return None
```

4.2 Control-flow graph



Figure 1. Control-flow graph for pre_routing_exclusion(). Node numbering is identical to the DOT source committed with the tests.

4.3 Cyclomatic complexity

Calculation	Value
Predicate method	6 decision nodes + 1 = 7
Graph method	E - N + 2 = 18 - 13 + 2 = 7
Required independent paths	7

4.4 Independent paths and executed results

Case	Independent node path	Input	Expected	Actual	Result
WB-PR-01	N1-N2(T)-N3-N13	count=2, threshold=3	BELOW_THRESHOLD	BELOW_THRESHOLD	PASS
WB-PR-02	N1-N2(F)-N4(F)-N12-N13	park; count=threshold=3	None	None	PASS
WB-PR-03	N1-N2(F)-N4(T)-N5(T)-N6(T)-N7-N13	sports; count=3; venue min=4	GROUP_SIZE	GROUP_SIZE	PASS
WB-PR-04	N1-N2(F)-N4(T)-N5(F)-N8(F)-N12-N13	sports; no min; no lead	None	None	PASS
WB-PR-05	N1-N2(F)-N4(T)-N5(T)-N6(F)-N8(F)-N12-N13	sports; count=min=4; no lead	None	None	PASS
WB-PR-06	N1-N2(F)-N4(T)-N5(T)-N6(F)-N8(T)-N9-N10(T)-N11-N13	24h lead; start only 23h away	BOOKING_LEAD_TIME	BOOKING_LEAD_TIME	PASS
WB-PR-07	N1-N2(F)-N4(T)-N5(T)-N6(F)-N8(T)-N9-N10(F)-N12-N13	24h lead; start exactly 24h away	None	None	PASS

5 White-box Method 2: Participant Attendance Status

This method preserves four distinct participant states. A missing response and a withdrawn response are returned before interval processing. For an active response, any BUSY overlap overrides AVAILABLE time; otherwise the slot must be fully contained in an AVAILABLE block.

5.1 Source excerpt

```
111      def status_for(self, start: datetime, end: datetime) -> AttendanceStatus:
112          p = self.participant
113          if p.record_status is None:
114              return AttendanceStatus.NO_RESPONSE
115          if p.record_status is RecordStatus.WITHDRAWN:
116              return AttendanceStatus.WITHDRAWN
117          # A BUSY block (e.g. imported from Google Calendar, FR-B8) that overlaps
118          # any part of the slot makes the Participant unavailable for it.
119          if any(bs < end and start < be for bs, be in self.busy):
120              return AttendanceStatus.UNAVAILABLE
121          # The slot must lie wholly inside one merged AVAILABLE block.
122          if any(as_ <= start and end <= ae for as_, ae in self.available):
123              return AttendanceStatus.AVAILABLE
124          return AttendanceStatus.UNAVAILABLE
```

5.2 Control-flow graph



Figure 2. Application-level CFG for _ParticipantAvailability.status_for(). Each any(...) result is one boolean decision; Python iterator internals are outside this graph's abstraction boundary.

5.3 Cyclomatic complexity

Calculation	Value
Predicate method	4 decision nodes + 1 = 5
Graph method	E - N + 2 = 14 - 11 + 2 = 5
Required independent paths	5

5.4 Independent paths and executed results

Case	Independent node path	Input	Expected	Actual	Result
WB-PA-01	N1-N2(T)-N3-N11	record_status=None	NO_RESPONSE	NO_RESPONSE	PASS
WB-PA-02	N1-N2(F)-N4(T)-N5-N11	record_status=WITHDRAWN	WITHDRAWN	WITHDRAWN	PASS
WB-PA-03	N1-N2(F)-N4(F)-N6(T)-N7-N11	available covers slot; BUSY overlaps	UNAVAILABLE	UNAVAILABLE	PASS
WB-PA-04	N1-N2(F)-N4(F)-N6(F)-N8(T)-N9-N11	slot fully inside AVAILABLE	AVAILABLE	AVAILABLE	PASS
WB-PA-05	N1-N2(F)-N4(F)-N6(F)-N8(F)-N10-N11	AVAILABLE ends 1 min early	UNAVAILABLE	UNAVAILABLE	PASS

6 Execution Evidence and Cross-check

Verification	Observed result	Status
Lab 4 black-box tests	17 passed, 0 failed, 0 errors	PASS
Lab 4 white-box tests	12 passed, 0 failed, 0 errors	PASS
Combined Lab 4 JUnit run	29 passed, 0 failed, 0 errors	PASS
Full backend regression	293 passed; 1 third-party deprecation warning	PASS
Frontend unit/UI tests	21 passed	PASS
Frontend lint	oxlint exit code 0	PASS
Frontend production build	152 modules transformed; build exit code 0	PASS

6.1 Manual compliance matrix

Manual requirement	Evidence in this report	Status
3.2.1: one important control class	RecommendationEngine.generate(); Sections 2-3	Met
3.2.1: equivalence classes	Section 2.1 and BB test rows	Met
3.2.1: boundary values	Section 2.2; 14/15, 480/481, -1/0, 100/101, 60/61	Met
3.2.2: two complex methods	Sections 4 and 5	Met
3.2.2: basis-path testing	Two CFGs, two complexity calculations, 12 path cases	Met
3.2.3: minimise cases	One representative per partition plus boundary neighbours; Section 2.3	Met
3.2.4: execute and document	Every row has input, expected, actual, and result; Section 6	Met

6.2 Consistency checks

1. All 29 report case IDs exactly match the 29 JUnit test names.
2. Every equivalence class and boundary in Section 2 maps to at least one executed case.
3. The first CFG has N=13 and E=18; both formulas give V(G)=7; seven independent paths were executed.
4. The second CFG has N=11 and E=14; both formulas give V(G)=5; five independent paths were executed.
5. Actual outputs are literal observations asserted by the final passing tests, not restatements of expected output.
6. No secrets, access tokens, credentials, or personal availability data appear in this report.

7 Limitations and Conclusion

7.1 Limitations

The black-box control tests use a deterministic router at the external provider port so that boundary outcomes are reproducible and do not depend on OneMap availability. This is appropriate for unit-level control-class testing but does not replace the separate deployed smoke test of Google authentication, OneMap, PostgreSQL, and Render. The report also uses an application-level CFG: the internal iteration performed by Python's any(...) is treated as part of expression evaluation rather than as a separate business-logic decision.

7.2 Conclusion

The selected tests provide systematic evidence for the recommendation control logic and two complex decision methods. Equivalence partitioning, boundary-value analysis, and basis-path testing were applied consistently; redundant combinations were avoided; all expected and actual results are traceable to automated test IDs; and the full regression checks found no introduced failures.

Reference. SC2006 Lab 4 Manual: Implementation, Testing, and Preparation for Demo, sections 3.2.1-3.2.4. Source code and automated tests are available on branch lab4/software-testing-report.