

Figure 3: Single-hop and multi-hop inter-cluster transmission mode

Figure 5: CH selection and CM joining cluster

Figure 1: Structure diagram of rounds

transmission is shown in Fig. 5 and Fig. 3. multi-hop inter-cluster transmission strategy. The network topology of clustering and inter-cluster data forwarding, which is not suitable for real-time network. In this paper, we adopt a single-hop and consumption and balance energy consumption, but also increase the energy consumption and delay of transmission, and the energy consumption is distributed to each CH, which can reduce energy cycle will be greatly shortened. Multi-hop mode divides long-distance transmission into short-distance distance is too large, energy consumption will increase sharply, nodes will die too fast, and network transmission mode. Single-hop mode is straightforward and easy to execute. However, once the communicate directly with BS in single-hop mode. Many scholars have studied multi-hop phase, as shown in Fig. 1, after which the CH communicates with the BS. In LEACH protocol, all CH The clustering protocols generally have two phases: clustering phase and stable transmission 3.1. Network Topology Model

In Figure 3, cluster head E is the leader CH, which is responsible for communication with BS or Sink. Other CHs send data to leader CH in the form of single hop or multi hops. For example, cluster heads A and B are transmitted to leader CH through multi-hop mode, while D communicates with E directly through single hop. In this way, a routing tree with the leader CH as the root is formed to balance the network energy consumption to each CH, thus prolonging the network lifetime.

3.2. Network Energy Consumption Model

We adopt the energy consumption model of wireless communication in reference [6]. As shown in Fig. 4, the sensor communication module has a transmitting device and a receiving device. In this model, the transmitter sends l bits data from a distance of d , and the corresponding energy consumption of the transmitter satisfies the following formula:

$$E_{Tx}(l, d) = \begin{cases} lE_{elec} + l_{fs}d^2, & d \leq d_0 \\ lE_{elec} + l_{mp}d^4, & d > d_0 \end{cases} \quad (1)$$

Where E_{elec} is the energy consumed by the transmitting circuit to transmit unit data. l_{fs} is the parameter under the free space model, l_{mp} is the parameter under the multipath model, and d_0 is calculated according to the following formula:

$$d_0 = \sqrt{\frac{l_{fs}}{l_{mp}}} \quad (2)$$

The energy required by the receiver is:

$$E_{Rx}(l, d) = E_{Tx}(l) + lE_{elec} \quad (3)$$

Figure 4. Energy consumption model of wireless communication

3.3. Optimal Cluster Head Probability

The CH selection mechanism of LEACH protocol is directly related to the proportion of CHs in the network, so determining the CH ratio has a direct impact on the network power consumption. In this paper, we assume that N homogeneous nodes are randomly distributed in $M \times M$ network, the number of CHs is k , the amount of data transmission per round is L bits, the energy consumption of data fusion per bit is E_{Df} , and the communication distance between clusters is less than d_0 . d_{CMtoCH} is the distance between CM and CH, d_{CHtoCH} represents the distance between CH and CH, and d_{LDtoBS} represents distance between leader CH and BS or Sink. The steps are as follows.

Step 1. The total energy consumption of CMs is:

Step 4. According to formula (9) and (10), the total energy consumption of all CHs is as follows:

$$E^{CH-Header} = [(\frac{K}{N} - 1) E^{elec} + (\frac{K}{N} - 1) E^{Dl} + \frac{1}{2} q_4^{DioBZ}] \Gamma \quad (10)$$

remote BS or Sink.

Step 3. The difference between leader CH and normal CH is that the data needs to be sent to the

$$E^w = E^{CH-NRM} = [(\frac{K}{N} - 1) (E^{elec} + E^{Dl}) + \frac{1}{2} \frac{K}{M_5}] \Gamma \quad (8)$$

node to act as an ordinary CH, that is, the energy threshold of a normal CH, which is denoted as E^w :

this value, it will die due to insufficient energy. Therefore, E^{CH-NRM} is the minimum standard for a

Equation (8) represents the minimum energy required for the normal CH to work. If it is less than

$$E^{CH-NRM} = [(\frac{K}{N} - 1) (E^{elec} + E^{Dl}) + \frac{1}{2} \frac{K}{M_5}] \Gamma \quad (8)$$

$M_5 = \frac{K}{M_5}$. Equation (7) can be changed into:

average area of each cluster is $\frac{K}{M_5}$, $\frac{q^{CHIOCH}}{M_5} = \frac{1}{2} \frac{K}{M_5}$ can be obtained from formula

The average value of q^{CHIOCH} is twice the radius of the cluster area (denoted as R), and the

$$E^{CH-NRM} = (\frac{K}{N} - 1) \Gamma E^{elec} + \Gamma E^{elec} + (\frac{K}{N} - 1) \Gamma E^{Dl} + \Gamma E^{elec} + \frac{1}{2} \Gamma q_5^{CHIOCH} \quad (1)$$

sends its own data and received data to the next CH. The energy consumption is as follows:

Step 5. On average, each normal CH receives the data of one CH and $\frac{K}{N} - 1$ members, and

$$E^{CM} = (N - K) (E^{elec} + \frac{1}{2} \frac{K}{M_5}) \Gamma \quad (9)$$

Incorporating formula (2) into formula (4) can obtain the total energy consumption of CMs:

$$E[q_5^{CMIOCH}] = (x_5 - y_5) + (x, y) \ln \frac{1}{\sqrt{1-x^2-y^2}} + \frac{1}{2} \frac{K}{M_5} \quad (2)$$

of the distance between the CM and the CH is obtained as follows:

Assuming that the CH is in the center of the cluster, the node density is $(x, y) = \frac{M_5 \sqrt{K}}{I}$, the mean

$$E^{CM} = (N - K) (E^{elec} + \frac{1}{2} \Gamma q_5^{CMIOCH}) \quad (4)$$

$$M(c^i,n)=\frac{D_5(n^i,n)}{E^n}$$

$$q^c=\frac{q(c p^i, l q) E^i}{q(l^i, c p^i) E^0}$$

$$i \qquad \qquad \qquad \mathbb{B}$$

$$- \,$$

$$0^{\circ} i \quad \mathbb{C}$$

$$\Delta^i = \frac{1 - b^i}{b^i} \wedge \max \frac{b^i}{I} \\ \frac{1}{b^i} [E^2 - (1 - E^2) \lambda^q] i \in \mathbb{C}$$

$$i$$

high nodes; to solve the propriety of high-energy nodes being selected as CHs, but also effectively protect low-energy nodes. When Δ^i less than 0, the node can not be selected as CH. Therefore, formula (13) can not only protect the network. If the residual energy of node i is below the threshold, resulting in b^i less than 0

Where E^i is the remaining energy of node i and $\underline{E} = \frac{V_{i-1}}{I_{i-1}} E^i$ is the current average energy

improved protocol, EID is 1081 rounds, and the MID is 5832 rounds.

MID. For GEACH, EID is 401 rounds, and no node survives after the 1058th round, while the

Figure 7 shows the comparison between the improved protocol and GEACH's EID, MID, and

Figure 7. EID, MID and MID

reduced energy consumption, which can effectively extend the network life cycle.

not the graph in short rounds. It can be seen that the improved protocol has better stability and more energy consumption balance of the new clustering algorithm, so that after EID, network nodes will the slope of the improved algorithm curve is significantly smaller than GEACH, which is due to the operation. The stable period of the improved protocol is significantly longer than GEACH. In addition, the beginning of the network operation to the EID, this stage is called the stable period of network the life cycle of the improved protocol is significantly longer than that of the GEACH protocol. From

Figure 8 shows the changes between the number of alive nodes and the rounds. It is obvious that

Figure 8. Alive nodes per round

- lookup logic for WM2N[1]. Multimedia Tools and Applications, 2012, 26(12): 18122-18120.
- [13] Jung K D, Lee J A, Jeong H A. Improving adaptive cluster head selection of leech protocol using Communication Technologies, New Delhi, Springer, 2010: 323-323.
- network[C]\Proceedings of the second International Conference on Computer and
- [15] Murai A, Gupta S H. Analysis of energy efficient, LEACH-based cooperative wireless sensor information sciences, 2018, 30(5): 522-522.
- consumption in wireless sensor networks[1]. Journal of King Saud University-Computer and
- [11] Elshikawey M, Elshehri S M, Wahed M E. An enhancement approach for reducing the energy systems and Computers, 2012, 26(01): 1220004.
- lookup C-means and genetic lookup system for wireless sensor network[1]. Journal of Circuits,
- [10] Prokhorov A, Maslennikov-Maslov B. An energy-efficient clustering algorithm using Networking, 2012, 2012(1): 1-2.
- for data gathering in W2N[1]. EURASIP Journal on Wireless Communications and
- [9] Arumugam G S, Ponnuchamy L. EE-LEACH: development of energy-efficient LEACH Protocol Networking (ICON). IEEE, 2018: 235-232.
- for W2N using optimal cluster size[C]\2018 International Conference on Information
- [8] Bazzaz M, Nurgomran D D, Zhu S. Energy efficient K-means clustering-based routing protocol Organized by IEM in Collaboration with IEEE, 2011: 503-508.
- Means induced clustering of a Wireless Sensor Network[1]. Proceedings of the IEMCON
- [7] Dasgupta S, Dutta B. An improved Leach approach for Head selection strategy in a Fuzzy-C conference on system sciences, IEEE, 2000: 10 pp. vol. 5.
- for wireless microsensor networks[C]\Proceedings of the 33rd annual Hawaii international
- [6] Heinzelman W B, Chandrakasan A, Balakrishnan H. Energy-efficient communication protocol Wireless Computing, Communication and Applications, IEEE, 2015: 235-232.
- distribution of sources in W2N[C]\2015 Seventh International Conference on Broadband,
- [2] Fareed M S, Javadi N, Akbar M, et al. Optimal number of cluster head selection for efficient for wireless sensor networks[1]. IEEE Communications Magazine, 2002, 43(3): 28-13.
- [4] Muruganathan S D, Ma D C E, Bhasin K I, et al. A centralized energy-efficient routing protocol Technology (ICCT). IEEE, 2012: 255-252.
- wireless sensor networks[C]\2012 IEEE 14th International Conference on Communication
- [3] Zhou J, Chen S, Wang X, et al. Spatial compression scheme for improving the lifetime of communications, 2005, 1(4): 220-220.
- architecture for wireless microsensor networks[1]. IEEE Transactions on Wireless
- [5] Heinzelman W B, Chandrakasan A B, Balakrishnan H. An application-specific protocol 3(4): 250-235.
- collection in large-scale wireless sensor networks[1]. IEEE Internet of Things Journal, 2012,
- [1] Xu S, Chen L, Chen C, et al. Joint clustering and routing design for reliable and efficient data

National science and technology major special funded projects (2018ZX0301002-004).

good performance.

and FID aspects. The results indicate that the improved protocol is superior to LEACH and has reduce energy consumption. We compare and analyze the two protocol from network lifetime, FID, consider the remaining energy and distance factors to form a non-uniform network cluster structure to energy, node density, and communication factors. Second, in the clustering stage of ordinary nodes, network life. First, in the cluster head selection stage, consider the impact of energy threshold, residual In this paper, we propose a new clustering algorithm to distribute energy consumption and extend

