

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

Problem	Points	Lost	Gained	Running Total	TA
1	1				
2	24				
3	15				
4	20				
5	20				
6	20				
Total	100				

You may ask for clarification but you are ultimately responsible for the answer you write on the paper. If you make any assumptions state them.

Please look through the entire test before starting. WE MEAN IT!!!

NOTE:  $M = 10^6$   $K = 10^3$   $Mi = 2^{20}$   $Ki = 2^{10}$   
Illegible answers are wrong answers.

Show your work in the space provided to get any credit for problem-oriented questions.

Good luck!

1. (1 point, 1 min) (don't worry you get 1 point regardless of what you say!)

The last time Jackets beat the Bulldogs in football

- (a) 2013
- (b) 2012
- (c) 2008
- (d) 2009
- (e) 1999
- (f) at the time of big bang

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

## Cache

2. (24 points, 20 min)

- a) (3 points) A page fault occurs for a process when the CPU cannot find a page table entry in the page table to translate the virtual address generated by the process. Fill in the table below indicating by writing "hardware" or "software" as to who is responsible for dealing with the events shown to continue with the execution of the process:

Event	Who handles it?
TLB Miss	
Cache Miss	
Page Fault	

- b) (6 points)

Given:

- 8 total cache blocks
- 2-way set-associative organization
- Cache initially empty
- LRU replacement policy
- Memory blocks A, B, C, and D all map to the same cache line.
- The processor performs a total of eight accesses, to memory blocks A, B, B, A, C, B, A, and C, in that order. For each of these accesses, specify (by filling in the table below) whether it is a cache hit or a cache miss, type of miss (cold/capacity/conflict), and the memory block evicted (if any). **Note: capacity miss dominates over conflict; cold dominates over capacity.**

C0	C1

Memory Access	Hit/miss	Type of miss	Block evicted from cache
A			
B			
B			
A			
C			
B			
A			
C			

(Area for rough work)

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

- c) (2 points) Spatial locality suggests that... (circle the correct choice)
- (i) Once brought into the cache, we should keep the data around as long as possible
  - (ii) On a miss, we should bring in adjacent memory locations into the cache
  - (iii) The memory location being brought in due to a miss is not likely to be referenced in the future
  - (iv) None of the above
- d) (2 points) Temporal locality suggests that... (circle the correct choice)
- (i) Once brought into the cache, we should keep the data around as long as possible
  - (ii) On a miss, we should bring in adjacent memory locations into the cache
  - (iii) The memory location being brought in due to a miss is not likely to be referenced in the future
  - (iv) None of the above
- e) (2 points) Drop in miss rate with increasing blocksize of the cache stops after a point due to (circle the right choice)
- (i) bugs in the cache implementation
  - (ii) the cache miss penalty
  - (iii) the changes in the working set of the program
  - (iv) the number of stages in the pipelined processor
- f) (2 points) Virtually indexed and physical tagged cache is attractive because (circle the correct choice)
- (i) it results in a better cache hit ratio for a given cache organization
  - (ii) it eliminates the memory aliasing problem with physically indexed physically tagged caches
  - (iii) it enables building bigger first level caches than physically indexed and physically tagged caches
  - (iv) it removes the address translation through the TLB out of the critical path of the cache access

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

g) (2 points) Page coloring is a ... (circle the correct choice)

- (i) type of page replacement algorithm
- (ii) technique for increasing the hit rate of the first level cache
- (iii) technique to allow the hardware to increase the size of the first level cache
- (iv) technique to reduce the TLB lookup time

h) (5 points) Consider a **4-way set associative** cache:

- Total **data size** for the cache = **256 KiB** (note: Ki = 1024)
- CPU generates 32-bit byte-addressable memory addresses
- Each memory **word** consists of **4 bytes**
- The cache **block size** is **64 bytes**
- The cache has **one valid bit per block**
- The cache uses **write-back** policy with **one dirty bit per word**
- The cache **protects the MOST RECENTLY USED** cache block from being replaced

c0	c1	c2	c3
	.		
	.		

Answer the following questions (**you have to show your work for ANY credit**):

(i) How many index bits are needed for this cache organization?

(ii) How many tag bits are needed in each cache block?

(iii) How many dirty bits are needed in each cache block?

(iv) How much meta data is needed per cache block?

(v) How much meta data is needed per cache line?

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_


## Input/Output and Disk

3. (15 points, 20 min)

a) (2 points) Memory mapped I/O is a ... (circle the right choice)

- (i) technique for interfacing slow speed devices to the CPU
- (ii) technique for interfacing high speed devices to the CPU
- (iii) technique that allows the CPU to use Load/Store instructions to access the device registers
- (iv) technique that allows the CPU to quickly find the location of the handler code for a device

b) (3 points) What is the role of the buffer in a DMA controller?



c) (2 points) Zoned bit recording ... (circle the right choice)

- (i) has the same number of sectors on all the tracks
- (ii) has more sectors on the outer tracks compared to the inner tracks
- (iii) has more sectors on the inner tracks compared to the outer tracks
- (iv) has different number of sectors on different tracks of the same cylinder

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

d) Given the following specification for a disk drive:

Average seek time	=	8 ms
Rotational speed	=	12000 RPM
Platters	=	2
Surface per platter	=	2
Tracks per surface	=	1024
Sectors per track	=	256
Recording density	=	256 bytes per sector

(i) (1 point) How much time is needed to get to a random sector on the disk?

(ii) (1 point) How much time is needed to read one random sector from the disk when the head is already positioned on the desired sector?

(iii) (2 points) If the disk gets a request to read 6 random sectors, how much total time will that request take to complete?

(iv) (2 points) If the disk gets a request to read 6 consecutive sectors, how much total time will that request take to complete?

(v) (2 points) What is the transfer rate of the disk?

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

## File Systems

4. (20 points, 20 min)

a)

Notes:

- Unix "**touch** <file>" command creates a zero byte new file or updates the timestamp of the named file
- Unix "**ln** <file1> <file2>" command creates a hard link
- Unix "**ln -s** <file1> <file2>" command creates a sym link
- Unix "**rm** <file>" removes the named file

(i) (8 points) In the following table, assume **none of the files exist to start with** in the current directory. Fill in the table. The reference count in the table pertains to the i-node that is affected by the command in that row. If a new i-node is created, show the old reference count for that i-node as 0.

Command	New i-node created (yes/no)	Reference count	
		old	new
touch f1			
touch f2			
ln -s f2 f3			
ln -s f1 f4			
ln -s f4 f5			
ln f4 f6			
rm f4			
rm f2			

Use this area for rough work for this question.

(ii) (2 points) After all the above commands are executed which file names will result in successful access?

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

b) (NOTE  $M_i = 2^{20}$ )

Given the following:

Size of index block = 256 bytes

Size of Data block = 1024

bytes

Size of pointer = 8 bytes

(to index or data blocks)


The i-node consists of

2 direct data block pointers,

1 single indirect pointer, and

1 double indirect pointer.

Note that the index blocks and data blocks are allocated on a need basis. An index block is used for the top-level i-node as well as for the index blocks that store pointers to other index blocks and data blocks (see Figure).



- i. (2 points) How many pointers does each index block contain?
- ii. (2 points) How many data blocks are used to store a 40 KiB file?
- iii. (2 points) How many index blocks (including the i-node for the file) are needed to store a 258 KiB file?
- iv. (2 points) What is the largest file size that can be supported in this file system?



# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

c) (2 points) Multilevel indexed allocation results in (circle ONE choice that captures ALL the TRUE statements in the following list)

- (i) External Fragmentation
- (ii) Internal fragmentation
- (iii) Ability to grow the file easily
- (iv) Inefficiency for accessing small files
- (v) {1 and 2}
- (vi) {2 and 3}
- (vii) {2, 3, and 4}
- (viii) None of the above

## Parallel Systems

5. (20 points, 20 mins)

a) (2 points) Deadlock (circle the right choice)

- (i) Is a condition where threads are not using mutex locks
- (ii) Is a condition where all the locks variables are in use
- (iii) A lock variable that is dead
- (iv) Is a condition where one or more threads are waiting for an event that will never happen

b) (2 points) User level threads with process level scheduling ... (circle the right choice)

- (i) Can take advantage of the hardware concurrency available in multiprocessor
- (ii) Is impossible to implement on a true multiprocessor
- (iii) Will have no performance advantage on a multiprocessor compared to a uniprocessor

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

b) Given the following code:

```
#define BUSY 1
#define NOT_BUSY 0
int res_state = NOT_BUSY; /* init */
mutex_t cs_mutex;
cond_var_t res_not_busy;

// A thread calls this function to acquire access to a shared resource
acquire_shared_resource()
{
    thread_mutex_lock(cs_mutex); /* function provided by the OS */
    L1: while (res_state == BUSY)
        thread_cond_wait (res_not_busy, cs_mutex); /* function provided by the OS */
    L2:
        res_state = BUSY;
    thread_mutex_unlock(cs_mutex); /* function provided by the OS */
}

// A thread calls this function to release access to a shared resource
release_shared_resource()
{
    thread_mutex_lock(cs_mutex);
    res_state = NOT_BUSY;
    thread_cond_signal(res_not_busy);
    thread_mutex_unlock(cs_mutex);
}
```

(i) (3 points) In the statement labeled L1, why do we need a "while" loop?

(ii) (2 points) If a thread is at label L2 (i.e., fallen through the while loop) what are the invariants?

(iii) (2 points) Who ensures that the invariants are satisfied when a thread is at label L2?

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

- c) (4 points) In the following code, `buflock`, `bufavail`, and `frame_buf` are shared variables. Each of the functions (`digitizer` and `tracker`) are executed by two distinct threads. What is the problem (if any) with the following code?

```
digitizer()
{
    image_type dig_image;
    int tail = 0;

    loop {
        grab(dig_image);
        thread_mutex_lock(buflock);
        while (bufavail == 0) do nothing;
        thread_mutex_unlock(buflock);
        frame_buf[tail mod MAX] =
            dig_image;
        tail = tail + 1;
        thread_mutex_lock(buflock);
        bufavail = bufavail - 1;
        thread_mutex_unlock(buflock);
    }
}

tracker()
{
    image_type track_image;
    int head = 0;

    loop {
        thread_mutex_lock(buflock);
        while (bufavail == MAX) do nothing;
        thread_mutex_unlock(buflock);
        track_image = frame_buf[head mod
            MAX];
        head = head + 1;
        thread_mutex_lock(buflock);
        bufavail = bufavail + 1;
        thread_mutex_unlock(buflock);
        analyze(track_image);
    }
}
```

- d) (3 points) Pictorially show the memory footprint of a multithreaded process.

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

e) (2 points) Shown below is code for implementing mutual exclusion lock.

```
lock(L):                                unlock(L):
    L1: if (L == 0) L = 1;                L = 0;
        else
            while (L == 1); /* spin */
            go to L1;
```

If you have only atomic read and write instructions, will the above code work for implementing mutual exclusion lock? If not, why not?

## Networking

6. (20 points, 20 min)

a) (2 points) In stop-and-wait protocol, what are the fundamental assumptions that make it possible to use a 1-bit sequence number?

b) (2 points) The sequence number in a packet ... (circle the right choice)

- (i) Gives the destination address
- (ii) Is needed for message reconstruction at the destination
- (iii) Assures the integrity of the packet
- (iv) Is computed using cyclic redundancy check (CRC) algorithm
- (v) Is the same for every packet in a given message

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM


Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

c) (2 points) In the sliding window protocol,

(i) when is the window size decreased?

(ii) when is the window size increased?

d) (4 points) Show the wave form for the following packet with Manchester encoding (the space between the vertical lines represent time per bit):



e) (2 points) Token ring ... (circle the correct choice)

(i) Is as collision prone as Ethernet

(ii) Uses IP addresses


- (iii) Results in better throughput under high load compared to Ethernet

- (iv) Results in less average latency per transmission compared to Ethernet

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

f) (2 points) How many IP networks in the following figure?



g) (3 points)

Given the following:

Message size	= 10,000 bits
Bandwidth on the wire	= 100,000 bits/sec
Time of flight	= 10 msec
Sender overhead	= 1 ms
Receiver overhead	= 1 ms

Compute the throughput.

# CS 2200 Fall 2013 Final Exam 8 AM to 10 AM

Name: \_\_\_\_\_ GT Number: \_\_\_\_\_

h) (3 points)

Given the following:

Message size	=	90,000 bits
Header size per packet	=	1000 bits
Packet size	=	10,000 bits
Bandwidth on the wire	=	400,000 bits/sec
Time of flight	=	2 secs
Window size	=	10
Sender overhead	=	0
Receiver overhead	=	0
Size of ACK message	=	negligible (take it as 0)

Assuming a 10% packet loss on DATA packets (no loss on ACK packets), how many total DATA packets are transmitted by the sender to accomplish the above message delivery?