```
Tabbed 2
Tabbed 3
Tabbed 4

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>

long unsigned int64;

char *cmd, *cmdline, c, *cmd_arg[64];
int cmdlen, pos, argnum;

/* Read next command line */
int
read_cmd(void)
{
	*cmdline='\0';
	pos = 0;
	cmd = cmdline;
	for (argnum = 0; argnum < 64; argnum++)
		cmd_arg[argnum] = NULL;
	argnum = 0;
	return(1);
}

/* Add char to command line, exit if too long */
int
add_char(int c)
{
	if (pos+1 >= cmdlen) {
		printf("Command line too long\n");
		exit(1);
	}
	cmdline[pos++] = c;
	cmdline[pos] = '\0';
	return(0);
}

/* Add argument to cmd_arg array */
int
add_arg(int c)
{
	if (argnum+1 >= 64) {
		printf("Too many arguments\n");
		exit(1);
	}
	if (*cmdline == '\0' || cmd_arg[argnum] != NULL) {
		cmd_arg[++argnum] = cmdline+pos;
	}
	return(0);
}

/* Execute command line */
int
exec_cmd(void)
{
	pid_t cpid, mypid;
	int pid, status;

	cpid = fork();
	if (cpid > 0) {
		mypid = getpid();
		pid = wait(&status);
	} else if (cpid == 0) {
		execvp(cmd, cmd_arg);
		exit(1);
	} else {
		perror("fork");
	}
	return(0);
}

/* Main loop - read and execute commands */
int
main(int argc, char *argv[])
{
	cmdlen = 1000;
	cmdline = malloc(cmdlen);
	read_cmd();
	while ((c = getchar()) != EOF) {
		if (c == '\n')
			exec_cmd();
		else if (c == ' ')
			add_arg(c);
		else
			add_char(c);
	}
	return(0);
}
```

```
```