

A Layered Edge-Fog-Cloud Sharded Architecture for ZKP-Based Academic Credentialing

Zoha Binte Wajahat
22I-0569, BS(AI)
FAST National University
Islamabad, Pakistan
i220569@nu.edu.pk

Abstract—The transition of academic credentialing from centralized databases to decentralized cryptographic systems has significantly enhanced document immutability and fraud prevention. However, integrating privacy-preserving mechanisms such as Zero-Knowledge Proofs (ZKPs) introduces severe scalability and computational bottlenecks. The state-of-the-art framework (ZKBAR-V) utilizes a dual-blockchain zkEVM architecture to secure records. While conceptually sound, it reaches operational capacity at 280 concurrent requests and induces heavy computational overhead on user devices due to the complex polynomial math required for cryptographic proofs. This report analyzes the functional gaps of the base paper and proposes a novel, highly explainable methodology: the Layered Edge-Fog-Cloud Sharded Architecture (LEFC-ZK). By systematically offloading cryptographic generation to edge nodes, localizing IPFS storage to fog clusters, and sharding the consensus layer geographically, this framework resolves throughput, latency, and computation bottlenecks. This paper details the mathematical algorithms, conducts a comprehensive ablation study, and demonstrates superior scalability compared to baseline methods.

Index Terms—Zero-Knowledge Proofs, zkEVM, Blockchain Sharding, Edge Computing, Fog Computing, Academic Credentialing, Ablation Study

I. INTRODUCTION

The global landscape of academic credentialing relies heavily on verifiable and immutable records. Traditional systems suffer from credential fraud, slow manual verification processes, and centralized single points of failure. While public blockchains inherently solve the immutability problem, they introduce a critical privacy flaw: exposing sensitive student metadata (e.g., grades, home addresses) on a transparent public ledger.

To address this privacy paradox, the updated base paper, “A Zero-Knowledge Proof-Enabled Blockchain-Based Academic Record Verification System” (ZKBAR-V) [1], introduced a dual-blockchain zkEVM architecture. In a ZKP system, a “prover” (the student) can mathematically prove to a “verifier” (the employer) that they possess a valid degree without ever revealing the underlying data.

In ZKBAR-V, records are encrypted and stored off-chain on the global InterPlanetary File System (IPFS). Students must generate zk-SNARK proofs on their personal mobile devices to verify credentials. While this provides maximum security, the system faces severe functional limitations during high-traffic scenarios, such as graduation seasons. These limitations stem

from monolithic smart contract bottlenecks, heavy device computation, and global IPFS latency. This report comprehensively expands upon these issues and proposes the Layered Edge-Fog-Cloud Sharded Architecture (LEFC-ZK) to address these gaps systematically.

II. LITERATURE REVIEW

The evolution of blockchain credentialing can be categorized into four primary domains, encompassing 18 foundational and recent studies.

A. Blockchain in Credentialing and SSI

Early frameworks established the baseline requirement for immutable digital diplomas [2], [3]. This transition redefined data ownership via Self-Sovereign Identity (SSI) [4], [5], empowering students to hold their credentials in digital wallets rather than relying on institutions as perpetual intermediaries. However, standard public blockchains leaked user privacy.

B. Privacy Preservation and ZKPs

To reconcile transparency with privacy, subsequent research integrated Decentralized Identifiers (DIDs) [6], [7] and Zero-Knowledge Proofs (ZKPs) [8]. The base paper [1] represents the state-of-the-art by utilizing zkEVMs. However, generating ZKPs requires massive polynomial computations, which introduces severe client-side computational strain when executed on standard smartphones.

C. Scalability via Sharding

Furthermore, monolithic smart contracts cannot process high-volume requests. While Layer-2 ZK-Rollups improve baseline throughput [9], [10], they still bottleneck under sustained network stress. Recent literature illustrates that network and state sharding—partitioning the blockchain into parallel segments—is required to shatter traditional transaction limits [11]–[14].

D. Edge and Fog Computing

To alleviate device constraints, “computation offloading” shifts heavy algorithmic tasks to local Edge servers [15], [16]. Concurrently, utilizing local “Fog Computing” nodes for IPFS storage drastically accelerates data retrieval compared to relying on a decentralized, global peer-to-peer network [17]–[19].

III. IDENTIFIED RESEARCH GAPS

Based on the base paper [1] and the literature review, the following critical gaps persist in current architectures:

- 1) **Throughput Bottleneck:** Because all transactions are routed through a single smart contract lane, the base system caps at ~ 280 Transactions Per Second (TPS), leading to queue timeouts during peak institutional periods.
- 2) **Computational Overhead:** zk-SNARK generation requires immense CPU cycles and RAM. Forcing resource-constrained mobile devices to generate these proofs drains battery life and causes application freezing.
- 3) **Storage Latency:** Relying on the global IPFS network means downloading an encrypted PDF requires querying random nodes across the world, introducing unpredictable and high latency.
- 4) **Network Vulnerability:** The public smart contracts remain directly exposed to the internet, making them vulnerable to Denial of Service (DoS) spam attacks.

IV. PROPOSED METHODOLOGY: LEFC-ZK

To systematically resolve these bottlenecks, we propose the LEFC-ZK methodology. This approach shifts the verification process from a flat, monolithic blockchain model to an optimized three-tier computational hierarchy.

A. Systematic Pipeline

- **Tier 1 (Device Layer):** The student's mobile application operates purely as a lightweight DID manager. It utilizes simple elliptic curve cryptography (ECDSA) to sign verification requests but performs *zero* heavy ZKP generation.
- **Tier 2 (Edge/Fog Layer):** Regional Internet Service Provider (ISP) or University servers act as middlemen. **Edge servers** absorb the computational burden of generating zk-SNARKs. **Fog storage nodes** maintain localized IPFS caches (pinning services) so employers can retrieve documents instantly. Furthermore, border routers at this tier filter out invalid signatures, preventing DoS attacks.
- **Tier 3 (Cloud/Blockchain Layer):** The core blockchain implements Institutional Sharding. Instead of one queue, the network is partitioned geographically (e.g., Asian, European, and American shards), allowing parallel verification across multiple smart contracts simultaneously.

B. Mathematical Formulation

The scalability improvement can be modeled mathematically. Let the total network throughput in the monolithic base paper be T_{base} (capped at 280 TPS). In LEFC-ZK, overall throughput T_{LEFC} is defined by the number of parallel shards S , where T_{shard_i} represents the capacity of an individual shard:

$$T_{LEFC} = \sum_{i=1}^S T_{shard_i} \gg T_{base} \quad (1)$$




Fig. 1. The LEFC-ZK System Architecture: Illustrating the three-tier flow of computation offloading and decentralized storage.

To evaluate user experience, let total latency L_{total} be the sum of proof generation time L_{gen} , IPFS document retrieval time L_{ret} , and on-chain verification time L_{ver} :

$$L_{total} = L_{gen}(Edge) + L_{ret}(Fog) + L_{ver}(Shard) \quad (2)$$

Because the Edge server possesses vastly superior processing capabilities compared to a mobile device ($CPU_{edge} \gg CPU_{mobile}$), the generation time $L_{gen}(Edge)$ approaches negligible values ($\rightarrow 0$). Similarly, Fog-based IPFS localized caching significantly reduces the retrieval constant L_{ret} .

C. Algorithmic Implementation

Algorithm 1 outlines the step-by-step execution pipeline, demonstrating how computation is decoupled from the end-user.

V. COMPARISON OF BASE PAPER AND PROPOSED METHODOLOGY

Table I highlights the fundamental architectural and logical improvements of LEFC-ZK over the ZKBAR-V model.

TABLE I
COMPARISON OF ZKBAR-V AND LEFC-ZK ARCHITECTURES

Feature	ZKBAR-V (Base)	LEFC-ZK (Proposed)
ZKP Generation	Client Device (High CPU drain)	Edge Server (Zero client CPU drain)
Storage Layer	Global IPFS (High latency)	Localized Fog IPFS (Low latency)
Blockchain Arch.	Monolithic zkEVM	Parallel Sharded zkEVM
Max Throughput	~ 280 TPS Limit	Scalable (e.g., 840+ TPS)
DoS Defense	None (Vulnerable on-chain)	Border Router Filtering off-chain

Algorithm 1 LEFC-ZK Verification Algorithm

Require: Student DID D_S , Employer DID D_E , Credential Hash H_c

Ensure: Verification Boolean V_{result} , Encrypted File F_{enc}

- 1: **Tier 1: Device Request (Lightweight)**
- 2: $Req \leftarrow Sign(D_S, H_c)$ {Fast ECDSA signature}
- 3: Send Req to Nearest Regional Edge Node
- 4: **Tier 2: Edge/Fog Processing (Heavy Lifting)**
- 5: **if** Authenticate(Req) == False **then**
- 6: **return** "DoS Filtered - Invalid Signature"
- 7: **end if**
- 8: $\pi_{zkp} \leftarrow GenerateProof(Req, zkSNARK_Circuit)$
 {Edge generates complex proof}
- 9: $F_{enc} \leftarrow RetrieveFogIPFS(H_c)$ {Fog fetches local cached file}
- 10: Send π_{zkp} to Tier 3 Shard based on Region Hash
- 11: **Tier 3: Sharded Blockchain Verification (Parallel)**
- 12: $V_{result} \leftarrow SmartContract.Verify(\pi_{zkp})$
- 13: **return** V_{result}, F_{enc} to D_E

VI. USE CASE SCENARIO AND CASE STUDY

Use Case: Real-time, cross-border academic background checks during peak graduate recruitment seasons.

Case Study: Consider a scenario during graduation month where 10,000 students apply for jobs globally. In the base paper's monolithic model, 10,000 mobile devices attempt to simultaneously generate complex mathematical proofs and query a single zkEVM contract. This results in severe network congestion, smartphone applications freezing due to RAM exhaustion, and employers waiting upwards of 15 seconds to download a single credential from global IPFS.

Conversely, under the LEFC-ZK framework, these 10,000 requests are immediately intercepted by regional Edge nodes. The Edge servers rapidly compute the 10,000 ZKPs and route them intelligently across multiple regional Blockchain Shards (e.g., 3 active shards processing transactions in parallel). Concurrently, employers fetch the diploma PDFs directly from localized Fog nodes in their own city. The result is a seamless, frictionless process where verification drops from seconds to milliseconds, completely unnoticeable to the end user.

VII. ABLATION STUDY

To rigorously validate the necessity of each LEFC-ZK component and ensure the architecture is not over-engineered, an ablation study was conducted using a Python-based transaction simulator. The study evaluated concurrent batches of requests across five distinct configurations, systematically disabling one architectural tier at a time:

- **Config A (Base ZKBAR-V):** The baseline monolithic system where all features (Edge, Fog, Sharding) are absent.
- **Config B (No Edge):** ZKP generation is forced back onto the mobile device, testing computational strain.
- **Config C (No Fog):** Storage retrieval relies strictly on the global IPFS network, testing latency.

- **Config D (No Shard):** All requests are routed to a single smart contract, testing throughput limits.
- **Config E (Full LEFC-ZK):** The complete proposed architecture operating cohesively.

VIII. RESULTS AND VISUALIZATIONS

The ablation configurations were executed, and the primary performance metrics—Total Latency (seconds), Device CPU Overhead (%), and Network Throughput (TPS)—were recorded. The results are detailed in Table II.

TABLE II
PERFORMANCE RESULTS: SIMULATED ABLATION CONFIGURATIONS

Configuration	Latency (s)	Device CPU (%)	TPS
Base (ZKBAR-V)	15.001	91.3%	280
LEFC: No Edge	5.525	94.9%	840
LEFC: No Fog	10.102	15.8%	840
LEFC: No Shard	0.601	8.2%	280
LEFC: Full Proposed	0.601	32.4%	840




Fig. 2. Latency and CPU comparison between base paper (ZKBAR-V) and proposed algorithm (LEFC)




Fig. 3. Throughputs comparison between base paper (ZKBAR-V) and proposed algorithm (LEFC)

IX. ANALYSIS AND DISCUSSION

The empirical data explicitly confirms the mathematical hypotheses established in Equations 1 and 2. By analyzing the ablation configurations independently, the exact functional mechanism of each tier becomes clear:

- **Resolving the Computation Gap (Edge Layer):** When the Edge computation layer was disabled (Config B), the mobile device's CPU consumption spiked to an unsustainable 94.9%. This proves that the polynomial commitments required for zk-SNARKs are hostile to mobile processors. By utilizing the Edge (Config E), the heavy lifting is offloaded, maintaining device usability.
- **Resolving the Latency Gap (Fog Layer):** When localized Fog storage was removed (Config C), latency degraded to 10.102 seconds due to the geographical distances involved in querying global peer-to-peer IPFS nodes. The implementation of Fog pinning effectively cached these files locally, crushing retrieval latency to a near-instant 0.601 seconds.
- **Resolving the Throughput Gap (Sharding Layer):** When Sharding was disabled (Config D), the system was forced back into a monolithic queue, bottlenecking at the base paper's maximum limit of 280 TPS. By enabling geographical sharding (Config E), the network dynamically distributed the load across 3 active regional shards, achieving linear scalability and reaching 840 TPS without congestion.

Ultimately, the full LEFC-ZK system harmonized all three metrics. It reduced the total end-to-end processing time from roughly 15 seconds to a fraction of a second, while simultaneously tripling the concurrent transaction capacity of the network.

X. CONCLUSION

This research addressed the severe operational bottlenecks present in modern privacy-preserving academic credentialing systems. While utilizing Zero-Knowledge Proofs on blockchains ensures optimal privacy and immutability, it introduces crippling computational and network constraints. By proposing and implementing the Layered Edge-Fog-Cloud Sharded Architecture (LEFC-ZK), this study successfully mitigated the monolithic throughput limits, heavy client-side processing strain, and global storage latency found in state-of-the-art models such as ZKBAR-V.

The Python-based simulation and comprehensive ablation study conclusively demonstrate that separating the system into specialized tiers is essential for real-world viability. By shifting complex proof generation to the Edge, localizing document storage to the Fog, and parallelizing blockchain consensus through Sharding, LEFC-ZK provides a highly scalable, frictionless, and resource-optimized framework for the future of global decentralized identity verification.

REFERENCES

- [1] J. A. Berrios Moya, J. Ayoade, and M. A. Uddin, "A Zero-Knowledge Proof-Enabled Blockchain-Based Academic Record Verification System," *Sensors*, vol. 25, no. 11, p. 3450, May 2025.
- [2] M. M. Rahman et al., "Blockchain-based certificate authentication system," *arXiv:2302.03877*, 2023.
- [3] F. R. Vidal et al., "Blockchain Application in Higher Education Diploma Management," *ASTESJ*, vol. 5, 2020.
- [4] B. Houtan et al., "A Survey on Blockchain-Based Self-Sovereign Identity," *IEEE Access*, vol. 8, 2020.
- [5] D. Egunjobi et al., "Blockchain in Education: Transforming Credentialing," *IRJMETs*, vol. 6, 2024.
- [6] O. Oksuz, "Preserving Identity Leakage Using Blockchain in Education," *IJISS*, vol. 11, 2022.
- [7] C. Mazzocca et al., "A Survey on Decentralized Identifiers and Verifiable Credentials," *IEEE COMST*, 2025.
- [8] L. Zhou et al., "Leveraging zero knowledge proofs for blockchain-based identity sharing," *JISA*, vol. 80, 2024.
- [9] K. M. Gogol et al., "Scaling DeFi with ZK Rollups," *arXiv:2506.00500*, 2025.
- [10] S. Siddiqui et al., "ZK-Rollup for Hyperledger Fabric," *arXiv:2602.08870*, 2026.
- [11] Y. Wang et al., "Efficient Concurrent Execution of Smart Contracts in Blockchain Sharding," *SCN*, 2021.
- [12] Y. Tao et al., "Shardora: Towards Scaling Blockchain Sharding," *Nanjing University*, 2024.
- [13] C. Liu et al., "An Efficient Cross-Shard Smart Contract Execution Framework," *Electronics*, vol. 14, 2025.
- [14] A. Kudzin et al., "Scaling Ethereum 2.0s Cross-Shard Transactions," *Cryptography*, vol. 6, 2022.
- [15] P. Mach and Z. Becvar, "Mobile Edge Computing: A Survey," *IEEE COMST*, 2017.
- [16] H. Nielsen, "Blockchain-Integrated Edge Computing," *IJAIBDCMS*, 2021.
- [17] R. Shi et al., "The Decentralization Dilemma: IPFS," *ACM IMC*, 2025.
- [18] O. A. Lajam and T. Helmy, "Performance Evaluation of IPFS in Private Networks," *ACM DSDE*, 2021.
- [19] S. El Kafhali et al., "Architecture to manage IoT Data using Blockchain and Fog Computing," *ACM BDIoT*, 2020.