

**Department of Software Engineering**  
**Mehran University of Engineering and Technology, Jamshoro**

**Course: SW222 – Database Management & Administration**

<b>Instructor</b>	Ms Shafiya Qadeer	<b>Practical/Lab No.</b>	02
<b>Date</b>	20-21/01/2021	<b>CLOs</b>	2
<b>Signature</b>		<b>Assessment Score</b>	2 Marks

<b>Topic</b>	<b>To become familiar with Table creation and population of table</b>
<b>Objectives</b>	<b>- TO BECOME FAMILIAR DESIGNING A DATABASE</b>

**Lab Discussion: Theoretical concepts and Procedural steps**

**DATABASE DESIGN:**

- It is the process of creating data models of database.
- data model: it determines the logical structure of a database.
- Designing is always done before the implementation of the database.
- It focuses on data requirements/needs.
- It is also called database modeling

**PHASES FOR DESIGNING THE DATABASE**

- There are three levels of data modeling/designing.
  1. Conceptual Data Model
  2. Logical Data Model
  3. Physical Data Model

**CONCEPTUAL MODEL**

- It describes the data in less detail and does not contain any implementation details(not physically implemented).
- It is a graphical representation of the data requirements.
- Transforms data requirements to conceptual model.
- Conceptual data model includes ERDs.

**ENTITY RELATIONSHIP DIAGRAM(ERD)**

- An entity-relationship diagram (ERD) is a graphical representation of an information system that shows the relationship between people, places, concepts or events within that system.
- An entity relationship diagram (ERD) shows the relationships of entities stored in a database.
- ER Diagrams are most often used to design relational databases.

**COMPONENTS OF ER DIAGRAM**

1. Entity
2. Attributes
3. Relationship

## 1. ENTITY

- An entity can be a real-world object that can be easily identifiable.
- A definable thing such as a person, object, place or event.
- Examples: a customer, student, car or product etc.
- Entities are represented by rectangles.



## TYPES OF ENTITIES

### 1. WEAK ENTITY:


- Weak entity is an entity that depends on another entity. Weak entities are also called dependent entities, it is represented by a double rectangle.
- The weak entity has a partial discriminator key.

Weak Entity

### 2. STRONG ENTITY

- If an entity type has a key attribute specified then it is a strong entity type.
- The Strong Entity is the one whose existence does not depend on the existence of any other entity. It is denoted by a single rectangle.

Strong Entity




Observing the ER-diagram above, for each loan, there should be at least one borrower otherwise that loan would not be listed in Loan entity set. But even if a customer does not borrow any loan it would be listed in Customer entity set. So we can conclude that a customer entity does not depend on a loan entity.

## 2. ATTRIBUTES

- Attributes are the properties or characteristics of entities.
- Attributes are represented by means of ellipses.
- Every ellipses represents one attribute and is directly connected to its entity (rectangle).
- E.g. color of a car, balance of an account, price of a product, name of a student etc.

### EXAMPLES



### **Types of Attributes**


**1. Simple/ Single Valued attribute:** Simple attributes are atomic/single values, which cannot be divided further. For example, student's age etc.

**2. Multi-valued attribute:** Multi-value attributes may contain more than one values. For example, a person can have more than one phone number, email\_address, etc. Multivalued attributes are depicted by double ellipse.

**3. Derived attribute:** Derived attributes are the attributes that do not exist in the physical database, but their values are derived from other attributes present in the database. For example, average\_salary in a department should not be saved directly in the database, instead it can be derived. Derived attributes are depicted by dashed ellipse.

### **4. Key Attribute:**


Key attribute represents the main characteristic/attribute of an Entity. It is used to represent Primary key. Ellipse with underlying lines represent Key Attribute



## **RELATIONSHIP**

- There can be relationships between entities, which also can have attributes.
- Relationships are represented by diamond-shaped box.
- Name of the relationship is written inside the diamond-box.
- All the entities (rectangles) participating in a relationship, are connected to it by a line.
- For example, an employee works\_at a department, a student enrolls in a course.

## REPRESENTATION:



E.g. Person owns Car




## TYPES OF RELATIONSHIP(3 TYPES)

### 1. One-to-one: (1:1)

One element of entity A may only be linked to one element of entity B. For example, A university has 1 VC. Or customer will have one mailing address




### EXAMPLE:




### 2. One-to-many (1:N)

- An element of A may be linked to many elements of B.
- one entity is associated with many number of same entity.
- For example, a single customer might place an order for multiple products.



### **3. Many to many (M:N) :**

multiple elements of A linked to multiple elements of B.




eg: Multiple students enrolls in multiple courses.

### **ERD CASE STUDY (Enrollment of Student in Courses)**



Consider the Following requirement List:

1. A student can be enrolled in multiple courses.
2. Every student has a unique roll number and name.
3. Course has a unique courseID , name of the course and course duration.
4. A teacher can teach multiple courses.
5. Teacher has a unique ID , name and department name.

### **ERD EXAMPLE**



## Symbols and Notations




## **LOGICAL DATA MODEL**

A logical data model describes the data in as much detail as possible, without regard to how they will be physically implemented in the database.


- The steps for designing the logical data model are as follows:
- Specify primary keys for all entities.
- Find the relationships between different entities.
- Find all attributes for each entity.
- Resolve many-to-many relationships.
- Normalization.

### **EXAMPLE**



### **Resolve many-to-many relationships**

- To resolve a many-to-many relationship, A new entity comes between the original entities, and this new entity is referred to as an intersection entity.
- Intersection Entity contains the ID's (the integer values) and is referred as "Fact Table".




## **Physical Data Model**

- Physical data model represents how the model will be built in the database.
- A physical database model shows all table structures, including column name, column data type, primary key and foreign key, and relationships between tables.


### Steps for physical data model design

1. Convert entities into tables.
2. Convert relationships into foreign keys.
3. Convert attributes into columns.


## Conceptual Model Design



## Logical Model Design



## Physical Model Design



## Lab Tasks

The Flight Database stores details about an airline's flights and seat bookings. Consider the Following requirement List:

- The airline has one or more airplanes.
  - An airplane has a model number, a unique registration number, and the capacity.
  - An airplane flight has a unique flight number, a departure airport, a destination airport, a departure date and time and an arrival date and time.
  - Each flight is carried out by a single airplane.
  - A passenger has given names, a surname and a unique email address.
  - A passenger can book one or more seats on a flight.
- 
- **For the above mentioned case study**
    1. Identify the Entities.
    2. Specify the attributes for each of the entity.
    3. Specify the relationship among entities.
  - **Draw the Conceptual Model, , Logical Model and Physical Model.**