COMSATS UNIVERSITY ISLAMABAD

ATTOCK CAMPUS



Submitted To

Sir Bilal Haider

Submitted By

Muhammad Ayan Irfan (SP22-BCS-060)

/Zohaib Alam

(SP22-BCS-028)

MINI-COMPILER

Introduction and Overview

Project Overview

This mini compiler is a complete implementation of a programming language compiler written in C#. It demonstrates all major phases of compilation from source code to executable instructions, providing a practical example of compiler construction principles.

Supported Language Features

Data Types: int, float, bool

· Variables: Declaration and assignment

• Expressions: Arithmetic, logical, and comparison operations

Control Flow: if/else statements, while loops
 Built-in Functions: print
 statement for output

Operators:

```
    Arithmetic: +, -, *, /, % o Comparison:
    ==, !=, <, >, <=, >= o
    Logical: &&, | |, !
```

Target Platform

The compiler generates code for a custom stack-based virtual machine (VM), making it platform-independent while maintaining educational clarity.

Educational Value

This implementation serves as a learning tool for understanding:

- Compiler construction phases
- Abstract Syntax Tree (AST) generation
- Symbol table management
- Intermediate code generation
- Virtual machine execution

Compiler Architecture and Design

Seven-Phase Architecture

The compiler follows the traditional compilation pipeline with seven distinct phases:

Phase 1: Lexical Analysis (Tokenization)

Component: Lexer class

Purpose: Converts source code into tokens

Output: List of tokens with type, value, and position information

• **Features**: Handles keywords, identifiers, literals, operators, and comments

Phase 2: Syntax Analysis (Parsing)

Component: Parser class

Purpose: Builds Abstract Syntax Tree from tokens

Algorithm: Recursive descent parser

• Grammar: Supports operator precedence and associativity

Phase 3: Semantic Analysis

Component: Semantic Analyzer class

Purpose: Type checking and symbol table management

 Features: Scope management, type compatibility verification, initialization checking

Phase 4: Intermediate Code Generation

Component: IRGenerator class

• **Purpose**: Generates platform-independent intermediate representation

• Format: Three-address code style instructions

Phase 5: Optimization

Component: Optimizer class

Purpose: Code improvement (basic implementation)

Note: Currently minimal, designed for future enhancement

Phase 6: Code Generation

Component: CodeGenerator class

Purpose: Translates IR to target machine code

Target: Stack-based VM instructions

Phase 7: Execution

Component: StackVM class

Purpose: Executes generated code

Architecture: Stack-based virtual machine with memory management

Design Patterns Used

Visitor Pattern: For AST traversal in semantic analysis

Strategy Pattern: For different optimization techniques

• Interpreter Pattern: For VM instruction execution

Language Specification and Grammar

Lexical Specification Keywords int, float, bool, void, if, else, while, for,

function, return, print, true, false

Operators and Delimiters

Arithmetic: + - * / %

Assignment: =

Comparison: == != < > <= >=

Logical: && | |!

Delimiters: ; , () { } .

Literals

• Integer: Sequences of digits (e.g., 42, 0, 123)

• Float: Numbers with decimal points (e.g., 3.14, 0.5)

- **Boolean**: true or false
- String: Quoted text with escape sequences Grammar Specification

(BNF-style) bnf program → statement*

```
statement
             → varDecl | assignment | ifStmt | whileStmt
          | printStmt | block | ";"
             → type IDENTIFIER ("=" expression)? ";" assignment
varDecl
IDENTIFIER "=" expression ";" ifStmt → "if" "(" expression ")"
statement ("else" statement)?
whileStmt → "while" "(" expression ")" statement
printStmt → "print" expression ";" block
"{" statement* "}"
expression → logicalOr logicalOr → logicalAnd (" | | "
logicalAnd)* logicalAnd → equality ("&&" equality)*
equality \rightarrow comparison (("==" | "!=") comparison)*
comparison \rightarrow term ((">" | ">=" | "<" | "<=") term)* term
\rightarrow factor (("+" | "-") factor)* factor \rightarrow unary (("*" | "/"
| "%") unary)* unary \rightarrow ("!" | "-") unary | primary
           → NUMBER | FLOAT | BOOLEAN | IDENTIFIER
primary
         | "(" expression ")"
          \rightarrow "int" | "float" | "bool"
type
```

Operator Precedence (Highest to Lowest)

1. Unary operators (!, -)

```
2. Multiplicative (*, /, %)
```

- 3. Additive (+, -)
- 4. Relational (<, >, <=, >=)
- 5. Equality (==, !=)
- 6. Logical AND (&&)
- 7. Logical OR (| |)

Type System

- Static Typing: All variables must be declared with explicit types
- Type Compatibility: Automatic promotion from int to float in mixed expressions
- Type Checking: Compile-time verification of type consistency

Implementation Details

Key Data Structures Token Structure

```
csharp public class Token {    public
TokenType Type { get; set; }    public
string Value { get; set; }    public int
Line { get; set; }    public int Column
{ get; set; }
}
```

AST Node Hierarchy

- Base Class: ASTNode with type and position information
- **Expression Nodes**: BinaryOpNode, UnaryOpNode, NumberNode, etc.
- **Statement Nodes**: VarDeclarationNode, AssignmentNode, IfNode, etc. **Symbol Table** csharp public class Symbol { public string Name { get;

```
set; } public DataType Type { get; set; } public int Scope { get; set; }
public int Address { get; set; } public bool IsInitialized { get; set; }
}
```

Error Handling Strategy

- Custom Exception: CompilerException with line/column information
- Error Recovery: Continues parsing after errors when possible
- Semantic Errors: Detailed type mismatch and undeclared variable messages

Memory Management

- Stack-based VM: Uses evaluation stack for expression computation
- Variable Storage: Array-based memory with address allocation
- Scope Management: Hierarchical symbol table with scope stack

Intermediate Representation


The IR uses a simple instruction set:

- Data Movement: LOAD_CONST, LOAD_VAR, STORE_VAR
- Arithmetic: ADD, SUB, MUL, DIV, MOD
- Comparison: CMP_EQ, CMP_NEQ, CMP_LT, etc.
- Control Flow: JUMP, JUMP_IF_FALSE, LABEL
- I/O: PRINT

Virtual Machine Architecture

- Stack-based Execution: Operands pushed/popped from evaluation stack
- Memory Model: Linear array for variable storage
- Instruction Pointer: Sequential execution with jump capabilities
- Type Handling: Dynamic type conversion during arithmetic operations

Diagrams **Activity Diagram:**



Sequence Diagram:





Diagram:

GitHub Repository



https://github.com/UMAR-CUI/Mini-Compiler-SP22.git