

RUKN — Assignment 3 (docs/)

*High-Fidelity Prototype + Updated CRUD + Validation + Dynamic UI +
Implementation Starter*

Group 02 — Zomorodah Bakhit (122200145), Omar Othman (122200162), Rewan Afifi (122200013), Reem Khalil (122200137), Faysal Dabbagh (122200015), Omar Anouti (121200031)

CMPE 372 — User Interface Design — Section 02 (CMPE)

o. Submission package

Item	Where
Figma file (edit)	https://www.figma.com/design/p2AijWf8LQuh9paEm12eaW
Figma prototype (play)	https://www.figma.com/proto/p2AijWf8LQuh9paEm12eaW/?node-id=20-2&starting-point-node-id=20%3A2
Source code (this folder)	Group02_RUKN_Assignment3.zip
Implementation starter (HTML/CSS/JS)	src/dashboard.html
Schema	database/schema.sql (unchanged from A2)
Original A2 doc	docs/RUKN_Assignment_2.md
This document (markdown)	Group02_RUKN_Assignment3.md

Team — Group 02

Name	ID
Zomorodah Bakhit	122200145
Omar Othman	122200162
Rewan Afifi	122200013
Reem Khalil	122200137
Faysal Dabbagh	122200015
Omar Anouti	121200031

1. Project overview

Rukn (رُكن — Arabic for *a corner*) is a bilingual (Arabic / English) web application that gathers three reading experiences into one cozy space:

1. A full in-app e-book reader for **PDF** and **EPUB** files.
2. A passage-linked **journaling system** — select text, attach a reflection right to that passage, or write freeform thoughts in a global journal.
3. A customizable **ambient corner** with three illustrated scenes (Maghrib dusk, Olive grove, Cozy library), five ambient sounds, and a focus timer.

Three conceptual user roles:

- **Guest** — unregistered visitor, time-limited sampling, no persistence.
- **Free registered user** — full reading, full journaling, full library tools, three sounds, one scene.
- **Paid registered user** — every scene, every sound, audiobooks, offline downloads, ad-free.

The visual language is warm, dim, and grounded: deep dusk-brown canvas, hand-set dome-and-minaret silhouettes set against a gradient sky, hanging amber lantern, custom-drawn line icons (no emojis), Cormorant Garamond display + Manrope body + Amiri/Noto Kufi Arabic for RTL content. Every screen ships with glass cards, sub-pixel typography, and a centered-from-button press animation.

2. Final screen set

The shipped prototype contains **8 main screens**, **6 homepage variants**, **4 settings variants**, and **4 modal overlays** — all native Figma layers (no image-fill placeholders) with real prototype reactions wired between them.


#	Screen	Frame ID	Notes
01	Homepage (Maghrib)	20:2	Base scene + 3 dock variants (sounds, timer, scenes open) + 2 alt scenes (Olive 53:2 , Library 53:72).
02	Login / Register	21:2	Split layout, brand vignette with arch + lantern + Gibran pull-quote, form card with tabs.
03	Dashboard	21:39	Glass widget canvas over dusk scene; Continue Reading + Today's Journal + Stats + Dock + Try Premium.
04	Library	22:2	7 unique illustrated book covers; working Filter + Sort dropdown overlays; tabs (My books / Public domain / Collections).
05	Reader	22:114	Sepia paper, left tool rail, right notes panel, footer with progress bar.
06	Journal	22:177	List + detail two-pane; filter pill, sort pill, FAB. Mixed LTR + RTL entries.
07	Settings	22:277	Section nav + active card. Sub-variants: Preferences 69:?, Plan ?, Account data ? — each section pill swaps the entire card content.
08	Premium	68:2	Full-page hero + 4 feature cards + Monthly/Yearly plan toggle + Start Premium CTA.

Modal overlays:

Modal	Trigger	Frame
Sounds window	Dock 🌧️ button	sibling frame, dock icon highlights
Timer window	Dock 🕒 button	sibling frame, dock icon highlights
Scene window	Dock 🎨 button	sibling frame; 3 thumbs swap homepage scene
Library Filter dropdown	Filter pill	OPEN_OVERLAY, X closes
Library Sort dropdown	Sort pill	OPEN_OVERLAY, X closes
Delete-account confirm	Settings → Account data → Delete	modal hosted on dim backdrop

3. Screen reference (renders from the new Figma file)


3.1 Homepage



01 — Homepage (Maghrib scene, dock collapsed)

The arch silhouette reveals a setting sun, a row of domed mosques, two minarets, and a single lit window — all grounded on a continuous dark foreground strip (no floating squares). A brass lantern hangs from the top of the arch with a warm radial glow. The bottom-center dock has three round buttons (Rain → Sound window, Clock → Timer window, Palette → Scene window). Top-right has a ghost **Log in** button and a paper **Begin** primary button — both routed to Login.


3.2 Homepage — Scene window open



01 — Scene window expanded; Maghrib thumbnail highlighted

Clicking the palette dock button navigates to a sibling frame where (a) the palette button gains an amber active highlight and a dot underneath, and (b) the Scene window appears above the dock. Each thumbnail is a real mini illustration (sun + city silhouette / olive trees / books on a shelf), not a swatch. Clicking Olive or Library navigates to one of the alternate base homepages (53:2 or 53:72). The × closes the window back to the base.

3.3 Login / Register



The image shows a dark-themed login/register page for 'RUKN' (رُكن). The page is split into two main panels. The left panel features a large arched window with a warm sunset scene, a hanging lantern, and a desk with books and a small plant. Below the window is a quote by Khalil Gibran. The right panel contains the login/register form with fields for email and password, and buttons for 'Log in' and 'Create account'. A 'Forgot password?' link is also present. The top left has the 'RUKN' logo and a 'Back to home' link. The bottom right has a link for new users to 'Create one'.

• RUKN رُكن ‹ Back to home

Welcome back.

Pull up your chair — your books, notes, and ambience are exactly where you left them.

Log in Create account

EMAIL
you@example.com

PASSWORD
Forgot password?

Log in


New to Rukn? Create one

*"Your daily life is your temple
and your religion."*
— KHALIL GIBRAN

02 — Login

Split-screen: left panel has the brand mark, a smaller arch with its own lantern and city, a windowsill with stacked books + an open book + a small plant, and the Khalil Gibran pull-quote in EB Garamond Italic (deliberately clean, not curly). Right panel hosts the form card — *Welcome back*, segmented Log in / Create account tabs, email + password fields with eye toggle, forgot link, primary submit. Back-arrow top-left returns to Homepage.


3.4 Dashboard



03 — Dashboard

Top bar: greeting eyebrow + *Layla.* in serif. Right cluster: 3 scene quick-switch thumbs, shuffle icon, avatar circle. Three glass cards float over a dimmed dusk arch backdrop: **Continue Reading** with mini book cover + progress, **Today's Journal** with text area + 5 vector mood icons + tag chips + Save, and **Reading Stats** with three big numbers + a 7-day bar chart. Dock at the bottom with seven dock buttons (Continue, Journal, Stats, Sounds, Timer, Scene, Customize). **Try Premium** warm pill bottom-right routes to Screen 08.

3.5 Library




04 — Library

Title baseline reads “**My library** — 7 BOOKS” (inline count badge). Right of the search input are real **Filter** and **Sort** pill buttons that open dropdown overlays. Seven unique book covers, each hand-illustrated:

- *The Prophet* — warm brown, mountain + sun + serif title
- *Pride & Prejudice* — cream with classical column
- *زقاق المدق* (Midaq Alley) — dark with orange arch silhouette + Arabic typography
- *Meditations* — deep blue with two golden columns
- *The Little Prince* — blue with a tiny prince on a planet under stars
- *كليلة ودمنة* (Kalila wa Dimna) — olive with two animal silhouettes
- *CS 101 Notes* — warm brown with a grid pattern overlay

Format badges (EPUB / PDF), AR badges where applicable, and progress bars below each cover.


3.6 Reader



05 — Reader

Sepia paper card centered, chapter eyebrow + serif title + thin rule + four paragraphs of *On Love* — Khalil Gibran (real text, not lorem ipsum). Top mini-bar has back arrow, centered book title + chapter, session timer pill, cog icon, close ×. Left vertical tool rail: highlight, note, bookmark, then a divider, then focus timer, ambient audio, settings. Right notes panel with two example highlight cards (page numbers, excerpts, titles, bodies, hash-tag chips). Footer has prev/next page buttons and a continuous progress bar at 47/96.

3.7 Journal



06 — Journal

Two-pane: entries list (left) with four cards showing date + vector mood icon + title + book reference + excerpt + tag chips. Right pane is the selected entry's detail with edit/share/delete icon row, a warm quote block with **Open in book** link back to the Reader, a serif title, and the entry body. One entry is rendered in Arabic (Mahfouz, *Midaq Alley*) to demonstrate inline RTL support. + **New entry** warm pill bottom-right opens the composer.

3.8 Settings — Account

Settings LAYLA_AMIN

Account
Identity & language

Preferences
Theme, font, sound

Plan
Free or Premium

Account data
Export · Delete

Account
Your identity — visible to you, used for syncing.

DISPLAY NAME

USERNAME

EMAIL

Lowercase letters, numbers, underscore — 3 to 20.

PREFERRED LANGUAGE

✓ English العربية

CHANGE PASSWORD

CURRENT


NEW (MIN 8)

Save changes

07 — Settings (Account)

Section nav left: **Account** (active, amber outline + check icon), Preferences, Plan, Account data. Right card: display name, username, email, preferred language pill group (English check-marked active), change-password dual field, Save changes primary button. The other three section pills are wired — clicking navigates to a sibling frame whose right card swaps to Preferences, Plan, or Account data content (real cards, not placeholders).

3.9 Premium (08 — new)



08 — Premium upgrade

Hero card with stylized dusk scene + sparkle. Big serif headline *Make Rukn fully yours*. Four feature cards in a row: **Audiobooks**, **Full customization**, **Offline downloads**, **Ad-free, always** — each with a vector icon in an amber circle. Plan toggle: **Monthly** (\$5.99) vs **Yearly** (\$49) — the yearly card is highlighted with a “Save 32%” floating badge. **Start Premium** warm CTA + **Maybe later** ghost link. Back-arrow top-left returns to Dashboard.

4. Updated UI – CRUD mapping

Supersedes Section E of Assignment 2. Every action in the final shipped prototype is listed below with its database target and CRUD verb. Table names match the schema in `database/schema.sql` (unchanged from A2).

4.1 Screen 01 — Homepage

User action	Table(s)	CRUD
Land on page	—	None (guest, client-side only)
Click Log in	—	Navigate → Screen 02
Click Begin	—	Navigate → Screen 02
Click dock Sound / Timer / Scene	—	None (UI sibling-frame swap; preview only)
Pick Maghrib / Olive / Library in Scene window	—	None for guests; would set <code>user_preferences.background</code> for registered users

4.2 Screen 02 — Login / Register

User action	Table(s)	CRUD
Submit login form	<code>users</code> (READ), <code>users.last_login</code> (UPDATE)	READ + UPDATE
Submit register form	<code>users</code> , <code>free_users</code> , <code>user_preferences</code> , <code>journals</code> (freeform)	CREATE (atomic — 4 inserts)
Inline email-format validation	—	None (client-only)
Inline password-strength validation	—	None (client-only)
Back to home	—	Navigate → Screen 01

4.3 Screen 03 — Dashboard

User action	Table(s)	CRUD
Load “Continue Reading”	<code>reading_progress</code> ⌕ <code>books</code>	READ
Click Resume	<code>reading_progress.last_read_at</code>	UPDATE + navigate
Save quick journal from widget	<code>journal_entries</code> , <code>tags</code> , <code>journal_entry_tags</code>	CREATE
Load Reading Stats	<code>reading_progress</code> (aggregated)	READ
Toggle a sound chip	<code>user_preferences.ambient_sound</code>	UPDATE
Drag volume slider	<code>user_preferences.sound_volume</code>	UPDATE (debounced)
Click avatar	—	Navigate → Settings
Click Try Premium pill	—	Navigate → Screen 08
Click locked Customization / Audiobook widget	—	Navigate → Screen 08
Sidebar Library / Journal / Settings	—	Navigate
Focus timer start / pause / reset / skip	—	UI state only (future: <code>reading_progress.total_seconds_read</code>)

4.4 Screen 04 — Library

User action	Table(s)	CRUD
Load My Books tab	<code>books</code> WHERE <code>uploaded_by = user</code> , <code>reading_progress</code>	READ
Load Public Domain tab	<code>books</code> WHERE <code>is_public_domain = TRUE</code>	READ
Load Collections tab	<code>collections</code> , <code>collection_books</code> , <code>books</code>	READ
Search input	<code>books</code> (LIKE on title / author)	READ
Filter pill → dropdown → pick a format	<code>books</code> filtered	READ
Sort pill → dropdown → pick an option	<code>books</code> re-ordered	READ
Click book cover	<code>reading_progress</code> (created if missing)	READ + CREATE-on-first-open
Upload button → modal → submit	<code>books</code>	CREATE
Long-press book → Remove	<code>books</code> (cascades)	DELETE
Add to collection (from book menu)	<code>collection_books</code>	CREATE
Create collection (Collections tab)	<code>collections</code>	CREATE
Rename collection	<code>collections.name</code>	UPDATE
Remove book from collection	<code>collection_books</code>	DELETE

4.5 Screen 05 — Reader

User action	Table(s)	CRUD
Open a book	<code>reading_progress</code> ⇌ <code>books</code> + load file	READ
Auto-save progress every 30 s	<code>reading_progress</code> (<code>current_page</code> , <code>pages_read</code> , <code>total_seconds_read</code> , <code>last_read_at</code>)	UPDATE
Click prev / next page	same	UPDATE
Highlight a passage (color only)	<code>highlights</code>	CREATE
Change highlight color	<code>highlights.color</code>	UPDATE
Delete a highlight	<code>highlights</code> (linked entries survive with <code>highlight_id = NULL</code>)	DELETE
Highlight + Add note overlay → Save	<code>highlights</code> (insert), <code>journals</code> (book — INSERT IGNORE), <code>journal_entries</code> , <code>tags</code> , <code>journal_entry_tags</code>	CREATE (1–4 inserts)
Bookmark icon	<code>bookmarks</code>	CREATE / DELETE (toggle)
Open right notes panel	<code>highlights</code> , <code>journal_entries</code> for current chapter	READ
Adjust display settings (font / theme)	<code>user_preferences</code> (or future per-book overrides)	UPDATE
Back to library	—	Navigate
Close ×	—	Navigate → Dashboard

4.6 Screen 06 — Journal

User action	Table(s)	CRUD
Load All entries / By book / Freeform tab	<code>journal_entries</code> ⌵ <code>journals</code> ⌵ <code>highlights</code> , <code>books</code>	READ
Search entries	LIKE on <code>journal_entries.content</code> / <code>title</code> , <code>tags.name</code>	READ
Sort newest / oldest	same, <code>ORDER BY entry_date</code>	READ
Filter pill → pick a tag	<code>journal_entry_tags</code> ⌵ <code>tags</code>	READ
Click entry card	reads the row + its tags	READ
Open in book	—	Navigate → Reader at <code>highlights.page_number</code>
+ New entry FAB → composer → Save	<code>journals</code> (freeform), <code>journal_entries</code> , <code>tags</code> , <code>journal_entry_tags</code>	CREATE
Edit (pen icon) → inline → Save	<code>journal_entries.title</code> / <code>content</code> / <code>updated_at</code>	UPDATE
Add a tag inside an entry	<code>tags</code> (INSERT IGNORE), <code>journal_entry_tags</code>	CREATE
Remove a tag chip	<code>journal_entry_tags</code>	DELETE
Delete (trash icon) → confirm	<code>journal_entries</code> (cascades to <code>journal_entry_tags</code> ; <code>highlights</code> survive)	DELETE

4.7 Screen 07 — Settings (4 sections)

User action	Table(s)	CRUD
Open Settings (any section)	<code>users</code> , <code>user_preferences</code>	READ
Account → Update display name / username / email	<code>users</code>	UPDATE
Account → Pick preferred language pill	<code>users.preferred_lang</code>	UPDATE
Account → Change password (current + new)	<code>users.password_hash</code> (after verify)	UPDATE
Account → Save changes button	commits the dirty fields above	UPDATE
Preferences → Pick a theme card	<code>user_preferences.theme</code>	UPDATE
Preferences → Pick a reading font	<code>user_preferences.font</code>	UPDATE
Preferences → Font-size slider	<code>user_preferences.font_size</code>	UPDATE
Preferences → Default ambient sound pill	<code>user_preferences.ambient_sound</code>	UPDATE
Preferences → Default volume slider	<code>user_preferences.sound_volume</code>	UPDATE
Plan (free) → Start Premium	<code>paid_users</code> (INSERT), <code>free_users</code> (DELETE)	CREATE + DELETE (transactional)
Plan (paid) → Cancel subscription	<code>paid_users</code> (DELETE), <code>free_users</code> (INSERT)	DELETE + CREATE
Account data → Download .json	All user-owned tables	READ-only (assembled client-side, downloaded as a blob)
Account data → Delete account → confirm-phrase → Yes	<code>users</code>	DELETE (cascades through every owned table)

4.8 Screen 08 — Premium upgrade

User action	Table(s)	CRUD
Toggle Monthly / Yearly	—	None (UI state)
Click Start Premium	<code>paid_users</code> (INSERT), <code>free_users</code> (DELETE)	CREATE + DELETE
Click Maybe later / back-arrow	—	Navigate → Dashboard

4.9 Cascade summary

`DELETE FROM users WHERE user_id = ?` removes the row and, via `ON DELETE CASCADE`, also removes:

- `free_users` *or* `paid_users` row
- `user_preferences`
- `reading_progress`
- `highlights` (and their `journal_entry.highlight_id` references go NULL — entries survive)
- `bookmarks`
- `journals` (and their `journal_entries`, which cascade their `journal_entry_tags`)
- `tags`
- `collections` (and their `collection_books`)

Books that the user uploaded survive with `uploaded_by = NULL` (`ON DELETE SET NULL`).

5. Validation logic

Every form in the prototype layers three validation passes: **HTML5 attributes** (cheap, in-browser, kicks in before JS loads), **JavaScript rules** (richer messaging, debounced live-checks), and (in a real backend) server-side re-validation. The table below covers every input the user can touch.

5.1 Field-by-field rules

Screen	Field	HTML5 attr	JS rule	UI on failure
Register	Username	<code>required pattern="[a-z0-9_]{3,20}"</code>	Lowercase letters / numbers / underscore, 3–20 chars	Red border, inline  Use lowercase letters, numbers, underscore – 3 to 20.
Register	Email	<code>required type="email"</code>	RFC pattern + DNS-style TLD	 Please enter a valid email address.
Register	Password	<code>required minlength="8"</code>	≥ 8 chars AND contains a digit or symbol	 At least 8 characters with one number or symbol.
Register	Confirm password	<code>required</code>	Must equal Password field	 Passwords don't match.
Login	Email	<code>required type="email"</code>	Same as register	Same
Login	Password	<code>required</code>	Non-empty	 Password is required.
Login	Submit	—	Both fields pass before POST allowed	Submit visually disabled (opacity 0.4, <code>cursor:not-allowed</code>)
Dashboard journal widget	Body	<code>required minlength="3" maxlength="500"</code>	3–500 trimmed chars; live char counter	 Please write something before saving. /  Entry is too long (max 500).
Dashboard journal	Tag input	<code>pattern="[a-z0-9\-\]+" maxlength="20"</code>	Lowercase letters / numbers / dash, max 5 tags / entry	Red-mark toast: Lowercase, letters/numbers/dash only.
Reader → Add Note overlay	Body	<code>required minlength="3"</code>	Same as dashboard	Same
Reader add note	Tags	Same	Same	Same
Journal → New Entry overlay	Title	<code>maxlength="80"</code>	Optional; defaults to “Untitled”	—
Journal new entry	Body	<code>required minlength="3"</code>	Same	Same

Screen	Field	HTML5 attrs	JS rule	UI on failure
Journal new entry	Tags	Same	Same	Same
Library → Upload Book modal	File picker	required accept=".pdf,.epub"	MIME-type sniff + ≤ 50 MB	⚠ Only PDF or EPUB, up to 50 MB.
Upload book	Title	required maxlength="255"	Non-empty	⚠ Title is required.
Upload book	Author	maxlength="255"	Optional	—
Settings → Account	Display name	maxlength="40"	Non-empty when changed	⚠ Display name can't be empty.
Settings account	Username	pattern="[a-z0-9_]{3,20}"	Same as register	Same
Settings account	Email	type="email"	Same as register	Same
Settings account	Current password	required when New is filled	If New is filled, Current must be too	⚠ Enter your current password to change it.
Settings account	New password	minlength="8"	Same as register	Same
Settings → Account data → Delete confirm	Confirm-phrase input	—	Exact case-insensitive match of delete my account	Yes button disabled until phrase matches

5.2 Error-state visual convention

All error states share one visual language across the system:

- **Input border:** 1px solid `rgba(226, 107, 90, 0.50)` (soft red on idle, deepens on focus).
- **Inline error message:** 12 px Manrope Medium, color `#E26B5A`, ⚠ icon prefix, slides in below the field over 200 ms.
- **Disabled primary button:** opacity 0.40, `cursor: not-allowed`, no hover transform.
- **Toast** (for short rule violations like tag formatting): soft red stripe on left, auto-dismiss after 2.2 s, bottom-center position.
- **Required-field hint** (for empty submit attempt): focus jumps to the first invalid field, page scrolls to it, error message reads with a screen reader.

5.3 Required-field validation example (Login)

When the user clicks **Log in** with either field empty:

1. The form's `noValidate` is OFF, so the browser blocks submit and focuses the first invalid field.
2. The JS handler also adds `.has-error` to the field's wrapper, which paints the red border via `.field.has-error input` selector.
3. The inline error span is filled with the rule text and `[hidden]` is removed.
4. The Log in button stays disabled until both `emailValid && pwValid`.

5.4 Incorrect-input handling example (Register password)

Live-validation triggers on `input` event (every keystroke):

- `< 8 chars` → red border, message `At least 8 characters with one number or symbol.`
- `≥ 8 chars` but no digit / symbol → red border, same message.
- Passes both → border returns to default; if Confirm has a value, re-check that it still matches.

5.5 Server-side error handling (Login wrong password)

On a 401 response the form clears the password field, refocuses it, and shows a non-blocking banner above the card:

⚠ Email or password is incorrect.

The banner auto-dismisses on the next `input` event.

6. Dynamic UI behavior mapping

Two perpendicular axes: (a) **dynamic content** that updates the DOM without a page navigation, and (b) **asynchronous interactions** where loading / saving state is visible.

6.1 Dynamic content (DOM updates without navigation)

Location	Trigger	What updates	Mechanism
Dashboard → Recent Entries list	User saves an entry from the Today's Journal widget	New <code></code> prepended with fade-in; entries counter pill increments	Imperative DOM insertion + CSS keyframe <code>entry-in</code>
Dashboard → Today's Journal textarea	User types	Live <code>n / 500</code> char counter; error state clears as soon as value becomes valid	<code>input</code> listener
Dashboard → Today's Journal tags	User types tag + Enter	Tag chip appended to chip list; input clears	Keydown handler + in-memory <code>draft.tags</code> re-render
Dashboard → Continue Reading	User clicks Resume	Progress bar width animates to new % via <code>transition: width 600ms on --p</code>	CSS custom-property transition
Dashboard → Reading Stats	After any save	Streak / pages / hours recompute from <code>reading_progress</code> aggregate	Re-render after CRUD write
Dashboard → Sound chips	User clicks a chip	Active chip swaps via <code>.is-active</code> toggle	Click handler + class toggle
Dashboard → Focus Timer	User clicks play	<code>mm:ss</code> counts down every second; play icon swaps to pause	<code>setInterval(tick, 1000)</code>
Dashboard → Theme cycler	User clicks sun icon	Entire scene re-themes via <code>body[data-theme]</code> swap	CSS custom-property cascade
Dashboard → Locked widget	User clicks Try Premium	Premium screen navigates in	Sibling-frame nav in Figma; modal toggle in HTML starter
Premium → Start Premium	User confirms	<code>data-tier</code> flips to <code>paid</code> , locked widgets unlock, pill disappears	Attribute toggle, CSS selectors do the rest
Library → Tab switch	Click My books / Public domain / Collections	Book grid swaps content	Component variant render
Library → Search input	Live typing	Grid filters live across title + author	<code>input</code> event + array filter

Location	Trigger	What updates	Mechanism
Library → Filter pill / Sort pill	Click pill	Dropdown overlay slides in; X closes	OPEN_OVERLAY in Figma; class toggle in HTML
Library → Upload modal success	File ingested	New book card prepends to the grid	Imperative DOM insertion
Library → Long-press book	Mouse-down ≥ 600 ms	Context menu fades in over the card	Pointer timer + <code>.is-menu</code> class
Reader → Text selection	User selects text	Highlight popover appears anchored to the selection rect	<code>selectionchange</code> event
Reader → Highlight color pick	User clicks a swatch	Selection becomes a stroked span with <code>data-color</code>	DOM mutation + CSS
Reader → Add Note save	User saves	Right notes panel adds a new card; bottom toast confirms	State update + animated insert
Reader → Bookmark icon	User clicks	Icon fills (active state); toast confirms	Class toggle + toast spawn
Reader → Footer page input	User types page # + Enter	Reader jumps to that page; progress bar animates	Form submit + state update
Journal → Entry click	User clicks list card	Right detail panel updates to that entry	State change + conditional render
Journal → Filter / Sort tab	Click	List re-filters / re-orders	Filter on entries array
Journal → Search input	Live typing	List filters across title + body + tags + book	Filter on entries array
Journal → New entry save	User saves	New entry prepends; selection moves to it; toast	Imperative + state update
Journal → Delete	User confirms in modal	Entry disappears; selection moves to next	Filter + state update
Settings → Section pill	Click Account / Prefs / Plan / Account data	Right card swaps	Sibling-frame nav in Figma; conditional render in HTML
Settings → Theme card	Pick a theme	Entire stage re-themes immediately via <code>data-palette</code> on <code><html></code>	Attribute toggle + CSS cascade

Location	Trigger	What updates	Mechanism
Settings → Save changes	Click Save	“Saved ✓” status pill appears next to button, fades after 2.5 s	<code>setTimeout</code> -cleared state
Settings → Upgrade	Start Premium	Plan section re-renders as the Paid variant; tier flips	Conditional render driven by <code>user.tier</code>

6.2 Asynchronous interactions (loading / saving feedback)

Location	Operation	Visible UX feedback
Login submit	Authenticate user	Button label swaps to “Signing in...”, spinner glyph replaces the arrow, button disabled. On success → navigate. On failure → red banner above form, password field cleared and refocused.
Register submit	Create account (4 inserts atomic)	Same pattern — “Creating your corner...” while the transaction runs.
Library initial load	Fetch user’s books + progress	6 shimmer card skeletons render first; replaced by real cards on resolve.
Library upload	Upload book file → CREATE	Modal shows a 0–100 % progress bar while the file uploads; success → modal closes + toast <code>Book added to your library</code> .
Library cover lookup	Public-domain default cover from external service	Cover slot shows a soft amber shimmer until the URL resolves.
Reader open	Stream book PDF/EPUB	Page shows shimmer skeleton lines while the file streams in; cancellable.
Reader auto-save	UPDATE reading_progress every 30 s	Tiny “saved · just now” indicator in the top mini-bar (never blocks).
Reader Add Note save	INSERT highlight + journal_entry + tags	Save button label → “Saving...”, disabled. On success → overlay closes + toast <code>Note saved</code> .
Journal new entry save	Same	Same — “Saving...” → close + toast.
Settings save	UPDATE one or more rows	Save button → “Saving...” → green ✓ check, fades after 2.5 s.
Settings export	READ all user data	Button → “Preparing...” then triggers JSON blob download.
Premium → Start Premium	INSERT paid_users + DELETE free_users	Button → “Activating...” then on success: full-screen amber wash for ~250 ms, then modal closes and dashboard reloads in Paid variant.

6.3 Where reactive state lives

For the HTML starter (`src/dashboard.js`) the rule is one **immutable state object** mirroring the SQL tables, mutated only through CRUD functions, persisted with `localStorage.setItem(STORAGE_KEY, JSON.stringify(state))` after every write. A render function for each widget reads from `state` and replaces its container's `innerHTML` . No virtual-DOM library; the data model is small enough that full-widget re-renders stay under 16 ms.

For the Figma prototype, “state” is **frame variants**: each meaningful state of the homepage / settings / library is its own frame, and click reactions navigate between them. Smart Animate transitions ease the visual continuity at 250 ms `EASE_OUT` .

7. Design system reference

Authored from scratch — every token below is defined in `prototype/styles.css` , `prototype/journal.css` , `prototype/settings.css` , and `src/dashboard.css` . No external design framework was used.

7.1 Color palette

Token	Desert Dusk	Olive Grove	Candlelight	Rose Vellum
<code>--night-deep</code>	<code>#15090A</code>	<code>#0E1610</code>	<code>#0F0A06</code>	<code>#1B0E1A</code>
<code>--plum</code>	<code>#3F2A4A</code>	<code>#2E3A2E</code>	<code>#1F140C</code>	<code>#2A1830</code>
<code>--terracotta</code>	<code>#C66B3D</code>	<code>#8A7A3F</code>	<code>#9C4F1E</code>	<code>#B8466A</code>
<code>--sky-sun</code>	<code>#F2B36A</code>	<code>#D9B86A</code>	<code>#F2C77A</code>	<code>#F0A6A0</code>
<code>--paper</code>	<code>#F6EDD8</code>	<code>#F6EDD8</code>	<code>#F6EDD8</code>	<code>#F6EDD8</code>

On-glass text levels: `--on-glass` `#F6EDD8` , `--on-glass-dim` `rgba(246,237,216,0.78)` , `--on-glass-soft` `rgba(246,237,216,0.55)` .

Semantic: success `#8FCB9B` , error `#E26B5A` , highlight swatches `#F2D580` / `#D88A8E` / `#A8B070` / `#8FB6D8` .

7.2 Typography

Role	Family	Weights
Display (headings, book titles, large numbers)	Cormorant Garamond	400, 500
Body sans (UI, buttons, paragraphs)	Manrope	400, 500, 600, 700
Quotes, italics on quotes	EB Garamond Italic	400, 500
Arabic display + reading	Amiri	400, 700
Arabic UI	Noto Kufi Arabic	400, 500, 600
Mono (delete-confirm phrase only)	JetBrains Mono	400

Scale: Eyebrow 10–11 px (UPPER, letter-spacing 0.12em) · Caption 11–12 · Body small 12.5–13 · Body 13.5–14 · Widget title 18–22 · Display H1 26–38 (`clamp(28px, 3vw, 38px)`) · Display XL 56.

7.3 Spacing

4-px base. Allowed values: **4 / 6 / 8 / 10 / 12 / 14 / 16 / 18 / 22 / 24 / 28 / 32 / 36 / 40 / 48**.

7.4 Geometry

`--r-sm` 8 (chips), `--r-md` 14 (inputs, most cards, buttons), `--r-lg` 20 (modal, hero), `--r-pill` 999 (pills, FAB, lang toggle).

7.5 Surfaces (glassmorphism)

```
--glass-fill:      rgba(20, 12, 7, 0.78);
--glass-fill-2:    rgba(28, 18, 11, 0.86);
--glass-stroke:    rgba(247, 239, 224, 0.10);
--glass-stroke-2:  rgba(247, 239, 224, 0.18);
--glass-shadow:    0 24px 60px -22px rgba(0,0,0,0.6),
                  0 1px 0 rgba(247,239,224,0.05) inset;
backdrop-filter:   blur(16-28px) saturate(120%);
```

7.6 Buttons

Variant	Use
Primary — paper fill, ink text, slight lift on hover	Save, Resume, Start Premium, Begin
Ghost — transparent fill, dim text	Cancel, Discard, Maybe later, Back
Danger — red fill, light text	Delete account, Delete entry
Icon — square 36/40, ghost-tinted	Top bar utilities, Reader tools
FAB pill — primary + pill radius, fixed pos	+ New entry, + Add tag
Premium pill — warm fill, paper text + sparkle icon	Try Premium floating

All buttons share: `transition: transform 220ms / box-shadow 220ms / background-color 220ms`, hover `translateY(-1px)`, active `scale(0.94)` with a center-originating `center-pulse` animation, focus-visible 2 px sky-sun outline at 2 px offset.

7.7 Iconography

Custom-drawn vector strokes (1.6 px, round caps, 24 × 24 box). No emoji is used as UI chrome anywhere in the app. Specific glyphs in the system: home, book, feather (journal), user, sliders, sparkle, warn, check, search, filter, sort, chevron, close, back, next, play, pause, reset, skip, rain (cloud + drops), clock, palette, download, upload, headphones, shield, edit, share, trash, plus, arrow, moon, cup, drop, leaf, music, heart, highlight, note, cog.

8. Implementation starter (HTML + CSS + JS)

Location: `src/dashboard.html` , `src/dashboard.css` , `src/dashboard.js` .

A fully working, framework-free implementation of the Dashboard screen. Vanilla DOM API, no build step, no transpiler. Renders correctly in any modern browser.

8.1 How to run it

```
# From the submission root:  
cd src  
python -m http.server 8000  
# then open http://localhost:8000/dashboard.html
```

You can also just double-click `src/dashboard.html` — most things work, but `localStorage` is blocked from `file://` URLs in some browsers, so persistence won't survive a reload. Use the python server above if you want the data to persist.

8.2 What it demonstrates

Submission requirement	Where it lives
Semantic HTML layout	<code>dashboard.html</code> — <code><header></code> , <code><nav></code> , <code><main></code> , <code><section></code> , <code><article></code> , <code><aside></code> , <code><footer></code> , ARIA roles, <code><label for></code> pairings throughout
Responsive Grid / Flexbox	<code>dashboard.css</code> — <code>display: grid</code> for widget canvas (12-col) + media queries at 1100 px and 720 px
HTML5 + JS form validation	<code><textarea required minlength="3" maxlength="500"></code> + <code>VALID.journalEntry()</code> and <code>VALID.tagName()</code> rules + inline <code>△</code>
Dynamic content rendering	<code>renderEntries()</code> , <code>renderStats()</code> , <code>renderSounds()</code> , <code>renderTimer()</code> — re-run on every state change
Async-style feedback	Toast spawn, save-button label swap, animated chip insertion
CRUD operations	<code>CRUD.createEntry</code> , <code>readTodayEntries</code> , <code>readStats</code> , <code>updateTheme</code> , <code>updateSound</code> , <code>updateLanguage</code> , <code>upgradeToPaid</code> , <code>deleteEntry</code> — each annotated with its SQL equivalent in a comment
Persistence (no backend)	<code>localStorage.setItem(STORAGE_KEY, JSON.stringify(state))</code> after every change

8.3 End-to-end flows you can drive in the browser

1. **CREATE → READ → DELETE journal entry.** Type into the textarea, pick a mood, add tags by pressing Enter, click **Save entry**. The entry appears in Recent Entries. Reload — it's still there. Click × — it's gone.
2. **UPDATE preferences.** Click the sun icon to cycle theme (Dusk → Olive → Candlelight → back). The whole scene re-themes. Reload — your choice persists.
3. **UPDATE sound + volume.** Click any chip, drag the volume slider. Both persist.
4. **Focus Timer.** Press ► — the timer actually counts down second by second. Reaches 00:00 → switches to a 5-minute break with a toast.
5. **Premium upgrade flow.** Click the **Try Premium** pill → modal opens → toggle Monthly / Yearly → **Start Premium** → modal closes, locked widgets unlock, pill disappears. Reload — still Premium.
6. **Validation.** Submit an empty entry → `△` inline error. Type 2 characters → `△` "A little more". Try a tag with uppercase → red-mark toast with the rule.

8.4 Map to A2 schema

Every CRUD function in `dashboard.js` is annotated:

```
// CREATE – INSERT INTO journal_entries (journal_id, content, ...)  
createEntry({ content, mood, tags }) { ... }  
  
// UPDATE – UPDATE user_preferences SET theme=? WHERE user_id=?  
updateTheme(theme) { ... }  
  
// DELETE – DELETE FROM journal_entries WHERE entry_id=?  
deleteEntry(entry_id) { ... }
```

In a backend-connected version, replacing `localStorage` with `fetch('/api/...')` against an Express / Flask endpoint running `crud_queries.sql` would not require **any** UI change.

9. Submission package layout

```
Group02_RUKN_Assignment3/
├─ Group02_RUKN_Assignment3.pdf ← this document (rendered)
├─ Group02_RUKN_Assignment3.md ← markdown source of this document
├─ figma/
│   └─ README.md ← live Figma + prototype URLs
├─ database/
│   ├── schema.sql ← from A2, unchanged
│   └─ crud_queries.sql ← from A2, unchanged
├─ src/ ← implementation starter
│   ├── dashboard.html
│   ├── dashboard.css
│   ├── dashboard.js
│   └─ README.md ← "how to run" instructions
├─ prototype/ ← full React/JSX prototype (7 HTML screens)
│   ├── Homepage.html
│   ├── Login.html
│   ├── Dashboard.html
│   ├── Library.html
│   ├── Reader.html
│   ├── Journal.html
│   ├── Settings.html
│   └─ *.jsx, *.css
├─ docs/
│   ├── RUKN_Assignment_2.md ← original (schema, ER diagram, CRUD)
│   └─ RUKN_Assignment_3.md ← supporting doc (same content, internal)
└─ screenshots/
    ├── 01_homepage_v2.png
    ├── 01_homepage_scenes_v2.png
    ├── 02_login_v2.png
    ├── 03_dashboard_v2.png
    ├── 04_library_v2.png
    ├── 05_reader_v2.png
    ├── 06_journal_v2.png
    ├── 07_settings_v2.png
    └─ 08_premium_v2.png
```

9.1 Filename convention

The folder is named `Group02_RUKN_Assignment3` and zipped to `Group02_RUKN_Assignment3.zip` — matching the assignment 3 spec.

10. Change-log against Submission 2

- **+2 screens.** Settings (07) absorbs everything previously labeled “Profile & Settings” plus the customization controls. Premium (08) is a new full-page upgrade screen.
- **–2 screens (folded into widgets).** Insights → Reading Stats widget on Dashboard. Customization → Settings → Preferences section.
- **+5 overlay modals** properly speced: Library Filter, Library Sort, Reader Add-Note, Journal New-Entry composer, Delete-account confirm.
- **+6 homepage variants** (Maghrib base, Sounds-open, Timer-open, Scenes-open, Olive base, Library base) so the dock buttons and scene picker are pixel-true to a real interaction (active highlight syncs with the open window).
- **Vanilla implementation starter** (`src/dashboard.html`) replaces a React-only render.
- **Bilingual Journal entry.** One entry written in Arabic (Mahfouz, *Midaq Alley*) renders RTL automatically inside the LTR page — proves the bidi support claimed in A2 Section A actually works in the UI.
- **CRUD mapping reorganized by final screen.** Section 4 above replaces A2 Section E line-by-line.
- **Real vector icons** everywhere (no emoji in UI chrome).
- **Real book-cover illustrations** for all 7 Library books (no flat color swatches).
- **EB Garamond Italic** for pull-quotes (replaces the curlier Cormorant Italic).
- **EN / AR top-bar pill removed** from every screen (the language preference still lives in Settings → Account, where it belongs).