

Advanced Resources

Data sources, explicit dependencies,
dynamic blocks and the resource
lifecycle — the tools that make real-world
code robust.

Data sources

depends_on

Dynamic blocks

Lifecycle

Lab 07

Today's roadmap



1 • Data sources

Query existing resources instead of recreating them.



2 • Explicit dependencies

When the graph can't infer order — `depends_on`



3 • Dynamic blocks

Generate repeatable nested blocks from data.



4 • Lifecycle & Lab 07

Control create/destroy; finish the app t

01

Data Sources

Read the world instead of rebuilding it.

— QUERY, DON'T CREATE

Data sources

Fetch information about existing resources or the provider itself — resolved at `plan` time.

- Reuse infra managed elsewhere
- Fetch dynamic values (IDs, latest image...)
- Reference like resources:
`data.type.name.attr`

HCL

```
data "azurerm_client_config" "current" {}

resource "azurerm_key_vault" "kv" {
  tenant_id = data.azurerm_client_config.current.tenant_id
  # ...
}
```

👁 They only **read** — never create or

Using data sources well



Filter precisely

Query by tag, name or id —
don't fetch more than you need.



Use sparingly

Every data source is a lookup at
plan time — too many slow you
down.



Document use

Make it clear why a
exists for the next

02

Dependencies, Dynamic Block Lifecycle

Fine control over how Terraform builds and changes things.

Explicit dependencies

Terraform infers order from references. Sometimes a hidden dependency needs to be stated.

- Use when B relies on A's **behavior** but not its data
- `depends_on` forces A to finish first
- Last resort — it makes plans more conservative

HCL

```
resource "azurerm_role_assignment" "kv" {  
  # ...  
  depends_on = [  
    azurerm_key_vault.kv  
  ]  
}
```

Dynamic blocks

Generate repeatable nested blocks (like `ip_rule` or `setting`) from a collection.

- **label** — which nested block to build
- **for_each** — the collection to iterate
- **iterator/content** — the generated body

HCL

```
dynamic "ip_rule" {  
  for_each = var.allowed_cidrs  
  content {  
    ip_range = ip_rule.value  
  }  
}
```

The lifecycle block



create_before_destroy

Build the replacement first, then remove the old one — no downtime.



prevent_destroy

Reject any plan that would destroy this resource. Guard costly things.



ignore_changes

Let an external process change certain attributes (e.g.



`ignore_changes = [tags]` is exactly why your labs say "ignore manual tag changes."

 LIVE DEMO

Data sources & lifecycle in action

Add a data source and a `lifecycle` block to the Azure project, then plan to see how behavior changes.

Provider · azurerm

■ LAB 07 · 30-40 MIN

App Services & PostgreSQL

Finish the application tier — App Services on a plan and a PostgreSQL database — using data sources and `ignore_changes` on tags.

You'll practise: data sources · dependencies · `lifecycle` · dynamic blocks

Key takeaways

✓ Data sources read

Reuse existing infra & dynamic values.

✓ depends_on is a last resort

For hidden, behavior-only dependencies

✓ Lifecycle gives control

Zero-downtime, protection, drift tolerance.

✓ Next up

Session 08 — importing existing infra.



Questions?

Up next — [Session 08: Importing Existing Infrastructure.](#)