



# **Data Structure**

## **Lab Session #09: Internal Sorting 2**

**U Kang**  
**Seoul National University**



# Goals

- Implement **“Heap Sort”**
  - Complete “MinHeap” class in MinHeap.java
  - Complete “HeapSort” class in HeapSort.java
  
- Print the sample output corresponding to the sample input
  - Please carefully observe the I/O specification.



# Notice

- After implementing “HeapSort”, check if your program works well.
  - Check sample input and output files in the ‘testcase’ folder.
  - Test your program by using it.
- When you finish implementing the program, you can leave.
  - But, you need to stay for at least an hour.
- Check your attendance.



# Build a project

- Download the project for this lab from eTL.
- Extract the project, and open it in IntelliJ.
  - See the slide of 1<sup>st</sup> lab session to check how to open the project in IntelliJ.



# Heap Sort

- Given a series of integers, build min-heap.
- Extract values from the top until the tree empty.
- Refer to **lec12** if you don't remember heap.




Figure. Min-heap



# Function that you need to fill in

## ■ In 'MinHeap':

- ❑ insert
- ❑ remove
- ❑ find
- ❑ siftDown
- ❑ removeMin

## ■ In 'HeapSort':

- ❑ add
- ❑ remove
- ❑ sort



# I/O Specification

## ■ add

Input format	Output format
add 3	(heap_state)
Description	
<ul style="list-style-type: none"><li>- Add a value into the min-heap.</li><li>- Value is an integer.</li></ul>	
Example Input	Example Output
add 3	3
add 5	3 5



# I/O Specification

## ■ remove

Input format		Output format	
remove		(heap_state)	
Description			
<div><div>- Remove a value from the min-heap.</div><div>- Value is an integer.</div></div>			
Example Input		Example Output	
remove 15		1 1 9 3 10 15 20 5 (last state) 1 1 5 3 10 9 20 (after remove 15)	





# I/O Specification

## ■ sort

Input format	Output format
sort_a/sort_d	(sorted integers)  (heap_state)
Description	
<ul style="list-style-type: none"><li>- Print out values in ascending(sort_a)/descending(sort_d) order using the min-heap.</li><li>- (Sorted integers) is a sequence of integers sorted in ascending/descending order.</li><li>- After sorting, heapify all elements again and print heap_state.</li></ul>	
Example Input	Example Output
sort_a/sort_d	1 3 5 9 10 15 / 20 9 7 5 3 1 1 1 3 9 5 10 15 / 1 3 1 5 9 7 20



# Sample Input

```
add      3
add      5
add      15
add      9
add      10
add      1
sort_a
add      20
add      1
remove   15
add      7
remove   10
sort_d
```



# Sample Output

op	operand	heap_state
add	3	3
add	5	3 5
add	15	3 5 15
add	9	3 5 15 9
add	10	3 5 15 9 10
add	1	1 5 3 9 10 15
sort_a	1 3 5 9 10 15	1 3 9 5 10 15
add	20	1 3 9 5 10 15 20
add	1	1 1 9 3 10 15 20 5
remove	15	1 1 5 3 10 9 20
add	7	1 1 5 3 7 9 20
remove	10	1 1 5 3 7 9 20
sort_d	20 9 7 5 3 1 1	1 3 1 5 9 7 20

Heap\_state may vary depending on how you heapify after sorting, but you have to make sure every heap\_state follows heap property.



# Questions?