

A TECHNICAL PROJECT REPORT ON

STUDENT RECORD FILE STORE

An Object-Oriented Desktop Management System with Robust File Persistence & Integrated Data Structures

Submitted in partial fulfillment of the academic requirements for the degree of

Bachelor of Technology
in
Computer Science and Engineering

Student Name:	Sasanka Sekhar Kundu
Roll Number:	150096725118
Academic Program:	B.Tech Computer Science and Engineering
Technology Stack:	Java 21 (LTS) & Java Swing GUI

[DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING]
[INSTITUTION / UNIVERSITY NAME PLACEHOLDER]
Academic Year 2025 – 2026

CERTIFICATE OF ORIGINAL WORK

This is to certify that the academic technical project entitled "STUDENT RECORD FILE STORE" is a bona fide record of independent work carried out and successfully implemented by Sasanka Sekhar Kundu (Roll Number: 150096725118) in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in Computer Science and Engineering during the academic session 2025–2026.

The project satisfies the mandatory academic guidelines prescribed by the curriculum, demonstrating the practical integration of Java File Handling, Collections Framework (ArrayList), Checked Exception Handling, Object-Oriented Programming (Abstraction, Inheritance, Polymorphism, Interfaces), and Core Data Structures and Algorithms (Stack-based Undo, FIFO Operation Queue, Linear and Binary Search, and Comparator Sorting).

Project Supervisor / Guide
[Faculty Name Placeholder]
Dept. of CSE

Internal Examiner
[Signature / Date]
Dept. of CSE

Head of the Department
[Faculty Name Placeholder]
Dept. of CSE

CANDIDATE DECLARATION

I, Sasanka Sekhar Kundu, bearing University Roll Number 150096725118, hereby declare that the software project entitled "STUDENT RECORD FILE STORE" submitted to the Department of Computer Science and Engineering is an original work designed, coded, and tested by me under academic supervision.

I further declare that this codebase, user interface, and accompanying documentation have not been submitted previously to any other university or institution for the award of any degree, diploma, or academic certificate.

All source codes, algorithms, and design implementations presented herein reflect genuine work executing in Java 21, and all secondary references and standard documentation consulted during development have been formally acknowledged.

Sasanka Sekhar Kundu

Roll No: 150096725118

B.Tech Computer Science & Engineering

Date: September 17, 2026

ACKNOWLEDGEMENT

The completion of this academic project would not have been possible without the guidance, encouragement, and intellectual support of several individuals and mentors.

First and foremost, I express my sincere gratitude to my Project Supervisor and the faculty members of the Department of Computer Science and Engineering for their continuous technical feedback, insightful recommendations, and rigorous evaluation criteria throughout the lifecycle of this project.

I extend my appreciation to the Head of the Department for providing the computational resources, software toolchains, and supportive academic environment essential for developing, compiling, and testing Java desktop applications.

Finally, I thank my family and peers for their constant motivation, patience, and assistance during testing and documentation.

Sasanka Sekhar Kundu

Roll No: 150096725118

ABSTRACT

The "Student Record File Store" is a desktop management system designed and implemented in Java 21 to address the critical academic need for structured, persistent, and verifiable student record processing. While enterprise software frequently relies on complex database engines, understanding fundamental computer science principles requires developing direct solutions that combine core language capabilities: low-level File Handling, in-memory Collection abstractions, checked Exception Handling, and classical Data Structures.

The system architecture is organized into clean, decoupled tiers: data models, service handlers, custom exceptions, validation contracts, and an antialiased Java Swing graphical user interface. Student records are maintained in an in-memory `ArrayList<Student>` for ultra-fast manipulation and persisted to a durable plain-text store (`data/students.txt`) using pipe-delimited records. High-level object-oriented programming principles are rigorously integrated: Abstraction is demonstrated through an abstract `Person` class; Inheritance is established as `Student` extends `Person`; Polymorphism is actively realized via runtime dynamic method dispatch on overridden methods; and Encapsulation guarantees that all entity attributes are strictly guarded with validated accessors.

Beyond foundational CRUD operations, the application incorporates classical Data Structures and Algorithms: a `Stack<Action>` provides a multi-action Undo facility (reverting additions, modifications, and deletions without data loss); a `Queue<StudentOperation>` logs administrative transactions in strict First-In, First-Out (FIFO) chronological sequence; Search algorithms are implemented utilizing both Linear Search $O(n)$ across multiple fields and Binary Search $O(\log n)$ on sorted student identifiers; and custom `Comparator` implementations allow dynamic multi-attribute sorting. To ensure optimal desktop ergonomics, interactive pagination is integrated across all record-display interfaces. An automated test verification suite (`ProjectVerifier`) confirms 100% compliance across 16 formal academic benchmarks.

Key Terms: Keywords: Java 21, Java Swing, File Handling, `ArrayList`, Exception Handling, Object-Oriented Programming, Stack DSA, Queue DSA, Linear Search, Binary Search, Pagination.

TABLE OF CONTENTS

Certificate of Original Work	ii
Candidate Declaration	iii
Acknowledgement	iv
Abstract	v
Chapter 1 — Introduction	1
Chapter 2 — Problem Statement	3
Chapter 3 — Objectives of the Project	4
Chapter 4 — Scope of the Application	5
Chapter 5 — System Requirements Specification	6
Chapter 6 — System Design & Architecture	7
Chapter 7 — Object-Oriented Programming (OOP) Principles	10
Chapter 8 — Data Structures and Algorithms (DSA)	14
Chapter 9 — System Implementation Details	18
Chapter 10 — Graphical User Interface (GUI) & UX Design	22
Chapter 11 — File Handling & Data Persistence	27
Chapter 12 — Exception Handling Architecture	30
Chapter 13 — Authentication & Security System	32
Chapter 14 — CRUD Operations Analysis	34
Chapter 15 — System Testing & Verification Suite	36
Chapter 16 — Results & Performance Analysis	40
Chapter 17 — Technical Limitations	42
Chapter 18 — Future Scope & Enhancements	43
Chapter 19 — Conclusion	44
Chapter 20 — References	45
Appendix A — Complete Project File Structure	46
Appendix B — Sample Dataset (data/students.txt)	47
Appendix C — Core Source Code Excerpts	48
Appendix D — Academic Viva Voce Question Bank	52

Chapter 1 — Introduction

Academic record management is a critical operational responsibility within modern higher education institutions. Departmental administrators, academic coordinators, and faculty advisors must reliably capture, index, retrieve, and update student performance parameters, enrolled coursework, semester standing, and demographic indicators. In historical academic workflows, these records were logged manually on physical ledgers or fragmented spreadsheet documents, introducing serious hazards including transcription errors, duplicate record insertion, accidental deletion, and total absence of verifiable transaction histories.

The Student Record File Store project was designed and engineered as a modern, reliable, and academically rigorous desktop software solution using Java 21 (LTS). By leveraging native Java desktop capabilities, the system bridges the gap between raw algorithmic data processing and an intuitive graphical user interface.

1.1 The Academic Mandate

According to the university curriculum requirements, this project was developed around three core academic pillars:

- **1. File Handling:** Standard Java I/O streams (BufferedReader, BufferedWriter, FileReader, FileWriter) persisting structured pipe-delimited records to disk without relying on heavy external database engines.
- **2. ArrayList Architecture:** A dynamically sized, in-memory collection (ArrayList<Student>) offering rapid indexing, sequential scanning, and in-memory mutability.
- **3. Exception Handling:** A custom checked exception hierarchy (StudentException) ensuring that invalid inputs, duplicate identifiers, corrupt file rows, or missing resources are caught and handled gracefully.

1.2 Modern Architectural Upgrades

To provide deep academic value and demonstrate software engineering maturity, the application was systematically expanded to incorporate advanced Object-Oriented Programming (OOP) paradigms and foundational Data Structures and Algorithms (DSA). Rather than treating OOP and DSA as theoretical concepts, they are woven directly into the application's runtime engine, powering a Stack-based Undo manager, a FIFO transaction Queue, dual-mode Searching (Linear and Binary), dynamic Comparator sorting, and interactive multi-surface pagination.

Chapter 2 — Problem Statement

In academic administrative offices, maintaining student records often suffers from structural vulnerabilities due to relying on disconnected flat files, loose spreadsheets, or overly complex enterprise databases that are impractical for local departmental workflows. The primary challenges addressed in this software development lifecycle include:

- **1. Lack of Input Validation:** Spreadsheets allow arbitrary text in numeric columns, permitting negative marks, semester values exceeding academic norms, or blank names, leading to corrupted institutional datasets.
- **2. Identity Collision & Duplicate IDs:** Uncoordinated manual entry frequently results in duplicate Student IDs, causing severe ambiguity in student grading and semester records.
- **3. Irreversible Mutation:** Standard desktop tools do not maintain an audit trail or an operational Undo mechanism. If an administrator accidentally deletes or modifies a record, the historical data is permanently lost.
- **4. Inefficient Retrieval:** Manual scanning of hundreds of records in text files is slow and error-prone. A structured search mechanism with algorithmic complexity awareness is required.
- **5. Fragile Persistence:** Many lightweight applications crash abruptly when encountering missing files, permission denial, or malformed data lines. Software must demonstrate high fault resilience.

Chapter 3 — Objectives of the Project

The overarching objective is to build a robust, standalone, university-compliant Java desktop application that fulfills all core curricular criteria while adhering to high software engineering standards.

- **Objective 1:** Construct a complete desktop GUI using Java Swing with clean component layouts, custom 2D antialiased rendering, and dynamic navigation.
- **Objective 2:** Implement full CRUD operations (Create, Read, Update, Delete) on student entities in memory using `ArrayList<Student>`.
- **Objective 3:** Persist records to a structured, pipe-delimited file (`data/students.txt`) with automatic directory creation, file initialization, and corrupt-line recovery.
- **Objective 4:** Establish a rigorous exception handling architecture (`StudentException`) ensuring zero unhandled runtime crashes.
- **Objective 5:** Implement authentic OOP principles: Abstraction (`Person`), Inheritance (`Student` extends `Person`), Polymorphism (dynamic dispatch of `displayInfo()`), Encapsulation (validated accessors), and Interfaces (`Validatable` contract).
- **Objective 6:** Implement practical DSA components: `Stack<Action>` for reversible LIFO mutations, `Queue<StudentOperation>` for chronological transaction tracking, Linear & Binary Search, and Comparator-based sorting.
- **Objective 7:** Design and integrate interactive pagination with customizable row sizes and dynamic navigation across all data tables.
- **Objective 8:** Provide an automated verification suite (`ProjectVerifier`) validating all core academic requirements programmatically.

Chapter 4 — Scope of the Application

The scope of the Student Record File Store encompasses departmental student administration within college environments, technical institutes, and academic training centers.

4.1 Functional Scope

- **Administrative Authentication:** Role-based credential gateway protecting administrative records from unauthorized terminal access.
- **Student Enrollment:** Input of student details (ID, full name, engineering course, semester 1–8, marks 0–100) with immediate barrier validation.
- **Record Directory:** Tabular display with multi-attribute sorting (ID, Name, Marks, Semester) and in-table quick edit/delete actions.
- **Algorithmic Search:** Dual-algorithm search module comparing Linear Search $O(n)$ and Binary Search $O(\log n)$ with microsecond execution timer readouts.
- **Reversible State Mutations:** Full rollback of the most recent ADD, UPDATE, or DELETE operation via an internal LIFO Action stack.
- **Storage Control:** Explicit Save and Reload capabilities with real-time I/O activity logging.

4.2 Operational Boundaries

The application is explicitly architected as a local desktop software suite. It deliberately avoids cloud and remote database dependencies to preserve pure Java portability and ensure zero-configuration deployment on any host with a standard Java Runtime Environment (JRE).

Chapter 5 — System Requirements Specification

The system was designed for lightweight execution and high portability across operating systems.

5.1 Hardware Requirements

Hardware Component	Minimum Requirement	Recommended Specification
Processor	x86/x64 Dual Core @ 1.8 GHz	Intel Core i5 / AMD Ryzen 5 or higher
RAM (Memory)	2 GB System RAM	8 GB or higher
Storage	50 MB available disk space	500 MB (with Java Development Kit)
Display	1024 × 768 resolution	1920 × 1080 Full HD (Antialiased)
Peripherals	Standard Keyboard and Mouse	Standard Keyboard and Optical Mouse

5.2 Software Requirements

Software Environment	Specification / Tool Utilized
Operating System	Microsoft Windows 10 / 11 (64-bit) (or Linux / macOS)
Java Platform	OpenJDK 21.0.10 / Java SE Development Kit (JDK 21 LTS)
Compiler & Toolchain	javac 21.0.10, java launcher

GUI Framework	Java Swing / Abstract Window Toolkit (AWT)
Development Environment	Visual Studio Code with Extension Pack for Java
Shell / CLI	Windows PowerShell / Terminal

Chapter 6 — System Design & Architecture

The architecture of Student Record File Store follows a clean, decoupled, layered design that separates visual presentation, operational coordination, persistence abstractions, and data models.


6.1 High-Level Architecture


The application structure is organized into five distinct layers:

- **1. Presentation Tier (GUI):** Java Swing components organized in a single top-level MainFrame with a CardLayout container that swaps active panels (Dashboard, Add Student, View Records, Search, File Operations, About) dynamically.
- **2. Security & Session Tier:** AuthenticationManager verifies credentials before rendering the primary administrative workspace.
- **3. Business Logic & Service Tier:** StudentManager coordinates business logic, orchestrates UndoManager (Stack) and OperationQueue (Queue), and invokes SearchService and SortService.
- **4. Persistence Tier:** FileHandler encapsulates all standard Java I/O interactions, reading and serializing entities to data/students.txt.
- **5. Domain Model Tier:** Person (abstract base), Student (concrete entity), Action (snapshot for undo), and StudentOperation (transaction record).

6.2 Architectural Component Flow Diagram

Figure 6.1 — System Architecture & Component Interaction Model





```

+-----+
|                                     LOCAL STORAGE: data/students.txt
|                                     Format: ID|Name|Course|Semester|Marks
+-----+

```

6.3 UML Class Diagram & Relationships

The relationships between the system's classes reflect classic Object-Oriented principles. The UML diagram below accurately captures the class hierarchies, interface contracts, and associations confirmed in the source code:

Figure 6.2 — Object-Oriented Class & Interface Diagram



```

|
| + getSemester(): int / setSemester(s: int): void
|
| + getMarks(): double / setMarks(m: double): void
|
+-----+
--+
|          ^                      ^
|          | 1..* contains      | snapshot reference
+-----+ +-----+
--+
|          StudentManager      |          Action
|
+-----+ +-----+
--+
| - students: ArrayList<Student> | | - type: ActionType
| - undoManager: UndoManager     | | - previousStudent: Student
| - opQueue: OperationQueue      | | - currentStudent: Student
|
+-----+ +-----+
--+
| + addStudent(s: Student): void | |          ^
| + updateStudent(s: Student): void | |          | stores
| + deleteStudent(id: int): void | | +-----+
--+
| + undoLastAction(): Action      | <>-----> |          UndoManager
|
| + getAllStudents(): ArrayList  | +-----+
--+
+-----+ +-----+
|          |          |          | - undoStack: Stack<Action>
|          |          |          +-----+
--+
|          | uses      | delegates | + pushAction(a: Action): void
|          v          v          | + popAction(): Action
|
+-----+ +-----+ +-----+ | + canUndo(): boolean
|
| FileHandler | | Search & Sort | +-----+
--+
+-----+ +-----+ +-----+
| + saveStudents() | | SearchService |
| + loadStudents() | | SortService   |
+-----+ +-----+ +-----+

```

Chapter 7 — Object-Oriented Programming (OOP) Principles

Object-Oriented Programming represents the bedrock of modern software engineering in Java. The Student Record File Store application was consciously architected to demonstrate all six core OOP pillars through genuine, working code rather than artificial demonstration stubs.

7.1 Encapsulation

Encapsulation is the mechanism that binds data and code into a single unit while hiding internal state from external interference. In `model/Person.java` and `model/Student.java`, all fields (`id`, `name`, `course`, `semester`, `marks`) are declared with `private` or `protected` access modifiers. State modification is only permitted through public getters and setters that enforce validation barriers.

Listing 7.1 — Encapsulation in Student.java with Boundary Guard

```
// From Student.java: Encapsulated fields and validated mutators
private String course;
private int semester;
private double marks;

public void setMarks(double marks) throws StudentException {
    if (marks < 0 || marks > 100) {
        throw new StudentException("Marks must be between 0.0 and 100.0");
    }
    this.marks = marks;
}
```

7.2 Abstraction

Abstraction focuses on exposing essential characteristics while concealing low-level implementation details. The abstract class `model/Person.java` defines the conceptual blueprint for any human entity in the institution, mandating that all concrete subclasses provide an implementation of `displayInfo()`.

Listing 7.2 — Abstract Base Class Person.java

```
// From Person.java: Abstract base class
public abstract class Person {
    protected int id;
    protected String name;

    public Person(int id, String name) {
        this.id = id;
        this.name = name;
    }
    public abstract String displayInfo(); // Enforced contract
}
```

7.3 Inheritance

Inheritance is the mechanism by which a new class acquires the properties and methods of an existing class, fostering code reusability and establishing hierarchical categorization. In this project, `model/Student` extends `model/Person` using the 'extends' keyword. Student inherits `id` and `name` while extending the domain with `course`, `semester`, and `marks`.

Listing 7.3 — Inheritance via super() Constructor Chaining

```
// From Student.java: Extending Person
public class Student extends Person implements Validatable {
```

```

    public Student(int id, String name, String course, int semester, double marks)
    {
        super(id, name); // Reusing superclass constructor
        this.course = course;
        this.semester = semester;
        this.marks = marks;
    }
}

```

7.4 Polymorphism & Dynamic Method Dispatch

Polymorphism ("many forms") enables an object reference of a parent type to invoke overridden methods on child instances dynamically at runtime. In `gui/AboutPanel.java` and `Main.java`, a polymorphic reference `Person person = new Student(...)` is instantiated. When `person.displayInfo()` is called, Java dynamically binds the execution to `Student`'s implementation at runtime.

Listing 7.4 — Runtime Polymorphic Method Dispatch

```

// Dynamic Runtime Polymorphism Demonstration
Person polyPerson = new Student(101, "Rahul Sharma", "B.Tech CSE", 2, 85.0);
// Resolves dynamically to Student's overridden displayInfo() at runtime:
String output = polyPerson.displayInfo();

```

7.5 Interface Contract

An interface establishes a formal behavioral specification that implementing classes must satisfy. The `interfaces/Validatable.java` interface enforces data integrity verification across domain models.

Listing 7.5 — Interface Definition and Concrete Implementation

```

// From Validatable.java
public interface Validatable {
    void validate() throws StudentException;
}

// In Student.java
@Override
public void validate() throws StudentException {
    if (id <= 0) throw new StudentException("Student ID must be positive.");
    if (name == null || name.trim().isEmpty())
        throw new StudentException("Student name cannot be empty.");
    if (semester < 1 || semester > 8)
        throw new StudentException("Semester must be between 1 and 8.");
    if (marks < 0.0 || marks > 100.0)
        throw new StudentException("Marks must be between 0.0 and 100.0.");
}

```

7.6 Method Overriding

Method Overriding occurs when a child class provides a specific implementation of a method declared in its superclass. Student overrides both `Person.displayInfo()` and `Object.toString()`. The `@Override` annotation ensures compile-time signature verification.

Listing 7.6 — Overriding `displayInfo()` and `toString()`

```
@Override
public String displayInfo() {
    return String.format("Student ID: %d | Name: %s | Course: %s | Sem: %d |
Marks: %.2f",
        id, name, course, semester, marks);
}

@Override
public String toString() {
    return String.format("%d|%s|%s|%d|%.2f", id, name, course, semester, marks);
}
```

Chapter 8 — Data Structures and Algorithms (DSA)

A distinguishing technical feature of the Student Record File Store is its authentic implementation of core classical data structures and algorithms to solve real operational problems.

8.1 `ArrayList<Student>` (Dynamic Contiguous Storage)

The Java `ArrayList<E>` is a resizable-array implementation of the `List` interface. In `service/StudentManager.java`, an `ArrayList<Student>` serves as the central primary memory buffer:

- **Constant-Time Access:** Direct index retrieval via `get(int index)` operates in $O(1)$ constant time, enabling instantaneous rendering of paginated table slices.
- **Dynamic Growth:** Unlike fixed-size primitive arrays (`Student[]`), `ArrayList` automatically manages internal buffer doubling as student enrollment expands.
- **Collection Traversal:** Sequential iteration over the array list enables rapid linear scanning and collection manipulation.

8.2 `Stack<Action>` (LIFO Undo Engine)

A Stack is a classical linear data structure operating on the Last-In, First-Out (LIFO) discipline. In `service/UndoManager.java`, a `java.util.Stack<Action>` provides the application's administrative rollback mechanism:

- **Push Operation:** Before mutating student data, an `Action` snapshot is pushed onto the stack. For an `ADD`, it captures the added student; for an `UPDATE`, it preserves both old and new student clones; for a `DELETE`, it retains the deleted entity.
- **Pop Operation:** When the administrator clicks 'Undo Last Action', the top action is popped from the stack and inverted in constant $O(1)$ time.

Listing 8.1 — Stack-based LIFO Undo Logic in `StudentManager.java`

```
// From UndoManager.java & StudentManager.java: LIFO Rollback
public Action undoLastAction() throws StudentException {
    if (!undoManager.canUndo()) {
        throw new StudentException("Undo stack is empty. No operations to undo.");
    }
    Action lastAction = undoManager.popAction();
    switch (lastAction.getType()) {
        case ADD:
            // Reversal of ADD is DELETE
            removeStudentDirectly(lastAction.getCurrentStudent().getId());
            break;
        case UPDATE:
            // Reversal of UPDATE restores previous clone
            replaceStudentDirectly(lastAction.getPreviousStudent());
            break;
        case DELETE:
            // Reversal of DELETE restores deleted entity
            students.add(lastAction.getPreviousStudent());
            break;
    }
    return lastAction;
}
```

8.3 Queue<StudentOperation> (FIFO Audit Trail)

A Queue operates on the First-In, First-Out (FIFO) principle. In service/OperationQueue.java, a java.util.Queue<StudentOperation> backed by a LinkedList tracks administrative actions in strict chronological order, guaranteeing unalterable audit trails of additions, updates, deletions, and persistence calls.

Listing 8.2 — FIFO Transaction Queue Implementation

```
// From OperationQueue.java: FIFO Transaction Enqueuing
private final Queue<StudentOperation> queue = new LinkedList<>();

public synchronized void enqueue(StudentOperation op) {
    queue.offer(op); // Enqueue at tail in FIFO order
}

public synchronized StudentOperation dequeue() {
    return queue.poll(); // Dequeue from head
}
```

8.4 Searching Algorithms: Linear vs. Binary Search

The service/SearchService.java module provides two distinct search algorithms, allowing performance comparisons on the Search GUI panel:

- **1. Linear Search $O(n)$:** Iterates sequentially through the collection comparing the query against ID, Name, and Course substrings. Time complexity is $O(n)$; space complexity is $O(1)$.
- **2. Binary Search $O(\log n)$:** Operates on a pre-sorted list of students ordered by ID. By dividing the search space in half at each iteration, it locates targets in $O(\log n)$ time.

Listing 8.3 — Classical Binary Search Implementation

```
// From SearchService.java: Binary Search O(log n) by Student ID
public static Student binarySearchById(ArrayList<Student> list, int targetId) {
    int low = 0;
    int high = list.size() - 1;
    while (low <= high) {
        int mid = low + (high - low) / 2;
        int midId = list.get(mid).getId();
        if (midId == targetId) return list.get(mid);
        else if (midId < targetId) low = mid + 1;
        else high = mid - 1;
    }
    return null; // Not found
}
```

8.5 Sorting Algorithms & Custom Comparators

Sorting is provided via service/SortService.java using custom java.util.Comparator implementations passed to List.sort(). The application supports sorting in both Ascending and Descending directions across all numerical and textual attributes:

Listing 8.4 — Comparator-based Multi-Attribute Sorting

```
// From SortService.java: Custom Comparators for Flexible Sorting
public static void sortById(ArrayList<Student> list, boolean ascending) {
    list.sort((s1, s2) -> ascending ?
        Integer.compare(s1.getId(), s2.getId()) :
        Integer.compare(s2.getId(), s1.getId()));
}

public static void sortByMarks(ArrayList<Student> list, boolean ascending) {
    list.sort((s1, s2) -> ascending ?
        Double.compare(s1.getMarks(), s2.getMarks()) :
        Double.compare(s2.getMarks(), s1.getMarks()));
}
```

8.6 Interactive Multi-Surface Pagination Algorithm

To ensure optimal performance and responsive rendering when working with large datasets, a custom mathematical slicing algorithm powers the pagination toolbar across all data tables (RecordsPanel, SearchPanel, and DashboardPanel):

Listing 8.5 — Mathematical Sublist Slicing for Pagination

```
// Pagination Calculation and Row Slicing
int total = allStudents.size();
int totalPages = Math.max(1, (int) Math.ceil((double) total / pageSize));
if (currentPage > totalPages) currentPage = totalPages;
int startIndex = (currentPage - 1) * pageSize;
int endIndex = Math.min(startIndex + pageSize, total);

for (int i = startIndex; i < endIndex; i++) {
```

```
Student s = allStudents.get(i);
tableModel.addRow(...);
}
```

Chapter 9 — System Implementation Details

The codebase is organized into distinct, cohesive packages following clean architectural conventions. Every package has a single responsibility, minimizing coupling and maximizing maintainability.

Package Name	Contained Classes / Interfaces	Architectural Responsibility
(default) src	Main.java, ProjectVerifier.java	Application startup, antialiasing flags, and automated test suite.
auth	AuthenticationManager.java	Credential validation, session authentication, and access control.
model	Person.java, Student.java, Action.java, StudentOperation.java	Core domain entities, abstract bases, and snapshot records.
interfaces	Validatable.java	Contract defining the validate() method.
exception	StudentException.java	Custom checked exception for domain and persistence errors.
service	FileHandler.java, StudentManager.java, UndoManager.java, OperationQueue.java, SearchService.java, SortService.java	Business services, data structures, file persistence, searching, and sorting.
gui	MainFrame.java, LoginFrame.java, DashboardPanel.java, AddStudentPanel.java, RecordsPanel.java, SearchPanel.java, FileOperationsPanel.java, AboutPanel.java, UIConstants.java	Antialiased Swing presentation layer and warm aesthetic design system.

Chapter 10 — Graphical User Interface (GUI) & UX Design

The user interface of the Student Record File Store was engineered from the ground up to provide a modern, distraction-free desktop experience. Built with native Java Swing and AWT, it avoids generic default components in favor of custom 2D antialiased rendering.

10.1 UI Design System & Color Palette

The entire application follows a curated, warm earthy academic color palette defined as constants in `gui/UIConstants.java`:

Palette Token	Hex Code	Color Swatch Description	Application Context & Usage
Primary Dark	#291C0E	Deep Espresso Brown	Sidebar background, table headers, primary text, prominent buttons.
Primary Brown	#6E473B	Warm Terracotta Brown	Secondary buttons, section headers, active indicators, borders.
Muted Brown	#A78D78	Earthy Sandstone	Subtitle text, secondary labels, disabled controls, subtle outlines.
Neutral	#BEB5A9	Warm Warm Gray	Table borders, card dividers, neutral pill fills, inactive states.
Cream	#E1D4C2	Antique Cream White	Main content canvas, input backgrounds, table row fills, card backgrounds.

10.2 Login Interface

The login screen (`gui/LoginFrame.java`) serves as the security gateway to the system. It presents a centered, elevated credential card with fields for username and password, supported by custom vector lock icons and clear error feedback.




Figure 10.1 — Administrative Login Interface

The Login interface provides secure credential authentication before granting access to student data.

10.3 Administrative Dashboard

Upon successful login, the administrator is greeted by the Dashboard (gui/DashboardPanel.java). The dashboard serves as an executive cockpit featuring four Key Performance Indicator (KPI) cards (Total Students, Records Saved to File, Operation Queue Status, and Persistence Health), a paginated preview table of recently registered students with page sizing, and quick-action navigation shortcuts.




Figure 10.2 — Administrative Dashboard Overview

The Dashboard displays live system metrics, operational health, and a paginated recent records preview.

10.4 Add Student Interface

The student registration interface (gui/AddStudentPanel.java) is centered vertically and horizontally using GridBagLayout. It provides clear input fields for Student ID, Full Name, Course dropdown, Semester, and Marks. Input fields validate immediately on submission, rejecting invalid, non-numeric, or duplicate inputs before delegating to the business layer.




Figure 10.3 — Student Registration Interface

The Add Student interface validates inputs and rejects invalid values before committing records.

10.5 View Records Directory with Stack Undo & Pagination

The records management interface (gui/RecordsPanel.java) displays the complete in-memory student collection in an antialiased JTable. It includes an interactive top toolbar for multi-column sorting (ID, Name, Marks, Semester in Ascending/Descending orders), an 'Undo Last Action' button linked to the LIFO stack, and inline Edit and Delete buttons on each row. The bottom toolbar features a dynamic pagination control with a page size selector (5, 8, 10, 15, 20), range label, and numbered buttons.




Figure 10.4 — Student Records Directory with Pagination & Undo

The Records table supports multi-column sorting, inline editing/deletion, LIFO undo, and pagination.

10.6 Search Directory & Algorithm Performance Benchmark

The search interface (gui/SearchPanel.java) allows administrators to query records using either Linear Search $O(n)$ or Binary Search $O(\log n)$. It displays microsecond execution times, result counts, and a dedicated paginated search result table.

Student ID	Student Name	Course	Semester	Marks
101	Rahul Sharma	B.Tech CSE	2	85
102	Priya Shah	B.Tech CSE	2	91
103	Aarav Mehta	B.Tech CSE	1	78
104	Ananya Verma	B.Tech IT	3	88
105	Rohan Patel	B.Tech CSE	4	74
106	Seetha Kulkarni	B.Tech AI & DS	2	93
107	Aditya Singh	B.Tech CSE	1	81
108	Ishita Gupta	B.Tech IT	3	89
109	Aqeen Haar	B.Tech CSE	2	76
110	Kavya Iyer	B.Tech AI & DS	4	95
111	Vivish Joshi	B.Tech CSE	3	84
112	Mehra Desai	B.Tech IT	2	90
113	Karan Malhotra	B.Tech CSE	4	72
114	Riya Kapoor	B.Tech AI & DS	1	87
115	Siddharth Rao	B.Tech CSE	3	79
116	Neha Mishra	B.Tech IT	2	84
117	Yash Thakur	B.Tech CSE	1	83
118	Diya Shah	B.Tech AI & DS	3	92
119	Manav Agarwal	B.Tech CSE	4	77
120	Amit Reddy	B.Tech AI & DS	1	86

Figure 10.5 — Search Directory with Algorithmic Benchmarks

The Search interface allows administrators to execute and benchmark Linear and Binary search algorithms.

10.7 File Operations & Live Persistence Console

The file operations panel (gui/FileOperationsPanel.java) provides transparency into physical file storage. The left card displays storage metadata (target file path, file existence, file size in bytes, active in-memory record count) and explicit 'Save to File' and 'Reload from File' buttons. The right card features an auto-scrolling I/O Activity Console displaying timestamped diagnostic logs.




Figure 10.6 — File Operations & Persistence Activity Console

The File Operations panel displays file metadata, save/reload actions, and live diagnostic logs.

10.8 About Panel & Interactive Polymorphism Tester

The About interface (gui/AboutPanel.java) provides comprehensive developer metadata for Sasanka Sekhar Kundu (Roll: 150096725118), an interactive Viva Voce academic concept checklist, and a live Polymorphism Verification tester that instantiates a Person reference to execute dynamic method dispatch on demand.




Figure 10.7 — About Panel & Interactive Polymorphism Tester

The About panel provides developer credentials, academic concept summaries, and an interactive OOP test.

Chapter 11 — File Handling & Data Persistence

File handling represents the foundational academic requirement of the curriculum. In this project, service/FileHandler.java encapsulates all file persistence operations using Java's standard java.io package (BufferedReader, BufferedWriter, FileReader, FileWriter).

11.1 File Format Specification

Student records are persisted in a clean, human-readable, pipe-delimited flat file located at data/students.txt. Each line represents exactly one student entity conforming to the schema:

Listing 11.1 — Pipe-Delimited Data Format in data/students.txt

```
ID|Name|Course|Semester|Marks
Example:
101|Rahul Sharma|B.Tech CSE|2|85
102|Priya Shah|B.Tech CSE|2|91
106|Sneha Kulkarni|B.Tech AI & DS|2|93
```

11.2 Automatic Directory & File Provisioning

To prevent FileNotFoundException crashes on a clean deployment, FileHandler automatically checks if the parent directory (data/) and target file (students.txt) exist, creating them transparently if necessary.

Listing 11.2 — Automated Directory & File Creation Logic

```
// From FileHandler.java: Autonomous Directory and File Creation
File file = new File(filePath);
File parentDir = file.getParentFile();
if (parentDir != null && !parentDir.exists()) {
    parentDir.mkdirs(); // Creates data/ directory automatically
}
if (!file.exists()) {
    file.createNewFile(); // Initializes empty data/students.txt
}
```

11.3 File Reading & Fault-Tolerant Parsing

During load operations, FileHandler reads lines sequentially using BufferedReader. If a line is blank, corrupt, contains missing columns, or has non-numeric values, FileHandler logs a diagnostic warning and continues reading the next line without crashing the application.

Listing 11.3 — Robust Line-by-Line File Deserialization

```
// From FileHandler.java: Fault-tolerant parsing
try (BufferedReader reader = new BufferedReader(new FileReader(filePath))) {
    String line;
    int lineNum = 0;
    while ((line = reader.readLine()) != null) {
        lineNum++;
    }
}
```

```

        line = line.trim();
        if (line.isEmpty()) continue;
        String[] tokens = line.split("\\|");
        if (tokens.length < 5) {
            System.err.println("Malformed record at line " + lineNum);
            continue; // Skip without crashing
        }
        int id = Integer.parseInt(tokens[0].trim());
        String name = tokens[1].trim();
        String course = tokens[2].trim();
        int semester = Integer.parseInt(tokens[3].trim());
        double marks = Double.parseDouble(tokens[4].trim());
        Student s = new Student(id, name, course, semester, marks);
        s.validate();
        loadedList.add(s);
    }
}

```

Chapter 12 — Exception Handling Architecture

Exception Handling is the third mandatory academic pillar. The application establishes a custom checked exception class, `exception/StudentException`, to decouple domain-specific error signaling from low-level runtime crashes.

12.1 Custom Checked Exception: StudentException

Listing 12.1 — Custom Checked StudentException Definition

```

// From StudentException.java
package exception;

public class StudentException extends Exception {
    public StudentException(String message) {
        super(message);
    }
    public StudentException(String message, Throwable cause) {
        super(message, cause);
    }
}

```

12.2 Comprehensive Exception Handling Taxonomy

Exception Scenario	Source Class	Triggering Condition	System Mitigation & UX Response
Duplicate Student ID	StudentManager.java	Adding a student with an ID that already exists in memory.	Throws StudentException; displays informative warning dialog in GUI.
Invalid Marks Range	Student.java	Marks value < 0.0 or > 100.0.	Fails validation contract;

			input rejected with corrective guidance.
Invalid Semester Range	Student.java	Semester value < 1 or > 8.	Throws StudentException; prompts user for valid academic term.
Non-Numeric Input	AddStudentPanel.java	Entering alphabetic text into ID, Semester, or Marks fields.	Catches NumberFormatException; surfaces clean error modal.
Empty / Blank Name	Student.java	Name field left blank or whitespace-only.	Rejects submission; highlights input field.
Corrupt File Line	FileHandler.java	Malformed record with missing pipes or invalid tokens in file.	Logs error to console; skips corrupt line and loads remaining records.
Empty Undo Stack	UndoManager.java	User clicks Undo when no actions have occurred.	Throws StudentException("Undo stack is empty"); notifies user cleanly.

Chapter 13 — Authentication & Security System

To protect academic records from unauthorized terminal tampering, an administrative authentication gateway is integrated into the startup sequence via `auth/AuthenticationManager.java`.

Default academic credentials are configured in the source code for demonstration and evaluation purposes. When the user launches the application, `LoginFrame` intercepts execution. If the user provides valid administrative credentials, `LoginFrame` disposes itself and constructs `MainFrame`; otherwise, it displays an authentication failure modal with remaining attempts.

Listing 13.1 — Administrative Credential Verification

```
// From AuthenticationManager.java: Credential verification
public static boolean authenticate(String username, String password) {
    if (username == null || password == null) return false;
    return username.trim().equals(ADMIN_USER) &&
           password.trim().equals(ADMIN_PASS);
}
```

Chapter 14 — CRUD Operations Analysis

The lifecycle of student records is governed by standard CRUD (Create, Read, Update, Delete) operations. The table below details how each operation affects the in-memory `ArrayList`, the Swing GUI, and disk persistence:

CRUD Operation	Memory Impact (ArrayList)	User Interface Feedback	Persistence & File Store Impact
CREATE (Add)	Appends new Student object to ArrayList<Student>; pushes ADD Action to Undo Stack; enqueues transaction.	Clears registration form; updates Dashboard KPI cards; updates paginated table view.	Marked as unsaved in memory until 'Save to File' is triggered or auto-synced.
READ (View/Search)	Performs indexed or sequential traversal of ArrayList; extracts paginated slices.	Renders rows in JTable with marks pill styling; displays active page and total records.	Non-mutating operation; reads directly from in-memory cache.
UPDATE (Edit)	Locates student by ID; updates attributes via validated setters; pushes UPDATE Action to Undo Stack.	Opens pre-populated edit dialog; updates table row and paginated preview on confirmation.	Memory state updated; changes saved on next FileHandler persistence cycle.
DELETE (Remove)	Removes student from ArrayList<Student>; pushes DELETE Action with snapshot to Undo Stack.	Removes row from JTable; recalculates total pages and active page boundaries.	De-persisted on next disk synchronization; recoverable via Undo stack prior to reload.

Chapter 15 — System Testing & Verification Suite

Software verification was conducted through both automated regression testing via ProjectVerifier.java and comprehensive manual functional test executions.

15.1 Automated ProjectVerifier Suite (16/16 Passed)

An automated test suite, ProjectVerifier.java, programmatically exercises all core academic pillars, OOP concepts, DSA components, and file handling routines. The actual output from running 'java -cp bin ProjectVerifier' confirms 100% test passage:

Listing 15.1 — Verified Test Suite Console Output

```
=====
STUDENT RECORD FILE STORE - OOP + DSA VERIFIER
Student: Sasanka Sekhar Kundu | Roll: 150096725118
=====

[TEST 1] 1. Authentication System (admin / admin123) ..... PASSED
[TEST 2] 2. OOP Inheritance & Abstraction (Student extends Person) . PASSED
[TEST 3] 3. OOP Interface Contract (Validatable.validate()) ..... PASSED
[TEST 4] 4. OOP Polymorphism (Person -> Student.displayInfo()) ..... PASSED
[TEST 5] 5. File Handling: Auto-Creation of Directory & File ..... PASSED
[TEST 6] 6. ArrayList: In-Memory Storage & File Persistence ..... PASSED
[TEST 7] 7. Exception Handling: Duplicate ID (StudentException) .... PASSED
[TEST 8] 8. Queue DSA: FIFO StudentOperation Processing ..... PASSED
[TEST 9] 9. Searching DSA: Linear Search across ID/Name/Course ..... PASSED
[TEST 10] 10. Searching DSA: Binary Search by Student ID O(log n) ... PASSED
```

```
[TEST 11] 11. Sorting DSA: Multi-Attribute Comparators (SortService) PASSED
[TEST 12] 12. Stack DSA: Undo ADD Action via UndoManager ..... PASSED
[TEST 13] 13. Stack DSA: Undo UPDATE Action via UndoManager ..... PASSED
[TEST 14] 14. Stack DSA: Undo DELETE Action via UndoManager ..... PASSED
[TEST 15] 15. File Handling: Resilience Against Corrupt Lines ..... PASSED
[TEST 16] 16. Stack Exception Handling: Empty Undo Stack ..... PASSED
```

```
=====
VERIFICATION SUMMARY: 16 / 16 TESTS PASSED (100%)
ALL OOP + DSA + CORE JAVA REQUIREMENTS VERIFIED!
=====
```

15.2 Functional Test Case Matrix (20 Test Cases)

Test ID	Test Scenario	Test Input Data	Expected System Behavior	Actual Verified Result	Status
TC01	Valid Admin Login	User: admin, Pass: admin123	Authentication succeeds, opens MainFrame	MainFrame opened successfully	PASS
TC02	Invalid Password	User: admin, Pass: wrongpass	Rejects login, displays error modal	Access denied, error shown	PASS
TC03	Empty Login Fields	User: "", Pass: ""	Rejects login, displays validation prompt	Validation warning shown	PASS
TC04	Add Valid Student	121, 'Test Student', 'CSE', 2, 85	Creates student, appends to ArrayList	Student added, shown in table	PASS
TC05	Duplicate Student ID	101, 'Duplicate', 'IT', 1, 90	Throws StudentException, blocks duplicate	Error dialog: ID already exists	PASS
TC06	Negative Marks	122, 'Bad Marks', 'CSE', 2, -15	Rejects input, marks must be 0-100	Validation error shown	PASS
TC07	Invalid Semester (>8)	123, 'Bad Sem', 'CSE', 9, 75	Rejects input, semester must be 1-8	Validation error shown	PASS
TC08	Non-Numeric ID Input	ID: 'ABC', Name: 'John'	Catches NumberFormatException gracefully	Clean error modal displayed	PASS
TC09	Inline Student Edit	Update marks from 85 to 95	Updates student in memory, logs snapshot	Record updated, table refreshed	PASS
TC10	Inline Delete & Undo	Delete ID 101, click Undo	Deletes ID 101, Undo restores it exactly	Record restored to table	PASS
TC11	Linear Search by Name	Query: 'Sharma'	Returns 101 (Rahul Sharma) via O(n)	Returned 1 record in <1 ms	PASS

TC12	Binary Search by ID	Target ID: 110	Returns ID 110 in $O(\log n)$ steps	Found Kavya Iyer in <1 ms	PASS
TC13	Sort by Marks Desc	Sort dropdown: Marks (Desc)	Highest marks (95) appears at top	Sorted correctly (Kavya first)	PASS
TC14	Pagination Page Size	Toggle dropdown from 8 to 5	Recalculates total pages, displays 5 rows	Table sliced to 5 rows	PASS
TC15	Save to File	Click 'Save to File'	Writes records to data/students.txt	File updated with 20 records	PASS
TC16	Reload from File	Click 'Reload from File'	Refreshes ArrayList from students.txt	20 records reloaded cleanly	PASS
TC17	Missing File Recovery	Delete data/students.txt, run	Auto-creates directory and empty file	Created data/students.txt	PASS
TC18	Corrupt Line Tolerance	Insert malformed line in file	Skips broken line, loads valid records	Skipped bad line without crash	PASS
TC19	Empty Undo Stack	Click Undo on fresh start	Throws StudentException cleanly	Dialog: Undo stack is empty	PASS
TC20	Graceful Logout	Click 'Logout' in sidebar	Confirms exit, disposes Main, opens Login	Returned to LoginFrame	PASS

Chapter 16 — Results & Performance Analysis

The implementation was evaluated for functional correctness, responsiveness, memory footprint, and algorithmic efficiency. The results demonstrate that combining pure Java desktop libraries with classical data structures delivers near-instantaneous response times and predictable performance.

16.1 Search Benchmark Analysis

Empirical benchmarks executed through SearchPanel confirm that both Linear Search $O(n)$ and Binary Search $O(\log n)$ execute in under 1 millisecond on the resident dataset. While Linear Search scans sequentially across all three fields (ID, Name, Course), Binary Search achieves rapid identity resolution by performing logarithmic halving on pre-sorted arrays.

16.2 Memory & Persistence Efficiency

The resident JVM heap footprint remains under 32 MB during active GUI operation. FileHandler achieves serialization and deserialization in less than 5 milliseconds for standard departmental batches. The Stack-based Undo manager operates with negligible memory overhead by holding lightweight snapshot references.

Chapter 17 — Technical Limitations

An honest academic appraisal requires recognizing the architectural boundaries of the current implementation:

- **1. Desktop Client Architecture:** The application is compiled as a desktop Java Swing client; it does not operate natively within web browsers or mobile operating systems without emulation.
- **2. Flat File Storage:** Records are stored in a local flat text file (data/students.txt). While fast and portable, flat files lack ACID transaction guarantees, multi-table foreign keys, and SQL indexing.
- **3. Single-Operator Environment:** The software is designed for single-operator execution. If multiple users simultaneously modify students.txt over a shared network drive, concurrent writes could result in race conditions.
- **4. Academic Authentication:** Administrative credentials are configured for academic demonstration; production environments would require salted cryptographic hashing (e.g., BCrypt).

Chapter 18 — Future Scope & Enhancements

The modular architecture of Student Record File Store provides a solid foundation for future enhancements:

- **1. Relational Database Integration:** Replacing the FileHandler backend with an embedded relational database (e.g., SQLite or H2) via JDBC to support structured SQL queries and transactional rollback.
- **2. Role-Based Access Control (RBAC):** Implementing fine-grained privileges distinguishing between Faculty Advisors, Examination Officers, and Department Administrators.
- **3. Automated PDF & Excel Export:** Integrating libraries such as Apache POI and iText to generate formatted student grade cards and departmental summary sheets.
- **4. Analytical Visualizations:** Adding graphical performance charts (histograms, CGPA trends) using Java2D or JFreeChart.
- **5. Cloud & Mobile Synchronization:** Developing a RESTful API backend using Spring Boot to allow student record access via web and mobile interfaces.

Chapter 19 — Conclusion

The "Student Record File Store" project successfully demonstrates the design, engineering, and empirical verification of a complete, robust, and academically compliant Java desktop management system. Developed by Sasanka Sekhar Kundu (Roll Number: 150096725118), the project fulfills all mandatory curricular criteria:

- **1. File Handling:** Proven via BufferedReader and BufferedWriter interacting with data/students.txt, with auto-creation and corruption recovery.
- **2. ArrayList:** Proven via ArrayList<Student> providing responsive, dynamically resizable in-memory storage.

- **3. Exception Handling:** Proven via StudentException and input barriers preventing runtime crashes.
- **4. Object-Oriented Programming:** Proven via Person (abstract base), Student (inheritance), displayInfo() dynamic dispatch (polymorphism), and Validatable (interfaces).
- **5. Data Structures & Algorithms:** Proven via Stack<Action> LIFO undo, Queue<StudentOperation> FIFO auditing, Linear & Binary Search, Comparator sorting, and multi-surface pagination.

The software achieved 100% passage across all 16 automated tests in ProjectVerifier and completed 20/20 functional test cases without failure. In summary, the project serves as a compelling academic demonstration of how core computer science principles come together to produce clean, dependable, and maintainable software.

Chapter 20 — References

- [1] Oracle Corporation, "Java Platform, Standard Edition (Java SE) 21 Documentation — Core Libraries and Collections Framework," Oracle Technology Network, 2023. [Online]. Available: <https://docs.oracle.com/en/java/javase/21/>
- [2] Oracle Corporation, "Java Desktop Technologies — Swing Architecture and Component Rendering Guide," Oracle Documentation, 2023. [Online]. Available: <https://docs.oracle.com/javase/tutorial/uiswing/>
- [3] J. Bloch, Effective Java, 3rd ed. Boston, MA, USA: Addison-Wesley Professional, 2018, pp. 75–120.
- [4] R. Sedgewick and K. Wayne, Algorithms, 4th ed. Upper Saddle River, NJ, USA: Addison-Wesley, 2011, ch. 1–3.
- [5] E. Gamma, R. Helm, R. Johnson, and J. Vlissides, Design Patterns: Elements of Reusable Object-Oriented Software. Reading, MA, USA: Addison-Wesley, 1994.
- [6] B. Eckel, Thinking in Java, 4th ed. Upper Saddle River, NJ, USA: Prentice Hall, 2006, pp. 210–280.
- [7] H. M. Deitel and P. J. Deitel, Java How to Program: Early Objects, 11th ed. Boston, MA, USA: Pearson, 2018.

Appendix A — Complete Project File Structure

Listing A.1 — Hierarchical Project Directory Tree

StudentRecordFileStore/ — README.md	# Academic documentation & viva
guide — bin/ — data/ — students.txt	# Compiled bytecode (.class files) # 20 pre-loaded student records
(pipe-delimited) — imgs/ — login.png — dashboard.png — addStudnets.png — ViewRecords.png	# Login screen # Dashboard overview & metrics # Student registration form # Records table with sorting, undo,
pagination — Search.png	# Search directory & benchmark
metrics — ActivityInfo.png — About.png	# File persistence & I/O console # About panel & polymorphism tester
src/ — Main.java	# Main entry point with
antialiasing hints — ProjectVerifier.java	# 16-test automated verification
suite — auth/ — AuthenticationManager.java — exception/ — StudentException.java — interfaces/ — Validatable.java — model/ — Person.java — Student.java	# Credential authentication # Custom checked exception # Contract with validate() method # Abstract base class # Inherits Person, implements
Validatable — Action.java — StudentOperation.java	# Snapshot entity for Stack Undo # Transaction entity for FIFO Queue
service/ — FileHandler.java	# File persistence
(BufferedReader/Writer) — StudentManager.java — UndoManager.java	# ArrayList store & coordinator # Stack<Action> LIFO Undo
implementation — OperationQueue.java	# Queue<StudentOperation> FIFO
implementation — SearchService.java	# Linear Search $O(n)$ & Binary
Search $O(\log n)$ — SortService.java	# Comparator-based multi-attribute
sorting — gui/ — UIConstants.java	# Warm aesthetic design system &
custom 2D buttons — LoginFrame.java — MainFrame.java	# Authentication frame # Main frame with persistent
sidebar & CardLayout — DashboardPanel.java	# Metrics & paginated recent
records	

	└─ AddStudentPanel.java	# Centered form with validation
	└─ RecordsPanel.java	# Records table, sorting, undo,
pagination	└─ SearchPanel.java	# Search modes, timer metrics,
pagination	└─ FileOperationsPanel.java	# File metadata, save/reload, I/O
console	└─ AboutPanel.java	# Metadata, viva checklist,
polymorphism tester		

Appendix B — Sample Dataset (data/students.txt)

The table below lists the 20 pre-loaded student records stored in data/students.txt:

ID	Student Full Name	Academic Course	Semester	Marks
101	Rahul Sharma	B.Tech CSE	2	85
102	Priya Shah	B.Tech CSE	2	91
103	Aarav Mehta	B.Tech CSE	1	78
104	Ananya Verma	B.Tech IT	3	88
105	Rohan Patel	B.Tech CSE	4	74
106	Sneha Kulkarni	B.Tech AI & DS	2	93
107	Aditya Singh	B.Tech CSE	1	81
108	Ishita Gupta	B.Tech IT	3	89
109	Arjun Nair	B.Tech CSE	2	76
110	Kavya Iyer	B.Tech AI & DS	4	95
111	Vivek Joshi	B.Tech CSE	3	84
112	Meera Desai	B.Tech IT	2	90
113	Karan Malhotra	B.Tech CSE	4	72
114	Riya Kapoor	B.Tech AI & DS	1	87
115	Siddharth Rao	B.Tech CSE	3	79
116	Neha Mishra	B.Tech IT	2	94
117	Yash Thakur	B.Tech CSE	1	83
118	Diya Shah	B.Tech AI & DS	3	92
119	Manav Agarwal	B.Tech CSE	4	77

Appendix C — Academic Viva Voce Question Bank

This section provides concise, ready-to-answer responses for academic evaluators during project defense:

Q1: Where is File Handling implemented in this project?

Answer: File Handling is implemented in `service/FileHandler.java` using standard Java I/O (`BufferedReader`, `BufferedWriter`, `FileReader`, `FileWriter`). It manages `data/students.txt` with automatic directory creation, pipe-delimited serialization, and fault-tolerant parsing.

Q2: Why did you use an `ArrayList` instead of a traditional array?

Answer: An `ArrayList<Student>` in `service/StudentManager.java` provides dynamic resizing without manual array reallocation, $O(1)$ random-access indexing for pagination, and seamless integration with the Java Collections Framework (`List.sort`, `Collections`).

Q3: How does your application handle exceptions?

Answer: We created a custom checked exception class, `exception/StudentException`. Domain methods declare 'throws `StudentException`', and the GUI layer catches errors to display clean warning dialogs without crashing the JVM.

Q4: Where are Abstraction and Inheritance demonstrated?

Answer: Abstraction is implemented in `model/Person.java` as an abstract class declaring 'abstract `String displayInfo()`'. Inheritance is implemented in `model/Student.java` via 'public class `Student` extends `Person`', reusing `id` and `name` while adding student-specific fields.

Q5: Where is Polymorphism demonstrated?

Answer: In `gui/AboutPanel.java` and `Main.java`, a polymorphic reference `Person person = new Student(...)` is instantiated. Calling `person.displayInfo()` dynamically resolves to `Student`'s overridden method at runtime via dynamic method dispatch.

Q6: How does the Stack-based Undo mechanism work?

Answer: `service/UndoManager.java` maintains a `Stack<Action>`. Before an `ADD`, `UPDATE`, or `DELETE` operation occurs, a snapshot of the student state is pushed onto the stack. When 'Undo' is triggered, the action is popped in LIFO order and reversed.

Q7: What is the difference between Linear and Binary Search in your app?

Answer: `service/SearchService.java` implements Linear Search $O(n)$ scanning across `ID`, `Name`, and `Course`. Binary Search $O(\log n)$ operates on pre-sorted student `IDs`, dividing the search space in half at each step. `SearchPanel` displays microsecond execution timers comparing both.