

# PublicBoard API 接口文档

## PublicBoard API Specification

项目名称：PublicBoard

摘要：本文档主要详细介绍 PublicBoard 项目的接口

相关文档：

版权所有：（除特别允许否则只在项目组内部使用）

修改记录：

日期	版本	说明	作者
2021-11-16	v1.0	实现用户登录注册及用户管理模块	黄泽豪
2021-11-30	v2.0	实现增加用户权限、编辑查看帖子模块	黄泽豪
2021-12-13	v3.0	实现个人主页面模块以及账号重复处理	黄泽豪
2021-12-22	v4.0	实现评论模块、完善邮箱验证、实现匿名模块	黄泽豪

# 目 录

<b>1 用户管理.....</b>	<b>3</b>
1.1 用户注册.....	3
1.2 查看用户表.....	4
1.3 获取已登录用户信息.....	5
1.4 查看个人信息.....	5
1.5 修改个人信息.....	6
1.6 修改密码.....	7
1.7 开启/关闭匿名模式.....	8
1.8 发送验证码.....	9
1.9 忘记密码.....	10
1.10 修改邮箱.....	11
<b>2 帖子管理.....</b>	<b>12</b>
2.1 查看帖子表.....	12
2.2 查看帖子详情.....	15
2.3 获取所有帖子类型.....	18
2.4 发布帖子带图片.....	19
2.5 帖子点赞与取消点赞.....	20
2.6 帖子评论.....	21
2.7 帖子回复.....	25
2.8 搜索帖子.....	28
2.9 查看我的帖子.....	32

# 1 用户管理

## 1.1 用户注册

**URL:** /user/add

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 用户注册

**Body-parameters:**

Parameter	Type	Description	Required	Since
userid	int32	账号	false	-
password	string	密码	false	-
email	string	邮箱	false	-
code	string	验证邮箱的验证码	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /user/add --data '{
  "userid": "2019xxxxxx",
  "password": "123456789",
  "email": "123456789@qq.com",
  "code": "123456"
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
```

```
"success": true,
"code": 200,
"msg": "success",
"data": {
  "waring": "You may have used non-display generics."
},
"timestamp": "2022-01-02 20:06:02"
}
```

## 1.2 查看用户表

**URL:** /user/admin/checkuser

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 查看用户表

**Query-parameters:**

Parameter	Type	Description	Required	Since
page	int32	页数	true	-
size	int32	每页记录数	true	-

**Request-example:**

```
curl -X GET -i /user/admin/checkuser?page=1&size=10
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  }
}
```

```
},  
  "timestamp": "2022-01-02 20:06:02"  
}
```

## 1.3 获取已登录用户信息

**URL:** /user/whoami

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 获取已登录用户信息

**Request-example:**

```
curl -X GET -i /user/whoami
```

**Response-example:**

```
529
```

## 1.4 查看个人信息

**URL:** /user/showprofile

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 查看个人信息

**Request-example:**

```
curl -X GET -i /user/showprofile
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{  
  "success": true,  
  "code": 200,  
  "msg": "success",  
}
```

```
"data": {
  "waring": "You may have used non-display generics."
},
"timestamp": "2022-01-02 20:06:02"
}
```

## 1.5 修改个人信息

**URL:** /user/updateprofile

**Type:** POST

**Content-Type:** multipart/form-data

**Description:** 修改个人信息

**Query-parameters:**

Parameter	Type	Description	Required	Since
multipartFile	file	图片集	true	-
userid	int32	用户账号	false	-
username	string	用户名	false	-
email	string	邮箱	false	-
headimage	string	头像	false	-
banstate	string	用户状态	false	-
usertype	string	用户类型	false	-
logintime	string	登录时间	false	-
anonymousmode	boolean	匿名模式	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: multipart/form-data' -i /user/updateprofile --data
'banstate=封禁状态&logintime=2022-01-02
20:06:01&anonymousmode=true&usertype=管理员&username=张三
&email=2019192000@szu.edu.cn&headimage=05fe71557e164b32b503708271365dfd.pn
g&userid=2019192018'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-

data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 1.6 修改密码

**URL:** /user/changepassword

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 修改密码

**Body-parameters:**

Parameter	Type	Description	Required	Since
oldPassword	string	旧密码	false	-
newPassword	string	新密码	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /user/changepassword
--data '{
  "oldPassword": "xwcjjd",
  "newPassword": "pp5iq4"
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-

timestamp	string	时间戳	-
-----------	--------	-----	---

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 1.7 开启/关闭匿名模式

**URL:** /user/switchmode

**Type:** POST

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 开启/关闭匿名模式

**Request-example:**

curl -X POST -i /user/switchmode

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```



## 1.8 发送验证码

**URL:** /user/sendcode

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 发送验证码

**Query-parameters:**

Parameter	Type	Description	Required	Since
to	string	验证码发往的邮箱	false	-
flag	string	"exist"表示需要邮箱已注册(忘记密码); "noexist"表示需要邮箱未注册(注册, 修改邮箱)	false	-

**Request-example:**

```
curl -X GET -i /user/sendcode?flag=9hmqz&to=189g6v
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 1.9 忘记密码

**URL:** /user/forget

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 忘记密码

**Body-parameters:**

Parameter	Type	Description	Required	Since
newPassword	string	新密码	false	-
email	string	邮箱	false	-
code	string	验证邮箱的验证码	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /user/forget --data '{
  "newPassword": "123456789",
  "email": "123456789@qq.com",
  "code": "123456"
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 1.10 修改邮箱

**URL:** /user/changeemail

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 修改邮箱

**Body-parameters:**

Parameter	Type	Description	Required	Since
email	string	新邮箱	false	-
code	string	验证码	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /user/changeemail
--data '{
  "email": "jasper.ward@yahoo.com",
  "code": "39394"
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 2 帖子管理

### 2.1 查看帖子表

**URL:** /news/admin/checkNews

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 查看帖子表

**Query-parameters:**

Parameter	Type	Description	Required	Since
page	int32	页数	true	-
size	int32	每页记录数	true	-

**Request-example:**

```
curl -X GET -i /news/admin/checkNews?size=10&page=1
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└total	int64	总记录数	-
└list	array	结果集	-
└newsid	int32	帖子 id	-
└userid	int32	发帖人账号	-
└username	string	发帖人用户名	-
└headimage	string	发帖人头像 url	-

└─newstitle	string	标题	-
└─content	string	内容	-
└─sendtime	string	发布时间	-
└─viewnum	int32	浏览量	-
└─likenum	int32	点赞量	-
└─newstypename	string	帖子类型名字	-
└─imgUrls	array	帖子图像下载 url	-
└─pageNum	int32	当前页	-
└─pageSize	int32	每页数量	-
└─size	int32	当前页的数量	-
└─pages	int32	总页数	-
└─prePage	int32	前一页	-
└─nextPage	int32	下一页	-
└─firstPage	boolean	是否为第一页	-
└─lastPage	boolean	是否为最后一页	-
└─hasPreviousPage	boolean	是否有前一页	-
└─hasNextPage	boolean	是否有下一页	-

└navigatePages	int32	导航页码数	-
└navigateFirstPage	int32	导航条上的第一页	-
└navigateLastPage	int32	导航条上的最后一页	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "total": 704,
    "list": [
      {
        "newsid": 927,
        "userid": 274,
        "username": "dalton.pollich",
        "headimage": "g08bdj",
        "newstitle": "z45bme",
        "content": "k54bkl",
        "sendtime": "2022-01-02 20:06:01",
        "viewnum": 291,
        "likenum": 822,
        "newstypename": "dalton.pollich",
        "imgUrls": [
          "xgld22"
        ]
      }
    ]
  },
  "pageNum": 728,
  "pageSize": 10,
  "size": 10,
  "pages": 149,
  "prePage": 1,
  "nextPage": 1,
  "firstPage": true,
  "lastPage": true,
  "hasPreviousPage": true,
  "hasNextPage": true,
  "navigatePages": 116,
```

```
    "navigateFirstPage": 1,  
    "navigateLastPage": 1  
  },  
  "timestamp": "2022-01-02 20:06:01"  
}
```

## 2.2 查看帖子详情

**URL:** /news/view

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 查看帖子详情

**Query-parameters:**

Parameter	Type	Description	Required	Since
newsid	int32	帖子 id	true	-

**Request-example:**

```
curl -X GET -i /news/view?newsid=197
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└─newsid	int32	帖子 id	-
└─userid	int32	发帖人账号	-
└─username	string	发帖人用户名	-
└─headimage	string	发帖人头像 url	-
└─newstitle	string	标题	-

└content	string	内容	-
└sendtime	string	发布时间	-
└viewnum	int32	浏览量	-
└likenum	int32	点赞量	-
└newstypename	string	帖子类型名字	-
└anonymousstate	boolean	发帖人匿名状态	-
└imgUrls	array	帖子图像下载 url	-
└isLike	boolean	是否点赞	-
└comments	array	帖子评论	-
└commentid	int32	评论 id	-
└userid	int32	用户账号	-
└username	string	用户名	-
└headImage	string	用户头像	-
└commenttime	string	评论时间	-
└content	string	内容	-
└showreply	boolean	是否展示回复	-
└replynum	int32	回复数	-



↳replys	array	回复	-
↳replyid	int32	回复 id	-
↳targetid	int32	目标 id	-
↳commentid	int32	评论 id	-
↳userid	int32	用户账号	-
↳username	string	用户名	-
↳headImage	string	头像	-
↳commenttime	string	评论时间	-
↳content	string	评论内容	-
timestamp	string	时间戳	-

#### Response-example:

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "newsid": 761,
    "userid": 845,
    "username": "dalton.pollich",
    "headimage": "4uavkb",
    "newstitle": "lqkhm",
    "content": "tvnghv",
    "sendtime": "2022-01-02 20:06:01",
    "viewnum": 154,
    "likenum": 163,
    "newstypename": "dalton.pollich",
    "anonymousstate": true,
    "imgUrls": [
      "ifspIn"
    ],
  },
}
```

```
"isLike": true,
"comments": [
  {
    "commentid": 234,
    "userid": 871,
    "username": "dalton.pollich",
    "headImage": "vv6vvo",
    "commenttime": "2022-01-02 20:06:01",
    "content": "6vf43s",
    "showreply": true,
    "replynum": 3,
    "replies": [
      {
        "replyid": 21,
        "targetid": 666,
        "commentid": 76,
        "userid": 497,
        "username": "dalton.pollich",
        "headImage": "9x8mep",
        "commenttime": "2022-01-02 20:06:01",
        "content": "rkopat"
      }
    ]
  }
]
},
"timestamp": "2022-01-02 20:06:02"
}
```

## 2.3 获取所有帖子类型

**URL:** /news/getNewsType

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 获取所有帖子类型

**Request-example:**

curl -X GET -i /news/getNewsType

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-

code	int32	状态码	-
msg	string	处理信息	-
data	array	处理数据	-
└─typeid	int32	帖子类型编号	-
└─typename	string	帖子类型名	-
timestamp	string	时间戳	-

#### Response-example:

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": [
    {
      "typeid": 855,
      "typename": "dalton.pollich"
    }
  ],
  "timestamp": "2022-01-02 20:06:02"
}
```

## 2.4 发布帖子带图片

**URL:** /news/addwithimages

**Type:** POST

**Content-Type:** multipart/form-data

**Description:** 发布帖子带图片

#### Query-parameters:

Parameter	Type	Description	Required	Since
multipartFiles	file	图片集(array of file)	true	-
userid	int32	用户账号	false	-
newstitle	string	标题	false	-
content	string	内容	false	-
newstypeid	int32	帖子类型	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: multipart/form-data' -i /news/addwithimages --data 'userid=715&newstitle=5yzb1s&content=s7gsnc&newstypeid=383'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "waring": "You may have used non-display generics."
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 2.5 帖子点赞与取消点赞

**URL:** /news/likenews

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 帖子点赞与取消点赞

**Query-parameters:**

Parameter	Type	Description	Required	Since
newsid	int32	帖子 id	true	-

**Request-example:**

```
curl -X GET -i /news/likenews?newsid=881
```

**Response-fields:**

Field	Type	Description	Since
-------	------	-------------	-------

success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	array	处理数据	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": [
    483,
    570
  ],
  "timestamp": "2022-01-02 20:06:02"
}
```

## 2.6 帖子评论

**URL:** /news/comment

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 帖子评论

**Body-parameters:**

Parameter	Type	Description	Required	Since
newsid	int32	帖子 id	false	-
content	string	评论内容	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /news/comment --data '{
  "newsid": 811,
  "content": "682o4w"
}'
```

**Response-fields:**

Field	Type	Description	Since
-------	------	-------------	-------

success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└─newsid	int32	帖子 id	-
└─userid	int32	发帖人账号	-
└─username	string	发帖人用户名	-
└─headimage	string	发帖人头像 url	-
└─newstitle	string	标题	-
└─content	string	内容	-
└─sendtime	string	发布时间	-
└─viewnum	int32	浏览量	-
└─likenum	int32	点赞量	-
└─newstypename	string	帖子类型名字	-
└─anonymoustate	boolean	发帖人匿名状态	-
└─imgUrls	array	帖子图像下载 url	-
└─isLike	boolean	是否点赞	-
└─comments	array	帖子评论	-
└─commentid	int32	评论 id	-

└userid	int32	用户账号	-
└username	string	用户名	-
└headImage	string	用户头像	-
└commenttime	string	评论时间	-
└content	string	内容	-
└showreply	boolean	是否展示回复	-
└replynum	int32	回复数	-
└replys	array	回复	-
└replyid	int32	回复 id	-
└targetid	int32	目标 id	-
└commentid	int32	评论 id	-
└userid	int32	用户账号	-
└username	string	用户名	-
└headImage	string	头像	-
└commenttime	string	评论时间	-
└content	string	评论内容	-
timestamp	string	时间戳	-

**Response-example:**

```
{
```

```
"success": true,
"code": 200,
"msg": "success",
"data": {
  "newsid": 87,
  "userid": 849,
  "username": "dalton.pollich",
  "headimage": "hlbee9",
  "newstitle": "mgs0oi",
  "content": "iymq6d",
  "sendtime": "2022-01-02 20:06:01",
  "viewnum": 689,
  "likenum": 830,
  "newstypename": "dalton.pollich",
  "anonymousstate": true,
  "imgUrls": [
    "sbx0eh"
  ],
  "isLike": true,
  "comments": [
    {
      "commentid": 420,
      "userid": 572,
      "username": "dalton.pollich",
      "headImage": "1bwmpd",
      "commenttime": "2022-01-02 20:06:01",
      "content": "vqottz",
      "showreply": true,
      "replynum": 935,
      "replies": [
        {
          "replyid": 221,
          "targetid": 371,
          "commentid": 767,
          "userid": 387,
          "username": "dalton.pollich",
          "headImage": "6x0wht",
          "commenttime": "2022-01-02 20:06:01",
          "content": "og3zc2"
        }
      ]
    }
  ]
}
],
},
```



```
"timestamp": "2022-01-02 20:06:02"
}
```

## 2.7 帖子回复

**URL:** /news/reply

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 帖子回复

**Body-parameters:**

Parameter	Type	Description	Required	Since
commentid	int32	评论 id	false	-
content	string	内容	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /news/reply --data '{
  "commentid": 17,
  "content": "i6yavo"
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└─newsid	int32	帖子 id	-
└─userid	int32	发帖人账号	-
└─username	string	发帖人用户名	-
└─headimage	string	发帖人头像 url	-
└─newstitle	string	标题	-

└content	string	内容	-
└sendtime	string	发布时间	-
└viewnum	int32	浏览量	-
└likenum	int32	点赞量	-
└newstypename	string	帖子类型名字	-
└anonymousstate	boolean	发帖人匿名状态	-
└imgUrls	array	帖子图像下载 url	-
└isLike	boolean	是否点赞	-
└comments	array	帖子评论	-
└commentid	int32	评论 id	-
└userid	int32	用户账号	-
└username	string	用户名	-
└headImage	string	用户头像	-
└commenttime	string	评论时间	-
└content	string	内容	-
└showreply	boolean	是否展示回复	-
└replynum	int32	回复数	-

↳replys	array	回复	-
↳replyid	int32	回复 id	-
↳targetid	int32	目标 id	-
↳commentid	int32	评论 id	-
↳userid	int32	用户账号	-
↳username	string	用户名	-
↳headImage	string	头像	-
↳commenttime	string	评论时间	-
↳content	string	评论内容	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "newsid": 486,
    "userid": 8,
    "username": "dalton.pollich",
    "headimage": "jpcfgv",
    "newstitle": "sdk6g3",
    "content": "873bdx",
    "sendtime": "2022-01-02 20:06:01",
    "viewnum": 483,
    "likenum": 126,
    "newstypename": "dalton.pollich",
    "anonymousstate": true,
    "imgUrls": [
      "3oqi2f"
    ],
  },
}
```

```
"isLike": true,
"comments": [
  {
    "commentid": 527,
    "userid": 795,
    "username": "dalton.pollich",
    "headImage": "n14dns",
    "commenttime": "2022-01-02 20:06:01",
    "content": "zkkf4t",
    "showreply": true,
    "replynum": 618,
    "replies": [
      {
        "replyid": 461,
        "targetid": 187,
        "commentid": 223,
        "userid": 458,
        "username": "dalton.pollich",
        "headImage": "91lz66",
        "commenttime": "2022-01-02 20:06:01",
        "content": "cbwd3d"
      }
    ]
  }
]
},
"timestamp": "2022-01-02 20:06:02"
}
```

## 2.8 搜索帖子

**URL:** /news/search

**Type:** POST

**Content-Type:** application/json; charset=utf-8

**Description:** 搜索帖子

**Body-parameters:**

Parameter	Type	Description	Required	Since
key	string	关键词	false	-
sort	int32	排序方式 1=按时间排序	false	-

		2=按浏览量排序 3=按点赞量排序		
type	string	查找的帖子类型	false	-
pageSize	int32	每页的记录数	false	-
pageNum	int32	当前页数	false	-

**Request-example:**

```
curl -X POST -H 'Content-Type: application/json; charset=utf-8' -i /news/search --data '{
  "key": "饭堂",
  "sort": 1,
  "type": "校园卡丢失",
  "pageSize": 8,
  "pageNum": 1
}'
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└total	int64	总记录数	-
└list	array	结果集	-
└newsid	int32	帖子 id	-
└userid	int32	发帖人账号	-
└username	string	发帖人用户名	-
└headimage	string	发帖人头像 url	-
└newstitle	string	标题	-
└content	string	内容	-

└sendtime	string	发布时间	-
└viewnum	int32	浏览量	-
└likenum	int32	点赞量	-
└newstypename	string	帖子类型名字	-
└imgUrls	array	帖子图像下载 url	-
└pageNum	int32	当前页	-
└pageSize	int32	每页数量	-
└size	int32	当前页的数量	-
└pages	int32	总页数	-
└prePage	int32	前一页	-
└nextPage	int32	下一页	-
└firstPage	boolean	是否为第一页	-
└lastPage	boolean	是否为最后一页	-
└hasPreviousPage	boolean	是否有前一页	-
└hasNextPage	boolean	是否有下一页	-
└navigatePages	int32	导航页码数	-
└navigateFirstPage	int32	导航条上的第一页	-

└navigateLastPage	int32	导航条上的最后一页	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "total": 37,
    "list": [
      {
        "newsid": 16,
        "userid": 391,
        "username": "dalton.pollich",
        "headimage": "6kzv6f",
        "newstitle": "u2aik1",
        "content": "zdilcx",
        "sendtime": "2022-01-02 20:06:01",
        "viewnum": 162,
        "likenum": 742,
        "newstypename": "dalton.pollich",
        "imgUrls": [
          "m2sitk"
        ]
      }
    ],
    "pageNum": 692,
    "pageSize": 10,
    "size": 10,
    "pages": 378,
    "prePage": 1,
    "nextPage": 1,
    "firstPage": true,
    "lastPage": true,
    "hasPreviousPage": true,
    "hasNextPage": true,
    "navigatePages": 476,
    "navigateFirstPage": 1,
    "navigateLastPage": 1
  },
  "timestamp": "2022-01-02 20:06:02"
}
```

## 2.9 查看我的帖子

**URL:** /news/mynews

**Type:** GET

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 查看我的帖子

**Query-parameters:**

Parameter	Type	Description	Required	Since
page	int32	当前页数	true	-
size	int32	每页记录数	true	-

**Request-example:**

```
curl -X GET -i /news/mynews?size=10&page=1
```

**Response-fields:**

Field	Type	Description	Since
success	boolean	成功标志	-
code	int32	状态码	-
msg	string	处理信息	-
data	object	处理数据	-
└total	int64	总记录数	-
└list	array	结果集	-
└newsid	int32	帖子 id	-
└userid	int32	发帖人账号	-
└username	string	发帖人用户名	-
└headimage	string	发帖人头像 url	-
└newstitle	string	标题	-



└─content	string	内容	-
└─sendtime	string	发布时间	-
└─viewnum	int32	浏览量	-
└─likenum	int32	点赞量	-
└─newstypename	string	帖子类型名字	-
└─imgUrls	array	帖子图像下载 url	-
└─pageNum	int32	当前页	-
└─pageSize	int32	每页数量	-
└─size	int32	当前页的数量	-
└─pages	int32	总页数	-
└─prePage	int32	前一页	-
└─nextPage	int32	下一页	-
└─firstPage	boolean	是否为第一页	-
└─lastPage	boolean	是否为最后一页	-
└─hasPreviousPage	boolean	是否有前一页	-
└─hasNextPage	boolean	是否有下一页	-
└─navigatePages	int32	导航页码数	-

└navigateFirstPage	int32	导航条上的第一页	-
└navigateLastPage	int32	导航条上的最后一页	-
timestamp	string	时间戳	-

**Response-example:**

```
{
  "success": true,
  "code": 200,
  "msg": "success",
  "data": {
    "total": 812,
    "list": [
      {
        "newsid": 632,
        "userid": 891,
        "username": "dalton.pollich",
        "headimage": "oli68i",
        "newstitle": "4w39ol",
        "content": "a8brve",
        "sendtime": "2022-01-02 20:06:01",
        "viewnum": 352,
        "likenum": 150,
        "newstypename": "dalton.pollich",
        "imgUrls": [
          "rf41m7"
        ]
      }
    ]
  },
  "pageNum": 609,
  "pageSize": 10,
  "size": 10,
  "pages": 796,
  "prePage": 1,
  "nextPage": 1,
  "firstPage": true,
  "lastPage": true,
  "hasPreviousPage": true,
  "hasNextPage": true,
  "navigatePages": 40,
  "navigateFirstPage": 1,
  "navigateLastPage": 1
}
```

```
},  
  "timestamp": "2022-01-02 20:06:02"  
}
```