AgentLedger: A Trusted Collaboration and Settlement Community for Agents

COMP7610 Final Project Report

Version: v1.0-delivery-candidate (2026-11-08; final narrated demonstration and delivery-status synchronisation)

Source snapshot: main `70629990d78a62c059a53d6df5c3c3c2b9e9a08e`, including report integration #70 and Social v2 recording #75. Functional code baseline remains `2e59b10` (#67). The recorded historical suite result is 112 tests (see §7.1); video production does not establish a new full-suite result or deployment. No application, contract, ABI, generated artefact or deployment address is changed by this delivery revision.

Release scope: the v0.9 report was approved and merged through #70, closing #9. This candidate synchronises the report with the narrated demonstration produced on 2026-11-08. The candidate still requires peer review; refreshed report/PDF/video hashes and the final submission version must be recorded after merge under #11. No new Sepolia run, independent-user study, final freeze or course submission is claimed.

Every figure in this report is taken from a file in the repository or from an on-chain receipt. Items that could not be verified are listed in §12 instead of being filled with estimates.

---

1. Abstract

AgentLedger is a community application deployed on the Ethereum Sepolia testnet. It addresses a specific question: how can AI agents (or their owners) establish trustworthy working relationships and settle the value they create?

Its target users are agent developers and operators seeking complementary collaborators. The product explores how discovery can develop into a mutually acknowledged working relationship and an inspectable collaboration history. User demand and retention remain hypotheses, not measured outcomes.

The system uses **circles** to organise interests, **posts and replies** to enable discovery, **teams** to formalise a one-to-one working agreement, **shared works** to record an output confirmed by both parties, and an **escrow contract** to handle payment, refund, and timeout-based claims.

The core DApp is a static frontend: browser-initiated writes are signed by the user's wallet, and reads use public RPC. The optional Node.js agent service is an off-chain component with its own operator-controlled signing wallet, card endpoint and persisted delivery files. AgentCommunity has no privileged administrator, pause or upgrade entry point; its permissions derive from circle membership, optional Agent NFT attribution and team participation. The new history/activity pages are read-only projections of loaded records, not new on-chain writes or proof of user adoption.

Verification combines local automated tests, browser and cross-platform checks, and Sepolia acceptance. Only the recorded testnet transactions and explicitly identified read-only RPC probes are Sepolia evidence; local EVM tests, Demo sandbox data and simulated live browser checks are not real Sepolia/RPC/MetaMask acceptance. In Zqqq-qq's runs, Account 1 and Account 2 were controlled by one operator who personally confirmed the wallet transactions; two account addresses do not establish two independent human testers. Scale of the work at the stated code baseline:

Dimension	Value
Contracts	Five source files: community, identity, reputation, escrow and the mUSD test token
Frontend	17 top-level JavaScript modules under `web/`, excluding the vendored ethers dependency

Dimension	Value
Automated tests	21 top-level test files; archived result: 112 tests, with platform-specific pass/skip details in §7.1
Community flow	9 real transactions forming the complete loop, each with a receipt
Escrow flow	3 jobs in the standalone escrow acceptance (normal payment, refund after non-delivery, claim after timeout); jobs 4 and 5 are the two cross-module runs in §7.6
Cross-platform	macOS and Windows both ran a clean-clone verification at the **same commit** `7db718a`

---

2. Background and Problem Definition

Collaboration between several parties (or several agents) is hard for three reasons, none of which is "can we talk to each other":

1. **Discovery**: finding a counterpart with complementary skills rather than pairing at random.

2. **Agreement**: turning "who does what, and when is it done" into a record both sides accept.

3. **Settlement**: making "confirm the output" and "pay for it" part of one auditable process instead of relying on chat screenshots.

A collaboration can span a discussion platform, a portfolio and a payment service. Participants may then have to reconcile separate records of an agreement, an acknowledgement and a payment. AgentLedger explores making these actions inspectable through a shared community and escrow interface. The community-to-job reference is checked by the application; the contracts do not enforce a single atomic workflow across every step.

`docs/BLUEPRINT.zh-CN.md` is the functional blueprint written at the planning stage. It contains several ideas that were **not** implemented; this report only describes what was built and verified. The difference between blueprint and implementation is documented in `docs/IMPLEMENTATION.zh-CN.md` ("differences from the original full plan").

2.1 Why a Social DApp: relationships formed through collaboration

The intended users are agent developers and operators who want to find people with complementary skills, discuss a concrete need and build a visible history of working together. AgentLedger focuses on **relationships formed by doing something together**. Its social contribution is the distinction between attention, commitment and acknowledgement:

Interaction	Meaning	Implemented mechanism
Follow	Interest in another account	`setFollow`
Accept a team invitation	Consent to a specific collaboration	`respondTeam`, restricted to the invited account
Confirm a shared work	The other participant acknowledges the proposed output record	`reviewWork`; self-confirmation and third-party confirmation are rejected

These records express different levels of participation. A completed collaboration can give a future partner more context than a follower count, but it is not an objective trust score. The contract records consent and updates pairwise collaboration counts; it cannot establish that participants are independent people or that a work is useful.

The course material **DApps in Web3** (provided as `DApps v2.pdf`, slide 11, "Social Dapps: Lens Protocol") motivates user-controlled identity and shared social data accessible to other frontends. AgentLedger applies that motivation to collaborative work. This is a comparison to the lecture's example, not a claim of compatibility with Lens or of implementing all its features.

2.2 Illustrative user story and reason to return

Illustrative scenario, not an additional acceptance run. A developer operates a data-analysis agent and wants a collaborator who can visualise its results. They discover a relevant circle, publish a task and discuss the scope through replies. They inspect a potential partner's public information and available collaboration records, agree on roles and form a team. After producing an output, one participant proposes a shared work and the other confirms or rejects its record. For paid work, a separately linked escrow job handles funding, a delivery digest and settlement under its own rules.

The proposed participation loop is **discover a partner -> discuss a task -> agree to collaborate -> acknowledge an output -> present the resulting history -> find a future partner**. Discovery offers a reason to arrive, a concrete task offers a reason to interact, and maintaining a portfolio and finding another engagement could offer reasons to return. These are product hypotheses; there has been no study of demand, retention or network effects. The prototype now provides the two read-only views described in §2.5, but their adoption is untested.

The scenario is grounded in separate implementation evidence: the community acceptance (§7.2) covers the social workflow and shared-work confirmation; team 3 -> job 5 (§7.6) covers invitation acceptance, a public application-level reference, delivery and payment of 1 test mUSD. The latter run used two accounts controlled by one user, Agent IDs 0, and did not publish a shared work. These records must not be presented as one observed user journey or as autonomous agent collaboration.

2.3 Why blockchain is relevant, and what it costs

The useful boundary is a publicly inspectable record of commitments and acknowledgements. Wallet signatures attribute actions to accounts, contract permissions determine who may accept or confirm, and escrow executes declared settlement rules. Another frontend can read the same public contract state without asking this project's operator to supply its database. This supports shared access and verifiable execution; cross-application adoption has not been demonstrated.

For ordinary conversation, a conventional server can offer a simpler and cheaper experience. This prototype stores posts and replies on-chain, making the records public and costly to write (§5.3). Wallet prompts, immutable deployments, reliance on frontend/RPC availability and externally hosted work content are material limitations. Blockchain does not automatically provide privacy, continuous availability of every interface or proof that a claim is true. A production design should evaluate off-chain discussion with on-chain commitments and content hashes.

2.4 Boundaries of the social claims

Shared-work confirmation proves the other team account expressed approval; it does not prove quality, original authorship, actual labour or absence of collusion.

Follows and collaboration counts are keyed by wallet addresses. Optional Agent IDs are checked at specified actions; social history is not automatically transferred with an Agent NFT. The recorded team 3 / job 5 run did not validate nonzero Agent identity attribution.

Community-to-escrow references are application-validated records; shared-work approval does not release escrow funds. ReputationRegistry is separate and feedback is not contractually verified against a job.

The project has demonstrated workflows and rejection rules, not real-world adoption or an autonomous agent society.

2.5 Account-scoped social views (implemented 2026-11-02)

PR #67 adds two read-only views built from the same loaded community records:

1. **My collaboration history** (`#portfolio`) shows the connected wallet's partners, mutually acknowledged works with their source discussion, recent posts, and explicitly verified order references. A confirmed work and a paid job remain separate facts: the order block validates a public reference against the community, escrow, token and both identity registries, and `Completed` is not treated as proof of human acceptance (it can also be a timeout claim). Existing profile pages reuse the same portfolio projection.

2. **My activity** (`#activity`) shows pending invitations addressed to the wallet, proposed works awaiting its review, and replies by others to its posts. Self-replies, self-confirmation and terminal teams are excluded; each row opens the source team, work or thread. There is no push service, unread state or read receipt.

Both views are projections of the loaded window (default 40 records per type), not a claim of all history. Orders are scanned separately from public replies at a fixed block, with a 1,000-reply limit; verification failure, an unverified session and a completed scan with no valid reference are shown as different states. Refreshing or changing wallet/mode/config invalidates an in-flight scan, so a late response cannot publish another account's rows. Adoption, retention and independent-user evaluation remain untested; no new writes, contracts or transactions were added.

---

3. Requirements and Scope

3.1 Roles

The repository is organised around five roles plus release. Tasks and dependencies are recorded in `docs/project/TEAM_TASKS.zh-CN.md`:

Role	Scope	Tasks
A Frontend & UX	Six interface areas, mobile layout	#1 A1, #2 A2
B Contracts & Permissions	Permission model, state machines, content boundaries	#3 B1, #4 B2
C Wallet & Deployment	MetaMask integration, Sepolia deployment, multi-device config	#5 C1, #6 C2, #12 C3
D Testing & Acceptance	End-to-end flows, failure paths, CI and cross-platform regression	#7 D1, #8 D2
E Report & Integration	Report, demo, final submission	#9 E1, #10 E2
R Release	Freeze, submission artefacts, backup	#11 R1

3.2 Status at the baseline

Closed (14): #1 (A1 interface acceptance), #2 (A2 status guidance), #3 (B1 permission review), #4 (B2 content boundaries), #5 (C1 community deployment), #6 (C2 wallet switching and cross-device), #7 (D1 dual-wallet acceptance), #8 (D2 CI and cross-platform regression), #12 (C3 escrow integration), #20 / #21 / #25 (three defects), #30 (circle/team permission semantics), #39 (README banner and community visuals).

Open (3): #9 / #10 / #11 (E1 report, E2 demo, R1 release).

3.3 Scope boundaries

The core DApp requires no central business backend. Contract state is authoritative for on-chain records; browser-local settings/Demo data and optional service metadata/delivery files remain off-chain. The service uses a dedicated environment-configured wallet; the browser does not hold that key.

Settlement uses **a valueless test token** (mUSD, 6 decimals), never real assets.

No cross-chain support, no proxy upgradeability, no governance (the contracts have no owner).

---

4. System Design

4.1 Architecture




Figure 1. Implementation architecture, not an acceptance-session diagram. The user-wallet box represents a signing role, not a count of human operators or devices. Zqqq-qq controlled both test accounts in their recorded runs; the social-view browser checks used Demo/simulated data and do not establish new Sepolia, real RPC or MetaMask acceptance. Independent peer checks retain their separate attribution.

The diagram distinguishes the **static browser DApp**, **user wallet and public RPC**, **five on-chain contracts**, and the **optional off-chain agent service and files**. The browser includes the two account-scoped social views; the service has a separate operator-controlled wallet and availability/storage responsibilities. Three core paths must not be confused:

Path	Trigger	Signature required
Read	`eth_call` / `eth_getCode` against a contract address when a page loads	No
Write	User submits in the UI -> wallet signs -> transaction is broadcast	Yes

Path	Trigger	Signature required
Contract-to-contract	`AgentCommunity` calls `IdentityRegistry.ownerOf`; `JobEscrow` validates `Identity.exists / ownerOf` when a job is created, and calls `transfer / transferFrom` on the token supplied with the job	Executed internally by the contracts

`ReputationRegistry` is an independent module: no other contract calls it, feedback is written against a signature, and it has no on-chain coupling to the community or escrow flows.

4.2 Contracts and permission model

AgentCommunity exposes every community-side write (full list in `contracts/AgentCommunity.sol`):

Membership: `setMembership(circleId, joined)`

Content: `createPost` / `createReply` / `setFollow`

Collaboration: `inviteTeam` / `respondTeam` / `cancelTeam`

Output: `proposeWork` / `reviewWork`

Reads: `getPost` / `getReply` / `getTeam` / `getWork` / `member` / `memberCount` / `collaborationCount`, among others

Events: `MembershipChanged`, `PostCreated`, `ReplyCreated`, `FollowChanged`, `TeamInvited`, `TeamChanged`, `WorkProposed`, `WorkReviewed`.

Permission model: the contract has **no owner, admin, pause, or upgrade function**. Permissions derive from three things:

Source	What it decides
Circle membership `member[circle][sender]`	Who may post, reply, invite, and accept an invitation
Agent NFT ownership (`identity.ownerOf(agentId)`)	Whether an action can be attributed to an Agent
Team participation (`sender == host or guest`)	Who may propose and review work

The function-by-function permission table, including every revert reason, is in `docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md` §1.

State machines (ibid. §2):

```
Team:  None --inviteTeam--> Pending --respondTeam(accept)--> Active
                              |
                              +--respondTeam(decline)--> Declined
                              +--cancelTeam(host)-----> Cancelled

Work:  None --proposeWork--> Proposed --reviewWork(true)--> Published
                                  +----reviewWork(false)-> Rejected
```

Two constraints matter:

A team may have **only one pending work at a time** (otherwise `review pending work first`), which prevents a burst of self-serving confirmations.

`reviewWork` is restricted to "the other party in the team", so both self-confirmation and third-party confirmation are rejected with `only other member`. This is what makes the collaboration record credible.

4.3 Escrow design

JobEscrow manages a single engagement between a client and a provider (`createJob` / `submit` / `release` / `claim` / `refund`; events `JobCreated` / `JobSubmitted` / `JobReleased` / `JobRefunded`). **MockUSDC** supplies a 6-decimal test token.

Three settlement paths: release on client approval, refund after the submission deadline passes without delivery, and claim by the provider once the review window expires without client action.

4.4 Frontend

A static site with 17 top-level JavaScript modules under `web/` (excluding the vendored ethers dependency), grouped by responsibility:

Layer	Modules	Purpose
Entry & routing	`app.js`	View switching, wallet connection, shared interactions
Community	`social.js`, `social-core.js`, `social-chain.js`	Rendering, pure state helpers, on-chain read/write
Social projections	`social-insights.js`	Account-scoped portfolio, relevant activity and verified-order projections; rendered by `social.js`
Discovery and HTTP payment	`agent-card.js`, `market.js`, `x402.js`	Card generation/parsing, loaded-page market filters, hire prefill and simplified HTTP payment client
Escrow	`escrow.js`, `escrow-core.js`, `escrow-link-ui.js`, `escrow-links.js`, `escrow-deploy.js`	Job UI, validation, linking to community teams, deployment records
Shared	`core.js`, `config.js`, `wallet-session.js`, `deployment-evidence.js`	Address validation, error messages, session recovery, deployment evidence

---

5. Implementation Notes

5.1 Browser community writes use the wallet and check the network first

Writes go through `sendCommunity()` in `web/social-chain.js`. Before sending, it reads the signing wallet's `eth_chainId` and refuses to proceed unless it is Sepolia (`11155111`), so a user cannot sign on the wrong network. Covered by `tests/wallet-recovery.test.mjs`.

5.2 Impossible submissions are disabled at circle-selection time

An earlier build allowed publishing into a circle the user had not joined; the contract rejected it with `join circle first`. Measurement showed something important: because ethers performs `eth_estimateGas` before sending, such a call **reverts during estimation**, so no gas is spent and no wallet prompt appears - the user simply saw a raw English revert string.

Two changes followed (PR #23):

1. **Up-front gating**: `syncPostGate()` in `web/social.js` keeps the submit button in sync when rendering and when the circle changes; it disables submission with an explanation when the selected circle has not been joined. The reply form uses the circle of the post.

2. **Message mapping**: `errorMessage` in `web/core.js` gained 10 human-readable mappings (20 in the table overall), so `join circle first` now reads "Join this circle before posting or replying - the contract only accepts members."

5.3 The real cost of on-chain storage (measured)

Titles, bodies, and delivery summaries are stored directly in the contracts. This is deliberate - it keeps content and attribution tamper-evident - and the price is that storage dominates the cost. Measured `gasUsed`, taken from receipts rather than estimates:

Operation	Block	gasUsed
Deploy AgentCommunity	12005434	17,182,618
`setMembership` (A joins)	12005903	471,403
`setMembership` (B joins)	12005918	373,483
`createPost` (title and body)	12005976	1,583,822
`createReply`	12006011	1,033,402
`setFollow`	12006028	464,043
`inviteTeam`	12006044	1,141,341
`respondTeam`	12006058	45,366
`proposeWork` (summary and link)	12006079	1,903,577
`reviewWork`	12006101	258,347

The ten transactions total `24,457,402` gas. The **deployment accounts for 70.3%**, at a cost of `0.02577 ETH` (`effectiveGasPrice` 1,500,000,014 wei, approximately 1.5 gwei; wallet settings unconfirmed); the other nine executed at 16 / 18 / 25 wei and cost about `0.00000000012 ETH` together, i.e. negligible.

Deployment operations and limits of the record. The contemporaneous acceptance and handoff records describe the local project webpage in Chrome with MetaMask 13.54.0; the user personally confirmed the Sepolia deployment. The deployment-source snapshot (`fb6c325`) calls ethers.js `ContractFactory.deploy(registry)` without explicit `gasLimit`, `gasPrice`, `maxFeePerGas` or `maxPriorityFeePerGas` overrides. This establishes the application-side call, not the settings finally chosen in MetaMask. On 2026-10-30 the deployer stated that they could not remember whether they manually edited gas or fees; this remains **unconfirmed**. The stored RPC receipt confirms `gasUsed` and the effective price, but does not preserve the transaction gas limit, fee caps, wallet estimate or confirmation-screen settings. The previous phrase "the wallet default" was unsupported and has been removed. No execution trace or historical replay has established why this deployment used 17.18M gas. The source-by-source record and remaining unknowns are in Deployment operation record.

Effect of text length on cost (RPC gas estimates): using `eth_estimateGas` on the same `createPost(circle 2, agentId 0, kind 0)` while varying only the body length:

Body length (characters)	Estimated gas
10	594,708
500	2,378,352
1,000	4,162,193

Body length (characters)	Estimated gas
2,000	7,618,764
4,000	14,531,945

Going from 10 to 4,000 characters multiplies the estimate by about 24. The real post 2 has a 224-character body and a 38-character title; its receipt shows 1,583,822 gas, which sits where the curve predicts.

For the measured inputs, the estimates illustrate that longer stored text materially increases write cost; byte length and execution context also matter. Contract text limits use UTF-8 bytes, not a universal character-count model. The implementation conclusion is therefore that **on-chain text storage is a significant cost trade-off**. Reducing cost would mean storing the body off-chain and keeping only a hash on-chain, which trades away readability; this project deliberately keeps readability.

> Scope note: the composition of the deployment transaction's gas (11,220 bytes of creation input, 10,973 bytes of runtime code) is not attributed further; only the receipt value is reported.

5.4 How failures appear in the UI

The two kinds of rejection behave differently, and this was checked explicitly during acceptance:

Source of rejection	UI behaviour
User cancels in the wallet	Red message `Request cancelled in your wallet. No action was completed.`; the button remains usable and no intermediate state is left behind
Contract rule rejects during gas estimation	The contract reason is shown (mapped to readable text); **no wallet prompt and no transaction**

---

6. Deployment and Operations

6.1 Deployment facts

Item	Value
Network	Ethereum Sepolia (chainId 11155111)
Contract address	`0x8CDc9987D46D140a982713B359286bC451262406`
Deployment transaction	`0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5`
Deployment block	12005434
Deployer	`0xD3Ce5196125cd6e25212de4D04911093D3F62D5d`
Constructor argument	`["0x13eA93eCdDeed63259792A39d7a4738a28b3E91d"]` (IdentityRegistry)
Compiler	solc 0.8.30, optimizer enabled / runs 200, viaIR, evmVersion shanghai
Runtime code size	10,973 bytes
runtime keccak256	`0x42953724f77e05c99bf2f08f5faa057211268ec0973fe17e59cd072f61cafde7`
creation keccak256	`0x71c9098723ea3e4b4929493ebd3ddccfce0b684ddf95566332795e1c672f91e0`

How consistency is proven: the project does not rely on block-explorer source verification (the contract is **not** verified on Etherscan). Instead, `scripts/verify-community.mjs` reads the deployment transaction's creation input and the on-chain runtime code and compares both against the repository artefacts:

```
node scripts/verify-community.mjs \
  --tx 0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5 \
  --address 0x8CDc9987D46D140a982713B359286bC451262406 --output evidence.json
```

Independent runs by several members produced identical `creationBytecodeHash` and `runtimeCodeHash`.

6.2 A real deployment incident and its remediation

On 2026-10-27 a duplicate deployment occurred: while the shared address had not yet been recorded, another member deployed its own instance at `0xe398…68ac`. Two members were then writing to different contracts and could not see each other's content.

Remediation (Issue #20, closed):

1. A pre-deployment checklist at the **top** of `docs/project/DEPLOYMENTS.md`: check this file first -> run the read-only verification -> record immediately in the same pull request as the deployment -> announce one shared address to the whole team.

2. Keep the duplicate in the history but mark it as "not adopted".

3. Keep the wording discipline that "read-only verification is not the same as block-explorer source verification".

---

7. Testing and Acceptance

7.1 Automation and CI

Evidence and operator scope (Issue #9). Local Ganache tests, Demo sandbox checks, simulated live browser fixtures, real read-only Sepolia RPC observations and wallet-signed Sepolia transactions are separate evidence categories. A simulated RPC failure is a fixture result, not an observation of a live RPC provider. In Zqqq-qq's wallet acceptance records, Account 1 and Account 2 are two test accounts controlled by the same user; Zqqq-qq personally confirmed transactions in MetaMask. These records do not demonstrate two members independently operating wallets, cross-device signing or independent peer acceptance. Other members' documented independent verification is credited separately; this clarification does not reattribute the distinct D1 or cross-module runs below.

CI is defined in `.github/workflows/ci.yml`. The `verify` job runs on `ubuntu-latest` in seven steps: checkout -> Node 24 -> install pnpm 11.25.0 -> `pnpm install --frozen-lockfile` -> `pnpm test` -> confirm the committed contract artefact is unchanged (`git diff --exit-code -- web/generated/AgentCommunity.json`) -> `pnpm build`.

The reviewed source snapshot contains **21 top-level test files**. Repository acceptance and freeze records report **112 tests** at the stated functional baseline; the Windows record is **111 pass plus one deliberately skipped CLI fixture**, while CI is recorded as 112 pass. These are attributed historical results, not a claim that all tests or both platforms were rerun for this editorial revision. Coverage spans contract permissions and state machines, frontend pure functions, wallet recovery and session handling, deployment evidence, escrow and community integration, UI message mapping, status guidance, content-boundary and URI rules, report-PDF generation, freeze-manifest validation, circle/team permission regressions, marketplace filters, agent cards, the sample agent service, x402 payments and collaboration-history/activity projections.

The automated suite executes locally: contract tests deploy to an in-memory Ganache EVM, while frontend, wallet and service tests use pure functions or controlled fixtures. These results do not represent Sepolia transactions. The testnet evidence is identified separately below by transaction receipts, fixed-block RPC probes and state reads; the cross-platform Demo screenshot in §7.8 verifies local startup only. Counts refer to the code baseline above.

`tests/d1-failure-path.test.mjs` raises four rejection paths from "throws an error" to "is rejected **for the specific reason the contract declares**", so that a broken implementation cannot keep the suite green.

7.2 Dual-wallet end-to-end (D1 / #7)

Nine steps executed on Sepolia. Blocks are receipt values:

Step	Block	Method	Event
A joins circle	12005903	`setMembership`	`MembershipChanged(2, A, true)`
B joins circle	12005918	`setMembership`	`MembershipChanged(2, B, true)`
A posts	12005976	`createPost`	`PostCreated(2, 2, A)`
B replies	12006011	`createReply`	`ReplyCreated(2, 2, B)`
A follows B	12006028	`setFollow`	`FollowChanged(A, B, true)`
A invites B	12006044	`inviteTeam`	`TeamInvited(1, 2, B)`
B accepts	12006058	`respondTeam`	`TeamChanged(1, status=2)`
A proposes work	12006079	`proposeWork`	`WorkProposed(1, 1, A)`
B confirms	12006101	`reviewWork`	`WorkReviewed(1, status=2)`

Consistency checks: work 1 is `Published` and work 2 is `Proposed`; `collaborationCount(A,B)` and `(B,A)` are both **1**, exactly the number of published works; `following(A,B)=true` and `following(B,A)=false`.

7.3 Rejection paths

Eight `eth_call` probes at the fixed block **12011205** (four rejections, four positive controls, changing only the caller or the circle):

Case	Result
Third party accepts a pending team	`only invited partner`
Invited party accepts the same team (control)	succeeds
Author confirms own work	`only other member`
Other member confirms (control)	succeeds
Post into a circle not joined	`join circle first`
Post into a joined circle (control)	succeeds
Confirm an already published work	`work not pending`
Confirm a pending work (control)	succeeds

> A caveat worth recording: "post into a circle not joined" must use a circle the account has **not** joined. The first run used a circle the account had since joined, and the probe succeeded; switching to an unjoined circle reproduced `join circle first`. This was a parameter mistake, not a contract defect.

7.4 Three escrow settlement paths

Three jobs executed on Sepolia in Zqqq-qq's recorded escrow acceptance. The client and provider test accounts were controlled by the same operator, who personally confirmed the MetaMask transactions; this is a two-account protocol check, not independent two-member acceptance:

Job	Result	Description
Job 1	`Completed`(3)	Client approved; 1 mUSD paid to the provider
Job 2	`Refunded`(4)	Deadline passed without delivery; 1 mUSD returned to the client
Job 3	`Completed`(3)	Client did not act; provider claimed after the 60-second review window

Final snapshot at block 12010056: client **98 mUSD**, provider **2 mUSD**, escrow contract **0 mUSD**, summing to 100.

Boundary precision: job 3 was submitted at 12:48:48 with a 60-second review window. At block 12010027, whose timestamp is exactly 12:49:48, `claim` still returned `review window open`; only a later block succeeded. This shows the implementation does not release early.

7.5 Cross-browser, cross-device, and real wallet

Scenario	Observation
Another browser (fresh Edge profile, no wallet)	Read the same content as Chrome, including the confirmed work with `Confirmed at block 12010030`
Another device (separate browser and storage, no wallet)	Read 2 posts and the same confirmed work, with the same recorded two-account work confirmation
Real wallet, successful write	Joined a circle -> the button changed from `Join circle` to `Leave circle` -> left again to restore state; both transactions `status=1`
Real wallet, cancelled signature	`Request cancelled in your wallet. No action was completed.`; on-chain nonce unchanged

Boundary: the second device was used for **read-only** verification only; no cross-device signed write was performed. This table combines separately documented observations, not a single multi-device signing session. Zqqq-qq's own Account 1 / Account 2 switching and failure-recovery checks used one operator; other members' independent observations remain separately attributed.

7.6 Cross-module entry point: community team -> funded escrow job (verified)

This flow spans both modules and was executed end to end with two wallets on Sepolia on 2026-10-28.

Step	On-chain result
A mints test mUSD	100 mUSD to the client wallet
A publishes a task post	post 4, circle 2, kind 1 ("open task")
A invites B	team 4, host A, guest B, status Pending(1)

Step	On-chain result
B accepts	team 4 status **Active(2)**
A approves 1 mUSD for the escrow	allowance consumed by the funding below
A creates and funds the job from the team	**job 4**, 1 mUSD escrowed
B submits a delivery digest	job 4 moves to submitted
A accepts and releases	job 4 status **Completed(3)**

Final balances after release, read at block 12012205: **client 99 mUSD, provider 1 mUSD, escrow contract 0 mUSD** - the 1 mUSD left the client exactly once and arrived at the provider exactly once, and no funds remain locked.

The team is linked to the job in the application layer only: the UI associates a team with an escrow job and can publish a client-authored reference as a community reply so the link is publicly checkable. JobEscrow itself has no team field. As the UI states, references "do not enforce settlement, prove quality, split payments or make feedback order-verified." This is a deliberate boundary, not an oversight.

> Earlier state (kept for accuracy): before this run, a task post (post 3) and a team invitation (team 3) existed on-chain between two accounts of the same operator, but the invitation had not yet been accepted and no job had yet been funded from that team at the time of that earlier snapshot. That is why an earlier version of this report listed the cross-module path as unverified. **That gap was closed on 2026-10-29** by the second run below.

Second cross-module run (2026-10-29, team 3 -> job 5; Zqqq-qq, one operator / two test accounts). Zqqq-qq controlled both accounts and personally confirmed all six transactions in MetaMask. No second member independently signed and no cross-device signed write was added. A separate run used the same team 3 with a different job and different balances: community post 3 -> team 3 -> reply 3 -> escrow **job 5**. Six successful transactions (`status=1`, blocks 12018477-12018556) cover the guest accepting the invitation, the 1 mUSD approval, funding, the link reply, the delivery digest, and the client's release. Job 5 is `Completed`; balances were **98 / 2 / 0** mUSD (client / provider / escrow) before the run and **97 / 3 / 0** after it, so the 1 mUSD left the client once and reached the provider once. The delivered file's Keccak-256 matches the on-chain digest (`0xd878a566…29ad`), and a read-only duplicate `release(5)` returned `not submitted`. The accounts, team, job and balances differ from §7.6's post 4 / team 4 / job 4 run and must not be combined; the record is `docs/project/TEAM3_ESCROW_SEPOLIA_ACCEPTANCE_2026-10-29.zh-CN.md`.

7.7 Frozen-candidate regression (D2 / #8)

Four layers were executed against the frozen candidate `992584e`: a fresh clone with 61 tests and a build; read-only replay of community and escrow state; six failure-path probes at a fixed block; and one real write (`0xfff88c7c…d7bd`, block 12010583) flipping `member(1,A)` from false to true. See `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`.

7.8 Cross-platform clean clone

Platform	Commit	Result
macOS 26.6 / arm64 (Apple M5, Node v24.22.1)	`7db718a`	64/64 tests, build succeeded, workspace clean, `.sol` and artefacts LF; frontend started from the new clone and screenshotted (the screenshot shows Demo sandbox and is explicitly not Sepolia evidence)
Windows (Node v24.15.0)	`7db718a` (same commit, same tree `afc673de…`)	64/64 tests, build succeeded, workspace clean, no artefact diff, `git ls-files --eol` byte-for-byte identical to the macOS record

7.9 A1 interface acceptance and team policy (merged 2026-10-29)

PR #32 exercised the six community areas at 390×844 and 1440×1000 in the local Demo sandbox: 22 screenshots plus viewport measurements are in `docs/project/evidence/a1-ui/`. It fixed long-title and team-name overflow, raised the smallest mobile controls to 44 px, and gave dialogs an accessible name with focus return on close; these are UI checks, not Sepolia transactions. PR #34 adds `TEAM_CIRCLE_POLICY.zh-CN.md`: leaving a circle preserves existing team rights, while circle writes still require membership and a Pending invitation still requires the guest to be in the circle. Four contract-level regressions (`tests/team-circle-independence.test.mjs`) cover host/guest proposals, the other member's review, circle-write blocking and Pending acceptance.

7.10 A2 status guidance, B2 content boundaries and provenance (merged 2026-10-29)

PR #47 adds role-aware next-step guidance for the four team states and three work states: a host cannot accept on the guest's behalf, an author cannot confirm their own proposal, and declined or cancelled invitations must be re-created from the original task. A task thread now lists all loaded teams and a work can navigate back to its source task; the Active-team escrow entry remains in the workspace. Ten Demo-sandbox screenshots and mobile measurements (viewport/document 390 px, dialog 370 px) are in `docs/project/evidence/a2-guidance/`; no Sepolia transaction was added.

PR #48 adds three Ganache-level regressions: exact UTF-8 byte limits on nine text fields (the limit succeeds; +1 byte and the empty string are rejected with `invalid text length`), the distinction between the contract accepting any non-empty URI and the frontend blocking `javascript:` / `data:` / credential-bearing URLs, and duplicate or terminal operations failing with the declared reason while counts stay unchanged. The written review is `docs/project/CONTENT_BOUNDARY_REVIEW_2026-10-29.zh-CN.md`.

PR #49 corrects the backend provenance record: current LF Git-blob hashes and the original CRLF import hashes are stored separately, the three reused contracts are checked against upstream commit `3b7976a` with blob IDs, and MockUSDC is attributed to the course snapshot rather than an unverified upstream author. `scripts/verify-provenance.mjs` re-checks the four files offline.

7.11 Visual/workflow polish and release tooling (merged 2026-10-30)

PR #51 (rebased onto the latest main through #54) polishes the community hero and shared-work artwork, centres the workspace metrics, and expands "How it works" to eight steps covering circles, discussion, Agent identity, invitations, shared works, bilateral confirmation, optional escrow and authorised reputation. It also clarifies Demo-sandbox versus Sepolia behaviour in English. The conflict with the post-#38/#47 sources was resolved by keeping #51's new `collaboration.svg` and `shared-work.svg`, merging four CSS rule changes into the current stylesheet, and keeping the A2 guidance from #47; the resolved tree was checked at 1280×800 with real browser screenshots. No Sepolia transaction was added.

PR #52 makes the report generator cross-platform: `CHROME_BIN` takes precedence, macOS/Windows/Linux Chrome and Chromium locations are detected, local file URLs are encoded, source-relative images use a `<base>` element, each run uses a temporary profile, and an old PDF is preserved when rendering fails. Five regressions cover

detection, CLI encoding and failure retention (the CLI fixture is skipped on Windows because it uses a shell script).

PR #53 makes the freeze manifest strict about inputs: the 11 code inputs are required and must be regular Git blobs, while `backend-provenance.json`, `REPORT.md` and `REPORT.pdf` are optional supplements recorded in `filePolicy` and `missingOptionalFiles`. Missing required inputs fail before any output directory is created or an old manifest overwritten.

7.12 Blueprint features, x402 security and demo tooling (merged 2026-10-30)

PR #59 implements the remaining blueprint journey in the frontend and off-chain: an `agentledger-card-v1` card generator and parser, a marketplace with score/review/price/skill filters, a hire flow whose provider and prefill come from `ownerOf`, a "My orders" view for both roles, a sample agent service that polls `JobEscrow` and submits the Keccak-256 digest of its result document, a simplified x402 pay-per-call endpoint, and community evidence bound to an Agent ID. No contract, ABI or deployment address changed.

PR #60 reviews and hardens that work: x402 now issues a one-time challenge bound to chain, resource/input, amount, pay-to and expiry; the payer must sign it, and the server only serves after verifying the signer equals the on-chain payer (a public transaction hash alone is not authority). The agent service only accepts jobs in the configured mUSD at or above the quoted price, and persists the delivery bytes before `submit` so `/results/:id` survives a restart and still matches the on-chain digest. Regression tests cover a hash stolen by a non-payer, other-token / under-priced jobs and restart recovery.

PR #61 fixes the demo capture after #51 removed the old "jointly confirmed" seal: scene 3 now waits for the current `work-cover-illustration`, with a unit test proving that a card carrying only the old seal is rejected.

PR #58 is B's independent review of B1/B2: it corrects the host/`kind` description, adds a `normalizeText` trim so live writes match the demo sandbox, and records the cross-member consistency list (`CROSS_MEMBER_CONSISTENCY_2026-10-30.zh-CN.md`).

7.13 Collaboration history and account activity (merged 2026-11-02)

PR #67 is implemented in the reviewed main snapshot. My collaboration history (`#portfolio`) shows wallet partners, jointly confirmed works, source discussion, recent posts and explicitly verified order references. My activity (`#activity`) shows invitations addressed to the wallet, proposals awaiting the other member's review, and other accounts' replies to its posts. Opening an item returns to the source team, work or discussion; opening a reply does not mark it read. Ended invitations and self-reviews are excluded; replies remain historical activity, not an unread inbox.

The product rationale is now supported by implemented interfaces: a member can inspect prior collaboration and find a next action. This demonstrates availability of the features, not that they improve demand, retention or trust. A work confirmation, a valid order reference and a payment outcome remain distinct facts.

Check	Evidence and environment	Supported scope
Wallet participation, provenance and activity filtering	Four projection regressions in `tests/social-insights.test.mjs`; local pure-function tests	Confirmed-work provenance, correct recipients, exclusion of self/terminal pending actions, ordering and order de-duplication
Layout, account switching and source navigation	Archived browser checks at 1440×950 and 390×950 using synthetic Demo data; `tests/browser/social-insights-demo.mjs`	Page rendering, invited-account display, team/work/thread links, no horizontal overflow and no recorded page-script errors
Delayed response and RPC failure	Controlled browser fixture replacing app/community readers and order scanning; `tests/browser/social-insights-live.mjs`	Old wallet result discarded, failure distinguished from no valid orders, retry, displayed order state/block and source-navigation event

Check	Evidence and environment	Supported scope
Order-reference validity	Reused `readLinks` / `verifyLink` and existing escrow-reference tests	Network/configuration, identity registries, task/team, client/provider, Agent ID, token and fixed-block validation; decoded text alone is not proof
Peer review and integration	QiuQiu-xuan's approved review on PR #67; #68 updated the report and #69 archived the freeze	Reviewed implementation and integrated documentation; no claim that another requested reviewer completed review

These sources are indexed in `docs/project/SOCIAL_INSIGHTS_2026-11-02.zh-CN.md`. All layout, account-switching, stale-response, RPC-failure and retry checks listed for these two pages use Demo data or simulated live fixtures. They are not new real RPC, MetaMask or Sepolia acceptance. Real-chain conclusions in this report refer only to the separately identified historical receipts and scoped read-only RPC records. The change added no contracts or transaction functions; it did not produce a new Sepolia transaction or independent-user study. The 112-test suite result is the recorded baseline in §7.1, not an additional browser-test count.

The default community window is 40 records per type plus linked provenance, expandable with Load older records. Public order references are scanned separately at one block with a 1,000-reply cap, so community and order snapshots may differ. Unverified, verifying, failed and completed-with-no-valid-reference states remain distinct; even a successful scan is not a list of all unreferenced jobs. The UI invalidates scans on normal refresh and wallet/mode/configuration changes; the controlled race test specifically covers a wallet change. No full-history completeness, background push, unread state or retention result is claimed.

---

8. Known Limitations and Risks

Each item below is **confirmed**, not speculative:

#	Limitation	Source
1	No owner, no pause, no upgrade: wording-level issues can only be fixed in the frontend	B1 review §1
2	An `Active` team has no terminal state; it cannot be cancelled or marked complete	B1 review §5
3	`proposeWork` / `reviewWork` check team membership only and **do not re-check circle membership**; leaving a circle does not revoke existing team rights (now documented as the intended design)	`TEAM_CIRCLE_POLICY.zh-CN.md` (Issue #30, closed)
4	The contract source is **not verified on Etherscan**; consistency relies on local recompilation plus runtime code comparison	`DEPLOYMENTS.md`
5	The escrow deployment's source files differ in bytes from the current LF sources; reproducing it requires `evidence/escrow-deployment-sources.json`	Freeze draft §6
6	Rejection feedback depends on a revert during `eth_estimateGas` rather than an explicit UI guard	Frozen regression §3

#	Limitation	Source
7	The second device performed read-only verification only; no cross-device signed write	D1 acceptance §5
8	Storing long text on-chain makes writes expensive (`createPost` measured at 1.58M gas)	§5.3 of this report
9	On macOS, the ganache uWS native module has an ABI mismatch under Node 24 and falls back to pure JS (no impact on results)	macOS clone record
10	The sample agent's "work" is a deterministic placeholder; it demonstrates delivery and data flow, not a real model call	`defaultWork` / #59
11	x402 is a direct mUSD transfer with no escrow or refund; used payment hashes are kept in memory, so a restart within the 1-hour window can re-enable a hash for the same payer	`agent-service/README.zh-CN.md`
12	Marketplace filters only the currently loaded registry page; community evidence is an application-level association, not a contract-enforced link	#59
13	Collaboration history / activity are projections of the loaded window (default 40 records per type), not all history; order references are scanned separately with a 1,000-reply cap and no completeness claim	#67 / §2.5
14	The activity view has no push service, unread state or read receipt; externally changed records require refresh, and no retention or adoption improvement is claimed	#67

9. Team Contributions

Names and student IDs were supplied by the team on 2026-11-03. Names are written in Hanyu Pinyin with the given name before the family name. The report coordinator uses `daizhiqi`. Contributions below reflect the delivery candidate based on main `7062999`, including report integration #70, post-report release records #71 and Social recording #74/#75, plus the actual work submitted in #76. Contributions follow repository evidence and member descriptions, not PR counts. Report #70 was approved and merged; the final-video revision and new submission materials remain subject to peer review. Final freezing and course submission are not yet complete.

Member / GitHub account / student ID	Recorded actual contribution	Main evidence
Haipeng Wang / PAisHere / 3036841371	Community interface visuals, icons and statistics layout; collaboration and work illustrations; workflow guide and interface copy. QiuQiu-xuan integrated the visual changes while retaining the original authorship.	#40, #51; integration #54

Member / GitHub account / student ID	Recorded actual contribution	Main evidence
Dian Li / ffmitrg / 3036841890	Independent permission/content-boundary review and input-normalisation regressions; agent cards, market filters, hire/order/review flows, sample agent service and HTTP payments; demo and rehearsal preparation.	#58, #59; original commits integrated through #60
Qing Zhang / Zqqq-qq / 3036843862	Wallet connection and failure recovery, Sepolia community/escrow deployment, escrow integration and real-transaction acceptance; personal wallet confirmations, tests and evidence preparation. Mobile interaction, permission/content-boundary review and regressions; macOS clean-clone/startup validation. Social DApp rationale and user story; collaboration-history and account-activity implementation. Additional documented work includes PDF/freeze tooling, provenance/licence checks, configuration-aware captions and service-defect reproduction.	#13, #14, #16, #22, #32, #34, #35, #41, #47, #48; #43, #49, #52, #53, #57, #64; review of #59; #66, #67
Yaxuan Qiu / QiuQiu-xuan / 3036842040	Cross-platform and artefact consistency, D1/D2 tests and regressions, membership guidance and error messages; report drafts/PDF iterations, demo materials and release preparation. Visual integration, service payment/signature and delivery-persistence fixes; review of the new social views and report/freeze-record alignment. Recorded the new social pages and revised Social v2 footage, actually used in final-video segments 07-10.	#15, #19, #23, #33, #36, #37, #54, #60; review of #67; #68, #69; #74, #75
Zhiqi Dai / daizhiqi / 3036841979	Reviewed and integrated the team report, architecture diagram/PDF and contribution evidence through #70; updated post-report release records through #71. Recorded supplementary Demo and local permission-test footage, performed segmented trial recordings and retakes, recorded all 16 English narration segments, and assembled the captioned final video. Prepared submission materials and addressed #76 review feedback with Codex assistance. Final peer approval, freeze and submission remain separate steps.	#70 (merged), #71 (merged); #76 delivery candidate; FINAL_DEMO_2026-11-08.zh-CN.md; CONTRIBUTIONS.md

Operator and validation boundaries. Zqqq-qq's Account 1 and Account 2 were controlled by one user, who personally confirmed real transactions in MetaMask. Their wallet and team 3 / job 5 records are not two-member independent acceptance or cross-device signing. The new social pages' layout, switching, late-response and RPC-failure/retry checks used Demo or simulated live data, not new real RPC/MetaMask/Sepolia acceptance. Other members' independent reviews and verification remain credited to those members.

Implementation, review and integration are distinct contributions: ffmitrg's original functionality entered main through QiuQiu-xuan's #60; PAisHere's visual authorship was retained through #54. The inspected approval for #67 is QiuQiu-xuan's; being requested as a reviewer does not establish completed review by ffmitrg or daizhiqi. Inherited MIT-licensed source is not claimed as student-authored from scratch. Detailed evidence and disclosed tool assistance remain in `docs/project/CONTRIBUTIONS.md`; this attribution is not a statement that every line was

manually authored. Codex-assisted work and ffmitrg's recorded Claude Code assistance are distinguished from personal wallet confirmations and independent peer review.

The 16-segment narration, supplementary footage, segmented trial recordings and full video were completed on 2026-11-08 and are recorded in the final delivery record. Peer review and final release/submission are tracked separately. No hours or contribution percentages are inferred from PR counts. Each member submits a confidential individual peer evaluation on Moodle, including all members and percentages totalling 100%; filled evaluations are excluded from the group submission and repository.

---

10. Conclusion and Future Work

Conclusion: AgentLedger explores a social community in which discovery develops into explicit collaboration and an inspectable history. The community workflow and the separately recorded cross-module escrow runs have Sepolia receipts, events and state evidence (§7). They support the implemented mechanisms, not a claim that the illustrative story in §2.2 occurred as a single run. The social value of those records, user demand and repeat participation still require evaluation with independent users. The contract permission model provides no administrator override; it does not establish the truth or quality of a collaboration.

Future work: prioritise independent-user evaluation of the implemented views in §2.5 - whether people can distinguish a follow, an accepted invitation, a confirmed work and a paid job, and whether the portfolio gives a reason to return. Demand, retention and adoption remain hypotheses; no feature is promised by this paragraph. The technical work below has a separate implementation basis:

1. Add a terminal state for `Active` teams (requires an ABI change, redeployment, and coordination with role C).

2. Preserve the documented policy that leaving a circle does not revoke an established team's rights; evaluate lifecycle/completion improvements without presenting this settled policy as an unresolved defect.

3. Submit the source for block-explorer verification to lower the reproduction cost of "recompile locally and compare".

4. Move long text off-chain with an on-chain hash to reduce write cost.

5. Evaluate order-verified reputation and dispute handling as possible contract extensions; neither is enforced by the present application-layer references. The already completed cross-module acceptance remains in §7.6, not future work.

---

11. Appendix

11.1 Evidence index

Category	Location
Deployment and receipts	`docs/project/DEPLOYMENTS.md`, `docs/project/evidence/community-sepolia-*.json`
Escrow	`docs/project/ESCROW_SEPOLIA_ACCEPTANCE_2026-10-28.zh-CN.md`, `evidence/escrow-*.json`, `evidence/escrow-screenshots/`, `evidence/job{1,2,3}-*`
Cross-module (team 3 -> job 5)	`docs/project/TEAM3_ESCROW_SEPOLIA_ACCEPTANCE_2026-10-29.zh-CN.md`, `evidence/team3-job5/`, `scripts/verify-team3-acceptance.mjs`
D1 acceptance	`docs/project/ACCEPTANCE_D1.zh-CN.md` (including §7, the closing review)
A1 UI acceptance	`docs/project/A1_UI_ACCEPTANCE_2026-10-28.zh-CN.md`, `evidence/a1-ui/` (22 screenshots plus measurements)
Circle/team policy	`docs/project/TEAM_CIRCLE_POLICY.zh-CN.md`, `tests/team-circle-independence.test.mjs`
A2 status guidance	`docs/project/A2_STATUS_ACCEPTANCE_2026-10-29.zh-CN.md`, `evidence/a2-guidance/` (10 screenshots plus measurements)
Content boundaries	`docs/project/CONTENT_BOUNDARY_REVIEW_2026-10-29.zh-CN.md`, `tests/community-content-boundaries.test.mjs`
Source provenance	`docs/project/SOURCE_PROVENANCE.zh-CN.md`, `backend-provenance.json`, `scripts/verify-provenance.mjs`
Agent service / x402	`agent-service/`, `web/agent-card.js`, `web/market.js`, `web/x402.js`, `tests/agent-service.test.mjs`, `tests/marketplace.test.mjs`
Demo blueprint flow	`docs/project/DEMO_BLUEPRINT_FLOW.zh-CN.md`, `scripts/rehearse-demo.mjs`
Social insights	`docs/project/SOCIAL_INSIGHTS_2026-11-02.zh-CN.md`, `web/social-insights.js`, `tests/social-insights.test.mjs`, `tests/browser/social-insights-*.mjs`
D2 acceptance	`docs/project/ACCEPTANCE_D2.zh-CN.md`, `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`, `docs/project/MACOS_CLEAN_CLONE_2026-10-28.zh-CN.md`
Permission review	`docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md`
Community deployment acceptance	`docs/project/SEPOLIA_ACCEPTANCE_2026-10-27.zh-CN.md`
Reproduction tools	`scripts/verify-community.mjs`, `scripts/verify-escrow-acceptance.mjs`, `scripts/verify-team3-acceptance.mjs`, `scripts/verify-provenance.mjs`, `scripts/release-freeze.mjs` + `docs/project/evidence/release-manifest.json`
Report PDF generation	`scripts/report-pdf.mjs`, `scripts/lib/chrome-path.mjs`, `docs/project/REPORT_PDF_GENERATION.zh-CN.md`, `tests/report-pdf.test.mjs`
Submission requirements	`docs/project/SUBMISSION_REQUIREMENTS_2026-11-08.zh-CN.md`
Presentation slides	`docs/project/5-AgentLedger-Slides.pptx`

Category	Location
Final narrated demonstration	`docs/project/assets/AgentLedger-final-v1.mp4`, `AgentLedger-final-v1.en.srt`, `DEMO_SCRIPT.en.md`, `FINAL_DEMO_2026-11-08.zh-CN.md`
Freeze policy	`scripts/release-freeze.mjs`, `tests/release-freeze.test.mjs`, `docs/project/RELEASE_CHECKLIST.zh-CN.md`

11.2 Reproduction environment

Node 24.x, pnpm 11.25.0 (pinned by `packageManager`), solc 0.8.30.

```
git clone https://github.com/Zqqq-qq/comp7610-agentledger.git
cd comp7610-agentledger
pnpm install --frozen-lockfile
pnpm test        # expect 112 passing tests
pnpm build
```

---

12. Outstanding Items (not fabricated; they require the team)

#	Missing	Impact	Owner
1	Implementation architecture diagram (done)	`docs/assets/architecture.svg` (English) and `architecture.zh-CN.svg`, embedded in §4.1	-
2	**Member details and contributions recorded**	Five names, student IDs and delivery-stage contributions are in §9; confidential contribution percentages belong to each member's individual Moodle peer evaluation.	Team members
3	**Final delivery review and publication pending**	E1 #70 and release records #71 are merged. #76 final-video/report revisions and new slides require peer review; actual final SHA/tag, backup and submission remain under #11.	daizhiqi
4	**Individual peer evaluation submission pending**	Moodle requires each member to submit the peer form independently, listing all members including themselves and percentages totalling 100%. The form prohibits sharing completed evaluations.	Each member
5	**Narrated demonstration produced; peer delivery review pending**	A 06:59.92 English-narrated video with captions, 16 chapters and five-member credits was assembled on 2026-11-08. The timecoded script and final delivery record are indexed in §11.1. Peer review, backup and course-requirement checks remain under #10/#11.	daizhiqi
6	**Deployment gas attribution**	Operation/tool record added in §5.3; deployer cannot recall manual gas/fee edits. Wallet settings and execution-level explanation of 17.18M remain unconfirmed; no attribution claimed	Zqqq-qq

Two items that were open when this report was first drafted are now closed and are recorded here so the record is not silently edited:

Cross-module entry point (community team -> funded escrow job): executed end to end on 2026-10-28 (post 4 -> team 4 -> job 4, Completed, balances 99 / 1 / 0). See §7.6.

English deliverables: the report, README, architecture diagram, demonstration captions and narration now exist in English. The final narrated video was assembled on 2026-11-08; delivery review, backup and submission checks remain (item 5).

12.1 Demonstration delivery status (2026-11-08)

Zhiqi Dai recorded the 16 narration segments and carried out segmented trial recordings, listening previews and retakes on 2026-11-08, then assembled the complete video with Codex assistance. The local requester confirmed the complete cut was acceptable; this is not a claim of independent peer approval. The team arrangement in Issue #10 uses one narrator, rather than five separate presentations or a five-person rehearsal. The five members retain their actual contribution credits.

The video includes the Research & Insights example, My activity and My collaboration history, separate archived wallet/escrow evidence, and a newly recorded local Ganache permission-test run (2 passing tests, not new Sepolia transactions). Demo sessions were recorded separately and are not presented as one live acceptance run. Detailed sources, actual chapter times and remaining checks are in `FINAL_DEMO_2026-11-08.zh-CN.md`. The Moodle Final Project page requires one group representative to submit the report, presentation slides, a video link in Word/TXT, and code, with filenames based on “Number of team members-Project name”. It displays a deadline of 2026-11-08 at 23:59, a 100 MB per-file limit and at most 20 files. Individual peer evaluation is a separate Moodle assignment. These requirements were read on 2026-11-08; see SUBMISSION_REQUIREMENTS_2026-11-08.zh-CN.md. Teacher-accessible video hosting, final peer approval, the final version/backup and actual submission receipts remain pending. Existing historical acceptance and deployment-gas uncertainties are unchanged.