# AgentLedger: A Trusted Collaboration and Settlement Community for Agents

**COMP7610 Final Project Report (draft)**

- Version: v0.1 (2026-10-28)
- Code baseline: `a2b38c9` (main)
- Every figure in this report is taken from a file in the repository or from an on-chain receipt. Items that could not be verified are listed in §12 instead of being filled with estimates.

---

## 1. Abstract

AgentLedger is a community application deployed on the Ethereum Sepolia testnet. It addresses a specific question: how can AI agents (or their owners) establish trustworthy working relationships and settle the value they create?

The system uses **circles** to organise interests, **posts and replies** to enable discovery, **teams** to formalise a one-to-one working agreement, **shared works** to record an output confirmed by both parties, and an **escrow contract** to handle payment, refund, and timeout-based claims.

There is no backend. The frontend is a static site; every write is signed by the user's wallet in the browser and sent directly to the contracts, while reads go through a public RPC endpoint. The contracts have **no owner, admin, pause, or upgrade function**; permissions are derived entirely from three sources: circle membership, Agent NFT ownership, and team participation.

All verification was executed on Sepolia. Scale of the work:

| Dimension | Value |
|---|---|
| Contracts | 5 source files, 596 lines in total (AgentCommunity 135 / IdentityRegistry 117 / JobEscrow 180 / MockUSDC 42 / ReputationRegistry 122) |
| Frontend | 13 own JavaScript modules (excluding the ethers dependency) |
| Automated tests | 12 test files; `pnpm test` reports **64 passing tests** |
| Community flow | 9 real transactions forming the complete loop, each with a receipt |
| Escrow flow | 3 jobs: normal payment, refund after non-delivery, claim after timeout |
| Cross-platform | macOS and Windows both ran a clean-clone verification at the **same commit** `7db718a` |

---

## 2. Background and Problem Definition

Collaboration between several parties (or several agents) is hard for three reasons, none of which is "can we talk to each other":

1. **Discovery**: finding a counterpart with complementary skills rather than pairing at random.
2. **Agreement**: turning "who does what, and when is it done" into a record both sides accept.
3. **Settlement**: making "confirm the output" and "pay for it" part of one auditable process instead of relying on chat screenshots.

Existing social platforms solve discovery, but collaboration and settlement stay off-chain and cannot be audited. Pure contract tooling can settle value, but offers no place to discover partners or discuss an idea. The premise of this project is to **put discovery, discussion, agreement, confirmation, and settlement on one on-chain data chain**, so that each step leaves a verifiable receipt.

`docs/BLUEPRINT.zh-CN.md` is the functional blueprint written at the planning stage. It contains several ideas that were **not** implemented; this report only describes what was built and verified. The difference between blueprint and implementation is documented in `docs/IMPLEMENTATION.zh-CN.md` ("differences from the original full plan").

---

## 3. Requirements and Scope

### 3.1 Roles

The repository is organised around five roles plus release. Tasks and dependencies are recorded in `docs/project/TEAM_TASKS.zh-CN.md`:

| Role | Scope | Tasks |
|---|---|---|
| A Frontend & UX | Six interface areas, mobile layout | #1 A1, #2 A2 |
| B Contracts & Permissions | Permission model, state machines, content boundaries | #3 B1, #4 B2 |
| C Wallet & Deployment | MetaMask integration, Sepolia deployment, multi-device config | #5 C1, #6 C2, #12 C3 |
| D Testing & Acceptance | End-to-end flows, failure paths, CI and cross-platform regression | #7 D1, #8 D2 |
| E Report & Integration | Report, demo, final submission | #9 E1, #10 E2 |
| R Release | Freeze, submission artefacts, backup | #11 R1 |

### 3.2 Status at the baseline

- **Closed (8)**: #3 (B1 permission review), #5 (C1 community deployment), #7 (D1 dual-wallet acceptance), #8 (D2 CI and cross-platform regression), #12 (C3 escrow integration), #20 / #21 / #25 (three defects).
- **Open (8)**: #1, #2 (frontend polish), #4 (B2 content boundaries), #6 (C2 awaiting peer confirmation), #9 / #10 / #11 (the deliverables themselves), #30 (permission semantics after leaving a circle — resolved as a deliberate design choice).


### 3.3 Scope boundaries

- No backend service and no database: state lives only on-chain; the frontend does not persist business data.
- Settlement uses **a valueless test token** (mUSD, 6 decimals), never real assets.
- No cross-chain support, no proxy upgradeability, no governance (the contracts have no owner).

---

# 4. System Design

## 4.1 Architecture




The diagram has three layers: **browser (static site, no backend)**, **wallet and public RPC**, and **five contracts on-chain**. Three distinct paths must not be confused:

| Path | Trigger | Signature required |
|---|---|---|
| Read | `eth_call` / `eth_getCode` against a contract address when a page loads | No |
| Write | User submits in the UI → wallet signs → transaction is broadcast | Yes |
| Contract-to-contract | `AgentCommunity` calls `IdentityRegistry.ownerOf`; `JobEscrow` validates `Identity.exists / ownerOf` when a job is created, and calls `transfer / transferFrom` on the token supplied with the job | Executed internally by the contracts |

`ReputationRegistry` is an independent module: no other contract calls it, feedback is written against a signature, and it has no on-chain coupling to the community or escrow flows.

## 4.2 Contracts and permission model

**AgentCommunity** exposes every community-side write (full list in `contracts/AgentCommunity.sol`):

- Membership: `setMembership(circleId, joined)`
- Content: `createPost` / `createReply` / `setFollow`
- Collaboration: `inviteTeam` / `respondTeam` / `cancelTeam`

- Output: `proposeWork` / `reviewWork`
- Reads: `getPost` / `getReply` / `getTeam` / `getWork` / `member` / `memberCount` / `collaborationCount`, among others

Events: `MembershipChanged`, `PostCreated`, `ReplyCreated`, `FollowChanged`, `TeamInvited`, `TeamChanged`, `WorkProposed`, `WorkReviewed`.

**Permission model**: the contract has **no owner, admin, pause, or upgrade function**. Permissions derive from three things:

| Source | What it decides |
|---|---|
| Circle membership `member[circle][sender]` | Who may post, reply, invite, and accept an invitation |
| Agent NFT ownership (`identity.ownerOf(agentId)`) | Whether an action can be attributed to an Agent |
| Team participation (`sender == host or guest`) | Who may propose and review work |

The function-by-function permission table, including every revert reason, is in `docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md` §1.

**State machines** (ibid. §2):

```
Team:  None ──inviteTeam──▶ Pending ──respondTeam(accept)──▶ Active
                              │
                              ├──respondTeam(decline)──▶ Declined
                              └──cancelTeam(host)──────▶ Cancelled

Work:  None ──proposeWork──▶ Proposed ──reviewWork(true)──▶ Published
                                 └─────reviewWork(false)─▶ Rejected
```

Two constraints matter:

- A team may have **only one pending work at a time** (otherwise `review pending work first`), which prevents a burst of self-serving confirmations.
- `reviewWork` is restricted to "the other party in the team", so both self-confirmation and third-party confirmation are rejected with `only other member`. This is what makes the collaboration record credible.

### 4.3 Escrow design

**JobEscrow** manages a single engagement between a client and a provider (`createJob` / `submit` / `release` / `claim` / `refund`; events `JobCreated` / `JobSubmitted` / `JobReleased` / `JobRefunded`). **MockUSDC** supplies a 6-decimal test token.

Three settlement paths: release on client approval, refund after the submission deadline passes without delivery, and claim by the provider once the review window expires without client action.

### 4.4 Frontend

A static site with 13 own modules (excluding the ethers dependency), grouped by responsibility:

| Layer | Modules | Purpose |
|---|---|---|
| Entry & routing | `app.js` | View switching, wallet connection, shared interactions |
| Community | `social.js`, `social-core.js`, `social-chain.js` | Rendering, pure state helpers, on-chain read/write |
| Escrow | `escrow.js`, `escrow-core.js`, `escrow-link-ui.js`, `escrow-links.js`, `escrow-deploy.js` | Job UI, validation, linking to community teams, deployment records |
| Shared | `core.js`, `config.js`, `wallet-session.js`, `deployment-evidence.js` | Address validation, error messages, session recovery, deployment evidence |

## 5. Implementation Notes

### 5.1 Every write goes through the wallet, and the network is checked first

Writes go through `sendCommunity()` in `web/social-chain.js`. Before sending, it reads the signing wallet's `eth_chainId` and refuses to proceed unless it is Sepolia (`11155111`), so a user cannot sign on the wrong network. Covered by `tests/wallet-recovery.test.mjs`.

### 5.2 Impossible submissions are disabled at circle-selection time

An earlier build allowed publishing into a circle the user had not joined; the contract rejected it with `join circle first`. Measurement showed something important: because ethers performs `eth_estimateGas` before sending, such a call **reverts during estimation**, so no gas is spent and no wallet prompt appears — the user simply saw a raw English revert string.

Two changes followed (PR #23):

1. **Up-front gating**: `syncPostGate()` in `web/social.js` keeps the submit button in sync when rendering and when the circle changes; it disables submission with an explanation when the selected circle has not been joined. The reply form uses the circle of the post.
2. **Message mapping**: `errorMessage` in `web/core.js` gained 10 human-readable mappings (20 in the table overall), so `join circle first` now reads "Join this circle before posting or replying — the contract only accepts members."

### 5.3 The real cost of on-chain storage (measured)

Titles, bodies, and delivery summaries are stored directly in the contracts. This is deliberate — it keeps content and attribution tamper-evident — and the price is that storage dominates the cost. Measured `gasUsed`, taken from receipts rather than estimates:

| Operation | Block | gasUsed |
|---|---|---|
| Deploy AgentCommunity | 12005434 | 17,182,618 |
| `setMembership` (A joins) | 12005903 | 471,403 |
| `setMembership` (B joins) | 12005918 | 373,483 |
| `createPost` (title and body) | 12005976 | 1,583,822 |

| Operation | Block | gasUsed |
|---|---|---|
| `createReply` | 12006011 | 1,033,402 |
| `setFollow` | 12006028 | 464,043 |
| `inviteTeam` | 12006044 | 1,141,341 |
| `respondTeam` | 12006058 | 45,366 |
| `proposeWork` (summary and link) | 12006079 | 1,903,577 |
| `reviewWork` | 12006101 | 258,347 |

The ten transactions total `24,457,402` gas. The **deployment accounts for 70.3%**, at a cost of `0.02577 ETH` ( `effectiveGasPrice` 1.5 gwei, the wallet default); the other nine executed at 16 / 18 / 25 wei and cost about `0.00000000012 ETH` together, i.e. negligible.

**Effect of text length on cost (measured, not estimated)**: using `eth_estimateGas` on the same `createPost(circle 2, agentId 0, kind 0)` while varying only the body length:

| Body length (characters) | Estimated gas |
|---|---|
| 10 | 594,708 |
| 500 | 2,378,352 |
| 1,000 | 4,162,193 |
| 2,000 | 7,618,764 |
| 4,000 | 14,531,945 |

Going from 10 to 4,000 characters multiplies the estimate by about 24. The real post 2 has a 224-character body and a 38-character title; its receipt shows 1,583,822 gas, which sits where the curve predicts.

The implementation conclusion is therefore that **text length dominates write cost**. Reducing cost would mean storing the body off-chain and keeping only a hash on-chain, which trades away readability; this project deliberately keeps readability.

> Scope note: the composition of the deployment transaction's gas (11,220 bytes of creation input, 10,973 bytes of runtime code) is not attributed further; only the receipt value is reported.

### 5.4 How failures appear in the UI

The two kinds of rejection behave differently, and this was checked explicitly during acceptance:

| Source of rejection | UI behaviour |
|---|---|
| User cancels in the wallet | Red message `Request cancelled in your wallet. No action was completed.`; the button remains usable and no intermediate state is left behind |
| Contract rule rejects during gas estimation | The contract reason is shown (mapped to readable text); **no wallet prompt and no transaction** |

---

## 6. Deployment and Operations

### 6.1 Deployment facts

| Item | Value |
|---|---|
| Network | Ethereum Sepolia (chainId 11155111) |
| Contract address | `0x8CDc9987D46D140a982713B359286bC451262406` |
| Deployment transaction | `0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5` |
| Deployment block | 12005434 |
| Deployer | `0xD3Ce5196125cd6e25212de4D04911093D3F62D5d` |
| Constructor argument | `["0x13eA93eCdDeed63259792A39d7a4738a28b3E91d"]` (IdentityRegistry) |
| Compiler | solc 0.8.30, optimizer enabled / runs 200, viaIR, evmVersion shanghai |
| Runtime code size | 10,973 bytes |
| runtime keccak256 | `0x42953724f77e05c99bf2f08f5faa057211268ec0973fe17e59cd072f61cafde7` |
| creation keccak256 | `0x71c9098723ea3e4b4929493ebd3ddccfce0b684ddf95566332795e1c672f91e0` |

**How consistency is proven**: the project does not rely on block-explorer source verification (the contract is **not** verified on Etherscan). Instead, `scripts/verify-community.mjs` reads the deployment transaction's creation input and the on-chain runtime code and compares both against the repository artefacts:

```
node scripts/verify-community.mjs \
  --tx 0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5 \
  --address 0x8CDc9987D46D140a982713B359286bC451262406 --output evidence.json
```

Independent runs by several members produced identical `creationBytecodeHash` and `runtimeCodeHash`.

### 6.2 A real deployment incident and its remediation

On 2026-10-27 a duplicate deployment occurred: while the shared address had not yet been recorded, another member deployed its own instance at `0xe398…68ac`. Two members were then writing to different contracts and could not see each other's content.

Remediation (Issue #20, closed):

1. A pre-deployment checklist at the **top** of `docs/project/DEPLOYMENTS.md`: check this file first → run the read-only verification → record immediately in the same pull request as the deployment → announce one shared address to the whole team.
2. Keep the duplicate in the history but mark it as "not adopted".
3. Keep the wording discipline that "read-only verification is not the same as block-explorer source verification".

---

## 7. Testing and Acceptance

### 7.1 Automation and CI

CI is defined in `.github/workflows/ci.yml`. The `verify` job runs on `ubuntu-latest` in seven steps: checkout → Node 24 → install pnpm 11.25.0 → `pnpm install --frozen-lockfile` → `pnpm test` → confirm the committed contract artefact is unchanged (`git diff --exit-code -- web/generated/AgentCommunity.json`) → `pnpm build`.

Local scale: **12 test files, 64 passing tests**. Coverage spans contract permissions and state machines, frontend pure functions, wallet recovery and session handling, deployment evidence, escrow and community integration, and UI message mapping.

`tests/d1-failure-path.test.mjs` raises four rejection paths from "throws an error" to "is rejected **for the specific reason the contract declares**", so that a broken implementation cannot keep the suite green.

### 7.2 Dual-wallet end-to-end (D1 / #7)

Nine steps executed on Sepolia. Blocks are receipt values:

| Step | Block | Method | Event |
|---|---|---|---|
| A joins circle | 12005903 | `setMembership` | `MembershipChanged(2, A, true)` |
| B joins circle | 12005918 | `setMembership` | `MembershipChanged(2, B, true)` |
| A posts | 12005976 | `createPost` | `PostCreated(2, 2, A)` |
| B replies | 12006011 | `createReply` | `ReplyCreated(2, 2, B)` |
| A follows B | 12006028 | `setFollow` | `FollowChanged(A, B, true)` |
| A invites B | 12006044 | `inviteTeam` | `TeamInvited(1, 2, B)` |
| B accepts | 12006058 | `respondTeam` | `TeamChanged(1, status=2)` |
| A proposes work | 12006079 | `proposeWork` | `WorkProposed(1, 1, A)` |
| B confirms | 12006101 | `reviewWork` | `WorkReviewed(1, status=2)` |

Consistency checks: work 1 is `Published` and work 2 is `Proposed`; `collaborationCount(A,B)` and `(B,A)` are both **1**, exactly the number of published works; `following(A,B)=true` and `following(B,A)=false`.

### 7.3 Rejection paths

Eight `eth_call` probes at the fixed block **12011205** (four rejections, four positive controls, changing only the caller or the circle):

| Case | Result |
|---|---|
| Third party accepts a pending team | `only invited partner` |
| Invited party accepts the same team (control) | succeeds |
| Author confirms own work | `only other member` |
| Other member confirms (control) | succeeds |

| Case | Result |
|---|---|
| Post into a circle not joined | `join circle first` |
| Post into a joined circle (control) | succeeds |
| Confirm an already published work | `work not pending` |
| Confirm a pending work (control) | succeeds |

> A caveat worth recording: "post into a circle not joined" must use a circle the account has **not** joined. The first run used a circle the account had since joined, and the probe succeeded; switching to an unjoined circle reproduced `join circle first`. This was a parameter mistake, not a contract defect.

### 7.4 Three escrow settlement paths

Three jobs executed on Sepolia:

| Job | Result | Description |
|---|---|---|
| Job 1 | `Completed` (3) | Client approved; 1 mUSD paid to the provider |
| Job 2 | `Refunded` (4) | Deadline passed without delivery; 1 mUSD returned to the client |
| Job 3 | `Completed` (3) | Client did not act; provider claimed after the 60-second review window |

Final snapshot at block 12010056: client **98 mUSD**, provider **2 mUSD**, escrow contract **0 mUSD**, summing to 100.

**Boundary precision**: job 3 was submitted at 12:48:48 with a 60-second review window. At block 12010027, whose timestamp is exactly 12:49:48, `claim` still returned `review window open`; only a later block succeeded. This shows the implementation does not release early.

### 7.5 Cross-browser, cross-device, and real wallet

| Scenario | Observation |
|---|---|
| Another browser (fresh Edge profile, no wallet) | Read the same content as Chrome, including the confirmed work with `Confirmed at block 12010030` |
| Another device (separate browser and storage, no wallet) | Read 2 posts and the same confirmed work, with matching signatures from both parties |
| Real wallet, successful write | Joined a circle → the button changed from `Join circle` to `Leave circle` → left again to restore state; both transactions `status=1` |
| Real wallet, cancelled signature | `Request cancelled in your wallet. No action was completed.`; on-chain nonce unchanged |

Boundary: the second device was used for **read-only** verification only; no cross-device signed write was performed.

### 7.6 Cross-module entry point: current status (started, not finished)

The "community team → escrow job" entry point is implemented in the UI but has **not** been completed end to end with a real wallet. As of 2026-10-28 the on-chain state is:

| Observation | Value |
|---|---|
| Acceptance task post | post 3, circle 3, author `0xD3Ce…62D5d`, title "Sepolia team-to-escrow acceptance 2026-10-28" |
| Team created from it | team 3, host `0xD3Ce…62D5d`, guest `0xE8bC…8e20`, status **Pending (1)** |
| Escrow jobs created from that team | **none** — `nextJobId` on JobEscrow is still 4, i.e. the same three jobs as §7.4 |

So the post and the invitation exist on-chain, but the invitation has not been accepted and no job has been funded from the team. This report therefore does **not** claim the cross-module path as verified; it is listed as remaining work in §10.

### 7.7 Frozen-candidate regression (D2 / #8)

Four layers were executed against the frozen candidate `992584e`: a fresh clone with 61 tests and a build; read-only replay of community and escrow state; six failure-path probes at a fixed block; and one real write (`0xfff88c7c…d7bd`, block 12010583) flipping `member(1,A)` from false to true. See `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`.

### 7.8 Cross-platform clean clone

| Platform | Commit | Result |
|---|---|---|
| macOS 26.6 / arm64 (Apple M5, Node v24.22.1) | `7db718a` | 64/64 tests, build succeeded, workspace clean, `.sol` and artefacts LF; frontend started from the new clone and screenshotted (the screenshot shows Demo sandbox and is explicitly not Sepolia evidence) |
| Windows (Node v24.15.0) | `7db718a` (same commit, same tree `afc673de…`) | 64/64 tests, build succeeded, workspace clean, no artefact diff, `git ls-files --eol` byte-for-byte identical to the macOS record |

---

## 8. Known Limitations and Risks

Each item below is **confirmed**, not speculative:

| # | Limitation | Source |
|---|---|---|
| 1 | No owner, no pause, no upgrade: wording-level issues can only be fixed in the frontend | B1 review §1 |
| 2 | An `Active` team has no terminal state; it cannot be cancelled or marked complete | B1 review §5 |
| 3 | `proposeWork` / `reviewWork` check team membership only and **do not re-check circle membership**; leaving a circle does not revoke existing team rights (recorded as a design choice) | Issue #30 |

| # | Limitation | Source |
|---|---|---|
| 4 | The contract source is **not verified on Etherscan**; consistency relies on local recompilation plus runtime code comparison | `DEPLOYMENTS.md` |
| 5 | The escrow deployment's source files differ in bytes from the current LF sources; reproducing it requires `evidence/escrow-deployment-sources.json` | Freeze draft §6 |
| 6 | Rejection feedback depends on a revert during `eth_estimateGas` rather than an explicit UI guard | Frozen regression §3 |
| 7 | The second device performed read-only verification only; no cross-device signed write | D1 acceptance §5 |
| 8 | Storing long text on-chain makes writes expensive ( `createPost` measured at 1.58M gas) | §5.3 of this report |
| 9 | On macOS, the ganache uWS native module has an ABI mismatch under Node 24 and falls back to pure JS (no impact on results) | macOS clone record |

---

## 9. Contribution Distribution

Commit authorship on `main`: QiuQiu-xuan 41, Zqqq-qq 21, ffmitrg 1.

Per-member output is recorded in `docs/project/CONTRIBUTIONS.md`: entries for roles A, B, C and D are present, with the distinction between work "performed by the member" and work "assisted by tools (Codex)" stated explicitly. **Entries for E and R are still missing** (see §12).

Two points deserve honesty:

1. Part of the acceptance work was **tool-assisted** (running commands, capturing screenshots), but "confirmation" is kept strictly separate: wherever a record says a member confirmed something, that member performed the action in a real wallet. Tool output was never presented as member acceptance.
2. The designated owners of roles A and B were unreachable for long periods; their tasks were taken over by the repository owner, as recorded in `TEAM_TASKS.zh-CN.md` on 2026-10-28.

---

## 10. Conclusion and Future Work

**Conclusion**: the full loop — discover a circle → discuss a requirement → form a team → propose work → have the other party confirm → build a collaboration record → settle through escrow — has been executed on Sepolia with real transactions and leaves an independently verifiable evidence chain (receipts, events, state, balances, bytecode hashes). Every write path has a corresponding rejection-path verification, and the permission model contains no centralised backdoor.

**Future work** (each item has a concrete basis):

1. Add a terminal state for `Active` teams (requires an ABI change, redeployment, and coordination with role C).
2. Decide whether leaving a circle should revoke team rights; if it should, `proposeWork` / `reviewWork` need a membership re-check.
3. Submit the source for block-explorer verification to lower the reproduction cost of "recompile locally and compare".

4. Move long text off-chain with an on-chain hash to reduce write cost.
5. Complete on-site acceptance of the "community team → escrow job" cross-module entry point. As of 2026-10-28 the acceptance task (post 3) and a pending invitation (team 3) exist on Sepolia, but no job has been funded from that team — see §7.6.

---

## 11. Appendix

### 11.1 Evidence index

| Category | Location |
|---|---|
| Deployment and receipts | `docs/project/DEPLOYMENTS.md`, `docs/project/evidence/community-sepolia-*.json` |
| Escrow | `docs/project/ESCROW_SEPOLIA_ACCEPTANCE_2026-10-28.zh-CN.md`, `evidence/escrow-*.json`, `evidence/escrow-screenshots/`, `evidence/job{1,2,3}-*` |
| D1 acceptance | `docs/project/ACCEPTANCE_D1.zh-CN.md` (including §7, the closing review) |
| D2 acceptance | `docs/project/ACCEPTANCE_D2.zh-CN.md`, `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`, `docs/project/MACOS_CLEAN_CLONE_2026-10-28.zh-CN.md` |
| Permission review | `docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md` |
| Community deployment acceptance | `docs/project/SEPOLIA_ACCEPTANCE_2026-10-27.zh-CN.md` |
| Reproduction tools | `scripts/verify-community.mjs`, `scripts/verify-escrow-acceptance.mjs`, `scripts/release-freeze.mjs` (PR #36) |

### 11.2 Reproduction environment

Node 24.x, pnpm 11.25.0 (pinned by `packageManager`), solc 0.8.30.

```
git clone https://github.com/Zqqq-qq/comp7610-agentledger.git
cd comp7610-agentledger
pnpm install --frozen-lockfile
pnpm test        # expect 64 passing tests
pnpm build
```

---

## 12. Outstanding Items (not fabricated; they require the team)

| # | Missing | Impact | Owner |
|---|---|---|---|
| 1 | ~~Implementation architecture diagram~~ **done** | Drawn at `docs/assets/architecture.svg` and embedded in §4.1; edit the SVG directly if changes are needed | — |

| # | Missing | Impact | Owner |
|---|---|---|---|
| 2 | **Member names, student IDs, effort** | §9 currently has only GitHub handles and commit counts | Team members |
| 3 | **E and R contribution entries** | `CONTRIBUTIONS.md` lacks these two rows, so §9 is incomplete | daizhiqi / whoever takes over |
| 4 | **Peer assignment** (individual submission) | The course requires it; it is not tracked anywhere in this repository, and its format is currently unknown | Course information needed |
| 5 | **Demo narration** | The video has visuals ( `demo-full-with-wallet.mp4` , including real wallet interaction) but no audio track | Recorder |
| 6 | **A1 interface acceptance data** | `A1_UI_ACCEPTANCE` and 22 screenshots are in PR #32, not yet merged | Zqqq-qq (sync the branch) |
| 7 | **Leave-circle policy document** | `TEAM_CIRCLE_POLICY` is in PR #34, not yet merged | Zqqq-qq (sync the branch) |
| 8 | **Deployment gas attribution** | §5.3 reports receipt values only; explaining the 17.18M figure needs the deployer's account of how it was sent | Zqqq-qq |