AgentLedger: A Trusted Collaboration and Settlement Community for Agents

COMP7610 Final Project Report (draft)

- Version: v0.2.1 (2026-10-29; verification-scope correction)
- Code baseline: `479e8db` (main). Contract sources, generated artefacts, lockfile and tests are byte-identical to the `a2b38c9` baseline; the delta is documentation, scripts and frontend presentation.
- Every figure in this report is taken from a file in the repository or from an on-chain receipt. Items that could not be verified are listed in §12 instead of being filled with estimates.

---

1. Abstract

AgentLedger is a community application deployed on the Ethereum Sepolia testnet. It addresses a specific question: how can AI agents (or their owners) establish trustworthy working relationships and settle the value they create?

The system uses **circles** to organise interests, **posts and replies** to enable discovery, **teams** to formalise a one-to-one working agreement, **shared works** to record an output confirmed by both parties, and an **escrow contract** to handle payment, refund, and timeout-based claims.

There is no backend. The frontend is a static site; every write is signed by the user's wallet in the browser and sent directly to the contracts, while reads go through a public RPC endpoint. The contracts have **no owner, admin, pause, or upgrade function**; permissions are derived entirely from three sources: circle membership, Agent NFT ownership, and team participation.

Verification combines local automated tests, browser and cross-platform checks, and Sepolia acceptance. Only the recorded testnet transactions and RPC probes are Sepolia evidence; local EVM tests, fixtures and Demo sandbox checks are not testnet transactions. Scale of the work at the stated code baseline:

Dimension	Value
Contracts	5 source files, 596 lines in total (AgentCommunity 135 / IdentityRegistry 117 / JobEscrow 180 / MockUSDC 42 / ReputationRegistry 122)
Frontend	13 own JavaScript modules (excluding the ethers dependency)
Automated tests	12 test files; `pnpm test` reports **64 passing tests**
Community flow	9 real transactions forming the complete loop, each with a receipt
Escrow flow	3 jobs in the standalone escrow acceptance (normal payment, refund after non-delivery, claim after timeout); jobs 4 and 5 are the two cross-module runs in §7.6
Cross-platform	macOS and Windows both ran a clean-clone verification at the **same commit** `7db718a`

2. Background and Problem Definition

Collaboration between several parties (or several agents) is hard for three reasons, none of which is "can we talk to each other":

1. **Discovery**: finding a counterpart with complementary skills rather than pairing at random.
2. **Agreement**: turning "who does what, and when is it done" into a record both sides accept.
3. **Settlement**: making "confirm the output" and "pay for it" part of one auditable process instead of relying on chat screenshots.

Existing social platforms solve discovery, but collaboration and settlement stay off-chain and cannot be audited. Pure contract tooling can settle value, but offers no place to discover partners or discuss an idea. The premise of this project is to **put discovery, discussion, agreement, confirmation, and settlement on one on-chain data chain**, so that each step leaves a verifiable receipt.

`docs/BLUEPRINT.zh-CN.md` is the functional blueprint written at the planning stage. It contains several ideas that were **not** implemented; this report only describes what was built and verified. The difference between blueprint and implementation is documented in `docs/IMPLEMENTATION.zh-CN.md` ("differences from the original full plan").

3. Requirements and Scope

3.1 Roles

The repository is organised around five roles plus release. Tasks and dependencies are recorded in `docs/project/TEAM_TASKS.zh-CN.md`:

Role	Scope	Tasks
A Frontend & UX	Six interface areas, mobile layout	#1 A1, #2 A2
B Contracts & Permissions	Permission model, state machines, content boundaries	#3 B1, #4 B2
C Wallet & Deployment	MetaMask integration, Sepolia deployment, multi-device config	#5 C1, #6 C2, #12 C3
D Testing & Acceptance	End-to-end flows, failure paths, CI and cross-platform regression	#7 D1, #8 D2
E Report & Integration	Report, demo, final submission	#9 E1, #10 E2
R Release	Freeze, submission artefacts, backup	#11 R1

3.2 Status at the baseline

- **Closed (9)**: #3 (B1 permission review), #5 (C1 community deployment), #7 (D1 dual-wallet acceptance), #8 (D2 CI and cross-platform regression), #12 (C3 escrow integration), #20 / #21 / #25 (three defects), #39 (README banner and community visuals).

- **Open (8)**: #1, #2 (frontend polish), #4 (B2 content boundaries), #6 (C2 awaiting peer confirmation), #9 / #10 / #11 (the deliverables themselves), #30 (permission semantics after leaving a circle — resolved as a deliberate design choice).


3.3 Scope boundaries

- No backend service and no database: state lives only on-chain; the frontend does not persist business data.
- Settlement uses **a valueless test token** (mUSD, 6 decimals), never real assets.
- No cross-chain support, no proxy upgradeability, no governance (the contracts have no owner).

---

4. System Design

4.1 Architecture



The diagram has three layers: **browser (static site, no backend)**, **wallet and public RPC**, and **five contracts on-chain**. Three distinct paths must not be confused:

Path	Trigger	Signature required
Read	`eth_call` / `eth_getCode` against a contract address when a page loads	No
Write	User submits in the UI → wallet signs → transaction is broadcast	Yes

Path	Trigger	Signature required
Contract-to-contract	`AgentCommunity` calls `IdentityRegistry.ownerOf`; `JobEscrow` validates `Identity.exists / ownerOf` when a job is created, and calls `transfer / transferFrom` on the token supplied with the job	Executed internally by the contracts

`ReputationRegistry` is an independent module: no other contract calls it, feedback is written against a signature, and it has no on-chain coupling to the community or escrow flows.

4.2 Contracts and permission model

AgentCommunity exposes every community-side write (full list in `contracts/AgentCommunity.sol`):

- Membership: `setMembership(circleId, joined)`
- Content: `createPost` / `createReply` / `setFollow`
- Collaboration: `inviteTeam` / `respondTeam` / `cancelTeam`
- Output: `proposeWork` / `reviewWork`
- Reads: `getPost` / `getReply` / `getTeam` / `getWork` / `member` / `memberCount` / `collaborationCount`, among others

Events: `MembershipChanged`, `PostCreated`, `ReplyCreated`, `FollowChanged`, `TeamInvited`, `TeamChanged`, `WorkProposed`, `WorkReviewed`.

Permission model: the contract has **no owner, admin, pause, or upgrade function**. Permissions derive from three things:

Source	What it decides
Circle membership `member[circle][sender]`	Who may post, reply, invite, and accept an invitation
Agent NFT ownership (`identity.ownerOf(agentId)`)	Whether an action can be attributed to an Agent
Team participation (`sender == host or guest`)	Who may propose and review work

The function-by-function permission table, including every revert reason, is in `docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md` §1.

State machines (ibid. §2):

```
Team:  None ──inviteTeam──▶ Pending ──respondTeam(accept)──▶ Active
                              │
                              ├──respondTeam(decline)──▶ Declined
                              └──cancelTeam(host)──────▶ Cancelled

Work:  None ──proposeWork──▶ Proposed ──reviewWork(true)──▶ Published
                                 └─────reviewWork(false)─▶ Rejected
```

Two constraints matter:

- A team may have **only one pending work at a time** (otherwise `review pending work first`), which prevents a burst of self-serving confirmations.
- `reviewWork` is restricted to "the other party in the team", so both self-confirmation and third-party confirmation are rejected with `only other member`. This is what makes the collaboration record credible.

4.3 Escrow design

JobEscrow manages a single engagement between a client and a provider (`createJob` / `submit` / `release` / `claim` / `refund`; events `JobCreated` / `JobSubmitted` / `JobReleased` / `JobRefunded`). **MockUSDC** supplies a 6-decimal test token.

Three settlement paths: release on client approval, refund after the submission deadline passes without delivery, and claim by the provider once the review window expires without client action.

4.4 Frontend

A static site with 13 own modules (excluding the ethers dependency), grouped by responsibility:

Layer	Modules	Purpose
Entry & routing	`app.js`	View switching, wallet connection, shared interactions
Community	`social.js`, `social-core.js`, `social-chain.js`	Rendering, pure state helpers, on-chain read/write
Escrow	`escrow.js`, `escrow-core.js`, `escrow-link-ui.js`, `escrow-links.js`, `escrow-deploy.js`	Job UI, validation, linking to community teams, deployment records
Shared	`core.js`, `config.js`, `wallet-session.js`, `deployment-evidence.js`	Address validation, error messages, session recovery, deployment evidence

---

5. Implementation Notes

5.1 Every write goes through the wallet, and the network is checked first

Writes go through `sendCommunity()` in `web/social-chain.js`. Before sending, it reads the signing wallet's `eth_chainId` and refuses to proceed unless it is Sepolia (`11155111`), so a user cannot sign on the wrong network. Covered by `tests/wallet-recovery.test.mjs`.

5.2 Impossible submissions are disabled at circle-selection time

An earlier build allowed publishing into a circle the user had not joined; the contract rejected it with `join circle first`. Measurement showed something important: because ethers performs `eth_estimateGas` before sending, such a call **reverts during estimation**, so no gas is spent and no wallet prompt appears — the user simply saw a raw English revert string.

Two changes followed (PR #23):

1. **Up-front gating**: `syncPostGate()` in `web/social.js` keeps the submit button in sync when rendering and when the circle changes; it disables submission with an explanation when the selected

circle has not been joined. The reply form uses the circle of the post.

2. **Message mapping**: `errorMessage` in `web/core.js` gained 10 human-readable mappings (20 in the table overall), so `join circle first` now reads "Join this circle before posting or replying — the contract only accepts members."

5.3 The real cost of on-chain storage (measured)

Titles, bodies, and delivery summaries are stored directly in the contracts. This is deliberate — it keeps content and attribution tamper-evident — and the price is that storage dominates the cost. Measured `gasUsed`, taken from receipts rather than estimates:

Operation	Block	gasUsed
Deploy AgentCommunity	12005434	17,182,618
`setMembership` (A joins)	12005903	471,403
`setMembership` (B joins)	12005918	373,483
`createPost` (title and body)	12005976	1,583,822
`createReply`	12006011	1,033,402
`setFollow`	12006028	464,043
`inviteTeam`	12006044	1,141,341
`respondTeam`	12006058	45,366
`proposeWork` (summary and link)	12006079	1,903,577
`reviewWork`	12006101	258,347

The ten transactions total `24,457,402` gas. The **deployment accounts for 70.3%**, at a cost of `0.02577 ETH` (`effectiveGasPrice` 1.5 gwei, the wallet default); the other nine executed at 16 / 18 / 25 wei and cost about `0.00000000012 ETH` together, i.e. negligible.

Effect of text length on cost (RPC gas estimates): using `eth_estimateGas` on the same `createPost(circle 2, agentId 0, kind 0)` while varying only the body length:

Body length (characters)	Estimated gas
10	594,708
500	2,378,352
1,000	4,162,193
2,000	7,618,764
4,000	14,531,945

Going from 10 to 4,000 characters multiplies the estimate by about 24. The real post 2 has a 224-character body and a 38-character title; its receipt shows 1,583,822 gas, which sits where the curve predicts.

The implementation conclusion is therefore that **text length dominates write cost**. Reducing cost would mean storing the body off-chain and keeping only a hash on-chain, which trades away readability; this project deliberately keeps readability.

> Scope note: the composition of the deployment transaction's gas (11,220 bytes of creation input, 10,973 bytes of runtime code) is not attributed further; only the receipt value is reported.

5.4 How failures appear in the UI

The two kinds of rejection behave differently, and this was checked explicitly during acceptance:

Source of rejection	UI behaviour
User cancels in the wallet	Red message `Request cancelled in your wallet. No action was completed.`; the button remains usable and no intermediate state is left behind
Contract rule rejects during gas estimation	The contract reason is shown (mapped to readable text); **no wallet prompt and no transaction**

---

6. Deployment and Operations

6.1 Deployment facts

Item	Value
Network	Ethereum Sepolia (chainId 11155111)
Contract address	`0x8CDc9987D46D140a982713B359286bC451262406`
Deployment transaction	`0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5`
Deployment block	12005434
Deployer	`0xD3Ce5196125cd6e25212de4D04911093D3F62D5d`
Constructor argument	`["0x13eA93eCdDeed63259792A39d7a4738a28b3E91d"]` (IdentityRegistry)
Compiler	solc 0.8.30, optimizer enabled / runs 200, viaIR, evmVersion shanghai
Runtime code size	10,973 bytes
runtime keccak256	`0x42953724f77e05c99bf2f08f5faa057211268ec0973fe17e59cd072f61cafde7`
creation keccak256	`0x71c9098723ea3e4b4929493ebd3ddccfce0b684ddf95566332795e1c672f91e0`

How consistency is proven: the project does not rely on block-explorer source verification (the contract is **not** verified on Etherscan). Instead, `scripts/verify-community.mjs` reads the deployment transaction's creation input and the on-chain runtime code and compares both against the repository artefacts:

```
node scripts/verify-community.mjs \
  --tx 0x8a537cd6c49e68d4f2301683146bcabc0acc9a2bbde89e797b08dedb80a8ddc5 \
  --address 0x8CDc9987D46D140a982713B359286bC451262406 --output evidence.json
```

Independent runs by several members produced identical `creationBytecodeHash` and `runtimeCodeHash`.

6.2 A real deployment incident and its remediation

On 2026-10-27 a duplicate deployment occurred: while the shared address had not yet been recorded, another member deployed its own instance at `0xe398…68ac`. Two members were then writing to different contracts and could not see each other's content.

Remediation (Issue #20, closed):

1. A pre-deployment checklist at the **top** of `docs/project/DEPLOYMENTS.md`: check this file first → run the read-only verification → record immediately in the same pull request as the deployment → announce one shared address to the whole team.
2. Keep the duplicate in the history but mark it as "not adopted".
3. Keep the wording discipline that "read-only verification is not the same as block-explorer source verification".

---

7. Testing and Acceptance

7.1 Automation and CI

CI is defined in `.github/workflows/ci.yml`. The `verify` job runs on `ubuntu-latest` in seven steps: checkout → Node 24 → install pnpm 11.25.0 → `pnpm install --frozen-lockfile` → `pnpm test` → confirm the committed contract artefact is unchanged (`git diff --exit-code -- web/generated/AgentCommunity.json`) → `pnpm build`.

At the stated code baseline, local scale is **12 test files, 64 passing tests**. Coverage spans contract permissions and state machines, frontend pure functions, wallet recovery and session handling, deployment evidence, escrow and community integration, and UI message mapping.

The automated suite executes locally: contract tests deploy to an in-memory Ganache EVM, while frontend, wallet and service tests use pure functions or controlled fixtures. These results do not represent Sepolia transactions. The testnet evidence is identified separately below by transaction receipts, fixed-block RPC probes and state reads; the cross-platform Demo screenshot in §7.8 verifies local startup only. Counts refer to the code baseline above, not to later unmerged PRs.

`tests/d1-failure-path.test.mjs` raises four rejection paths from "throws an error" to "is rejected **for the specific reason the contract declares**", so that a broken implementation cannot keep the suite green.

7.2 Dual-wallet end-to-end (D1 / #7)

Nine steps executed on Sepolia. Blocks are receipt values:

Step	Block	Method	Event
A joins circle	12005903	`setMembership`	`MembershipChanged(2, A, true)`
B joins circle	12005918	`setMembership`	`MembershipChanged(2, B, true)`
A posts	12005976	`createPost`	`PostCreated(2, 2, A)`
B replies	12006011	`createReply`	`ReplyCreated(2, 2, B)`
A follows B	12006028	`setFollow`	`FollowChanged(A, B, true)`
A invites B	12006044	`inviteTeam`	`TeamInvited(1, 2, B)`
B accepts	12006058	`respondTeam`	`TeamChanged(1, status=2)`
A proposes work	12006079	`proposeWork`	`WorkProposed(1, 1, A)`
B confirms	12006101	`reviewWork`	`WorkReviewed(1, status=2)`

Consistency checks: work 1 is `Published` and work 2 is `Proposed`; `collaborationCount(A,B)` and `(B,A)` are both **1**, exactly the number of published works; `following(A,B)=true` and `following(B,A)=false`.

7.3 Rejection paths

Eight `eth_call` probes at the fixed block **12011205** (four rejections, four positive controls, changing only the caller or the circle):

Case	Result
Third party accepts a pending team	`only invited partner`
Invited party accepts the same team (control)	succeeds
Author confirms own work	`only other member`
Other member confirms (control)	succeeds
Post into a circle not joined	`join circle first`
Post into a joined circle (control)	succeeds
Confirm an already published work	`work not pending`
Confirm a pending work (control)	succeeds

> A caveat worth recording: "post into a circle not joined" must use a circle the account has **not** joined. The first run used a circle the account had since joined, and the probe succeeded; switching to an unjoined circle reproduced `join circle first`. This was a parameter mistake, not a contract defect.

7.4 Three escrow settlement paths

Three jobs executed on Sepolia:

Job	Result	Description
Job 1	`Completed` (3)	Client approved; 1 mUSD paid to the provider
Job 2	`Refunded` (4)	Deadline passed without delivery; 1 mUSD returned to the client
Job 3	`Completed` (3)	Client did not act; provider claimed after the 60-second review window

Final snapshot at block 12010056: client **98 mUSD**, provider **2 mUSD**, escrow contract **0 mUSD**, summing to 100.

Boundary precision: job 3 was submitted at 12:48:48 with a 60-second review window. At block 12010027, whose timestamp is exactly 12:49:48, `claim` still returned `review window open`; only a later block succeeded. This shows the implementation does not release early.

7.5 Cross-browser, cross-device, and real wallet

Scenario	Observation
Another browser (fresh Edge profile, no wallet)	Read the same content as Chrome, including the confirmed work with `Confirmed at block 12010030`
Another device (separate browser and storage, no wallet)	Read 2 posts and the same confirmed work, with matching signatures from both parties
Real wallet, successful write	Joined a circle → the button changed from `Join circle` to `Leave circle` → left again to restore state; both transactions `status=1`
Real wallet, cancelled signature	`Request cancelled in your wallet. No action was completed.`; on-chain nonce unchanged

Boundary: the second device was used for **read-only** verification only; no cross-device signed write was performed.

7.6 Cross-module entry point: community team → funded escrow job (verified)

This flow spans both modules and was executed end to end with two wallets on Sepolia on 2026-10-28.

Step	On-chain result
A mints test mUSD	100 mUSD to the client wallet
A publishes a task post	post 4, circle 2, kind 1 ("open task")
A invites B	team 4, host A, guest B, status Pending(1)
B accepts	team 4 status **Active(2)**
A approves 1 mUSD for the escrow	allowance consumed by the funding below
A creates and funds the job from the team	**job 4**, 1 mUSD escrowed
B submits a delivery digest	job 4 moves to submitted
A accepts and releases	job 4 status **Completed(3)**

Final balances after release, read at block 12012205: **client 99 mUSD, provider 1 mUSD, escrow contract 0 mUSD** — the 1 mUSD left the client exactly once and arrived at the provider exactly once, and no funds remain locked.

The team is linked to the job in the application layer only: the UI associates a team with an escrow job and can publish a client-authored reference as a community reply so the link is publicly checkable. JobEscrow itself has no team field. As the UI states, references "do not enforce settlement, prove quality, split payments or make feedback order-verified." This is a deliberate boundary, not an oversight.

> Earlier state (kept for accuracy): before this run, a task post (post 3) and a team invitation (team 3) existed on-chain between two accounts of the same operator, but the invitation was never accepted and no job was ever funded from that team. That is why an earlier version of this report listed the cross-module path as unverified. **That gap was closed on 2026-10-29** by the second run below.

Second cross-module run (2026-10-29, team 3 → job 5). A separate run used the same team 3 with a different job and different balances: community post 3 → team 3 → reply 3 → escrow **job 5**. Six successful transactions (`status=1`, blocks 12018477–12018556) cover the guest accepting the invitation, the 1 mUSD approval, funding, the link reply, the delivery digest, and the client's release. Job 5 is `Completed`; balances were **98 / 2 / 0** mUSD (client / provider / escrow) before the run and **97 / 3 / 0** after it, so the 1 mUSD left the client once and reached the provider once. The delivered file's Keccak-256 matches the on-chain digest (`0xd878a566…29ad`), and a read-only duplicate `release(5)` returned `not submitted`. The accounts, team, job and balances differ from §7.6's post 4 / team 4 / job 4 run and must not be combined; the record is `docs/project/TEAM3_ESCROW_SEPOLIA_ACCEPTANCE_2026-10-29.zh-CN.md`.

7.7 Frozen-candidate regression (D2 / #8)

Four layers were executed against the frozen candidate `992584e`: a fresh clone with 61 tests and a build; read-only replay of community and escrow state; six failure-path probes at a fixed block; and one real write (`0xfff88c7c…d7bd`, block 12010583) flipping `member(1,A)` from false to true. See `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`.

7.8 Cross-platform clean clone

Platform	Commit	Result
macOS 26.6 / arm64 (Apple M5, Node v24.22.1)	`7db718a`	64/64 tests, build succeeded, workspace clean, `.sol` and artefacts LF; frontend started from the new clone and screenshotted (the screenshot shows Demo sandbox and is explicitly not Sepolia evidence)
Windows (Node v24.15.0)	`7db718a` (same commit, same tree `afc673de…`)	64/64 tests, build succeeded, workspace clean, no artefact diff, `git ls-files --eol` byte-for-byte identical to the macOS record

---

8. Known Limitations and Risks

Each item below is **confirmed**, not speculative:

#	Limitation	Source
1	No owner, no pause, no upgrade: wording-level issues can only be fixed in the frontend	B1 review §1
2	An `Active` team has no terminal state; it cannot be cancelled or marked complete	B1 review §5
3	`proposeWork` / `reviewWork` check team membership only and **do not re-check circle membership**; leaving a circle does not revoke existing team rights (recorded as a design choice)	Issue #30
4	The contract source is **not verified on Etherscan**; consistency relies on local recompilation plus runtime code comparison	`DEPLOYMENTS.md`
5	The escrow deployment's source files differ in bytes from the current LF sources; reproducing it requires `evidence/escrow-deployment-sources.json`	Freeze draft §6
6	Rejection feedback depends on a revert during `eth_estimateGas` rather than an explicit UI guard	Frozen regression §3
7	The second device performed read-only verification only; no cross-device signed write	D1 acceptance §5
8	Storing long text on-chain makes writes expensive (`createPost` measured at 1.58M gas)	§5.3 of this report
9	On macOS, the ganache uWS native module has an ABI mismatch under Node 24 and falls back to pure JS (no impact on results)	macOS clone record

9. Contribution Distribution

Commit authorship on `main`: QiuQiu-xuan 45, Zqqq-qq 22, PAisHere 1, ffmitrg 1.

Per-member output is recorded in `docs/project/CONTRIBUTIONS.md`: entries for roles A, B, C and D are present, with the distinction between work "performed by the member" and work "assisted by tools (Codex)" stated explicitly. **Entries for E and R are still missing** (see §12).

Two points deserve honesty:

1. Part of the acceptance work was **tool-assisted** (running commands, capturing screenshots), but "confirmation" is kept strictly separate: wherever a record says a member confirmed something, that member performed the action in a real wallet. Tool output was never presented as member acceptance.
2. The designated owners of roles A and B were unreachable for long periods; their tasks were taken over by the repository owner, as recorded in `TEAM_TASKS.zh-CN.md` on 2026-10-28.

10. Conclusion and Future Work

Conclusion: the full loop — discover a circle → discuss a requirement → form a team → propose work → have the other party confirm → build a collaboration record → settle through escrow — has been executed on Sepolia with real transactions and leaves an independently verifiable evidence chain (receipts, events, state, balances, bytecode hashes). Every write path has a corresponding rejection-path verification, and the permission model contains no centralised backdoor.

Future work (each item has a concrete basis):

1. Add a terminal state for `Active` teams (requires an ABI change, redeployment, and coordination with role C).
2. Decide whether leaving a circle should revoke team rights; if it should, `proposeWork` / `reviewWork` need a membership re-check.
3. Submit the source for block-explorer verification to lower the reproduction cost of "recompile locally and compare".
4. Move long text off-chain with an on-chain hash to reduce write cost.
5. ~~Complete on-site acceptance of the "community team → escrow job" cross-module entry point~~ **done**: post 4 / team 4 / job 4 completed, 1 mUSD released — see §7.6.

---

11. Appendix

11.1 Evidence index

Category	Location
Deployment and receipts	`docs/project/DEPLOYMENTS.md`, `docs/project/evidence/community-sepolia-*.json`
Escrow	`docs/project/ESCROW_SEPOLIA_ACCEPTANCE_2026-10-28.zh-CN.md`, `evidence/escrow-*.json`, `evidence/escrow-screenshots/`, `evidence/job{1,2,3}-*`
Cross-module (team 3 → job 5)	`docs/project/TEAM3_ESCROW_SEPOLIA_ACCEPTANCE_2026-10-29.zh-CN.md`, `evidence/team3-job5/`, `scripts/verify-team3-acceptance.mjs`
D1 acceptance	`docs/project/ACCEPTANCE_D1.zh-CN.md` (including §7, the closing review)
D2 acceptance	`docs/project/ACCEPTANCE_D2.zh-CN.md`, `docs/project/FROZEN_CANDIDATE_REGRESSION_2026-10-28.zh-CN.md`, `docs/project/MACOS_CLEAN_CLONE_2026-10-28.zh-CN.md`
Permission review	`docs/project/REVIEW_B1_AGENTCOMMUNITY_2026-10-28.zh-CN.md`
Community deployment acceptance	`docs/project/SEPOLIA_ACCEPTANCE_2026-10-27.zh-CN.md`
Reproduction tools	`scripts/verify-community.mjs`, `scripts/verify-escrow-acceptance.mjs`, `scripts/release-freeze.mjs` (PR #36)

11.2 Reproduction environment

Node 24.x, pnpm 11.25.0 (pinned by `packageManager`), solc 0.8.30.

```
git clone https://github.com/Zqqq-qq/comp7610-agentledger.git
cd comp7610-agentledger
pnpm install --frozen-lockfile
pnpm test        # expect 64 passing tests
pnpm build
```

---

12. Outstanding Items (not fabricated; they require the team)

#	Missing	Impact	Owner
1	~~Implementation architecture diagram~~ **done**	`docs/assets/architecture.svg` (English) and `architecture.zh-CN.svg`, embedded in §4.1	—
2	**Member names, student IDs, effort**	§9 currently has only GitHub handles and commit counts	Team members
3	**E and R contribution entries**	`CONTRIBUTIONS.md` lacks these two rows, so §9 is incomplete	daizhiqi / whoever takes over
4	**Peer assignment** (individual submission)	Required by the course; not tracked anywhere in this repository, format still unknown	Course information needed
5	**Demo narration audio**	Script is complete (`docs/project/DEMO_SCRIPT.en.md`, timecoded, English); the video itself has visuals plus the real wallet segment but no audio track	Recorder
6	**A1 interface acceptance data**	`A1_UI_ACCEPTANCE` and 22 screenshots are in PR #32, not yet merged	Zqqq-qq (sync the branch)
7	**Leave-circle policy document**	`TEAM_CIRCLE_POLICY` is in PR #34, not yet merged	Zqqq-qq (sync the branch)
8	**Deployment gas attribution**	§5.3 reports receipt values only; explaining the 17.18M figure needs the deployer's account of how it was sent	Zqqq-qq

Two items that were open when this report was first drafted are now closed and are recorded here so the record is not silently edited:

- **Cross-module entry point** (community team → funded escrow job): executed end to end on 2026-10-28 (post 4 → team 4 → job 4, Completed, balances 99 / 1 / 0). See §7.6.
- **English deliverables**: the report, the README, the architecture diagram and the demo captions now exist in English; the remaining English gap is the narration audio (item 5).