

# Designing an MPC Controller for a Simplified Rocket Landing Problem

Sebastiano Zuddas

dept. Automatic Control & Systems Engineering

University of Sheffield

Sheffield, United Kingdom

sebastianozuddas1@gmail.com

**Abstract**—This document is a model and instructions for  $\text{\LaTeX}$ . This and the `IEEEtran.cls` file define the components of your paper [title, text, heads, etc.]. **\*CRITICAL: Do Not Use Symbols, Special Characters, Footnotes, or Math in Paper Title or Abstract.**

**Index Terms**—MPC, Rocket Landing, Model Predictive Control, Control Theory, Control Engineering

## I. INTRODUCTION

The objective of the assignment is to implement a model-predictive control (MPC) scheme to land a simplified model of a rocket. The problem is fundamentally one of 'controllability', ie  $x(0) = x_s \rightarrow x(t_f) = 0$ . The assignment gives an abstracted model, we start by rewriting the model as follows:

$$\begin{bmatrix} r_x(k+1) \\ r_y(k+1) \\ r_z(k+1) \\ v_x(k+1) \\ v_y(k+1) \\ v_z(k+1) \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & T_s & 0 & 0 \\ 0 & 1 & 0 & 0 & T_s & 0 \\ 0 & 0 & 1 & 0 & 0 & T_s \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} r_x(k) \\ r_y(k) \\ r_z(k) \\ v_x(k) \\ v_y(k) \\ v_z(k) \end{bmatrix} + \begin{bmatrix} \frac{T_s^2}{2m} & 0 & 0 \\ 0 & \frac{T_s^2}{2m} & 0 \\ 0 & 0 & \frac{T_s^2}{2m} \\ T_s & 0 & 0 \\ 0 & T_s & 0 \\ 0 & 0 & T_s \end{bmatrix} \begin{bmatrix} f_x(k) + w_x \\ f_y(k) + w_y \\ f_z(k) - mg \end{bmatrix} \quad (1)$$

Although we assume the system is reachable, it is important to check for controllability. Through MATLAB: `Rank = rank(ctrb(A, B))` we find the system is controllable, and we can proceed with designing a controller.

## II. DESIGN

### A. Controller Design

Three separate controllers are considered in this report. The first controller is an unconstrained, two stage MPC. The second controller builds on the first, and introduces both state and input constraints. The third controller further builds on the first two, introducing disturbance rejection. We start by looking at the unconstrained controller.

1) *Unconstrained:* The  $Q$  and  $R$  matrices are chosen as follows:

$$Q = \begin{bmatrix} 5 & 0 & 0 & 0 & 0 & 0 \\ 0 & 5 & 0 & 0 & 0 & 0 \\ 0 & 0 & 100 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 100 \end{bmatrix}; R = I \cdot 0.1 \text{ for } I \in \mathbb{R}^{3 \times 3}$$

The  $Q$  matrix was chosen as to prioritise the vertical position and velocity. This represents the high level of importance given to landing at the correct altitude. Similarly, the prioritisation of velocity represents the importance of landing a velocity that prevents a hard landing. The lateral positions, ie  $r_x$  and  $r_y$ , are given a lower priority than the vertical position, but a higher priority than the lateral velocity,  $v_x$  and  $v_y$ . The reasoning behind this is that it is more important that the landing location is correct over the lateral velocities throughout the entire simulation.

The  $R$  matrix was chosen as to penalise the control inputs,  $f_x$ ,  $f_y$  and  $f_z$ , equally. The small value given to  $R$ , 0.1, represents the low cost associated with expending fuel to control the rocket, and encourages the rocket to use fuel to exercise control in all three directions equally. Essentially, control is cheap. The horizon length  $N$  was chosen to be 5 as it provided a spectral radius of 0.5975, which is well within the stability region of the system.

The poles of the closed loop system were placed through `K_2 = -place(A, B, [0.01 0.01 0 0.01 0 0])`. The most important poles, ie the poles representing  $r_z$ ,  $v_z$  were placed at zero. The limitations of the `place()` function meant that not every pole could be set to zero, hence the other poles were set to 0.01. The weighting matrix  $P$  was calculated using `P = dlyap((A+B*K_2), Q+K_2'*R*K_2)`. The prediction matrices  $F$  and  $G$  were generated using the `predict_mats()` function, and the corresponding cost matrices  $H$ ,  $L$  and  $M$  were generated using the `cost_mats()` function. We assume at this point that  $Q \succeq 0$  and  $R \succ 0$  which implies  $\bar{u}_N^*(k) = -H^{-1} \cdot Lx(k)$ . As such, the unique and optimal solution to the optimal control problem is obtained and is through quadratic programming at

each time step  $U_{\text{opt}} = \text{quadprog}(H, L \star x)$

2) *Constrained*: The constrained controller builds on the unconstrained controller by introducing both state and input constraints. The input constraints are chosen as follows: The linear inequality constraints are based on the brief, and are chosen as follows:

$$P_x = \begin{bmatrix} I_x \\ -I_x \end{bmatrix} P_u = \begin{bmatrix} I_u \\ -I_u \end{bmatrix} \text{ for } I_x \in \mathbb{R}^{6 \times 6} \text{ and } I_u \in \mathbb{R}^{3 \times 3}$$

$$q_x = \begin{bmatrix} \frac{r_z}{\tan \phi} + 50 \\ \frac{r_z}{\tan \phi} + 50 \\ 500 \\ 20 \\ 20 \\ 15 \\ \frac{r_z}{\tan \phi} + 50 \\ \frac{r_z}{\tan \phi} + 50 \\ 0 \\ 20 \\ 20 \\ 15 \end{bmatrix} \quad q_u = \begin{bmatrix} f_z \cdot \tan \theta \\ f_z \cdot \tan \theta \\ 12 \\ f_z \cdot \tan \theta \\ f_z \cdot \tan \theta \\ 0 \end{bmatrix}$$

The  $r_x$   $r_y$  constraints were given in the brief as  $|r_x|, |r_y| \leq \frac{r_z}{\tan \phi}$  where  $\phi$  represents the glide slope angle, and is chosen as a constant  $\phi = 30^\circ = 0.52$  rad. The input constraints given in the brief as  $|f_x|, |f_y| \leq f_z \tan \theta$  where  $\theta$  represents the maximum allowable angle of the rocket engines, and is chosen as  $\theta = 10^\circ = 0.17$  rad.




Fig. 1.  $f_z$  on the  $z$  axis.

Figure ?? provides a visualisation of how  $f_z$  acts on the point mass.

3) *Disturbance Rejection*: The disturbance rejection controller builds on both the unconstrained and constrained controllers. No reference tracking is included in the following controller. Only wind disturbance is considered, and is modelled as a sinusoid as follows:

$$\vec{w}(k) = \begin{bmatrix} \sin \frac{50}{k} \\ \cos \frac{50}{k} \\ 0 \end{bmatrix}$$

The use of a sinusoid disturbance is intended to represent the changing windspeeds as the rocket descends. The sinusoid functions were chosen to be out of phase as to yield visibly different results.

In terms of controller design, equation ?? is rewritten as follows:

$$\begin{cases} x(k+1) = Ax(k) + Bu(k) + Ew(k) \\ y(k) = Cx(k) + Fd(k) \end{cases}$$

where  $E = B$  and  $F = 0$  since we ignore output disturbance, hence:

$$\begin{cases} x(k+1) = Ax(k) + B(u(k) + w(k)) \\ y(k) = Cx(k) \end{cases}$$

It is now possible to formulate the  $T$  matrix to find  $x_{ss}; u_{ss}$ .

$$T = \begin{bmatrix} I - A & -B \\ C & 0 \end{bmatrix}$$

In this case, we have  $C \in \mathbb{R}^{6 \times 6} \wedge B \in \mathbb{R}^{6 \times 3} \therefore p < m \iff 3 < 6$ . As such, we expect only some as such,  $x_{ss}; u_{ss}$  are given by:

$$\begin{bmatrix} x_{ss}(k) \\ u_{ss}(k) \end{bmatrix} = \begin{bmatrix} T^{-1}B \cdot \vec{w}(k) \\ 0 \end{bmatrix}$$

### B. Experiment Setup

First, it is important to state simplifications assumed.

Let the starting parameters be as follows:

$$\vec{x}(0) = \begin{bmatrix} 600 \\ 600 \\ 500 \\ 5 \\ 5 \\ -15 \end{bmatrix} \wedge \vec{u}(0) = \vec{0}$$

These starting conditions are the limits of what the assignment permits, i.e a maximum starting altitude of 500m, and a maximum lateral distance of 600m.

## III. RESULTS

## IV. ANALYSIS & DISCUSSION

## V. CONCLUSION

## VI. EASE OF USE

### A. Maintaining the Integrity of the Specifications

The IEEEtran class file is used to format your paper and style the text. All margins, column widths, line spaces, and text fonts are prescribed; please do not alter them. You may note peculiarities. For example, the head margin measures proportionately more than is customary. This measurement and others are deliberate, using specifications that anticipate your paper as one part of the entire proceedings, and not as an independent document. Please do not revise any of the current designations.

## VII. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections ??-?? below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— $\LaTeX$  will do that for you.

### A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

### B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as “3.5-inch disk drive”.
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: “Wb/m<sup>2</sup>” or “webers per square meter”, not “webers/m<sup>2</sup>”. Spell out units when they appear in text: “. . . a few henries”, not “. . . a few H”.
- Use a zero before decimal points: “0.25”, not “.25”. Use “cm<sup>3</sup>”, not “cc”.)

### C. Equations

Number equations consecutively. To make your [?] equations more compact, you may use the solidus ( / ), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in:

$$a + b = \gamma \quad (2)$$

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(??)”, not “Eq. (??)” or “equation (??)”, except at the beginning of a sentence: “Equation (??) is . . .”

### D. $\LaTeX$ -Specific Advice

Please use “soft” (e.g., `\eqref{Eq}`) cross references instead of “hard” references (e.g., (1)). That will make it possible to combine sections, add equations, or change the order of figures or citations without having to go through the file line by line.

Please don’t use the `{eqnarray}` equation environment. Use `{align}` or `{IEEEeqnarray}` instead. The `{eqnarray}` environment leaves unsightly spaces around relation symbols.

Please note that the `{subequations}` environment in  $\LaTeX$  will increment the main equation counter even when there are no equation numbers displayed. If you forget that, you might write an article in which the equation numbers skip from (17) to (20), causing the copy editors to wonder if you’ve discovered a new method of counting.

$\BIBTeX$  does not work by magic. It doesn’t get the bibliographic data from thin air but from .bib files. If you use  $\BIBTeX$  to produce a bibliography you must send the .bib files.

$\LaTeX$  can’t read your mind. If you assign the same label to a subsubsection and a table, you might find that Table I has been cross referenced as Table IV-B3.

$\LaTeX$  does not have precognitive abilities. If you put a `\label` command before the command that updates the counter it’s supposed to be using, the label will pick up the last counter to be cross referenced instead. In particular, a `\label` command should not go before the caption of a figure or a table.

Do not use `\nonumber` inside the `{array}` environment. It will not stop equation numbers inside `{array}` (there won’t be any anyway) and it might stop a wanted equation number in the surrounding equation.

### E. Some Common Mistakes

- The word “data” is plural, not singular.
- The subscript for the permeability of vacuum  $\mu_0$ , and other common scientific constants, is zero with subscript formatting, not a lowercase letter “o”.
- In American English, commas, semicolons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an “inset”, not an “insert”. The word alternatively is preferred to the word “alternately” (unless you really mean something that alternates).

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of

quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

#### ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

**Temporary page!**

L<sup>A</sup>T<sub>E</sub>X was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it.

If you rerun the document (without altering it) this surplus page will go away, because L<sup>A</sup>T<sub>E</sub>X now knows how many pages to expect for this document.