

Designing an MPC Controller for a Simplified Rocket Landing Problem

Sebastiano Zuddas
dept. Automatic Control & Systems Engineering
University of Sheffield
Sheffield, United Kingdom
sebastianozuddas1@gmail.com

Abstract—This document is a model and instructions for L^AT_EX. This and the IEEEtran.cls file define the components of your paper [title, text, heads, etc.]. *CRITICAL: Do Not Use Symbols, Special Characters, Footnotes, or Math in Paper Title or Abstract.

Index Terms—MPC, Rocket Landing, Model Predictive Control, Control Theory, Control Engineering

I. INTRODUCTION

The objective of the assignment is to implement a model-predictive control (MPC) scheme to land a simplified model of a rocket. The problem is fundamentally one of 'controllability', ie $x(0) = x_s \rightarrow x(t_f) = 0$. The assignment gives an abstracted model, we start by rewriting the model as follows:

$$(1) \begin{bmatrix} r_x(k+1) \\ r_y(k+1) \\ r_z(k+1) \\ v_x(k+1) \\ v_y(k+1) \\ v_z(k+1) \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & T & 0 & 0 \\ 0 & 1 & 0 & 0 & T & 0 \\ 0 & 0 & 1 & 0 & 0 & T \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} r_x(k) \\ r_y(k) \\ r_z(k) \\ v_x(k) \\ v_y(k) \\ v_z(k) \end{bmatrix} + \begin{bmatrix} \frac{T^2}{2m} & 0 & 0 \\ 0 & \frac{T^2}{2m} & 0 \\ 0 & 0 & \frac{T^2}{2m} \\ T & 0 & 0 \\ 0 & T & 0 \\ 0 & 0 & T \end{bmatrix} \begin{bmatrix} f_x(k) + w_x \\ f_y(k) + w_y \\ f_z(k) - mg \end{bmatrix}$$

Although we assume the system is reachable, it is important to check for controllability. Through MATLAB: `Rank = rank(ctrb(A, B))` we find the system is controllable, and we can proceed with designing a controller.

II. DESIGN

A. Controller Design

Three separate controllers are considered in this report. The first controller is an unconstrained, two stage MPC. The second controller builds on the first, and introduces both state and input constraints. The third controller further builds on

the first two, introducing disturbance rejection. We start by looking at the unconstrained controller.

1) *Unconstrained*: The Q and R matrices are chosen as follows:

$$Q = \begin{bmatrix} 5 & 0 & 0 & 0 & 0 & 0 \\ 0 & 5 & 0 & 0 & 0 & 0 \\ 0 & 0 & 100 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 100 \end{bmatrix}; R = I \cdot 0.1 \text{ for } I \in \mathbb{R}^{3 \times 3}$$

The Q matrix was chosen as to prioritise the vertical position and velocity. This represents the high level of importance given to landing at the correct altitude. Similarly, the prioritisation of velocity represents the importance of landing a velocity that prevents a hard landing. The lateral positions, ie r_x and r_y , are given a lower priority than the vertical position, but a higher priority than the lateral velocity, v_x and v_y . The reasoning behind this is that it is more important that the landing location is correct over the lateral velocities throughout the entire simulation.

The R matrix was chosen as to penalise the control inputs, f_x , f_y and f_z , equally. The small value given to R , 0.1, represents the low cost associated with expending fuel to control the rocket, and encourages the rocket to use fuel to exercise control in all three directions equally. Essentially, control is cheap. The horizon length N was chosen to be 5 as it provided a spectral radius of 0.5975, which is well within the stability region of the system.

2) *Constrained*: The constrained controller builds on the unconstrained controller by introducing both state and input constraints. The input constraints are chosen as follows:

$$u_{max} \begin{bmatrix} f_z \cdot \tan \theta \\ f_z \cdot \tan \theta \\ 0 \end{bmatrix}; u_{min} = \begin{bmatrix} -f_z \cdot \tan \theta \\ -f_z \cdot \tan \theta \\ -12 \end{bmatrix}$$

the input constraints given in the brief as $|f_x|, |f_y| \leq f_z \tan \theta$. The angle θ represents the maximum allowable angle of the rocket engines, and is chosen as $\theta = 10^\circ = 0.17$ rad.




Fig. 1. f_z on the z axis.

Figure ?? shows the justification for setting the f_z constraint in the negative z direction. Since the rocket must exert thrust to decelerate, the f_z input must be negative.

The state constraints are chosen as follows:

$$x_{max} = \begin{bmatrix} \frac{r_z}{\tan \phi} + 50 \\ \frac{r_z}{\tan \phi} + 50 \\ 500 \\ 20 \\ 20 \\ 15 \end{bmatrix}; x_{min} = \begin{bmatrix} -\frac{r_z}{\tan \phi} - 50 \\ -\frac{r_z}{\tan \phi} - 50 \\ 0 \\ -20 \\ -20 \\ -15 \end{bmatrix}$$

The r_x r_y constraints were given in the brief as $|r_x|, |r_y| \leq \frac{r_z}{\tan \phi}$. The angle ϕ represents the glide slope angle, and is chosen as a constant $\phi = 30^\circ = 0.52$ rad.

3) *Disturbance Rejection:* The disturbance rejection controller builds on both the unconstrained and constrained controllers. Only wind disturbance is considered, and is modelled as a sinusoid as follows:

$$\vec{w}(k) = \begin{bmatrix} \sin \frac{50}{k} \\ \cos \frac{50}{k} \\ 0 \end{bmatrix}$$

In terms of controller design, we start by rewriting equation ?? as follows:

$$\begin{cases} x(k+1) = Ax(k) + Bu(k) + Ew(k) \\ y(k) = Cx(k) + Fd(k) \end{cases}$$

where $E = B$ and $F = 0$ since we ignore output disturbance, hence:

$$\begin{cases} x(k+1) = Ax(k) + B(u(k) + w(k)) \\ y(k) = Cx(k) \end{cases}$$

It is now possible to formulate the T matrix to find $x_{ss}; u_{ss}$.

$$T = \begin{bmatrix} I - A & -B \\ C & 0 \end{bmatrix}$$

In this case, we have $C \in \mathbb{R}^{6 \times 6} \wedge C \in \mathbb{R}^{6 \times 3} \therefore p < m \iff 3 < 6$. As such, we expect only some as such, $x_{ss}; u_{ss}$ are given by:

$$\begin{bmatrix} x_{ss}(k) \\ u_{ss}(k) \end{bmatrix} = \begin{bmatrix} T^{-1}B \cdot \vec{w}(k) \\ 0 \end{bmatrix}$$

B. Experiment Setup

First, it is important to state simplifications assumed. Let the starting parameters be as follows:

$$\vec{x}(0) = \begin{bmatrix} 600 \\ 600 \\ 500 \\ 5 \\ 5 \\ -15 \end{bmatrix} \wedge \vec{u}(0) = \vec{0}$$

These starting conditions are the limits of what the assignment permits, i.e a maximum starting altitude of 500m, and a maximum lateral distance of 600m.

III. RESULTS

IV. ANALYSIS & DISCUSSION

V. CONCLUSION

VI. EASE OF USE

A. Maintaining the Integrity of the Specifications

The IEEEtran class file is used to format your paper and style the text. All margins, column widths, line spaces, and text fonts are prescribed; please do not alter them. You may note peculiarities. For example, the head margin measures proportionately more than is customary. This measurement and others are deliberate, using specifications that anticipate your paper as one part of the entire proceedings, and not as an independent document. Please do not revise any of the current designations.

VII. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections ??-?? below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— \LaTeX will do that for you.

A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as “3.5-inch disk drive”.
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: “Wb/m²” or “webers per square meter”, not “webers/m²”. Spell out units when they appear in text: “. . . a few henries”, not “. . . a few H”.
- Use a zero before decimal points: “0.25”, not “.25”. Use “cm³”, not “cc”.)

C. Equations

Number equations consecutively. To make your [?] equations more compact, you may use the solidus (/), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in:

$$a + b = \gamma \quad (2)$$

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(??)”, not “Eq. (??)” or “equation (??)”, except at the beginning of a sentence: “Equation (??) is . . .”

D. \LaTeX -Specific Advice

Please use “soft” (e.g., `\eqref{Eq}`) cross references instead of “hard” references (e.g., (1)). That will make it possible to combine sections, add equations, or change the order of figures or citations without having to go through the file line by line.

Please don’t use the `{eqnarray}` equation environment. Use `{align}` or `{IEEEeqnarray}` instead. The `{eqnarray}` environment leaves unsightly spaces around relation symbols.

Please note that the `{subequations}` environment in \LaTeX will increment the main equation counter even when there are no equation numbers displayed. If you forget that, you might write an article in which the equation numbers skip from (17) to (20), causing the copy editors to wonder if you’ve discovered a new method of counting.

\BIBTeX does not work by magic. It doesn’t get the bibliographic data from thin air but from .bib files. If you use \BIBTeX to produce a bibliography you must send the .bib files.

\LaTeX can’t read your mind. If you assign the same label to a subsubsection and a table, you might find that Table I has been cross referenced as Table IV-B3.

\LaTeX does not have precognitive abilities. If you put a `\label` command before the command that updates the counter it’s supposed to be using, the label will pick up the last counter to be cross referenced instead. In particular, a `\label` command should not go before the caption of a figure or a table.

Do not use `\nonumber` inside the `{array}` environment. It will not stop equation numbers inside `{array}` (there won’t be any anyway) and it might stop a wanted equation number in the surrounding equation.

E. Some Common Mistakes

- The word “data” is plural, not singular.
- The subscript for the permeability of vacuum μ_0 , and other common scientific constants, is zero with subscript formatting, not a lowercase letter “o”.
- In American English, commas, semicolons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an “inset”, not an “insert”. The word alternatively is preferred to the word “alternately” (unless you really mean something that alternates).

- Do not use the word “essentially” to mean “approximately” or “effectively”.
- In your paper title, if the words “that uses” can accurately replace the word “using”, capitalize the “u”; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones “affect” and “effect”, “complement” and “compliment”, “discreet” and “discrete”.
- Do not confuse “impl
- The prefix “non” is not a word it modifies, usually.
- There is no period after “et al.”.
- The abbreviation “i.e.” means “for example” and “e.g.” means “for instance”.

An excellent style manual

F. Authors and Affiliations

The class file is designed for authors. A minimum of one author is required for all conference articles. Author name should be placed at the top right and then moving down the author sequence that will be used by indexing services. Names should be grouped by affiliation. Please use the same style for all possible (for example, do not use different styles for members of the same organization).

G. Identify the Headings

Headings, or heads, are used to lead the reader through your paper. They include section heads and text heads.

Component heads identify the sections of your paper and are not to be confused with section heads. Examples include Acknowledgments, References, etc. For these, the correct style to use is “Section Head” for your Figure caption. Run-in heads, such as “Figure 1”, should be used to apply a style (in this case, the style provided by the drop down menu) to the text.

Text heads organize the topics of a document on a hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced.

H. Figures and Tables

a) *Positioning Figures and Tables:* Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert

TABLE I
TABLE TYPE STYLES

Table Head	Table Column Head		
	Table column subhead	Subhead	Subhead
copy	More table copy ^a		

^aSample of a Table footnote.




Fig. 2. Example of a figure caption.

figures and tables after they are cited in the text. Use the abbreviation “Fig. ??”, even at the beginning of a sentence.

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of

quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

Temporary page!

L^AT_EX was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it.

If you rerun the document (without altering it) this surplus page will go away, because L^AT_EX now knows how many pages to expect for this document.