

莫队

普通莫队做法

P2709 【模板】莫队 / 小B的询问

- 核心模型:
- 思维误区 (Bug):
- 修正逻辑 (Patch):
- 关键代码:

```
struct qry
{
    int l, r, id;
};

void solve()
{
    int n, m, k;
    cin >> n >> m >> k;
    vi nums(n + 1);
    for (int i = 1; i <= n; i++)
    {
        cin >> nums[i];
    }
    vi cnt(k + 3);
    vector<qry> qry(m);

    for (int i = 0; i < m; i++)
    {
        cin >> qry[i].l >> qry[i].r;
        qry[i].id = i;
    }
    int bk = max(1, (int)sqrt(n));
    sort(all(qry), [&](qry a, qry b)
        {
            int aa=a.l/bk;
            int bb=b.l/bk;
            if(aa!=bb)return aa<bb;
            else
            {
                return a.r<b.r;
            }
        });

    int now = 0;
    auto add = [&](int x) -> void
    {
        now += 2 * cnt[nums[x]] + 1;
        cnt[nums[x]]++;
    };
    auto del = [&](int x) -> void
```

```
{
    now -= 2 * cnt[nums[x]] - 1;
    cnt[nums[x]]--;
};

int lef = 1;
int ri = 0;
vi anss(m);
ll ans = 0;
for (int i = 0; i < m; i++)
{
    while (lef > qry[i].l)
    {
        lef--;
        add(lef);
    }

    while (ri < qry[i].r)
    {
        ri++;
        add(ri);
    }

    while (lef < qry[i].l)
    {
        del(lef);
        lef++;
    }

    while (ri > qry[i].r)
    {
        del(ri);
        ri--;
    }

    anss[qry[i].id] = now;
}
for (int i = 0; i < m; i++)
{
    cout << anss[i] << '\n';
}
}
```