

# Discrete-time models- Lab 5

Zhu Chenhao

22320630

Consider a linear system of the form

$$\ddot{y} + a_1 \dot{y} + a_0 y = b_0 u, \quad (1)$$

where  $a_0, a_1, b_0 \in \mathbb{R}$ ,  $y$  - is output of the system and  $u$  - is control signal.

## 0. Initial Data

```
task.parameters
```

```
ans = 包含以下字段的 struct:
```

```
T: 2.3000  
a0: 10  
a1: 20  
b0: 1
```

```
T = 2.3000;  
a0 = 10;  
a1 = 20;  
b0 = 1;
```

## 1. State space model

```
A = [0 1; -a0 -a1];  
B = [0; b0];  
C = [1 0];  
D = 0;
```

## 2. Eigenvalues

```
eig_value = eig(A)
```

```
eig_value = 2x1  
-0.5132  
-19.4868
```

```
eig_value_continuous_1 = eig_value(2,1);  
eig_value_continuous_2 = eig_value(1,1);
```

### 3. Discrete system

```
sys = ss(A, B, C, D);  
Ad = expm(A*T);  
Bd = A \ (Ad - eye(size(A)))*B;
```

### 4. Eigenvalues of a discrete system

```
sysd = ss(Ad, Bd, C, D, T);  
eig_value_d = eig(Ad);  
eig_value_discrete_1 = eig_value_d(2,1);  
eig_value_discrete_2 = eig_value_d(1,1);
```

### 5. Stepinfo to find the number of steps


```
step_info = stepinfo(sysd);  
disp(step_info);
```

```
RiseTime: 2.3000  
TransientTime: 9.2000  
SettlingTime: 9.2000  
SettlingMin: 0.0903  
SettlingMax: 0.1000  
Overshoot: 2.2204e-14  
Undershoot: 0  
Peak: 0.1000  
PeakTime: 75.9000
```

```
transient_time = step_info.TransientTime;  
num_steps_until_end_of_transient = transient_time / T
```


```
num_steps_until_end_of_transient = 4
```

```
step(sysd, sys)
```




## 6. Using ode45 and input signal $u(t) = 1$

```
u = 1;
tspan = [0 50];
x0 = [0; 0];
sol = ode45(@(t,x) odefun(t,x,u,a0,a1,b0),tspan,x0);
plot(sol.x,sol.y(1,:))
hold on;
t_d = 0:T:50;
n = length(t_d);
x_d = zeros(2,n);
x_d(:, 1) = x0;
for k = 1:n-1
    x_d(:, k+1) = Ad*x_d(:, k)+Bd*u;
end
plot(t_d, x_d(1, :))
legend show;
hold off;
```




```
y_kt = x_d(1, :);
for k = 1:n
    y_t(:,k) = deval(sol, t_d(k));
end
plot(t_d, y_t(1, :) - y_kt, 'LineWidth', 2);
title("error")
```



## 7. Input signal $u(t) = 2 \cdot \sin(4 \cdot t)$


```
tspan = [0 100];
x0 = [0; 0];
sol = ode45(@(t,x) odefun2(t,x,a0,a1,b0), tspan, x0);
plot(sol.x, sol.y(1,:))
hold on;
t_d2 = 0:T:100;
n = length(t_d2);
x_d = zeros(2, n);
x_d(:, 1) = x0;
u_d = zeros(1,n);
for k = 1:n-1
    u_d(1, k) = 2*sin(4*k*T);
    x_d(:, k+1) = Ad*x_d(:, k) + Bd * u_d(1, k);
end
plot(t_d2, x_d(1,:))
legend show;
hold off;
```



```





y2_kt = x_d(1, :);
for k = 1:n
    y2_t(:, k) = deval(sol, t_d2(k));
end
plot(t_d2, y2_t(1, :) - y2_kt, 'LineWidth', 2);

```



## 8. Plot the graphs

## Lab 5: Continuous vs Discrete System Responses



Because my sampling time  $T_s$  is relatively large, the discrete data does not fit well for sinusoidal response.

## Answers

ans = 包含以下字段的 struct:

```
eig_value_continuous_1: -19.4868
eig_value_continuous_2: -0.5132
eig_value_discrete_1: 1.7347e-18
eig_value_discrete_2: 0.3072
steps_transition_process: 4
```

You have 37 attempts left

ans = 包含以下字段的 struct:

```
eig_value_continuous_1: 0.5000
eig_value_continuous_2: 0.5000
eig_value_discrete_1: 0.5000
eig_value_discrete_2: 0.5000
steps_transition_process: 1
total_score: 3
```