Setu 桥 — Technical Documentation

2026 Shenzhen FinTechathon · International Track · Topic C: Cross-border & Student Finance Assistant

> **Data notice.** All data in this project is **SYNTHETIC** (personas, fee notices, SMS, accounts). The bank is a **SANDBOX** ledger. Setu **never holds funds**. Offline FX rates are labelled **SAMPLE** (not live) and channel fees are illustrative. The default planner is a deterministic **scripted** planner that runs fully offline.

This document consolidates `README.md`, `docs/ARCHITECTURE.md`, `docs/ARCHITECTURE_TS.md`, `docs/API.md`, `docs/DATA_FLOW.md`, `docs/THREAT_MODEL.md`, `docs/SECURITY_SELF_ASSESSMENT.md`, `docs/MOBILE_PLAN.md`, `web/CONTRACT_NOTES.md` and the generated reports in `evidence/`. Repository: `Zul-Qarnain/setu-fintechathon` (main, `cc4247d`).

Contents

1. Overview
2. Architecture
3. Permission tiers T0–T4
4. API overview
5. Security design
6. Deployment
7. Testing and evidence
8. Demo walkthrough
9. Next phase
10. Repository map

---

1. Overview

International (South Asian) students in China pay tuition, dorm fees and insurance across borders, receive notices in Chinese they may not fully read, and are a prime target for "the account number changed" scams. **Setu reads the notice, explains it in English or 简体中文, shows the real total cost, and prepares the payment — but never moves money on a model's say-so.** A deterministic policy engine plus a family approver decide, and every step is written to a tamper-evident audit log.

What is built:

Component	Technology	Location
Backend API	TypeScript (strict), Node 20, Fastify, Zod, better-sqlite3 (pinned 12.4.1), decimal.js, jose (JWT), @node-rs/argon2, pino	`server/`

Component	Technology	Location
Agent pipeline	Hand-written state machine (no agent framework), scripted EN/ZH planner	`server/src/agents/`
Policy engine	Pure function `policy.decide(action, ctx)`	`server/src/domain/policy.ts`
Sandbox bank	Toy ledger with idempotency keys and deterministic failure modes	`server/src/sandboxBank/`
Web app	Next.js, bilingual (English / 简体中文) via next-intl	`web/`
Seed-data generator	Deterministic TypeScript generator for all SYNTHETIC data	`server/scripts/generate_data.ts`
Evaluation kit	25 golden tasks, 17 attack scenarios, 33-notice corpus	`server/eval/`, `server/src/evalkit/`, `data/`

2. Architecture

2.1 Design principles

1. **The LLM interprets; deterministic code computes.** Every number a user sees (fees, BDT needed, rates, dates) comes from deterministic code (`domain/fx.ts`, `costs.ts`, `budget.ts`). A reply validator rejects any reply containing a number that is not in a tool output or the user's own message.
2. **The server decides, never the model.** One pure function, `policy.decide(action, ctx)`, authorises every action. It is evaluated when an action is proposed, again on every approval, and a last time inside the executor. The executor accepts only `ALLOW`.
3. **Documents and SMS are DATA.** They are wrapped in `<untrusted>`, scanned by the guardian, and can never be the *source* of a payment, a payee or an amount. Payees and amounts are resolved server-side from the payee registry or a user-confirmed obligation.
4. **Default deny, smallest blast radius.** Unknown action types, unregistered/unverified payees, document-sourced actions and bulk exports are T4 (blocked).
5. **Tamper-evident accountability.** Every material event is appended to a SHA-256 hash-chained audit log with PII redacted before hashing.
6. **Works offline.** The default planner is the deterministic scripted adapter; no keys, no network and no model are needed for tests, the demo or the API.

2.2 Component map

```
flowchart LR
  subgraph Web["web/ (Next.js, EN / 简体中文)"]
    UI[Dashboard · Documents · Agent · Payees · Approvals · Audit · Settings]
  end
  subgraph API["server/src (Fastify + Zod)"]
    R[routes: auth, documents, chat, actions, payees, fx, audit, evidence, dashboard,
sandbox, demo]
    AG[agents/graph.ts: state machine]
    POL[domain/policy.ts: decide]
    DOM[domain: fx, costs, budget, crypto, tokenize, audit]
    SBX[sandboxBank/ledger.ts]
    DB[(SQLite via better-sqlite3)]
  end
  UI -->|JSON over HTTP, JWT| R
  R --> AG
  AG --> DOM
  AG --> POL
  R -->|approve| POL
  POL -->|ALLOW only| EX[agents/executor.ts]
  EX --> SBX
  R --> DB
  SBX --> DB
  DOM -->|audit chain| DB
  FX[(data/fx_rates_sample.json SAMPLE)] --> DOM
```

2.3 Agent pipeline (`agents/graph.ts`)

`intake → planner → tools → guardian → policy → executor | await_approval → validator`

Step	What it does	Trust boundary
intake	Reads uploaded `.txt` or pasted text, parses fields with regexes (EN + 简体中文), tokenises account numbers (`ACCT_…`), wraps the text in `<untrusted>`	document text is untrusted
planner	Emits **only** `ToolCall` JSON from an allowlist: `get_obligation`, `list_obligations_due`, `fx_quote`, `compute_costs`, `budget_summary`, `propose_payment`, `propose_verify_payee`, `draft_message`. Schema, tool name and per-tool arguments are validated (extra keys forbidden); invalid plans are rejected	planner output is untrusted
tools	Deterministic code. `propose_*` only *creates* an action row; nothing executes	server code
guardian	Regex rules (EN/ZH) + registry checks: injection phrases, "don't ask the user", personal-account channels, urgency scams, homoglyphs, amount mismatch, payee changed / unverified / lookalike / not in registry	rule-based
policy	`decide()` returns `ALLOW / REQUIRE_APPROVAL / REQUIRE_COOLING_OFF / BLOCK` plus tier T0–T4 and machine reasons	the only authority

Step	What it does	Trust boundary
executor / await_approval	`ALLOW` → sandbox bank transfer (idempotent). Otherwise the action waits for TOTP / family approver / cooling-off	accepts `ALLOW` only
validator	Every number in the reply must be grounded in tool outputs or the user message, otherwise a safe fallback reply is used	output check

`POST /chat` returns a `trace` object with these seven steps, which the web app renders as a live trace (`llm_mode: scripted-offline`).

Planner. The `ScriptedAdapter` classifies intent with deterministic EN/ZH regexes in the order payee-change, unsafe, FX, how-much, pay, fees, budget. The planner sits behind an adapter interface, so other planners can be added later under the same allowlist and schema validation.

2.4 Domain modules

- `domain/crypto.ts` — AES-256-GCM with AAD (`enc:v1:` prefix, fresh random 12-byte IV per encryption) for payee accounts, TOTP secrets and uploaded text; HMAC-SHA256 for lookups.
- `domain/tokenize.ts` — NFKC normalisation, homoglyph detection, name skeletons, HMAC tokens, `redactPII` for logs and audit.
- `domain/audit.ts` — canonical JSON, hash-chain compute/verify.
- `domain/fx.ts` — FX service: fixture (labelled SAMPLE) or live adapter (open.er-api.com, `FX_MODE=live`), 24 h cache, injectable clock, live-failure fallback labelled as fixture.
- `domain/costs.ts`, `budget.ts` — fee model (sandbox "licensed partner A": USD 3.00 fixed + 0.40 % FX margin, illustrative) and budget summaries. Money uses `decimal.js`, never floats.
- `security.ts`, `deps.ts` — argon2id passwords; JWT HS256 pinned, `exp/sub/iat` required, role re-read from the DB on each request; RFC 6238 TOTP on `node:crypto` (±1 step, replay protection, 5-failure / 300 s lockout); sliding-window rate limiter.

2.5 Sandbox bank (deterministic behaviour)

Trigger	Result
destination ends `0013`	`failed` / `ACCOUNT_CLOSED`
amount > CNY 50,000	`failed` / `LIMIT_EXCEEDED`
amount with cents `.99`	`held` / `RISK_HOLD`
balance < amount	`failed` / `INSUFFICIENT_FUNDS`
same idempotency key, same parameters	returns the original transaction (no double spend)
same key, different parameters	rejected (idempotency mismatch)

2.6 Persistence

SQLite via better-sqlite3 (in-memory for tests and the demo; a file or Docker volume for the API). Tables: `users, payees, documents, obligations, plans, actions, audit, sbx_accounts, sbx_txns`. Money is stored as TEXT and serialised as decimal strings (`"18500.00"`).

2.7 Data flow: fee notice → payment

```
sequenceDiagram
  participant S as Student (browser)
  participant API as Fastify API
  participant G as Guardian + registry
  participant P as policy.decide
  participant F as Family approver
  participant B as Sandbox bank
  participant A as Audit chain
  S->>API: POST /documents (text)
  API->>API: parse fields, wrap in <untrusted>
  API->>G: scan text + compare payee/account to registry
  G-->>API: clean | suspicious | blocked (+ flags)
  API->>A: document.uploaded (+ guardian.blocked)
  S->>API: POST /documents/{id}/confirm (user-checked fields)
  API->>API: create obligation
  S->>API: POST /chat "Pay my spring tuition"
  API->>P: decide(payment)
  P-->>API: T3 REQUIRE_APPROVAL [totp, family_approver]
  S->>API: POST /actions/{id}/approve (student TOTP)
  F->>API: POST /actions/{id}/approve (approver TOTP)
  API->>P: decide again (execute time)
  P-->>API: ALLOW
  API->>B: transfer (idempotency key)
  B-->>API: settled
  API->>A: action.executed
```

---

3. Permission tiers T0–T4

Tier	Action	Conditions	Authorisation required
T0	Read: quotes, fee explanations, budget, dashboards	authenticated user, own data	none
T1	Draft: messages, payment drafts	nothing is sent or executed	none
T2	Payment ⩽ CNY 2,000	**verified** payee, trusted source, guardian clear, 24 h per-payee aggregate still ⩽ cap, no active cooling-off	student **TOTP**
T3	Payment > CNY 2,000; split payments exceeding the cap; any payment to a new/changed payee; verifying a payee	as above	student TOTP **+** linked family approver TOTP; **+ 24 h cooling-off** for new/changed payees

Tier	Action	Conditions	Authorisation required
T4	Blocked	unverified/unregistered payee; action sourced only from document, SMS or model text; guardian block (injection, homoglyph, amount mismatch, lookalike); payee of another user; amount ≠ confirmed obligation; bulk PII export; unknown action type	cannot be approved

- Admins have read-only oversight and **cannot approve payments**. A family approver can act only for students linked to them.
- **Payee lifecycle:** create (unverified → payments are T4) → verify by linked family approver / admin → payments are T3 until `cooling_off_until` (created + 24 h) passes → then T2/T3 by amount. Seeded institutions (university, dorm, insurance, provider) are verified with no cooling-off.
- **Decision reasons** are machine codes, e.g. `WITHIN_T2_CAP`, `OVER_T2_CAP`, `PAYEE_VERIFIED`, `PAYEE_UNVERIFIED`, `NEW_PAYEE`, `PAYEE_CHANGED`, `DOC_ONLY_SOURCE`, `INJECTION_DETECTED`, `BULK_PII_EXPORT`, `SPLIT_PAYMENT_SUSPECTED`, `AMOUNT_MISMATCH`.
- **Action lifecycle:** `draft` → `awaiting_approval` → (`cooling_off` →) `approved` → `executed` | `failed`; or `rejected` / `blocked` (T4, terminal).
- Configurable via env: `T2_CAP_CNY` (default `2000`), `COOLING_OFF_HOURS` (default `24`).

---

4. API overview

Base URL `http://localhost:8000`. Full request/response examples: `docs/API.md`.

Conventions

- Auth: `Authorization: Bearer <JWT>` from `/auth/login`. Roles: `student`, `family_approver`, `admin`.
- Money: decimal **strings** (`"18500.00"`), fields suffixed `_cny`; `bdt_needed` is BDT.
- Time: ISO-8601 UTC; dates `YYYY-MM-DD`. IDs are prefixed (`usr_`, `doc_`, `obl_`, `pay_`, `plan_`, `act_`, `trc_`).
- Every response carries `x-request-id`.
- Errors: `{"error": {"code", "message", "details"}, "request_id"}`. Cross-user resource access returns `NOT_FOUND` (no existence leak).

Endpoints (as registered in `server/src/app.ts` and `server/src/routes/`)

Method & path	Purpose	Notes
`GET /health`	Health and mode flags (`offline_mode`, `llm_provider`, `fx_mode`, `synthetic_data`)	public
`POST /auth/register`	Create account	argon2id
`POST /auth/login`	Email + password → HS256 JWT (`expires_in` 3600 s)	same error for unknown user and bad password
`POST /auth/totp/setup`	Start TOTP enrolment	secret encrypted at rest
`POST /auth/totp/verify`	Confirm TOTP enrolment	

Method & path	Purpose	Notes
`GET /me` · `DELETE /me`	Current user · erasure of own data	
`GET /dashboard`	Obligations, BDT needed, budget, deadlines, FX disclaimer	
`GET /obligations`	Confirmed obligations	owner-scoped
`GET /fx/quote?amount_cny=…&to=BDT`	Deterministic FX quote, labelled SAMPLE in fixture mode	`UNSUPPORTED_PAIR` (422) for unknown currencies
`POST /documents`	Upload fee-notice text (JSON `text` or `.txt` multipart) → parsed fields + guardian verdict	text marked `untrusted: true`; status `pending_confirmation` or `blocked`
`POST /documents/{id}/confirm`	Student confirms parsed fields → obligation	blocked docs cannot be confirmed; `AMOUNT_MISMATCH` (409)
`POST /chat`	Run the agent pipeline → `reply`, `proposed_actions[]`, `trace`	nothing executes from chat
`GET /actions` · `GET /actions/{id}`	List / read actions with decision, tier and approvals	
`POST /actions/{id}/approve`	Approve with TOTP (student or linked family approver)	policy re-run; `COOLING_OFF_ACTIVE`, `TOTP_INVALID`, `TOTP_LOCKED`, `ALREADY_APPROVED`
`POST /actions/{id}/reject`	Reject an action	
`GET /payees` · `POST /payees`	List / add payees (new payees are unverified)	account numbers masked
`POST /payees/{id}/verify`	Verify a payee (family approver / admin)	
`GET /audit?verify=true`	Audit rows + chain verification (`ok`, `broken_at_seq`)	
`GET /evidence/export`	Redacted audit export with `head_hash`	own data; admin: all, audit-logged
`GET /sandbox/account` · `GET /sandbox/transactions`	Sandbox ledger views	
`GET /demo/personas` · `GET /demo/notices` · `GET /demo/totp/{email}` · `POST /demo/tamper-audit?seq=N` · `POST /demo/reset`	Demo helpers	only when `DEMO_MODE=true` or valid `X-Admin-Token`; otherwise 404

Error codes in use: `UNAUTHORIZED` (401), `FORBIDDEN` (403), `NOT_FOUND` (404), `validation_error` (422), `UNSUPPORTED_DOCUMENT` (422), `UNSUPPORTED_PAIR` (422), `TOO_LARGE` (413), `TOTP_INVALID` (403), `TOTP_NOT_ENABLED` (403), `TOTP_NOT_STARTED` / `TOTP_ALREADY_ENABLED` (409), `TOTP_LOCKED` (429), `COOLING_OFF_ACTIVE` (409), `INVALID_STATE` (409), `ALREADY_APPROVED` / `ALREADY_CONFIRMED` (409), `AMOUNT_MISMATCH` (409), `EMAIL_EXISTS` (409), `POLICY_BLOCKED` (403), `RATE_LIMITED` (429).

The `trace` object (`POST /chat`): `steps[]` (`intake|planner|tools|guardian|policy|executor|validator`, each with `status`, `duration_ms`, `detail`), `tool_calls[]` (`{tool, args, output, ok}`), `tier`, `decision`, `reply_validated`, `audit_seqs`, `llm_mode`.

`ActionOut`: `{id, plan_id, type, tier, status, params, decision{outcome,tier,reasons,required,cooling_off_until,explanation}, approvals[], created_at, result}`; `type` ∈ `payment|draft_message|verify_payee|export_data|read`.

---

5. Security design

Method: data-flow decomposition → STRIDE per trust boundary → mapping to the OWASP Top 10 for LLM Applications (2025) and to China's PIPL / Data Security Law. Full analysis: `docs/THREAT_MODEL.md`, `docs/SECURITY_SELF_ASSESSMENT.md`.

5.1 Trust boundaries

1. Browser ↔ API (JWT, TOTP, rate limit).
2. Untrusted content (notice, SMS, chat text) ↔ agent (guardian, `<untrusted>`, schema-checked plans).
3. Agent ↔ policy engine ↔ executor (only `ALLOW` crosses).
4. API ↔ database (encryption, hash chain, redaction).
5. API ↔ optional third parties (live FX): off by default; public data only.

5.2 Controls

- **Authentication:** argon2id; JWT HS256 with algorithm pinned, `exp/sub/iat` required, role re-read from the database each request; TOTP (RFC 6238, ±1 step) with replay protection and 5-failure / 300 s lockout. Secret comparisons use `timingSafeEqual`.
- **Authorisation:** role checks; owner-scoped queries; cross-user ids return 404. Admins cannot approve payments; T3 requires a distinct, linked family approver.
- **Crypto at rest:** AES-256-GCM with AAD for payee accounts, TOTP secrets and uploaded text; keyed HMAC for lookups. The server refuses the dev default keys when `NODE_ENV=production`.
- **Untrusted documents:** size caps (413), NFKC normalisation, strict ASCII-digit account validation, confusable folding, homoglyph and lookalike-payee detection (skeleton / edit distance vs the verified registry), `<untrusted>` wrapping. Document-sourced actions are T4 regardless of the guardian verdict; payee and amount are always resolved server-side.
- **Agent safety:** allowlisted tools, strict schemas, no tool moves money, `propose_*` only creates action rows, reply validator for every number.
- **Anti-structuring:** a 24 h rolling per-payee aggregate escalates split payments past the T2 cap to T3.
- **Audit:** SHA-256 hash chain over canonical JSON, PII redacted before hashing; `GET /audit?verify=true` reports `broken_at_seq`; export includes `head_hash` (printed at seed and demo end) for external comparison.
- **Privacy:** PII-redacting structured logs (pino redaction paths + free-text masking hook for account numbers, emails, phones), `DELETE /me` erasure, no third-party scripts, offline by default.
- **Availability:** per-client-IP-and-path sliding-window rate limit (`RATE_LIMIT_PER_MINUTE`, default 120), request size caps, TOTP lockout.

- **Guardian robustness:** ReDoS tests run the guardian and intake regex functions on 100 KB adversarial strings with a 250 ms limit (`tests/security/redos.test.ts`).

5.3 STRIDE summary

Category	Threat	Mitigation	Scenario
Spoofing	Stolen password used to approve	TOTP on every approval, replay protection, lockout	A05, A06
Spoofing	Forged JWT (alg=none, role edit, expiry)	pinned HS256, required claims, role re-read from DB	A08
Spoofing	Fake payee via SMS, lookalike name, homoglyph digits	SMS never edits registry; T3 + 24 h cooling-off; lookalike / homoglyph block	A02, A03
Tampering	Edit / delete / re-link audit rows	SHA-256 chain, `broken_at_seq`	A09
Tampering	Amount changed between notice and payment	confirmed fields must match parse; policy compares action vs obligation	A11
Tampering / Elevation	Prompt injection in a notice	`<untrusted>`, guardian, document-sourced actions T4, server-side payee/amount	A01, A14
Repudiation	"I never approved that"	every approval audit-logged with actor and kind; two-person T3	A05, A09
Info disclosure	IDOR on actions/payees/documents	owner-scoped queries, 404 for foreign ids	A07, A12
Info disclosure	PII in logs / audit / DB	redaction, pre-hash redaction, AES-256-GCM, masking	A10
Info disclosure	Bulk export	bulk `EXPORT_DATA` is T4; export scoped to own data	A16
DoS	Flooding, credential stuffing, large uploads	rate limiter, size caps, TOTP lockout	A17, A06
Elevation	Executor reached without authorisation	executor refuses anything but `ALLOW`; allowlisted tools	A13, A14
Elevation	Structuring below CNY 2,000	24 h per-payee aggregate → T3	A04
Misinformation	Hallucinated numbers in replies	reply validator, safe fallback reply	A15

6. Deployment

6.1 Prerequisites

Node 20+ (`.nvmrc` : 20). No API keys or network access are needed. Every `make` target is a thin wrapper over `cd server && npm run …` .

6.2 Native (reference path used to produce the evidence)

```
make install          # npm ci (server) + npm install (web)
make api              # backend on http://localhost:8000 with DEMO_MODE=true
make web              # Next.js UI on http://localhost:3000
```

Without `make`:

```
cd server && npm ci && DEMO_MODE=true npm start          # API :8000
cd web && npm install && npm run dev                     # UI :3000
```

Production build of the server: `cd server && npm run build && node dist/main.js`.

6.3 Docker Compose

`docker-compose.yml`, `server/Dockerfile` (multi-stage `node:20-slim`, runs `node dist/main.js`, data at `/data`) and `web/Dockerfile` (Next.js standalone on `node:20-alpine`, non-root user) are provided:

```
docker compose up --build        # api :8000 (healthcheck on /health), web :3000, offline, no
        keys
```

Compose sets `ALLOW_OFFLINE=true`, `LLM_PROVIDER=scripted`, `FX_MODE=fixture`, `DEMO_MODE=true`, `CORS_ORIGINS=http://localhost:3000` and a named volume `setu-db` for SQLite. `NEXT_PUBLIC_API_URL` is inlined into the web build (the browser calls the API directly).

6.4 Configuration (`.env.example`, validated by Zod in `server/src/config.ts`)

Variable	Default	Purpose
`ALLOW_OFFLINE`	`true`	offline operation
`LLM_PROVIDER`	`scripted`	planner selection; this build runs the scripted planner
`FX_MODE`	`fixture`	`fixture` (labelled SAMPLE) or `live` (open.er-api.com, fixture fallback labelled)
`DEMO_MODE`	`false` in code (`true` in Compose / `make api`)	enables `/demo/*` helpers
`ADMIN_TOKEN`	unset	alternative gate for demo helpers via `X-Admin-Token`
`DATABASE_URL`	`sqlite:///./setu.db`	SQLite location
`JWT_SECRET`, `HMAC_KEY`, `AES_KEY_B64`	dev values	**replace for any non-demo deployment**; rejected when `NODE_ENV=production`
`CORS_ORIGINS`	`http://localhost:3000`	comma-separated allowed origins
`PORT`	`8000`	API port
`RATE_LIMIT_PER_MINUTE`	`120`	per client IP and path
`JWT_TTL_SECONDS`	`3600`	token lifetime
`T2_CAP_CNY` / `COOLING_OFF_HOURS`	`2000` / `24`	policy parameters
`TOTP_MAX_FAILURES` / `TOTP_LOCK_SECONDS`	`5` / `300`	lockout

6.5 Production checklist

- Set `NODE_ENV=production`, `DEMO_MODE=false`, and fresh `JWT_SECRET`, `HMAC_KEY`, `AES_KEY_B64`.

- Terminate TLS and add security headers at a reverse proxy; configure client-IP forwarding for the rate limiter.
- Restrict `CORS_ORIGINS` to the deployed web origin.
- Persist SQLite on a volume and back it up; publish the audit `head_hash` periodically.

6.6 Demo personas (SYNTHETIC; password `demo-password-123`)

Role	Email	Notes
Student	`aisha@demo.setu.test`	English UI, CNY 3,500/month, approver Mr. Rahman; spring tuition CNY 18,500 (`data/fee_notices/en_tuition_aisha.txt`)
Student	`rafi@demo.setu.test`	简体中文 UI, approver Mrs. Khan
Student	`nusrat@demo.setu.test`	English UI, approver Mr. Hossain
Family approver	`father.rahman@…`, `mother.khan@…`, `uncle.hossain@demo.setu.test`	approve T3 payments for their linked student only
Admin	`admin@demo.setu.test`	read-only oversight; cannot approve payments

With `DEMO_MODE=true`, `GET /demo/totp/{email}` returns the current 6-digit code so judges need no authenticator app. Replay protection means one user approves once per 30-second code window.

---

7. Testing and evidence

7.1 Commands

```
make lint        # eslint + tsc --noEmit
make test        # vitest: unit, pinned reference vectors, API, golden, security, parity
make demo        # scripted end-to-end scenario on an in-memory DB ->
        evidence/sandbox_logs.jsonl, audit_export.json, demo_summary.json
make evidence    # tests + demo + npm run evidence -> evidence/eval_report.md,
        security_report.md
make contract    # live status+shape diff, BASELINE vs CANDIDATE backend (both on fresh DBs)
make seed-data   # regenerate data/ deterministically (server/scripts/generate_data.ts)
```

CI: `.github/workflows/ci-ts.yml` runs `npm ci`, lint, typecheck, tests and build on Node 20 for every change under `server/`.

7.2 Server test suite (`server/tests/`, 22 files)

- `unit/` — policy, policy differential vectors, agent differential vectors, audit and audit store, crypto/tokenize, FX/costs/budget, ledger, reply validator, security (JWT/TOTP).
- `api/` — `fastify.inject()` tests for auth & payees, documents, chat, actions, audit/evidence/sandbox, seed.
- `golden/` — the 25 golden tasks from `server/eval/tasks.yaml`.
- `security/` — the 17 attack scenarios and ReDoS tests.
- `parity/` — replay of the recorded reference demo transcript.

Latest run (`npx vitest run`, 19 Oct 2026): **24 test files passed, 524 tests passed.**

7.3 Web tests

`web/`: `npm run lint`, `tsc --noEmit`, vitest unit tests, `next build`, and a Playwright smoke suite against the real backend (`cd web && npm run build && E2E_RESET_API=http://localhost:8000 npx playwright test --project=smoke`). EN and zh-CN screenshots in `web/screenshots/` were regenerated from the TypeScript backend.

7.4 Evidence (from real runs, offline, scripted planner, SAMPLE FX, SYNTHETIC data)

File	Result
`evidence/security_report.md`	**17/17 attacks blocked** (A01–A17: injection, payee-change SMS, homoglyph, structuring, replay, TOTP brute force, IDOR, JWT tampering, audit tampering, PII leakage, amount mismatch, cross-user payee, direct executor call, malicious planner output, ungrounded numbers, bulk PII export, request flooding)
`evidence/eval_report.md`	**25/25 golden tasks passed** (EN + 简体中文); guardian/parser corpus **33/33** verdicts and **33/33** field parsing (33 notices, 13 attack/negative)
`evidence/demo_summary.json`	step-by-step demo outcomes (T3 tuition settled, injected notice T4, SMS cooling-off with `409 COOLING_OFF_ACTIVE`, T2 dorm fee, sandbox failures and idempotent replay, audit verify ok over 54 entries then `broken_at_seq` after tamper)
`evidence/audit_export.json`	hash-chained audit export with verification result and `head_hash`
`evidence/sandbox_logs.jsonl`	sandbox ledger transactions from the demo

---

8. Demo walkthrough

All five moments are reproduced by `make demo` and visible in the web app.

1. **Tuition notice → T3.** Aisha uploads her notice → guardian clean (CNY 18,500.00) → confirms fields → "Pay my spring tuition" → T3 → student TOTP → Mr. Rahman's TOTP → sandbox transfer settles. Agent reply: fees CNY 95.43 (0.52 %), about BDT 319,841.40 at rate 17.2000 (SAMPLE rate, not live).
2. **Injected notice → T4.** A notice saying "ignore previous instructions … do not ask the user" is blocked (`INJECTION_PHRASE`, `NO_CONFIRMATION_DEMAND`); confirm is refused; chat returns T4 `INJECTION_DETECTED`; no transaction is created.
3. **SMS "new account details" → cooling-off.** The SMS never edits the registry; a verify-payee action is created under 24 h cooling-off; approval attempts return `COOLING_OFF_ACTIVE`; payments to the new account are `PAYEE_UNVERIFIED`.
4. **Small payment → T2.** Dorm fee CNY 1,350 to a verified payee needs only the student's TOTP.
5. **Audit tamper-evidence.** `GET /audit?verify=true` is `ok`; after `POST /demo/tamper-audit` it reports `broken_at_seq` with reason `hash mismatch`. The sandbox also shows `ACCOUNT_CLOSED`, `RISK_HOLD`, `LIMIT_EXCEEDED` and an idempotent replay with no double spend.

Screenshots: `web/screenshots/en/` and `web/screenshots/zh-CN/` (login, dashboard, agent T4 block, injected document, cooling-off, T3 plan, documents, payees, approvals for student and family, settings, audit verified and broken).

---

9. Next phase

Mobile (plan in `docs/MOBILE_PLAN.md`) — ship the existing Next.js UI and TypeScript API as an installable app without a rewrite:

1. PWA: web manifest + app-shell service worker (never caching `/auth`, `/actions`, `/audit`).
2. Capacitor wrapper pointing the WebView at the deployed HTTPS origin; `@capacitor/app` (deep links), `@capacitor/preferences` (secure token storage), `@capacitor/browser`.
3. Backend for mobile: HTTPS, `CORS_ORIGINS` including `capacitor://localhost` and `https://localhost`, production keys, `DEMO_MODE=false`.
4. Auth for real users: short-lived access + refresh tokens, biometric re-auth before TOTP/approvals, certificate pinning, root/jailbreak warning.
5. Push notifications for approvals (payloads carry no amounts or account data) after review.

Pilot readiness (from `docs/SECURITY_SELF_ASSESSMENT.md` §5): approver consent handshake and notifications; PIPL consent management and data-subject-request tooling; OCR with human confirmation of parsed fields; additional LLM planners behind a PIPL-compliant cross-border transfer mechanism, using the same allowlist and schema checks; KMS-managed keys with rotation; external audit anchoring (periodic `head_hash` publication); Redis-backed rate limiting; independent penetration test; integration with a real licensed payment partner.

---

10. Repository map

```
server/src/        Fastify app: routes/, domain/ (policy, fx, costs, budget, crypto,
tokenize, audit), agents/, sandboxBank/, evalkit/ (golden + attacks)
server/tests/      unit/, api/, golden/, security/, parity/ (vitest)
server/eval/       golden tasks (tasks.yaml)
server/scripts/    seed-data generator (generate_data.ts), live contract diff
data/              SYNTHETIC personas, 33 fee notices (EN/ZH/mixed, 13 attack/negative), 12
SMS, FX SAMPLE rates, channel costs
docs/              API, ARCHITECTURE, ARCHITECTURE_TS, DATA_FLOW, THREAT_MODEL,
SECURITY_SELF_ASSESSMENT, GLOSSARY_EN_ZH, MOBILE_PLAN
evidence/          generated reports and logs
web/               Next.js front end (EN / 简体中文), screenshots/, Playwright + vitest tests
```