

Nama : Sasmita Rachmawati

Absen : 15

Packet Tracer - Investigate Disaster Recovery

Objectives

Part 1: Review a Switch Configuration

Part 2: Backup Files to a TFTP Server

Part 3: Replace a Failed Switch

Part 4: Restore Network Operations

Background / Scenario

In this Packet Tracer (PT) activity, you will back up switch configuration files, replace a failed switch with a new switch, and then restore network operations by applying the backed up configuration from the failed switch to the new switch. The backup configuration files are saved to a Trivial File Transfer Protocol (TFTP) server. You are required to restore the saved files from the TFTP server to get the replacement switch online with as little down time as possible.

Note: The activity opens in the **Wiring Closet** for **HQ**. Although you can navigate out of the **Wiring Closet**, all tasks in this activity will occur inside the **Wiring Closet**. Switching to **Logical** mode is disabled.

Instructions

Part 1: Review a Switch Configuration

In this part, you will review and document the current configuration of the MDF-1 switch in the HQ Wiring Closet. This information will be necessary for manually configuring a replacement switch and verifying the new switch is operating as expected.

Step 1: Observe the contents of NVRAM.

- a. Click **MDF-1 > CLI** tab, and then press **Enter**.
- b. Enter the **enable** command, and then enter the **dir nvram** command to observe the contents of NVRAM.

Question:

What is the size of the startup-config file?

```
MDF-1>enable
MDF-1#dir nvram
Directory of nvram:/

 238  -rw-          2838          <no date>  startup-config

2838 bytes total (237588 bytes free)
```

MDF-1#

Step 2: Document the VLANs and other important configuration information.

- a. Enter the **show vlan** command.

Question:

What VLANs have been configured on MDF-1?

```
MDF-1#show vlan
```

VLAN	Name	Status	Ports
1	default	active	
10	Accounting	active	
20	Sales	active	
50	Common	active	
75	Servers	active	Fa0/1, Fa0/2
99	Admin	active	Fa0/3, Fa0/15
999	Unused	active	Fa0/4, Fa0/5, Fa0/6, Fa0/7 Fa0/8, Fa0/9, Fa0/10, Fa0/11 Fa0/12, Fa0/13, Fa0/14, Fa0/16 Fa0/17, Fa0/18, Fa0/23, Fa0/24 Gig0/2
1002	fdi-default	active	
1003	token-ring-default	active	
1004	fdinet-default	active	
1005	trnet-default	active	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
10	enet	100010	1500	-	-	-	-	-	0	0
20	enet	100020	1500	-	-	-	-	-	0	0
50	enet	100050	1500	-	-	-	-	-	0	0
75	enet	100075	1500	-	-	-	-	-	0	0
99	enet	100099	1500	-	-	-	-	-	0	0
999	enet	100999	1500	-	-	-	-	-	0	0
1002	fdi	101002	1500	-	-	-	-	-	0	0
1003	tr	101003	1500	-	-	-	-	-	0	0
1004	fdnet	101004	1500	-	-	-	ieee	-	0	0
1005	trnet	101005	1500	-	-	-	ibm	-	0	0

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
10	enet	100010	1500	-	-	-	-	-	0	0
20	enet	100020	1500	-	-	-	-	-	0	0
50	enet	100050	1500	-	-	-	-	-	0	0
75	enet	100075	1500	-	-	-	-	-	0	0
99	enet	100099	1500	-	-	-	-	-	0	0
999	enet	100999	1500	-	-	-	-	-	0	0
1002	fdi	101002	1500	-	-	-	-	-	0	0
1003	tr	101003	1500	-	-	-	-	-	0	0
1004	fdnet	101004	1500	-	-	-	ieee	-	0	0
1005	trnet	101005	1500	-	-	-	ibm	-	0	0

Remote SPAN VLANs

Primary	Secondary	Type	Ports

- b. Enter the **show run** command. Review the output to document the following information, which you will need to manually configure on a switch after a disaster.

```
interface GigabitEthernet0/1
  switchport trunk native vlan 99
  switchport mode trunk
!
interface GigabitEthernet0/2
  switchport access vlan 999
  switchport mode access
  shutdown
!
interface Vlan1
  no ip address
  shutdown
!
interface Vlan99
  ip address 192.168.99.150 255.255.255.0
!
ip default-gateway 192.168.99.1
```

Question:

Record the following settings in the following table:

MDF-1 Settings	Command Output
VLAN 99 IP Address	192.168.99.150
Default Gateway IP Address	192.168.99.1
VLAN Assignment of Interface F0/1	VLAN 75
Native LAN and Trunk Status of G0/1	VLAN 99

Part 2: Backup Files to a TFTP Server

In this part, you will copy the configuration files for the MDF-1 switch to the TFTP server. You will then verify that the files are listed on the TFTP server.

Step 1: Enable the TFTP service on the FTP server.

- In the **Wiring Closet**, on the right rack, click the **FTP** server > **Desktop** tab > **Command Prompt**.
- Enter the **ipconfig** command.

Question:

What is the IP address for the FTP server?


```
Cisco Packet Tracer SERVER Command Line 1.0
C:\>ipconfig

FastEthernet0 Connection:(default port)

    Connection-specific DNS Suffix...:
    Link-local IPv6 Address . . . . .: FE80::290:21FF:FE64:E9B9
    IPv6 Address . . . . .: ::
    IPv4 Address . . . . .: 192.168.75.2
    Subnet Mask . . . . .: 255.255.255.0
    Default Gateway . . . . .: ::
                                192.168.75.1

C:\>
```

- Click the **Services** tab, and then under **SERVICES**, click **TFTP**.
- Enable the TFTP service.



Step 2: Upload the vlan.dat and the startup-config files to the TFTP server.

- Click **MDF-1**, and then **CLI** tab, if necessary. If you were logged out, enter the **enable** command again.
- Enter **copy flash tftp** command and specify **vlan.dat** as the source filename. You documented the IP address in the previous step. Enter **MDF-1_vlan.dat** for the destination filename.

Question:

Record the command below:

```
MDF-1#copy flash tftp
Source filename []? vlan.dat
Address or name of remote host []? 192.168.75.2
Destination filename [vlan.dat]? MDF-1_vlan.dat
```

```
Writing vlan.dat.....!!
[OK - 916 bytes]
```

```
916 bytes copied in 7.011 secs (130 bytes/sec)
MDF-1#
```

- Enter the **copy startup-config tftp** command to copy the configuration to the TFTP server. You documented the IP address in the previous step. Enter **MDF-1_startup-config** as the destination filename.

Question:

Record the command below:


```
916 bytes copied in 7.011 secs (130 bytes/sec)
MDF-1#copy startup-config tftp
Address or name of remote host []? 192.168.75.2
Destination filename [MDF-1-config]? MDF-1_startup-config
```

```
Writing startup-config...!!
[OK - 3012 bytes]
```

```
3012 bytes copied in 0.01 secs (301200 bytes/sec)
MDF-1#
```

Step 3: Verify that the files are on the TFTP server.

Click **FTP** server. Under **TFTP** in **SERVICES**, verify the two files are listed in the **File** section. If necessary, refresh the File list by clicking another service and then clicking the TFTP service again.



Part 3: Replace a Failed Switch

Assume that the **MDF-1** switch has failed. This could be from a power surge, a corrupted chip, or some other environmental hazard or hardware failure. In this Part, you will install a replacement switch and move the cable connections from the failed switch to the new switch.

Step 1: Add a new switch to the network.

- On the **Table** in the **Wiring Closet**, locate **spare-switch_01**.
- Click and drag it to the rack below **HQ-WLC-1**.
- Click **spare-switch_01** > **CLI** tab, and then press **Enter**.
- Enter the following commands to deactivate all the interfaces.

enable

configure terminal

interface range f0/1 - 23, g0/1 - 2

shutdown

exit

```
spare-switch_01#enable
spare-switch_01#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
spare-switch_01(config)#interface range fa0/1 - 23, g0/1 - 2
spare-switch_01(config-if-range)#shutdown

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/4, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/5, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/6, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/7, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/8, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/9, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/10, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/11, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/12, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/13, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/14, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/15, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/16, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/17, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/18, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/19, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/20, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/21, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/22, changed state to administratively down
%LINK-5-CHANGED: Interface FastEthernet0/23, changed state to administratively down
%LINK-5-CHANGED: Interface GigabitEthernet0/1, changed state to administratively down
%LINK-5-CHANGED: Interface GigabitEthernet0/2, changed state to administratively down
spare-switch_01(config-if-range)#exit
spare-switch_01(config)#
```

Step 2: Move the cable connections from the MDF-1 switch to new switch.

- On the top toolbar, click **Zoom In** several times until you can easily see the cable connections for both **MDF-1** and **spare-switch_01**.


Alternatively, you can right click each switch and choose **Inspect Front**. But you will need to do this each time you move a connection from **MDF-1** to **spare-switch_01**.

- Click and drag a cable connection from **MDF-1** to the same port number on **spare-switch_01**. Repeat until all cables are moved from **MDF-1** to **spare-switch_01**.

- c. To verify cables are in the correct ports, right click **spare-switch_01** and choose **Inspect Front**. Zoom in and then float your mouse over each cable, wait for the information popup, and then make sure the cable connections map to this table.

MDF-1 Interface Port	Connected Device
F0/1	FTP Server
F0/2	MAIL Server
F0/3	AAA-RADIUS Server
F0/15	Net-Admin PC
F0/19	FL-1 F0/19
F0/20	FL-1 F0/20
F0/21	FL-2 F0/21
F0/22	FL-2 F0/22
G0/1	HQ Edge Router

- d. Right click the **Rack** and choose **Manage All Cables on Rack**.
- e. Uninstall **MDF-1** from the **Rack**. Click and drag it to the **Table**.
- f. On the top toolbar, click **Zoom Reset**.



Part 4: Restore Network Operations

In this Part, you will manually configure the new switch so that it can access the TFTP server. You will then copy the configuration files from the TFTP server to the new switch and verify the switch is operating as expected.

Step 1: Configure spare-switch_01 to access the network.

To access the TFTP server over the network, the spare switch will need network information configured manually. Enter the following configuration into **spare-switch_01** to connect it to the network and prepare it for TFTP server access.

```
vlan 99
```

```
name Admin
```

```
exit
```

```
interface vlan 99
```

```
ip address 192.168.99.150 255.255.255.0
```

```
exit
```

```
ip default-gateway 192.168.99.1
```

```
interface fa0/1
```

```
switchport mode access
```

```
switchport access vlan 75
```

```
no shutdown
```

```
interface g0/1
```

```
switchport mode trunk
```

```
switchport trunk native vlan 99
```

```
no shutdown
```

```
end
```

```
spare-switch_01(config)#vlan 75
spare-switch_01(config-vlan)#name User_VLAN
spare-switch_01(config-vlan)#exit
spare-switch_01(config)#vlan 99
spare-switch_01(config-vlan)#name Admin
spare-switch_01(config-vlan)#exit
```

```
spare-switch_01(config)#interface vlan 99
spare-switch_01(config-if)#ip address 192.168.99.150 255.255.255.0
spare-switch_01(config-if)#exit
spare-switch_01(config)#ip default-gateway 192.168.99.1
spare-switch_01(config)#interface fa0/1
spare-switch_01(config-if)#switchport mode access
spare-switch_01(config-if)#switchport access vlan 75
spare-switch_01(config-if)#no shutdown
```

```
spare-switch_01(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
```

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
```

```
spare-switch_01(config-if)#interface g0/1
spare-switch_01(config-if)#switchport mode trunk
```

```
spare-switch_01(config-if)#switchport trunk native vlan 99
spare-switch_01(config-if)#no shutdown

spare-switch_01(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan99, changed state to up

spare-switch_01(config-if)#end
spare-switch_01#
%SYS-5-CONFIG_I: Configured from console by console
```

Step 2: Test connectivity to the TFTP server.

Enter **ping 192.168.75.2** to verify **spare-switch_01** can access the TFTP server.

```
spare-switch_01#ping 192.168.75.2

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.75.2, timeout is 2 seconds:
..!!!
Success rate is 60 percent (3/5), round-trip min/avg/max = 0/0/2 ms
```

Step 3: Download the vlan.dat and startup-config files from the TFTP server.

a. Enter the **copy tftp flash** command. Specify the IP address of the TFTP server. The source filename is **MDF-1_vlan.dat**. The destination filename MUST be **vlan.dat**. Confirm you want to overwrite the current vlan.dat file.

Question:

Record the command below:

```
spare-switch_01#copy tftp flash
Address or name of remote host []? 192.168.75.2
Source filename []? MDF-1_vlan.dat
Destination filename [MDF-1_vlan.dat]? vlan.dat
%Warning:There is a file already existing with this name
Do you want to over write? [confirm]
```

```
Accessing tftp://192.168.75.2/MDF-1_vlan.dat...
Loading MDF-1_vlan.dat from 192.168.75.2: !
[OK - 916 bytes]
```

```
916 bytes copied in 0 secs
spare-switch_01#
```

b. Enter the **dir flash** command to verify the **vlan.dat** file is in the directory.

Question:

Record the command below:


```

spare-switch_01#dir flash
Directory of flash:/

   1  -rw-     4670455      <no date>  2960-lanbasek9-mz.150-2.SE4.bin
   4  -rw-         1089      <no date>  config.text
   5  -rw-         916      <no date>  vlan.dat

64016384 bytes total (59343924 bytes free)
spare-switch_01#

```

- c. Enter the **copy tftp startup-config** command. Specify the IP address of the TFTP server. The source filename is **MDF-1_startup-config**. The destination filename **MUST** be **startup-config**.

Question:

Record the command below:

```

spare-switch_01#copy tftp startup-config
Address or name of remote host []? 192.168.75.2
Source filename []? MDF-1_startup-config
Destination filename [startup-config]? startup-config

Accessing tftp://192.168.75.2/MDF-1_startup-config...
Loading MDF-1_startup-config from 192.168.75.2: !
[OK - 3012 bytes]

3012 bytes copied in 0 secs
spare-switch_01#

```

- d. Enter the **dir nvram** command to verify the startup-config file is now in NVRAM.

Question:

Record the command below:

```

spare-switch_01#dir nvram
Directory of nvram:/

   238  -rw-         2838      <no date>  startup-config

2838 bytes total (237588 bytes free)

spare-switch_01#

```

What is the size of the startup-config file? **2838**

Is this the same size as the startup-config recorded in Part 1, Step 1? **Same**

Step 4: Reload and verify the new switch now has the correct configuration.

- a. Enter the **reload** command. The startup-config file will be copied into RAM and become the running configuration.

Important: Answer **no** to the prompt, **System configuration has been modified. Save?**, and then press **Enter** to confirm reload.

Question:

Record the command below:

```
spare-switch_01#reload
System configuration has been modified. Save? [yes/no]:no
Proceed with reload? [confirm]
C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)FX, RELEASE SOFTWARE (fc4)
Cisco WS-C2960-24TT (RC32300) processor (revision C0) with 21039K bytes of memory.
2960-24TT starting...
Base ethernet MAC Address: 0030.A327.7520
Xmodem file system is available.
Initializing Flash...
flashfs[0]: 3 files, 0 directories
flashfs[0]: 0 orphaned files, 0 orphaned directories
flashfs[0]: Total bytes: 64016384
flashfs[0]: Bytes used: 4674383
flashfs[0]: Bytes available: 59342001
flashfs[0]: flashfs fsck took 1 seconds.
...done Initializing Flash.
```

```
Boot Sector Filesystem (bs:) installed, fsid: 3
Parameter Block Filesystem (pb:) installed, fsid: 4
```

```
Loading "flash:/2960-lanbasek9-mz.150-2.SE4.bin"...
##### [OK]
Smart Init is enabled
smart init is sizing iomem
      TYPE      MEMORY_REQ
TOTAL:      0x00000000
Rounded IOMEM up to: 0Mb.
Using 6 percent iomem. [0Mb/512Mb]
```

Restricted Rights Legend
Use, duplication, or disclosure by the Government is
subject to restrictions as set forth in subparagraph
(c) of the Commercial Computer Software - Restricted
Rights clause at FAR sec. 52.227-19 and subparagraph
(c) (1) (ii) of the Rights in Technical Data and Computer
Software clause at DFARS sec. 252.227-7013.
cisco Systems, Inc.
170 West Tasman Drive

```
San Jose, California 95134-1706
Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE
(fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnnguyen
Initializing flashfs...
fsck: Disable shadow buffering due to heap fragmentation.
flashfs[2]: 2 files, 1 directories
flashfs[2]: 0 orphaned files, 0 orphaned directories
flashfs[2]: Total bytes: 32514048
flashfs[2]: Bytes used: 11952128
flashfs[2]: Bytes available: 20561920
flashfs[2]: flashfs fsck took 2 seconds.
flashfs[2]: Initialization complete....done Initializing flashfs.
Checking for Bootloader upgrade..
Boot Loader upgrade not required (Stage 2)
POST: CPU MIC register Tests : Begin
POST: CPU MIC register Tests : End, Status Passed
POST: PortASIC Memory Tests : Begin
POST: PortASIC Memory Tests : End, Status Passed
POST: CPU MIC interface Loopback Tests : Begin
POST: CPU MIC interface Loopback Tests : End, Status Passed
POST: PortASIC RingLoopback Tests : Begin
POST: PortASIC RingLoopback Tests : End, Status Passed
POST: PortASIC CAM Subsystem Tests : Begin
POST: PortASIC CAM Subsystem Tests : End, Status Passed
POST: PortASIC Port Loopback Tests : Begin
POST: PortASIC Port Loopback Tests : End, Status Passed
Waiting for Port download...Complete
```

This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product you agree to comply with applicable laws and regulations. If you are unable to comply with U.S. and local laws, return this product immediately. A summary of U.S. laws governing Cisco cryptographic products may be found at:

```

http://www.cisco.com/wwl/export/crypto/tool/stqrg.html
If you require further assistance please contact us by sending email to
export@cisco.com.
cisco WS-C2960-24TT-L (PowerPC405) processor (revision B0) with 65536K bytes of memory.
Processor board ID FOC1010X104
Last reset from power-on
1 Virtual Ethernet interface
24 FastEthernet interfaces
2 Gigabit Ethernet interfaces
The password-recovery mechanism is enabled.
64K bytes of flash-simulated non-volatile configuration memory.
Base ethernet MAC Address      : 00:30:A3:27:75:20
Motherboard assembly number    : 73-10390-03
Power supply part number      : 341-0097-02
Motherboard serial number     : FOC10093R12
Power supply serial number    : AZS1007032H
Model revision number         : B0
Motherboard revision number   : B0
Model number                  : WS-C2960-24TT-L
System serial number          : FOC1010X104
Top Assembly Part Number      : 800-27221-02
Top Assembly Revision Number  : A0
Version ID                   : V02
CLEI Code Number              : COM3L00BRA
Hardware Board Revision Number : 0x01

Switch Ports Model          SW Version        SW Image
-----
* 1 26 WS-C2960-24TT-L 15.0(2)SE4       C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE
(fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnnguyen

Press RETURN to get started!

```

- b. After the switch reloads, review the configuration.
 - o The hostname is now be **MDF-1**.
 - o Enter the **show vlan** command and verify VLANs you documented in Part 1, Step 2 are listed.

```

MDF-1>show vlan

VLAN Name                Status    Ports
-----
1    default                active    Fa0/1, Fa0/2
10   Accounting              active    Fa0/3, Fa0/15
20   Sales                   active    Fa0/4, Fa0/5, Fa0/6, Fa0/7
50   Common                  active    Fa0/8, Fa0/9, Fa0/10, Fa0/11
75   Servers                  active    Fa0/12, Fa0/13, Fa0/14, Fa0/16
99   Admin                    active    Fa0/17, Fa0/18, Fa0/23, Fa0/24
999  Unused                   active    Gig0/2

1002 fddi-default          active
1003 token-ring-default    active
1004 fddinet-default        active
1005 trnet-default          active

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp    BrdgMode Trans1 Trans2
-----
1    enet  100001    1500    -      -      -      -      -      0      0
10   enet  100010    1500    -      -      -      -      -      0      0
20   enet  100020    1500    -      -      -      -      -      0      0
50   enet  100050    1500    -      -      -      -      -      0      0
75   enet  100075    1500    -      -      -      -      -      0      0
99   enet  100099    1500    -      -      -      -      -      0      0
999  enet  100999    1500    -      -      -      -      -      0      0
1002 fddi  101002    1500    -      -      -      -      -      0      0
1003 tr   101003    1500    -      -      -      -      -      0      0
1004 fdnet 101004    1500    -      -      -      ieee  -      0      0
1005 trnet 101005    1500    -      -      -      ibm   -      0      0

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp    BrdgMode Trans1 Trans2
-----

Remote SPAN VLANs
-----

Primary Secondary Type      Ports
-----
MDF-1>

```

- o Enter the **show ip interface brief** command. Verify that your connected physical ports are now all up.

MDF-1>show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
Port-channel1	unassigned	YES	manual	up	up
Port-channel2	unassigned	YES	manual	up	up
FastEthernet0/1	unassigned	YES	manual	up	up
FastEthernet0/2	unassigned	YES	manual	up	up
FastEthernet0/3	unassigned	YES	manual	up	up
FastEthernet0/4	unassigned	YES	manual	administratively down	down
FastEthernet0/5	unassigned	YES	manual	administratively down	down
FastEthernet0/6	unassigned	YES	manual	administratively down	down
FastEthernet0/7	unassigned	YES	manual	administratively down	down
FastEthernet0/8	unassigned	YES	manual	administratively down	down
FastEthernet0/9	unassigned	YES	manual	administratively down	down
FastEthernet0/10	unassigned	YES	manual	administratively down	down
FastEthernet0/11	unassigned	YES	manual	administratively down	down
FastEthernet0/12	unassigned	YES	manual	administratively down	down
FastEthernet0/13	unassigned	YES	manual	administratively down	down
FastEthernet0/14	unassigned	YES	manual	administratively down	down
FastEthernet0/15	unassigned	YES	manual	up	up
FastEthernet0/16	unassigned	YES	manual	administratively down	down
FastEthernet0/17	unassigned	YES	manual	administratively down	down
FastEthernet0/18	unassigned	YES	manual	administratively down	down
FastEthernet0/19	unassigned	YES	manual	up	up
FastEthernet0/20	unassigned	YES	manual	up	up
FastEthernet0/21	unassigned	YES	manual	up	up
FastEthernet0/22	unassigned	YES	manual	up	up
FastEthernet0/23	unassigned	YES	manual	administratively down	down
FastEthernet0/24	unassigned	YES	manual	administratively down	down
GigabitEthernet0/1	unassigned	YES	manual	up	up
GigabitEthernet0/2	unassigned	YES	manual	administratively down	down
Vlan1	unassigned	YES	manual	administratively down	down
Vlan99	192.168.99.150	YES	manual	up	up

MDF-1>