

DETAILED PAINT SPECIFICATION

Detailed Paint Specification

This specification has been prepared following inspection of the project and outlines the recommended preparation procedures, coating systems and estimated material requirements for the surfaces included within this quotation. All recommendations are based on the recorded site conditions at the time of inspection.

PROJECT

121

CUSTOMER

**Mohammed Zulfikar
Ismail**

REFERENCE

PSP-Q-000042

PREPARED BY

Mohammed test

DATE

07 September 2026

SECTIONS

4

Project Overview

A professional specification for quality, durability and long-lasting results.

PROJECT

121

CUSTOMER

**Mohammed
Zulfikar Ismail**

QUOTATION REFERENCE

PSP-Q-000042

PREPARED BY

Mohammed test

DATE

07 September 2026

SPECIFICATION SECTIONS

4

Purpose

The purpose of this specification is to provide a structured coating recommendation for each inspected surface included within this quotation. The document should be used together with the official quotation and manufacturer product data sheets.

General Application Notes

- Ensure all surfaces are clean, dry and free from contaminants before coating.
- Moisture levels should fall within manufacturer recommendations before application.
- All preparation work should be completed before primers or finish coats are applied.
- Observe all manufacturer drying and recoat times. Application should only be carried out under suitable environmental conditions.

1

ITEM 1 : Interior Walls

INTERIOR · INTERIOR_WALLS



Preparation Requirements

Clean

Application Requirements

The substrate is Previously painted – good condition. Apply 1 coat of TEST Waterproofing with a brush and roller and allow to dry for approximately 2-4 hours before proceeding. Apply 1 coat of TEST Primer with a brush and roller and allow to dry for approximately 2-4 hours before proceeding. Apply 2 coats of TEST Interior Smooth Matte with a brush and roller and allow to dry for approximately 2-4 hours before proceeding.

Coating System

Coating System	Technical Data Sheet	Spread Rate (m ² /L)	DFT (µm)	Application Methods
Coat 1: TEST Waterproofing	TEST-TDS-011	10.00	80–120	Brush,Roller
Coat 2: TEST Primer	TEST-TDS-010	10.00	80–120	Brush,Roller
Coat 3: TEST Interior Smooth Matte	TEST-TDS-001	10.00	80–120	Brush,Roller
Coat 4: TEST Interior Smooth Matte	TEST-TDS-001	10.00	80–120	Brush,Roller

Surface / Product

Item No.	Surface Type	Substrate	Product	Coverage per 20L	Coverage (m ² /L)	Colour	Pack Size	Unit Price (excl. VAT)	Paint cost per m ² (excl. VAT)
1	Interior Walls	Brick	TEST Waterproofing	200.00	10.00	—	1L	R 100.00	R 10.00
1	Interior Walls	Brick	TEST Primer	200.00	10.00	—	1L	R 100.00	R 10.00
1	Interior Walls	Brick	TEST Interior Smooth Matte	200.00	10.00	White	1L	R 100.00	R 20.00

2

ITEM 2 : Interior Walls

2

INTERIOR · INTERIOR_WALLS



Preparation Requirements

Inspect existing coating. Allow surfaces to dry; re-check moisture before painting.

Application Requirements

The substrate is Previously painted – good condition. Apply 2 coats of TEST Interior Smooth Sheen with a brush and roller and allow to dry for approximately 2-4 hours before proceeding.

Coating System

Coating System	Technical Data Sheet	Spread Rate (m ² /L)	DFT (µm)	Application Methods
Coat 1: TEST Interior Smooth Sheen	TEST-TDS-002	10.01	80–120	Brush,Roller
Coat 2: TEST Interior Smooth Sheen	TEST-TDS-002	10.01	80–120	Brush,Roller

Surface / Product

Item No.	Surface Type	Substrate	Product	Coverage per 20L	Coverage (m ² /L)	Colour	Pack Size	Unit Price (excl. VAT)	Paint cost per m ² (excl. VAT)
2	Interior Walls 2	Drywall / Plasterboard	TEST Interior Smooth Sheen	200.20	10.01	White	1L	R 100.00	R 20.00

3 ITEM 3 : Floors

INTERIOR · FLOORS



Preparation Requirements

Inspect existing coating. Allow surfaces to dry; re-check moisture before painting.

Application Requirements

The substrate is Previously painted – good condition. Apply 1 coat of TEST Waterproofing with a brush and roller and allow to dry for approximately 2-4 hours before proceeding. Apply 1 coat of TEST Interior Smooth Matte with a brush and roller and allow to dry for approximately 2-4 hours before proceeding.

Coating System

Coating System	Technical Data Sheet	Spread Rate (m ² /L)	DFT (µm)	Application Methods
Coat 1: TEST Waterproofing	TEST-TDS-011	10.00	80–120	Brush,Roller
Coat 2: TEST Interior Smooth Matte	TEST-TDS-001	10.00	80–120	Brush,Roller

Surface / Product

Item No.	Surface Type	Substrate	Product	Coverage per 20L	Coverage (m ² /L)	Colour	Pack Size	Unit Price (excl. VAT)	Paint cost per m ² (excl. VAT)
3	Floors	Concrete	TEST Waterproofing	200.00	10.00	—	1L	R 100.00	R 10.00
3	Floors	Concrete	TEST Interior Smooth Matte	200.00	10.00	White	1L	R 100.00	R 10.00

4

ITEM 4 : Floors**2**

INTERIOR · FLOORS

Preparation Requirements

Inspect existing coating. Allow surfaces to dry; re-check moisture before painting.

Application Requirements

The substrate is Previously painted – poor condition. Apply 1 coat of TEST Interior Smooth Matte with a brush and roller and allow to dry for approximately 2-4 hours before proceeding.

Coating System

Coating System	Technical Data Sheet	Spread Rate (m ² /L)	DFT (µm)	Application Methods
Coat 1: TEST Interior Smooth Matte	TEST-TDS-001	10.00	80–120	Brush,Roller

Surface / Product

Item No.	Surface Type	Substrate	Product	Coverage per 20L	Coverage (m ² /L)	Colour	Pack Size	Unit Price (excl. VAT)	Paint cost per m ² (excl. VAT)
4	Floors 2	Soft wood	TEST Interior Smooth Matte	200.00	10.00	White	1L	R 100.00	R 10.00

Project Pricing Summary

Subtotal (excl. VAT)	R 2800.00
VAT	R 420.00
Grand Total	R 3220.00

Important Notes

Material quantities are estimates based on the recorded surface areas and selected coating systems. Actual consumption may vary depending on substrate porosity, application method and site conditions.

This specification should be read together with the official quotation and any manufacturer technical data sheets supplied with the selected coating products.

PREPARED BY

Mohammed test

COMPANY DETAILS

ProStar Paints

QUOTATION

PSP-Q-000042

Generated 07 September 2026