Training–Rollout Mismatch in Low-Precision LLM Reinforcement Learning: A Survey

Zunhai Su
The University of Hong Kong

Abstract: Quantized rollouts can lower the cost of language-model reinforcement learning while changing the policy that generates training experience. Mismatch with the learner can then alter gradient estimates, clipping decisions, and later trajectories. This focused qualitative survey synthesizes twenty-nine studies through a policy formulation that separates numerical execution, decoding, and staleness, while distinguishing conditional correction from response-level change of measure. It organizes interventions by their direct targets: shared computation, numerical fidelity, gradient estimation, update influence, and optimization schedules. Three relationships recur in the reviewed evidence: correction and mismatch evolve together; alignment gains depend on the computation actually shared; and signed update contributions expose effects hidden by average discrepancy. These relationships explain why numerical design and learning correction can be complementary, and why agreement or throughput alone does not establish efficient learning. We connect these mechanisms to information requirements, learning outcomes, and system costs, and identify open problems in diagnosis, composition, and stateful collection.

Keywords: quantized rollout; low-precision reinforcement learning; training–inference mismatch; importance sampling; quantization-aware training.

Literature snapshot: October 20, 2026.

Survey resources: https://github.com/ZunhaiSu/awesome-low-precision-rl

Living survey, under active development. Suggestions, corrections, and research collaborations are welcome via GitHub Issues.




Figure 1: Survey at a glance. Numerical methods act on learner or sampler execution; learning methods change how samples drive updates. Their effects return through the rollout–learning loop. W, A, and KV denote weights, activations, and key–value cache.

Contents

1 Introduction and Scope **4**

1.1 Why Low-Precision Rollouts Complicate Policy Optimization 4

1.2 Scope and Related Work 4

1.3 Perspective and Contributions 5

2 Problem Formulation and Taxonomy **6**

2.1 Learner, Behavior, Proximal, and Reference Policies 6

2.2 Execution Mismatch versus Policy Staleness 6

2.3 A Component-Level Taxonomy of Interventions 9

2.4 Numerical Regimes and Contribution Roles 9

3 Mechanisms: From Numerical Discrepancy to Learning Dynamics **9**

3.1 Sources and Propagation of Execution Discrepancy 9

3.2 Distorted Estimation and Update Decisions 10

3.3 Feedback across Optimization Steps 11

3.4 Diagnosing the Effects of Mismatch 12

4 Numerical Design and Execution Alignment **13**

4.1 Aligning Learner and Rollout Computation 13

4.2 Controlling Quantization Error and Preserving Parameter Updates 14

4.3 Residual Mismatch and Limits of Alignment 15

5 Learning under Residual Mismatch **16**

5.1 Correcting Gradient Estimation 16

5.2 Controlling the Influence of Policy Updates 17

5.3 Adapting the Optimization Schedule 18

5.4 Compatibility, Bias, and Failure Modes 19

6 Synthesis of Findings and Practical Trade-offs **19**

6.1 Experimental Regimes 20

6.2 Findings on Stability and Learning Quality 20

6.3 Efficiency Gains and Implementation Costs 23

6.4 Evidence Limits and Coverage Gaps 24

7 Open Problems **25**

7.1 Predicting Harmful Mismatch 25

7.2 Composing Numerical and Learning Interventions 25

7.3 Precision, Staleness, and Long-Horizon Interaction 25

7.4 Generalization and Comparable Evidence 26

8 Conclusion **26**

A Surveyed Papers and Section Mapping **27**

B Source Selection and Version Handling **29**

C Evidence, Assumptions, and Transfer **29**

D Terminology **30**

Reading pathways

Foundations	Methods	Evidence
Policy roles, execution mismatch, and its effects on learning.	Numerical interfaces, estimator correction, and update control.	Within-study findings, system costs, and open problems.
Sections 2–3	Sections 4–5	Sections 6–7

Appendix A: surveyed papers · Appendices B–C: sources and assumptions · Appendix D: terminology

1. Introduction and Scope

1.1. Why Low-Precision Rollouts Complicate Policy Optimization

In language-model reinforcement learning, generation determines the responses, rewards, and histories from which the next policy is learned. Quantizing the rollout engine changes this source of training data as well as its computational cost. A local numerical difference can alter a sampled token, the learning signal assigned to a response, and the parameter update that shapes later generation. The resulting training–rollout mismatch is a low-precision instance of training–inference mismatch (TIM), with consequences that extend beyond the accuracy of a single forward pass.

The practical objective is to learn a capable policy within a finite computational budget. Faster generation contributes to that objective through the quality of the data it supplies and the updates those data support. Numerical agreement, optimization stability, task performance, and runtime capture different parts of this relationship. Aggressive clipping, for example, can stabilize training while discarding useful signal; a more faithful sampler can preserve that signal while reducing the throughput gained from quantization. Their value depends on how efficiently the complete learning process improves the policy.

Existing methods intervene at different points in this process. FlashRL uses actual rollout probabilities to correct learning from a different sampling policy; Jet-RL coordinates learner and sampler precision flow; subsequent studies act on quantization, clipping, gradient estimation, and local update dynamics [1, 3]. These interventions often coexist within one system. Numerical components act on learner or sampler computation, including the interface between them; learning-side rules determine how the resulting samples influence the next policy. Component-level classification preserves these distinct roles within integrated systems.

Figure 2 organizes these components by the computation or update they change. Cross-category assignments preserve the distinct contributions of integrated methods; Appendix A summarizes the corresponding papers.

1.2. Scope and Related Work

This survey focuses on numerical and execution mismatch in LLM reinforcement learning, especially quantized rollout and related low-precision training configurations. It covers a higher-precision learner paired with a lower-precision sampler, as well as low precision on both sides. Weight, activation, and key–value (KV) cache quantization affect different computational interfaces. Policy staleness enters where parameter changes interact with those interfaces.

The twenty-nine focal contributions comprise nineteen method or system studies, nine formulation or general mismatch studies, and one exploration boundary case. These roles describe their use in the synthesis: MiniRL, for example, develops the formulation and also evaluates FP8 rollout [14]. The literature snapshot is October 20, 2026. Appendix B describes source selection and version handling.

Broader surveys address low-precision LLM training, rollout strategies, and reinforcement learning for reasoning models [33–35]. The distinctive concern here is the connection between actual sampling probabilities, numerical execution, and the update computed from sampled data. General post-training quantization, pretraining-only methods, and speculative-draft acceleration enter only where they clarify that connection.




Figure 2: Taxonomy of the surveyed work. Branches identify what each component directly changes; repeated names reveal cross-category contributions. All nineteen core studies, nine supporting studies, and the exploration boundary case are shown. Numerical configurations remain separate comparison axes. Appendix A gives the paper-by-paper summary and discussion locations.

The collection supports a focused qualitative synthesis of primary studies. Numerical format, architecture, adaptation, and collection protocol remain separate comparison axes. Table 5 summarizes the represented regimes; Appendix D defines recurring abbreviations.

1.3. Perspective and Contributions

Numerical fidelity and learning correction are coupled. A more faithful sampler changes the errors a correction encounters, while the update rule determines which errors affect learning. Their joint

design determines which sample contributions reach the parameter update and the computation needed to preserve them.

We develop this perspective by connecting policy definitions, failure mechanisms, and method components. The formulation in Section 2 identifies which distribution each probability ratio refers to; Section 3 traces discrepancies through estimation and optimization. This foundation supports the comparison of numerical and learning interventions in Sections 4–5. Their shared dependencies explain the published findings and practical trade-offs synthesized in Section 6, from which the open problems in Section 7 follow.

2. Problem Formulation and Taxonomy

2.1. Learner, Behavior, Proximal, and Reference Policies

Let x be a prompt, $y_{1:T}$ a response, and $h_t = (x, y_{<t})$ its prefix. A policy is specified by both a parameter state and the computation used to evaluate it. Write $p_\theta(a \mid h)$ for the current learner policy and $p_k(a \mid h)$ for the same learner-side path at sampling snapshot θ_k.

The behavior policy $q_k(a \mid h)$ is the distribution that actually sampled the token. It includes the rollout engine, numerical representation, and sampling transformation. Temperature and vocabulary truncation therefore belong to its definition: a raw-model log-probability returned by an engine need not equal the probability after decoding transformations.

The collection protocol is part of the behavior law. Under deterministic execution and version schedules, the generated history determines the sampler state, including cache entries computed under earlier parameter versions. The subscript k abbreviates that rollout path. Cache provenance identifies the parameter versions and numerical paths that produced retained cache entries; a checkpoint identifier alone cannot specify this state.

A proximal policy p_{prox} supplies the denominator of a policy-update constraint. A reference policy p_{ref} supplies a regularization target. These are different roles: a frozen pre-update learner may be proximal, while a much earlier policy is the KL reference. Neither is automatically the policy that generated every token. PPO and GRPO provide familiar contexts for these distinctions [30, 31]; mismatch-aware formulations require them to remain explicit [1, 14].

Policy identity also determines the object whose improvement matters after synchronization. MIPU explicitly distinguishes improving the learner from improving the resulting inference policy [23]. This distinction becomes consequential when conversion and rollout execution change the distribution realized by an accepted update.

2.2. Execution Mismatch versus Policy Staleness

At a fixed prefix and token with positive relevant probabilities,

$$\frac{p_\theta(a \mid h)}{q_k(a \mid h)} = \underbrace{\left(\frac{p_\theta(a \mid h)}{p_k(a \mid h)}\right)}_{\text{parameter change / lag}} \times \underbrace{\left(\frac{p_k(a \mid h)}{q_k(a \mid h)}\right)}_{\substack{\text{same-snapshot} \\ \text{execution / decoding}}} . \tag{1}$$

The first factor captures parameter change since collection, including asynchronous version lag; the factorization requires no independence assumption. The second compares execution at the sampling

Table 1: Policies and quantities used throughout the survey. Execution paths are part of policy identity.

Symbol	Meaning
p_θ	Current learner policy under its specified execution path.
p_k	Learner-side policy evaluated at sampling snapshot θ_k.
q_k	Actual behavior policy that sampled the token.
p_{prox}	Policy used to define the proximal update ratio.
p_{ref}	Policy used for KL regularization; not the behavior denominator.
Δ_k	Same-snapshot log-probability difference, $\log p_k - \log q_k$.
d_θ	Current learner–behavior gap, $\log p_\theta - \log q_k$.
A_t	Advantage or other policy-gradient learning signal.
$s_\theta(a, h)$	Score vector, $\nabla_\theta \log p_\theta(a \mid h)$.
$c_t, \bar{c}_t$	Behavior-to-proximal correction and its truncated or masked form.
$r_t(\theta)$	Proximal update ratio, $p_\theta / p_{\text{prox}}$.
$W_\theta(y \mid x)$	Complete-response likelihood ratio, P_θ / Q.
N, sg	Valid-token count and stop-gradient operator in Equation (9).

snapshot. It isolates numerical differences when decoding is matched and also includes decoding differences when temperature or top-p filtering changes. The intermediate policy p_k is a conceptual reference and need not be retained by the implementation. In partial rollout, a response can span collection boundaries, so $k = k(t)$ may vary across tokens. If caches survive synchronization, their earlier computations remain part of the behavior path, so reconstructing q_k requires cache provenance or the realized sampling probabilities as well as the current checkpoint.

Figure 3 separates these snapshot comparisons from the two policy roles used by the loss. A proximal anchor and a KL reference can be chosen independently of the actual sampler.




Figure 3: Policy identities and loss roles. Horizontal links denote the ratio comparisons in Equation (1), rather than data flow. Execution differences isolate numerical mismatch when decoding is matched. The lower cards identify separate roles in optimization.

Two limiting cases make the distinction concrete. At the sampling snapshot, the learner-side parameter-change factor is one while execution mismatch can remain. With matched execution and decoding, the second factor can instead be one while policy lag remains. A numerical intervention and a staleness correction therefore solve different parts of the same ratio.

Probability ratios also require support conditions. A token observed from q_k has a defined denominator, but that alone does not establish that q_k covers every action with positive target probability. Truncation sampling can violate this condition. Similarly, a token-level change of measure is not

automatically a correction for the prefix distribution. At fixed h,

$$\mathbb{E}_{a\sim q_k(\cdot|h)}\left[\frac{p_\theta(a \mid h)}{q_k(a \mid h)} f(a,h)\right] = \mathbb{E}_{a\sim p_\theta(\cdot|h)}[f(a,h)] \tag{2}$$

holds under support and integrability assumptions. It says nothing by itself about whether the outer distribution over h is the desired one. It also does not undo changes to group-relative advantages induced by collecting different responses.

For comparison, the full-response likelihood ratio is

$$W_\theta(y \mid x) = \frac{P_\theta(y \mid x)}{Q(y \mid x)} = \prod_{t=1}^{T} \frac{p_\theta(y_t \mid h_t)}{q_{k(t)}(y_t \mid h_t)}. \tag{3}$$

Here P_θ and Q are the induced response laws, and the denominator factors must be their actual conditional probabilities under the documented protocol. Unobserved execution randomness requires marginalizing that state or extending the likelihood to the corresponding execution events. The two response laws use a common stopping convention; an end-of-sequence decision is included when applicable. For a fixed behavior law and a parameter-independent reward R, the usual likelihood-ratio identity gives

$$\nabla_\theta \mathbb{E}_{P_\theta}[R] = \mathbb{E}_Q\left[W_\theta R \sum_{t=1}^{T} s_\theta(y_t, h_t)\right] \tag{4}$$

under support, integrability, and differentiation assumptions. The product illustrates why exact response-level correction can have high variance; multiplying only the current token ratio into an arbitrary sampled advantage is a different estimator. Nor does Equation (4) directly justify reusing group-normalized advantages computed under Q. Score Centering explicitly distinguishes sequence-level importance sampling from practical token-level corrections [10].

A two-step example in Figure 4 makes the distinction tangible. The second-token conditionals agree exactly, yet the first-token histories have different probabilities. A correction using only the second-token ratio therefore leaves that prefix imbalance, whereas the full-response ratio includes the earlier decision.




Figure 4: Conditional and response-level correction in a two-step probability tree. Leaf values are complete-response probabilities. Equal second-token conditionals coexist with different prefix masses; the product ratio restores the four target probabilities of 0.25. This is a constructed illustration, not an experimental result.

2.3. A Component-Level Taxonomy of Interventions

We group components by the object they directly modify. **A: numerical interventions** alter representation or execution. A1 matches computation between learner and sampler; A2 controls quantization error or preserves parameter updates. **B: learning interventions** alter how sampled data produce updates. B1 corrects gradient estimation; B2 controls the acceptance, magnitude, or direction of policy updates; B3 adapts the optimization schedule.

Classification follows the operation and its target, while secondary effects can cross class boundaries. Alignment may improve fidelity, and both estimator correction and update control can use multiplicative weights. B1 targets a distributional expectation; B2 regulates sample influence on the update. QaRL and QuRL therefore occupy several classes through coequal components. An adopted correction remains separate from a system's proposed contribution; discussion locations indicate expository placement. Direct low-bit evidence for B3 remains limited.

Table 2: Five intervention classes. These categories describe operative components, not exclusive paper types.

Class	Direct object	Representative components	Residual limitation
A1	Shared computation	Precision flow; aligned QAT; guided rounding	Unmatched execution interfaces.
A2	Quantization fidelity	UAQ; residual compensation; calibration; selective precision	Resolution of useful parameter changes.
B1	Gradient estimator	TIS; AIS; CIS; Score Centering	Target expectation and approximation bias.
B2	Update influence	ACR; TBPO; calibrated clipping; direction-aware controls	Retained signed learning signal.
B3	Optimization schedule	Mismatch-informed LR adaptation	Stability relative to learning progress.

2.4. Numerical Regimes and Contribution Roles

The same intervention can operate under different W/A/KV precisions, dense or mixture-of-experts (MoE) architectures, low-rank or full-parameter updates, and synchronous or partial collection. Native kernels and quantize–dequantize simulation also implement different numerical paths. In particular, "FP4 training" leaves open the precision of master weights, backward computation, and optimizer states.

These configuration axes also preserve attribution: integrating a correction into a quantized system is distinct from introducing that correction. A study's contribution role and the regimes tested in its experiments are recorded separately.

3. Mechanisms: From Numerical Discrepancy to Learning Dynamics

3.1. Sources and Propagation of Execution Discrepancy

Scale selection, rounding, accumulation, kernel choice, batch shape, and cached state can all alter a numerical policy's output distribution. Two paths using the same nominal format can consequently disagree. FP16-based analysis illustrates the role of precision selection, while R3 exposes the effect of discrete MoE routing decisions [15, 16]. Routing disagreement can also arise independently of quantization.

Cross-TP deterministic inference isolates another execution source: changing the reduction order can change probabilities even when parameters and nominal precision match. TBIK coordinates reduction trees across tensor-parallel sizes, providing a matched-execution reference rather than a low-bit accelerator [28]. At more aggressive precision, HiFloat4 studies outlier-driven underflow in rollout activations; its precision ablations connect this local information loss to degraded RL outcomes [24].

Shared-prefix comparison holds the token history fixed and isolates differences between conditional distributions. Free-running comparison allows different samples to change the histories visited later. These settings expose different stages of propagation: a small conditional error can redirect generation, while a favorable shared-prefix average can conceal disagreement on histories reached by only one policy.

Discretization introduces a further asymmetry. An update can be visible in the learner's parameter space but fail to change the sampler's quantized representation. Conversely, a small change near a rounding boundary can abruptly change a codeword. QuRL studies the former through update-aware quantization; TRACE targets inconsistency in rounding outcomes [5, 13]. The relevant object is therefore not only error magnitude, but its relationship to the evolving parameters and the discretization boundaries.

Figure 5 organizes the resulting learning effects into relative influence, expected direction, and update selection. These routes can coexist, which explains why one aggregate disagreement statistic can miss the active mechanism.




Figure 5: Three routes from execution discrepancy to learning dynamics: relative influence, expected score direction, and update selection. These effects can coexist and feed back through later updates and generated histories. Arrows indicate possible propagation under the policy and estimator assumptions in the text.

3.2. Distorted Estimation and Update Decisions

At an observed prefix, numerical disagreement can change an update through its weight, its expected direction, or the clipping branch it activates. Absolute probability error captures only part of this effect. Writing $p = q + \delta$ gives $p/q = 1 + \delta/q$: the same absolute perturbation has greater relative influence when q is small. Tails and confidence-conditioned statistics therefore reveal structure that a mean absolute error can hide. CIS uses this confidence dependence in its correction design [20].

DPPO makes a related distinction between relative ratios and moved probability mass [29]. A large ratio on a rare token need not represent a large distributional shift, while a moderate ratio on a common token can move substantial mass. This motivates separating the geometry of an update constraint from the numerical size of its sampled ratio.

Estimation can also acquire a systematic drift. For a normalized differentiable learner distribution, $\mathbb{E}_{a\sim p_\theta}[s_\theta(a,h)] = 0$. Under behavior sampling, the corresponding expectation need not vanish. At fixed h,

$$\mathbb{E}_q[As_\theta] = \mathrm{Cov}_q(A, s_\theta) + \mathbb{E}_q[A]\mathbb{E}_q[s_\theta]. \tag{5}$$

The expectations are conditional on the prefix and include the sampled action and any random continuation used to form A. Centering advantages across a prompt group need not center them at each prefix. Score Centering uses this distinction to motivate an additive correction [10]: it removes a first-moment drift term while leaving the behavior distribution itself unchanged.

Mismatch additionally affects decisions made by a surrogate objective. In a clipped policy-gradient objective, changing a ratio can change which branch is active and therefore whether a token contributes gradient. Thus, a perturbation can matter through a threshold crossing even when its absolute magnitude appears modest. The full-pipeline FP8 study isolates a failure involving excessive clipping of negative-advantage tokens [11]. This is a different intervention target from merely decreasing the variance of a sampled importance weight.

The sign dependence can be seen without assuming a particular quantizer. Let $\ell(r, A) = \min\{rA, \mathrm{clip}(r, 1-\epsilon, 1+\epsilon)A\}$, with $0 < \epsilon < 1$ and fixed A. Away from the two boundaries,

$$\frac{\partial \ell}{\partial r} = \begin{cases} A\,\mathbf{1}\{r < 1+\epsilon\}, & A > 0, \\ A\,\mathbf{1}\{r > 1-\epsilon\}, & A < 0, \\ 0, & A = 0. \end{cases} \tag{6}$$

Thus the active clipping side depends on the learning signal. For an illustrative objective that clips the combined learner–behavior ratio, a same-snapshot ratio of 0.7 with $\epsilon = 0.2$ already suppresses a negative-advantage token, even before a learner update. This is not the decoupled surrogate in Section 5.1; the example explains why naming the clipped ratio is essential to interpreting a failure or a repair.

Figure 6 makes this sign dependence explicit for the standard surrogate. It also shows why clipping the combined learner–behavior ratio can suppress an update that a proximal ratio would still permit.

3.3. Feedback across Optimization Steps

The learning loop turns a local discrepancy into a dynamic process. Updates based on sampled responses change the learner; synchronization transfers those changes to the sampler; subsequent rollouts come from the updated numerical realization. Stability depends on this feedback, not solely on whether one frozen batch has a small error.

The magnitude of a learner–behavior gap alone does not determine how an update changes it. In a simplified local picture, reducing a learner probability that is already below the behavior probability can enlarge their log gap. ACRL and TRIAGE use update-direction information in their controls [9, 12]. For a shared-parameter network, however, one token's update changes other probabilities




Figure 6: Signed clipping in Equation (6), with $\epsilon = 0.2$ and $A = \pm 1$. The gray interval is $[0.8, 1.2]$; amber segments are flat. At $r = 0.7$, a negative-advantage token contributes no gradient through this objective. The clipped policy ratio determines the interpretation. This is a constructed illustration, not an experimental result.

too. The sign argument supplies local intuition; interactions through shared parameters determine the scope of any stability result.

Optimization scale adds another feedback channel. Beyond Precision studies the relationship between mismatch and optimization dynamics and proposes response-length-triggered learning-rate decay [18]. This connects numerical observations to the scale of optimization, while leaving transfer of the schedule to aggressive FP4 execution open.

3.4. Diagnosing the Effects of Mismatch

Diagnosis begins with the comparison used to isolate an effect. Replacing an inference engine can simultaneously change arithmetic, batching, memory use, and generated trajectories. A resulting quality difference cannot automatically be assigned to the precision format. VeXact constructs a zero-mismatch reference to help separate execution mismatch from other training effects [19]. It supplies a diagnostic counterfactual against which the effects of accelerated execution can be interpreted.

The diagnostics in Table 3 locate different effects within the chain from execution to learning. A controlled comparison connects a change in conditional probabilities to an estimator or update decision; the training trajectory reveals its accumulated consequence.

Shared-prefix measurements isolate conditional effects, whereas free-running trajectories include changes in the histories visited. Signed update diagnostics additionally depend on the surrogate and fixed advantage signals. Their connection to learning requires evidence over the training trajectory.

Box 1. Quantization and exploration

QeRL combines low-precision execution, low-rank adaptation, and adaptive quantization noise, making exploration an explicit part of the training design [2]. It occupies a boundary of this survey: the numerical perturbation changes the search process as well as agreement between computations. Its results establish a role for quantization noise in that setting, with task utility depending on the induced sampling distribution and the learner's adaptation capacity. They do not establish a benefit from arbitrary cross-engine error.

Table 3: Mechanisms, observable diagnostics, and intervention targets. Diagnostics characterize different effects and do not by themselves predict downstream quality.

Mechanism	Diagnostic at a specified policy and prefix	Related intervention
Relative influence	Tails of p/q, conditioned on token confidence; correction truncation or masking rate.	B1: TIS, AIS, and CIS control estimator influence [1, 7, 20].
Conditional score drift	Estimated $\mathbb{E}_q[s_\theta]$ and the contribution $\mathbb{E}_q[A]\mathbb{E}_q[s_\theta]$; reconstruction error matters.	B1: Score Centering removes the exact first-moment term; implementations approximate it [10].
Update selection	Active clipping branches and retained contributions, separated by advantage sign; local directional patterns.	B2: clipping calibration and direction-aware control [11, 12].

These mechanisms connect numerical design to the learning signal it preserves. Relative weighting, conditional drift, threshold decisions, and trajectory feedback expose different consequences of the same execution change. The numerical and learning interventions that follow address different parts of that chain.

4. Numerical Design and Execution Alignment

Numerical design can act on the learner, the sampler, or the interface between them. Alignment brings their computations closer at a shared interface; fidelity control preserves information that a low-precision representation would otherwise lose. The distinction matters because two approximate paths can agree without either becoming more accurate relative to a higher-precision model.

4.1. Aligning Learner and Rollout Computation

Jet-RL coordinates the precision flow used by learner and sampler [3]. Its unified FP8 design matches corresponding operators and quantization granularity across the endpoints. This makes the computation, rather than the format label, the interface of alignment.

QaRL implements such coupling through rollout-aligned quantization-aware training (QAT): the learner's forward pass reflects the representation used during generation [6]. QUADS takes a deliberately asymmetric approach, fake-quantizing learner weights while retaining higher-precision learner activations [8]. Both designs bring part of the learner computation closer to the sampler, but QUADS leaves activation error to a separate rollout-side component. These designs illustrate selective alignment; uniform precision across the whole model is neither its definition nor a prerequisite. QAT emulation and native low-precision kernels nevertheless remain distinct numerical paths.

TRACE shares realized quantization information [13]. Compact rollout-side guidance informs learner-side FP4 rounding when a common quantizer specification still yields different decisions near a boundary. Its local rounding argument explains the benefit at that interface; full-network divergence also depends on downstream computation.

System implementations make these interfaces concrete. Miles coordinates checkpoint conversion, learner forward computation, rollout kernels, and live weight export through shared quantization rules [25]. Its FP8, MXFP8, and NVFP4 recipes retain specified higher-precision exceptions;

the latter two are marked Beta. QATFactory's QARL path instead pairs native NVFP4 rollout with a BF16 learner that simulates the target quantization, and exports inference-ready low-bit weights [26]. This aligns representation and conversion semantics without claiming native FP4 training.

The shared information distinguishes these approaches: Jet-RL coordinates precision flow, aligned QAT emulates a representation, and TRACE communicates realized numerical decisions. Routing replay couples discrete MoE choices through a related principle [15]. TBIK illustrates the stronger requirement of coordinating reduction order across parallel configurations [28]. More specific coupling introduces dependencies on token positions, modules, and parameter versions. Agreement of the complete policies still depends on the computation surrounding the shared interface.

4.2. Controlling Quantization Error and Preserving Parameter Updates

Alignment alone does not ensure that the sampler can express the changes made by training. For an illustrative deterministic quantizer Q, an update can satisfy

$$Q(w + \delta w) = Q(w), \tag{7}$$

even when $\delta w \neq 0$. Visibility depends on the distance to a quantization boundary and on scale behavior, as well as update magnitude. QuRL's Update-Aware Quantization uses invariant scaling to alter the relationship between quantization resolution and parameter updates [5]. Its numerical contribution is therefore distinct from ACR, which modifies the clipping rule in Section 5.2.

Figure 7 shows a smaller update crossing a boundary while a larger one stays within its cell. Changing the scale moves these boundaries.




Figure 7: Quantized-update visibility in Equation (7). Under the fixed-step scalar quantizer, the blue update stays inside a cell while the smaller amber update crosses a boundary. Variable scales change these boundaries. This is a constructed illustration, not an experimental result.

QUADS addresses another residual: activation error in the rollout path. Its Residual Activation Compensation complements learner-side weight QAT, allowing alignment and error reduction to operate on different parts of the system [8]. The component ablations are particularly useful here because they distinguish what weight alignment recovers from what activation compensation adds.

HiFloat4 / Rollout-ResQ targets rollout activation underflow through a sparse residual correction [24]. Its comparison of learner and sampler precisions shows why restoring learner precision alone

need not repair a degraded sampling path. This is direct rollout-fidelity evidence, distinct from a generic analysis of FP4 arithmetic. All reported FP4 experiments are simulated, however, so the results establish accuracy behavior in those simulations rather than measured native-FP4 speedup.

FP8-RL maintains numerical fidelity as the policy changes through blockwise W8A8 rollout, scale recalibration for FP8 attention and KV execution, and dynamic weight synchronization [4]. It integrates these components with adopted TIS/MIS correction. Its v2 experiments also explore end-to-end FP8, so learner precision varies across the paper's experimental settings.

Miles exposes fidelity choices within an integrated precision recipe: selected tensors remain in BF16, and an optional dequantized backward path trades training throughput for gradient stability without changing the quantized forward values [25]. Such exceptions belong to the numerical configuration; they do not imply that every operation uses the headline format.

KV4-RL allocates fidelity across positions instead of raising precision uniformly [17]. INT4 KV storage is supplemented by bounded INT8 protection for attention-sink and recent positions. Its retained TIS recipe makes the distinction between sampler fidelity and conditional correction especially clear: protecting the cache changes the data-generating computation even when the correction is held fixed. The experiments use colocated, quota-based partial collection, with generation and optimization alternating; responses may span collection boundaries.

These methods preserve different information needed by learning. Parameter rescaling protects update visibility, residual compensation reduces activation error, recalibration follows distributional change, and positional protection targets sensitive cache states. Their W/A/KV targets locate the computation on which each mechanism acts.

4.3. Residual Mismatch and Limits of Alignment

Alignment and fidelity constrain different comparisons: agreement between endpoints and faithfulness to a higher-precision computation. Shared weights can coexist with different activations, and a common quantizer with different surrounding kernels. Each result is therefore conditional on the shared interface, parameter snapshot, and input history.

Residual differences connect numerical design to learning correction. A more faithful sampler may still lag behind the learner, and conditional agreement at observed prefixes does not restore a response distribution changed by earlier decisions. A learning intervention addresses how these remaining differences affect estimation or the resulting update.

Maintaining a shared numerical interface requires information as well as arithmetic. Operator choices require coordination, QAT depends on matching quantizer semantics, and rounding guidance requires storage and correspondence with learner states [3, 6, 8, 13]. Fidelity control instead uses calibration, compensation, or selective execution to preserve sensitive information [4, 5, 17]. Table 4 compares these dependencies and the discrepancies each leaves unresolved.

The relevant correction depends on which residual effect changes the estimator or update, and on the information available to control it.

Table 4: Numerical strategies, the information they share or preserve, and their remaining execution differences.

Strategy	Shared or protected object	Information dependency	Residual discrepancy
Precision flow	Corresponding operator precision and granularity	Coordinated numerical configuration	Engine and surrounding-kernel differences.
Aligned QAT	Learner representation corresponding to rollout	Matching quantizer semantics	Native versus simulated arithmetic; unmatched activations.
Guided rounding	Realized rollout quantization decisions	Stored and matched rollout guidance	Unshared modules and downstream propagation.
Fidelity control	Scales, update resolution, residuals, or protected states	Calibration, compensation, or selective execution	Other execution paths and policy staleness.

5. Learning under Residual Mismatch

Residual mismatch enters learning through both estimation and optimization. Estimator correction changes how behavior samples represent a target expectation; update control regulates their influence; scheduling changes the scale of adaptation over time. These objectives lead to different trade-offs among bias, variance, progress, and stability.

5.1. Correcting Gradient Estimation

Multiplicative correction and truncation. Importance sampling supplies a conditional change of measure under the assumptions of Equation (2). Practical surrogate objectives usually distinguish the mismatch correction from the proximal update ratio. With frozen p_{prox} and recorded behavior q, define

$$c_t = \frac{p_{\text{prox}}(a_t \mid h_t)}{q(a_t \mid h_t)}, \qquad r_t(\theta) = \frac{p_\theta(a_t \mid h_t)}{p_{\text{prox}}(a_t \mid h_t)}. \tag{8}$$

A representative decoupled surrogate is

$$\widehat{L}(\theta) = \frac{1}{N} \sum_t \text{sg}(\bar{c}_t) \min[r_t(\theta)A_t, \text{clip}(r_t(\theta), 1-\epsilon, 1+\epsilon)A_t], \tag{9}$$

where $\bar{c}_t$ is a possibly truncated correction, the sampled advantages are held fixed, and sg denotes no differentiation through the correction weight. The separation exposes two different operations: bounding the mismatch correction c_t and clipping the proximal ratio r_t. Individual objectives differ in how they perform and combine these operations. An upper-truncated correction, for example, takes $\bar{c}_t = \min(c_t, C)$, whereas masking can discard selected ratios. Here N counts valid sampled tokens. Response-level averaging and length normalization assign different relative weights, so the reduction rule is part of the estimator being compared.

FlashRL's truncated importance sampling (TIS) provides a basic bounded correction using actual rollout probabilities [1]. MiniRL exemplifies the mismatch-aware distinction between behavior and proximal policies underlying this notation [14]. FP8-RL adopts token-level TIS and masked importance sampling (MIS) variants, while KV4-RL retains TIS alongside cache protection [4, 17]. The

system studies show how the correction operates alongside other numerical components. Truncation bounds extreme influence while changing the expectation; recording an actual behavior denominator supplies the required probability semantics, but does not remove that truncation bias.

Adapting the amount and location of correction. Adaptive importance sampling (AIS) uses observable mismatch diagnostics to interpolate between uncorrected and fully importance-weighted gradients [7]. Its adaptive quantity is the estimator mixture, not a precision schedule. Calibrated importance sampling (CIS) instead derives a confidence-dependent importance-weight cap from a discrepancy representation [20]. These approaches differ in what they adapt: overall correction strength versus the location of truncation across token confidence. CIS is used here as general TIM evidence; its BF16 cross-engine experiments are not direct FP4 validation.

Additive score correction. Score Centering replaces the score at a prefix with

$$\widetilde{s}_\theta(a,h) = s_\theta(a,h) - \mathbb{E}_{b\sim q(\cdot|h)}[s_\theta(b,h)]. \tag{10}$$

With the exact expectation, its mean under q vanishes and the drift term in Equation (5) is removed [10]. The remaining covariance is still measured under q, so this is not full recovery of an on-policy gradient. The reported implementation uses sampler top-k log-probabilities and models the omitted tail using the learner distribution; its default is $k = 128$ [10]. The omitted mass therefore enters through a modeled tail rather than being discarded. The coefficients used to form the correction are detached, and its fidelity depends on that behavior reconstruction.

The covariance analysis of baselines and score centering further qualifies their composition [27]. For the estimators studied there, sequence-level regularized importance sampling gains no additional centering benefit once the group-mean baseline is used. At token level, the group baseline alone generally leaves bias under regularized ratios. These statements concern the specified covariance estimands and do not imply that one correction should always be added to every RL objective.

These corrections differ in their targets and information requirements. Ratio-based methods use sampled-action probabilities to adjust relative weights; score centering uses a behavior-weighted score expectation to remove conditional drift. Truncation and tail reconstruction approximate different objects. Their gradient interpretation also depends on the learner computation, including any surrogate gradient through a quantizer. These distinctions remain relevant when corrections are combined.

5.2. Controlling the Influence of Policy Updates

Restoring or reshaping update constraints. QuRL's Adaptive Clipping Range (ACR) adjusts the update boundary in response to the relationship between proximal and behavior probabilities [5]. QaRL's Trust-Band Policy Optimization (TBPO) combines negative-sample treatment with sequence-level trust-band control [6]. The full-pipeline FP8 method first matches the lower clipping quantile on negative-advantage tokens to a BF16 reference, then adjusts the upper boundary to rebalance positive and negative contributions [11]. Periodic reference passes amortize the calibration cost. All three act on the update constraint, but use different signals and aggregation levels. "Calibration" in the last method refers to objective boundaries, not quantizer scales.

The shared issue is which learning signal reaches the parameter update. A token-level boundary can restore a contribution lost to clipping, whereas a sequence-level trust band controls a whole response. Widening either region admits more updates, but their value depends on advantage sign and influence. The clipping count becomes informative when connected to those retained contributions.

Batch reliability and divergence geometry. P3O replaces a fixed clip range with control based on normalized effective sample size (ESS) of the batch's policy ratios [21]. The same reliability statistic governs a score-weight cap and off-policy regularization. Its FP8-rollout experiment directly instantiates numerical mismatch, while its other comparisons show that the benefit depends on the model and collection setting. The contribution is adaptive update control, distinct from AIS's mixture of gradient estimators.

DPPO replaces sampled-ratio clipping with a divergence-based trust region [29]. DRPO retains the Binary-TV geometry but replaces hard masking with a smooth regularizer that supplies corrective gradients outside the boundary [22]. DRPO evaluates both FP8-rollout-only and end-to-end FP8 MoE settings; DPPO supplies the broader trust-region foundation. Their classification follows the update constraint they change, rather than treating any use of a policy ratio as estimator correction.

Accepting updates in the inference policy. MIPU constructs candidates relative to the sampler and then evaluates whether the synchronized candidate should become the next inference policy [23]. The two stages separate candidate quality from acceptance after numerical conversion. Its practical inference-gap proxy can reject harmful candidates in the evaluated FP8 runs, but it is not an unconditional certificate of monotonic improvement. The resulting acceptance or rollback decision acts on the whole candidate update.

Controlling disagreement through update direction. ACRL uses advantage-guided probability adjustment, with response-level discrepancy relative to a reference controlling token reweighting [9]. It regulates how updates change disagreement. TRIAGE combines segment-local risk information, direction-selective gating, rebalancing, and bounded repair in native NVFP4 execution [12]. Both belong to B2 because their operative rule controls update influence. Their different risk signals and aggregation levels determine which contributions are admitted, suppressed, or repaired.

The granularity of control matters. A response-level statistic aggregates evidence across many tokens; a segment statistic can expose local concentration; a token rule is directly selective but may be sensitive to noise. Aggregation trades localization against statistical reliability. Finer granularity improves localization only when the resulting diagnostic remains reliable enough to guide the update.

5.3. Adapting the Optimization Schedule

A third intervention changes the scale of learning over time. Beyond Precision motivates learning-rate scheduling through the evolution of optimization and mismatch [18]. This is complementary to changing a numerical path or a token weight: it modifies the trajectory of parameter updates themselves.

Schedule adaptation remains less developed for direct low-bit settings than the estimator and update controls above. Its promise depends on preserving progress as well as stability: smaller

steps can avoid divergence while delaying useful learning. Comparable quality within a comparable budget is therefore the relevant test of transfer to aggressive quantization.

5.4. Compatibility, Bias, and Failure Modes

The operators in Figure 8 act on different objects even when they share a reweighting implementation. Importance correction targets an expectation; a gate or trust band regulates the update it permits. Their combination depends on a common behavior law and on how each operation changes the estimator received by the next.

The baseline analysis also makes aggregation part of the compatibility question: token-level and sequence-level regularized estimators need not benefit from the same centering construction [27]. A component should therefore be compared in its actual loss and reduction rule, rather than identified only by its name.




Figure 8: Learning interventions distinguished by their target object. The displayed expressions are explanatory examples with fixed sampled advantages; the B1 forms are not assumed to be interchangeable, and the B2 panel omits method-specific correction factors. A combined objective needs its own estimator definition.

Composition takes several forms. QaRL and QuRL combine numerical and learning interventions, while QUADS couples numerical alignment with activation-error compensation. Score Centering combines estimator corrections by centering the importance-weighted score [5, 6, 8, 10]. These results motivate composition while leaving its behavior under other combinations open.

Compatibility is a property of the joint estimator. A center computed for an unweighted score need not remove drift after weighting; successive masks can discard the same examples; a reference pass adds computation to an otherwise inexpensive rule. Consistent behavior probabilities and parameter snapshots establish the common basis of the operations, while their interaction determines the retained update and its cost.

Complementarity consequently depends on the residual effect addressed by each component and on the signed contributions left after all operations have acted.

6. Synthesis of Findings and Practical Trade-offs

Within-study comparisons connect numerical execution to update behavior and learned-policy quality. They expose how closely the endpoints share computation, how samples enter the estimator, and

which contributions survive optimization. These connections explain why numerical agreement, stability, and quality can respond differently to an intervention. Training cost determines whether the resulting benefit improves learning efficiency.

6.1. Experimental Regimes

Asymmetric learner–sampler precision exposes differences between numerical representations. Low precision on both sides makes the consistency of their execution paths and the resulting update especially salient. KV quantization acts on retained state, whereas weight and activation quantization alter other parts of computation. Low-rank adaptation and full-parameter RL also provide different degrees of freedom for responding to these changes.

AIS evaluates diffusion-based LLaDA alongside autoregressive Qwen models [7]. Its autoregressive experiments connect directly to the token-level formulation used here. Interpreting the denoising results requires likelihoods defined for that generation process, so those experiments broaden the empirical scope without validating the autoregressive factorization for diffusion.

Architecture and collection protocol further condition conclusions. MoE execution introduces discrete route choices; cache-heavy long responses expose different runtime bottlenecks from shorter generations; partial collection permits a response to contain tokens sampled under different parameter versions. A method evaluated in one of these regimes may motivate a hypothesis in another, but that transfer is not itself an experimental result.

Table 5 makes the scope and its boundaries explicit.

Miles adds production-scale agentic system evidence, whereas QATFactory isolates a smaller NVFP4 QARL workload [25, 26]. Native low-precision arithmetic, simulated quantization, and BF16 execution on quantized operands are distinct regimes. In particular, HiFloat4 reports simulated FP4 RL rather than measured native-FP4 training [24].

Table 6 brings together six within-study comparisons that illuminate these interactions. Appendix A covers all twenty-nine focal works, and the companion evidence collection provides source locations for observations from all nineteen core studies.

6.2. Findings on Stability and Learning Quality

Across these regimes, the evidence links the evolution of mismatch, the interface being aligned, and the signed updates retained by the objective. Figure 9 locates these relationships across numerical measurements, update behavior, learning trajectories, and quality and cost.

Correction and mismatch evolve together. QuRL observes disagreement beyond an initially stable period, with ACR and UAQ addressing different changes in clipping and update visibility [5]. AIS adapts the correction mixture, ACRL regulates discrepancy through update influence, and Score Centering removes a conditional estimator drift term [7, 9, 10]. The common feature is feedback: an altered update changes the policy and the mismatch encountered later. Early agreement and bounded weights describe only part of this process.

Alignment gains depend on the shared interface. Jet-RL couples precision flow; QaRL, QUADS, and TRACE couple representations or realized rounding decisions [3, 6, 8, 13]. QUADS separates

Table 5: Coverage matrix for the qualitative snapshot. Rows are independent dimensions; the presence of two regimes does not imply that their combination has been evaluated.

Dimension	Represented in the focal collection	Boundary of the synthesis
Intervention	A1/A2 numerical design; B1/B2 learning rules; B3 scheduling.	Direct low-bit evidence is thinner for B3 than for the other classes.
Numerical interface	Weight/activation quantization, KV storage, scales, rounding, routing, and synchronization.	An interface-level result does not establish full-network agreement.
Precision	FP8, FP4/NVFP4, INT8/INT4; BF16/FP16 comparisons provide context.	Format labels omit scale granularity, precision exceptions, and native versus simulated arithmetic.
Model and adaptation	Dense and MoE models; low-rank and full-parameter updates appear in different studies.	Architecture and adaptation are separate axes; cross-regime transfer is not assumed.
Collection	Snapshot-based hybrid execution, policy lag, and quota-based partial collection.	Stateful provenance and fully overlapped execution require additional behavior and timing semantics.
Learning and generation	PPO/GRPO-style autoregressive RL; AIS also studies diffusion generation.	This survey's likelihood equations are autoregressive; denoising requires its own formulation.
Contribution role	Nineteen core studies, nine supporting studies, and one exploration boundary.	Role identifies relevance to the argument, independently of experimental strength.




Figure 9: Four layers of evidence connecting numerical execution to effective training. Controlled ablations can link an intervention across these layers; improvement at one layer alone leaves the others unresolved.

two effects: asymmetric weight QAT recovers much of the performance loss, and rollout activation compensation further narrows the gap. Its asymmetric-versus-symmetric comparison shows why nominal symmetry alone does not define effective alignment. FP8-RL adds calibration and synchronization for a changing low-precision policy [4]. Transfer depends on preserving the interface responsible for the gain and its surrounding computation.

Signed update selection explains effects hidden by averages. The full-pipeline FP8 study connects excessive lower-side clipping of negative-advantage tokens to pathological training dynamics, whereas TRIAGE uses local and direction-dependent information to select interventions [11, 12]. Both link stability to the signed signal retained after control. An aggregate clipping fraction or

mean log-probability gap can hide that structure. TRIAGE's MoE routing-conditioned analysis also shows limits to token-wise directional predictiveness, distinguishing a population pattern from a reliable predictor for each token.

Table 6: Within-study evidence for the synthesis. Regimes, comparison rules, and interpretive limits are retained; the companion evidence collection provides source locations.

Study / setting	Comparison	Reported finding	Interpretation and limit
QuRL [5] INT8/FP8	Longer TIS runs; ACR and invariant-scaling ablations.	Later behavior departs from the initially stable window; clipping and update visibility need distinct treatment.	Early stability does not establish long-run effectiveness; the reported horizon is setting-specific.
QUADS [8] NVFP4 MoE	Weight-only learner QAT, then added rollout activation compensation.	Weight alignment recovers much of the performance loss; compensation further improves held-out scores.	Supports complementarity within this design; transfer across engines is untested.
Score Centering [10] BF16 learner	Additive and importance corrections under shared objectives; composition under lag.	Corrections affect distinct estimator terms; their composition helps in the reported staleness tests.	Behavior expectations are reconstructed; trajectory-distribution mismatch can remain.
Full Pipeline FP8 [11] FP8 both sides	Clipping calibration across scaling choices; main GRPO endpoints over 500 steps.	Reference calibration improves reported outcomes while restoring signed contributions.	Main results select the best average checkpoint, rather than the final checkpoint at a fixed budget.
TRIAGE [12] Native NVFP4	Local tail analysis, direction-selective gating, and repair.	Local and signed patterns motivate intervention; MoE analysis restricts token-wise predictiveness.	Population trends do not ensure contraction for each token.
KV4-RL [17] INT4 KV	Unprotected INT4 versus bounded INT8 protection, with TIS retained.	Protection recovers later gains and near-BF16 endpoint quality.	Cache fidelity and conditional correction affect different mechanisms; claims concern the studied partial-collection workload.

These studies illustrate different forms of complementarity. QUADS combines two numerical interventions, QuRL combines update visibility with clipping control, and KV4-RL improves cache fidelity while retaining the correction recipe. Their results connect the component being changed to the contributions available for learning. They support the combinations tested within each system and suggest how numerical fidelity and learning correction can address different residual effects.

The expanded studies sharpen these distinctions. P3O preserves later reward and held-out performance in its Qwen3-8B FP8 comparison, without establishing a higher peak or universal resistance to collapse [21]. DRPO tests corrective regularization across BF16 and FP8 regimes, and MIPU separates candidate construction from inference-side acceptance through ablations [22, 23]. HiFloat4's precision ablations locate rollout activation error within a simulated FP4 pipeline [24]. QATFactory compares NVFP4 QARL with both BF16 RL and post-RL quantization, separating learning in the target representation from quantizing only the endpoint [26].

6.3. Efficiency Gains and Implementation Costs

An intervention's computational benefit depends on the work required for generation, learning, synchronization, and correction. For serialized phases, iteration time can be decomposed as

$$T_{\text{iter}} = T_{\text{rollout}} + T_{\text{learner}} + T_{\text{sync}} + T_{\text{quant/calib}} + T_{\text{other}}, \tag{11}$$

where synchronization and quantization/calibration costs are separated from generation and learning. Accelerating one phase exposes the others. With overlapping execution, the relevant quantity is the critical path, so the phase times in Equation (11) cannot simply be added.

The serialized model also gives a simple bound on what a rollout improvement can achieve. If rollout occupies fraction f of the baseline time, a rollout speedup s and added work hT_0 give $T/T_0 = (1-f) + f/s + h$, holding the other phases and workload fixed. Figure 10 illustrates the arithmetic. Overlap, changed response lengths, or changed concurrency require a different cost model.




Figure 10: Serialized timing with a faster rollout phase and added overhead. Doubling rollout speed reduces iteration time from T_0 to $0.7T_0$ when rollout accounts for 60% of the baseline. Added work of $0.1T_0$ reduces the overall speedup from 1.43× to 1.25×. This is a constructed illustration, not an experimental result.

Each intervention changes a different part of this cost. FP8-RL illustrates the work needed for scale estimation and numerical conversion [4]. Reference calibration adds learner computation; guided rounding adds storage, transport, and state matching; selective precision adds work in the protected region. Table 7 relates these dependencies to the information each method needs.

P3O requires batch-level ratio statistics, while MIPU's acceptance step adds inference-side assessment and possible rollback [21, 23]. Miles and QATFactory emphasize conversion and inference-ready weight transfer as part of the execution contract [25, 26]. TBIK's coordinated reductions can carry a kernel-performance cost [28]. Rollout-ResQ's sparse correction is designed for efficient hardware execution, but its simulated experiments do not measure a native FP4 speedup [24].

Token throughput also depends on the realized workload. A policy that produces shorter responses can appear faster without improving execution per token; one that produces longer responses can incur more work despite a faster kernel. Memory savings can increase concurrency, which changes the workload seen by attention and compute kernels. Serving research such as

PagedAttention provides background for why cache management and scheduling affect observed throughput [32], but serving speed alone does not establish RL learning efficiency.

Table 7: Information and execution dependencies of the reviewed approaches. These interfaces explain system cost without assigning an overhead ranking.

Approach	Information or execution dependency	Consequence for implementation
TIS / AIS / CIS	Behavior probabilities and learner/proximal probabilities	Stored probabilities must include the sampling transformations.
Score Centering	A behavior-weighted score expectation, exact or approximated	Exact evaluation requires distributional information; reconstruction introduces approximation.
Aligned QAT	A learner path corresponding to rollout quantization	Unmatched kernels and interfaces leave residual execution error.
Guided rounding	Realized rollout-side quantization information	Guidance requires storage, transport, and matching to learner states.
Calibrated Clipping [11]	Higher-precision reference ratios at calibration points	Reference passes add training computation, amortized across calibration intervals.
Selective KV precision	Low-bit cache execution with protected positions	Protected positions add work whose share depends on the context workload.

KV4-RL illustrates the difference between generation and training gains. Over 400 iterations on Qwen3-8B-Base, it reports 1.80× cumulative rollout speedup and 1.27× cumulative full-iteration speedup over BF16 rollout [17]. Other phases absorb part of the generation gain. Its common-BF16 evaluation separately compares learned-policy quality under a shared evaluation precision. Both conclusions apply to the study's collection workload.

Time or compute to a specified quality level connects these measurements to the learning objective. Endpoint scores, iteration time, and rollout throughput supply different parts of the picture. The trajectory is needed to recover time-to-quality when an intervention changes response length, learning speed, or checkpoint selection.

6.4. Evidence Limits and Coverage Gaps

The strongest empirical support concerns mechanisms within the settings in which they were isolated. Model families, tasks, horizons, hardware, and numerical kernels vary across studies. Mathematical reasoning is a recurring evaluation setting, while interactive trajectories and broader task distributions are less directly covered. Transfer across precision formats likewise depends on scaling rules, higher-precision exceptions, and the surrounding kernels.

This synthesis inherits the scope of its curated sources and the implementation details they make available. Source-linked observations expose the basis of the comparisons, while unreported conditions remain unresolved. The collection supports neither an exhaustive account of the field nor independent replication of its empirical results.

Direct low-bit scheduling evidence remains limited, and stateful provenance is only partly characterized. Multi-turn agent evidence includes system demonstrations, but controlled attribution of low-precision effects across long interactions remains limited; diffusion results are contextual to the autoregressive analysis. Seed counts, uncertainty, negative results, and cross-hardware replication

are not systematically extracted. These are limits of this synthesis, not claims of absence from the wider literature.

7. Open Problems

The remaining challenge is to predict when mismatch becomes harmful, how interventions interact, and which benefits transfer across systems and tasks.

7.1. Predicting Harmful Mismatch

Learning depends on where error occurs and which update it changes. Confidence-conditioned tails, signed clipping distortions, conditional drift, and directional concentration are candidate diagnostics with closer links to the update than mean disagreement. Their ability to predict instability or lost progress early enough to guide intervention remains unresolved.

Collapse, reduced progress per update, and failure to reach a quality threshold need not share a precursor. A mechanism-based diagnostic should remain predictive across models and correction rules. Lowering it without improving learning may instead reflect correlation, or suppression of useful signal alongside the measured risk.

7.2. Composing Numerical and Learning Interventions

Greater fidelity alters the discrepancy encountered by a correction; restrictive update rules can conceal the value of finer quantization by suppressing the affected contributions. A component's value therefore depends on its marginal effect on learning progress and cost after other interventions act.

Multiple masks, truncations, or trust bands can suppress the same contributions, making weak learning appear stable. Analysis of the joint estimator must identify its bias and variance, the contributions retained from positive and negative advantages, and the cost of reference passes or reconstructed expectations. This connects compatibility to quality gained per unit of computation.

7.3. Precision, Staleness, and Long-Horizon Interaction

Partial and asynchronous collection can make the sampling version token-dependent. A probability gap may then combine parameter change with execution mismatch, as Equation (1) makes explicit. Separating their effects requires information about snapshots, replay, or retained cache states that a production system may not store. The smallest behavior record sufficient for reliable correction remains a joint statistical and system question.

Long responses amplify this difficulty. An early numerical perturbation changes the prefixes visited later, even if conditional correction at each observed prefix is accurate. This suggests allocating precision according to position, layer, context, and training phase, with learning benefit as the objective. Local tensor error alone cannot identify where the extra fidelity is worth its cost.

Multi-turn interaction adds tool observations and environment transitions that shape later behavior. These may need to accompany cache provenance and sampling probabilities in the behavior record. Evidence from single-response generation leaves the effectiveness of the surveyed interventions in these settings open.

7.4. Generalization and Comparable Evidence

Transfer depends on behavior and execution semantics. Correction requires probabilities of actual sampling events; rounding guidance requires correspondence between numerical states. Predecoding probabilities and changed synchronization protocols can violate these requirements. Controlled comparisons across stacks are needed to establish which benefits survive changes in kernels, collection protocols, and correction recipes.

8. Conclusion

Quantized rollout places numerical approximation inside the learning loop: the data-generating policy affects both the current update and future trajectories. The surveyed interventions address distinct parts of this loop through computation alignment, numerical fidelity, estimator correction, update control, and schedule adaptation.

Numerical fidelity changes the error presented to the learner; correction changes its influence on the update. This interaction makes average agreement, short-term stability, and rollout throughput incomplete measures of effective training. The goal is policy quality at lower total computational cost. Predictive diagnostics and joint-estimator analysis can clarify when a combination achieves that goal across systems and collection regimes.

A. Surveyed Papers and Section Mapping

Table 8 summarizes the twenty-nine focal studies, numerical regimes, and component assignments. Years denote first public appearance; bibliography records may cite later formal publications. Main discussion locations precede additional locations in parentheses. Contribution roles are defined in Appendix B.

Table 8: Surveyed papers: numerical regimes, method components, and section mapping. Conference and preprint versions count as one contribution.

Work / first year	Numerical regime	Component(s) and contribution	Discussion
Core method and system studies (19)			
FlashRL / TIS [1] 2025	Higher-precision learner; quantized rollout	**B1**: Recorded behavior probabilities and truncated correction.	**5.1** (1.1; 2.1)
Jet-RL [3] 2026	Unified FP8 learner and rollout paths	**A1; A2**: Unified FP8 precision flow.	**4.1** (6.2)
FP8-RL [4] 2026	W8A8 rollout; FP8 attention / KV; FP8 learner explored in v2	**A2; system**: W8A8 rollout, FP8 attention/KV, and stack integration.	**4.2** (5.1; 6.2; 6.3)
QuRL [5] 2026	INT8 / FP8 rollout	**B2; A2**: Adaptive clipping and update-aware quantization.	**5.2** (3.1; 4.2; 5.4; 6.2)
QaRL [6] 2026	Quantized MoE rollout; aligned learner QAT	**A1; B2**: Rollout-aligned QAT and trust-band updates.	**4.1** (5.2; 5.4; 6.2)
P3O / ESS [21] 2026	BF16 learner / FP8 rollout; dense reasoning models	**B2**: Batch-adaptive ESS cap and regularization.	**5.2** (6.2; 6.3)
AIS [7] 2026	BF16 learner / FP8 rollout; autoregressive and diffusion models	**B1**: Adaptive importance-weighted estimator mixture.	**5.1** (6.1; 6.2)
DRPO [22] 2026	BF16, FP8 rollout-only, and FP8 end-to-end MoE settings	**B2**: Smooth corrective divergence regularization.	**5.2** (6.2)
MIPU [23] 2026	BF16 learner / FP8 rollout; Qwen3-1.7B and 4B	**B2; formulation**: Inference-policy candidate construction and acceptance.	**5.2** (2.1; 6.2; 6.3)
QUADS [8] 2026	NVFP4 MoE rollout; learner weight QAT	**A1; A2**: NVFP4 MoE weight alignment and activation compensation.	**4.1** (4.2; 5.4; 6.2)
ACRL [9] 2026	FP8 rollout; discrepancy-dependent updates	**B2**: Discrepancy-dependent update control.	**5.2** (3.3; 6.2)
HiFloat4 / Rollout-ResQ [24] 2026	Simulated end-to-end HiF4 / MXFP4; rollout residual correction	**A2**: Sparse residual correction for FP4 rollout activations.	**4.2** (3.1; 6.2; 6.3)
Miles v0.1 [25] 2026	FP8 / MXFP8 / NVFP4 RL recipes; precision exceptions	**A1; A2; system**: Shared quantization, synchronization, and precision contracts.	**4.1** (4.2; 6.1; 6.3)
Score Centering [10] 2026	BF16 learner; quantized rollout or policy lag	**B1**: Additive behavior-weighted score correction.	**5.1** (2.2; 3.2; 5.4; 6.2)
Full Pipeline FP8 RL [11] 2026	FP8 learner and rollout; calibration against BF16	**B2; system**: FP8 learner/rollout and calibrated clipping.	**5.2** (3.2; 6.2; 6.3)

Continued on next page

Table 8 continued: Surveyed papers

Work / first year	Numerical regime	Component(s) and contribution	Discussion
QATFactory / QARL [26] 2026	Native NVFP4 rollout; simulated-quantization BF16 training	**A1; system**: Deployment-aligned QARL and inference-ready weight synchronization.	**4.1** (6.2; 6.3)
TRIAGE [12] 2026	Native NVFP4 W4A4; MoE analysis	**B2**: Direction-aware control for native NVFP4.	**5.2** (3.3; 6.2)
TRACE [13] 2026	FP4 MoE rollout; guided learner QAT	**A1**: Rollout-guided FP4 rounding for MoE.	**4.1** (3.1; 6.2)
KV4-RL [17] 2026	INT4 KV with bounded INT8 protection	**A2; system**: INT4 KV with selective INT8 protection.	**4.2** (5.1; 6.2; 6.3)
Supporting formulation and general TIM studies (9)			
R3 [15] 2025	MoE routing; general execution mismatch	**Support; A1**: MoE routing alignment.	**3.1** (4.1)
FP16-Mismatch [16] 2025	BF16 / FP16 numerical comparison	**Support; A2**: BF16/FP16 precision-selection evidence.	**3.1**
TBIK / Deterministic Inference [28] 2025	BF16 / FP32; matched reduction order across TP sizes	**Support; A1**: Cross-TP deterministic kernels as an alignment reference.	**3.1** (4.1; 6.3)
MiniRL [14] 2025	Hybrid-engine RL; includes FP8-rollout experiments	**Support; B1/B2**: Policy roles and mismatch-aware formulation; FP8 experiments.	**2.1** (1.2; 5.1)
Beyond Precision [18] 2026	General TIM; optimization scheduling	**Support; B3**: Optimization schedule under general TIM.	**5.3** (3.3)
DPPO [29] 2026	General LLM trust-region and cross-engine mismatch evidence	**Support; B2**: Divergence-based trust regions under general TIM.	**5.2** (3.2)
VeXact / Diagnosing TIM [19] 2026	Matched-execution diagnostic reference	**Diagnostic**: Zero-mismatch diagnostic reference.	**3.4**
CIS [20] 2026	BF16 cross-engine mismatch	**Support; B1**: Confidence-dependent correction under BF16 cross-engine mismatch.	**5.1** (3.2)
Baselines and Score Centering [27] 2026	Sequence- and token-level regularized importance sampling	**Support; B1**: Granularity-dependent roles of baselines and score centering.	**5.1** (5.4)
Exploration boundary case (1)			
QeRL [2] 2025	NVFP4 with LoRA and adaptive noise	**Boundary**: NVFP4 with LoRA and adaptive noise; exploration setting..	**Box 1**

B. Source Selection and Version Handling

Construction of this snapshot. The collection comprises twenty-nine contributions to quantized rollout, low-precision RL, and mechanisms needed to interpret training–rollout mismatch. Primary papers and official records provide the evidence. A targeted update searched arXiv metadata through October 20, 2026, followed by primary-text checks and backward citation tracing. This curated narrative review does not claim exhaustive coverage.

Inclusion and exclusion. A focal study contributes a direct quantized-rollout or low-precision RL intervention, a mechanism needed to interpret that setting, or a carefully identified boundary case. General quantization and RL background is cited selectively. Papers devoted only to low-precision pretraining, unrelated generation modalities, or alternative rollout acceleration do not become focal entries solely because they use the same precision format.

Versions and names. The catalog distinguishes first-publication dates, publication venues, and reviewed versions. QeRL, QuRL, and QaRL use formal publication records in the bibliography. Conference and preprint versions, aliases, and changes in presentation count as one contribution. Unpinned arXiv links are distinguished from locally reviewed versions, since a later revision may change the claims supported by a source.

Attribution of evidence. Method claims and observations are attributed to primary sources. The likelihood, drift, and clipping identities explain mechanisms under the stated assumptions; they are distinct from experimental findings. Figures and tables are original syntheses, and constructed examples are labeled separately from published measurements. The companion evidence collection links observations to reviewed sources.

Evidence roles and verification. Contribution role identifies relevance to the argument; evidence domain identifies the setting examined. Neither grades experimental quality. Source-linked observations retain their conditions and limitations. No independent reproduction was performed, and unextracted statistical or implementation fields remain unassessed. The catalog separates identified reviewed versions from version-unspecified records.

C. Evidence, Assumptions, and Transfer

Transfer depends on the relationship between sampled behavior and learner computation. Parameter versions, numerical paths, decoding, and retained state determine the behavior law; learner, proximal, and reference policies define separate loss roles. Changing execution can alter a correction's meaning even at the same nominal precision.

Each approximation leaves a specific residual: prefix selection after conditional correction, truncation bias, unmatched execution after alignment, or reconstruction error in an expectation. A tested combination supports its reported estimator and regime; transfer requires the assumptions responsible for that result to remain valid.

D. Terminology

Table 9: Terminology and component abbreviations used in the text and figures.

Term	Meaning
TIM	Training–inference mismatch; the survey emphasizes the learner–rollout interface.
W / A / KV	Weights, activations, and key–value cache; distinct numerical targets.
MoE / LoRA	Mixture-of-experts architecture / low-rank adaptation; architecture and adaptation are separate dimensions.
FP8 / FP4 / NVFP4	Floating-point format families with eight or four bits; NVFP4 is a particular four-bit representation. Scaling, accumulation, and exceptions also determine execution.
INT8 / INT4	Integer quantization at eight or four bits, with scales and execution semantics specified separately.
QAT	Quantization-aware training: the learner forward path models a quantized representation; this need not reproduce native kernel arithmetic.
TIS / MIS	Truncated / masked importance sampling; bounded or discarded corrections alter the estimator.
AIS / CIS	Adaptive / calibrated importance sampling: estimator-mixture adaptation and confidence-dependent truncation, respectively.
ACR / UAQ	QuRL's Adaptive Clipping Range / Update-Aware Quantization; B2 update control and A2 update visibility.
TBPO / RAC	QaRL's Trust-Band Policy Optimization / QUADS's Residual Activation Compensation; distinct objective and numerical components.
PPO / GRPO	Proximal Policy Optimization / Group Relative Policy Optimization. Their loss roles require behavior and proximal policies to be distinguished.
ESS / P3O	Effective sample size / Policy-on Policy-off Policy Optimization; batch-ratio reliability controls update influence and regularization.
DPPO / DRPO	Divergence Proximal / Divergence Regularized Policy Optimization; divergence-based masking versus smooth corrective regularization.
MIPI / MIPU	Monotonic Inference Policy Improvement / Update; inference-policy objective and practical candidate construction/acceptance.
Rollout-ResQ	Sparse residual correction of rollout activation quantization; the reviewed HiFloat4 experiments simulate FP4.
TBIK	Tree-Based Invariant Kernels; matched reduction order across tensor-parallel sizes.
Partial rollout	Collection in which a response can span collection boundaries; it does not by itself imply concurrent generation and optimization.
Cache provenance	Parameter versions and numerical execution paths that produced retained cache entries.
Behavior / proximal / reference	Actual sampling law / update-ratio anchor / KL-regularization target; see Table 1.

References

[1] Feng Yao, Liyuan Liu, Dinghuai Zhang, Chengyu Dong, Jingbo Shang, Jianfeng Gao. On the Rollout-Training Mismatch in Modern RL Systems. *OPT 2025: Optimization for Machine Learning*, 2025. https://www.opt-ml.org/papers/2025/paper116.pdf.

[2] Wei Huang, Yi Ge, Shuai Yang, Yicheng Xiao, Huizi Mao, Yujun Lin, Hanrong Ye, Sifei Liu, Ka Chun Cheung, Hongxu Yin, Yao Lu, Xiaojuan Qi, Song Han, Yukang Chen. QeRL: Beyond Efficiency - Quantization-enhanced Reinforcement Learning for LLMs. *International Conference on Learning Representations*, 2026. https://proceedings.iclr.cc/paper_files/paper/2026/hash/a15a2ece7f0663d1ba7db91103ac61c9-Abstract-Conference.html.

[3] Haocheng Xi, Charlie Ruan, Peiyuan Liao, Yujun Lin, Han Cai, Yilong Zhao, Shuo Yang, Kurt Keutzer, Song Han, Ligeng Zhu. Jet-RL: Enabling On-Policy FP8 Reinforcement Learning with Unified Training and Rollout Precision Flow. *arXiv preprint*, 2026. https://arxiv.org/abs/2601.14243v2.

[4] Zhaopeng Qiu, Shuang Yu, Jingqi Zhang, Shuai Zhang, Xue Huang, Jingyi Yang, Junjie Lai. FP8-RL: A Practical and Stable Low-Precision Stack for LLM Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2601.18150v2.

[5] Yuhang Li, Reena Elangovan, Xin Dong, Priyadarshini Panda, Brucek Khailany. QuRL: Low-Precision Reinforcement Learning for Efficient Reasoning. *International Conference on Learning Representations*, 2026. https://proceedings.iclr.cc/paper_files/paper/2026/hash/6b4880ced785077159b340710ceb7681-Abstract-Conference.html.

[6] Hao Gu, Hao Wang, Jiacheng Liu, Lujun Li, Qiyuan Zhu, Bei Liu, Binxing Xu, Lei Wang, Xintong Yang, Sida Lin, Sirui Han, Yike Guo. QaRL: Rollout-Aligned Quantization-Aware RL for Fast and Stable Training under Training–Inference Mismatch. *Findings of the Association for Computational Linguistics: ACL 2026*, 2026. https://aclanthology.org/2026.findings-acl.841/.

[7] Jiajun Zhou, Wei Shao, Lingchao Zheng, Yuwei Fan, Ngai Wong. AIS: Adaptive Importance Sampling for Quantized RL. *arXiv preprint*, 2026. https://arxiv.org/abs/2605.13907v1.

[8] Zhengyang Zhuge, Hao Yu, Xin Wang, Zheng Li, Yizhong Cao, Dayiheng Liu, Jianwei Zhang. QUADS: Stabilizing NVFP4 Reinforcement Learning for MoE via QUantization-error Alignment across Dual Sides. *arXiv preprint*, 2026. https://arxiv.org/abs/2607.15810v1.

[9] Wenwu Fan, Qihong Lin, Zhijie Xia, Zhuo Zheng, Sihao Wang, Qiang Chen, Liangsheng Zhu. ACRL: Adaptive Control of Training-Inference Discrepancy for Stable Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2607.24062v1.

[10] Martin Marek, Max Ryabinin. Score Centering Stabilizes Off-policy Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2609.20807v1.

[11] Fanchao Chen, Ziheng Jiang, Ziyun Wei, Zheng Zhong, Du Li, Chi Zhang, Haibin Lin, Shivaram Venkataraman. Towards Full Pipeline FP8 Reinforcement Learning for LLMs. *arXiv preprint*, 2026. https://arxiv.org/abs/2609.22870v1.

[12] Zhen Li, Shuai Zhang, Yanggan Gu, Yiming Zhang, Yang Yu, Mingfa Feng, Congkai Xie, Shuang Yu, Junjie Lai, Hongxia Yang. TRIAGE: Direction-Aware Mismatch Stabilization of Native NVFP4 Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2610.07043v2.

[13] Xin Wang, Hao Yu, Zhengyang Zhuge, Bochao Mao, Zheng Li, Junda Feng, Yuyan Luo, Yi Zhang, Yizhong Cao, Mi Zhang, Dayiheng Liu, Jianwei Zhang. TRACE: Rollout-Guided Quantization-Aware Training for FP4 Reinforcement Learning of MoE Language Models. *arXiv preprint*, 2026. https://arxiv.org/abs/2610.07767v2.

[14] Chujie Zheng, Kai Dang, Bowen Yu, Mingze Li, Huiqiang Jiang, Junrong Lin, Yuqiong Liu, Hao Lin, Chencan Wu, Feng Hu, An Yang, Jingren Zhou, Junyang Lin. Stabilizing Reinforcement Learning with LLMs: Formulation and Practices. *arXiv preprint*, 2025. https://arxiv.org/abs/2512.01374v3.

[15] Wenhan Ma, Hailin Zhang, Liang Zhao, Yifan Song, Yudong Wang, Zhifang Sui, Fuli Luo. Stabilizing MoE Reinforcement Learning by Aligning Training and Inference Routers. *arXiv preprint*, 2025. https://arxiv.org/abs/2510.11370v2.

[16] Penghui Qi, Zichen Liu, Xiangxin Zhou, Tianyu Pang, Chao Du, Wee Sun Lee, Min Lin. Defeating the Training-Inference Mismatch via FP16. *arXiv preprint*, 2025. https://arxiv.org/abs/2510.26788v1.

[17] Sihwan Park, Sung-Yub Kim, Doohyuk Jang, Eunho Yang. KV4-RL: Unlocking Faster Asynchronous Rollouts for RLVR with INT4 KV Cache Quantization. *arXiv preprint*, 2026. https://arxiv.org/abs/2610.14448v1.

[18] Yaxiang Zhang, Yingru Li, Jiacai Liu, Jiawei Xu, Ziniu Li, Qian Liu, Haoyuan Li. Beyond Precision: Training-Inference Mismatch is an Optimization Problem and Simple LR Scheduling Fixes It. *arXiv preprint*, 2026. https://arxiv.org/abs/2602.01826v1.

[19] Tianle Zhong, Neiwen Ling, Yifan Pi, Zijun Wei, Tianshu Yu, Geoffrey Fox, Peng Wu, Xiao Yu. Diagnosing Training Inference Mismatch in LLM Reinforcement Learning via a Zero-Mismatch Reference. *arXiv preprint*, 2026. https://arxiv.org/abs/2605.14220v2.

[20] Tianrun Yu, Kaixiang Zhao, Shangzhe Li, Yuxiao Yang, Porter Jenkins, Weitong Zhang, Taylor W. Killian. Rethinking Training-Inference Mismatch in LLM Reinforcement Learning: Where It Arises and How to Correct It. *arXiv preprint*, 2026. https://arxiv.org/abs/2609.32444v1.

[21] Rasool Fakoor, Murdock Aubry, Nicholas Stranges, Alexander J. Smola. Let the Batch Decide, On- or Off-Policy: Effective Sample Size for RL Post-Training. *arXiv preprint*, 2026. https://arxiv.org/abs/2605.12380v2.

[22] Jiarui Yao, Xiangxin Zhou, Penghui Qi, Wee Sun Lee, Liefeng Bo, Tianyu Pang. Rethinking the Divergence Regularization in LLM RL. *arXiv preprint*, 2026. https://arxiv.org/abs/2606.09821v1.

[23] Jing Liang, Hongyao Tang, Yi Ma, Yancheng He, Weixun Wang, Xiaoyang Li, Ju Huang, Wenbo Su, Jinyi Liu, Yan Zheng, Jianye Hao, Bo Zheng. The Mirage of Optimizing Training Policies: Monotonic Inference Policies as the Real Objective for LLM Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2606.29526v1.

[24] Hei Yi Mak, Shadan Golestan, Hoang Le, Mehran Taghian Jazi, Yunke Peng, Yaoyuan Wang, Yao Wang, Junsong Wang, Tianchi Hu, Fengchen He, Guipeng Hu, Tanzila Rahman, Anandharaju Durai Raju. HiFloat4 Format for End-To-End Reinforcement Learning Post-Training of Large Language Models. *arXiv preprint*, 2026. https://arxiv.org/abs/2607.26515v1.

[25] RadixArk, Tom Chen, Mao Cheng, Shi Dong, Kangrui Du, Yanbin Jiang, Jiajun Li, Yiming Li, Tao Lin, Yusheng Su, Andy Ye, Yueming Yuan, Zhichen Zeng. Miles v0.1: Production-Level Post-Training. *arXiv preprint*, 2026. https://arxiv.org/abs/2609.08368v1.

[26] Weili Xu, Jisen Li, Yuqing Jian, Chenxi Li, Zhizhou Sha, Yifan Yu, Qingyang Wu, Chenfeng Xu, Zhongzhu Zhou, Tianyi Zhang, Ben Athiwaratkun. QATFactory: A Versatile, Deployment-Aligned Framework for Quantization-aware Training and Distillation of LLMs. *arXiv preprint*, 2026. https://arxiv.org/abs/2609.39223v2.

[27] Shuo Han, Ziqing Hu. Baselines and Score Centering in Policy Gradient Estimation. *arXiv preprint*, 2026. https://arxiv.org/abs/2610.22263v1.

[28] Ziyang Zhang, Xinheng Ding, Jiayi Yuan, Rixin Liu, Huizi Mao, Jiarong Xing, Zirui Liu. Deterministic Inference across Tensor Parallel Sizes That Eliminates Training-Inference Mismatch. *arXiv preprint*, 2025. https://arxiv.org/abs/2511.17826v2.

[29] Penghui Qi, Xiangxin Zhou, Zichen Liu, Tianyu Pang, Chao Du, Min Lin, Wee Sun Lee. Rethinking the Trust Region in LLM Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2602.04879v3.

[30] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, Oleg Klimov. Proximal Policy Optimization Algorithms. *arXiv preprint*, 2017. https://arxiv.org/abs/1707.06347.

[31] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, Daya Guo. DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models. *arXiv preprint*, 2024. https://arxiv.org/abs/2402.03300.

[32] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, Ion Stoica. Efficient Memory Management for Large Language Model Serving with PagedAttention. *arXiv preprint*, 2023. https://arxiv.org/abs/2309.06180.

[33] Zhiwei Hao, Jianyuan Guo, Li Shen, Yong Luo, Han Hu, Guoxia Wang, Dianhai Yu, Yonggang Wen, Dacheng Tao. Low-Precision Training of Large Language Models: Methods, Challenges, and Opportunities. *arXiv preprint*, 2025. https://arxiv.org/abs/2505.01043.

[34] Rohan Surana, Gagan Mundada, Xunyi Jiang, Chuhan Wang, Zhenwei Tang, Difan Jiao, Zihan Huang, Yuxin Xiong, Junda Wu, Sheldon Yu, Xintong Li, Raghav Jain, Nikki Kuang, Sizhe Zhou, Bowen Jin, Zhendong Chu, Tong Yu, Ryan Rossi, Kuan-Hao Huang, Jingbo Shang, Jiawei Han, Julian McAuley. Generate, Filter, Control, Replay: A Comprehensive Survey of Rollout Strategies for LLM Reinforcement Learning. *arXiv preprint*, 2026. https://arxiv.org/abs/2605.02913.

[35] Kaiyan Zhang, Yuxin Zuo, Bingxiang He, Youbang Sun, Runze Liu, Che Jiang, Yuchen Fan, Kai Tian, Guoli Jia, Pengfei Li, Yu Fu, Xingtai Lv, Yuchen Zhang, Sihang Zeng, Shang Qu, Haozhan Li, Shijie Wang, Yuru Wang, Xinwei Long, Fangfu Liu, Xiang Xu, Jiaze Ma, Xuekai Zhu, Ermo Hua, Yihao Liu, Zonglin Li, Huayu Chen, Xiaoye Qu, Yafu Li, Weize Chen, Zhenzhao Yuan, Junqi Gao, Dong Li, Zhiyuan Ma, Ganqu Cui, Zhiyuan Liu, Biqing Qi, Ning Ding, Bowen Zhou. A Survey of Reinforcement Learning for Large Reasoning Models. *arXiv preprint*, 2025. https://arxiv.org/abs/2509.08827.