

Contents

Authentication API Reference	2
Table of Contents	2
Overview	2
Base URLs	2
Authentication Methods	2
Common Headers	2
Rate Limits	3
Authentication	3
Get Current User	3
Sign In / Sign Out	3
Sign In with Email/Password	3
Sign In with SSO	4
SSO Callback	5
Sign Out	5
Refresh Token	5
Password Management	6
Request Password Reset	6
Reset Password	6
Change Password	6
Validate Password Strength	7
Multi-Factor Authentication	7
Get MFA Status	7
Setup TOTP	8
Verify and Enable TOTP	8
Verify MFA Code (During Sign-In)	9
Use Backup Code	9
Regenerate Backup Codes	10
Disable MFA	10
Get Trusted Devices	10
Remove Trusted Device	11
Session Management	11
List Active Sessions	11
Revoke Session	12
Revoke All Other Sessions	12
OAuth 2.0 Endpoints	12
Authorization Endpoint	12
Token Endpoint	13
Token Introspection	14
Token Revocation	14
UserInfo Endpoint (OIDC)	14
User Profile	15
Update Profile	15
Update Avatar	15
Error Responses	15
Error Format	15
Error Codes	16

Validation Errors	16
Related Documentation	16

Authentication API Reference

Version: 5.52.29 | **Last Updated:** January 25, 2026 | **Base URL:** <https://api.radiant.ai/v1>

Complete API reference for RADIANT authentication endpoints.

Table of Contents

- [1. Overview](#)
 - [2. Authentication](#)
 3. Sign In / Sign Out
 - [4. Password Management](#)
 - [5. Multi-Factor Authentication](#)
 - [6. Session Management](#)
 7. OAuth 2.0 Endpoints
 - [8. User Profile](#)
 - [9. Error Responses](#)
-

Overview

Base URLs

Environment	URL
Production	https://api.radiant.ai/v1
Staging	https://api.staging.radiant.ai/v1

Authentication Methods

Method	Header	Use Case
Bearer Token	Authorization: Bearer <token>	User requests
API Key	X-API-Key: <key>	Server-to-server

Common Headers

Content-Type: application/json
 Accept: application/json
 Authorization: Bearer eyJhbGciOiJSUzI1NiIs...
 X-Request-ID: uuid-for-tracing

Rate Limits

Endpoint Category	Limit	Window
Authentication	10 requests	1 minute
Password reset	3 requests	1 hour
MFA verification	5 requests	1 minute
General API	100 requests	1 minute

Authentication

Get Current User

Retrieve the authenticated user's profile.

GET /auth/me

Authorization: Bearer <access_token>

Response 200:

```
{
  "id": "usr_abc123def456",
  "email": "user@example.com",
  "name": "Jane Doe",
  "avatar_url": "https://cdn.radiant.ai/avatars/abc123.png",
  "tenant_id": "ten_xyz789",
  "roles": ["member"],
  "mfa_enabled": true,
  "language": "en",
  "timezone": "America/New_York",
  "created_at": "2024-01-15T10:30:00Z",
  "last_sign_in_at": "2026-01-25T08:00:00Z"
}
```

Sign In / Sign Out

Sign In with Email/Password

POST /auth/signin

Content-Type: application/json

Request Body:

```
{
  "email": "user@example.com",
  "password": "SecurePassword123!",
  "remember_me": true
}
```

Response 200 (Success):

```
{
  "access_token": "eyJhbGciOiJSUzI1NiIs...\"",
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2g...",
  "token_type": "Bearer",
  "expires_in": 3600,
  "user": {
    "id": "usr_abc123def456",
    "email": "user@example.com",
    "name": "Jane Doe"
  }
}
```

Response 200 (MFA Required):

```
{
  "challenge": "MFA_REQUIRED",
  "session": "session_token_for_mfa",
  "mfa_methods": ["totp", "backup_code"]
}
```

Response 401:

```
{
  "error": "invalid_credentials",
  "message": "Invalid email or password"
}
```

Sign In with SSO

Initiate SSO sign-in flow.

POST /auth/sso/initiate

Content-Type: application/json

Request Body:

```
{
  "email": "user@company.com"
}
```

Response 200:

```
{
  "sso_url": "https://idp.company.com/saml/sso?SAMLRequest=...",
  "provider": "saml",
  "provider_name": "Company SSO"
}
```

Response 200 (No SSO):

```
{
  "sso_enabled": false,
}
```

```
  "message": "No SSO configured for this domain"
}
```

SSO Callback

Handle SSO provider callback (internal use).

POST /auth/sso/callback

Content-Type: application/x-www-form-urlencoded

Sign Out

POST /auth/signout

Authorization: Bearer <access_token>

Request Body (optional):

```
{
  "all_devices": false
}
```

Response 200:

```
{
  "success": true,
  "message": "Signed out successfully"
}
```

Refresh Token

Exchange refresh token for new access token.

POST /auth/refresh

Content-Type: application/json

Request Body:

```
{
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2g..."
}
```

Response 200:

```
{
  "access_token": "eyJhbGciOiJSUzI1NiIs...",
  "refresh_token": "bmV3IHJlZnJlc2ggdG9rZW4...",
  "token_type": "Bearer",
  "expires_in": 3600
}
```

Password Management

Request Password Reset

POST /auth/password/forgot

Content-Type: application/json

Request Body:

```
{  
  "email": "user@example.com"  
}
```

Response 200:

```
{  
  "success": true,  
  "message": "If an account exists, a reset link has been sent"  
}
```

Note: Always returns success to prevent email enumeration.

Reset Password

POST /auth/password/reset

Content-Type: application/json

Request Body:

```
{  
  "token": "reset_token_from_email",  
  "password": "NewSecurePassword123!",  
  "password_confirmation": "NewSecurePassword123!"  
}
```

Response 200:

```
{  
  "success": true,  
  "message": "Password reset successfully"  
}
```

Response 400:

```
{  
  "error": "invalid_token",  
  "message": "Reset token is invalid or expired"  
}
```

Change Password

POST /auth/password/change

Authorization: Bearer <access_token>

Content-Type: application/json

Request Body:

```
{
  "current_password": "OldPassword123!",
  "new_password": "NewSecurePassword456!",
  "new_password_confirmation": "NewSecurePassword456!"
}
```

Response 200:

```
{
  "success": true,
  "message": "Password changed successfully",
  "sessions_revoked": true
}
```

Validate Password Strength

POST /auth/password/validate

Content-Type: application/json

Request Body:

```
{
  "password": "TestPassword123!"
}
```

Response 200:

```
{
  "valid": true,
  "score": 4,
  "requirements": {
    "min_length": { "required": 12, "met": true },
    "uppercase": { "required": true, "met": true },
    "lowercase": { "required": true, "met": true },
    "number": { "required": true, "met": true },
    "special": { "required": true, "met": true }
  },
  "suggestions": []
}
```

Multi-Factor Authentication

Get MFA Status

GET /auth/mfa/status

Authorization: Bearer <access_token>

Response 200:

```
{
  "enabled": true,
  "methods": [
    {
      "type": "totp",
      "enabled": true,
      "configured_at": "2024-06-15T10:30:00Z"
    }
  ],
  "backup_codes_remaining": 8,
  "trusted_devices": 2
}
```

Setup TOTP

POST /auth/mfa/totp/setup
 Authorization: Bearer <access_token>

Response 200:

```
{
  "secret": "JBSWY3DPEHPK3PXP",
  "qr_code": "...",
  "otpauth_uri": "otpauth://totp/RADIANT:user@example.com?secret=JBSWY3DPEHPK3PXP&issuer=RADIANT"
}
```

Verify and Enable TOTP

POST /auth/mfa/totp/verify
 Authorization: Bearer <access_token>
 Content-Type: application/json

Request Body:

```
{
  "code": "123456"
}
```

Response 200:

```
{
  "success": true,
  "backup_codes": [
    "ABCD1234",
    "EFGH5678",
    "IJKL9012",
    "MNOP3456",
    "QRST7890",
    "UVWX1234",
    "YZAB5678",
    "CDEF9012",
  ]
}
```



```

    "GHIJ3456",
    "KLMN7890"
  ],
  "message": "MFA enabled. Save your backup codes securely."
}

```

Verify MFA Code (During Sign-In)

POST /auth/mfa/verify
 Content-Type: application/json

Request Body:

```

{
  "session": "session_token_from_signin",
  "code": "123456",
  "trust_device": true
}

```

Response 200:

```

{
  "access_token": "eyJhbGciOiJSUzI1NiIs...",
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2g...",
  "token_type": "Bearer",
  "expires_in": 3600,
  "device_trusted": true
}

```

Use Backup Code

POST /auth/mfa/backup/verify
 Content-Type: application/json

Request Body:

```

{
  "session": "session_token_from_signin",
  "backup_code": "ABCD1234"
}

```

Response 200:

```

{
  "access_token": "eyJhbGciOiJSUzI1NiIs...",
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2g...",
  "backup_codes_remaining": 7,
  "message": "Backup code used. 7 codes remaining."
}

```

Regenerate Backup Codes

POST /auth/mfa/backup/regenerate
Authorization: Bearer <access_token>
Content-Type: application/json

Request Body:

```
{  
  "mfa_code": "123456"  
}
```

Response 200:

```
{  
  "backup_codes": [  
    "NEWC1234",  
    "ODES5678",  
    "..."  
  ],  
  "message": "New backup codes generated. Previous codes are now invalid."  
}
```

Disable MFA

POST /auth/mfa/disable
Authorization: Bearer <access_token>
Content-Type: application/json

Request Body:

```
{  
  "mfa_code": "123456",  
  "password": "CurrentPassword123!"  
}
```

Response 200:

```
{  
  "success": true,  
  "message": "MFA disabled"  
}
```

Response 403:

```
{  
  "error": "mfa_required",  
  "message": "MFA cannot be disabled for your account type"  
}
```

Get Trusted Devices

GET /auth/mfa/devices
Authorization: Bearer <access_token>

Response 200:

```
{
  "devices": [
    {
      "id": "dev_abc123",
      "name": "Chrome on MacOS",
      "last_used": "2026-01-25T08:00:00Z",
      "trusted_at": "2026-01-20T10:00:00Z",
      "expires_at": "2026-02-19T10:00:00Z",
      "current": true
    },
    {
      "id": "dev_def456",
      "name": "Safari on iPhone",
      "last_used": "2026-01-24T15:30:00Z",
      "trusted_at": "2026-01-15T09:00:00Z",
      "expires_at": "2026-02-14T09:00:00Z",
      "current": false
    }
  ]
}
```

Remove Trusted Device

DELETE /auth/mfa/devices/{device_id}
Authorization: Bearer <access_token>

Response 200:

```
{
  "success": true,
  "message": "Device removed from trusted list"
}
```

Session Management

List Active Sessions

GET /auth/sessions
Authorization: Bearer <access_token>

Response 200:

```
{
  "sessions": [
    {
      "id": "sess_abc123",
      "device": "Chrome on MacOS",
      "ip_address": "192.168.1.100",
```

```

    "location": "New York, US",
    "created_at": "2026-01-20T10:00:00Z",
    "last_activity": "2026-01-25T08:30:00Z",
    "current": true
  },
  {
    "id": "sess_def456",
    "device": "Safari on iPhone",
    "ip_address": "10.0.0.50",
    "location": "New York, US",
    "created_at": "2026-01-22T14:00:00Z",
    "last_activity": "2026-01-24T18:00:00Z",
    "current": false
  }
]
}

```

Revoke Session

```

DELETE /auth/sessions/{session_id}
Authorization: Bearer <access_token>

```

Response 200:

```

{
  "success": true,
  "message": "Session revoked"
}

```

Revoke All Other Sessions

```

POST /auth/sessions/revoke-others
Authorization: Bearer <access_token>

```

Response 200:

```

{
  "success": true,
  "revoked_count": 3,
  "message": "3 sessions revoked"
}

```

OAuth 2.0 Endpoints

Authorization Endpoint

```

GET /oauth/authorize

```

Query Parameters:

Parameter	Required	Description
client_id	Yes	Application client ID
redirect_uri	Yes	Callback URL (must match registration)
response_type	Yes	code
scope	Yes	Space-separated scopes
state	Yes	CSRF protection token
code_challenge	Yes*	PKCE challenge (S256)
code_challenge_method	Yes*	S256

Example:

GET /oauth/authorize?client_id=app_123&redirect_uri=https://myapp.com/callback&response_type=c

Token Endpoint

POST /oauth/token

Content-Type: application/x-www-form-urlencoded

Authorization Code Grant:

```
grant_type=authorization_code
&code=AUTH_CODE
&redirect_uri=https://myapp.com/callback
&client_id=app_123
&client_secret=secret_456
&code_verifier=PKCE_VERIFIER
```

Refresh Token Grant:

```
grant_type=refresh_token
&refresh_token=REFRESH_TOKEN
&client_id=app_123
&client_secret=secret_456
```

Client Credentials Grant:

```
grant_type=client_credentials
&client_id=app_123
&client_secret=secret_456
&scope=read:data
```

Response 200:

```
{
  "access_token": "eyJhbGciOiJSUzI1NiIs... ",
  "token_type": "Bearer",
  "expires_in": 3600,
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2g...",
  "scope": "openid profile"
}
```

Token Introspection

POST /oauth/introspect

Content-Type: application/x-www-form-urlencoded

Authorization: Basic base64(client_id:client_secret)

Request:

token=ACCESS_TOKEN

Response 200:

```
{
  "active": true,
  "client_id": "app_123",
  "scope": "openid profile",
  "sub": "usr_abc123",
  "exp": 1706234567,
  "iat": 1706230967,
  "token_type": "Bearer"
}
```

Token Revocation

POST /oauth/revoke

Content-Type: application/x-www-form-urlencoded

Authorization: Basic base64(client_id:client_secret)

Request:

token=REFRESH_TOKEN

&token_type_hint=refresh_token

Response 200:

```
{
  "success": true
}
```

UserInfo Endpoint (OIDC)

GET /oauth/userinfo

Authorization: Bearer <access_token>

Response 200:

```
{
  "sub": "usr_abc123def456",
  "name": "Jane Doe",
  "given_name": "Jane",
  "family_name": "Doe",
  "email": "user@example.com",
  "email_verified": true,
}
```

```
  "picture": "https://cdn.radiant.ai/avatars/abc123.png"
}
```

User Profile

Update Profile

PATCH /auth/profile
Authorization: Bearer <access_token>
Content-Type: application/json

Request Body:

```
{
  "name": "Jane Smith",
  "language": "es",
  "timezone": "Europe/Madrid"
}
```

Response 200:

```
{
  "id": "usr_abc123def456",
  "email": "user@example.com",
  "name": "Jane Smith",
  "language": "es",
  "timezone": "Europe/Madrid",
  "updated_at": "2026-01-25T10:00:00Z"
}
```

Update Avatar

POST /auth/profile/avatar
Authorization: Bearer <access_token>
Content-Type: multipart/form-data

Request:

avatar: (binary file, max 5MB, PNG/JPG/GIF)

Response 200:

```
{
  "avatar_url": "https://cdn.radiant.ai/avatars/new_abc123.png"
}
```

Error Responses

Error Format

All errors follow this format:

```
{
  "error": "error_code",
  "message": "Human-readable message",
  "details": { },
  "request_id": "req_abc123"
}
```

Error Codes

Code	HTTP Status	Description
invalid_credentials	401	Email or password incorrect
account_locked	403	Too many failed attempts
account_suspended	403	Account has been suspended
mfa_required	401	MFA verification needed
mfa_invalid	401	MFA code incorrect
session_expired	401	Session has expired
token_invalid	401	Token is invalid or expired
token_revoked	401	Token has been revoked
insufficient_scope	403	Token lacks required scope
rate_limited	429	Too many requests
invalid_request	400	Request validation failed
not_found	404	Resource not found
server_error	500	Internal server error

Validation Errors

```
{
  "error": "validation_error",
  "message": "Validation failed",
  "details": {
    "fields": {
      "email": ["Invalid email format"],
      "password": ["Must be at least 12 characters"]
    }
  }
}
```

Related Documentation

- [Authentication Overview](#)
- [OAuth Developer Guide](#)
- [Security Architecture](#)