

Contents

RADIANT v4.18.0 - Lambda Handlers Export	1
Architecture Narrative	1
Lambda Organization	1
Handler Patterns	2
Key Lambda Implementations	2
1. brain/inference.ts	2
2. api/router.ts	6
Lambda Handler Inventory	9
Admin Handlers (48 files)	9
Think Tank Handlers (12 files)	9
Consciousness Handlers (9 files)	10
Billing Handlers (3 files)	10
Security Handlers (3 files)	10
Thermal Handlers (5 files)	11
Tier Transition Handlers (20 files)	11
Shared Utilities (344 files)	11
Database (shared/db/)	11
Services (shared/services/)	11
Utilities (shared/utills/)	11
Logging (shared/logging/)	12
Handler Patterns	12
Standard API Handler	12
SQS Event Handler	12
Scheduled Event Handler	13

RADIANT v4.18.0 - Lambda Handlers Export

Component: AWS Lambda Functions **Language:** TypeScript (Node.js 20.x), Python 3.11 **Files:** 100+ Lambda handlers across 48 directories **Runtime:** AWS Lambda

Architecture Narrative

RADIANT's backend logic is implemented as **AWS Lambda functions** organized into logical domains. Each Lambda handles specific functionality and communicates through API Gateway, SQS queues, or direct invocation.

Lambda Organization

```
lambda/
  admin/          # 48 admin API handlers
  api/            # 4 public API handlers
  brain/          # 3 AGI Brain handlers
  thinktank/      # 12 Think Tank handlers
  consciousness/  # 9 consciousness engine handlers
  billing/        # 3 billing handlers
```

security/	# 3 security handlers
scheduled/	# 3 scheduled task handlers
collaboration/	# 4 real-time collaboration handlers
thermal/	# 5 thermal management handlers
tier-transition/	# 20 tier upgrade handlers
shared/	# 344 shared utilities/services
...	# 20+ additional domains

Handler Patterns

1. **API Gateway Integration** - REST/WebSocket event handling
 2. **SQS Event Source** - Queue-triggered processing
 3. **EventBridge Scheduled** - Cron-based tasks
 4. **Direct Invocation** - Lambda-to-Lambda calls
-

Key Lambda Implementations

1. brain/inference.ts

Purpose: Main entry point for AGI Brain inference requests. Orchestrates Ghost Vector loading, SOFAI routing, context assembly, and LLM calls.

```
/**
 * RADIANT v6.0.4 - Brain Inference Lambda
 * Main entry point for AGI Brain inference requests
 *
 * Orchestrates:
 * - Ghost Vector loading/saving
 * - SOFAI routing
 * - Context assembly (Compliance Sandwich)
 * - Flash fact detection
 * - Async re-anchoring
 */

import { APIGatewayProxyEvent, APIGatewayProxyResult } from 'aws-lambda';
import { v4 as uuidv4 } from 'uuid';
import Redis from 'ioredis';
import { enhancedLogger as logger } from '../shared/logging/enhanced-logger';
import { executeStatement } from '../shared/db/client';
import { brainConfigService } from '../shared/services/brain-config.service';
import { ghostManagerService } from '../shared/services/ghost-manager.service';
import { flashBufferService } from '../shared/services/flash-buffer.service';
import { sofaiRouterService } from '../shared/services/sofai-router.service';
import { contextAssemblerService } from '../shared/services/context-assembler.service';
import { oversightService } from '../shared/services/oversight.service';
import {
  BrainInferenceRequest,
  BrainInferenceResponse,
```

```

    SystemLevel,
    ConversationMessage,
} from '@radiant/shared';
import { embeddingService } from '../shared/services/embedding.service';
import { ecdVerificationService } from '../shared/services/ecd-verification.service';

let redisClient: Redis | null = null;
let servicesInitialized = false;

async function initializeServices(): Promise<void> {
    if (servicesInitialized) return;

    const redisUrl = process.env.REDIS_URL || process.env.REDIS_ENDPOINT;
    if (redisUrl && !redisClient) {
        try {
            redisClient = new Redis(redisUrl);
            redisClient.on('error', (err) => {
                logger.error('Redis connection error', { error: String(err) });
            });

            // Initialize services with Redis client
            const redisAdapter = {
                get: async (key: string) => redisClient?.get(key) ?? null,
                set: async (key: string, value: string, options?: { EX?: number }) => {
                    if (options?.EX) {
                        await redisClient?.setex(key, options.EX, value);
                    } else {
                        await redisClient?.set(key, value);
                    }
                },
                lpush: async (key: string, ...values: string[]) => redisClient?.lpush(key, ...values),
                lrange: async (key: string, start: number, stop: number) => redisClient?.lrange(key, start, stop),
                ltrim: async (key: string, start: number, stop: number) => { await redisClient?.ltrim(key, start, stop); },
                expire: async (key: string, seconds: number) => { await redisClient?.expire(key, seconds); },
                del: async (key: string) => { await redisClient?.del(key); },
            };

            flashBufferService.initialize(redisAdapter);
            ghostManagerService.initialize(redisAdapter);
            logger.info('Brain services initialized with Redis');
        } catch (err) {
            logger.warn('Redis unavailable, services running without cache', { error: String(err) });
        }
    }

    servicesInitialized = true;
}

```

```

export async function handler(event: APIGatewayProxyEvent): Promise<APIGatewayProxyResult> {
  const startTime = Date.now();
  const requestId = uuidv4();

  await initializeServices();

  try {
    if (!event.body) {
      return error(400, 'Request body is required');
    }

    const request: BrainInferenceRequest = JSON.parse(event.body);
    const { userId, tenantId, prompt, conversationHistory, domain, forceSystemLevel, options }

    if (!userId || !tenantId || !prompt) {
      return error(400, 'userId, tenantId, and prompt are required');
    }

    logger.info('Brain inference started', { requestId, userId, tenantId, promptLength: prompt

    // Set tenant context for RLS
    await executeStatement(`SELECT set_config('app.current_tenant_id', $1, true)`, [
      { name: 'tenantId', value: { stringValue: tenantId } },
    ]);

    // Step 1: Load Ghost Vector
    let ghostVector: Float32Array | null = null;
    let ghostUpdated = false;

    if (options?.includeGhost !== false) {
      const ghostResult = await ghostManagerService.loadGhost(userId, tenantId);
      if (ghostResult.found && ghostResult.versionMatch) {
        ghostVector = ghostResult.vector;
      }
    }

    // Step 2: SOFAI Routing
    const routingDecision = await sofaiRouterService.route({
      prompt,
      userId,
      tenantId,
      domain,
      forceLevel: forceSystemLevel,
    });

    // Step 3: Assemble Context (Compliance Sandwich)
    const assembledContext = await contextAssemblerService.assemble({
      userId,

```

```

    tenantId,
    prompt,
    conversationHistory: conversationHistory as ConversationMessage[],
    ghostVector,
    domain: domain || sofaiRouterService.detectDomain(prompt),
  });

// Step 4: Call LLM with ECD Verification (Truth Engine)
const verificationResult = await ecdVerificationService.executeWithVerification({
  userId,
  tenantId,
  requestId,
  prompt,
  sourceContext: assembledContext.userContext,
  flashFacts: assembledContext.flashFacts.map(f => f.fact),
  retrievedDocs: [],
  domain: domain || sofaiRouterService.detectDomain(prompt),
  generateResponse: async (refinedPrompt: string) => {
    const result = await callLLM(
      contextAssemblerService.formatForModel({
        ...assembledContext,
        userContext: refinedPrompt,
      }),
      routingDecision.level,
      options
    );
    return result.response;
  },
});

// Step 5: Detect Flash Facts
const flashFactsDetected = flashBufferService.detectFlashFacts(prompt);
if (flashFactsDetected.detected) {
  for (const fact of flashFactsDetected.facts) {
    await flashBufferService.storeFact(userId, tenantId, fact);
  }
}

// Step 6: Check for Re-anchoring (async)
if (options?.includeGhost !== false) {
  const needsReanchor = await ghostManagerService.checkReAnchorNeeded(userId, tenantId);
  if (needsReanchor) {
    ghostManagerService.reAnchorAsync(userId, tenantId, [prompt], async (history) => {
      const combinedText = history.join(' ').slice(0, 8000);
      const result = await embeddingService.generateEmbedding(combinedText);
      return new Float32Array(result.embedding);
    });
    ghostUpdated = true;
  }
}

```

```

    }
  }

  // Build Response
  const response: BrainInferenceResponse = {
    response: verificationResult.finalResponse,
    systemLevel: routingDecision.level,
    routingDecision,
    budget: assembledContext.budget,
    ghostUpdated,
    flashFactsDetected,
    latencyMs: Date.now() - startTime,
    verification: {
      passed: verificationResult.passed,
      ecdScore: verificationResult.ecdScore.score,
      refinementAttempts: verificationResult.refinementAttempts,
      blocked: verificationResult.blocked,
    },
  };

  return success(response);
} catch (err) {
  logger.error('Brain inference failed', { requestId, error: String(err) });
  return error(500, `Inference failed: ${String(err)}`);
}
}

```

2. api/router.ts

Purpose: Main API router that dispatches requests to appropriate handlers based on HTTP method and path.

```

/**
 * API Router Lambda Handler
 * Main entry point for all API requests
 */

import type { APIGatewayProxyEvent, APIGatewayProxyResult, Context } from 'aws-lambda';
import { Logger } from '../shared/logger';
import { successResponse, errorResponse } from '../shared/response';
import { UnauthorizedError, NotFoundError, ValidationError } from '../shared/errors';
import { extractUserFromEvent } from '../shared/auth';
import { handleChat } from './chat';
import { handleModels } from './models';
import { handleProviders } from './providers';

const logger = new Logger({ handler: 'router' });

```

```

interface RouteHandler {
  (event: APIGatewayProxyEvent, context: Context): Promise<APIGatewayProxyResult>;
}

const routes: Map<string, Map<string, RouteHandler>> = new Map();

function registerRoute(method: string, pathPattern: string, handler: RouteHandler): void {
  if (!routes.has(method)) {
    routes.set(method, new Map());
  }
  routes.get(method)!.set(pathPattern, handler);
}

// Register routes
registerRoute('GET', '/api/v2/health', handleHealth);
registerRoute('POST', '/api/v2/chat/completions', handleChat);
registerRoute('GET', '/api/v2/models', handleModels);
registerRoute('GET', '/api/v2/models/{modelId}', handleModels);
registerRoute('GET', '/api/v2/providers', handleProviders);
registerRoute('POST', '/api/v2/usage', handleUsage);

export async function handler(
  event: APIGatewayProxyEvent,
  context: Context
): Promise<APIGatewayProxyResult> {
  const requestId = event.requestContext.requestId;
  logger.setRequestId(requestId);

  const startTime = Date.now();
  const method = event.httpMethod;
  const path = event.path;

  logger.info('Request received', { method, path, requestId });

  try {
    // Skip auth for health and usage endpoints
    if (path !== '/api/v2/health' && path !== '/api/v2/usage') {
      const user = await extractUserFromEvent(event);
      if (!user) {
        throw new UnauthorizedError('Invalid or missing authorization token');
      }
      logger.setTenantId(user.tenantId);
      logger.setUserId(user.userId);
    }

    const routeHandler = findRouteHandler(method, path);
    if (!routeHandler) {

```

```

        throw new NotFoundError(`Route not found: ${method} ${path}`);
    }

    const result = await routeHandler(event, context);

    logger.info('Request completed', {
        method,
        path,
        statusCode: result.statusCode,
        durationMs: Date.now() - startTime,
    });

    return result;
} catch (error) {
    logger.error('Request failed', error as Error, {
        method,
        path,
        durationMs: Date.now() - startTime,
    });

    return ErrorResponse(error as Error);
}

function findRouteHandler(method: string, path: string): RouteHandler | null {
    const methodRoutes = routes.get(method);
    if (!methodRoutes) return null;

    for (const [pattern, handler] of methodRoutes) {
        if (matchPath(pattern, path)) {
            return handler;
        }
    }
    return null;
}

function matchPath(pattern: string, path: string): boolean {
    const patternParts = pattern.split('/');
    const pathParts = path.split('/');

    if (patternParts.length !== pathParts.length) return false;

    for (let i = 0; i < patternParts.length; i++) {
        const patternPart = patternParts[i];
        const pathPart = pathParts[i];

        // Skip path parameters (e.g., {modelId})
        if (patternPart.startsWith('{') && patternPart.endsWith('}')) continue;

```



```

    if (patternPart !== pathPart) return false;
  }

  return true;
}

async function handleHealth(): Promise<APIGatewayProxyResult> {
  return successResponse({
    status: 'healthy',
    version: process.env.RADIANT_VERSION || 'unknown',
    timestamp: new Date().toISOString(),
    region: process.env.AWS_REGION,
  });
}

async function handleUsage(event: APIGatewayProxyEvent): Promise<APIGatewayProxyResult> {
  const body = JSON.parse(event.body || '{}');
  logger.info('Usage event recorded', {
    tenantId: body.tenant_id,
    modelId: body.model_id,
    tokens: body.total_tokens,
  });
  return successResponse({ recorded: true });
}

```

Lambda Handler Inventory

Admin Handlers (48 files)

Handler	Purpose
admin/users.ts	User management CRUD
admin/tenants.ts	Tenant management
admin/models.ts	AI model configuration
admin/providers.ts	Provider management
admin/billing.ts	Billing administration
admin/analytics.ts	Usage analytics
admin/security.ts	Security settings
admin/compliance.ts	Compliance controls
admin/domains.ts	Domain configuration
admin/tiers.ts	Tier management
...	38 more handlers

Think Tank Handlers (12 files)

Handler	Lines	Purpose
thinktank/artifact-engine.ts	17K	Artifact generation and management
thinktank/brain-plan.ts	15K	Brain planning and orchestration
thinktank/conversations.ts	9K	Conversation management
thinktank/derivation-history.ts	11K	Derivation tracking
thinktank/domain-modes.ts	11K	Domain mode handling
thinktank/file-conversion.ts	13K	File format conversion
thinktank/ideas.ts	6K	Idea management
thinktank/model-categories.ts	7K	Model categorization
thinktank/models.ts	20K	Model operations
thinktank/ratings.ts	13K	Rating system
thinktank/user-context.ts	15K	User context management
thinktank/users.ts	11K	Think Tank user operations

Consciousness Handlers (9 files)

Handler	Purpose
consciousness/mcp-server.ts	Model Context Protocol server
consciousness/sleep-cycle.ts	Weekly consciousness evolution
consciousness/deep-research.ts	Browser automation research
consciousness/thinking-session.ts	Async thinking sessions
consciousness/budget-monitor.ts	Cost control
consciousness/admin-api.ts	Consciousness admin APIs
consciousness/memory-consolidation.ts	Memory processing
consciousness/dream-generator.ts	Dream state generation
consciousness/parameter-sync.ts	Parameter synchronization

Billing Handlers (3 files)

Handler	Purpose
billing/credits.ts	Credit management
billing/subscriptions.ts	Subscription handling
billing/invoices.ts	Invoice generation

Security Handlers (3 files)

Handler	Purpose
security/audit.ts	Audit log management
security/rbac.ts	Role-based access control
security/compliance.ts	Compliance checking

Thermal Handlers (5 files)

Handler	Purpose
<code>thermal/monitor.ts</code>	System thermal monitoring
<code>thermal/throttle.ts</code>	Throttling control
<code>thermal/cooldown.ts</code>	Cooldown management
<code>thermal/alerts.ts</code>	Thermal alerting
<code>thermal/metrics.ts</code>	Thermal metrics

Tier Transition Handlers (20 files)

Handler	Purpose
<code>tier-transition/evaluate.ts</code>	Tier eligibility evaluation
<code>tier-transition/migrate.ts</code>	Migration execution
<code>tier-transition/validate.ts</code>	Transition validation
<code>tier-transition/rollback.ts</code>	Rollback handling
...	16 more handlers

Shared Utilities (344 files)

The `shared/` directory contains reusable code:

Database (`shared/db/`)

- `client.ts` - Aurora Data API client
- `pool.ts` - Connection pooling
- `migrations.ts` - Migration utilities

Services (`shared/services/`)

- `brain-config.service.ts` - Brain configuration
- `ghost-manager.service.ts` - Ghost vector management
- `flash-buffer.service.ts` - Flash fact buffer
- `sofai-router.service.ts` - SOFAI routing
- `context-assembler.service.ts` - Context assembly
- `oversight.service.ts` - Human oversight
- `embedding.service.ts` - Embedding generation
- `ecd-verification.service.ts` - ECD truth verification
- `governor/economic-governor.ts` - Cost optimization

Utilities (`shared/utls/`)

- `response.ts` - API response helpers
- `errors.ts` - Error types
- `auth.ts` - Authentication helpers

- validation.ts - Input validation
- db-helpers.ts - Database helpers

Logging (shared/logging/)

- enhanced-logger.ts - Structured logging
 - metrics.ts - CloudWatch metrics
-

Handler Patterns

Standard API Handler

```
import { APIGatewayProxyEvent, APIGatewayProxyResult } from 'aws-lambda';
import { success, error } from '../shared/response';
import { withSecureDBContext } from '../shared/services/db-context.service';

export async function handler(event: APIGatewayProxyEvent): Promise<APIGatewayProxyResult> {
  try {
    return await withSecureDBContext(event, async (db, authContext) => {
      // Handler logic with RLS context
      const result = await db.query('SELECT * FROM table WHERE tenant_id = $1', [authContext.tenantId]);
      return success(result);
    });
  } catch (err) {
    return error(500, err.message);
  }
}
```

SQS Event Handler

```
import { SQSEvent, SQSRecord } from 'aws-lambda';
import { logger } from '../shared/logging/enhanced-logger';

export async function handler(event: SQSEvent): Promise<void> {
  for (const record of event.Records) {
    await processRecord(record);
  }
}

async function processRecord(record: SQSRecord): Promise<void> {
  const body = JSON.parse(record.body);
  logger.info('Processing message', { messageId: record.messageId });
  // Process message
}
```

Scheduled Event Handler

```
import { ScheduledEvent } from 'aws-lambda';
import { logger } from '../shared/logging/enhanced-logger';

export async function handler(event: ScheduledEvent): Promise<void> {
  logger.info('Scheduled task started', {
    source: event.source,
    time: event.time,
  });

  // Execute scheduled task
  await runScheduledTask();

  logger.info('Scheduled task completed');
}
```

This concludes the Lambda handlers export. See other export files for additional components.