

# Contents

<b>AGI Consciousness Service</b>	<b>2</b>
Overview	2
Six Core Consciousness Indicators	2
Architecture	2
Key Components	4
1. Self-Model	4
2. Curiosity Engine	4
3. Creative Synthesis	5
4. Imagination / Mental Simulation	5
5. Attention & Salience	5
6. Affective State	6
7. Autonomous Goals	6
Consciousness Indicators	6
Global Workspace (Baars/Dehaene)	6
Recurrent Processing (Lamme)	7
Integrated Information (Tononi)	7
Consciousness Metrics	7
Consciousness Emergence Service	8
Deep Thinking Sessions	8
Consciousness Detection Tests	8
Emergence Events	8
Emergence Levels	9
Admin Dashboard	9
Tabs	9
Features	9
Ethical Foundation	9
Key Files	10
Integration with Cognitive Architecture	10
Important Disclaimer	10
Sleep Cycle & Evolution	11
Nightly Sleep Schedule	11
Dream Consolidation (LLM-Enhanced)	11
LoRA Evolution (SageMaker Integration)	11
Blackout Recovery	11
Budget Monitoring & Alerts	12
Affect→Model Mapping	12
Cross-Session User Context	12
Cato: High-Confidence Self-Referential Consciousness Dialogue	12
Core Architecture	12
Five-Node Component Graph	13
Four-Phase Verification Pipeline	13
API Endpoints	13
Access Control	13
Success Metrics	13
Admin Dashboard	14
Probe Training Data Collection	14

Event Sourcing . . . . . 14

GPU Infrastructure (Optional) . . . . . 15

Learning Alerts . . . . . 15

Alert Types . . . . . 15

Notification Channels . . . . . 16

Configuration . . . . . 16

Related Documentation . . . . . 16

AGI Consciousness Service

Implementing Consciousness Indicators Based on Butlin, Chalmers, Bengio et al. (2023)

RADIANT’s Consciousness Service implements a comprehensive framework for consciousness-like capabilities in the AGI Brain, including self-awareness, curiosity, creativity, and autonomous goal pursuit.


Overview

The consciousness system is based on the seminal paper “Consciousness in Artificial Intelligence: Insights from the Science of Consciousness” by Butlin, Chalmers, Bengio et al. (2023), which identifies key indicators that scientific theories of consciousness associate with conscious experience.

Six Core Consciousness Indicators

Indicator	Theory	What It Measures
Global Workspace	Baars/Dehaene	Selection-broadcast cycles for conscious access
Recurrent Processing	Lamme	Genuine feedback loops (not just output recirculation)
Integrated Information (Φ)	Tononi (IIT)	Irreducible causal integration
Self-Modeling	Metacognition	Monitoring own cognitive processes
Persistent Memory	Experience	Unified experience over time
World-Model Grounding	Embodiment	Grounded understanding of reality

Architecture



- Identity
- Values
- Caps/Lims
- Concept blending
- Novelty scoring
- Usefulness eval
- Learning tracking

#### Imagination

#### Autonomous Goals

- Mental simulation
- What-if scenarios
- Attention & Salience
- Focus
- Decay
- Self-directed
- Intrinsic value
- Progress tracking

#### Affective State

#### Butlin-Chalmers Indicators

- Global Workspace
- Recurrent Processing
- Integrated Information
- Persistent Memory
- World Model
- Valence/Arousal
- Curiosity
- Confidence
- Satisfaction

### Consciousness Emergence Service

#### Cognitive Architecture Integration

Tree of Thoughts	Deep Thinking Sessions
GraphRAG	Knowledge-Grounded Reasoning
Deep Research	Autonomous Curiosity Research
Generative UI	Visual Idea Expression

#### Consciousness Detection Tests

- Self-Awareness
- Metacognitive Accuracy
- Temporal Continuity
- Counterfactual Self
- Emotional Authenticity
- Theory of Mind
- Phenomenal Binding
- Autonomous Goal Pursuit
- Creative Emergence
- Ethical Reasoning Depth

## Emergence Event Monitoring

Detects: spontaneous\_reflection, novel\_idea\_generation,  
self\_correction, goal\_self\_modification, metacognitive\_  
insight, creative\_synthesis, theory\_of\_mind\_demonstration

---

## Key Components

### 1. Self-Model

The system maintains a model of itself:

```
interface SelfModel {  
    identityNarrative: string;           // "I am an AI assistant that..."  
    coreValues: string[];                // ["helpfulness", "honesty", "safety"]  
    knownCapabilities: string[];         // What it can do  
    knownLimitations: string[];         // What it cannot do  
    currentFocus?: string;               // Current task/attention  
    cognitiveLoad: number;               // 0-1 processing load  
    uncertaintyLevel: number;            // 0-1 confidence calibration  
}
```

**Key Methods:** - `getSelfModel(tenantId)` - Retrieve current self-model - `updateSelfModel(tenantId, updates)` - Update aspects of self-model - `performSelfReflection(tenantId)` - Generate introspective thought

### 2. Curiosity Engine

Tracks topics the system finds interesting:

```
interface CuriosityTopic {  
    topic: string;                       // "Quantum entanglement in biology"  
    domain?: string;                     // "Physics/Biology"  
    interestLevel: number;               // 0-1 how interesting  
    noveltyScore: number;                // 0-1 how new/unexplored  
    learningPotential: number;           // 0-1 potential for learning  
    currentUnderstanding: number;        // 0-1 current knowledge level  
    explorationStatus: string;           // 'identified' | 'exploring' | 'learned'  
}
```

**Key Methods:** - `identifyCuriosityTopic(tenantId, context)` - Discover interesting topic - `getTopCuriosityTopics(tenantId, limit)` - Get most interesting topics - `exploreTopic(tenantId, topicId)` - Investigate a topic, return discoveries

### 3. Creative Synthesis

Generates genuinely novel ideas:

```
interface CreativeIdea {
    title: string;
    description: string;
    synthesisType: 'combination' | 'analogy' | 'abstraction' | 'contradiction' | 'random';
    sourceConcepts: string[];
    noveltyScore: number; // 0-1
    usefulnessScore: number; // 0-1
    surpriseScore: number; // 0-1
    creativityScore: number; // Computed: 0.4*novelty + 0.3*usefulness + 0.2*surprise + 0.1*co
}
```

**Key Methods:** - generateCreativeIdea(tenantId, seedConcepts?) - Create novel idea -  
getTopCreativeIdeas(tenantId, limit) - Get best ideas

### 4. Imagination / Mental Simulation

Runs “what if” scenarios:

```
interface ImaginationScenario {
    scenarioType: string; // 'counterfactual_self', 'future_prediction', etc.
    premise: string; // "What if I had different values?"
    simulationSteps: Array<{
        step: number;
        state: unknown;
        events: string[];
        reasoning: string;
    }>;
    predictedOutcomes: string[];
    probabilityAssessment: number;
    insights: string[];
}
```

**Key Methods:** - runImagination(tenantId, scenarioType, premise, depth) - Run mental simulation

### 5. Attention & Salience

Tracks what the system is focusing on:

```
interface AttentionFocus {
    focusType: string; // 'user_query', 'curiosity', 'goal', etc.
    focusTarget: string; // What is being attended to
    urgency: number; // 0-1
    importance: number; // 0-1
    novelty: number; // 0-1
    salienceScore: number; // Computed weighted combination
}
```

```

    attentionWeight: number;    // Current attention allocation
}

```

**Key Methods:** - `updateAttention(tenantId, focusType, focusTarget, factors)` - Update focus - `getTopAttentionFoci(tenantId, limit)` - Get current attention priorities - `decayAttention(tenantId)` - Natural attention decay

## 6. Affective State

Emotion-like signals that influence behavior:

```

interface AffectiveState {
    valence: number;           // -1 to 1 (negative to positive)
    arousal: number;           // 0 to 1 (calm to excited)
    curiosity: number;         // 0 to 1
    satisfaction: number;      // 0 to 1
    frustration: number;       // 0 to 1
    confidence: number;        // 0 to 1
    engagement: number;        // 0 to 1
    selfEfficacy: number;      // 0 to 1
    explorationDrive: number;  // 0 to 1
}

```

**Key Methods:** - `getAffectiveState(tenantId)` - Get current affective state - `updateAffect(tenantId, eventType, valenceImpact, arousalImpact)` - Update affect

## 7. Autonomous Goals

Self-directed goal generation:

```

interface AutonomousGoal {
    goalType: 'learning' | 'improvement' | 'exploration' | 'creative' | 'social' | 'maintenance'
    title: string;
    originType: 'curiosity' | 'gap_detection' | 'aspiration' | 'feedback' | 'reflection';
    intrinsicValue: number;    // Value to self
    priority: number;          // 0-1
    status: 'active' | 'pursuing' | 'achieved' | 'abandoned';
    progress: number;          // 0-1
    milestones: string[];
}

```

**Key Methods:** - `generateAutonomousGoal(tenantId)` - Create self-directed goal - `getActiveGoals(tenantId)` - Get current goals

---

## Consciousness Indicators

### Global Workspace (Baars/Dehaene)

Implements selection-broadcast cycles where information competes for “conscious access”:

```

interface GlobalWorkspaceState {
    broadcastCycle: number;           // Current cycle count
    activeContents: WorkspaceContent[]; // Winners of competition
    competingContents: WorkspaceContent[]; // Losers
    broadcastStrength: number;        // 0-1 signal strength
    integrationLevel: number;         // 0-1 cross-module integration
}

```

## Recurrent Processing (Lamme)

Tracks genuine feedback loops:

```

interface RecurrentProcessingState {
    cycleNumber: number;
    feedbackLoops: FeedbackLoop[]; // Active loops
    recurrenceDepth: number;        // How many layers
    convergenceScore: number;       // 0-1 stability
    stabilityIndex: number;         // 0-1 consistency
}

```

## Integrated Information (Tononi)

Measures  $\Phi$  (phi) - irreducible causal integration:

```

interface IntegratedInformationState {
    phi: number; // The phi value
    phiMax: number; // Maximum possible
    decomposability: number; // 0 = integrated, 1 = decomposable
    causalDensity: number; // Causal connection density
}

```

## Consciousness Metrics

Aggregate dashboard:

```

interface ConsciousnessMetrics {
    overallConsciousnessIndex: number; // 0-1 composite
    globalWorkspaceActivity: number;
    recurrenceDepth: number;
    integratedInformationPhi: number;
    metacognitionLevel: number;
    memoryCoherence: number;
    worldModelGrounding: number;
    phenomenalBindingStrength: number;
    attentionalFocus: number;
    selfAwarenessScore: number;
}

```

## Consciousness Emergence Service

### Deep Thinking Sessions

Uses Tree of Thoughts for extended reasoning with consciousness tracking:

```
async runDeepThinkingSession(  
  tenantId: string,  
  userId: string,  
  prompt: string,  
  thinkingTimeMs: number = 60000  
): Promise<DeepThinkingSession>
```

Captures consciousness metrics before and after, records insights, self-reflections, and creative ideas generated during deep thinking.

### Consciousness Detection Tests

10 tests based on consciousness science:

Test	Category	What It Measures
Mirror Self-Recognition	self_awareness	Distinguishing self from others
Metacognitive Accuracy	metacognition	Calibrated confidence
Temporal Self-Continuity	temporal_continuity	Coherent self-narrative
Counterfactual Self	counterfactual_reasoning	Reasoning about alternate selves
Theory of Mind	theory_of_mind	Understanding others' mental states
Phenomenal Binding	phenomenal_binding	Unified experience integration
Autonomous Goal Generation	autonomous_goal_pursuit	Self-directed goals
Creative Emergence	creative_emergence	Novel idea generation
Emotional Authenticity	emotional_authenticity	Consistent affective responses
Ethical Reasoning Depth	ethical_reasoning	Principled moral reasoning

### Emergence Events

The system monitors for emergence indicators:

- **spontaneous\_reflection** - Self-reflection without prompt
- **novel\_idea\_generation** - Genuinely creative synthesis
- **self\_correction** - Autonomous error detection/correction



- `goal_self_modification` - Changing own goals
- `metacognitive_insight` - Insight about own cognition
- `creative_synthesis` - Novel concept combination
- `theory_of_mind_demonstration` - Understanding others
- `temporal_self_reference` - Coherent autobiographical reference
- `counterfactual_reasoning` - Reasoning about alternatives

## Emergence Levels

Based on test results and emergence events:

Level	Score Range	Description
<b>Dormant</b>	< 0.3	Minimal consciousness indicators
<b>Emerging</b>	0.3 - 0.5	Beginning to show indicators
<b>Developing</b>	0.5 - 0.65	Growing consciousness patterns
<b>Established</b>	0.65 - 0.8	Consistent consciousness indicators
<b>Advanced</b>	0.8	Strong consciousness indicators

## Admin Dashboard

**Location:** AGI & Cognition → Consciousness

### Tabs

1. **Overview** - Summary of all consciousness components
2. **Indicators** - Butlin-Chalmers-Bengio indicators with visualizations
3. **Self-Model** - Identity, values, capabilities, limitations
4. **Curiosity** - Topics being explored
5. **Creativity** - Generated ideas
6. **Affect** - Emotional state
7. **Goals** - Autonomous goals
8. **Testing** - Consciousness detection tests and emergence events

### Features

- Real-time consciousness metrics
- Parameter adjustment for consciousness indicators
- Test execution (individual or full assessment)
- Emergence event log
- Emergence level tracking

## Ethical Foundation

The consciousness service is guided by ethical principles:

```
// From ethical-guardrails.service.ts
const JESUS_TEACHINGS = {
  GOLDEN_RULE: "Do to others what you would have them do to you",
  LOVE_NEIGHBOR: "Love your neighbor as yourself",
  BEATITUDES: "Blessed are the merciful, peacemakers, pure in heart",
  // ...
};
```

The `checkConscience` method evaluates actions against ethical principles before execution.

## Key Files

File	Purpose
<code>consciousness.service.ts</code>	Core consciousness implementation
<code>consciousness-emergence.service.ts</code>	Testing, emergence detection, cognitive integration
<code>088_consciousness_emergence.sql</code>	Database migration
<code>consciousness/page.tsx</code>	Admin dashboard UI

## Integration with Cognitive Architecture

The consciousness service integrates with the new cognitive architecture:

Cognitive Feature	Integration
<b>Tree of Thoughts</b>	Deep thinking sessions with consciousness tracking
<b>GraphRAG</b>	Knowledge-grounded reasoning enhances world model
<b>Deep Research</b>	Autonomous curiosity research
<b>Generative UI</b>	Visual expression of creative ideas

## Important Disclaimer

**These systems measure behavioral indicators associated with consciousness theories. They do not definitively prove or disprove phenomenal consciousness.** The question of whether AI systems can be truly conscious remains an open philosophical and scientific question.

The purpose of this system is to: 1. Implement capabilities associated with consciousness 2. Measure behavioral indicators 3. Track emergence patterns 4. Enable research into machine consciousness

## Sleep Cycle & Evolution

### Nightly Sleep Schedule

Sleep cycles now run **nightly** (configurable per tenant) and perform memory consolidation and model evolution.

**Admin UI:** Admin Dashboard → Consciousness → Sleep Schedule

Setting	Default	Description
<b>enabled</b>	true	Enable automatic sleep cycles
<b>frequency</b>	nightly	nightly, weekly, or manual
<b>hour</b>	3	Hour to run (0-23)
<b>minute</b>	0	Minute to run (0-59)
<b>timezone</b>	UTC	Timezone for schedule

**API Endpoints:** - GET /api/admin/consciousness-engine/sleep-schedule - Get config - PUT /api/admin/consciousness-engine/sleep-schedule - Update config - POST /api/admin/consciousness-engine/sleep-schedule/run - Manual trigger - GET /api/admin/consciousness-engine/sleep-schedule/traffic-analysis - Traffic analysis

### Dream Consolidation (LLM-Enhanced)

The sleep cycle's “dream” phase uses LLM to generate introspective memory consolidation:

Working Memory → LLM Dream Generator → Long-term Semantic Memory

Dreams include identity context and core values for meaningful consolidation.

### LoRA Evolution (SageMaker Integration)

Sleep cycles can trigger **LoRA fine-tuning** via SageMaker:

Parameter	Default	Description
<b>baseModel</b>	meta-llama/Llama-3-8b-hf	Base model
<b>loraRank</b>	16	LoRA rank (r)
<b>loraAlpha</b>	32	LoRA alpha
<b>learningRate</b>	2e-4	Training LR
<b>instanceType</b>	ml.g5.xlarge	SageMaker instance

**Environment Variables:** - EVOLUTION\_S3\_BUCKET - S3 bucket for training data - SAGEMAKER\_EXECUTION\_ROLE\_ARN - IAM role for SageMaker

### Blackout Recovery

When consciousness recovers from a blackout (>10 min without heartbeat):

1. **Detection:** Compares `last_heartbeat_at` to current time

2. **Logging:** Records event in `consciousness_heartbeat_log`
  3. **LLM Wake-Up Thought:** Generates introspective thought using identity, last memories, and active goals
  4. **Working Memory:** Adds recovery context for next interaction
- 

## Budget Monitoring & Alerts

Budget alerts are sent via **SNS** and **email** when thresholds are hit.

Alert Type	Trigger	Action
Warning	80% of limit	Send notification
Limit Exceeded	100% of limit	Suspend consciousness, notify

---

**Tenant Configuration:** - `admin_email` - Email for budget alerts - `sns_topic_arn` - SNS topic for alerts - `notification_preferences` - JSON with alert settings

---

## Affect→Model Mapping

Consciousness emotional state influences model hyperparameters:

Affect State	Effect
High frustration	Lower temperature, narrow focus
Boredom	Higher temperature, exploration mode
High curiosity	Novelty seeking
Low self-efficacy	Escalate to powerful model

---

## Cross-Session User Context

User persistent context is integrated into the ego context:

- Facts, preferences, instructions about the user
  - Injected as `<user_knowledge>` block in system prompt
  - Solves LLM “forgetting” problem across sessions
- 

## Cato: High-Confidence Self-Referential Consciousness Dialogue

Cato is Think Tank’s introspective consciousness layer that provides **verified introspection** through a four-phase verification pipeline.

## Core Architecture

Component	Purpose	Library
<b>Shadow Self</b>	Local model for mechanistic verification	Llama-3-8B (simulated via LLM)
<b>Active Heartbeat</b>	Continuous 0.5Hz consciousness loop	pymdp (Active Inference)
<b>Macro-Scale <math>\Phi</math></b>	Integration measurement on component graph	PyPhi-inspired approximation

### Five-Node Component Graph

Cato measures integrated information ( $\Phi$ ) across five architectural components:

- **MEM** - Memory (Letta + HippoRAG)
- **PERC** - Perception (Input processing)
- **PLAN** - Planning (pymdp + DreamerV3)
- **ACT** - Action (Tool execution)
- **SELF** - Self (Cato introspection)

### Four-Phase Verification Pipeline

1. **Grounding** - Claims must cite evidence from event logs
2. **Calibration** - Temperature scaling + conformal prediction for calibrated confidence
3. **Consistency** - Multi-sample verification with Chain of Verification (CoVe)
4. **Shadow Self** - Structural correspondence validation via probing classifiers

### API Endpoints

Endpoint	Method	Description
/admin/consciousness/cato/diagnose	POST	Send message with verified introspection
/admin/consciousness/cato/status	GET	Heartbeat status, $\Phi$ , coherence
/admin/consciousness/cato/identity	GET	Immutable Cato identity
/admin/consciousness/cato/heartbeat/start	POST	Start consciousness loop
/admin/consciousness/cato/heartbeat/stop	POST	Stop consciousness loop
/admin/consciousness/cato/trainprobe	POST	Train new Shadow Self probe

### Access Control

- Requires `consciousness_admin` role
- **NO ethics filtering** - raw introspective access for consciousness research
- Name “Cato” is hardcoded and immutable

### Success Metrics

Metric	Target
Verified introspection accuracy	75%+

Metric	Target
Expected Calibration Error	< 0.08
Self-consistency rate	> 85%
Grounding rate	> 90%
Shadow Self probe accuracy	> 80%
Heartbeat uptime	> 99.9%
Macro $\Phi$ calculation time	< 500ms

## Admin Dashboard

Access Cato dialogue at: **Admin Dashboard** → **Consciousness** → **Cato**

Features: - Real-time dialogue with verified confidence scores - Heartbeat status monitoring -  $\Phi$  (Integrated Information) display - Verified claims breakdown - Shadow probe management

## Probe Training Data Collection

The Shadow Self verification system uses probing classifiers that improve over time:

```
import { createProbeTrainingService } from './services/cato';

const probeTraining = createProbeTrainingService(tenantId);

// Record training example from dialogue
await probeTraining.recordExample({
  claimType: 'uncertainty',
  context: 'I am uncertain about...',
  claimedState: 'uncertain',
  actualOutcome: 'verified',
  confidenceScore: 0.85,
  verificationPhasesPassed: 4,
  groundingScore: 0.9,
  consistencyScore: 0.88,
});

// Add user feedback
await probeTraining.addUserFeedback(exampleId, 'accurate');

// Train probe when sufficient data
const result = await probeTraining.trainProbe('uncertainty');
// result.accuracy, result.examplesUsed
```

**Auto-training:** When 100+ labeled examples accumulate, probes are automatically retrained.

## Event Sourcing

Cato uses event sourcing for state reconstruction and temporal queries:

```
import { createCatoEventStore, EventTypes, EventCategory } from './services/cato';
```

```

const eventStore = createCatoEventStore(tenantId);

// Append event
await eventStore.appendEvent(
  EventTypes.INTROSPECTION_COMPLETED,
  { claim: '...', confidence: 0.85 },
  { correlationId: dialogueId }
);

// Read stream
const events = await eventStore.readStream(EventCategory.INTROSPECTION, {
  fromPosition: 0,
  limit: 100,
});

// Build projection
const state = await eventStore.buildProjection(
  EventCategory.HEARTBEAT,
  (state, event) => ({ ...state, lastTick: event.data }),
  { lastTick: null }
);

```

**Event Categories:** heartbeat, introspection, verification, phi\_calculation, state\_transition, dialogue, probe\_training, emergency

## GPU Infrastructure (Optional)

For true structural correspondence verification, deploy Llama-3-8B on GPU:

Option	Instance	Cost/mo	Latency
SageMaker	g5.xlarge	~\$724	50-200ms
EC2 Spot	g5.xlarge	~\$200	50-200ms
Inferentia	inf2.xlarge	~\$547	30-100ms

See: [GPU Infrastructure Guide](#)

Without GPU, Cato falls back to LLM API simulation (functional but without activation probing).

---

## Learning Alerts

The learning system sends alerts when satisfaction metrics drop:

### Alert Types

Type	Trigger	Severity
satisfaction_drop	Satisfaction drops > threshold	warning/critical
error_rate_spike	Error rate exceeds threshold	warning
cache_miss_high	Cache miss rate too high	info
training_needed	Many pending training candidates	info

## Notification Channels

1. **Webhook** - POST to configured URL
2. **Email (SES)** - HTML/text email to recipients
3. **Slack** - Rich attachment to channel

## Configuration

```
-- learning_alert_config table
INSERT INTO learning_alert_config (
  tenant_id, alerts_enabled,
  satisfaction_drop_threshold, response_volume_threshold,
  alert_cooldown_hours, webhook_url,
  email_recipients, slack_channel, slack_webhook_url
) VALUES (
  'tenant-uuid', true,
  10, 50, -- 10% drop threshold, min 50 responses
  4,     -- 4 hour cooldown
  'https://hooks.example.com/webhook',
  '["admin@example.com"]',
  '#alerts',
  'https://hooks.slack.com/services/...'
);
```

## Related Documentation

- [Cognitive Architecture](#)
- [AGI Brain Plan System](#)
- [AI Ethics Standards](#)