

Contents

SECTION 25: FOCUS MODES & CUSTOM PERSONAS (v3.6.0)	1
	1
25.1 Focus Modes Overview	1
25.2 Personas Database Schema	1
25.3 Persona Service	2
	5

SECTION 25: FOCUS MODES & CUSTOM PERSONAS (v3.6.0)

25.1 Focus Modes Overview

Pre-configured AI behavior profiles and custom persona creation.

25.2 Personas Database Schema

-- migrations/034_focus_personas.sql

```
CREATE TABLE focus_modes (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  tenant_id UUID REFERENCES tenants(id),  
  mode_name VARCHAR(100) NOT NULL,  
  display_name VARCHAR(200) NOT NULL,  
  description TEXT,  
  icon VARCHAR(50),  
  system_prompt TEXT NOT NULL,  
  default_model VARCHAR(100),  
  settings JSONB DEFAULT '{}',  
  is_system BOOLEAN DEFAULT false,  
  is_active BOOLEAN DEFAULT true,  
  created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP  
);
```

```
CREATE TABLE user_personas (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  tenant_id UUID NOT NULL REFERENCES tenants(id),  
  user_id UUID NOT NULL REFERENCES users(id),  
  persona_name VARCHAR(100) NOT NULL,  
  display_name VARCHAR(200),  
  avatar_url VARCHAR(500),  
  system_prompt TEXT NOT NULL,  
  voice_id VARCHAR(100),  
  personality_traits JSONB DEFAULT '[]',  
  knowledge_domains JSONB DEFAULT '[]',
```

```

    conversation_style JSONB DEFAULT '{}',
    is_public BOOLEAN DEFAULT false,
    usage_count INTEGER DEFAULT 0,
    created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,
    updated_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP
);

CREATE TABLE persona_usage_log (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    persona_id UUID NOT NULL REFERENCES user_personas(id) ON DELETE CASCADE,
    user_id UUID NOT NULL REFERENCES users(id),
    chat_id UUID REFERENCES chats(id),
    tokens_used INTEGER,
    created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP
);

CREATE INDEX idx_focus_modes_tenant ON focus_modes(tenant_id) WHERE tenant_id IS NOT NULL;
CREATE INDEX idx_user_personas_user ON user_personas(tenant_id, user_id);
CREATE INDEX idx_persona_usage ON persona_usage_log(persona_id, created_at DESC);

ALTER TABLE focus_modes ENABLE ROW LEVEL SECURITY;
ALTER TABLE user_personas ENABLE ROW LEVEL SECURITY;
ALTER TABLE persona_usage_log ENABLE ROW LEVEL SECURITY;

-- System modes visible to all, tenant modes to tenant only
CREATE POLICY focus_modes_policy ON focus_modes USING (
    is_system = true OR tenant_id IS NULL OR tenant_id = current_setting('app.current_tenant_id')
);
CREATE POLICY user_personas_isolation ON user_personas USING (
    tenant_id = current_setting('app.current_tenant_id')::UUID AND
    (user_id = current_setting('app.user_id')::UUID OR is_public = true)
);
CREATE POLICY persona_usage_isolation ON persona_usage_log USING (
    persona_id IN (SELECT id FROM user_personas WHERE tenant_id = current_setting('app.current_tenant_id'))
);

-- Insert default focus modes
INSERT INTO focus_modes (mode_name, display_name, description, icon, system_prompt, is_system)
VALUES
('general', 'General Assistant', 'Versatile AI for any task', 'MessageSquare', 'You are a helpful assistant.', true),
('code', 'Code Expert', 'Programming and development focus', 'Code', 'You are an expert software developer.', false),
('writer', 'Creative Writer', 'Creative writing and content creation', 'PenTool', 'You are a creative writer.', false),
('analyst', 'Data Analyst', 'Data analysis and insights', 'BarChart', 'You are a data analyst.', false),
('researcher', 'Research Assistant', 'Deep research and fact-finding', 'Search', 'You are a research assistant.', false);

```

25.3 Persona Service

```
// packages/core/src/services/persona-service.ts
```

```

import { Pool } from 'pg';

interface PersonaCreate {
  name: string;
  displayName?: string;
  systemPrompt: string;
  avatarUrl?: string;
  voiceId?: string;
  traits?: string[];
  domains?: string[];
  style?: Record<string, any>;
  isPublic?: boolean;
}

export class PersonaService {
  private pool: Pool;

  constructor(pool: Pool) {
    this.pool = pool;
  }

  async getFocusModes(tenantId?: string): Promise<any[]> {
    const result = await this.pool.query(`
      SELECT * FROM focus_modes
      WHERE is_active = true AND (is_system = true OR tenant_id IS NULL OR tenant_id = $1)
      ORDER BY is_system DESC, mode_name
    `, [tenantId]);

    return result.rows;
  }

  async createPersona(tenantId: string, userId: string, persona: PersonaCreate): Promise<string> {
    const result = await this.pool.query(`
      INSERT INTO user_personas (
        tenant_id, user_id, persona_name, display_name, system_prompt,
        avatar_url, voice_id, personality_traits, knowledge_domains,
        conversation_style, is_public
      )
      VALUES ($1, $2, $3, $4, $5, $6, $7, $8, $9, $10, $11)
      RETURNING id
    `, [
      tenantId,
      userId,
      persona.name,
      persona.displayName,
      persona.systemPrompt,
      persona.avatarUrl,
      persona.voiceId,
    ]
  }

```

```

        JSON.stringify(persona.traits || []),
        JSON.stringify(persona.domains || []),
        JSON.stringify(persona.style || {}),
        persona.isPublic || false
    ]);

    return result.rows[0].id;
}

async getUserPersonas(tenantId: string, userId: string): Promise<any[]> {
    const result = await this.pool.query(`
        SELECT * FROM user_personas
        WHERE tenant_id = $1 AND (user_id = $2 OR is_public = true)
        ORDER BY usage_count DESC
    `, [tenantId, userId]);

    return result.rows;
}

async getPersona(personaId: string): Promise<any> {
    const result = await this.pool.query(`SELECT * FROM user_personas WHERE id = $1`, [personaId]);
    return result.rows[0];
}

async updatePersona(personaId: string, updates: Partial<PersonaCreate>): Promise<void> {
    const fields: string[] = [];
    const values: any[] = [personaId];
    let paramIndex = 2;

    if (updates.name) { fields.push(`persona_name = ${`${paramIndex++}`}`); values.push(updates.name); }
    if (updates.displayName) { fields.push(`display_name = ${`${paramIndex++}`}`); values.push(updates.displayName); }
    if (updates.systemPrompt) { fields.push(`system_prompt = ${`${paramIndex++}`}`); values.push(updates.systemPrompt); }
    if (updates.avatarUrl) { fields.push(`avatar_url = ${`${paramIndex++}`}`); values.push(updates.avatarUrl); }
    if (updates.voiceId) { fields.push(`voice_id = ${`${paramIndex++}`}`); values.push(updates.voiceId); }
    if (updates.traits) { fields.push(`personality_traits = ${`${paramIndex++}`}`); values.push(updates.traits); }
    if (updates.domains) { fields.push(`knowledge_domains = ${`${paramIndex++}`}`); values.push(updates.domains); }
    if (updates.style) { fields.push(`conversation_style = ${`${paramIndex++}`}`); values.push(updates.style); }
    if (typeof updates.isPublic === 'boolean') { fields.push(`is_public = ${`${paramIndex++}`}`); values.push(updates.isPublic); }

    fields.push('updated_at = NOW()');

    await this.pool.query(`UPDATE user_personas SET ${fields.join(', ')} WHERE id = $1`, values);
}

async logUsage(personaId: string, userId: string, chatId?: string, tokensUsed?: number): Promise<void> {
    await this.pool.query(`
        INSERT INTO persona_usage_log (persona_id, user_id, chat_id, tokens_used)
        VALUES ($1, $2, $3, $4)
    `);
}

```

```

    `, [personaId, userId, chatId, tokensUsed]);

    await this.pool.query(`
        UPDATE user_personas SET usage_count = usage_count + 1 WHERE id = $1
    `, [personaId]);
}

async buildPrompt(personaId: string, userMessage: string): Promise<string> {
    const persona = await this.getPersona(personaId);
    if (!persona) throw new Error('Persona not found');

    const traits = persona.personality_traits as string[];
    const domains = persona.knowledge_domains as string[];

    let prompt = persona.system_prompt;

    if (traits.length > 0) {
        prompt += `
\n\nPersonality traits: ${traits.join(', ')}.`;
    }

    if (domains.length > 0) {
        prompt += `
\n\nAreas of expertise: ${domains.join(', ')}.`;
    }

    return prompt;
}
}

```