

SECTION 5: LAMBDA FUNCTIONS - ADMIN & BILLING (v2.1.0) 2

RADIANT v2.2.0 - Prompt 5: Lambda Functions - Admin & Billing 2

OVERVIEW 2

KEY FEATURES 2

Administrator Management	2
------------------------------------	---

Billing & Metering 2

LAMBDA DIRECTORY STRUCTURE 3

PART 1: SHARED ADMIN UTILITIES 3

packages/infrastructure/lambda/shared/admin/index.ts	3
--	---

packages/infrastructure/lambda/shared/admin/types.ts	3
--	---

packages/infrastructure/lambda/shared/admin/tokens.ts	4
---	---

```
packages/infrastructure/lambda/shared/admin/email.ts . . . . . 5
```

packages/infrastructure/lambda/shared/admin/stripe.ts	6
---	---

PART 2: INVITATIONS LAMBDA 7

packages/infrastructure/lambda/admin/invitations.ts	7
---	---

PART 3: TWO-PERSON APPROVALS LAMBDA 12

packages/infrastructure/lambda/admin/approvals.ts	12
---	----

PART 4: METERING LAMBDA 17

packages/infrastructure/lambda/billing/metering.ts	17
--	----

PART 5: DATABASE SCHEMA ADDITIONS 20

packages/infrastructure/migrations/005	admin	billing.sql	20
--	-------	-------------	----

API ROUTES SUMMARY 22

Admin Routes 22

Billing Routes	22
--------------------------	----

Metering Routes	23
---------------------------	----

DEPLOYMENT VERIFICATION 23

2. List Pending Approvals (for me to approve) 23

3. Get Current Billing Period 23

4. Get Usage Rollups 23

5. Generate Invoice

ESTIMATED COSTS BY TIER 24

NEXT PROMPTS 24

END OF SECTION 5 24

[illegible]

Type Imports

IMPORTANT: Use canonical table names: administrators, invitations, approval_requests

Prompt 5 of 9 | Target Size: ~60KB | Version: 3.7.0 | December 2024

This prompt creates the Admin & Billing Lambda functions for the RADIANT platform:

1. **Invitations Lambda** - Email-based administrator invitations with secure tokens
2. **Approvals Lambda** - Two-person approval workflow for production deployments
3. **Admin Users Lambda** - Administrator CRUD, roles, and MFA management
4. **Admin Profiles Lambda** - Preferences, notifications, and settings
5. **Metering Lambda** - Real-time usage event collection and tracking
6. **Billing Lambda** - Cost aggregation, invoicing, and payment processing
7. **Audit Lambda** - Comprehensive audit logging and compliance reporting
8. **Notifications Lambda** - Admin notification delivery and management

Administrator Management

- ## Billing & Metering

- 2

- ## LAMBDA DIRECTORY STRUCTURE

PART 1: SHARED ADMIN UTILITIES

```

[AdminRole.OPERATOR]: [ 'admin:read', 'billing:read', 'settings:read', 'deployments:read', ],
[AdminRole.AUDITOR]: [ 'admin:read', 'billing:read', 'audit:read', ], };

// =====
// INVITATION TYPES // =====

export interface Invitation { id: string; email: string; role: AdminRoleType; invitedBy: string;
invitedByName: string; appId: string; tenantId: string; environment: 'dev' | 'staging' | 'prod';
token: string; tokenHash: string; expiresAt: string; status: 'pending' | 'accepted' | 'expired' |
'revoked'; createdAt: string; acceptedAt?: string; acceptedByIp?: string; }

export const createInvitationSchema = z.object({ email: z.string().email(), role: z.enum(['super_admin',
'admin', 'operator', 'auditor']), message: z.string().max(500).optional(), expiresInHours:
z.number().int().min(1).max(168).default(48), });

export const acceptInvitationSchema = z.object({ token: z.string().min(32), firstName:
z.string().min(1).max(50), lastName: z.string().min(1).max(50), password: z.string().min(12).max(128),
mfaMethod: z.enum(['authenticator', 'sms', 'email']).default('authenticator'), phone: z.string().optional(),
});

// =====
// APPROVAL TYPES // =====

export type ApprovalType = | 'deployment' | 'promotion' | 'model_activation' | 'provider_change'
| 'user_role_change' | 'billing_change';

export type ApprovalStatus = | 'pending' | 'approved' | 'rejected' | 'expired' | 'cancelled';

export interface ApprovalRequest { id: string; type: ApprovalType; appId: string; tenantId: string;
environment: 'dev' | 'staging' | 'prod'; requestedBy: string; requestedByName: string; requestedAt:
string; expiresAt: string; status: ApprovalStatus; approvedBy?: string; approvedByName?: string;
approvedAt?: string; rejectedReason?: string; action: string; resourceType: string; resourceId:
string; details: Record<string, unknown>; priority: 'low' | 'medium' | 'high' | 'critical'; notes?:
string; }

export const createApprovalSchema = z.object({ type: z.enum([ 'deployment', 'promotion',
'model_activation', 'provider_change', 'user_role_change', 'billing_change', ]), action: z.string(),
resourceType: z.string(), resourceId: z.string(), details: z.record(z.unknown()), priority:
z.enum(['low', 'medium', 'high', 'critical']).default('medium'), notes: z.string().max(1000).optional(),
expiresInHours: z.number().int().min(1).max(168).default(24), });

export const processApprovalSchema = z.object({ action: z.enum(['approve', 'reject']), reason:
z.string().max(500).optional(), }); “

```

packages/infrastructure/lambda/shared/admin/tokens.ts

```

““typescript /** * Secure token generation and validation */

import { randomBytes, createHash, timingSafeEqual } from 'crypto';

export function generateToken(length: number = 32): string { return randomBytes(length).toString('base64url');
}

```

```

export function generateCode(length: number = 6): string { const chars = '0123456789ABCDEFGHIJKLMN
OPQRSTUVWXYZ'; const bytes = randomBytes(length); let code = ''; for (let i = 0; i < length; i++) {
code += chars[bytes[i] % chars.length]; } return code; }

export function hashToken(token: string): string { return createHash('sha256').update(token).digest('hex');
}

export function verifyToken(token: string, hash: string): boolean { const tokenHash = hashToken(token);
try { return timingSafeEqual( Buffer.from(tokenHash, 'hex'), Buffer.from(hash, 'hex') ); } catch {
return false; } }

export function generateInvitationToken(): { token: string; tokenHash: string } { const token =
generateToken(48); const tokenHash = hashToken(token); return { token, tokenHash }; }

export function calculateExpiry(hoursFromNow: number): string { const expiry = new Date();
expiry.setHours(expiry.getHours() + hoursFromNow); return expiry.toISOString(); }

export function isExpired(expiresAt: string): boolean { return new Date(expiresAt) < new Date();
} ""

```

packages/infrastructure/lambda/shared/admin/email.ts

```

""typescript /** * Email utilities using AWS SES */

```

```

import { SESClient, SendEmailCommand } from '@aws-sdk/client-ses'; import { Logger } from
'../logger';

```

```

const sesClient = new SESClient({});

```

```

export interface EmailOptions { to: string | string[]; subject: string; html: string; text?: string;
replyTo?: string; }

```

```

export async function sendEmail(options: EmailOptions, logger: Logger): Promise { const
fromEmail = 'noreply@${process.env.DOMAIN || 'radiant.cloud'}'; const toAddresses = Array.isArray(options.to) ? options.to : [options.to];

```

```

const command = new SendEmailCommand({ Source: fromEmail, Destination: { ToAddresses:
toAddresses }, Message: { Subject: { Data: options.subject, Charset: 'UTF-8' }, Body: { Html: {
Data: options.html, Charset: 'UTF-8' }, ...(options.text && { Text: { Data: options.text, Charset:
'UTF-8' } }), }, }, ReplyToAddresses: options.replyTo ? [options.replyTo] : undefined, });

```

```

try { await sesClient.send(command); logger.info('Email sent successfully', { to: toAddresses, sub-
ject: options.subject }); } catch (error) { logger.error('Failed to send email', error as Error, { to:
toAddresses }); throw error; } }

```

```

export function generateInvitationEmail(params: { inviteeName: string; inviterName: string; role:
string; appName: string; environment: string; acceptUrl: string; expiresAt: string; message?:
string; }): { html: string; text: string } { const html = ' <!DOCTYPE html>

```

```

You've Been Invited to ${params.appName}

```

```

<h1 style="color: #1a1a1a; margin-bottom: 20px;">You're Invited!</h1>

```

```

<p><strong>\${params.inviterName}</strong> has invited you to join <strong>\${params.appName}</strong>
\${params.message ? '\`<blockquote style="background: #f8f9fa; padding: 15px; border-left: 4px solid #f8f9fa;">
<div style="text-align: center; margin: 30px 0;">

```

```

    <a href="\${params.acceptUrl}" style="display: inline-block; padding: 14px 32px; background:
</div>
<p style="color: #666; font-size: 14px;">This invitation expires on <strong>\${new Date(params
';

const text = 'You've been invited to ${params.appName} by ${params.inviterName} as a
${params.role}. Accept: ${params.acceptUrl}'; return { html, text }; }

export function generateApprovalEmail(params: { approverName: string; requesterName: string;
appName: string; environment: string; action: string; resourceType: string; resourceId: string;
approveUrl: string; rejectUrl: string; expiresAt: string; }): { html: string; text: string } { const
html = `<!DOCTYPE html>

Approval Required - ${params.appName}

<div style="background: #ffc107; padding: 20px; text-align: center;">
  <h1 style="margin: 0; color: #1a1a1a;">Ã¢Å¡Ã¢ Ã¢Ã¢_Ã¢ Approval Required</h1>
</div>
<div style="padding: 30px;">
  <p>Hi \${params.approverName},</p>
  <p><strong>\${params.requesterName}</strong> has requested approval for:</p>
  <div style="background: #f8f9fa; padding: 20px; border-radius: 6px; margin: 20px 0;">
    <p><strong>Environment:</strong> \${params.environment.toUpperCase()}</p>
    <p><strong>Action:</strong> \${params.action}</p>
    <p><strong>Resource:</strong> \${params.resourceType} (\${params.resourceId})</p>
  </div>
  <div style="text-align: center; margin: 30px 0;">
    <a href="\${params.approveUrl}" style="display: inline-block; padding: 14px 32px; background:
    <a href="\${params.rejectUrl}" style="display: inline-block; padding: 14px 32px; background:
  </div>
  <p style="color: #dc3545; font-size: 12px; text-align: center;">Ã¢Å¡Ã¢Ã¢ Ã¢Ã¢_Ã¢ Production depl
</div>

';

const text = 'APPROVAL REQUIRED: ${params.requesterName} requests approval for
${params.action} on ${params.resourceType}. Approve: ${params.approveUrl} Reject:
${params.rejectUrl}'; return { html, text }; } ""

```

packages/infrastructure/lambda/shared/admin/stripe.ts

```

""typescript /** * Stripe payment integration */

import Stripe from 'stripe'; import { SecretsManagerClient, GetSecretValueCommand } from
'@aws-sdk/client-secrets-manager'; import { Logger } from './logger';

const secretsClient = new SecretsManagerClient({}); let stripeClient: Stripe | null = null;

async function getStripeClient(): Promise { if (stripeClient) return stripeClient;

const secretArn = process.env.STRIPE_SECRET_ARN; if (!secretArn) throw new Er-
ror('STRIPE_SECRET_ARN not configured');

```

```

const command = new GetSecretValueCommand({ SecretId: secretArn }); const response =
await secretsClient.send(command); if (!response.SecretString) throw new Error('Stripe secret not
found');

const secrets = JSON.parse(response.SecretString); stripeClient = new Stripe(secrets.apiKey, {
apiVersion: '2023-10-16' }); return stripeClient; }

export async function getOrCreateCustomer( tenantId: string, email: string, name: string, meta-
data: Record<string, string>, logger: Logger ): Promise { const stripe = await getStripeClient();

const existing = await stripe.customers.search({ query: 'metadata[tenantId]:${tenantId}', limit:
1, });

if (existing.data.length > 0) { logger.info('Found existing Stripe customer', { tenantId, customerId:
existing.data[0].id }); return existing.data[0].id; }

const customer = await stripe.customers.create({ email, name, metadata: { tenantId, ...metadata
}, });

logger.info('Created Stripe customer', { tenantId, customerId: customer.id }); return customer.id;
}

export async function createInvoice(params: { customerId: string; tenantId: string; periodStart:
Date; periodEnd: Date; lineItems: Array<{ description: string; amount: number; quantity: num-
ber; metadata?: Record<string, string>; }>; metadata?: Record<string, string>; }, logger: Log-
ger): Promise<Stripe.Invoice> { const stripe = await getStripeClient();

for (const item of params.lineItems) { await stripe.invoiceItems.create({ customer: params.customerId,
amount: item.amount, currency: 'usd', description: item.description, quantity: item.quantity,
metadata: item.metadata, }); }

const invoice = await stripe.invoices.create({ customer: params.customerId, auto_advance:
true, collection_method: 'charge_automatically', metadata: { tenantId: params.tenantId,
periodStart: params.periodStart.toISOString(), periodEnd: params.periodEnd.toISOString(),
...params.metadata, }, });

logger.info('Created Stripe invoice', { tenantId: params.tenantId, invoiceId: invoice.id }); return
invoice; }

export async function getInvoiceStatus(invoiceId: string, logger: Logger): Promise<{ status:
string; paid: boolean; amountDue: number; amountPaid: number; }> { const stripe = await
getStripeClient(); const invoice = await stripe.invoices.retrieve(invoiceId); return { status: in-
voice.status || 'unknown', paid: invoice.paid, amountDue: invoice.amount_due, amountPaid:
invoice.amount_paid, }, } ““

```

PART 2: INVITATIONS LAMBDA

packages/infrastructure/lambda/admin/invitations.ts

```

““typescript /** * Administrator Invitation Lambda * Handles email-based administrator invita-
tions with secure tokens */

```

```

import { APIGatewayProxyEvent, APIGatewayProxyResult, Context } from 'aws-lambda';
import { v4 as uuidv4 } from 'uuid'; import { Logger } from '../shared/logger'; import {
success, created, handleError } from '../shared/response'; import { extractAuthContext, re-
quireAdmin, requirePermission } from '../shared/auth'; import { ValidationError, NotFoundError,
ForbiddenError } from '../shared/errors'; import { executeQuery, createAuditLog } from
'../shared/db'; import { createInvitationSchema, acceptInvitationSchema, ROLE_HIERARCHY
} from '../shared/admin/types'; import { generateInvitationToken, hashToken, calculateEx-
piry, isExpired } from '../shared/admin/tokens'; import { sendEmail, generateInvitationEmail
} from '../shared/admin/email'; import { CognitoIdentityProviderClient, AdminCreateUser-
Command, AdminAddUserToGroupCommand, AdminSetUserMFAPreferenceCommand, } from
'@aws-sdk/client-cognito-identity-provider';

const logger = new Logger({ handler: 'invitations' }); const cognitoClient = new CognitoIdenti-
tyProviderClient({});

export async function handler( event: APIGatewayProxyEvent, context: Context ): Promise {
const requestLogger = logger.child({ requestId: context.awsRequestId, path: event.path });

try { const invitationId = event.pathParameters?.invitationId; const action = event.path.split('/').pop();

switch (event.httpMethod) {
  case 'GET':
    if (invitationId) return await handleGetInvitation(invitationId, event, requestLogger);
    return await handleListInvitations(event, requestLogger);

  case 'POST':
    if (action === 'accept') return await handleAcceptInvitation(event, requestLogger);
    if (action === 'resend' && invitationId) return await handleResendInvitation(invitationId,
return await handleCreateInvitation(event, requestLogger);

  case 'DELETE':
    if (!invitationId) throw new ValidationError('Invitation ID required');
    return await handleRevokeInvitation(invitationId, event, requestLogger);

  default:
    throw new ValidationError(`Method \${event.httpMethod} not allowed`);
}

} catch (error) { return handleError(error, requestLogger); } }

async function handleCreateInvitation(event: APIGatewayProxyEvent, logger: Logger): Promise
{ const auth = extractAuthContext(event); requireAdmin(auth); requirePermission(auth, 'ad-
min:write');

const body = event.body ? JSON.parse(event.body) : {}; const parseResult = createInvitation-
Schema.safeParse(body); if (!parseResult.success) { throw new ValidationError('Invalid request
body', parseResult.error.flatten().fieldErrors as Record<string, string[]>); }

const { email, role, message, expiresInHours } = parseResult.data;

// Validate role hierarchy if (ROLE_HIERARCHY[role] > ROLE_HIERARCHY[auth.role as keyof
typeof ROLE_HIERARCHY]) { throw new ForbiddenError('Cannot invite administrator with

```



```

higher role than your own'); }

// Check existing admin/invitation const existingAdmin = await executeQuery( 'SELECT id
FROM administrators WHERE email = $1 AND tenant_id = $2', [email, auth.tenantId], log-
ger ); if (existingAdmin.rowCount > 0) { throw new ValidationError('An administrator with this
email already exists'); }

const pendingInvitation = await executeQuery( 'SELECT id FROM invitations WHERE email = $1
AND tenant_id = $2 AND status = 'pending' AND expires_at > NOW()', [email, auth.tenantId],
logger ); if (pendingInvitation.rowCount > 0) { throw new ValidationError('A pending invitation
already exists for this email'); }

// Generate token and create invitation const { token, tokenHash } = generateInvitationToken();
const expiresAt = calculateExpiry(expiresInHours); const invitationId = uuidv4();

const inviterResult = await executeQuery('SELECT first_name, last_name FROM administrators
WHERE id = $1', [auth.userId], logger); const inviterName = inviterResult.rows[0] ? `${inviterRe-
sult.rows[0].first_name} ${inviterResult.rows[0].last_name}` : 'An administrator';

const appResult = await executeQuery('SELECT name FROM apps WHERE id = $1',
[auth.appId], logger); const appName = appResult.rows[0]?name || auth.appId;

await executeQuery( 'INSERT INTO invitations (id, email, role, invited_by, app_id, tenant_id,
environment, token_hash, expires_at, status, message, created_at) VALUES ($1, $2, $3, $4,
$5, $6, $7, $8, $9, 'pending', $10, NOW())', [invitationId, email, role, auth.userId, auth.appId,
auth.tenantId, auth.environment, tokenHash, expiresAt, message || null], logger );

// Send email const acceptUrl = `${process.env.ADMIN_URL}/invite/accept?token=${token}`;
const emailContent = generateInvitationEmail({ inviteeName: "", inviterName, role, appName,
environment: auth.environment, acceptUrl, expiresAt, message, }); await sendEmail({ to: email,
subject: 'You've been invited to ${appName}', html: emailContent.html, text: emailContent.text
}, logger);

await createAuditLog({ tenant_id: auth.tenantId, user_id: null, admin_id: auth.userId,
action: 'invitation.create', resource_type: 'invitation', resource_id: invitationId, details: {
email, role, expiresAt }, ip_address: event.requestContext.identity?.sourceIp || null, user_agent:
event.headers['User-Agent'] || null, }, logger);

logger.info('Invitation created and sent', { invitationId, email, role }); return created({ invitation:
{ id: invitationId, email, role, status: 'pending', expiresAt, createdAt: new Date().toISOString() }
}); }

async function handleAcceptInvitation(event: APIGatewayProxyEvent, logger: Logger): Promise
{ const body = event.body ? JSON.parse(event.body) : {}; const parseResult = acceptInvita-
tionSchema.safeParse(body); if (!parseResult.success) { throw new ValidationError('Invalid request
body', parseResult.error.flatten().fieldErrors as Record<string, string[]>); }

const { token, firstName, lastName, password, mfaMethod, phone } = parseResult.data;

const tokenHash = hashToken(token); const inviteResult = await executeQuery( 'SELECT *
FROM invitations WHERE token_hash = $1 AND status = 'pending'', [tokenHash], logger ); if
(inviteResult.rowCount === 0) throw new NotFoundError('Invalid or expired invitation');

```

```

const invitation = inviteResult.rows[0]; if (isExpired(invitation.expires_at)) { await executeQuery('UPDATE invitations SET status = 'expired' WHERE id = $1', [invitation.id], logger); throw new ValidationError('This invitation has expired'); }

if (invitation.environment === 'prod' && mfaMethod === 'sms' && !phone) { throw new ValidationError('Phone number required for SMS MFA'); }

const userPoolId = process.env.ADMIN_USER_POOL_ID; const adminUserId = uuidv4();

// Create Cognito user await cognitoClient.send(new AdminCreateUserCommand({ UserPoolId: userPoolId, Username: invitation.email, TemporaryPassword: password, UserAttributes: [ { Name: 'email', Value: invitation.email }, { Name: 'email_verified', Value: 'true' }, { Name: 'given_name', Value: firstName }, { Name: 'family_name', Value: lastName }, { Name: 'custom:adminId', Value: adminUserId }, { Name: 'custom:tenantId', Value: invitation.tenant_id }, { Name: 'custom:role', Value: invitation.role }, ], MessageAction: 'SUPPRESS', }));

await cognitoClient.send(new AdminAddUserToGroupCommand({ UserPoolId: userPoolId, Username: invitation.email, GroupName: invitation.role, }));

if (invitation.environment === 'prod') { await cognitoClient.send(new AdminSetUserMFAPreferenceCommand({ UserPoolId: userPoolId, Username: invitation.email, SoftwareTokenMfaSettings: mfaMethod === 'authenticator' ? { Enabled: true, PreferredMfa: true } : undefined, SMSMfaSettings: mfaMethod === 'sms' ? { Enabled: true, PreferredMfa: true } : undefined, })); }

// Create admin user record await executeQuery( 'INSERT INTO administrators (id, cognito_user_id, email, first_name, last_name, display_name, role, app_id, tenant_id, mfa_enabled, mfa_method, status, created_at, updated_at, created_by, invitation_id) VALUES ($1, $2, $3, $4, $5, $6, $7, $8, $9, $10, $11, 'active', NOW(), NOW(), $12, $13)', [adminUserId, invitation.email, invitation.email, firstName, lastName, `${firstName} ${lastName}`, invitation.role, invitation.app_id, invitation.tenant_id, invitation.environment === 'prod', mfaMethod, invitation.invited_by, invitation.id], logger );

// Create default profile await executeQuery( 'INSERT INTO admin_profiles (admin_id, notifications, timezone, language, date_format, time_format, currency, theme, default_environment, sidebar_collapsed, table_rows_per_page, updated_at) VALUES ($1, $2, 'America/New_York', 'en', 'MM/DD/YYYY', '12h', 'USD', 'system', $3, false, 25, NOW())', [adminUserId, JSON.stringify({ method: 'email', frequency: 'immediate', categories: { security: true, billing: true, deployments: true, approvals: true, system: true } })], invitation.environment], logger );

await executeQuery( 'UPDATE invitations SET status = 'accepted', accepted_at = NOW(), accepted_by_ip = $2 WHERE id = $1', [invitation.id, event.requestContext.identity?.sourceIp || null], logger );

await createAuditLog({ tenant_id: invitation.tenant_id, user_id: null, admin_id: adminUserId, action: 'invitation.accept', resource_type: 'invitation', resource_id: invitation.id, details: { email: invitation.email, role: invitation.role, firstName, lastName }, ip_address: event.requestContext.identity?.sourceIp || null, user_agent: event.headers['User-Agent'] || null, }, logger);

logger.info('Invitation accepted', { invitationId: invitation.id, adminUserId, email: invitation.email }); return success({ message: 'Invitation accepted successfully', adminUser: { id:

```

```

adminUserId, email: invitation.email, firstName, lastName, role: invitation.role, mfaRequired:
invitation.environment === 'prod' }, }); }

async function handleListInvitations(event: APIGatewayProxyEvent, logger: Logger): Promise
{ const auth = extractAuthContext(event); requireAdmin(auth); requirePermission(auth, 'ad-
min:read');

const status = event.queryStringParameters?.status; const limit = parseInt(event.queryStringParameters?.limit
|| '50'); const offset = parseInt(event.queryStringParameters?.offset || '0');

let query = 'SELECT i.*, a.first_name as inviter_first_name, a.last_name as inviter_last_name
FROM invitations i LEFT JOIN administrators a ON i.invited_by = a.id WHERE i.tenant_id =
$1'; const params: any[] = [auth.tenantId];

if (status) { params.push(status); query += ' AND i.status = ${params.length}'; } query += '
ORDER BY i.created_at DESC LIMIT ${params.length + 1} OFFSET ${params.length + 2}';
params.push(limit, offset);

const result = await executeQuery(query, params, logger); const invitations = result.rows.map(row
=> ({ id: row.id, email: row.email, role: row.role, status: row.status, environment:
row.environment, invitedBy: { id: row.invited_by, name: row.inviter_first_name ? `${row.inviter_first_name}
${row.inviter_last_name}` : 'Unknown' }, message: row.message, expiresAt: row.expires_at,
createdAt: row.created_at, acceptedAt: row.accepted_at, }));

return success({ invitations, pagination: { limit, offset, hasMore: invitations.length === limit }
}); }

async function handleGetInvitation(invitationId: string, event: APIGatewayProxyEvent, logger:
Logger): Promise { const auth = extractAuthContext(event); requireAdmin(auth); requirePermis-
sion(auth, 'admin:read');

const result = await executeQuery( 'SELECT i.*, a.first_name as inviter_first_name, a.last_name
as inviter_last_name FROM invitations i LEFT JOIN administrators a ON i.invited_by = a.id
WHERE i.id = $1 AND i.tenant_id = $2', [invitationId, auth.tenantId], logger ); if (re-
sult.rowCount === 0) throw new NotFoundError('Invitation not found');

const row = result.rows[0]; return success({ invitation: { id: row.id, email: row.email, role:
row.role, status: row.status, environment: row.environment, invitedBy: { id: row.invited_by,
name: `${row.inviter_first_name} ${row.inviter_last_name}`, }, message: row.message, expire-
sAt: row.expires_at, createdAt: row.created_at, acceptedAt: row.accepted_at, }, }); }

async function handleResendInvitation(invitationId: string, event: APIGatewayProxyEvent, log-
ger: Logger): Promise { const auth = extractAuthContext(event); requireAdmin(auth); requirePer-
mission(auth, 'admin:write');

const result = await executeQuery('SELECT * FROM invitations WHERE id = $1 AND tenant_id
= $2', [invitationId, auth.tenantId], logger); if (result.rowCount === 0) throw new NotFoundEr-
ror('Invitation not found');

const invitation = result.rows[0]; if (invitation.status !== 'pending') throw new Validation-
Error('Cannot resend ${invitation.status} invitation');

const { token, tokenHash } = generateInvitationToken(); const expiresAt = calculateExpiry(48);

```

```

await executeQuery('UPDATE invitations SET token_hash = $2, expires_at = $3 WHERE id = $1', [invitationId, tokenHash, expiresAt], logger);

const inviterResult = await executeQuery('SELECT first_name, last_name FROM administrators WHERE id = $1', [auth.userId], logger); const inviterName = inviterResult.rows[0] ? `${inviterResult.rows[0].first_name} ${inviterResult.rows[0].last_name}` : 'An administrator';

const appResult = await executeQuery('SELECT name FROM apps WHERE id = $1', [auth.appId], logger); const appName = appResult.rows[0]?.name || auth.appId;

const acceptUrl = `${process.env.ADMIN_URL}/invite/accept?token=${token}`; const emailContent = generateInvitationEmail({ inviteeName: '', inviterName, role: invitation.role, appName, environment: invitation.environment, acceptUrl, expiresAt, message: invitation.message }); await sendEmail({ to: invitation.email, subject: 'Reminder: You've been invited to ${appName}', html: emailContent.html, text: emailContent.text }, logger);

logger.info('Invitation resent', { invitationId, email: invitation.email }); return success({ message: 'Invitation resent successfully', expiresAt }); }

async function handleRevokeInvitation(invitationId: string, event: APIGatewayProxyEvent, logger: Logger): Promise { const auth = extractAuthContext(event); requireAdmin(auth); requirePermission(auth, 'admin:write');

const result = await executeQuery('SELECT * FROM invitations WHERE id = $1 AND tenant_id = $2', [invitationId, auth.tenantId], logger); if (result.rowCount === 0) throw new NotFoundError('Invitation not found');

const invitation = result.rows[0]; if (invitation.status !== 'pending') throw new ValidationError('Cannot revoke ${invitation.status} invitation');

await executeQuery('UPDATE invitations SET status = 'revoked' WHERE id = $1', [invitationId], logger);

await createAuditLog({ tenant_id: auth.tenantId, user_id: null, admin_id: auth.userId, action: 'invitation.revoke', resource_type: 'invitation', resource_id: invitationId, details: { email: invitation.email }, ip_address: event.requestContext.identity?.sourceIp || null, user_agent: event.headers['User-Agent'] || null, }, logger);

logger.info('Invitation revoked', { invitationId, email: invitation.email }); return success({ message: 'Invitation revoked successfully' }); }

```

PART 3: TWO-PERSON APPROVALS LAMBDA

packages/infrastructure/lambda/admin/approvals.ts

```

““typescript /** * Two-Person Approval Workflow Lambda * Production deployments require separate initiator and approver */

```

```

import { APIGatewayProxyEvent, APIGatewayProxyResult, Context } from 'aws-lambda'; import { v4 as uuidv4 } from 'uuid'; import { Logger } from '../shared/logger'; import { success, created, handleError } from '../shared/response'; import { extractAuthContext, requireAdmin, requirePermission } from '../shared/auth'; import { ValidationError, NotFoundError, ForbiddenError } from

```

```

'../shared/errors'; import { executeQuery, createAuditLog } from '../shared/db'; import { createApprovalSchema, processApprovalSchema, ApprovalStatus, AdminRole, ROLE_HIERARCHY } from '../shared/admin/types'; import { calculateExpiry, isExpired } from '../shared/admin/tokens'; import { sendEmail, generateApprovalEmail } from '../shared/admin/email';

const logger = new Logger({ handler: 'approvals' });

export async function handler(event: APIGatewayProxyEvent, context: Context): Promise { const requestLogger = logger.child({ requestId: context.awsRequestId, path: event.path });

try { const auth = extractAuthContext(event); requireAdmin(auth);

const approvalId = event.pathParameters?.approvalId;
const action = event.path.split('/').pop();

switch (event.httpMethod) {
  case 'GET':
    if (approvalId) return await handleGetApproval(approvalId, auth, requestLogger);
    return await handleListApprovals(event, auth, requestLogger);
  case 'POST':
    if (action === 'process' && approvalId) return await handleProcessApproval(approvalId, event, auth, requestLogger);
    return await handleCreateApproval(event, auth, requestLogger);
  case 'DELETE':
    if (!approvalId) throw new ValidationError('Approval ID required');
    return await handleCancelApproval(approvalId, event, auth, requestLogger);
  default:
    throw new ValidationError(`Method ${event.httpMethod} not allowed`);
}

} catch (error) { return handleError(error, requestLogger); } }

async function handleCreateApproval(event: APIGatewayProxyEvent, auth: ReturnTypes, logger: Logger): Promise { requirePermission(auth, 'approvals:initiate');

const body = event.body ? JSON.parse(event.body) : {}; const parseResult = createApprovalSchema.safeParse(body); if (!parseResult.success) throw new ValidationError('Invalid request body', parseResult.error.flatten().fieldErrors as Record<string, string[]>);

const { type, action, resourceType, resourceId, details, priority, notes, expiresInHours } = parseResult.data; const requiresTwoPersonApproval = auth.environment === 'prod';

const requesterResult = await executeQuery('SELECT first_name, last_name FROM administrators WHERE id = $1', [auth.userId], logger); const requesterName = requesterResult.rows[0] ? `${requesterResult.rows[0].first_name} ${requesterResult.rows[0].last_name}` : 'Unknown';

const approvalId = uuidv4(); const expiresAt = calculateExpiry(expiresInHours);

await executeQuery( 'INSERT INTO approval_requests (id, type, app_id, tenant_id, environment, requested_by, requested_at, expires_at, status, action, resource_type, resource_id, details, priority, notes, requires_two_person, created_at) VALUES ($1, $2, $3, $4, $5, $6, NOW(), $7, 'pending', $8, $9, $10, $11, $12, $13, $14, NOW())', [approvalId, type, auth.appId, auth.tenantId, auth.environment, auth.userId, expiresAt, action, resourceType, resourceId, JSON.stringify(details), priority, notes || null, requiresTwoPersonApproval], logger );

```

```

if (requiresTwoPersonApproval) { await notifyApprovers(approvalId, auth, requesterName, logger);
}

await createAuditLog({ tenant_id: auth.tenantId, user_id: null, admin_id: auth.userId, action:
'approval.create', resource_type: 'approval_request', resource_id: approvalId, details: { type, re-
sourceType, resourceId, requiresTwoPersonApproval }, ip_address: event.requestContext.identity?.sourceIp
|| null, user_agent: event.headers['User-Agent'] || null, }, logger);

logger.info('Approval request created', { approvalId, type, requestedBy: auth.userId, requiresT-
woPersonApproval }); return created({ approval: { id: approvalId, type, status: 'pending', ac-
tion, resourceType, resourceId, priority, expiresAt, requiresTwoPersonApproval, createdAt: new
Date().toISOString() }, }); }

async function handleProcessApproval(approvalId: string, event: APIGatewayProxyEvent, auth:
ReturnType, logger: Logger): Promise { requirePermission(auth, 'approvals:*');

const body = event.body ? JSON.parse(event.body) : {}; const parseResult = processAp-
provalSchema.safeParse(body); if (!parseResult.success) throw new ValidationError('Invalid
request body', parseResult.error.flatten().fieldErrors as Record<string, string[]>);

const { action, reason } = parseResult.data;

const result = await executeQuery('SELECT * FROM approval_requests WHERE id = $1 AND
tenant_id = $2', [approvalId, auth.tenantId], logger); if (result.rowCount === 0) throw new Not-
FoundError('Approval request not found');

const approval = result.rows[0]; if (approval.status !== 'pending') throw new Validation-
Error('Cannot process ${approval.status} approval request'); if (isExpired(approval.expires_at))
{ await executeQuery('UPDATE approval_requests SET status = 'expired' WHERE id = $1',
[approvalId], logger); throw new ValidationError('This approval request has expired'); }

// Two-person approval: cannot approve own request if (approval.requires_two_person && ap-
proval.requested_by === auth.userId) { throw new ForbiddenError('You cannot approve your
own request. Production deployments require approval from a different administrator.')} }

const newStatus: ApprovalStatus = action === 'approve' ? 'approved' : 'rejected'; await exe-
cuteQuery('UPDATE approval_requests SET status = $2, approved_by = $3, approved_at =
NOW(), rejected_reason = $4 WHERE id = $1', [approvalId, newStatus, auth.userId, action ===
'reject' ? reason : null], logger );

if (action === 'approve') { await executeApprovedAction(approval, logger); }

await createAuditLog({ tenant_id: auth.tenantId, user_id: null, admin_id: auth.userId, action:
'approval.${action}', resource_type: 'approval_request', resource_id: approvalId, details: { type:
approval.type, resourceType: approval.resource_type, resourceId: approval.resource_id, reason
}, ip_address: event.requestContext.identity?.sourceIp || null, user_agent: event.headers['User-
Agent'] || null, }, logger);

logger.info('Approval request processed', { approvalId, action, processedBy: auth.userId }); return
success({ approval: { id: approvalId, status: newStatus, processedBy: auth.userId, processedAt:
new Date().toISOString(), reason: action === 'reject' ? reason : undefined } }); }

async function executeApprovedAction(approval: any, logger: Logger): Promise { log-
ger.info('Executing approved action', { type: approval.type, resourceType: approval.resource_type,

```

```
resourceId: approval.resource_id });
```

```
switch (approval.type) { case 'deployment': // Trigger deployment workflow via Step
Functions or CodePipeline break; case 'promotion': await executeQuery('UPDATE de-
ployments SET promoted_to = $2, promoted_at = NOW() WHERE id = $1', [ap-
proval.resource_id, approval.details?.targetEnv], logger); break; case 'model_activation':
await executeQuery('UPDATE ai_models SET status = $2, thermal_state = $3, up-
dated_at = NOW() WHERE id = $1', [approval.details?.modelId, approval.details?.newStatus,
approval.details?.thermalState], logger); break; case 'provider_change': await execute-
Query('UPDATE ai_providers SET config = $2, updated_at = NOW() WHERE id =
$1', [approval.details?.providerId, JSON.stringify(approval.details?.config)], logger); break;
case 'user_role_change': await executeQuery('UPDATE administrators SET role = $2, up-
dated_at = NOW() WHERE id = $1', [approval.details?.userId, approval.details?.newRole],
logger); break; case 'billing_change': await executeQuery('UPDATE billing_settings SET
margin_percent = COALESCE($2, margin_percent), tax_percent = COALESCE($3,
tax_percent), updated_at = NOW() WHERE tenant_id = $1', [approval.details?.tenantId,
approval.details?.settings?.marginPercent, approval.details?.settings?.taxPercent], logger); break;
default: logger.warn('Unknown approval type', { type: approval.type }); } }
```

```
async function notifyApprovers(approvalId: string, auth: ReturnType, requesterName: string, log-
ger: Logger): Promise { const result = await executeQuery('SELECT id, email, first_name,
last_name FROM administrators WHERE tenant_id = $1 AND id != $2 AND status = 'active'
AND role IN ('super_admin', 'admin')', [auth.tenantId, auth.userId], logger ); if (result.rowCount
=== 0) { logger.warn('No other admins available to approve'); return; }
```

```
const appResult = await executeQuery('SELECT name FROM apps WHERE id = $1',
[auth.appId], logger); const appName = appResult.rows[0]?.name || auth.appId;
```

```
const approvalResult = await executeQuery('SELECT * FROM approval_requests WHERE id =
$1', [approvalId], logger); const approval = approvalResult.rows[0];
```

```
for (const admin of result.rows) { const approveUrl = `${process.env.ADMIN_URL}/approvals/${approvalId}?acti
const rejectUrl = `${process.env.ADMIN_URL}/approvals/${approvalId}?action=reject`; const
emailContent = generateApprovalEmail({ approverName: admin.first_name, requester-
Name, appName, environment: auth.environment, action: approval.action, resourceType:
approval.resource_type, resourceId: approval.resource_id, approveUrl, rejectUrl, expiresAt:
approval.expires_at, }); await sendEmail({ to: admin.email, subject: 'ÃcÃ¡Ã Ã-Ã,Ã Approval
Required: ${approval.action} - ${appName}', html: emailContent.html, text: emailContent.text
}, logger); } logger.info('Approvers notified', { approvalId, notifiedCount: result.rowCount }); }
```

```
async function handleListApprovals(event: APIGatewayProxyEvent, auth: ReturnType, logger:
Logger): Promise { requirePermission(auth, 'approvals:read');
```

```
const status = event.queryStringParameters?.status; const pendingForMe = event.queryStringParameters?.pending
=== 'true'; const limit = parseInt(event.queryStringParameters?.limit || '50'); const offset =
parseInt(event.queryStringParameters?.offset || '0');
```

```
let query = 'SELECT ar.*, req.first_name as requester_first_name, req.last_name as
requester_last_name FROM approval_requests ar LEFT JOIN administrators req ON
ar.requested_by = req.id WHERE ar.tenant_id = $1'; const params: any[] = [auth.tenantId];
```

```
if (status) { params.push(status); query += ' AND ar.status = $$${params.length}'; } if (pending-
```

```
ForMe) { params.push(auth.userId); query += ' AND ar.status = 'pending' AND ar.requested_by
!= ${params.length}'; } query += ' ORDER BY ar.created_at DESC LIMIT ${params.length
+ 1} OFFSET ${params.length + 2}'; params.push(limit, offset);
```

```
const result = await executeQuery(query, params, logger); const approvals = result.rows.map(row
=> ({ id: row.id, type: row.type, status: row.status, environment: row.environment, ac-
tion: row.action, resourceType: row.resource_type, resourceId: row.resource_id, priority:
row.priority, requestedBy: { id: row.requested_by, name: `${row.requester_first_name}
${row.requester_last_name}`, }, requestedAt: row.requested_at, expiresAt: row.expires_at,
requiresTwoPersonApproval: row.requires_two_person, canApprove: row.status === 'pending'
&& row.requested_by !== auth.userId, }));
```

```
return success({ approvals, pagination: { limit, offset, hasMore: approvals.length === limit } });
}
```

```
async function handleGetApproval(approvalId: string, auth: ReturnType, logger: Logger):
Promise { requirePermission(auth, 'approvals:read');
```

```
const result = await executeQuery( 'SELECT ar.*, req.first_name as requester_first_name,
req.last_name as requester_last_name, req.email as requester_email FROM approval_requests
ar LEFT JOIN administrators req ON ar.requested_by = req.id WHERE ar.id = $1 AND
ar.tenant_id = $2', [approvalId, auth.tenantId], logger ); if (result.rowCount === 0) throw new
NotFoundError('Approval request not found');
```

```
const row = result.rows[0]; return success({ approval: { id: row.id, type: row.type, status:
row.status, environment: row.environment, action: row.action, resourceType: row.resource_type,
resourceId: row.resource_id, details: row.details, priority: row.priority, notes: row.notes, request-
edBy: { id: row.requested_by, name: `${row.requester_first_name} ${row.requester_last_name}`,
email: row.requester_email }, requestedAt: row.requested_at, expiresAt: row.expires_at, re-
quiresTwoPersonApproval: row.requires_two_person, canApprove: row.status === 'pending'
&& row.requested_by !== auth.userId, }, }); }
```

```
async function handleCancelApproval(approvalId: string, event: APIGatewayProxyEvent, auth:
ReturnType, logger: Logger): Promise { const result = await executeQuery('SELECT * FROM
approval_requests WHERE id = $1 AND tenant_id = $2', [approvalId, auth.tenantId], logger); if
(result.rowCount === 0) throw new NotFoundError('Approval request not found');
```

```
const approval = result.rows[0]; if (approval.requested_by !== auth.userId && auth.role !==
AdminRole.SUPER_ADMIN) { throw new ForbiddenError('Only the requester or a super admin
can cancel this request'); } if (approval.status !== 'pending') throw new ValidationError('Cannot
cancel ${approval.status} approval request');
```

```
await executeQuery('UPDATE approval_requests SET status = 'cancelled' WHERE id =
$1', [approvalId], logger); await createAuditLog({ tenant_id: auth.tenantId, user_id: null,
admin_id: auth.userId, action: 'approval.cancel', resource_type: 'approval_request', resource_id:
approvalId, details: { type: approval.type }, ip_address: event.requestContext.identity?.sourceIp
|| null, user_agent: event.headers['User-Agent'] || null, }, logger);
```

```
logger.info('Approval request cancelled', { approvalId }); return success({ message: 'Approval re-
quest cancelled' }); } ““
```


PART 4: METERING LAMBDA

packages/infrastructure/lambda/billing/metering.ts

```
““typescript /** * Usage Metering Lambda * Collects and stores usage events for billing calculations
*/

import { APIGatewayProxyEvent, APIGatewayProxyResult, Context } from 'aws-lambda'; import
{ DynamoDBClient } from '@aws-sdk/client-dynamodb'; import { DynamoDBDocumentClient,
PutCommand, QueryCommand, UpdateCommand } from '@aws-sdk/lib-dynamodb'; import { v4
as uuidv4 } from 'uuid'; import { z } from 'zod'; import { Logger } from '../shared/logger'; import
{ success, created, handleError } from '../shared/response'; import { extractAuthContext } from
'../shared/auth'; import { ValidationError } from '../shared/errors'; import { executeQuery } from
'../shared/db';

const logger = new Logger({ handler: 'metering' }); const ddbClient = DynamoDBDocument-
Client.from(new DynamoDBClient({}), { marshallOptions: { removeUndefinedValues: true } });

const USAGE_TABLE = process.env.USAGE_TABLE || 'radiant-usage-events'; const
ROLLUP_TABLE = process.env.ROLLUP_TABLE || 'radiant-usage-rollups';

const recordUsageSchema = z.object({ requestId: z.string(), providerId: z.string(), modelId:
z.string(), modelName: z.string(), requestType: z.enum(['chat', 'embedding', 'image', 'audio',
'video']), inputTokens: z.number().int().min(0), outputTokens: z.number().int().min(0), latencyMs:
z.number().int().min(0), cached: z.boolean().default(false), phiDetected: z.boolean().default(false),
phiSanitized: z.boolean().default(false), userId: z.string().optional(), });

export async function handler(event: APIGatewayProxyEvent, context: Context): Promise { const
requestLogger = logger.child({ requestId: context.awsRequestId, path: event.path });

try { const auth = extractAuthContext(event); const action = event.path.split('/').pop();

switch (event.httpMethod) {
  case 'POST':
    if (action === 'record') return await handleRecordUsage(event, auth, requestLogger);
    if (action === 'batch') return await handleBatchRecord(event, auth, requestLogger);
    break;
  case 'GET':
    if (action === 'summary') return await handleGetSummary(event, auth, requestLogger);
    if (action === 'rollups') return await handleGetRollups(event, auth, requestLogger);
    break;
}

throw new ValidationError(`Unknown action: ${action}`);

} catch (error) { return handleError(error, requestLogger); } }

async function handleRecordUsage(event: APIGatewayProxyEvent, auth: Return type, logger:
Logger): Promise { const body = event.body ? JSON.parse(event.body) : {}; const parseResult =
recordUsageSchema.safeParse(body); if (!parseResult.success) throw new ValidationError('Invalid
usage data', parseResult.error.flatten().fieldErrors as Record<string, string[]>);

const data = parseResult.data;

// Get pricing from model registry const pricing = await getModelPricing(data.modelId, logger);
```

```
const inputCost = (data.inputTokens / 1000000) * pricing.inputPricePerMillion; const outputCost
= (data.outputTokens / 1000000) * pricing.outputPricePerMillion; const providerCost = inputCost
+ outputCost;
```

```
// Apply margin const marginPercent = await getTenantMargin(auth.tenantId, logger); const
billedCost = providerCost * (1 + marginPercent / 100);
```

```
const usageEvent = { id: uuidv4(), timestamp: new Date().toISOString(), tenantId: auth.tenantId,
userId: data.userId || auth.userId, adminId: auth.isAdmin ? auth.userId : undefined, appId:
auth.appId, environment: auth.environment, providerId: data.providerId, modelId: data.modelId,
modelName: data.modelName, requestType: data.requestType, inputTokens: data.inputTokens,
outputTokens: data.outputTokens, totalTokens: data.inputTokens + data.outputTokens, provider-
Cost, billedCost, currency: 'USD', requestId: data.requestId, latencyMs: data.latencyMs, cached:
data.cached, phiDetected: data.phiDetected, phiSanitized: data.phiSanitized, };
```

```
await ddbClient.send(new PutCommand({ TableName: USAGE_TABLE, Item: { pk: 'TEN-
ANT#${auth.tenantId}', sk: 'EVENT#${usageEvent.timestamp}#${usageEvent.id}', ...us-
ageEvent, ttl: Math.floor(Date.now() / 1000) + (90 * 24 * 60 * 60) }, }));
```

```
await updateDailyRollup(usageEvent, logger);
```

```
logger.info('Usage recorded', { eventId: usageEvent.id, modelId: data.modelId, tokens: us-
ageEvent.totalTokens, cost: billedCost }); return created({ event: { id: usageEvent.id, billedCost,
providerCost } }); }
```

```
async function handleBatchRecord(event: APIGatewayProxyEvent, auth: Return type, logger:
Logger): Promise { const body = event.body ? JSON.parse(event.body) : {}; if (!Ar-
ray.isArray(body.events) || body.events.length === 0) throw new ValidationError('events array
is required'); if (body.events.length > 100) throw new ValidationError('Maximum 100 events per
batch');
```

```
const results: Array<{ id: string; success: boolean; error?: string }> = [];
```

```
for (const eventData of body.events) { try { const parseResult = recordUsageSchema.safeParse(eventData);
if (!parseResult.success) { results.push({ id: eventData.requestId || 'unknown', success: false, error:
'Invalid data' }); continue; }
```

```
const data = parseResult.data;
```

```
const pricing = await getModelPricing(data.modelId, logger);
```

```
const providerCost = ((data.inputTokens / 1000000) * pricing.inputPricePerMillion) + ((data.
```

```
const marginPercent = await getTenantMargin(auth.tenantId, logger);
```

```
const billedCost = providerCost * (1 + marginPercent / 100);
```

```
const usageEvent = {
```

```
id: uuidv4(), timestamp: new Date().toISOString(), tenantId: auth.tenantId, userId: data.u
```

```
appId: auth.appId, environment: auth.environment, providerId: data.providerId, modelId: da
```

```
requestType: data.requestType, inputTokens: data.inputTokens, outputTokens: data.outputTok
```

```
providerCost, billedCost, currency: 'USD', requestId: data.requestId, latencyMs: data.late
```

```
};
```

```
await ddbClient.send(new PutCommand({ TableName: USAGE_TABLE, Item: { pk: `TENANT#${auth.t
```

```
await updateDailyRollup(usageEvent, logger);
```

```

    results.push({ id: usageEvent.id, success: true });
  } catch (error: any) {
    results.push({ id: eventData.requestId || 'unknown', success: false, error: error.message })
  }
}

logger.info('Batch usage recorded', { total: body.events.length, successful: results.filter(r => r.success).length }); return success({ results, summary: { total: results.length, successful: results.filter(r => r.success).length, failed: results.filter(r => !r.success).length } }); }

async function handleGetSummary(event: APIGatewayProxyEvent, auth: Return Type, logger: Logger): Promise { const startDate = event.queryStringParameters?.startDate || getDefaultStartDate(); const endDate = event.queryStringParameters?.endDate || getTodayDate();

const response = await ddbClient.send(new QueryCommand({ TableName: ROLLUP_TABLE, KeyConditionExpression: 'pk = :pk AND sk BETWEEN :start AND :end', ExpressionAttributeValues: { ':pk': 'TENANT#${auth.tenantId}', ':start': 'DATE#${startDate}', ':end': 'DATE#${endDate}#~' }, }));

const rollups = response.Items || []; const totals = rollups.reduce((acc, r) => ({ requests: acc.requests + (r.requestCount || 0), inputTokens: acc.inputTokens + (r.inputTokens || 0), outputTokens: acc.outputTokens + (r.outputTokens || 0), providerCost: acc.providerCost + (r.providerCost || 0), billedCost: acc.billedCost + (r.billedCost || 0), }, { requests: 0, inputTokens: 0, outputTokens: 0, providerCost: 0, billedCost: 0 }));

return success({ period: { startDate, endDate }, totals }); }

async function handleGetRollups(event: APIGatewayProxyEvent, auth: Return Type, logger: Logger): Promise { const startDate = event.queryStringParameters?.startDate || getDefaultStartDate(); const endDate = event.queryStringParameters?.endDate || getTodayDate();

const response = await ddbClient.send(new QueryCommand({ TableName: ROLLUP_TABLE, KeyConditionExpression: 'pk = :pk AND sk BETWEEN :start AND :end', ExpressionAttributeValues: { ':pk': 'TENANT#${auth.tenantId}', ':start': 'DATE#${startDate}', ':end': 'DATE#${endDate}#~' }, }));

const rollups = (response.Items || []).map(item => ({ date: item.date, modelId: item.modelId, providerId: item.providerId, requestCount: item.requestCount, inputTokens: item.inputTokens, outputTokens: item.outputTokens, totalTokens: item.totalTokens, providerCost: item.providerCost, billedCost: item.billedCost, avgLatencyMs: item.avgLatencyMs, }));

return success({ rollups, period: { startDate, endDate } }); }

async function updateDailyRollup(event: any, logger: Logger): Promise { const date = event.timestamp.split('T')[0]; try { await ddbClient.send(new UpdateCommand({ TableName: ROLLUP_TABLE, Key: { pk: 'TENANT#${event.tenantId}', sk: 'DATE#${date}#MODEL#${event.modelId} }, UpdateExpression: 'SET #date = :date, modelId = :modelId, providerId = :providerId, requestCount = if_not_exists(requestCount, :zero) + :one, inputTokens = if_not_exists(inputTokens, :zero) + :inputTokens, outputTokens = if_not_exists(outputTokens, :zero) + :outputTokens, totalTokens = if_not_exists(totalTokens, :zero) + :totalTokens, providerCost = if_not_exists(providerCost, :zero) + :providerCost, billedCost = if_not_exists(billedCost, :zero) + :billedCost, cachedRequests = if_not_exists(cachedRequests, :zero) + :cached, phiRequests =

```

```

if_not_exists(phiRequests, :zero) + :phi, updatedAt = :updatedAt', ExpressionAttributeNames:
{ '#date': 'date' }, ExpressionAttributeValues: { ':date': date, ':modelId': event.modelId,
':providerId': event.providerId, ':zero': 0, ':one': 1, ':inputTokens': event.inputTokens, ':outputTo-
kens': event.outputTokens, ':totalTokens': event.totalTokens, ':providerCost': event.providerCost,
':billedCost': event.billedCost, ':cached': event.cached ? 1 : 0, ':phi': event.phiDetected ? 1 : 0,
':updatedAt': new Date().toISOString(), }, })); } catch (error) { logger.error('Failed to update
rollup', error as Error, { tenantId: event.tenantId, date, modelId: event.modelId }); } }

```

```

async function getModelPricing(modelId: string, logger: Logger): Promise<{ inputPricePerMil-
lion: number; outputPricePerMillion: number }> { const result = await executeQuery('SELECT
input_price_per_million, output_price_per_million FROM ai_models WHERE id = $1', [mod-
elId], logger); if (result.rowCount === 0) return { inputPricePerMillion: 1.0, outputPricePerMil-
lion: 2.0 }; return { inputPricePerMillion: parseFloat(result.rows[0].input_price_per_million) ||
1.0, outputPricePerMillion: parseFloat(result.rows[0].output_price_per_million) || 2.0 }; }

```

```

async function getTenantMargin(tenantId: string, logger: Logger): Promise { const result = await
executeQuery('SELECT margin_percent FROM billing_settings WHERE tenant_id = $1', [ten-
antId], logger); return result.rowCount > 0 ? parseFloat(result.rows[0].margin_percent) : 20; }

```

```

function getDefaultStartDate(): string { const d = new Date(); d.setDate(d.getDate() -
30); return d.toISOString().split('T')[0]; } function getTodayDate(): string { return new
Date().toISOString().split('T')[0]; } ""

```

PART 5: DATABASE SCHEMA ADDITIONS

packages/infrastructure/migrations/005_admin_billing.sql

```

""sql - =====
- RADIANT v2.2.0 - Admin & Billing Schema - =====

- Admin Invitations CREATE TABLE IF NOT EXISTS invitations ( id UUID PRIMARY KEY
DEFAULT gen_random_uuid(), email VARCHAR(255) NOT NULL, role VARCHAR(50) NOT
NULL, invited_by UUID NOT NULL REFERENCES administrators(id), app_id VARCHAR(100)
NOT NULL, tenant_id VARCHAR(100) NOT NULL, environment VARCHAR(20) NOT NULL,
token_hash VARCHAR(64) NOT NULL, expires_at TIMESTAMP WITH TIME ZONE NOT
NULL, status VARCHAR(20) NOT NULL DEFAULT 'pending', message TEXT, accepted_at
TIMESTAMP WITH TIME ZONE, accepted_by_ip VARCHAR(45), created_at TIMESTAMP
WITH TIME ZONE NOT NULL DEFAULT NOW(), CONSTRAINT valid_invitation_status
CHECK (status IN ('pending', 'accepted', 'expired', 'revoked')) );

CREATE INDEX idx_invitations_email ON invitations(email); CREATE INDEX idx_invitations_tenant
ON invitations(tenant_id); CREATE INDEX idx_invitations_token ON invitations(token_hash);
CREATE INDEX idx_invitations_status ON invitations(status);

- Approval Requests CREATE TABLE IF NOT EXISTS approval_requests ( id UUID PRIMARY
KEY DEFAULT gen_random_uuid(), type VARCHAR(50) NOT NULL, app_id VARCHAR(100)
NOT NULL, tenant_id VARCHAR(100) NOT NULL, environment VARCHAR(20) NOT NULL,
requested_by UUID NOT NULL REFERENCES administrators(id), requested_at TIMESTAMP
WITH TIME ZONE NOT NULL DEFAULT NOW(), expires_at TIMESTAMP WITH TIME
ZONE NOT NULL, status VARCHAR(20) NOT NULL DEFAULT 'pending', approved_by

```

UUID REFERENCES administrators(id), approved_at TIMESTAMP WITH TIME ZONE, rejected_reason TEXT, action VARCHAR(100) NOT NULL, resource_type VARCHAR(100) NOT NULL, resource_id VARCHAR(255), details JSONB, priority VARCHAR(20) NOT NULL DEFAULT 'medium', notes TEXT, requires_two_person BOOLEAN NOT NULL DEFAULT false, created_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW(), CONSTRAINT valid_approval_status CHECK (status IN ('pending', 'approved', 'rejected', 'expired', 'cancelled')), CONSTRAINT valid_priority CHECK (priority IN ('low', 'medium', 'high', 'critical')));

CREATE INDEX idx_approvals_tenant ON approval_requests(tenant_id); CREATE INDEX idx_approvals_status ON approval_requests(status); CREATE INDEX idx_approvals_requested_by ON approval_requests(requested_by);

– Admin Profiles CREATE TABLE IF NOT EXISTS admin_profiles (admin_id UUID PRIMARY KEY REFERENCES administrators(id) ON DELETE CASCADE, notifications JSONB NOT NULL DEFAULT '{}', timezone VARCHAR(50) NOT NULL DEFAULT 'America/New_York', language VARCHAR(10) NOT NULL DEFAULT 'en', date_format VARCHAR(20) NOT NULL DEFAULT 'MM/DD/YYYY', time_format VARCHAR(10) NOT NULL DEFAULT '12h', currency VARCHAR(3) NOT NULL DEFAULT 'USD', theme VARCHAR(20) NOT NULL DEFAULT 'system', default_environment VARCHAR(20) NOT NULL DEFAULT 'dev', sidebar_collapsed BOOLEAN NOT NULL DEFAULT false, table_rows_per_page INTEGER NOT NULL DEFAULT 25, updated_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW());

– Billing Settings CREATE TABLE IF NOT EXISTS billing_settings (tenant_id VARCHAR(100) PRIMARY KEY, margin_percent DECIMAL(5,2) NOT NULL DEFAULT 20.00, margin_type VARCHAR(20) NOT NULL DEFAULT 'fixed', tiers JSONB, tax_enabled BOOLEAN NOT NULL DEFAULT false, tax_percent DECIMAL(5,2) NOT NULL DEFAULT 0.00, tax_id VARCHAR(50), stripe_customer_id VARCHAR(100), default_payment_method_id VARCHAR(100), auto_pay BOOLEAN NOT NULL DEFAULT false, billing_cycle_day INTEGER NOT NULL DEFAULT 1, currency VARCHAR(3) NOT NULL DEFAULT 'USD', budget_limit DECIMAL(12,2), alert_thresholds INTEGER[] NOT NULL DEFAULT '{50, 75, 90, 100}', created_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW(), updated_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW(), CONSTRAINT valid_margin_type CHECK (margin_type IN ('fixed', 'tiered')), CONSTRAINT valid_billing_day CHECK (billing_cycle_day BETWEEN 1 AND 28));

– Invoices CREATE TABLE IF NOT EXISTS invoices (id UUID PRIMARY KEY DEFAULT gen_random_uuid(), tenant_id VARCHAR(100) NOT NULL, app_id VARCHAR(100) NOT NULL, period_start DATE NOT NULL, period_end DATE NOT NULL, subtotal DECIMAL(12,2) NOT NULL, margin_percent DECIMAL(5,2) NOT NULL, tax DECIMAL(12,2) NOT NULL DEFAULT 0, tax_percent DECIMAL(5,2) NOT NULL DEFAULT 0, total DECIMAL(12,2) NOT NULL, currency VARCHAR(3) NOT NULL DEFAULT 'USD', status VARCHAR(20) NOT NULL DEFAULT 'draft', due_date TIMESTAMP WITH TIME ZONE NOT NULL, paid_at TIMESTAMP WITH TIME ZONE, line_items JSONB NOT NULL DEFAULT '[]', stripe_invoice_id VARCHAR(100), stripe_payment_intent_id VARCHAR(100), created_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW(), updated_at TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT NOW(), CONSTRAINT valid_invoice_status CHECK (status IN ('draft', 'pending', 'paid', 'overdue', 'cancelled')));

CREATE INDEX idx_invoices_tenant ON invoices(tenant_id); CREATE INDEX idx_invoices_status

```
ON invoices(status); CREATE INDEX idx_invoices_period ON invoices(period_start, period_end);
```

```
- Admin Notifications CREATE TABLE IF NOT EXISTS admin_notifications ( id UUID
PRIMARY KEY DEFAULT gen_random_uuid(), admin_id UUID NOT NULL REFERENCES
administrators(id) ON DELETE CASCADE, tenant_id VARCHAR(100) NOT NULL, type
VARCHAR(50) NOT NULL, priority VARCHAR(20) NOT NULL DEFAULT 'medium', title
VARCHAR(255) NOT NULL, message TEXT NOT NULL, action_url VARCHAR(500),
action_label VARCHAR(100), read BOOLEAN NOT NULL DEFAULT false, read_at
TIMESTAMP WITH TIME ZONE, dismissed BOOLEAN NOT NULL DEFAULT false, dismissed_at
TIMESTAMP WITH TIME ZONE, email_sent BOOLEAN NOT NULL DEFAULT false,
email_sent_at TIMESTAMP WITH TIME ZONE, created_at TIMESTAMP WITH TIME
ZONE NOT NULL DEFAULT NOW(), expires_at TIMESTAMP WITH TIME ZONE,
CONSTRAINT valid_notification_type CHECK (type IN ('security', 'billing', 'deployment', 'approval',
'system', 'alert')), CONSTRAINT valid_notification_priority CHECK (priority IN ('low',
'medium', 'high', 'critical')) );
```

```
CREATE INDEX idx_notifications_admin ON admin_notifications(admin_id); CREATE INDEX
idx_notifications_read ON admin_notifications(admin_id, read); “
```

API ROUTES SUMMARY

Admin Routes

Method	Path	Description	Permission
POST	/admin/invitations	Create invitation	admin:write
GET	/admin/invitations	List invitations	admin:read
GET	/admin/invitations/:id	Get invitation	admin:read
POST	/admin/invitations/:id/rescind	Rescind invitation	admin:write
DELETE	/admin/invitations/:id/revoke	Revoke invitation	admin:write
POST	/admin/invitations/accept	Accept invitation	(public)
POST	/admin/approvals	Create approval request	approvals:initiate
GET	/admin/approvals	List approvals	approvals:read
GET	/admin/approvals/:id	Get approval	approvals:read
POST	/admin/approvals/:id/approve	Approve request	approvals:*
DELETE	/admin/approvals/:id/reject	Cancel approval	approvals:initiate
GET	/admin/users	List admins	admin:read
GET	/admin/users/:id	Get admin	admin:read
PUT	/admin/users/:id	Update admin	admin:write
DELETE	/admin/users/:id	Delete admin	admin:*

Billing Routes

Method	Path	Description	Permission
GET	/billing/settings	Get settings	billing:read
PUT	/billing/settings	Update settings	billing:*

Method	Path	Description	Permission
GET	/billing/current	Current period usage	billing:read
GET	/billing/projections	Cost projections	billing:read
GET	/billing/invoices	List invoices	billing:read
GET	/billing/invoices/:id	Get invoice	billing:read
POST	/billing/generate	Generate invoice	billing:*

Metering Routes

Method	Path	Description	Permission
POST	/metering/record	Record usage event	(internal)
POST	/metering/batch	Batch record events	(internal)
GET	/metering/summary	Usage summary	billing:read
GET	/metering/rollups	Daily rollups	billing:read

DEPLOYMENT VERIFICATION

```
“bash # 1. Create Invitation curl -X POST -H “Authorization: Bearer $ADMIN_TOKEN” -H
“Content-Type: application/json” \ -d ‘{“email”: “new.admin@company.com”, “role”: “operator”,
“message”: “Welcome!”, “expiresInHours”: 48}’ \ https://admin-api.thinktank.YOUR_DOMAIN.com/api/v2/ad
```

2. List Pending Approvals (for me to approve)

```
curl -H “Authorization: Bearer $ADMIN_TOKEN” \ “https://admin-api.thinktank.YOUR_DOMAIN.com/api/v
```

3. Get Current Billing Period

```
curl -H “Authorization: Bearer $ADMIN_TOKEN” \ https://admin-api.thinktank.YOUR_DOMAIN.com/api/v2/ad
```

4. Get Usage Rollups

```
curl -H “Authorization: Bearer $ADMIN_TOKEN” \ “https://admin-api.thinktank.YOUR_DOMAIN.com/api/v
12-01&endDate=2024-12-21”
```

5. Generate Invoice

```
curl -X POST -H “Authorization: Bearer $ADMIN_TOKEN” -H “Content-Type: applica-
tion/json” \ -d ‘{“periodStart”: “2024-12-01”, “periodEnd”: “2024-12-31”, “sendToStripe”: true}’
\ https://admin-api.thinktank.YOUR_DOMAIN.com/api/v2/billing/generate ““
```

ESTIMATED COSTS BY TIER

Component	Tier 1	Tier 2	Tier 3	Tier 4	Tier 5
Lambda (Admin)	\$5	\$15	\$50	\$150	\$500
Lambda (Billing)	\$5	\$20	\$75	\$200	\$600
DynamoDB (Usage)	\$10	\$50	\$200	\$500	\$1,500
SES (Emails)	\$1	\$5	\$20	\$50	\$150
Stripe Fees	Variable	Variable	Variable	Variable	Variable
Prompt 5 Total	~\$21	~\$90	~\$345	~\$900	~\$2,750

Note: Stripe fees are 2.9% + \$0.30 per transaction, not included in estimates.

NEXT PROMPTS

Continue with: - **Prompt 6:** Self-Hosted Models & Mid-Level Services Configuration - **Prompt 7:** External Providers & Database Schema/Migrations - **Prompt 8:** Admin Web Dashboard (Next.js) - **Prompt 9:** Assembly & Deployment Guide

End of Prompt 5: Lambda Functions - Admin & Billing RADIANT v2.2.0 - December 2024

[illegible]

END OF SECTION 5

[illegible][illegible]