User Stories and Acceptance Criteria: RAG-Diary

> Turns the functional requirements in the SRS into stories told from each user group's side, with Given/When/Then acceptance criteria and a priority, so the team can estimate and test.

> Thai version: USER-STORIES.md

1. Document control

Item	Detail
Document	User Stories and Acceptance Criteria
Version	1.0
Prepared	15 October 2026
Author	Business Analyst / System Analyst (project owner)
Status	Reviewed, round 1 (25 October 2026)
Related documents	SRS, AS-IS-TO-BE, USE-CASES, TEST-PLAN

2. Purpose and how to read it

This document answers one question: what does each user group need, and when is it accepted as working? It takes the user's side rather than the system's.

Each story follows INVEST: independent, negotiable, valuable, estimable, small, and testable.

A story takes the highest priority among the functional requirements it covers. US-04 covers FR-06 and FR-08, which are Must, and FR-07, which is Should, so US-04 is Must.

3. Story summary

ID	Persona	Story	Priority	Requirements
US-01	Long-term diarist	As a regular diarist, I want to sign up and log in, so my entries stay private and nobody else can read them	Must	FR-01, FR-02, FR-03
US-02	Occasional diarist	As an occasional user, I want to write an entry and tag it quickly, so writing does not become a chore	Must	FR-04

ID	Persona	Story	Priority	Requirements
US-03	Long-term diarist	As a user with many entries, I want the system to build the semantic index automatically, so I can find things later without extra work	Must	FR-05
US-04	Occasional diarist	As a diarist, I want to view, edit and delete my own entries, so the record matches what I meant	Must	FR-06, FR-07, FR-08
US-05	Long-term diarist	As a user who cannot recall the words, I want to search by meaning, so I can find old entries without exact wording	Must	FR-09
US-06	Long-term diarist	As a user who wants to review, I want to ask questions of my own entries, so the answer comes from what I wrote	Should	FR-10
US-07	Long-term diarist	As a user reviewing my mood, I want a summary and an image prompt, so I can see the trend in how I felt	Should	FR-11
US-08	Occasional diarist	As a user who enjoys the creative side, I want an illustration from the prompt, so the entry feels more personal	Could	FR-12
US-09	Long-term diarist	As a user who cares about privacy, I want to export and delete all my data, so I stay in control	Must	FR-13, FR-14
US-10	All user groups	As any user, I want my data strictly separated from other users, so I am sure nobody can read my entries	Must	FR-15

4. Acceptance criteria per story

> Criteria are numbered so a single one can be referenced (for example, US-01 criterion 2), and each follows Given / When / Then.

US-01 Register, log in and log out

1. Given the sign-up page is open, when a valid email and password are entered and submitted, then the system creates the account and takes the user to the home page with a working session.
2. Given a password shorter than 6 characters, when the form is submitted, then the system shows an error and creates no account.
3. Given an email already in use, when that email is submitted, then the system says the email is already taken.

4. Given the login page is open, when wrong credentials are submitted, then the system reports them as invalid and does not sign the user in.
5. Given the user has logged out, when a protected page is opened, then the system returns the user to the login page.

US-02 Write an entry with a tag

1. Given the user is signed in and opens the composer, when the screen appears, then the user can type content and choose or create a tag.
2. Given content is entered and saved, when the save succeeds, then the entry is stored in the account and appears in the list immediately.
3. Given the user is not signed in, when the composer is opened, then the system sends the user to the login page.

US-03 Build the semantic index automatically

1. Given a new entry is saved, when indexing runs, then an embedding is created from the content without any action from the user.
2. Given indexing fails, when the error occurs, then the system notifies the user and allows a retry.
3. Given an entry is edited, when the edit is saved, then the semantic index is updated to the new text.

US-04 View, edit and delete entries

1. Given the user is signed in, when the list opens, then only their own entries appear, newest first.
2. Given the user selects one of their entries, when they edit and save, then the change is stored and reads back.
3. Given the user selects one of their entries, when they confirm deletion, then the entry leaves the list and can no longer be found.

US-05 Semantic search

1. Given the user has an entry that does not contain the words they will type, when they type a phrase with a close meaning, then the system returns the related entry.
2. Given the user searches for words that appear nowhere, when the search runs, then the system says no results were found and suggests trying again.
3. Given search results are shown, when one is selected, then the full entry opens for reading.

US-06 Chat with the entries

1. Given the user types a question about something they wrote, when the question is sent, then the system answers using their entries.
2. Given the user asks about something absent from the entries, when the question is sent, then the system says it found no supporting information in the user's entries.
3. Given the AI provider cannot be reached, when the question is sent, then the system shows an understandable error and allows a retry.

US-07 Mood summary as text and an image prompt

1. Given the user picks a date range or tag, when they ask for a summary, then the system produces text describing the mood trend.
2. Given the system produces an image prompt, when the result is shown, then the user can carry that prompt into the image screen.
3. Given there are no entries in the chosen range, when the user asks for a summary, then the system asks them to add entries first.

US-08 Generate an illustration from the prompt

1. Given the user has entered a prompt, when they ask for an image, then the system shows the image produced by the external provider.
2. Given the image provider is slow or fails, when the user waits, then the system shows status and allows a retry.
3. Given the user changes the prompt, when they ask again, then the system generates an image from the latest prompt.

US-09 Export and delete all data

1. Given the user is signed in, when they export, then the system prepares a file containing all of their entries.
2. Given the user asks to delete everything, when they confirm, then the system deletes every entry and it cannot be read back.
3. Given the user asks to delete everything, when they cancel, then all data remains exactly as it was.

US-10 Isolate data per user

1. Given a user requests their own data, when the system processes it, then only that account's data is returned.
2. Given a user tries to request another user's data, when the request is sent, then the system refuses and returns nothing.
3. Given the user is not signed in, when a protected endpoint is called, then the system rejects the request.

5. Coverage of the functional requirements

Requirement	User story
FR-01	US-01
FR-02	US-01
FR-03	US-01
FR-04	US-02
FR-05	US-03
FR-06	US-04
FR-07	US-04
FR-08	US-04
FR-09	US-05
FR-10	US-06
FR-11	US-07
FR-12	US-08
FR-13	US-09
FR-14	US-09
FR-15	US-10

All 15 functional requirements are referenced at least once, which is 100 percent coverage.

6. Assumptions

- Personas follow STAKEHOLDER-MATRIX; the main groups are the occasional diarist and the long-term diarist.
- Priority follows the version 1.0 scope in PRODUCT-BRIEF.
- System-level use case detail and activity flow are in USE-CASES.

7. References

Document	Relationship
SRS	The source of the functional requirements
STAKEHOLDER-MATRIX	The source of the personas
AS-IS-TO-BE	The problems each story addresses
TEST-PLAN	Uses the acceptance criteria as the basis of the test set