Glossary: RAG-Diary

> The terms and abbreviations used across the document set, so every reader understands the same word in the same way. It covers both document codes and technical terms.

> Thai version: GLOSSARY.md

1. Document control

Item	Detail
Document	Glossary
Version	1.0
Prepared	15 October 2026
Author	Business Analyst / System Analyst (project owner)
Status	Reviewed, round 1 (25 October 2026)

2. Purpose

Records what each abbreviation and technical term in documents D-00 to D-24 means, so communication stays aligned.

3. Abbreviations and codes

Code	Meaning	Used in
D-xx	Document ID, for example D-05	DOCUMENT-PLAN
FR-xx	Functional requirement	SRS, RTM
NFR-xx	Non-functional (quality) requirement	SRS, NFR-SPEC, RTM
UC-xx	Use case	USE-CASES, RTM
US-xx	User story	USER-STORIES, RTM
BR-xx	Business rule	BUSINESS-RULES
GAP-xx	Gap between the as-is and the to-be state	AS-IS-TO-BE
PP-xx	Pain point	AS-IS-TO-BE
SH-xx	Stakeholder	STAKEHOLDER-MATRIX

Code	Meaning	Used in
R-xx	Risk	RISK-REGISTER
CR-xx	Change request	CHANGE-REQUEST-LOG
ADR-xx	Architecture decision record	ADR
PF-xx	Process flow	PROCESS-FLOWS
SEQ-xx	Sequence diagram	SEQUENCE-DIAGRAMS
TC-xx	Test case	TEST-PLAN, RTM
UAT-xx	User acceptance test scenario	UAT
AC	Acceptance criteria	SRS, USER-STORIES
IS-xx	In-scope capability	PRODUCT-BRIEF
C-xx	Constraint	PRODUCT-BRIEF, SRS

4. Technical terms

Term	Meaning	Reference
AI	Artificial intelligence	ADR, API-CONTRACT
MoSCoW	Priority scheme: Must, Should, Could, Won't	SRS, ROADMAP
PDPA	Thailand's Personal Data Protection Act	NFR-SPEC, DFD-PRIVACY
PII	Personally identifiable information	DFD-PRIVACY
DFD	Data flow diagram	DFD-PRIVACY
RTM	Requirements traceability matrix	TRACEABILITY-MATRIX
SRS	Software requirements specification	SRS
API	Application programming interface	API-CONTRACT, C4-ARCHITECTURE
BA	Business analyst	Several documents
DPO	Data protection officer	STAKEHOLDER-MATRIX
embedding	A numeric vector representing text, used for semantic search	DATA-MODEL, ADR
gemini-3.5-flash	The chat model from Google Gemini	AI module, ADR
HNSW	Hierarchical navigable small world, a vector index	DATA-MODEL, NFR-SPEC
localStorage	Browser-side storage (no longer used for the session since ADR-10)	ADR-06, ADR-10

Term	Meaning	Reference
httpOnly cookie	A cookie that JavaScript cannot read, used to hold the session	ADR-10, API-CONTRACT
rate limit	A cap on how many calls one user can make in a time window	API-CONTRACT, RISK-REGISTER
CI	Continuous integration: typecheck, tests and build run automatically	TEST-PLAN
Google Gemini	The AI provider (free tier through Google AI Studio)	ADR, DFD-PRIVACY
pgvector	The PostgreSQL extension for vectors	DATA-MODEL, ADR
prompt	An instruction that tells the AI what to produce	ADR, FR-11
RAG	Retrieval-augmented generation: retrieve first, then answer	ADR, SEQUENCE-DIAGRAMS
RLS	Row-level security	DATA-MODEL, ADR
SA	System analyst	Several documents
semantic search	Search by meaning rather than exact words	FR-09, API-CONTRACT
Supabase	The hosted database and authentication service	C4-ARCHITECTURE
token	An authentication token	API-CONTRACT, ADR
UAT	User acceptance test	UAT, TEST-PLAN
vector	A mathematical vector (1,536 dimensions) used to compare similarity	DATA-MODEL